

WB0055F

RTALFo

1 // RTAL

2 // Relea

3 // per-p

4 // pipel

5 // Fast-

6 // in pr

7 #pragma

8 #pragma

9

10 #include

11 #include

12 #include

13 #include

14 #include

15 #include

16 #include

17 #include

18 #include

19 #include

20 #include

21 #include

22 #include

23

<

Automatische Formatierung

Strg+T

Sketch archivieren

Kodierung korrigieren & neu laden

Bibliotheken verwalten...

Strg+Umschalt+

Serieller Monitor

Strg+Umschalt+

Serieller Plotter

Strg+Umschalt+

ESP32 LittleFS Data Upload

ESP32 Partition Tool

ESP32 Sketch Data Upload

ESP8266 Sketch Data Upload

Teensy 4 Security

WiFi101 / WiFININA Firmware Updater

ESP32 Sketch Data Upload

Board: "ESP32S3 Dev Module"

Upload Speed: "921600"

USB Mode: "USB-OTG (TinyUSB)"

USB CDC On Boot: "Disabled"

USB Firmware MSC On Boot: "Disabled"

USB DFU On Boot: "Disabled"

Upload Mode: "UART0 / Hardware CDC"

CPU Frequency: "240MHz (WiFi)"

Flash Mode: "QIO 120MHz"

Flash Size: "4MB (32Mb)"

Partition Scheme: "Huge APP (3MB No OTA/1MB SPIFFS)"

Core Debug Level: "Keine"

PSRAM: "OPI PSRAM"

Arduino Runs On: "Core 1"

Events Run On: "Core 1"

Erase All Flash Before Sketch Upload: "Disabled"

JTAG Adapter: "Disabled"

Port: "COM11"

Boardinformationen holen

Programmer

Bootloader brennen