

Phoenix_v1_1_0	Automatische Formatierung	Strg+T
1 // RTAL B	Sketch archivieren	
2 // Test k	Kodierung korrigieren & neu laden	
3 // Audio/	Bibliotheken verwalten...	Strg+Umschalt+I
4 // Sessio	Serieller Monitor	Strg+Umschalt+M
5 // Reverk	Serieller Plotter	Strg+Umschalt+L
6 // Diagn	ESP32 LittleFS Data Upload	
7 // Retain	ESP32 Partition Tool	
8 /*	ESP32 Sketch Data Upload	
9 Project	ESP8266 Sketch Data Upload	
10 v0.8.06	Teensy 4 Security	
11	WiFi101 / Wi-FiNINA Firmware Updater	
12 Phoenix	ESP32 Sketch Data Upload	
13 - Sampl	Board: "ESP32S3 Dev Module"	>
14 - OFF,	Upload Speed: "921600"	>
15 - Note	USB Mode: "USB-OTG (TinyUSB)"	>
16 - Four-	USB CDC On Boot: "Disabled"	>
17 - Every	USB Firmware MSC On Boot: "Disabled"	>
18 - SAMPL	USB DFU On Boot: "Disabled"	>
19 - C010	Upload Mode: "UART0 / Hardware CDC"	>
20 - C011	CPU Frequency: "240MHz (WiFi)"	>
21 - C012	Flash Mode: "QIO 120MHz"	>
22 - C013	Flash Size: "4MB (32Mb)"	>
23 - C014	Partition Scheme: "Huge APP (3MB No OTA/1MB SPIFFS)"	>
24 - C015	Core Debug Level: "Keine"	>
25 - C020	PSRAM: "OPI PSRAM"	>
26 - C021	Arduino Runs On: "Core 1"	>
27 - C022	Events Run On: "Core 1"	>
28 - C023	Erase All Flash Before Sketch Upload: "Disabled"	>
	JTAG Adapter: "Disabled"	>
	Port: "COM5"	>
	Boardinformationen holen	>
	Programmer	>
	Bootloader brennen	>