



GLOVES
COLLECTION

www.cephasmedical.net

**Manufacturer of Chemical
Resistant Nitrile Flock lined Gloves
and Personal Protective
Equipments.**

INTRODUCTION :

- **Cephas Medical Private Limited ,**
Established its State of the Art
Manufacturing facility with
International Standard Machines at
Virudhunagar, Tamil Nadu.
- We have we have obtained
several site certifications like
SEDEX, ISO & Product Certifications
like **CE, UKCA** our products globely
Accreditad with a production capacity
of around 7,00,000 pairs per month.

MISSION :

- To manufacture superior Gloves
to Ensure Safety & Trust
- To comply with International
Quality Standards
- To foster long-term partnerships
through trust and performance.



EN ISO 374-1:2016

PROTECTIVE GLOVES AGAINST DANGEROUS CHEMICALS AND MICRO-ORGANISMS

IT IS BASED ON THREE METHODS:

- Penetration test in accordance with standard EN 374-2:2014
- Penetration test in accordance with standard EN 16523-1:2015 which replaces standard EN 374-3
- Degradation test in accordance with standard EN 374-4:2013

THREE TYPES OF GLOVES

TYPE OF GLOVES	REQUIREMENT	MARKING
TYPE A	Penetration Resistance (EN374-2) Breakthrough time 30 min for at least 6 test chemicals, In the new list in (EN16523-1)	EN ISO 374-1/Type A AJKLPR
TYPE B	Penetration Resistance (EN374-2) Breakthrough time 30 min for at least 3 test chemicals In the new list in (EN16523-1)	EN ISO 374-1/Type B JKL
TYPE C	Penetration Resistance (EN374-2) Breakthrough time 10 min for at least 1 test chemical In the new list in (EN16523-1)	EN ISO 374-1/Type C

DEGRADATION TEST

Deterioration of the physical properties of the glove in contact with the chemical in accordance with EN 374-4:2013

LIST OF HAZARDOUS COMPOUNDS

CODE	CHEMICAL	CAS NUMBER	CLASS
A	Methanol	6756-1	Primary Alcohol
B	Acetone	6764-1	Ketone
C	Acetonitrile	75-05-8	Ketone
D	Dichloromethane	75-09-2	Chlorinated hydrocarbon
E	Carbon disulphide	75-15-0	Sulphur containing organic compound
F	Toluene	108-88-3	Aromatic hydrocarbon
G	Diethylamine	109-89-7	Amine
H	Tetrahydrofuran	109-99-9	Heterocyclic and ether compound
I	Ethyl acetate	141-78-6	Ester
J	n-Heptane	142-82-5	Saturated hydrocarbon
K	Sodium hydroxide 40%	1310-73-2	Inorganic base
L	Sulphuric acid 96%	7664-93-9	Inorganic mineral acid, oxidizing
M	Nitric acid 65%	7697-37-2	Inorganic mineral acid, oxidizing
N	Acetic acid 99%	64-19-7	Organic acid
O	Ammonium hydroxide 25%	1336-21-6	Organic base
P	Hydrogen peroxide 30%	7722-84-1	Peroxide
S	Hydrofluoric acid 40%	7664-39-3	Inorganic mineral acid
T	Formaldehyde 37%	50-00-0	Aldehyde

NITRILE FLOCKLINED GLOVES - 13 INCH

Chemical resistant glove made with a High performance Nitrile (Premium Acrylonitrile Butadiene Rubber) compound, Cotton flocklined, Diamond textured pattern on the palm.

CNF 15 (15mil Thickness) FEATURES

- Nitrile gloves manufactured by "State of the Art fully automated Dipping line."
- Resistant to a wide variety of chemicals and solvents
- Offers superior fit, puncture and abrasion protection over rubber or neoprene gloves
- Chlorinated to reduce Odour
- Thickness will be 15 mil / weight will be 70gm $\pm$ 3gm
- The Product can be Customized based on the customer's requirement.
- Size Availability S,M,L,XL & XXL

Chempro Safe CNF 17 (17mil Thickness) FEATURES

- Nitrile gloves manufactured by "State of the Art fully automated Dipping line."
- Resistant to a wide variety of chemicals and solvents
- Offers superior fit, puncture and abrasion protection over rubber or neoprene gloves
- Chlorinated to reduce Odour
- Thickness will be 17 mil / weight will be 80gm $\pm$ 3gm
- The Product can be Customized based on the customer's requirement.
- Size Availability S,M,L,XL & XXL



Unlined Nitrile Long Industrial Gloves (18" 22 Mil)

SPECIAL FEATURES

- Made from state-of-art dipping systems with 100% premium grade nitrile rubber.
- Raised diamond-pattern palm and fingers for sustained grip in wet and oily environments.
- Superior snag, puncture and abrasion protection with extended coverage, high levels of flexibility, comfort and dexterity.
- Chemical resistant for use against hydrocarbons including petroleum derivatives, certain acids, ketones, alkalis, vegetable oils and many cleaning media.
- Chlorinated to reduce Odour
- Thickness will be 22 mil / weight will be 165gm $\pm$ 3gm
- Customized Solution can be done based on the Volume
- Size Availability S,M,L,XL & XXL



CE Certificate



UKCA Certificate



EN 388:2016



PROTECTIVE GLOVES AGAINST MECHANICAL RISKS

According to this standard, characteristics such as abrasion resistance, cut resistance, tearing strength, puncture resistance and impact protection are tested. In conjunction with the pictogram, four numbers and one, or two letters, will be displayed. These signs indicate the performance of the glove.

- A** Abrasion resistance (0-4)
- B** Cut resistance, coup test (0-5)
- C** Tearing strength (0-4)
- D** Puncture resistance (0-4)
- E** Cut resistance, tom test iso 13997 (A-F)
- F** Impact protection (A-F)

TEST	LEVEL 0	LEVEL 1	LEVEL 2	LEVEL 3	LEVEL 4	LEVEL 5
A Abrasion (cycles)	<100	≥100	≥500	≥2000	≥8000	≥20000
B Cut, coup test (index)	<1.2	≥1.2	≥2.5	≥5.0	≥10.0	≥20.0
C Tear (newton)	<10	≥10	≥25	≥50	≥75	≥125
D Puncture (newton)	<20	≥20	≥60	≥100	≥150	≥250
	LEVEL A	LEVEL B	LEVEL C	LEVEL D	LEVEL E	LEVEL F
E Cut, TDM-100 test (newton)	<2	≥5	≥10	≥15	≥22	≥30
F Impact protection	If the glove has an impact protection, this information is given by the letter P as the 6th and last sign. If no P sign, no impact protection is claimed.					

EN 407:2004



PROTECTIVE GLOVES AGAINST THERMAL RISKS (HEAT AND/OR FIRE)

This standard specifies demands and test methods for protective gloves that shall protect against heat and/or fire. The numbers given besides the pictogram indicate the gloves performance for each test in the standard. The higher number the better performance level.

- A** Burning behaviour (0-4)
- B** Contact heat (0-4)
- C** Convective heat (0-4)
- D** Radiant heat (0-4)
- E** Small splashes of molten metal (0-4)
- F** Large quantities of molten metal (0-4)

TEST	LEVEL 1	LEVEL 2	LEVEL 3	LEVEL 4
A Burning behaviour	< 20 sec. -	< 10 sec. < 120 sec.	< 3 sec. < 25 sec.	< 2 sec. < 5 sec.
B Contact heat	100 ≥ 15 sec.	250 ≥ 15 sec.	350 ≥ 15 sec.	450 ≥ 15 sec.
C Convective heat	≥ 4 sec.	≥ 7 sec.	≥ 10 sec.	≥ 18 sec.
D Radiant heat	≥ 7 sec.	≥ 20 sec.	≥ 50 sec.	≥ 95 sec.
C Small splashes of molten metal	≥ 10 sec.	≥ 15 sec.	≥ 25 sec.	≥ 35 sec.
D Large quantities of molten metal	10g	60g	120g	200g

CST-LINT FREE

**13 GG Knitting with Synthetic liner,
Lint free Gloves with ealstic Cuff**

FEATURES

- Synthetic Polyester liner will provide you excellent fit to handy small components
- This product give you Lint free, hence Product will not have lint issue

PRODUCT INFORMATION

MATERIAL	Synthetic Polyester Liner
COLOR	White
PACKAGING	12 Pairs / Poly , 600 Pairs / Bag
SIZE	8 and 9
APPLICATION	Assembly, General Purpose



CST/LF/W

EN 388



CST-PU-W

**13 GG Knitting, Synthetic Polyester liner
with Pu coating in White Colour , Ealstic
wrist for comfort fit**

FEATURES

- 13 GG knitting synthetic polyester liner offer you basic Cut Level 1
- PU coating in Black colour gives better grip to handy small components

PRODUCT INFORMATION

MATERIAL	Synthetic Polyester
COLOR	White on White
PACKAGING	12 Pairs / Poly
SIZE	7,8,9
APPLICATION	Assembly, General application,



CST/PU -W

EN 388



4131

CST-PU-G

13 GG Knitting, Synthetic Polyester liner with Pu coating in Grey Colour , Ealstic wrist for comfort fit

FEATURES

- Fine Gsm give high breathablity and long wear
- Comfortable and Lint Free
- Washable and Resuable

PRODUCT INFORMATION

MATERIAL	Synthetic Polyester
COLOR	Grey on Grey
PACKAGING	12 Pairs / Poly
SIZE	7,8,9
APPLICATION	Assembly, General application,



CST/PU -G



CST-PU-B

13 GG Knitting, Synthetic Polyester liner with Pu coating in Balck Colour , Ealstic wrist for comfort fit

FEATURES

- 13 GG knitting synthetic polyester liner offer you basic Cut Level 1
- PU coating in Black colour gives better grip to handly small components

PRODUCT INFORMATION

MATERIAL	Synthetic Polyester
COLOR	Black on Black
PACKAGING	12 Pairs / Poly
SIZE	7,8,9
APPLICATION	Assembly, General application,



CST/PU -B



CST-FNC

13 GG Synthetic Polyester liner with Grey FaltSmooth nitrile coaring for oil application, Elastic Cuff for snug fit

FEATURES

- Synthetic polyester liner offers better small components handling
- Falt nitrile coating offers better oil grip, Light amount of heat reduction

PRODUCT INFORMATION

MATERIAL	Synthetic Polyester liner
COLOR	White Liner with Grey coating
PACKAGING	12 Pairs / Poly, 600 Pairs / Bag
SIZE	8 and 9
APPLICATION	Engine assembly, Painting area



CST/FNC



CST/ TESD

13 GG, Synthetic liner with carbon fiber for Anti Static Property, Finger Tips PU Coated for better Grip

FEATURES

- 13 GG Knitting will give you better Dexterity
- Snug Fit for samll component to pick
- Top PU coating will give better Grip

PRODUCT INFORMATION

MATERIAL	Synthetic Liner
COLOR	White
PACKAGING	12 Pairs / Poly , 600 Pairs / Gunny Bag
SIZE	Available 7, 8,9
APPLICATION	Electronic Industry, Assembly, EV Vehicle assembly



CST/TESD



CST-PESD

13 GG Synthetic knitted with carbon fiber for Anti Static property, Palm fully PU coated for better grip

FEATURES

- 13 GG Knitting with Carbon fiber will give you better grip
- AntiStatic Property

PRODUCT INFORMATION

MATERIAL	Synthetic liner with Carbon fiber
COLOR	White
PACKAGING	12 Pairs / Poly - 600 Pairs one bag
SIZE	8, 9
APPLICATION	Electronic Industry , Motehr board assembly



CST/PESD



CST-CLC

13 gg, Synthetic liner in Red colour with Palm Crinkle Latex coating for better Grip

FEATURES

- Synthetic liner will offer Cut Level 1
- Crinkle Latex Offers better grip , Product handling

PRODUCT INFORMATION

MATERIAL	13 GG knitting Synthetic Liner
COLOR	Red Liner, with Black Crinkle Latex Coating
PACKAGING	12 Pairs / Poly. 600 Pairs / Bag
SIZE	8 and 9
APPLICATION	Better Grip area, Tyre Industry, Glass Handling, Loading Unloading Area



CST/CLC



3121

CST-FLEXIGRIP

15 GG Knitted, Synthetic Special liner with Nitrile Foam coating offer better oil protection

FEATURES

- 15 GG Knitted will offer excellent dexterity
- Nitrile Micro Foam provides you with better grip with oil components

PRODUCT INFORMATION

MATERIAL	15 GG Knitted Synthetic Special yarn
COLOR	Grey liner with Black Nitrile Foam Coated
PACKAGING	12 Pairs / Poly, 600 Pairs / Bag
SIZE	8 and 9
APPLICATION	Micro Assembly, Mild Oil and greece Area



FLEXIGRIP



CST-CUT C

13 GG knitted, HPPE with Galss fiber yarn offers better Cut protection, Grey Pucoating for beetr Grip, Elastic Cuff for Sung Fit , DMF FREE

FEATURES


- 13 GG Knitted HPPE liner offers Cut level C
- Grey PU coating provides you better grip
- DMF Free PU Coating offers CE Standard , Skin friendly Coating

PRODUCT INFORMATION

MATERIAL	13 GG , HPPE with Glass fiber Yarn
COLOR	Grey Liner with Grey Coating
PACKAGING	12 Pairs / Poly , 600 Pairs / Bag
SIZE	8 and 9



CST/Cut C



CST-GN-CUT D

13 GG Knitted, HPPE liner with Polyethylen fiber for better Cut Protection and Black Sandy Finish coating for better Oil protection, Elastic Cuff for snug fit

FEATURES

- 13 GG knitted HPPE and Polyethylene fiber will give better cut protection
- Nitrile Sandy finish offers better grip and Less Oil Penetration
- Nitrile coating offers Conyact Heat level 1

PRODUCT INFORMATION

MATERIAL	HPPE plus Polyesthelne fiber
COLOR	Green
PACKAGING	12 Pairs / Poly , 600 Pairs / Bag
SIZE	7,8 and 9
APPLICATION	Wet Application , Mild oil and greece handling area with sharp objects



CST/GN/Cut D

EN 388:2016



4 x 42 D

EN 407



CST-OPU-CUT D

13 GG Knitted, HPPE liner with PE fiber combined with Elastane yarn for better Cut Protection and PU Black Plam coating for better Grip, with Elastic cuff for Snug Fit, DMF FREE

FEATURES

- 13 GG Knitting with HPPE fiber will provide excellent abbrasion and Cut Protection
- Black PU coating for better grip
- DMF Free PU Coating offers CE Standard , Skin friendly Coating

PRODUCT INFORMATION

MATERIAL	HPPE liner with PE fiber and elastane
COLOR	Orange liner with Black PU Coating
PACKAGING	12 Pairs/ poly, 600 Pairs / Bag
SIZE	8 and 9
APPLICATION	Sharp edges handling, Sheet metal, Glass Handling



CST/OPU/Cut D

EN 388:2016



4 x 42 D



DMF free

CST-BPU-CUT E

13 Gg Knitted , HPPE with Special yarn to checive Cut Level E , Black PU coating for better Grip, Elastic Cuff for Snug Fit, DMF FREE

FEATURES

- 13 GG Knitted, HPPE Yarn with special yarn offers Cut Level E for better protection
- Black PU gives your excellent Grip
- DMF Free PU Coating offers CE Standard , Skin friendly Coating

PRODUCT INFORMATION

MATERIAL	13 GG Knitted, HPPE with special yarn for High Cut Level
COLOR	Blue Color Liner with Black PU coating
PACKAGING	12 pairs / Poly , 600 Pairs /Bag
SIZE	8 and 9
APPLICATION	Heavy Cut Protection area like Glass Industry, Thin Sheet metal handling



CST/BPU/Cut E

EN 388:2016



DMF free



CONTACT DETAILS

CORPORATE ADDRESS

 B13 MEPZ Special
Economic Zone, Chennai
- 600 045. India

FACTORY ADDRESS

 No 33, 34 & 46, 47 SIDCO
Industrial Estate, (Urban,
Watrap - Alagapuri -
Virudhunagar Rd,
Virudhunagar, Tamil Nadu
626 003.

 +91 - 44 - 2262 1515
93635 86977

 gloves@cephasmedical.net

THANK YOU

www.cephasmedical.net