

Fall 2025 CPTS530 Final Project
MATH 448-548
Numerical Analysis

Aryan Ritwajeet Jha

11 December 2025

Contents

Problem 1: Orthogonal Matching Pursuit	2
Problem 1 - Part 1: OMP Implementation	4
Problem 1 - Part 2: OMP with Matrix A	5
Problem 1 - Part 3: OMP with Matrix B	6
Problem 1 - Part 4: Comparison	7
Problem 2: Fourth-Order Runge-Kutta Method	8
Problem 2 - Part A: Analytical Solution	9
Problem 2 - Part B: Numerical Solution	11
Problem 2 - Conclusion	13
Problem 3: Adams-Bashforth-Moulton Method	14
Appendix	17
A. Problem 2 Implementation	17

Problem 1: Orthogonal Matching Pursuit (OMP)

Problem Statement:

Part 0: Preliminary Information and Data

In part 2, use the matrix

$$A = \begin{bmatrix} 1 & -1/2 & -1/2 \\ 0 & \sqrt{3}/2 & -\sqrt{3}/2 \\ 1 & 3 & 3 \end{bmatrix}$$

In part 3, use the matrix B that is the 2×3 matrix consisting of the first two rows of A .

Singular Value Decomposition (SVD) and Pseudo-Inverse

Given a matrix $M_{m \times n}$ with $\text{rank}(M) = r$, write

$$M = U \Sigma V^T$$

where $U_{m \times m}$ and $V_{n \times n}$ are orthogonal matrices, and $\Sigma_{m \times n}$ is a diagonal matrix with nonzero diagonal entries $\sigma_1 \geq \sigma_2 \geq \dots \geq \sigma_r > 0$ called singular values of M .

Definition. Given M as above, the pseudo-inverse M^+ is defined by

$$M^+ = V \Sigma^+ U^T$$

where $\Sigma_{n \times m}^+$ is the diagonal matrix whose non-zero entries are $\frac{1}{\sigma_1}, \frac{1}{\sigma_2}, \dots, \frac{1}{\sigma_r}$.

Thresholding Operator

The **hard thresholding operator** H_s is defined as follows:

$$\mathbf{x} \rightarrow H_s(\mathbf{x}) \in \mathbb{R}^n$$

$H_s(\mathbf{x})$ sets all entries of $\mathbf{x}$ to zero except for s largest (in absolute value) entries.

The Matrix $A_{\mathcal{S}}$

Given a matrix A and an index set $\mathcal{S}$, denote by $A_{\mathcal{S}}$ the matrix consisting of columns of A with index in $\mathcal{S}$.

Assignments and Questions

1. Implement the pseudocode for the Orthogonal Matching Pursuit (OMP). The pseudocode is contained in a separate handwritten note attached to the Final project assignment. You may use the standard Matlab (or other language) commands to compute SVD and pseudo-inverse.

2. Run the code for $\mathbf{b} = A\mathbf{e}_1$ with $\mathbf{e}_1 = (1, 0, 0)^T$. See how well the obtained vector $\mathbf{x}$ matches $\mathbf{e}_1$.
 3. Run the code again, this time using the matrix B instead of A .
 4. Compare the results obtained in parts 2, 3. Explain the connection with compressed sensing and sparse recovery.
-

Problem 1 - Part 1: OMP Implementation

The Orthogonal Matching Pursuit algorithm was implemented from scratch in Julia following the provided pseudocode. Key components include:

- Hard thresholding operator $H_s(\mathbf{x})$ that retains only the s largest entries
- OMP iteration that computes correlations $\mathbf{g}_k = A^T \mathbf{r}_k$, applies hard thresholding, updates the support set, solves least squares using pseudo-inverse A_S^+ , and updates the residual
- Convergence detection based on residual norm threshold

See `final_p01.jl` for complete implementation.

Matrix Properties:

Matrix A (3×3):

- Rank: 3 (full rank)
- Condition number: 3.8842
- Singular values: $\sigma_1 = 4.3847$, $\sigma_2 = 1.2247$, $\sigma_3 = 1.1289$
- Square matrix providing $m = 3$ measurements for $n = 3$ unknowns

Matrix B (2×3):

- Rank: 2 (full row rank)
 - Condition number: 1.0000
 - Singular values: $\sigma_1 = 1.2247$, $\sigma_2 = 1.2247$
 - Underdetermined system with $m = 2$ measurements for $n = 3$ unknowns
-

Problem 1 - Part 2: OMP with Matrix A

Setup: Target $\mathbf{e}_1 = (1, 0, 0)^T$, observation $\mathbf{b} = A\mathbf{e}_1 = (1, 0, 1)^T$, sparsity $s = 1$.

Results:

- Final support set: $\mathcal{S} = \{2\}$
- Recovered solution: $\mathbf{x} = (0, 0.25, 0)^T$
- Recovery error: $\|\mathbf{e}_1 - \mathbf{x}\| = 1.0308$
- Final residual norm: 1.1726
- Number of iterations: 1 (stopped at sparsity level)

Analysis: The algorithm failed to recover the correct sparse vector. Despite Matrix A being full rank, OMP selected column 2 instead of column 1. This demonstrates that even with sufficient measurements, the greedy nature of OMP can lead to suboptimal selections when the correlation structure is unfavorable.

Problem 1 - Part 3: OMP with Matrix B

Setup: Target $\mathbf{e}_1 = (1, 0, 0)^T$, observation $\mathbf{b} = B\mathbf{e}_1 = (1, 0)^T$, sparsity $s = 1$.

Results:

- Final support set: $\mathcal{S} = \{1\}$
- Recovered solution: $\mathbf{x} = (1, 0, 0)^T$
- Recovery error: $\|\mathbf{e}_1 - \mathbf{x}\| = 0.0000$
- Final residual norm: 0.0000 (converged)
- Number of iterations: 1

Analysis: Perfect recovery! Despite being an underdetermined system with fewer measurements than unknowns, OMP successfully recovered the exact 1-sparse signal. The residual converged to machine precision, demonstrating successful sparse recovery from incomplete measurements.

Problem 1 - Part 4: Comparison and Connection to Compressed Sensing

Property	Matrix A	Matrix B
System type	Determined ($m = n$)	Underdetermined ($m < n$)
Rank	3 (full)	2 (full row rank)
Condition number	3.8842	1.0000
Recovery error	1.0308	0.0000
Recovery success	Failed	Perfect

Table 1: Comparison of OMP performance on matrices A and B

Key Observations:

1. **Paradoxical result:** Matrix B (underdetermined, compressed) achieved perfect recovery while Matrix A (fully determined) failed. This highlights that having more measurements does not guarantee better sparse recovery with greedy algorithms.
2. **Matrix structure matters:** Matrix B has equal singular values ($\sigma_1 = \sigma_2$) and perfect conditioning ($\text{cond} = 1.0$), suggesting excellent geometric properties for sparse recovery. Matrix A has varying singular values and worse conditioning.
3. **Compressed sensing connection:** Matrix B demonstrates the core principle of compressed sensing: *a sparse signal can be recovered from fewer measurements than the ambient dimension*, provided the measurement matrix satisfies certain properties (e.g., Restricted Isometry Property, low coherence).
4. **Greedy algorithm limitations:** OMP's greedy selection (choosing the column with maximum correlation at each step) can fail even when exact recovery is theoretically possible. More sophisticated algorithms or better measurement matrices may be needed for reliable recovery.

Conclusion: This experiment demonstrates that sparse recovery success depends critically on the measurement matrix structure rather than just the number of measurements. Matrix B's superior geometric properties enabled perfect 1-sparse recovery from just 2 measurements, while Matrix A's structure led to incorrect column selection despite having 3 measurements. This underscores the importance of measurement matrix design in compressed sensing applications.

Problem 2: Fourth-Order Runge-Kutta Method

Problem Statement:

Solve Computer problem 1 in Section 8.3. Write your own program from scratch. Then compare with the exact analytic solution that can be obtained by the method of integrating factors studied in Math 315. The exact solution is

$$x(t) = 12 \frac{e^t}{(e^t + 1)^2}$$

Computer Problem 8.3.1

Write a computer program to solve an initial-value problem $x' = f(t, x)$ with $x(t_0) = x_0$ on an interval $t_0 \leq t \leq t_m$ or $t_m \leq t \leq t_0$. Use the fourth-order Runge-Kutta method. Test it on this example:

$$\begin{aligned}(e^t + 1)x' + xe^t - x &= 0 \\ x(0) &= 3\end{aligned}$$

Determine the *analytic* solution and compare it to the computed solution on the interval $-2 \leq t \leq 0$. Use $h = -0.01$.

Problem 2 - Part A: Analytical Solution

We derive the exact analytical solution to the initial value problem:

$$\begin{aligned}(e^t + 1)x' + xe^t - x &= 0 \\ x(0) &= 3\end{aligned}$$

Derivation:

First, rewrite the ODE in standard form:

$$\frac{dx}{dt} = \frac{x(1 - e^t)}{1 + e^t}$$

Let $y = e^t$, then $dy = e^t dt$, which gives $dy = y dt$ or $dt = \frac{dy}{y}$.
Substituting into the ODE:

$$\frac{dx}{dt} = \frac{(1 - y)x}{(1 + y)}$$

Converting to the new variable:

$$\frac{dx}{x} = \frac{(1 - y)}{(1 + y)} \cdot \frac{dy}{y}$$

Now integrate both sides:

$$\int \frac{dx}{x} = \int \left(\frac{1 - y}{y} - \frac{1 - y}{y + 1} \right) dy$$

Simplifying the right-hand side:

$$\begin{aligned}\int \frac{dx}{x} &= \int \left(\frac{1}{y} - 1 - \frac{1}{y + 1} + \frac{y}{y + 1} \right) dy \\ \int \frac{dx}{x} &= \int \left(\frac{1}{y} - 1 - \frac{1}{y + 1} + 1 - \frac{1}{y + 1} \right) dy \\ \int \frac{dx}{x} &= \int \left(\frac{1}{y} - \frac{2}{y + 1} \right) dy\end{aligned}$$

Integrating:

$$\ln x = \ln y - 2 \ln(y + 1) + C$$

Therefore:

$$x = \frac{ky}{(y + 1)^2}$$

Substituting back $y = e^t$:

$$x = \frac{ke^t}{(e^t + 1)^2}$$

Using the initial condition $x(0) = 3$:

$$3 = \frac{k \cdot 1}{(1 + 1)^2} = \frac{k}{4}$$

Thus $k = 12$, and the analytical solution is:

$$x(t) = \frac{12e^t}{(e^t + 1)^2}$$

Problem 2 - Part B: Numerical Solution using RK4

We implement the fourth-order Runge-Kutta method to solve the initial value problem numerically on the interval $[-2, 0]$ with step size $h = -0.01$.

First, we rewrite the ODE in standard form $x' = f(t, x)$:

$$f(t, x) = \frac{x(1 - e^t)}{e^t + 1}$$

The RK4 method uses the following scheme:

$$\begin{aligned} k_1 &= f(t_n, x_n) \\ k_2 &= f\left(t_n + \frac{h}{2}, x_n + \frac{h}{2}k_1\right) \\ k_3 &= f\left(t_n + \frac{h}{2}, x_n + \frac{h}{2}k_2\right) \\ k_4 &= f(t_n + h, x_n + hk_3) \\ x_{n+1} &= x_n + \frac{h}{6}(k_1 + 2k_2 + 2k_3 + k_4) \end{aligned}$$

Implementation and Results:

The RK4 method was implemented in Julia with careful attention to the four-stage computation and proper backward integration handling. See Appendix A (Figures 2, 3, and 4) for detailed code implementation. The numerical solution is compared with the exact analytical solution at selected points:

t	RK4 Solution	Exact Solution	Absolute Error
-2.0	1.259923024853	1.259923024842	1.107×10^{-11}
-1.5	1.789757424847	1.789757424844	2.931×10^{-12}
-1.0	2.359343198897	2.359343198898	7.461×10^{-13}
-0.5	2.820044546419	2.820044546419	5.520×10^{-13}
0.0	3.000000000000	3.000000000000	0.000×10^0

Table 2: Comparison of RK4 numerical solution with exact analytical solution

Trajectory Visualization:

Figure 1 shows the complete trajectory comparison between the RK4 numerical solution and the analytical solution over the entire integration interval $[-2, 0]$.




Figure 1: Comparison of RK4 numerical solution (red dashed) with analytical solution (blue solid) for the ODE $(e^t + 1)x' + xe^t - x = 0$ with $x(0) = 3$. The solutions are computed over 200 backward integration steps with $h = -0.01$.

Problem 2 - Conclusion

The fourth-order Runge-Kutta method successfully solves this ODE problem numerically on the interval $[-2, 0]$ with step size $h = -0.01$ (200 steps total).

Error Analysis:

- Maximum absolute error: 1.107×10^{-11}
- Mean absolute error: 2.144×10^{-12}
- Relative error at $t = -2$: 8.791×10^{-12} (negligible)

The fourth-order Runge-Kutta method demonstrates exceptional accuracy for this problem, with errors at machine precision level ($\sim 10^{-11}$ to 10^{-13}). The extremely small errors confirm that RK4 is essentially exact for this smooth ODE with the chosen step size $h = -0.01$, successfully integrating backwards from $t = 0$ to $t = -2$ while maintaining the initial condition $x(0) = 3$.

Verification: The numerical results were verified against Wolfram Alpha's Runge-Kutta implementation [1].

Problem 3: Adams-Bashforth-Moulton Method

Problem Statement:

Solve Computer problem 3 in Section 8.4.

Computer Problem 8.4.3

Compute the solution of

$$\begin{aligned} y' &= -2xy^2 \\ y(0) &= 1 \end{aligned}$$

at $x = 1.0$ using $h = 0.25$ and the fourth-order Adams-Bashforth-Moulton method (Problems 8.4.4–5, p. 555) together with the fourth-order Runge-Kutta method. Give the computed solution to five significant digits at 0.25, 0.5, 0.75, and 1.0. Compare your results to the exact solution $y = 1/(1 + x^2)$.

Related Problems from Section 8.4

Problem 8.4.4: Use the method of undetermined coefficients to derive the **fourth-order Adams-Bashforth formula**

$$x_{n+1} = x_n + \frac{h}{24}[55f_n - 59f_{n-1} + 37f_{n-2} - 9f_{n-3}]$$

Problem 8.4.5: Derive the **fourth-order Adams-Moulton formula**

$$x_{n+1} = x_n + \frac{h}{24}[9f_{n+1} + 19f_n - 5f_{n-1} + f_{n-2}]$$

Solution Approach

The fourth-order Adams-Bashforth-Moulton (ABM4) method is a predictor-corrector scheme that requires multiple previous values. Since we only have the initial condition $y(0) = 1$, we use the fourth-order Runge-Kutta method to bootstrap the first three steps, then switch to ABM4.

Method Overview:

1. **Bootstrap (Steps 1-3):** Use RK4 to compute y_1, y_2, y_3
2. **Predictor (Adams-Bashforth 4-step):**

$$y_{n+1}^* = y_n + \frac{h}{24}[55f_n - 59f_{n-1} + 37f_{n-2} - 9f_{n-3}]$$

3. **Corrector (Adams-Moulton 4-step):**

$$y_{n+1} = y_n + \frac{h}{24}[9f_{n+1} + 19f_n - 5f_{n-1} + f_{n-2}]$$

where $f(x, y) = -2xy^2$ for our problem.

Computational Results

Bootstrap Phase (RK4):

x	y (RK4)	Exact Solution
0.00	1.0000000000	1.0000000000
0.25	0.9411540130	0.9411764706
0.50	0.7999481032	0.8000000000
0.75	0.6399738841	0.6400000000

Table 3: Bootstrap phase using RK4

ABM4 Phase:

At $x = 1.0$:

- Predicted value: $y^* = 0.5105894849$
- Corrected value: $y = 0.4982178726$
- Exact solution: $y = 0.5000000000$

Final Results (5 Significant Digits)

x	ABM4 Solution	Exact Solution	Absolute Error
0.25	0.94115	0.94118	2.246×10^{-5}
0.50	0.79995	0.80000	5.190×10^{-5}
0.75	0.63997	0.64000	2.612×10^{-5}
1.00	0.49822	0.50000	1.782×10^{-3}

Table 4: Comparison of ABM4 numerical solution with exact analytical solution $y = 1/(1 + x^2)$

Error Analysis

- Maximum absolute error: 1.782×10^{-3}
- Mean absolute error: 3.765×10^{-4}
- Relative error at $x = 1.0$: 0.356%

The ABM4 method demonstrates excellent accuracy for this problem. The errors are very small, with the largest error occurring at the final point $x = 1.0$. This is typical for multistep methods as errors can accumulate over integration steps. The predictor-corrector approach effectively reduces errors compared to using Adams-Bashforth alone.

Implementation Note: See `final_p03.jl` for the complete implementation.

Appendix

A. Problem 2 Code Implementation Details

The following figures show the detailed Julia implementation of the fourth-order Runge-Kutta method for Problem 2.

```
108 ∨ function rk4_step(f, t, x, h)
109     k1 = f(t, x)
110     k2 = f(t + h/2, x + h*k1/2)
111     k3 = f(t + h/2, x + h*k2/2)
112     k4 = f(t + h, x + h*k3)
113
114     x_next = x + (h/6) * (k1 + 2*k2 + 2*k3 + k4)
115     return x_next
116 end
```

Figure 2: RK4 Step Function: Implements a single step of the fourth-order Runge-Kutta method with the four-stage computation (k_1, k_2, k_3, k_4) .

```
134 ∨ function rk4_solve(f, to, tf, x0, h)
135     # Determine number of steps
136     n_steps = round(Int, (tf - to) / h)
137
138     # Initialize arrays
139     t_values = zeros(n_steps + 1)
140     x_values = zeros(n_steps + 1)
141
142     # Initial condition
143     t_values[1] = to
144     x_values[1] = x0
145
146     # RK4 iterations
147 ∨ for i in 1:n_steps
148     t_values[i+1] = t_values[i] + h
149     x_values[i+1] = rk4_step(f, t_values[i],
150                             x_values[i], h)
151 end
152 return t_values, x_values
153 end
```

Figure 3: RK4 Solve Function: Complete solver that iterates through all time steps, maintaining arrays of solution values.

```

162  # Problem parameters
163  t0 = 0.0
164  tf = -2.0
165  x0 = 3.0
166  h = -0.01
167
168  println("Initial time t0 = ", t0)
169  println("Final time te = ", tf)
170  println("Initial condition x0 = ", x0)
171  println("Step size h = ", h)
172  println("Number of steps = ", abs(round(Int, (tf -
    to) / h)))
173
174  # Solve using RK4
175  t_rk4, x_rk4 = rk4_solve(f, t0, tf, x0, h)

```

Figure 4: RK4 Solution Call: Main execution showing the ODE definition $f(t, x) = x(1 - e^t)/(e^t + 1)$, exact solution, and solver invocation with parameters.

The complete implementation can be found in `final_p02.jl`. The code demonstrates:

- Clean function decomposition with `rk4_step` and `rk4_solve`
- Proper handling of backward integration (negative step size)
- Array management for storing solution trajectory
- Verification against analytical solution

References

- [1] Wolfram Alpha. Runge-kutta method verification for problem 2. https://www.wolframalpha.com/input?i=Runge-Kutta+method%2C++dx%2Fdt+%3D+x*%281-exp%28t%29%29%2F%281%2Bexp%28t%29%29%2C+x%280%29+%3D+3%2C+from+t%3D-2+to+t%3D0%2C+h%3D0.01, 2025. Accessed: December 1, 2025.