

Week 4 Tutorial


COMP10001 – Foundations of Computing

Semester 2, 2025

Clement Chau

- Introduction to Functions
- More on Strings
- Methods, Tuples, Sequences

Revision: Functions!



sem1-2025 > week-4 > functions.py > ...

```
1  # This is an example of a function in Python
2  def add(a, b):
3      return a + b
4
5  result = add(1, 2)
6  print(result) # result = 3
```



-



TutSheet Week 4 – Question 1

1. What is shown on screen after you execute the program below? What is the value of res, res_p, res_r, and res_pr?

```
def ave(a, b):  
    result = (a + b) / 2  
    return ?  
  
def ave_p(a, b):  
    result = (a + b) / 2  
    print("p", result)  
  
def ave_r(a, b):  
    result = (a + b) / 2  
    return result  
  
def ave_pr(a, b):  
    result = (a + b) / 2  
    print("pr", result)  
    return result  
  
res = ave(1, 2)  
res_p = ave_p(1, 2)  
res_r = ave_r(1, 2)  
res_pr = ave_pr(1, 2)
```

	Shown on screen	Value of variables
res		None
res_p	p 1.5	None
res_r		1.5
res_pr	pr 1.5	1.5

return:

how a function stops execution and "gives back a value", so that the value can be, for example, assigned to a variable.

print:

show the value on your screen, but does **NOT** "gives back a value" as return does. As such, the value it "give back" is **None**

TutSheet Week 4 – Question 2

2. What's wrong with this code? How can you fix it?

```
def calc(n1, n2):  
    answer = n1 + (n1 * n2)  
    print(answer)  
    return answer  
  
num = int(input("Enter the second number: "))  
result = calc(2, num)  
→ print("The result is:", result) None  
    "The result is: None"
```

This function prints the answer to the calculation it's performed, **rather than returning it**.

This means that the value of `result` will be None and the last line will not work as intended.

TutSheet Week 4 – Question 3

3. Evaluate the following method calls given the assignment `s = "Computing is FUN!"` Think about the input and output of each method. You're not expected to know all methods for all types: if you haven't seen some of these before, your best guess based on the name will probably be right!

- | | | | |
|-------------------------------------|----------------------------|--------------------------------------|------------------------------------|
| (a) <code>s.isupper()</code> | <i>False</i> | (e) <code>s.strip('!')</code> | <i>"Computing is FUN"</i> |
| (b) <code>s.upper()</code> | <i>"COMPUTING IS FUN!"</i> | (f) <code>s.replace('i', '!')</code> | <i>"Comput!ng !s FUN!"</i> |
| (c) <code>s.endswith("FUN!")</code> | <i>True</i> | (g) <code>s.split()</code> | <i>["Computing", "is", "FUN!"]</i> |
| (d) <code>s.count('i')</code> | <i>2</i> | (h) <code>s.isdigit()</code> | <i>False</i> |

TutSheet Week 4 – Question 4

4. Evaluate the following given the assignment `lst = [2, ("green", "eggs", "ham"), False]`. Assume the list is reset after each part.

(a) `lst[2]` *False*

(b) `lst[1][-2]` *"eggs"*

(c) `lst[1][-2][:3]` *"egg"*

(d) `lst.append(5); print(lst)`
[2, ("green", "eggs", "ham"), False, 5]

(e) `lst.pop(2); print(lst)`
False, [2, ("green", "eggs", "ham")]

(f) `lst.reverse(); print(lst)`
[False, ("green", "eggs", "ham"), 2]

list	[2,	("green", "eggs", "ham"),			False]
index	0	1			2
	-3	-2			-1
		0	1	2	
		-3	-2	-1	

.pop()

- *remove an element from a list at a specified index*
- *If no index : remove the last element from list*

TutSheet Week 4 – Past Exam Q1

1. What does the following code produce as output?

(a) $\frac{22 \% 4}{2} * 4 + 1.5 - \frac{22 // 3}{7}$
 $2 * 4 + 1.5 - 7 = 2.5$

(b) `"hello"[:3] + "p"`
`"help"`

(c) $(1, 2) + \underline{(3)} + (4, 5)$
TypeError

*(3) : Not tuple, Integer
because a single value inside parentheses
without a trailing comma is interpreted as
a regular integer*

(d) `tuple('abc') + (4,)`
`('a', 'b', 'c', 4)`

TutSheet Week 4 – Past Exam Q2 (a)

2. One liners!

- (a) Suppose that `str1` and `str2` are two strings, and that `k` is a positive integer. Give a single Python assignment statement that assigns `True` to `match` if `str1` and `str2` have the same first `k` characters, and assigns `False` to `match` if not.

```
str1[:k] == str2[:k]
```

```
match = str1[:k] == str2[:k]
```

```
k = 2
str1 = "apple"
str2 = "ale"

match = str1[:k] == str2[:k]
print(match)
```

False

TutSheet Week 4 – Past Exam Q2 (b), (c)

- (b) Suppose that `lst` is a non-empty list of numbers. Give a single Python assignment statement that assigns the difference between the largest and smallest numbers in `lst` to the variable `diff`.

```
diff = max(lst) - min(lst)
```

- (c) Suppose that `text` is a Python string. Give a single Python assignment statement that assigns the number of words in `text` to `wrds`, where a “word” is any non-blank sequence of characters. (Hint: A method covered in previous exercises may be useful).

```
wrds = len(text.split())
```

```
text = "Computing is FUN!"  
  
wrds = len(text.split())  
  
print(text.split())  
print(wrds)
```

```
['Computing', 'is', 'FUN!']  
3
```

Independent Work

- **Do worksheets 6, 7, 8** on Ed (**due next Monday at 6pm**)
 - Remember that **Ed worksheets contributes to 10% of your total score!**
- **Raise your hand** if you have any questions!

Scan here for annotated slides

