(a) Recall that the cross entropy loss between the true probability distribution p and another distribution q is $-\sum_i p_i log(q_i)$. With given center word c, y is the true emprical distribution(a one-hot vector with a 1 for the true outside word o, and 0 everywhere), and \hat{y} is the predicted distribution, k^{th} entry in these vectors indicates the conditional probability of the k^{th} word being an outside word for the given c. So the cross entropy loss between p and p is:

$$-\sum_{w \in Vocab} y_w log(\hat{y}_w) = -\sum_{w \neq o, w \in Vocab} 0 * log(\hat{y}_w) - 1 * log(\hat{y}_o) = -log(\hat{y}_o)$$

just the same as the naive softmax loss for single pair words of o and c:

$$J_{naive-softmax}(v_c, o, U) = -logP(O = o|C = c)$$

$$\begin{split} &\frac{\partial}{\partial v_c} J_{naive-softmax}(v_c, o, U) \\ &= \frac{\partial}{\partial v_c} - log(\hat{y}_o) \\ &= -\frac{\partial}{\partial v_c} log \left(\frac{exp(u_o^T v_c)}{\sum_{w \in Vocab} exp(u_w^T v_c)} \right) \\ &= -\left(\frac{\partial}{\partial v_c} logexp(u_o^T v_c) - \frac{\partial}{\partial v_c} log \sum_{w \in Vocab} exp(u_w^T v_c) \right) \\ &= -\left(u_o - \frac{1}{\sum_{w \in Vocab} exp(u_w^T v_c)} \sum_{w \in Vocab} \frac{\partial}{\partial v_c} exp(u_w^T v_c) \right) \\ &= -\left(u_o - \frac{1}{\sum_{w \in Vocab} exp(u_w^T v_c)} \sum_{w \in Vocab} exp(u_w^T v_c) u_w \right) \\ &= -\left(u_o - \frac{\sum_{w \in Vocab} exp(u_w^T v_c) u_w}{\sum_{w \in Vocab} exp(u_w^T v_c)} \right) \\ &= -\left(u_o - \sum_{x \in Vocab} \frac{exp(u_w^T v_c)}{\sum_{w \in Vocab} exp(u_w^T v_c)} u_x \right) \\ &= -\left(u_o - \sum_{x \in Vocab} \hat{y}_x u_x \right) \\ &= \sum_{x \in Vocab} \hat{y}_x u_x - u_o \\ &= \sum_{x \in Vocab} \hat{y}_x u_x - \sum_{x \in Vocab} y_x u_x \\ &= U(\hat{y} - y)^T \end{split}$$

$$\begin{split} \frac{\partial}{\partial u_w} J_{naive-softmax}(v_c, o, U) \\ &= \frac{\partial}{\partial u_w} - log(\hat{y}_o) \\ &= -\frac{\partial}{\partial u_w} log \left(\frac{exp(u_o^T v_c)}{\sum_{w \in Vocab} exp(u_w^T v_c)} \right) \\ &= -\left(\frac{\partial}{\partial u_w} logexp(u_o^T v_c) - \frac{\partial}{\partial u_w} log \sum_{w \in Vocab} exp(u_w^T v_c) \right) \\ &= -\left(\frac{\partial}{\partial u_w} logexp(u_w^T v_c) - \frac{\partial}{\partial u_w} log \sum_{w \in Vocab} exp(u_w^T v_c) \right) \\ &= \frac{1}{\sum_{w \in Vocab} exp(u_w^T v_c)} \sum_{w \neq o} \frac{\partial}{\partial u_w} exp(u_w^T v_c) \\ &= \frac{1}{\sum_{w \in Vocab} exp(u_w^T v_c)} \sum_{w \neq o} exp(u_w^T v_c) v_c \\ &= \sum_{x \neq o} \frac{u_x^T v_c}{\sum_{w \in Vocab} exp(u_w^T v_c)} v_c \\ &= \sum_{x \neq o} \hat{y}_x v_c \\ &= \sum_{x \neq o} \hat{y}_x v_c \\ &= \frac{\partial}{\partial u_o} log \left(\frac{exp(u_o^T v_c)}{\sum_{w \in Vocab} exp(u_w^T v_c)} \right) \\ &= -\left(\frac{\partial}{\partial u_o} logexp(u_o^T v_c) - \frac{\partial}{\partial u_o} log \sum_{w \in Vocab} exp(u_w^T v_c) \right) \\ &= -\left(v_c - \frac{1}{\sum_{w \in Vocab} exp(u_w^T v_c)} exp(u_o^T v_c) v_c \right) \\ &= \hat{y}_o v_c - v_c \\ &= \frac{\partial}{\partial u_x} J_{naive-softmax}(v_c, o, U) \\ &= \sum_{x \in Vocab} v_c(\hat{y}_x (1 - y_x) + (\hat{y}_x - y_x) y_x) \\ &= \sum_{x \in Vocab} v_c(\hat{y}_x - y_x) \\ &= (\hat{y} - y) v_c \\ \\ \sigma'(x) &= -(1 + e^{-x})^{-2} e^{-x} * -1 \\ &= \frac{e^{-x}}{(1 + e^{-x})^2} \frac{1}{(1 + e^{-x})} \end{aligned}$$

$$\begin{split} \frac{\partial}{\partial v_c} J_{neg-sample(V_c,o,U)} \\ \text{(e)} &= -\frac{1}{\sigma(u_o^T v_c)} \sigma(u_o^T v_c) (1 - \sigma(u_o^T v_c)) u_o - \sum_{k=1}^K \frac{1}{\sigma(-u_k^T v_c)} \sigma(-u_k^T v_c) (1 - \sigma(-u_k^T v_c)) * - u_k \\ &= (\sigma(u_o^T v_c) - 1) u_o - \sum_{k=1}^K (\sigma(-u_k^T v_c) - 1) u_k \\ &\frac{\partial}{\partial u_o} J_{neg-sample(V_c,o,U)} = -\frac{1}{\sigma(u_o^T v_c)} \sigma(u_o^T v_c) (1 - \sigma(u_o^T v_c)) v_c = (\sigma(u_o^T v_c) - 1) v_c \\ &\frac{\partial}{\partial u_k} J_{neg-sample(V_c,o,U)} = -\frac{1}{\sigma(-u_k^T v_c)} \sigma(-u_k^T v_c) (1 - \sigma(-u_k^T v_c)) * - v_c = -(\sigma(-u_k^T v_c) - 1) v_c \end{split}$$

Negative sampling only updates u_o and K u_k , (K + 1) total, while naive softmax needs to update all the u_k .

$$egin{aligned} rac{\partial}{\partial U}J_{skip-gram}(v_c,w_{t-m},\ldots w_{t+m},U) &= \sum_{-m\leq j\leq m,j
eq 0}rac{\partial J(v_c,w_{t+j},U)}{\partial U} \ \end{aligned}$$
 (f) $rac{\partial}{\partial v_c}J_{skip-gram}(v_c,w_{t-m},\ldots w_{t+m},U) &= \sum_{-m\leq j\leq m,j
eq 0}rac{\partial J(v_c,w_{t+j},U)}{\partial v_c} \ rac{\partial}{\partial v_w}J_{skip-gram}(v_c,w_{t-m},\ldots w_{t+m},U) &= 0, orall w
eq c \end{aligned}$