

# Volatility forecast of financial returns with explanatory variables of different frequencies

Louis Geist

16/11/2023



- Financial risk measurement
- Daily volatility forecast can be useful to build confidence interval of the returns forecast
- Understand impact of long term explanatory variable on financial returns volatility
- Focus on S&P 500 and NASDAQ-100
- C. Conrad and O. Kleen. "Two are better than one: Volatility forecasting using multiplicative component GARCH-MIDAS models", 2020. [3]

# ① GARCH-MIDAS model

## ② Data

## ③ Empirical results

# ① GARCH-MIDAS model

## ② Data

## ③ Empirical results

# GARCH-MIDAS Model Definition

A process  $(\varepsilon_{i,t})_{t \in \mathbb{Z}, i \in I_t}$  follows a **GARCH-MIDAS model** if :  
 $\exists(\alpha, \beta, \gamma) \in \mathbb{R}^3, \exists(Z_{i,t})_{t \in \mathbb{Z}, i \in I_t} \sim WN, \forall t \in \mathbb{Z}, \forall i \in I_t$ :

$$\varepsilon_{it} = \sqrt{g_{it}\tau_t} Z_{i,t}$$

with :

- $g_{i,t} = (1 - \alpha - \frac{\gamma}{2} - \beta) + (\alpha + \gamma \mathbb{1}_{\varepsilon_{i-1,t} < 0}) \frac{\varepsilon_{i-1,t}^2}{\tau_t} + \beta g_{i-1,t}$
- $\tau_t$  is a fixed function of a low-frequency explanatory process  $X$
- $I_t$ , the list of values that can take "i" during the period  $t$ .

# GARCH-MIDAS Model Definition - $\tau$ definition

- $\tau$  expresses the influence of the low-frequency variable  $X$

$$\forall t \in \mathbb{N}, \tau_t = \exp\left(m + \theta \sum_{k=1}^K \varphi_k X_{t-k}\right)$$

# GARCH-MIDAS Model Definition - $\tau$ definition

- $\tau$  expresses the influence of the low-frequency variable  $X$

$$\forall t \in \mathbb{N}, \tau_t = \exp\left(m + \theta \sum_{k=1}^K \varphi_k X_{t-k}\right)$$

where :

- $K$  is the number of lags of the variable  $X$
- $m$  and  $\theta$  have to be estimated

# GARCH-MIDAS Model Definition - $\tau$ definition

- $\tau$  expresses the influence of the low-frequency variable  $X$

$$\forall t \in \mathbb{N}, \tau_t = \exp\left(m + \theta \sum_{k=1}^K \varphi_k X_{t-k}\right)$$

where :

- $K$  is the number of lags of the variable  $X$
- $m$  and  $\theta$  have to be estimated
- $\varphi_k$  is the weighting scheme  $\forall k \in [1, K]$

$$\varphi_k = \lambda \left[ \left( \frac{k}{K+1} \right)^{w_1-1} \left( 1 - \frac{k}{K+1} \right)^{w_2-1} \right]$$

where  $\lambda$  is defined so that  $\sum_{k=1}^K \varphi_k = 1$ .



# Results of estimation: Weighting Schemes




Figure 1: Examples of Weighting Schemes (restricted and unrestricted)

# Results of estimation: $\tau$




Figure 2: Example of a  $\tau$  transformation

# GARCH-MIDAS Forecast Formula

$$\forall s \in \mathbb{N}^*, \quad \boxed{\hat{h}_{k,t+s|t} = \tau_{t+1} (1 + \delta^{n_h} (g_{1,t+1} - 1))}$$

where :

- $\delta = \alpha + \frac{\gamma}{2} + \beta$
- $n_h = \#l_{t+1} + \dots + \#l_{t+s-1} + k - 1$  (horizon)

① GARCH-MIDAS model

② Data

③ Empirical results

# Table of Daily Quotation Availability

Index / Data Series	Start Date
S&P 500 (SPX)	05/01/1971
NASDAQ-100 (NDX)	02/10/1985
VIX	02/01/1990
RVOL22	03/02/1971
VRP	02/01/1990
NFCI	04/01/1971
NAI	01/02/1959
IP	01/02/1959
HOUST	01/02/1959

Table 1: Availability of Daily Quotations at Closing

# Table of Daily Quotation Availability


Index / Data Series	Start Date
S&P 500 (SPX)	05/01/1971
NASDAQ-100 (NDX)	02/10/1985
VIX	02/01/1990
RVOL22	03/02/1971
VRP	02/01/1990
NFCI	04/01/1971
NAI	01/02/1959
IP	01/02/1959
HOUST	01/02/1959

Table 1: Availability of Daily Quotations at Closing

Realized volatility availability :

- S&P 500 : 2000 - 2019 and 01/06/2023 - today
- NASDAQ-100 : 01/06/2023 - today

# Index Plots



**Figure 3:** Raw Series of Industrial Production Index (IP) & Logarithmic Differences Transformation of Industrial Production Index (IP) Over Time

1 GARCH-MIDAS model

2 Data

3 Empirical results




# Evaluating Volatility Prediction

- daily volatility : a theoretical quantity  $\rightarrow$  no realization

# Evaluating Volatility Prediction

- daily volatility : a theoretical quantity  $\rightarrow$  no realization
- estimator of the daily volatility based on the 5 minutes intraday data of the index

# Volatility point predictions of S&P500



**Figure 4:** Prediction of S&P 500 daily volatility with an origin date of 15/08/2023. "GM" stands for GARCH-MIDAS.

# Confidence Interval

---

**Algorithm 1** Estimation of a Confidence Interval for a forecast of horizon  $h$

---

Require:

- $(X_t)_{t \in [1, N]}$  target values
- $(\hat{X}_t)_{t \in [1, N]}$  predictions
- $\hat{X}_\nu$  for  $\nu > N$ , which is the prediction for which we want the confidence interval

Ensure:  $q_-$  and  $q_+$ , the bounds of the confidence interval of  $\hat{X}_\nu$  at level  $\alpha$ .

1: for  $i$  in  $[1, N]$  do

2:      $\gamma_i \leftarrow \frac{X_i}{\hat{X}_i}$

3: end for


4: Sort  $\gamma$  in ascending order.

5: Calculate  $n_- \leftarrow \lfloor \frac{1-\alpha}{2} N \rfloor$  &  $n_+ \leftarrow \lceil (1 - \frac{1-\alpha}{2}) N \rceil$

6: Calculate  $q_- \leftarrow \gamma_{n_-} \hat{X}_\nu$  &  $q_+ \leftarrow \gamma_{n_+} \hat{X}_\nu$   
   return  $q_-$  and  $q_+$

---

# Confidence Intervals



**Figure 5:** 90% confidence intervals for volatility predictions on S&P 500 from horizon 1 to 10 with an origin date of 15/08/2023.

# Model Comparison

## Loss function

- $\sigma^2$  the variance
- $h$  its prediction

$$QLIKE(\sigma^2, h) = \log\left(\frac{h}{\sigma^2}\right) + \frac{\sigma^2}{h} - 1$$




Figure 6: QLIKE Loss for  $\sigma^2 = 1$ .

# Model Comparison

<i>Horizon</i>	1	2	5	10	22	44	66
GM_dhous	0.29	0.26	0.36	0.42	0.40	0.33	0.29
GM_ip	0.32	0.28	0.35	0.39	0.36	0.29	0.23
GM_nai	0.29	0.26	0.34	0.39	0.36	<u>0.29</u>	<u>0.23</u>
GM_nfci	0.26	0.22	0.31	<u>0.37</u>	<u>0.35</u>	0.30	0.27
GM_Rvol22	0.27	0.23	0.32	0.38	0.36	0.29	0.24
GM_vix	<u>0.20</u>	<u>0.16</u>	<u>0.28</u>	0.40	0.46	0.45	0.44
GM_vrp	0.31	0.27	0.35	0.40	0.38	0.31	0.26
GM_vix_dhous	0.23	0.21	0.34	0.43	0.47	0.45	0.44
GM_vix_ip	0.23	0.21	0.33	0.43	0.46	0.45	0.42
GM_vix_nai	0.23	0.21	0.32	0.41	0.42	0.39	0.37
GM_vix_nfci	0.22	0.20	0.33	0.43	0.47	0.46	0.44
GARCH(1,1)	0.43	0.42	0.49	0.48	0.43	0.36	0.29

**Table 2:** Cumulative Mean Error of S&P 500 Volatility Predictions - Training period: 1991 - 2014.  $n = 250$ . For each horizon, the underlined value is the minimum error.





# Graphical User Interface

## Average error

### Models evaluation

Select another table number :

The following parameters were used:

**Main index :** spx

**Number of forecasts:** 250

**Training period :** 1991-01-05/2015-01-01

**Cumulative evaluation :** TRUE

#### QLIKE mean error

	1	2	5	10	22	44	66
GM_dhoust	0.30	0.26	0.36	0.42	0.40	0.33	0.29
GM_ip	0.32	0.28	0.35	0.39	0.36	0.29	0.23
GM_nai	0.30	0.26	0.34	0.39	0.36	0.29	0.23
GM_nfci	0.26	0.22	0.31	0.37	0.35	0.30	0.27
GM_Rvol22	0.27	0.23	0.33	0.39	0.37	0.30	0.24
GM_vix	0.20	0.16	0.28	0.40	0.46	0.45	0.44
GM_vrp	0.31	0.27	0.35	0.40	0.38	0.31	0.26
GM_vix_dhoust	0.23	0.21	0.34	0.43	0.47	0.46	0.44
GM_vix_ip	0.23	0.21	0.33	0.43	0.46	0.45	0.42
GM_vix_nai	0.24	0.21	0.32	0.41	0.43	0.40	0.37
GM_vix_nfci	0.22	0.20	0.33	0.43	0.47	0.46	0.44
GARCH(1,1)	0.43	0.42	0.49	0.49	0.43	0.36	0.29

#### Minimum mean error

	1	2	5	10	22	44	66
GM_dhoust							
GM_ip							
GM_nai						True	True
GM_nfci					True	True	
GM_Rvol22							
GM_vix		True	True	True			
GM_vrp							
GM_vix_dhoust							
GM_vix_ip							
GM_vix_nai							
GM_vix_nfci							
GARCH(1,1)							

Figure 8: RShiny - Part 2

# Conclusion

- Utilizing explanatory variables in a GARCH-MIDAS model enhances prediction accuracy compared to a classical GARCH model.
- However, the effectiveness depends on selecting the appropriate explanatory variables for the appropriate horizon.
- Not all GARCH-MIDAS models consistently outperform the GARCH(1,1) model in certain test periods.

- [1] Ole E. Barndorff-Nielsen and Neil Shephard. “Econometric Analysis of Realized Volatility and Its Use in Estimating Stochastic Volatility Models”. In: *Journal of the Royal Statistical Society. Series B (Statistical Methodology)* 64.2 (2002), pp. 253–280. ISSN: 13697412, 14679868. URL: <http://www.jstor.org/stable/3088799> (visited on 07/24/2023).
- [2] Winston Chang et al. *shiny: Web Application Framework for R*. R package version 1.7.4. 2022. URL: <https://CRAN.R-project.org/package=shiny>.
- [3] C. Conrad and O. Kleen. “Two are better than one: Volatility forecasting using multiplicative component GARCH-MIDAS models”. In: *J Appl Econ.* 35 (2020), pp. 19–45. URL: <https://doi.org/10.1002/jae.2742>.
- [4] Francis X Diebold and Robert S Mariano. “Comparing Predictive Accuracy”. In: *Journal of Business & Economic*

*Statistics* 20.1 (2002), pp. 134–144. DOI:  
10.1198/073500102753410444. eprint:  
<https://doi.org/10.1198/073500102753410444>. URL:  
<https://doi.org/10.1198/073500102753410444>.

- [5] Ghysels E. Engle R. F. and Sohn B. “Stock market volatility and macroeconomic fundamentals”. In: *Review of Economics and Statistics* 95 (2013), pp. 776–797.
- [6] Alexios Ghalanos. *rugarch: Univariate GARCH models*. R package version 1.4-9. 2022.
- [7] Onno Kleen. *alfred: Downloading Time Series from ALFRED Database for Various Vintage*. R package version 0.2.1. URL: <https://github.com/onnokleen/alfred/>.
- [8] Onno Kleen. *mfGARCH: Mixed-Frequency GARCH Models*. R package version 0.2.1. 2021. URL: <https://github.com/onnokleen/mfGARCH/>.

- [9] Carson Sievert. *Interactive Web-Based Data Visualization with R, plotly, and shiny*. Chapman and Hall/CRC, 2020. ISBN: 9781138331457. URL: <https://plotly-r.com>.