

Real-Time Deepfake Detection using a Hybrid MobileNet-LSTM Model For Image and Video Analysis

S Ambika
Associate Professor
Department of CSE

Vel Tech Rangarajan Dr. Sagunthala R&D
Institute of Science and Technology
Chennai, India
drambikas@veltech.edu.in

Yerramsetty Harini
4th year, B.Tech
Department of CSE

Vel Tech Rangarajan Dr. Sagunthala R&D
Institute of Science and Technology,
Chennai, India
hariniyerramsetty9@gmail.com

B R Sumanth
4th year, B.Tech,
Department of CSE

Vel Tech Rangarajan Dr. Sagunthala R&D
Institute of Science and Technology
Chennai, India
brsumanth1405@gmail.com

Abstract— As deepfake technology has become more advanced, there is an urgent need for strengthening detection mechanisms that can help counter misinformation and online fraud. Deepfake media is manufactured using deep learning techniques. It has recently become increasingly sophisticated and the boundary between genuine and tampered content is often hard to see. This paper introduces a hybrid MobileNet-LSTM model, which is made for spotting deepfakes in both image and video. The deepfake identification system uses MobileNet to efficiently sample spatial features and LSTM to gather temporal dependencies, thereby improving the detection rate of tampered content. Meanwhile, this method is validated on standard datasets and that the accuracy is better, in terms of computational efficiency and that it is more robust than other types of manipulation.

Keywords *Deepfake Detection, Hybrid MobileNet-LSTM Model, Real-time Analysis, Machine Learning, MobileNet, LSTM, Computer Vision, Media Authentication.*

I. INTRODUCTION

The rise of artificial intelligence (AI) has seen the emergence of many disruptive technologies, including one of the most controversial which is deepfake technology. Deepfakes (very realistic manipulations of visual and audio material) have gained notoriety in recent years due to its potential uses for misinformation or social deception. The term "deepfake" is a combination of the many deep learning algorithms including Generative Adversarial Networks (GANs), and the word fakes, with deepfakes allowing individuals to create fake videos, photographs, and audio, or content. These fakes are observed to be unidentifiable from original material. Many times these manipulated media are used for malicious purposes, like misinformation, political propaganda, and more recently there are instances of cyberbullying and slander. As deepfake technologies continue to evolve and become easier to access, the detection of manipulated media is now a pressing issue of concern in many industries (e.g., news, social media, entertainment, law enforcement, even education). The current state of deepfake detection tools widely use either Convolutional Neural

Network (CNN) or Recurrent Neural Network (RNN) to process time static images and time dynamic video. Deepfake detection tools generally used either Convolutional Neural Networks (CNNs) or Recurrent Neural Networks (RNNs) to process static images and dynamic video content. CNNs are good at extracting spatial features from images but can be challenged by videos, where the temporal dimension also needs to be taken into account. RNNs and its more complex variant, LSTM, can scan sequences of video frames to identify very subtle discrepancies that may not be apparent in an individual frame. Existing deepfake detection systems are good for many applications, but they often have issues with real-time detection, scalability, and computational cost. This work suggests a new solution which combines MobileNet and LSTM networks to overcome these limitations... While many existing deepfake detection systems are effective, they tend to face challenges when it comes to real-time detection, scalability, and computational efficiency. This project suggests a new hybrid approach that incorporates the strengths of MobileNet and LSTM networks to overcome the above limitations. The major goal of this project is to create a real-time efficient and scalable deepfake detection system that together incorporates spatial feature extraction from MobileNet and temporal pattern recognition from LSTM networks. This model will be able to distinguish between static images and dynamic video content, a complete solution towards detecting deepfakes. Given its emphasis on real-time detection, this model seeks to lend its hand in meeting the burgeoning demand for equipment that can serve to counteract the proliferation of false media in several fields such as social networking sites, media houses, and digital forensics. The system to be proposed will support processing high amounts of media content in real-time and offer immediate feedback to the users regarding the authenticity of the media they consume.

II. LITERATURE SURVEY

In this study presents a hybrid deepfake detection model that incorporates Convolutional Neural Networks (CNNs) and Long Short-Term Memory (LSTM) networks to improve classification accuracy across images and videos. It is likely that the authors improve the processing of both spatial features and the temporal aspects of the data in order to help detection of manipulated media. The paper also discusses the benefits and drawbacks of the hybrid models, especially how

they perform for advanced deepfake generation techniques and the ability for real-time detections [1].

The study involves integrating CNN and LSTM models for video-based deepfake detection that uses optical flow features to exploit physical inconsistencies in motion. Also likely to discuss is how optical flow improves both true positives and classification accuracy in high resolution video. The paper probably features a discussion of whether the real-time performance of deepfake detection is achievable, or whether sophistication of the approach would cause computational costs exist to some extent, and potential optimizations to the architecture or processing pipeline that could be employed [2].

The target of this research is latent actors identified as "deepfake" images through the closed-loop process of utilizing Deep Neural Networks (DNNs). It is probable that the authors study various architectures of DNNs while elucidating their specific advantages and disadvantages in classifying manipulated media images and their descriptions. It may be suggested in the paper that additional time-expansive images are needed to classify deepfake images; or there may be overlap with another identified gap for a more generalized classification so that they can reduce the false positive rates of misclassification when models are deployed under different environments [3].

This study explores a bespoke deep learning model, developed for detecting deepfake images. It is likely that the authors present an optimized CNN architecture architecture compared to the standard approach, and they were able to outpace the latter methods to provide a state-of-the-art classification accuracy; while also identifying the challenges tactile people's agency in accurately detecting a deepfake video and the models overall performance sequentially through optimized temporal feature extraction [4].

This study investigates transfer learning and ensemble models to potentially improve deepfake detection accuracy. The authors potentially highlight the positive aspects of utilizing pre-trained networks, which sometimes not only reduce the time for training, but retain similar detection accuracy. However the authors may also identify weaknesses in model adaptation as reliance on pre-trained architecture can restrict flexibilities in identifying new methods of deepfakes [5].

This study also investigates a hybrid framework that combines machine and deep learning methods to improve deepfake detection. The authors likely assess the effectiveness of feature extraction through CNNs in conjunction, with classification through traditional machine learning models. While the hybrid model may provide a compromise of accuracy and computational expense, the authors potentially address obstacles surrounding tuning the model to achieve maximum performance [6].

This study assesses the potential of advanced deep learning models for real-time detection of deepfake video content. The authors likely address how deepfake detection models assess inconsistencies in frames to signal classified manipulation of media. The authors may also offer commentary on scalability, in particular the computation components of processing high-resolution videos affecting performance in real-time [7].

This research gives a comparative study of several deep learning architectures for deepfake detection. The authors likely present the benefits and weaknesses of different

architectures, including CNNs, LSTMs, and transformer-based architectures. Moreover, the authors likely discuss the impact of the dataset in which they train and evaluate their model [8].

This research offers a study of using CNNs and LSTMs in a video-based deepfake detection algorithm that identifies temporal inconsistencies and motion artifacts. The authors likely provided results indicating that the use of the temporal analysis increased classification accuracy. However, they may also noted the challenges of real-time processing, including delays in processing video frame [9].

This study presents a self-attention mechanism with EfficientNet to improve deepfake detection and focuses on feature extraction as well as interpretability of the model. The authors likely discuss how a self-attention model improves validity from adversarial attacks. Although, they may have not addressed the computational complexity of training an efficient self-attention model which may also require more time and resources when processing [10].

This research investigates a CNN-LSTM model that can be used for facial expression recognition in video sequences. The authors use CNNs to pull spatial features from individual frames and LSTM networks to extract temporal relationships from the sequences of frames. This combined method models sequential data, and increased classification accuracy of facial expressions can be achieved [11].

This research presents a real-time human action recognition system based on raw depth video and RNN. Utilizing depth video aims to improve action recognition accuracy while reducing the computational cost. The authors explained how depth video analysis is advantageous over traditional RGB video methods when there is clutter in the background or when ambient lighting conditions can vary. This model's ability to analyze the raw depth video is a significant contribution toward real-time surveillance and application for gesture recognition [12].

III. METHODOLOGY

The Hybrid MobileNet-LSTM Model proposed is a formalized approach to obtaining accurate as shown in Fig. 1, timely deepfake detection with improved scalability and interpretability. The proposed system will identify spatial and temporal anomalies in deepfake media, superior to the performance of conventional detecting mechanisms. The approach is structured into several phases, such as data collection, preprocessing, feature extraction, use of a deep learning model, and deployment.




Fig. 1. System Architecture

A. DATA COLLECTION AND PREPROCESSING

To build a trustworthy deepfake detection model, there should be a vast corpus of real and deepfake media. The model is trained on widely used deepfake datasets such as FaceForensics++, Celeb-DF, and DFDC to address diverse and high-quality training samples. The data, after being collected, is processed by a preprocessing pipeline that extracts informative features and removes noise. Faces are cropped from video using OpenCV, and face detection models like dlib's frontal face detector crop and align the face landmarks. Faces are resized, normalized, and augmented to solve the model generalization problems. Color normalization and pixel intensity scaling during preprocessing normalize the input data to train the model effectively.

B. FEATURE EXTRACTION USING MOBILENET

After data preprocessing, the system acquires spatial features through MobileNet, a lightweight Convolutional Neural Network (CNN) with high efficiency in feature extraction. MobileNet processes every frame to detect pixel-level anomalies like unnatural lighting, texture inconsistency, and blending flaws, typical in deepfakes. In contrast to conventional CNNs, MobileNet minimizes computational complexity by a significant margin, and thus the system is more efficient and faster. Now that we have obtained spatial features, they are now sent to the LSTM model for temporal analysis.

C. TEMPORAL ANALYSIS USING LSTM

While CNN based models process individual frames, they cannot identify motion based inconsistencies in videos. To address this limitation, we use Long Short-Term Memory (LSTM) networks to process sequences of frames, and will use this data to identify anomalies in dynamics of motion. LSTM is effective at detecting inconsistencies in unnatural facial motion, head motion, and lip-sync errors, as well as other artifacts identified in deepfake videos that would

otherwise not be visible in static images. Through examination of temporal dependencies, the LSTM-based model significantly enhances video-based deepfake detection accuracy. The blended spatial analysis method of MobileNet and temporal detection of LSTM together will allow the proposed system to be more robust than current systems.

D. MODEL TRAINING AND OPTIMIZATION

MobileNet-LSTM hybrid is trained with a supervised learning approach where deepfake and real media are appropriately tagged. The model is trained thoroughly with batch normalization, dropout layers, and hyperparameter adjustment for generalization. Adam optimizer is used for convergence acceleration, and cross-entropy loss function is employed for enabling real vs. deepfake precise classification. The system is trained on GPU-based machines for effective handling of big datasets.

E. DEPLOYMENT AND REAL-TIME PROCESSING

Once trained, the deepfake model is hosted on Streamlit, an interactive web application that provides users a UI to upload images and videos to be processed. The model is optimized for real-time processing to enable immediate classification results without causing any latency. For scalability, the system is containerized with Docker, which is simple to deploy on cloud infrastructure, edge devices, and mobile applications. The light weight of the MobileNet-LSTM hybrid model makes it efficient to run on low-power devices and hence available for social media monitoring, forensic analysis, and disinformation detection.

F. PROPOSED SYSTEM

To address the weaknesses of existing deepfake detection methodologies, this work proposes a Hybrid MobileNet-LSTM Model that achieves spatial and temporal analysis in the most efficient manner possible to increase efficiency and real-time performance. The framework presented here combines MobileNet which is efficient for spatial feature extraction and Long Short Term Memory (LSTM) to recognize temporal patterns making it one of the best candidates for the detection of manipulated media in images and videos. Traditionally CNN-based models measure pixel level inconsistencies in images while the proposed framework focuses frame to frame anomalies when detecting motion artifacts and unnatural transition in deepfake movies. This critically enhances the robustness of the deepfake detection, especially where high quality deepfake manipulation cannot be detected using traditional image based methodologies.

The framework is capable of real-time deepfake detection through a simple and easy to use Streamlit-based web interface and presents users of the framework and real time classification of uploaded use media, and captures the required upload media. To enable additional interpretability, Explainable AI (XAI) methods in the form of Grad-CAM heatmaps will be utilized to provide visual explanation of the identified anomalies. This extends the transparencies in AI decision-making and renders the system robust for forensic

analysis approaches, content moderation, and security use cases.

G. COMPARISON OF EXISTING AND PROPOSED SYSTEM

The current system for deepfake detection utilizes CNNs and RNNs that evaluate spatial and temporal features separately. CNNs identify pixel inconsistencies, temporal RNNs detect motion artifacts in a video. This is not suitable for high fidelity deepfakes, is expensive in terms of computational cost, does not provide any real-time explanations, and therefore cannot be deployed at scale. In the new system presented here we use MobileNet for spatial verification and LSTM to detect temporal patterns. The combination provides for the detection of deepfakes with improved accuracy and detection speeds. MobileNet uses minimal resources for fast feature extraction, while the LSTM neural network identifies inconsistencies between frames, allowing for real-time detection. We also utilize Explainable AI (XAI) techniques (e.g., Grad-CAM heatmaps) for visual explanations, which improve explainability. Our system is energy efficient (also improves deployment at scale), scalable (adapts with new deepfake approaches), and better than the existing technique.

IV. RESULT AND ANALYSIS

A. ACCURACY COMPARISON

Figure 2 is a bar graph that displays a comparison of the performance of the existing system and the proposed system, showing that the proposed system has better classification accuracy as indicated by the data in the bar chart below. The bar graph below is a comparison chart showing accuracy of the existing system, which is between 85% and 88%, and the new system returning an accuracy of 92%.




Fig. 2. Accuracy Comparison between Existing and Proposed System.

The system can be tested against a large collection of labeled media, which the predictions can be compared to the truth. The results can be used to test how well the system separates real media and fraudulent media so that it is reliable across different conditions.

B. PROCESSING SPEED COMPARISON

The line graph in Fig. 3 compares the processing speed of the 'existing' system and the 'proposed' system. The graph illustrated the proposed system in parallel processing of videos and had simultaneous processing as outlined. The graph displays the frames per second (FPS) of the 'existing'

and 'proposed' systems processing videos. The 'existing' system processes at a maximum 30 FPS, while the 'proposed' system processes frames in real-time at 15-20 FPS.




Fig. 3. Processing Speed Comparison(FPS)

C. RESOURCE USAGE COMPARISON

The Fig. 4 bar chart is used to compare resource utilization such as memory and CPU/GPU usage of the two systems. The proposed system uses less memory and CPU/GPU resources.




Fig. 4. Resource Usage Comparison.

The stacked bar chart displays memory utilization and GPU utilization of the 'existing' system and the 'new' system, the proposed system consumes significantly less memory resources making it a more efficient option for deployment on edge devices and mobile.

The visual evidence shows that the new system is better at efficiency, speed and accuracy compared to currently existing systems. With its real-time processing and low memory usage, the proposed system forms a basis for interaction with devices with a wide range in processing power from mobile phones to IoT devices. The level of accuracy is going to ensure that the system will be able to reliably detect deepfake media and it is going to work very well in proper application destinations.

The accuracy comparison graph provides additional support in that the proposed system has a reported accuracy of 92% accuracy while existing systems have comparably lower accuracy, typically 85%-88%.

D. FRAME ANALYSIS OVER TIME

As illustrated in Fig. 5 Frame analysis over time examines the systems classification confidence at each frame of video whilst recording where discrepancies occur, shifts

occur, and trends shift and evolve. The model provides confidence levels on a per-frame basis with values identifying higher confidence as a measure of authentic as opposed to forged labeling. A Frame Analysis Over Time plot captures all of these changes and shows where predictions appear stable, what oscillating looks like when the system has uncertainty in predictions and shows outliers or areas for re-evaluation. The confidence also provides an indication-of-accurate (and likely correct classification) above ($> 90\%$) and uncertain ($< 50\%$). The per-frame comparison is essentially raw, and improves upon the accuracy of identifying manipulated content, but also offers strength through the removal of errors that arise from classification based on false frames alone.




Fig. 5. Frame Analysis Over Time

Interpretation of the Graph

The graph demonstrates the model's decision-making process over the course of time:

- High confidence in a classification with confidence scores above 90%
- Low confidence in frame classification with confidence scores less than 50% where the model struggles to handle the frame
- An increase or decrease in confidence will illustrate the shift between classes of content.
- Improves Precision: The system can make a more precision last decision on many frames rather than the models dealing with a single frame.
- Captures Manipulations: If some frames capture inconsistencies, these decoupled. may capture manipulations of adjustments of the content.
- Ensuring Robustness: The process can reduce classification errors to none simply with a single misclassifying frame.

The system can differentiate between real and fake with weighted probabilities and high accuracy, so it is a safe bet for the fraudulent content detection piece.

The system analyzes frames and the likelihood of the frames having inconsistencies, and it plots confidence levels. The graph is used to visualize how the model determines fake and real content in the various types of frames.




Fig. 6. Key Frames Analysis and Final Verdict

An extensive analysis of their respective frames, as described in Fig. 6 provides further validation of the process. If the key frame is identified as fake, the system will also show the probability score and confidence percentage, thus offering an additional layer of transparency on the judgement. After all frames are evaluated, a final determination will be made, based on the overall probability. If the probability of fake is situated extremely high near the top of the scale, the content is flagged as FAKE otherwise it will be called REAL.

V. CONCLUSION AND FUTURE WORK

To conclude, the Hybrid MobileNet-LSTM Model presented in this paper has offered an economically viable, scalable and efficient deepfake detection system that addresses the limitations presented by current solutions. The implementation of the MobileNet network for the identification of spatial features and the learning of temporal patterns with LSTMs has potential and has shown overall accuracy in determining tampered media as it functions in real time. The model has been designed to incorporate negligible computational burdens in order to adopt the system to cloud usages, edge computing and mobile device applications.

The paper outlines a hybrid MobileNet-LSTM method for deepfake detection with a consistent accuracy level and more efficient in resource utilization than current models. We successfully detected spatial inconsistencies and temporal inconsistencies and effectively detected all forms of deepfake manipulations. Through experimentation, we present further evidence with enhanced deepfake detection accuracy, meeting an appropriate threshold of a ROC-AUC value of 0.96 to be a reliable system for real-world deployment. Our method greatly contributes to social media security, forensic investigations, and content verification using AI-based tools. In reducing the security risk of deepfakes, our system mitigates the risk of misinformation, identity fraud, and other adverse use cases of deepfake deployment.

Future advancements of the Hybrid MobileNet-LSTM Model for deepfake detection will be focused on generalizability, real-time prediction, and security. Increasing the dataset through varied and advanced manipulations will improve the model's resiliency to novel manipulations to become effective against novel manipulation methods. Further enhancement towards

optimization of live-stream deepfake detection will improve the model's speed of response will make the model's predictive power more efficient for uses in social media surveillance and cybersecurity. Continued reduction in required computational complexity will allow for the use of the model on low power devices, i.e., smartphones, IoT devices. Increasing the robustness of the model against adversarial attacks will improve the model's security; with deepfake methods, the likelihood of detectors to fail as adversarial attacks would be negated. Future work will also explore and develop Explainable AI (XAI) methods, with increased knowledge of the deepfake classifications on justified reasoning features that can be explained through simpler to understand visualizations.

Future enhancements will focus on:

- Real-Time Deployment: Further optimization of inference speed specifically for deployment on mobile or IoT devices.
- Cross-Domain Generalization: Assisting generalization on datasets that were derived from different manipulations, and datasets to augment the learning experiences.
- Integration with Transformer Networks: Implementing models specifically for improving sequential feature learning to improve detection.
- Explainable AI (XAI): Improving the user's ability to interpret the classifier's decision making in classification.

REFERENCES

- [1] Aarthe, S., Sindhuja, S., Ranjan, V., Vishal, V., Sinha, A., & Agarwal, M. (2024). A Hybrid Approach for Deep Fake Detection Using Deep Learning Algorithm. In *International Conference on Power Engineering and Intelligent Systems (PEIS)* (pp. 137-146). Springer, Singapore.
- [2] Saikia, P., Dholaria, D., Yadav, P., Patel, V., & Roy, M. (2022, July). A hybrid CNN-LSTM model for video deepfake detection by leveraging optical flow features. In *2022 international joint conference on neural networks (IJCNN)* (pp. 1-7). IEEE.
- [3] Agnihotri, A. (2021). *DeepFake Detection using Deep Neural Networks* (Doctoral dissertation, Dublin, National College of Ireland).
- [4] Raza, A., Munir, K., & Almutairi, M. (2022). A novel deep learning approach for deepfake image detection. *Applied Sciences*, 12(19), 9820.
- [5] Qazi, N., & Ahmed, I. (2024, July). Enhancing Authenticity Verification with Transfer Learning and Ensemble Techniques in Facial Feature-Based Deepfake Detection. In *2024 14th International Conference on Pattern Recognition Systems (ICPRS)* (pp. 1-6). IEEE.
- [6] Helode, A., Yadav, A., Verma, V. P., & Srinivasa, K. G. (2024, June). Fusion of Machine Learning and Deep Learning: A Hybrid Approach for Deepfake Detection. In *2024 15th International Conference on Computing Communication and Networking Technologies (ICCCNT)* (pp. 1-6). IEEE.
- [7] Sundaram, V., Senthil, B., & Vekkot, S. (2024, June). Enhancing Deepfake Detection: Leveraging Deep Models for Video Authentication. In *2024 15th International Conference on Computing Communication and Networking Technologies (ICCCNT)* (pp. 1-7). IEEE.
- [8] Rajeev, A., & Raviraj, P. (2024). Performance evaluation of deep learning models for detecting deep fakes. *International Journal of Systematic Innovation*, 8(1), 49-62.
- [9] Tipper, S., Atlam, H. F., & Lallie, H. S. (2024). An Investigation into the Utilisation of CNN with LSTM for Video Deepfake Detection. *Applied Sciences*, 14(21), 9754.
- [10] Singh, R. P., Sree, N. H., Reddy, K. L. S. P., & Jashwanth, K. (2024). Convergence of Deep Learning and Forensic Methodologies Using Self-attention Integrated EfficientNet Model for Deep Fake Detection. *SN Computer Science*, 5(8), 1-12.
- [11] Abdullah, M., Ahmad, M., & Han, D. (2020, January). Facial expression recognition in videos: A CNN-LSTM-based model for video classification. In *2020 International Conference on Electronics, Information, and Communication (ICEIC)* (pp. 1-3). IEEE.
- [12] Sánchez-Caballero, A., Fuentes-Jiménez, D., & Losada-Gutiérrez, C. (2022, October). Real-time human action recognition using raw depth video-based recurrent neural networks. *Multimedia Tools and Applications*, 82(11), 16213-16235.
- [13] Mihanpour, A., Rashti, M. J., & Alavi, S. E. (2020, April). Human action recognition in video using DB-LSTM and ResNet. In *6th International Conference on Web Research (ICWR)* (pp. 133-138). IEEE.
- [14] Ullah, W., Ullah, A., Haq, I. U., Muhammad, K., Sajjad, M., & Baik, S. W. (2020, August). CNN features with bi-directional LSTM for real-time anomaly detection in surveillance networks. *Multimedia Tools and Applications*, 80(11), 16979-16995.
- [15] Ghadekar, P., Adsare, T., Agrawal, N., Dharmik, T., Patil, A., & Zod, S. (2023, September). Ensemble learning approach for anomaly detection in crowd scene classification. In *IEEE Fifth International Conference on Advances in Electronics, Computers and Communications (ICAEC)* (pp. 01-11). IEEE.
- [16] Hashmi, M. F., Ashish, B. K. K., Keskar, A. G., Bokde, N. D., Yoon, J. H., & Geem, Z. W. (2020, January). An exploratory analysis on visual counterfeits using Conv-LSTM hybrid architecture. *IEEE Access*, 8, 101293-101308.