


Inline v/s Block

Block elements :-

- Takes up full width available (full block)
- Start from new line



Inline elements :-

- Takes up only necessary width
- Don't start from new line.

- Heading element → Block
- paragraph element → Block
- Anchor tag → Inline
- Image element → Inline



Div Element

- Div is a container used to hold other HTML elements or group elements together.
- It is a block element.

Without div

```
< body >
  < a href = " www.google.com " > Google < / a >
  < a href = " www.youtube.com " > Youtube < / a >
  < a href = " www.facebook.com " > Facebook < / a >
< / body >
```

output: Google Youtube Facebook

with div

```
< body >
  < div >
    < a href = " www.google.com " > Google < / a >
    < a href = " www.youtube.com " > Youtube < / a >
  < / div >
  < a href = " www.facebook.com " > Facebook < / a >
< / body >
```

output: Google Youtube
Facebook

Span Element

- generic container used to hold other HTML elements
- inline element.

with span:

```
< body >
  < span >
    < a href = " www.google.com " > Google < /a >
    < a href = " www.youtube.com " > Youtube < /a >
  < /span >
    < a href = " www.facebook.com " > Facebook < /a >
< /body >
```

output:

Google Youtube

Facebook

Hr Tag

→ Horizontal Rule element

< Br > line break

< Hr > divider

Sub & Sup tag

sub → subscript

sup → superscript

H_2 → H ₂

a^2 → a ²

Semantic Markup

It is the markup that relates to meaning of content

Semantic

`<h1>`
`<p>`
`<img>`

non-semantic

`<div>`
`<span>`

- (1) more meaningful
- (2) structured layout
- (3) SEO (Search engine optimisation) friendly
- (4) ↑ readability
- (5) better screen reading.

Semantic tags

(1) Header :- `<header> </header>`

(2) Main :- display main content of a page

`<main> </main>`

(3) footer :- info at the bottom.
ex:- contact, address

* heart :- & hearts;

`<footer> </footer>`

* Usually one website contains one header, main, and footer.
Multiple Semantic tags are not used in a single page.

(4) Nav :- for navigation to other web pages

`<nav> </nav>`

* usually done inside the header tag.

`<header> I'm XYZ`

`<nav>`

`<ul>`

`<li> About us </li>`

`<li> Contact us </li>`

`</ul>`

`</nav>`

`</header>`

(5) Article :-

`<article></article>`

(6) Section :-

Group together similar content

• like div / Span

`<section></section>`

(7) Aside :

Indirectly related links / content

`<aside></aside>`

HTML Entities

- "String" starts with (&)
ends with (;)
- Displays reserved characters and invisible characters
- Used in place of characters, that are difficult to type in keyboard.
- Browser interprets and renders them correctly.

Ex :

space	 	(non breaking space)
<	<	
>	>	
♥	♥	
&	&	
"	"	

Emmet

- emmet.io

! → boiler plate code
└, emmet abbreviation

parent child relⁿ : nav > ul > li



```
<nav>
  <ul>
    <li></li>
  </ul>
</nav>
```

- Refer emmet cheatsheet

HTML 5 → HTML living standard + JavaScript APIs (enhanced storage, multimedia and hardware access)

HTML standard (living standard)

→ doc. that tells browser how HTML should work