

Extending Layer-wise Relevance Propagation using Semiring Annotations

Antoine Groudiev

L3, DI, ENS

Silviu Maniu

Slide Team, LIG, UGA

29th July 2024

Abstract

Recently, neural networks allowed computers to solve numerous problems from diverse machine learning fields, such as natural language processing and computer vision. Compared to traditional algorithms, machine learning models have proven both more successful and more difficult to interpret. Neural networks are considered as black boxes unable to easily explain themselves, that is justifying the reasons that led them to make a prediction. Layer-wise Relevance Propagation (LRP) is a technique that has been introduced to provide explainability by identifying the input features relevant to the output choice. In parallel, research in the databases field developed annotations techniques to compute provenance for queries. In this paper, we extend LRP propagation rules to semiring-based provenance annotations of the network, and implement semiring-based propagation rules for computer vision models of different scales.

1 Introduction

1.1 Problem statement

Deep neural networks have proven successful for solving with high accuracy machine learning problems. The expressivity of the class of functions generated by neural networks, combined with the relative simplicity of their training, make such models versatile tools to learn the relationship between the inputs and outputs of a dataset.

However, this versatility comes at the cost of poor interpretability: a neural network simply represents a function from one high-dimensional space to another, but provides no justification nor explanation for a given execution. If metrics such as the accuracy over a testing set provide confidence in the fact that the model is able to correctly classify inputs similar to the training set, no guarantee is given that the model generalizes well. Real-world examples show that networks can overfit the input data, or even take shortcuts instead of learning the intended solution [3]. For the user to have confidence in its predictions, a neural network should therefore be able to highlight the patterns in the input data that it actually learned.

1.2 Layer-wise Relevance Propagation

Layer-wise Relevance Propagation (LRP) [1] has been introduced as a technique to explain an execution of a neural network. LRP is a procedure propagating the output of the function backward in the network, using diverse rules to compute the *relevance* of a neuron depending on the relevances of the neurons of the upstream layer. LRP introduces the notion of *relevance score* for a neuron, intuitively quantifying the contribution of this neuron to the classification of final classification. A high relevance score indicates that the neuron led to the activation of the

considered output; a negative relevance score represents neurons that increased the activation of another output neuron instead of the one considered.

1.2.1 Setup and notations

In the following, we consider a deep neural network used for a classification task. We assume that it uses the rectifier activation function¹, which is the case in most applications. To ease the notation, we will not consider biases but instead assume that the first neuron of each layer represents the bias.

Let L be the number of layers of the network, including the input and output layers. We denote by $(a_k^{(l)})_k$ the activations of the network. Notably, $(a_k^{(1)})_k$ is the input data, and $(a_k^{(L)})_k$ is the output prediction. We denote by $(w_{j,k}^{(l)})_{j,k}$ the weights connecting the l -th layer to the $(l+1)$ -th layer. To simulate the biases using only weight matrices, we set:

$$\forall l \in \llbracket 1, L \rrbracket, \quad a_0^{(l)} = 1$$

and we define $w_{0,k}^{(l)}$ to be the bias of the k -th neuron of the $(l+1)$ -th layer. The forward propagation rule of a deep rectifier network is therefore:

$$\forall l \in \llbracket 1, L-1 \rrbracket, \forall k, \quad a_k^{(l+1)} = \text{ReLU} \left(\sum_{j=0} a_j^{(l)} w_{j,k}^{(l)} \right) = \max \left(0, \sum_{j=0} a_j^{(l)} w_{j,k}^{(l)} \right) \quad (1.2.1)$$

We denote by $R_j^{(l)}$ the relevance of the j -th neuron of the l -th layer. We assume that the output layer represents a one-hot encoding, that is that the belonging of the input to the i -th class is represented by an output vector is of the form $(0, \dots, a_i^{(L)}, \dots, 0)$, where the only non-null coefficient is in the i -th position. Finally, we denote by y the label of a classified input. To the label $y = i$ is associated the output vector $(0, \dots, a_i^{(L)}, \dots, 0)$.

1.2.2 Propagation rules

Relevance scores are initialized for the output layer, and are set to the output activation for the correct class, that is:

$$R_i^{(L)} = \begin{cases} a_i^{(L)} & \text{if } i = y \\ 0 & \text{otherwise} \end{cases} \quad (1.2.2)$$

The simplest LRP rule is called LRP-0. It propagates the relevance to a neuron of the lower layer proportionnaly to its contribution to each of the neuron of the next layer:

$$R_j^{(l)} = \sum_k \frac{a_j^{(l)} w_{j,k}^{(l)}}{\sum_{j'} a_{j'}^{(l)} w_{j',k}^{(l)}} R_k^{(l+1)} \quad (1.2.3)$$

The denominator $\sum_{j'} a_{j'}^{(l)} w_{j',k}^{(l)}$ guarantees a conservation property, that is that for any layer l :

$$\sum_j R_j^{(l)} = \sum_k R_k^{(l+1)}$$

This allows to keep the information regarding the total activation of the final layer.

¹That is $\text{ReLU}(x) = \max(0, x)$, where ReLU stands for *Rectified Linear Unit*.

The application of this simple rule can lead into noisy results that do not scale well. An overview of variations of LRP-0 is provided by [6]; not all rules are suitable for all layers. Complex deep neural networks architectures benefit from enhanced rules such as LRP- ε or LRP- γ , which provide more stable explanations.

Notably, the input layer must be handled using a different rule, since it does not receive its input from ReLU activations, but directly from the input data. The z^B rule is used in [6] to propagate from layer 2 to 1 (input layer):

$$R_j^{(1)} = \sum_k \frac{x_k w_{j,k} - l_j w_{j,k}^+ - h_j w_{j,k}^-}{\sum_{j'} x_k w_{j',k} - l_j w_{j',k}^+ - h_j w_{j',k}^-} R_k^{(2)} \quad (1.2.4)$$

where $(\cdot)^+ = \max(0, \cdot)$, $(\cdot)^- = \min(0, \cdot)$. The parameters l_i and h_i respectively define the theoretical minimum and maximum values of the inputs x_i . For instance, we might have $l_i = 0$ and $h_i = 255$ for pixels over 8 bits.

1.2.3 LRP results and pertinence

Previous works ([1], [6]), as well as the methods that we will introduce later on, were experimentally tested on models trained over two datasets: fully-connected networks trained on the MNIST handwritten digits dataset [5], and deep convolutional networks pre-trained on the ImageNet visual database such as VGG-16 [10].

Figure 1.1 shows relevance for a simple model: a fully-connected deep rectifier network with layers of sizes 28×28 , 300, 100 and 10, trained on the MNIST dataset. Pixels highlighted in red have a positive relevance while blue pixels have a negative relevance. As expected, the relevant pixels to classify this image as a 0 are the white pixels in the input image.




Figure 1.1: Input image and pixel-wise explanation of the output neuron 0

Figure 1.2 provides a visualization for a more complex example, an execution of the VGG-16 network over a 224×224 image.



Figure 1.2: Input image and relevance for the class "castle" of the VGG-16 network

Note that the castle part of the image is highlighted in red as intended. Furthermore, both the street sign and the street light have strong negative relevance; those two objects correspond to other classes of the ImageNet dataset (**street sign** (919) and **traffic light** (920)). Those two elements of the image would have positive relevance for LRP starting from the output neurons 919 and 920.

1.3 Semiring-based provenance annotations

In parallel, the notion of data provenance in databases theory developed formal solutions to a similar problem to ours. Data provenance aims at *explaining* a query by highlighting the tuples in the original database that led to the presence of a certain tuple in the query result. If contexts are different, deep neural networks explanation and data provenance share the same general setup: identifying a subset of the input that directly implied a certain output.

A framework to approach data provenance is *provenance semirings*, introduced in [4], annotates tuples using abstract elements of a semiring and apply semiring operations to the tuples appearing in the query. As the query is executed, information about the provenance of the intermediate results is aggregated, resulting in an abstract formula that can be concretized by substituting abstract elements and operations by a concrete semiring. Similarly, in the context of graph databases, edges can be annotated to derive a variety of properties of the query result. [7]

In the following, we provide a mathematical definition of a semiring as well as semiring examples suited for the application to deep neural networks.

Definition (Semiring). A *semiring* is an algebraic structure generalizing the notion of rings. A semiring $(\mathbb{K}, \oplus, \otimes, 0, 1)$ is composed of a set \mathbb{K} , binary operators \oplus and \otimes such that \otimes distributes over \oplus , verifying the following properties:

- $(\mathbb{K}, \oplus, 0)$ is a commutative monoid
- $(\mathbb{K}, \otimes, 1)$ is a monoid such that 0 is absorbing

Example. $(\mathbb{R}, +, \times, 0, 1)$ is a semiring. While it has no direct interpretation in the context of databases, we will see that it corresponds to the basic real-valued LRP.

Example (Boolean semiring). $(\{\perp, \top\}, \vee, \wedge, \perp, \top)$ is a semiring. Its use in databases provenance interprets as the existence of a path between two vertices, using edge weights as the number of different paths between two adjacent vertices.

Example (Counting semiring). $(\mathbb{N}, +, \times, 0, 1)$ is a semiring. For a non-cyclic graph database, its use allows to compute the total number of paths between two vertices, using edge weights as the number of different paths between two adjacent vertices.

Example (Viertbi semiring). $([0, 1], \max, \times, 0, 1)$ is a semiring. For a non-cyclic graph database where the annotations are interpreted as a “confidence” measure, its use allows to compute the confidence score of the result of a query.

2 Extending LRP using Semiring Annotations

We aim at extending Layer-wise Relevance Propagation by annotating the computational graph of a neural network with semiring elements.

2.1 Semiring generalization of the LRP rules

LRP rules all inherit the same structure, in which the relevance of a pixel can be expressed as the weighted sum of the relevance of pixels of the next layer:

$$R_j^{(l)} = \sum_k d_{j,k}^{(l)} \cdot R_k^{(l+1)} \quad (2.1.1)$$

where the $d_{j,k}^{(l)}$ are some coefficients proportional to the extent to which neuron j of the l -th layer has contributed to make neuron k of the $(l+1)$ -th layer relevant.

Equation 2.1.1 is the special real-valued case of a more general rule. Let $(\mathbb{K}, \oplus, \otimes, 0, 1)$ be a semiring, and $(\Theta^{(l)})_l$ be conversion functions of the form $\mathbb{R} \rightarrow \mathbb{K}$. We call \mathbb{K} -relevance for output neuron y the quantity $R \in \mathbb{K}$ inductively defined by:

$$R_i^{(L)} = \begin{cases} 1 & \text{if } i = y \\ 0 & \text{otherwise} \end{cases} \quad (2.1.2)$$

and

$$R_j^{(l)} = \bigoplus_k \Theta^{(l)}(d_{j,k}) \otimes R_k^{(l+1)} \quad (2.1.3)$$

Note that choosing $(\mathbb{R}, +, \times, 0, 1)$ as a semiring and $\Theta^{(l)} = x \mapsto x$ retrieves classical LRP up to a multiplicative factor of $a_i^{(L)}$ on each layer (which does not appear on the semiring initialization).

Equations 2.1.2 and 2.1.3 can be intuitively interpreted in two ways. Firstly, they can be seen as the abstraction of an LRP computation using formal semiring elements. Computing \mathbb{K} -relevance for an execution of the network results in an abstract formula in terms of elements of \mathbb{K} and operations \oplus and \otimes . While this might be useful in the context of graph provenance, visualizing abstract formulas is difficult because of the size of computational graphs associated to neural networks. Furthermore, the general structure of the formulas is always the same for a specific model, since neural networks usually have very simple computational graphs structures.

Therefore, a second approach that fits the graph properties of neural networks is to interpret semiring LRP as operations on an annotated circuit, similarly to [8]. For instance, in the case of the boolean semiring, computing $\{\perp, \top\}$ -relevance consists in taking for each node the logical conjunction of the annotations of its outgoing edges.

2.2 Results over the MNIST dataset

2.2.1 Boolean Semiring




Figure 2.1: Input image and $\{\perp, \top\}$ -relevance for the output neuron 0

2.2.2 Counting Semiring




Figure 2.2: Input image and \mathbb{N} -relevance for the output neuron 0

2.2.3 Viterbi Semiring




Figure 2.3: Input image and $[0, 1]$ -relevance for the output neuron 0

3 Handling of convolutional neural networks

3.1 Computing relevance for convolutional layers

3.1.1 Forward pass

3.1.2 Gradient expression of LRP

Classical LRP rules can be easily and efficiently implemented. A general rule encapsulating LRP-0/ ε/γ can be written as:

$$R_j^{(l)} = \sum_k \frac{a_j \cdot \rho(w_{j,k})}{\varepsilon + \sum_{j'} a_{j'} \cdot \rho(w_{j',k})} \cdot R_k^{(l+1)} \quad (3.1.1)$$

where $a = a^{(l)}$, $w = w^{(l)}$. Four steps, described in [6], allow for an efficient and effortless computation of relevance:

$$\begin{aligned} \forall k : z_k &= \varepsilon + \sum_{j'} a_{j'} \cdot \rho(w_{j',k}) \\ \forall k : s_k &= R_k / z_k \\ \forall j : c_j &= \sum_k \rho(w_{j,k}) \cdot s_k \\ \forall j : R_j &= a_j \cdot c_j \end{aligned} \quad (3.1.2)$$

These steps provide two majors benefits. Firstly, it allows for the costly divisions by z_k to be performed only once per k , independently of j . Secondly, the third step can be expressed as the computation of a gradient:

$$c_j = \left[\nabla \left(\sum_k z_k (a^{(l)}) \cdot s_k \right) \right]_j \quad (3.1.3)$$

where the gradient ∇ is taken with respect to the vector $a^{(l)}$ and where the s_k are treated as constants. This allows for a simple and efficient implementation, since the gradient can be computed using automatic differentiation: the high-level code is not only concise (two lines of PyTorch code), but also effortlessly generalizable to any layer implementing backward pass, and highly optimized using GPU operations.

3.1.3 Implementing LRP without automatic differentiation

3.2 Results for the VGG-16 network

3.3 Thresholds choice

4 Applications

4.1 Image mask computation




Figure 4.1: Class-wise mask for $\{\perp, \top\}$ -relevance of the class 0



Figure 4.2: All classes mask for $\{\perp, \top\}$ -relevance




Figure 4.3: Class-wise mask for N-relevance of the class 0



Figure 4.4: All classes mask for N-relevance

4.2 Network pruning using LRP ranking




Figure 4.5: Accuracy and loss evolution during network pruning for different neuron selection methods

4.3 Comparison to image perturbation

References

- [1] Sebastian Bach et al. ‘On Pixel-Wise Explanations for Non-Linear Classifier Decisions by Layer-Wise Relevance Propagation’. In: *PLOS ONE* (2015), pp. 1–46. URL: <https://doi.org/10.1371/journal.pone.0130140>.
- [2] Ruth C Fong and Andrea Vedaldi. ‘Interpretable explanations of black boxes by meaningful perturbation’. In: *Proceedings of the IEEE international conference on computer vision*. 2017, pp. 3429–3437. URL: <https://arxiv.org/abs/1704.03296>.
- [3] Robert Geirhos et al. ‘Shortcut learning in deep neural networks’. In: *Nature Machine Intelligence* 2 (2020), pp. 665–673. URL: <https://arxiv.org/abs/2004.07780>.
- [4] Todd J Green, Grigoris Karvounarakis and Val Tannen. ‘Provenance semirings’. In: *Proceedings of the twenty-sixth ACM SIGMOD-SIGACT-SIGART symposium on Principles of database systems*. 2007, pp. 31–40.
- [5] Yann LeCun. *The MNIST database of handwritten digits*. 1998. URL: <http://yann.lecun.com/exdb/mnist/>.
- [6] Grégoire Montavon et al. ‘Layer-Wise Relevance Propagation: An Overview’. In: *Explainable AI: Interpreting, Explaining and Visualizing Deep Learning*. Springer International Publishing, 2019, pp. 193–209. URL: https://doi.org/10.1007/978-3-030-28954-6_10.
- [7] Yann Ramusat, Silviu Maniu and Pierre Senellart. ‘Provenance-Based Algorithms for Rich Queries over Graph Databases’. In: *EDBT 2021 - 24th International Conference on Extending Database Technology*. 2021. URL: <https://inria.hal.science/hal-03140067>.
- [8] Pierre Senellart. ‘Provenance and probabilities in relational databases’. In: *ACM SIGMOD Record* 46.4 (2018), pp. 5–15. URL: <https://inria.hal.science/hal-01672566>.
- [9] Pierre Senellart et al. ‘Provsql: Provenance and probability management in postgresql’. In: *Proceedings of the VLDB Endowment (PVLDB)* (2018). URL: <https://inria.hal.science/hal-01851538>.
- [10] Karen Simonyan and Andrew Zisserman. ‘Very Deep Convolutional Networks for Large-Scale Image Recognition’. In: (2015). eprint: 1409.1556. URL: <https://arxiv.org/abs/1409.1556>.