

AdventOfCTF-14

Challenge

6 Solves



14
1400

web

We are testing a new 2 factor security system for Santa's deepest secrets. It should be pretty secure!

Visit <https://14.adventofctf.com> to start the challenge.

Flag

Submit

Advent of CTF 14

Your daily dose of CTF for December

Login ()

```
<?php

ini_set('display_errors', 0);

include("flag.php");

if (isset($_POST["password"], $_POST["verifier"])) {
    $password = $_POST["password"];
    $verifier = $_POST["verifier"];

    $hash = sha1($password + $secret_salt);
    $reference = substr($hash, 0, 7);

    if ($verifier === $reference) {
        echo $flag;
        die();
    }
}

header("Location: /index.php?error=That was not right.");
exit();

?>
```

The code here is not very readable. I hosted the code myself on this website.

The collaborative browser based IDE

Repl.it is a simple yet powerful online IDE, Editor, Compiler, Interpreter, and REPL.

 <https://repl.it/>



This is my setup.

```
//get_flag.php
<?php

ini_set('display_errors', 0);

include("flag.php");

if (isset($_POST["password"], $_POST["verifier"])) {
    $password = $_POST["password"];
    $verifier = $_POST["verifier"];

    $hash = sha1($password + $secret_salt);
    echo "(".($password + $secret_salt)."<br>";
    $reference = substr($hash, 0, 7);
    echo "Reference ".$reference."<br>";
    echo "hash ".$hash."<br>";

    if ($verifier === $reference) {
        echo $flag;
        die();
    }
    die();
}

header("Location: /index.php?error=That was not right.");
exit();

?>
```

get_flag.php

```
1  <?php
2
3  ini_set('display_errors', 0);
4
5  include("flag.php");
6
7  if (isset($_POST["password"], $_POST["verifier"])) {
8      $password = $_POST["password"];
9      $verifier = $_POST["verifier"];
10
11      $hash = sha1($password + $secret_salt);
12      echo "" . ($password + $secret_salt) . "<br>";
13      $reference = substr($hash, 0, 7);
14      echo "Reference " . $reference . "<br>";
15      echo "hash " . $hash . "<br>";
16
17      if ($verifier === $reference) {
18          echo $flag;
19          die();
20      }
21      die();
22  }
23
24  header("Location: /index.php?error=That was not right.");
25  exit();
26
27  ?>
```

```
//flag.php
<?php
$secret_salt = 2;
$flag = "Here is the flag {....}";
?>
```

flag.php

```
1  <?php
2  $secret_salt = 2;
3  $flag = "Here is the flag {....}";
4  ?>
```

```
//index.php
<html>
<head>
```


INF
Reference 55c1943
hash 55c1943f65c7c105ae98e6703cd64127b6585656

So if we put the password to the big value and the verifier to 55c1943 we should get the flag.

[illegible]

INF
Reference 55c1943
hash 55c1943f65c7c105ae98e6703cd64127b6585656
Here is the flag {....}

Nice!

Now let's go back to the ctf website and set the password and verifier to those values.

10000000000000000000(

55c1943

Submit

And we get redirected to the flag page.

NOVI{typ3 juggl1ng f0r 11fe}

Flag: NOVI{typ3_juggl1ng_f0r_l1fe}

