

## EVALUATION SEMANTICS OF COERCION

JONATHAN STERLING

An idea for a *new* evaluation dynamics of coercion inspired by the denotational semantics of cubical type theory. The main idea is that coercions should *not* be evaluated in an ordinary environment, but instead an environment where each cell is a line.

$$\begin{aligned}
& \llbracket \Gamma \vdash A \rrbracket : \llbracket \Gamma \rrbracket \rightarrow \mathbf{Type} \\
& \llbracket \Gamma \vdash a : A \rrbracket : \prod_{\gamma : \llbracket \Gamma \rrbracket} \llbracket \Gamma \vdash A \rrbracket_{\gamma} \\
& \mathbf{coe} \llbracket \Gamma \vdash A \rrbracket : \prod_{\gamma : \llbracket \Gamma \rrbracket} \prod_{r, s : \mathbb{I}} \prod_{a : \llbracket \Gamma \vdash A \rrbracket_{\gamma(r)}} \llbracket \Gamma \vdash A \rrbracket_{\gamma(s)} \\
& \llbracket \Gamma \vdash \mathbf{coe}_F^{r \rightarrow s} M : F(r) \rrbracket_{\gamma} = \mathbf{coe} \llbracket \Gamma. \mathbb{I} \vdash F(i) \rrbracket_{\langle \mathbf{refl}(\gamma), \mathbf{id}_{\mathbb{I}} \rangle}^{\llbracket \Gamma \vdash r : \mathbb{I} \rrbracket_{\gamma} \rightarrow \llbracket \Gamma \vdash s : \mathbb{I} \rrbracket_{\gamma}} \llbracket \Gamma \vdash M : F(r) \rrbracket_{\gamma} \\
& \mathbf{coe} \llbracket \Gamma \vdash \Pi(A, B) \rrbracket_{\gamma}^{r \rightarrow s} f = \lambda a. \mathbf{coe} \llbracket \Gamma. A \vdash B \rrbracket_{\langle \gamma, \lambda i. \mathbf{coe} \llbracket \Gamma \vdash A \rrbracket_{\gamma}^{s \rightarrow i} a \rangle} \mathbf{coe} \llbracket \Gamma \vdash A \rrbracket_{\gamma}^{s \rightarrow r} a \\
& \mathbf{coe} \llbracket \Gamma \vdash V_i(A, B, E) \rrbracket_{\gamma}^{r \rightarrow s}(v) = \begin{cases} ?0 & \text{if } \forall j : \mathbb{I}, \llbracket \Gamma \vdash i : \mathbb{I} \rrbracket_{\gamma(j)} = j \\ ?1 & \text{otherwise} \end{cases}
\end{aligned}$$