



Induction for Gödel's System \mathbb{T} Definable Bars via Effectful Forcing

Jon Sterling

Carnegie Mellon University

July 8, 2016

Brouwer's Bar Thesis

“All covers (bars) on a spread can be coded as wellfounded trees.”

Brouwer's Bar Thesis

“All covers (bars) on a spread can be coded as wellfounded trees.”

★ \Rightarrow the **Fan Theorem** (intuitionistic König's Lemma)

Brouwer's Bar Thesis

“All covers (bars) on a spread can be coded as wellfounded trees.”

- ★ \Rightarrow the **Fan Theorem** (intuitionistic König's Lemma)
- ★ \Rightarrow all functions on the interval $\mathbb{I} \triangleq [0, 1]$ are **uniformly continuous**

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

A spread is defined by a predicate S on lists of natural numbers subject to some laws:

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

A spread is defined by a predicate S on lists of natural numbers subject to some laws:

1. If $\vec{u} \in S$, then there exists an $x \in \mathbb{N}$ such that $\vec{u} \frown x \in S$.

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

A spread is defined by a predicate S on lists of natural numbers subject to some laws:

1. If $\vec{u} \in S$, then there exists an $x \in \mathbb{N}$ such that $\vec{u} \frown x \in S$.
2. If $\vec{u} \frown x \in S$, then also $\vec{u} \in S$.

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

A spread is defined by a predicate S on lists of natural numbers subject to some laws:

1. If $\vec{u} \in S$, then there exists an $x \in \mathbb{N}$ such that $\vec{u} \frown x \in S$.
2. If $\vec{u} \frown x \in S$, then also $\vec{u} \in S$.
3. Finally, $\langle \rangle \in S$.

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

A spread is defined by a predicate S on lists of natural numbers subject to some laws:

1. If $\vec{u} \in S$, then there exists an $x \in \mathbb{N}$ such that $\vec{u} \frown x \in S$.
2. If $\vec{u} \frown x \in S$, then also $\vec{u} \in S$.
3. Finally, $\langle \rangle \in S$.

The predicate S either defines the finite prefixes of paths down an infinite tree, or it defines the lattice of open sets of a topological space.

Spreads as spaces and trees

A *spread* is at the same time a topological space and a non-wellfounded tree.

A spread is defined by a predicate S on lists of natural numbers subject to some laws:

1. If $\vec{u} \in S$, then there exists an $x \in \mathbb{N}$ such that $\vec{u} \frown x \in S$.
2. If $\vec{u} \frown x \in S$, then also $\vec{u} \in S$.
3. Finally, $\langle \rangle \in S$.

The predicate S either defines the finite prefixes of paths down an infinite tree, or it defines the lattice of open sets of a topological space.

Usually, we will work implicitly with the *universal spread*, which always says “yes”.

Neighborhoods and points

A list of naturals $\vec{u} \in \mathbb{N}^*$ can be thought of as a **neighborhood** around a point, or as a **prefix** of a path through an infinite tree.

Neighborhoods and points

A list of naturals $\vec{u} \in \mathbb{N}^*$ can be thought of as a **neighborhood** around a point, or as a **prefix** of a path through an infinite tree.

A stream of naturals $\alpha \in \mathbb{N}^{\mathbb{N}}$ can be thought of as an **ideal point** in the spread (space), or as a **path** through the spread's infinite tree.

Neighborhoods and points

A list of naturals $\vec{u} \in \mathbb{N}^*$ can be thought of as a **neighborhood** around a point, or as a **prefix** of a path through an infinite tree.


A stream of naturals $\alpha \in \mathbb{N}^{\mathbb{N}}$ can be thought of as an **ideal point** in the spread (space), or as a **path** through the spread's infinite tree.

$$\vec{u} \prec \alpha$$

(\vec{u} approximates α)

$$\alpha \in \vec{u}$$

(\vec{u} is a neighborhood around α)



Bars and Securability

A **bar** \bar{B} is a predicate on neighborhoods such that every point “hits it”.
More generally, \bar{B} **bars** a neighborhood \vec{u} when every path through \vec{u} ends up in \bar{B} .

Bars and Securability

A **bar** \vec{B} is a predicate on neighborhoods such that every point “hits it”.
More generally, \vec{B} **bars** a neighborhood \vec{u} when every path through \vec{u} ends up in \vec{B} .


$$\frac{\forall \alpha \in \vec{u}. \exists n \in \mathbb{N}. \bar{\alpha}[n] \in \vec{B}}{\vec{u} \triangleleft \vec{B}}$$


Bars and Securability

A **bar** \vec{B} is a predicate on neighborhoods such that every point “hits it”. More generally, \vec{B} **bars** a neighborhood \vec{u} when every path through \vec{u} ends up in \vec{B} .

$$\frac{\forall \alpha \in \vec{u}. \exists n \in \mathbb{N}. \bar{\alpha}[n] \in \vec{B}}{\vec{u} \triangleleft \vec{B}}$$

We say that a neighborhood is **secured** when it is in the bar ($\vec{u} \in \vec{B}$), and that it is **securable** when every path out of it eventually hits the bar ($\vec{u} \triangleleft \vec{B}$).





Inductive Securability

“All demonstrations of securability can be analyzed into **inductive mental constructions.**”

Inductive Securability

“All demonstrations of securability can be analyzed into **inductive mental constructions.**”

Let $S^{\sharp}(\vec{u}) \triangleq \{x \in \mathbb{N} \mid \vec{u} \frown x \in S\}$. Presupposing $\vec{u} \in S$ and B *monotone*:

Inductive Securability

“All demonstrations of securability can be analyzed into **inductive mental constructions.**”

Let $S^{\sharp}(\vec{u}) \triangleq \{x \in \mathbb{N} \mid \vec{u} \frown x \in S\}$. Presupposing $\vec{u} \in S$ and \mathbb{B} *monotone*:

$$\frac{\vec{u} \in \mathbb{B}}{\vec{u} \triangleleft_{ind} \mathbb{B}} \eta \qquad \frac{\forall x \in S^{\sharp}(\vec{u}). \vec{u} \frown x \triangleleft_{ind} \mathbb{B}}{\vec{u} \triangleleft_{ind} \mathbb{B}} F$$

Inductive Securability

“All demonstrations of securability can be analyzed into **inductive mental constructions.**”

Let $S^{\natural}(\vec{u}) \triangleq \{x \in \mathbb{N} \mid \vec{u} \smallfrown x \in S\}$. Presupposing $\vec{u} \in S$ and \mathbb{B} monotone:

$$\frac{\vec{u} \in \mathbb{B}}{\vec{u} \triangleleft_{ind} \mathbb{B}} \eta \qquad \frac{\forall x \in S^{\natural}(\vec{u}). \vec{u} \smallfrown x \triangleleft_{ind} \mathbb{B}}{\vec{u} \triangleleft_{ind} \mathbb{B}} F$$

Admissible (by monotonicity):

$$\frac{\vec{u} \triangleleft_{ind} \mathbb{B}}{\vec{u} \smallfrown x \triangleleft_{ind} \mathbb{B}} \zeta$$

Brouwer's Bar Thesis

Recall $\vec{u} \triangleleft \vec{v} \triangleq \forall \alpha \in \vec{u}. \exists n \in \mathbb{N}. \bar{\alpha}[n] \in \vec{v}$.

Brouwer's Bar Thesis

Recall $\vec{u} \triangleleft \vec{b} \triangleq \forall \alpha \in \vec{u}. \exists n \in \mathbb{N}. \bar{\alpha}[n] \in \vec{b}$.

Brouwer's Bar Thesis is the *adequacy* of the inductive coding of securability:

$$\frac{\vec{u} \triangleleft \vec{b}}{\vec{u} \triangleleft_{ind} \vec{b}} \text{ BT?}$$

Brouwer's Bar Thesis

Recall $\vec{u} \triangleleft \vec{b} \triangleq \forall \alpha \in \vec{u}. \exists n \in \mathbb{N}. \bar{\alpha}[n] \in \vec{b}$.

Brouwer's Bar Thesis is the *adequacy* of the inductive coding of securability:

$$\frac{\vec{u} \triangleleft_{ind} \vec{b}}{\vec{u} \triangleleft \vec{b}} \text{ soundness} \qquad \frac{\vec{u} \triangleleft \vec{b}}{\vec{u} \triangleleft_{ind} \vec{b}} \text{ completeness?}$$

Brouwer's Bar Thesis

$$\frac{\vec{u} \blacktriangleleft_{ind} \mathbb{B}}{\vec{u} \triangleleft \mathbb{B}} \text{ soundness} \qquad \frac{\vec{u} \triangleleft \mathbb{B}}{\vec{u} \blacktriangleleft_{ind} \mathbb{B}} \text{ completeness?}$$

Brouwer's Bar Thesis

$$\frac{\vec{u} \blacktriangleleft_{ind} \mathbb{B}}{\vec{u} \triangleleft \mathbb{B}} \text{ soundness} \qquad \frac{\vec{u} \triangleleft \mathbb{B}}{\vec{u} \blacktriangleleft_{ind} \mathbb{B}} \text{ completeness?}$$


★ **soundness** is easy! Just count up the F -nodes.

Brouwer's Bar Thesis

$$\frac{\vec{u} \triangleleft_{ind} \mathbb{B}}{\vec{u} \triangleleft \mathbb{B}} \text{ soundness} \qquad \frac{\vec{u} \triangleleft \mathbb{B}}{\vec{u} \triangleleft_{ind} \mathbb{B}} \text{ completeness?}$$

- ★ **soundness** is easy! Just count up the F -nodes.
- ★ **completeness** does not (generally) hold: procedure exists, but its termination requires Brouwer's Thesis!

Computability at Higher Type







vulgar mechanicalism vs. *phenomenology*



Computability at Higher Type

Brouwer's Bar Thesis expresses a *scientific* hypothesis about the nature of higher-type computation.



Computability at Higher Type

Brouwer's Bar Thesis expresses a *scientific* hypothesis about the nature of higher-type computation.

Church's Thesis

general recursive λ -calculus

Brouwer's Thesis

wellfounded mental construction + oracles

Computability at Higher Type

Brouwer's Bar Thesis expresses a *scientific* hypothesis about the nature of higher-type computation.

Church's Thesis

general recursive λ -calculus
Russian constructivism

Brouwer's Thesis

wellfounded mental construction + oracles
intuitionism

Computability at Higher Type

Brouwer's Bar Thesis expresses a *scientific* hypothesis about the nature of higher-type computation.

Church's Thesis

general recursive λ -calculus
Russian constructivism
vulgar/mechanicalist materialism

Brouwer's Thesis

wellfounded mental construction + oracles
intuitionism
subjective idealism

Computability at Higher Type

Brouwer's Bar Thesis expresses a *scientific* hypothesis about the nature of higher-type computation.

Church's Thesis

general recursive λ -calculus
Russian constructivism
vulgar/mechanicalist materialism
uniform continuity fails on \mathbb{I}

Brouwer's Thesis

wellfounded mental construction + oracles
intuitionism
subjective idealism
uniform continuity obtains

System \mathbb{T} as a theory of constructions

Gödel's **System \mathbb{T}** of primitive recursive functionals of finite type.

System \mathbb{T} as a theory of constructions

Gödel's **System \mathbb{T}** of primitive recursive functionals of finite type.

Atomic Types

nat *atype*

System \mathbb{T} as a theory of constructions

Gödel's **System \mathbb{T}** of primitive recursive functionals of finite type.

Atomic Types

$$\overline{\text{nat } \textit{atype}}$$

General Types

$$\frac{\textit{\textcolor{teal}{\iota}} \textit{atype}}{\textit{\textcolor{teal}{\iota}} \textit{type}} \qquad \frac{\sigma \textit{ type} \quad \tau \textit{ type}}{\sigma \rightarrow \tau \textit{ type}}$$

System \mathbb{T} as a theory of constructions

Gödel's **System \mathbb{T}** of primitive recursive functionals of finite type.

Atomic Types

$$\overline{\text{nat } \textit{atype}}$$

General Types

$$\frac{\textit{t atype}}{\textit{t type}} \qquad \frac{\sigma \textit{ type} \quad \tau \textit{ type}}{\sigma \rightarrow \tau \textit{ type}}$$

Contexts

$$\frac{}{\cdot \textit{ ctx}} \qquad \frac{\Gamma \textit{ ctx} \quad \sigma \textit{ type}}{\Gamma, x : \sigma \textit{ ctx}} \quad (x \notin \Gamma)$$

System T as a theory of constructions

$$\frac{}{\Gamma, x : \sigma, \Delta \vdash x : \sigma} \text{var}$$

System T as a theory of constructions

$$\frac{}{\Gamma, x : \sigma, \Delta \vdash x : \sigma} \text{ var}$$

$$\frac{}{\Gamma \vdash z : \text{nat}} \text{ zero} \qquad \frac{\Gamma \vdash m : \text{nat}}{\Gamma \vdash s(m) : \text{nat}} \text{ succ}$$

$$\frac{\Gamma, x : \text{nat}, y : \sigma \vdash s[x, y] : \sigma \quad \Gamma \vdash z : \sigma \quad \Gamma \vdash n : \text{nat}}{\Gamma \vdash \text{rec}_{\sigma}([x, y].s[x, y]; z; n) : \sigma} \text{ rec}$$

System \mathbb{T} as a theory of constructions

$$\frac{}{\Gamma, x : \sigma, \Delta \vdash x : \sigma} \text{ var}$$

$$\frac{}{\Gamma \vdash z : \text{nat}} \text{ zero} \qquad \frac{\Gamma \vdash m : \text{nat}}{\Gamma \vdash s(m) : \text{nat}} \text{ succ}$$

$$\frac{\Gamma, x : \text{nat}, y : \sigma \vdash s[x, y] : \sigma \quad \Gamma \vdash z : \sigma \quad \Gamma \vdash n : \text{nat}}{\Gamma \vdash \text{rec}_\sigma([x, y].s[x, y]; z; n) : \sigma} \text{ rec}$$

$$\frac{\Gamma, x : \sigma \vdash m[x] : \tau}{\Gamma \vdash \lambda x. m[x] : \sigma \rightarrow \tau} \text{ lam} \qquad \frac{\Gamma \vdash m : \sigma \rightarrow \tau \quad \Gamma \vdash n : \sigma}{\Gamma \vdash m \bullet_\sigma n : \tau} \text{ ap}$$

Realizability of barhood

- ★ Use **System T** as a theory of constructions for primitive recursive arithmetic

Realizability of barhood

- ★ Use **System T** as a theory of constructions for primitive recursive arithmetic
- ★ $\vec{u} \triangleleft \mathbb{B}$ should be realized by a functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}$

Realizability of barhood

- ★ Use **System T** as a theory of constructions for primitive recursive arithmetic
- ★ $\vec{u} \triangleleft \vec{b}$ should be realized by a functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}$
- ★ **Idea:** construct a model for **System T** in which we can read from the interpretation of ϕ a proof of $\vec{u} \triangleleft_{ind} \vec{b}$

Standard semantics of System \mathbb{T}

Standard semantics of System \mathbb{T}

Standard semantics of System T

Atomic Types

$$U[\text{nat}] \triangleq \mathbb{N}$$

Standard semantics of System T

Atomic Types

$$U[\text{nat}] \triangleq \mathbb{N}$$

General Types

$$U[\iota] \triangleq U[\iota]$$

$$U[\sigma \rightarrow \tau] \triangleq U[\sigma] \rightarrow U[\tau]$$

Standard semantics of System \mathbb{T}

Atomic Types

$$U[\text{nat}] \triangleq \mathbb{N}$$

General Types

$$\begin{aligned} U[\iota] &\triangleq U[\iota] \\ U[\sigma \rightarrow \tau] &\triangleq U[\sigma] \rightarrow U[\tau] \end{aligned}$$

Contexts

$$\mathcal{G}[\Gamma] \triangleq \prod_{x \in |\Gamma|} U[\Gamma(x)]$$

Standard semantics of System \mathbb{T}

Presupposing $\rho \in \mathcal{G}[\Gamma]$ and $\Gamma \vdash m : \sigma$, define $\llbracket \Gamma \vdash m : \sigma \rrbracket_\rho \in \mathcal{U}[\sigma]$ by recursion on m :

$$\begin{aligned}\llbracket \Gamma \vdash x : \sigma \rrbracket_\rho &\triangleq \rho(x) \\ \llbracket \Gamma \vdash z : \text{nat} \rrbracket_\rho &\triangleq 0 \\ \llbracket \Gamma \vdash s(m) : \text{nat} \rrbracket_\rho &\triangleq 1 + \llbracket \Gamma \vdash m : \text{nat} \rrbracket_\rho \\ \llbracket \Gamma \vdash \text{rec}_\sigma([x, y].s[x, y]; z; n) : \sigma \rrbracket_\rho &\triangleq \text{PrimRec}(S, Z, N)\end{aligned}$$

where

$$\begin{aligned}S(a, b) &\triangleq \llbracket \Gamma, x : \text{nat}, y : \sigma \vdash s[x, y] : \sigma \rrbracket_{\rho, x \mapsto a, y \mapsto b} \\ Z &\triangleq \llbracket \Gamma \vdash z : \sigma \rrbracket_\rho \\ N &\triangleq \llbracket \Gamma \vdash n : \text{nat} \rrbracket_\rho\end{aligned}$$

Standard semantics of System \mathbb{T}

$$\begin{aligned} & \vdots \\ \llbracket \Gamma \vdash \lambda x. m[x] : \sigma \rightarrow \tau \rrbracket_\rho & \triangleq a \mapsto \llbracket \Gamma, x : \sigma \vdash m[x] : \tau \rrbracket_{\rho, x \mapsto a} \\ \llbracket \Gamma \vdash m \bullet_\sigma n : \tau \rrbracket_\rho & \triangleq \left(\llbracket \Gamma \vdash m : \sigma \rightarrow \tau \rrbracket_\rho \right) \left(\llbracket \Gamma \vdash n : \sigma \rrbracket_\rho \right) \end{aligned}$$

Revising the Bar Thesis

A functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \tau$ can be applied to a meta-level sequence α as follows:

$$\phi \langle \alpha \rangle \triangleq \llbracket \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rrbracket (\alpha)$$

Revising the Bar Thesis

A functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \tau$ can be applied to a meta-level sequence α as follows:

$$\phi \langle \alpha \rangle \triangleq \llbracket \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rrbracket (\alpha)$$

Redefine barhood as follows:

$$\frac{\forall \alpha \in \vec{u}. \exists n \in \mathbb{N}. \bar{\alpha}[n] \in \vec{b}}{\vec{u} \triangleleft \vec{b}}$$

Revising the Bar Thesis

A functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \tau$ can be applied to a meta-level sequence α as follows:

$$\phi \langle \alpha \rangle \triangleq \llbracket \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rrbracket (\alpha)$$

Redefine barhood as follows:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \vec{u}. \bar{\alpha}[\phi \langle \alpha \rangle] \in \vec{B}}{\vec{u} \triangleleft_{\mathbb{T}} \vec{B}}$$

Escardo dialogues

An inductive encoding of functionals $Y^X \rightarrow Z$:

$$\frac{z \in Z}{\eta(z) \in \{\{Y^X, Z\}\}} \text{ return} \qquad \frac{x \in X \quad e \in Y \rightarrow \{\{Y^X, Z\}\}}{\wp\langle x \rangle(e) \in \{\{Y^X, Z\}\}} \text{ query}$$

Escardo dialogues

An inductive encoding of functionals $Y^X \rightarrow Z$:

$$\frac{z \in Z}{\eta(z) \in \{\{Y^X, Z\}\}} \text{ return} \quad \frac{x \in X \quad e \in Y \rightarrow \{\{Y^X, Z\}\}}{\wp\langle x \rangle(e) \in \{\{Y^X, Z\}\}} \text{ query}$$

★ $\{\{Y^X, -\}\}$ is an endofunctor on **Set**

Escardo dialogues

An inductive encoding of functionals $Y^X \rightarrow Z$:

$$\frac{z \in Z}{\eta(z) \in \{Y^X, Z\}} \text{ return} \quad \frac{x \in X \quad e \in Y \rightarrow \{Y^X, Z\}}{\phi\langle x \rangle(e) \in \{Y^X, Z\}} \text{ query}$$

- ★ $\{Y^X, -\}$ is an endofunctor on **Set**
- ★ $\{Y^X, -\}$ is a monad on **Set**

Escardo dialogues

An inductive encoding of functionals $Y^X \rightarrow Z$:

$$\frac{z \in Z}{\eta(z) \in \{Y^X, Z\}} \text{ return} \quad \frac{x \in X \quad e \in Y \rightarrow \{Y^X, Z\}}{\phi\langle x \rangle(e) \in \{Y^X, Z\}} \text{ query}$$

- ★ $\{Y^X, -\}$ is an endofunctor on **Set**
- ★ $\{Y^X, -\}$ is a monad on **Set**

souped up neighborhood functions!

Escardo dialogues


We can execute dialogue trees against a sequence $\alpha \in Y^X$:

$$\begin{aligned}\eta(z) \diamond \alpha &\triangleq z \\ \wp\langle x \rangle(e) \diamond \alpha &\triangleq e(\alpha(x)) \diamond \alpha\end{aligned}$$

Escardo dialogues

We can execute dialogue trees against a sequence $\alpha \in Y^X$:


$$\begin{aligned}\eta(z) \diamond \alpha &\triangleq z \\ \wp(x)(e) \diamond \alpha &\triangleq e(\alpha(x)) \diamond \alpha\end{aligned}$$



Escardo dialogues

We can execute dialogue trees against a sequence $\alpha \in Y^X$:

$$\begin{aligned}\eta(z) \diamond \alpha &\triangleq z \\ \wp\langle x \rangle(e) \diamond \alpha &\triangleq e(\alpha(x)) \diamond \alpha\end{aligned}$$



Dialectical semantics of System \mathbb{T}

Atomic Types

$$U[\text{nat}] \triangleq \mathbb{N}$$

Dialectical semantics of System \mathbb{T}

Atomic Types

$$U[\text{nat}] \triangleq \mathbb{N}$$

Types

$$\begin{aligned} U\langle\iota\rangle &\triangleq \{\mathbb{N}^{\mathbb{N}}, U[\iota]\} \\ U\langle\sigma \rightarrow \tau\rangle &\triangleq U\langle\sigma\rangle \rightarrow U\langle\tau\rangle \end{aligned}$$

Dialectical semantics of System \mathbb{T}

Atomic Types

$$U[\text{nat}] \triangleq \mathbb{N}$$

Types

$$\begin{aligned} U\langle\iota\rangle &\triangleq \{\mathbb{N}^{\mathbb{N}}, U[\iota]\} \\ U\langle\sigma \rightarrow \tau\rangle &\triangleq U\langle\sigma\rangle \rightarrow U\langle\tau\rangle \end{aligned}$$

Contexts

$$\mathcal{G}\langle\Gamma\rangle \triangleq \prod_{x \in |\Gamma|} U\langle\Gamma(x)\rangle$$

Dialectical semantics of System \mathbb{T}

Higher-Type Kleisli Extension

Presupposing σ type and $f \in X \rightarrow U \langle\langle \sigma \rangle\rangle$, define:

$$f_{\sigma}^{\star} \in \{\mathbb{N}^{\mathbb{N}}, X\} \rightarrow U \langle\langle \sigma \rangle\rangle$$

$$f_i^{\star}(e) \triangleq f^{\star}(e)$$

$$f_{\sigma \rightarrow \tau}^{\star}(e) \triangleq s \mapsto f(-)(s)_{\tau}^{\star}(e)$$

Dialectical semantics of System \mathbb{T}

Presupposing $\rho \in \mathcal{G} \langle \Gamma \rangle$ and $\Gamma \vdash m : \sigma$, we define the interpretation $\langle \Gamma \vdash m : \sigma \rangle_\rho \in \mathcal{U} \langle \sigma \rangle$:

$$\langle \Gamma \vdash x : \sigma \rangle_\rho \triangleq \rho(x)$$

$$\langle \Gamma \vdash z : \text{nat} \rangle_\rho \triangleq \eta(0)$$

$$\langle \Gamma \vdash s(m) : \text{nat} \rangle_\rho \triangleq \{ \mathbb{N}^{\mathbb{N}}, 1 + - \} \left(\langle \Gamma \vdash m : \text{nat} \rangle_\rho \right)$$

$$\langle \Gamma \vdash \text{rec}_\sigma([x, y].s[x, y]; z; n) : \sigma \rangle_\rho \triangleq \text{PrimRec}(S, Z, -)^\star_\sigma(N)$$

where

$$S(a, b) \triangleq \langle \Gamma, x : \text{nat}, y : \sigma \vdash s[x, y] : \sigma \rangle_{\rho, x \mapsto a, y \mapsto b}$$

$$Z \triangleq \langle \Gamma \vdash z : \sigma \rangle_\rho$$


$$N \triangleq \langle \Gamma \vdash n : \text{nat} \rangle_\rho$$

Dialectical semantics of System \mathbb{T}

$$\begin{aligned} & \vdots \\ \langle\langle \Gamma \vdash \lambda x. m[x] : \sigma \rightarrow \tau \rangle\rangle_{\rho} & \triangleq a \mapsto \langle\langle \Gamma, x : \sigma \vdash m[x] : \tau \rangle\rangle_{\rho, x \mapsto a} \\ \langle\langle \Gamma \vdash m \bullet_{\sigma} n : \tau \rangle\rangle_{\rho} & \triangleq \left(\langle\langle \Gamma \vdash m : \sigma \rightarrow \tau \rangle\rangle_{\rho} \right) \left(\langle\langle \Gamma \vdash n : \sigma \rangle\rangle_{\rho} \right) \end{aligned}$$


Coherence via Logical Relations

We need to show that the two interpretations cohere at base type, i.e. that the following diagram commutes:



Coherence via Logical Relations

We need to show that the two interpretations cohere at base type, i.e. that the following diagram commutes:



SLOGAN: STRENGTHEN THE INDUCTIVE HYPOTHESIS WITH LOGICAL RELATIONS AS A WEAPON!

Coherence via Logical Relations

“logical relations” = family of relations defined by recursion on object-level types

Coherence via Logical Relations

“logical relations” = family of relations defined by recursion on object-level types

For all $\alpha \in \mathbb{N}^{\mathbb{N}}$, define:

$$R_{\sigma}^{\alpha} \subseteq U \llbracket \sigma \rrbracket \times U \langle\langle \sigma \rangle\rangle \qquad \overline{R_{\Gamma}^{\alpha}} \subseteq \mathcal{G} \llbracket \Gamma \rrbracket \times \mathcal{G} \langle\langle \Gamma \rangle\rangle$$

Coherence via Logical Relations

“logical relations” = family of relations defined by recursion on object-level types

For all $\alpha \in \mathbb{N}^{\mathbb{N}}$, define:

$$R_{\sigma}^{\alpha} \subseteq U \llbracket \sigma \rrbracket \times U \langle\langle \sigma \rangle\rangle \quad \overline{R}_{\Gamma}^{\alpha} \subseteq \mathcal{G} \llbracket \Gamma \rrbracket \times \mathcal{G} \langle\langle \Gamma \rangle\rangle$$

$$\frac{F = d \diamond \alpha}{F R_{\iota}^{\alpha} d} \quad \frac{\forall G \in U \llbracket \sigma \rrbracket, e \in U \langle\langle \sigma \rangle\rangle. G R_{\sigma}^{\alpha} e \implies F(G) R_{\tau}^{\alpha} d(e)}{F R_{\sigma \rightarrow \tau}^{\alpha} d}$$
$$\frac{\forall x \in |\Gamma|. \rho_0(x) R_{\Gamma(x)}^{\alpha} \rho_1(x)}{\rho_0 \overline{R}_{\Gamma}^{\alpha} \rho_1}$$

The Generic Point

The Generic Point

In the dialogue model, we can define a so-called “generic point” which is not definable in **System T**:

$$generic \in \{Y^X, X\} \rightarrow \{Y^X, Y\}$$

$$generic \triangleq (\lambda x. x)(\eta)^*$$

The Generic Point

In the dialogue model, we can define a so-called “generic point” which is not definable in **System T**:

$$\begin{aligned} \textit{generic} &\in \{\{Y^X, X\} \rightarrow \{Y^X, Y\}\} \\ \textit{generic} &\triangleq (\mathsf{q}\langle-\rangle(\eta))^* \end{aligned}$$

**THE GENERIC POINT IS THE MAGIC WEAPON TO VICTORIOUSLY
TRACE A FUNCTIONAL'S INTERACTION WITH THE AMBIENT
CHOICE SEQUENCE!**

— Quotations From Chairman Thierry Coquand

Taking stock

Taking stock

- ★ For any functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}$, we can compute a dialogue tree $\langle\langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle\rangle (\text{generic}) \in \{\mathbb{N}^{\mathbb{N}}, \mathbb{N}\}$.

Taking stock

- ★ For any functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}$, we can compute a dialogue tree $\langle\langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle\rangle (\text{generic}) \in \{\mathbb{N}^{\mathbb{N}}, \mathbb{N}\}$.
- ★ Similar to a Brouwerian mental construction of $\vec{u} \triangleleft_{ind} \mathbb{B}$, but not the same!

Taking stock

- ★ For any functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}$, we can compute a dialogue tree $\langle\langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle\rangle$ (*generic*) $\in \{\mathbb{N}^{\mathbb{N}}, \mathbb{N}\}$.
- ★ Similar to a Brouwerian mental construction of $\vec{u} \triangleleft_{\text{ind}} \mathbb{B}$, but not the same!
- ★ Escardó's trees represent *persistent inspection* of a choice sequence; Brouwer's trees represent *ephemeral consumption* of a choice sequence.

Taking stock

- ★ For any functional $\cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}$, we can compute a dialogue tree $\langle\langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle\rangle$ (*generic*) $\in \{\mathbb{N}^{\mathbb{N}}, \mathbb{N}\}$.
- ★ Similar to a Brouwerian mental construction of $\vec{u} \triangleleft_{ind} \mathbb{B}$, but not the same!
- ★ Escardó's trees represent *persistent inspection* of a choice sequence; Brouwer's trees represent *ephemeral consumption* of a choice sequence.
- ★ **Idea:** Normalize dialogue trees into Brouwerian mental constructions.

Brouwer's ephemeral dialectics

$$\frac{z \in Z}{\eta(z) \in (Y^{\mathbb{N}}, Z)} \text{ spit} \qquad \frac{b \in Y \rightarrow (Y^{\mathbb{N}}, Z)}{F(b) \in (Y^{\mathbb{N}}, Z)} \text{ bite}$$

Brouwer's ephemeral dialectics

$$\frac{z \in Z}{\eta(z) \in \langle Y^{\mathbb{N}}, Z \rangle} \text{ spit} \qquad \frac{b \in Y \rightarrow \langle Y^{\mathbb{N}}, Z \rangle}{F(b) \in \langle Y^{\mathbb{N}}, Z \rangle} \text{ bite}$$

Ephemeral execution:

$$\eta(z) \diamond \alpha \triangleq z$$

$$F(b) \diamond \alpha \triangleq b(\text{head}(\alpha)) \diamond \text{tail}(\alpha)$$

Normalizing dialogues

Presupposing $t \in \{Y^{\mathbb{N}}, Z\}$, define total normalization relation $\vec{u} \Vdash t \rightsquigarrow b$ with $b \in (Y^{\mathbb{N}}, Z)$.

Normalizing dialogues

Presupposing $t \in \{Y^{\mathbb{N}}, Z\}$, define total normalization relation $\vec{u} \Vdash t \rightsquigarrow b$ with $b \in (Y^{\mathbb{N}}, Z)$.


Naïve Algorithm:

$$\begin{aligned} \text{norm}_{\vec{u}}(\eta(z)) &\triangleq \eta(z) \\ \text{norm}_{\vec{u}}(\varphi\langle i \rangle(t)) &\triangleq \begin{cases} \vec{u}_i & \text{if } i < |\vec{u}| \\ \mathsf{F}(y \mapsto \text{norm}_{\vec{u} \smallfrown y}(\varphi\langle i \rangle(t))) & \text{if } i \geq |\vec{u}| \end{cases} \end{aligned}$$

$$\frac{\text{norm}_{\vec{u}}(t) \equiv b}{\vec{u} \Vdash t \rightsquigarrow b}$$

Structurally recursive definition easy, but bureaucratic. See paper.

The Birds'-Eye View



The Bar Thesis

The Bar

The Bar is a group of people who are interested in the same thing. They are interested in the same thing because they are interested in the same thing.

The Bar is a group of people who are interested in the same thing. They are interested in the same thing because they are interested in the same thing.

The Bar is a group of people who are interested in the same thing. They are interested in the same thing because they are interested in the same thing.

The Bar Theorem

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\vec{u} \triangleleft_{\mathbb{T}} \vec{b}}{\vec{u} \triangleleft_{ind} \vec{b}} \text{ completeness}$$

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \vec{u}. \bar{\alpha}[\phi \langle \alpha \rangle] \in \vec{B}}{\vec{u} \blacktriangleleft_{\text{ind}} \vec{B}} \text{ completeness}$$

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \langle \rangle. \overline{\vec{u} \oplus \alpha}[\phi \langle \alpha \rangle + |\vec{u}|] \in \vec{\mathfrak{B}}}{\vec{u} \blacktriangleleft_{ind} \vec{\mathfrak{B}}} \text{ completeness}$$

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \langle \rangle. \overline{\vec{u} \oplus \alpha}[\phi \langle \alpha \rangle + |\vec{u}|] \in \vec{b}}{\vec{u} \triangleleft_{ind} \vec{b}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$.

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \quad \forall \alpha \in \langle \rangle. \quad \overline{\vec{u} \oplus \alpha}[\phi \langle \alpha \rangle + |\vec{u}|] \in \mathfrak{B}}{\vec{u} \triangleleft_{ind} \mathfrak{B}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$. By coherence, we have $\overline{\vec{u} \oplus \alpha}[b \diamond \alpha + |\vec{u}|] \in \mathfrak{B}$ for all α .

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \quad \forall \alpha \in \langle \rangle. \quad \overline{\vec{u} \oplus \alpha}[\phi \langle \alpha \rangle + |\vec{u}|] \in \mathfrak{B}}{\vec{u} \triangleleft_{ind} \mathfrak{B}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$. By coherence, we have $\overline{\vec{u} \oplus \alpha}[b \diamond \alpha + |\vec{u}|] \in \mathfrak{B}$ for all α . Proceed by induction on $b \in (\mathbb{N}^{\mathbb{N}}, \mathbb{N})$.

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \langle \rangle. \overline{\vec{u} \oplus \alpha}[\phi \langle \alpha \rangle + |\vec{u}|] \in \mathfrak{B}}{\vec{u} \triangleleft_{ind} \mathfrak{B}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$. By coherence, we have $\overline{\vec{u} \oplus \alpha}[b \diamond \alpha + |\vec{u}|] \in \mathfrak{B}$ for all α . Proceed by induction on $b \in (\mathbb{N}^{\mathbb{N}}, \mathbb{N})$.

★ Case $b \equiv \eta(0)$. Then we already have $\vec{u} \in \mathfrak{B}$, so apply η rule.

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \langle \rangle. \overline{\vec{u} \oplus \alpha}[\phi \langle \alpha \rangle + |\vec{u}|] \in \mathfrak{B}}{\vec{u} \triangleleft_{ind} \mathfrak{B}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$. By coherence, we have $\overline{\vec{u} \oplus \alpha}[b \diamond \alpha + |\vec{u}|] \in \mathfrak{B}$ for all α . Proceed by induction on $b \in (\mathbb{N}^{\mathbb{N}}, \mathbb{N})$.

- ★ Case $b \equiv \eta(0)$. Then we already have $\vec{u} \in \mathfrak{B}$, so apply η rule.
- ★ Case $b \equiv \eta(k+1)$. Apply F rule, and use IH at $\eta(k)$.

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \quad \forall \alpha \in \langle \rangle. \quad \overline{\vec{u} \oplus \alpha[\phi \langle \alpha \rangle + |\vec{u}|]} \in \mathfrak{B}}{\vec{u} \triangleleft_{ind} \mathfrak{B}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$. By coherence, we have $\overline{\vec{u} \oplus \alpha[b \diamond \alpha + |\vec{u}|]} \in \mathfrak{B}$ for all α . Proceed by induction on $b \in (\mathbb{N}^{\mathbb{N}}, \mathbb{N})$.

- ★ Case $b \equiv \eta(0)$. Then we already have $\vec{u} \in \mathfrak{B}$, so apply η rule.
- ★ Case $b \equiv \eta(k+1)$. Apply F rule, and use IH at $\eta(k)$.
- ★ Case $b \equiv \mathsf{F}(f)$. Apply F rule, fixing $y \in \mathbb{N}$; use IH at $f(y)$.

The Bar Theorem

It suffices to show the validity of the following completeness rule:

$$\frac{\exists \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat}. \forall \alpha \in \langle \rangle. \overline{\vec{u} \oplus \alpha[\phi \langle \alpha \rangle + |\vec{u}|]} \in \mathfrak{B}}{\vec{u} \triangleleft_{ind} \mathfrak{B}} \text{ completeness}$$

Proof. Let $t \triangleq \langle \cdot \vdash \phi : (\text{nat} \rightarrow \text{nat}) \rightarrow \text{nat} \rangle$ (*generic*) such that $\langle \rangle \Vdash t \rightsquigarrow b$. By coherence, we have $\overline{\vec{u} \oplus \alpha[b \diamond \alpha + |\vec{u}|]} \in \mathfrak{B}$ for all α . Proceed by induction on $b \in (\mathbb{N}^{\mathbb{N}}, \mathbb{N})$.

- ★ Case $b \equiv \eta(0)$. Then we already have $\vec{u} \in \mathfrak{B}$, so apply η rule.
- ★ Case $b \equiv \eta(k+1)$. Apply \mathfrak{F} rule, and use IH at $\eta(k)$.
- ★ Case $b \equiv \mathfrak{F}(f)$. Apply \mathfrak{F} rule, fixing $y \in \mathbb{N}$; use IH at $f(y)$.



Summary of Results



- ★ The Bar Theorem is *constructively valid* in primitive recursive realizability (with correct/full interpretation of functional types).
- ★ Thence, we have the *Bar Induction Principle* and the *Fan Theorem* (constructive König's Lemma).
- ★ What is the status of Brouwer's Thesis as a *scientific hypothesis*?

Summary of Results



- ★ The Bar Theorem is *constructively valid* in primitive recursive realizability (with correct/full interpretation of functional types).
- ★ Thence, we have the *Bar Induction Principle* and the *Fan Theorem* (constructive König's Lemma).
- ★ What is the status of Brouwer's Thesis as a *scientific hypothesis*?

Can this result be extended to general recursive realizability (assuming open interpretation of \rightarrow)?