



designing the people's refinement logic

Jon Sterling

Carnegie Mellon University

what is RedPRL?

A project to build a modernized Nuprl for Computational Cubical Type Theory (Angiuli, Harper, Wilson): the first ever *interactive* proof assistant for higher dimensional type theory.

what is RedPRL?

A project to build a modernized Nuprl for Computational Cubical Type Theory (Angiuli, Harper, Wilson): the first ever *interactive* proof assistant for higher dimensional type theory.

I hate writing code, and mechanization with current tools frustrates me. I wish everything could be done on paper.


what is RedPRL?

A project to build a modernized Nuprl for Computational Cubical Type Theory (Angiuli, Harper, Wilson): the first ever *interactive* proof assistant for higher dimensional type theory.

I hate writing code, and mechanization with current tools frustrates me. I wish everything could be done on paper.

So, why bother?

the absolute idea



(With thanks to Hegel, Marx, Mao and Lawvere.)

overview of RedPRL

Cubical Refinement Logic		
Cubical Abstract Machine	Cubical Type Theory	Dependent LCF
Cubical Abstract Binding Trees		
Indexed Second-Order Algebra	Lawvere Duality	

outline

1. The LCF/PRL Tradition

2. The Revisionists And Their Running Dogs

3.  RedPRL: New Synthesis Of Proof Refinement

lcf architecture

```
type evd (* evidence *)
type  $\alpha$  state =  $\alpha$  list  $\otimes$  (evd list  $\rightarrow$  evd) (* proof state *)
type ( $\alpha, \beta$ ) tactic =  $\alpha \rightarrow \beta$  state
```


lcf architecture

```
type evd                                (* evidence *)
type  $\alpha$  state =  $\alpha$  list  $\otimes$  (evd list  $\rightarrow$  evd) (* proof state *)
type ( $\alpha, \beta$ ) tactic =  $\alpha \rightarrow \beta$  state

(* proof state “monad” *)
val id : ( $\alpha, \alpha$ ) tactic
val map : ( $\alpha \rightarrow \beta$ )  $\rightarrow$  ( $\alpha$  state,  $\beta$ ) tactic
val mul : ( $\alpha$  state state,  $\alpha$ ) tactic
val orelse : ( $\alpha, \beta$ ) tactic  $\otimes$  ( $\alpha, \beta$ ) tactic  $\rightarrow$  ( $\alpha, \beta$ ) tactic
```

lcf architecture

```
type evd                                (* evidence *)
type  $\alpha$  state =  $\alpha$  list  $\otimes$  (evd list  $\rightarrow$  evd)  (* proof state *)
type  $(\alpha, \beta)$  tactic =  $\alpha \rightarrow \beta$  state

(* proof state "monad" *)
val id :  $(\alpha, \alpha)$  tactic
val map :  $(\alpha \rightarrow \beta) \rightarrow (\alpha$  state,  $\beta)$  tactic
val mul :  $(\alpha$  state state,  $\alpha)$  tactic
val orelse :  $(\alpha, \beta)$  tactic  $\otimes$   $(\alpha, \beta)$  tactic  $\rightarrow (\alpha, \beta)$  tactic

(* standard tacticals *)
val then :  $(\alpha, \beta)$  tactic  $\otimes$   $(\beta, \gamma)$  tactic  $\rightarrow (\alpha, \gamma)$  tactic
fun then ( $t_1, t_2$ ) = mul  $\circ$  map  $t_2 \circ t_1$ 
val then1 :  $(\alpha, \beta)$  tactic  $\otimes$   $(\beta, \gamma)$  tactic list  $\rightarrow (\alpha, \gamma)$  tactic
```

lcf architecture

include LCF

lcf architecture

```
include LCF
datatype prop =
  |  $\wedge$  of prop  $\otimes$  prop
  |  $\vee$  of prop  $\otimes$  prop
  |  $\supset$  of prop  $\otimes$  prop
  | T,  $\perp$ 
```

lcf architecture

```
include LCF
```

```
datatype prop =
```

```
  |  $\wedge$  of prop  $\otimes$  prop
```

```
  |  $\vee$  of prop  $\otimes$  prop
```

```
  |  $\supset$  of prop  $\otimes$  prop
```

```
  |  $\top, \perp$ 
```

```
datatype jdg =  $\vdash$  of prop dict  $\otimes$  prop
```

```
type rule = (jdg, jdg) tactic
```

lcf architecture

```
include LCF
```

```
datatype prop =
```

```
   $\wedge$  of prop  $\otimes$  prop
```

```
   $\vee$  of prop  $\otimes$  prop
```

```
   $\supset$  of prop  $\otimes$  prop
```

```
   $\top, \perp$ 
```

```
datatype jdg =  $\vdash$  of prop dict  $\otimes$  prop
```

```
type rule = (jdg, jdg) tactic
```

```
val  $\wedge_R, \vee_R, \supset_R, \top_R, \perp_R$  : rule
```

```
val hyp : string  $\rightarrow$  rule
```

```
val  $\wedge_L$  : string  $\otimes$  string  $\otimes$  string  $\rightarrow$  rule
```

```
...
```

programs as evidence

Abstract (!!)

type of evidence implemented as functional programming language:

datatype `evd` =

```
var of string
λ of string ⊗ evd
ap of evd ⊗ evd
pair of evd ⊗ evd
π1, π2 of evd
inl, inr of evd
split of evd ⊗ evd ⊗ evd
```

programs as evidence

Abstract (!!) type of evidence implemented as functional programming language:

datatype `evd` =

```
var of string
λ of string ⊗ evd
ap of evd ⊗ evd
pair of evd ⊗ evd
π1, π2 of evd
inl, inr of evd
split of evd ⊗ evd ⊗ evd
```

Other options possible: **machine code**, **JavaScript**, **Perl**, **PHP**, **Julia** ;-), etc.

inference rules

inference rule \Leftrightarrow ML function

inference rules

inference rule \Leftrightarrow ML function

$\frac{}{\Delta, x : P, \Xi \vdash P}$ *hyp*[*x*]

\Leftrightarrow

```
fun hyp(x) ( $\Gamma \vdash P$ ) =  
  let ( $\Delta, Q, \Xi$ ) = split( $\Gamma, x$ )  
  and true = ( $P = Q$ )  
  in ( $[], \text{fn } [] \Rightarrow \text{var}(x)$ )
```

inference rules

inference rule \Leftrightarrow ML function

$$\frac{}{\Delta, x : P, \Xi \vdash P} \text{hyp}[x] \quad \Leftrightarrow$$

```
fun hyp(x) ( $\Gamma \vdash P$ ) =  
  let ( $\Delta, Q, \Xi$ ) = split( $\Gamma, x$ )  
  and true = ( $P = Q$ )  
  in ( $[], \text{fn } [] \Rightarrow \text{var}(x)$ )
```

$$\frac{\Gamma \vdash P \quad \Gamma \vdash Q}{\Gamma \vdash P \wedge Q} \wedge_R \quad \Leftrightarrow$$

```
fun  $\wedge_R$  ( $\Gamma \vdash P \wedge Q$ ) =  
  ( $\left[ \begin{array}{c} \Gamma \vdash P, \Gamma \vdash Q \\ \text{fn } [M, N] \Rightarrow \text{pair}(M, N) \end{array} \right]$ )
```

inference rules

$$\frac{\Delta, x : P \wedge Q, y : P, z : Q, \Xi \vdash R}{\Delta, x : P \wedge Q, \Xi \vdash R} \wedge_L[x, y, z]$$

\Updownarrow

```
fun  $\wedge_L(x, y, z)$  ( $\Gamma \vdash R$ ) =  
  let  $(\Delta, P \wedge Q, \Xi) = \text{split}(\Gamma, x)$   
  in  $\left( \begin{array}{l} [\Delta, x : P \wedge Q, y : P, z : Q, \Xi \vdash R], \\ \text{fn } [M] \Rightarrow [\pi_1(\text{var}(x)), \pi_2(\text{var}(x))/y, z]M \end{array} \right)$ 
```

proofs and scripts

$$\overline{x : P \wedge Q \vdash P \wedge Q}$$



proofs and scripts

$$\frac{\overline{x : P \wedge Q, y : P, z : Q \vdash P \wedge Q}}{x : P \wedge Q \vdash P \wedge Q} \wedge_L [x, y, z]$$

\Updownarrow

$$\wedge_L (x, y, z)$$

proofs and scripts

$$\frac{\frac{\overline{x : P \wedge Q, y : P, z : Q \vdash P} \quad \overline{x : P \wedge Q, y : P, z : Q \vdash Q}}{x : P \wedge Q, y : P, z : Q \vdash P \wedge Q} \wedge_R}{x : P \wedge Q \vdash P \wedge Q} \wedge_L [x, y, z]$$

\Updownarrow

$\wedge_L (x, y, z)$
then \wedge_R

proofs and scripts

$$\frac{\frac{\frac{x : P \wedge Q, y : P, z : Q \vdash P}{hyp[y]} \quad \frac{x : P \wedge Q, y : P, z : Q \vdash Q}{hyp[z]}}{x : P \wedge Q, y : P, z : Q \vdash P \wedge Q} \wedge_R}{x : P \wedge Q \vdash P \wedge Q} \wedge_L [x, y, z]$$

\Updownarrow

$\wedge_L (x, y, z)$
then \wedge_R
then1 $\left[\begin{array}{l} hyp(y), \\ hyp(z) \end{array} \right]$

proofs and scripts

$$\frac{\frac{\frac{\overline{x : P \wedge Q, y : P, z : Q \vdash P} \text{hyp}[y] \quad \frac{\overline{x : P \wedge Q, y : P, z : Q \vdash Q} \text{hyp}[z]}{\wedge_R} \quad \frac{x : P \wedge Q, y : P, z : Q \vdash P \wedge Q}{\wedge_L [x, y, z]} \quad x : P \wedge Q \vdash P \wedge Q}{\wedge_L [x, y, z]}$$

\Updownarrow

$\wedge_L (x, y, z)$
then \wedge_R
then1 $\left[\begin{array}{c} \text{hyp}(y), \\ \text{hyp}(z) \end{array} \right] \rightsquigarrow \text{pair}(\pi_1(\text{var}(x)), \pi_2(\text{var}(x)))$

free program invariants

A proof synthesizes a program (*stop calling this “extraction”!*). Depending on the structure of our logic, we can enforce many invariants!

free program invariants

A proof synthesizes a program (*stop calling this “extraction”!*). Depending on the structure of our logic, we can enforce many invariants!

- ★ **Structural invariants:** ordered/affine/linear resource usage

free program invariants

A proof synthesizes a program (*stop calling this “extraction”!*). Depending on the structure of our logic, we can enforce many invariants!

- ★ **Structural invariants:** ordered/affine/linear resource usage
- ★ **Behavioral invariants:** termination, productivity, specification satisfaction

free program invariants

A proof synthesizes a program (*stop calling this “extraction”!*). Depending on the structure of our logic, we can enforce many invariants!

- ★ **Structural invariants:** ordered/affine/linear resource usage
- ★ **Behavioral invariants:** termination, productivity, specification satisfaction
- ★ **Cost invariants?**

free program invariants

A proof synthesizes a program (*stop calling this “extraction”!*). Depending on the structure of our logic, we can enforce many invariants!

- ★ **Structural invariants:** ordered/affine/linear resource usage
- ★ **Behavioral invariants:** termination, productivity, specification satisfaction
- ★ **Cost invariants?**

All this is possible, whilst generating efficient codes in an **arbitrary language**. Proof structure does not appear in programs.

orthodox lcf architecture

orthodox lcf architecture

- ★ sequent calculus rules trivially translated into ML
- ★ easy to check that a collection of rules is correct
- ★ **THESE RULES ARE *definitive***

orthodox lcf architecture

- ★ sequent calculus rules trivially translated into ML
- ★ easy to check that a collection of rules is correct
- ★ **THESE RULES ARE *definitive***
- ★ data abstraction guarantees provenience of evidence

orthodox lcf architecture

- ★ sequent calculus rules trivially translated into ML
- ★ easy to check that a collection of rules is correct
- ★ **THESE RULES ARE *definitive***
- ★ data abstraction guarantees provenience of evidence
- ★ “decidable” typechecking ***completely irrelevant***: type membership just another judgment

orthodox lcf architecture

- ★ sequent calculus rules trivially translated into ML
- ★ easy to check that a collection of rules is correct
- ★ **THESE RULES ARE *definitive***
- ★ data abstraction guarantees provenience of evidence
- ★ “decidable” typechecking ***completely irrelevant***: type membership just another judgment
- ★ “independently checkable evidence” likewise a distraction¹, because of the soundness of the rules

¹full employment for purveyors of proof assistants

orthodox lcf architecture

- ★ sequent calculus rules trivially translated into ML
- ★ easy to check that a collection of rules is correct
- ★ **THESE RULES ARE *definitive***
- ★ data abstraction guarantees provenience of evidence
- ★ “decidable” typechecking ***completely irrelevant***: type membership just another judgment
- ★ “independently checkable evidence” likewise a distraction¹, because of the soundness of the rules

DECISIVELY SMASH THE FORMALIST CLIQUE!

¹full employment for purveyors of proof assistants

orthodox lcf architecture

there were some problems...

orthodox lcf architecture

there were some problems...

- ★ sadly, no dependent refinement (cf. “constructible subgoals property”)

orthodox lcf architecture

there were some problems...

- ★ sadly, no dependent refinement (cf. “constructible subgoals property”)
- ★ no existential variables and unification in core LCF framework (compromises soundness for some logics)

orthodox lcf architecture

there were some problems...

- ★ sadly, no dependent refinement (cf. “constructible subgoals property”)
- ★ no existential variables and unification in core LCF framework (compromises soundness for some logics)
- ★ many sensible rules cannot be encoded (e.g. bidirectional typing)

orthodox lcf architecture

there were some problems...

- ★ sadly, no dependent refinement (cf. “constructible subgoals property”)
- ★ no existential variables and unification in core LCF framework (compromises soundness for some logics)
- ★ many sensible rules cannot be encoded (e.g. bidirectional typing)
- ★ complicated and brittle tactics are necessary for basic use

outline

1. The LCF/PRL Tradition

2. The Revisionists And Their Running Dogs

3.  RedPRL: New Synthesis Of Proof Refinement

revisionist coq architecture




revisionist coq architecture

★ untrusted, non-definitive rules




revisionist coq architecture

- ★ untrusted, non-definitive rules
- ★ core language with definitive typechecker




revisionist coq architecture

- ★ untrusted, non-definitive rules
- ★ core language with definitive typechecker
- ★ non-local unification and existential variables in rules and tactics (generally unsound)



revisionist coq architecture


- ★ untrusted, non-definitive rules
- ★ core language with definitive typechecker
- ★ non-local unification and existential variables in rules and tactics (generally unsound)
- ★ “fine”, because everything must pass through the typechecker



revisionist coq architecture

- ★ untrusted, non-definitive rules
- ★ core language with definitive typechecker
- ★ non-local unification and existential variables in rules and tactics (generally unsound)
- ★ “fine”, because everything must pass through the typechecker

Advantages: excellent proof automation; very practical in many cases; can experiment with fancy tactics and refinement strategies without compromising soundness.




revisionist coq architecture

- ★ untrusted, non-definitive rules
- ★ core language with definitive typechecker
- ★ non-local unification and existential variables in rules and tactics (generally unsound)
- ★ “fine”, because everything must pass through the typechecker

Advantages: excellent proof automation; very practical in many cases; can experiment with fancy tactics and refinement strategies without compromising soundness.

Coq is the most successful proof assistant based on type theory in history.



revisionist coq architecture

Disadvantages of revisionism



revisionist coq architecture

Disadvantages of revisionism

1. dangling existential variables (partly mitigated)



revisionist coq architecture

Disadvantages of revisionism


1. dangling existential variables (partly mitigated)
2. obscenely large objects must exist in memory and be shoved through a typechecker: space usage is out of control, easy to wedge Coq



revisionist coq architecture

Disadvantages of revisionism


1. dangling existential variables (partly mitigated)
2. obscenely large objects must exist in memory and be shoved through a typechecker: **space usage is out of control**, easy to wedge Coq
3. not clear how to integrate external sources of truth (**solvers**) without destroying the character of the logic



revisionist coq architecture

Disadvantages of revisionism


1. dangling existential variables (partly mitigated)
2. obscenely large objects must exist in memory and be shoved through a typechecker: space usage is out of control, easy to wedge Coq
3. not clear how to integrate external sources of truth (solvers) without destroying the character of the logic
4. more difficult to verify a (real) typechecker than a (real) refiner



revisionist coq architecture

Disadvantages of revisionism

1. dangling existential variables (partly mitigated)
2. obscenely large objects must exist in memory and be shoved through a typechecker: **space usage is out of control**, easy to wedge Coq
3. not clear how to integrate external sources of truth (**solvers**) without destroying the character of the logic
4. **more difficult to verify a (real) typechecker than a (real) refiner**
5. logical rules are duplicated in two encodings: refinement rules and typechecking rules



revisionist coq architecture

Disadvantages of revisionism

1. dangling existential variables (partly mitigated)
2. obscenely large objects must exist in memory and be shoved through a typechecker: **space usage is out of control**, easy to wedge Coq
3. not clear how to integrate external sources of truth (**solvers**) without destroying the character of the logic
4. **more difficult to verify a (real) typechecker than a (real) refiner**
5. logical rules are duplicated in two encodings: refinement rules and typechecking rules

RESIST FRENCH IMPERIALISM AND UPHOLD ROBIN MILNER THOUGHT!

outline

1. The LCF/PRL Tradition

2. The Revisionists And Their Running Dogs

3.  **RedPRL: New Synthesis Of Proof Refinement**

RedPRL: dependent refinement

 **RedPRL** is a return to **orthodoxy**, synthesizing modern developments in proof refinement.

RedPRL: dependent refinement

 **RedPRL** is a return to **orthodoxy**, synthesizing modern developments in proof refinement.

- ★ ***Dependent LCF***: each subgoal induces a metavariable that can be used in the statements of later subgoals.

RedPRL: dependent refinement

 RedPRL is a return to **orthodoxy**, synthesizing modern developments in proof refinement.

- ★ ***Dependent LCF***: each subgoal induces a metavariable that can be used in the statements of later subgoals.
- ★ **Metavariables can only be resolved *locally***, by refinement rules (NOT UNIFICATION).

RedPRL: dependent refinement

 RedPRL is a return to **orthodoxy**, synthesizing modern developments in proof refinement.

- ★ ***Dependent LCF***: each subgoal induces a metavariable that can be used in the statements of later subgoals.
- ★ **Metavariables can only be resolved *locally***, by refinement rules (NOT UNIFICATION).
- ★ Strict $1 \leftrightarrow 1$ relation between goals and metavariables in context.

RedPRL: dependent refinement

 RedPRL is a return to **orthodoxy**, synthesizing modern developments in proof refinement.

- ★ ***Dependent LCF***: each subgoal induces a metavariable that can be used in the statements of later subgoals.
- ★ **Metavariables can only be resolved *locally***, by refinement rules (NOT UNIFICATION).
- ★ Strict $1 \leftrightarrow 1$ relation between goals and metavariables in context.
- ★ Precisely what is needed to encode **bidirectional typing rules**.

remark on unification

Resolving existential variables via unification is so much fun! **But it induces non-local soundness conditions for a refiner** (very sad!).

remark on unification

Resolving existential variables via unification is so much fun! **But it induces non-local soundness conditions for a refiner** (very sad!).

1. **Changes the character of the implemented logic:** can make type theory anti-classical if not careful (cf. Agda).

remark on unification

Resolving existential variables via unification is so much fun! **But it induces non-local soundness conditions for a refiner** (very sad!).

1. **Changes the character of the implemented logic:** can make type theory anti-classical if not careful (cf. Agda).
2. Probably **unsound in the presence of subtyping** and non-discrete equality (e.g. Nuprl).

remark on unification

Resolving existential variables via unification is so much fun! **But it induces non-local soundness conditions for a refiner** (very sad!).

1. **Changes the character of the implemented logic:** can make type theory anti-classical if not careful (cf. Agda).
 2. Probably **unsound in the presence of subtyping** and non-discrete equality (e.g. Nuprl).
- ★ Works out fine in Coq because the **refinement rules do not need to be sound**.

remark on unification

Resolving existential variables via unification is so much fun! **But it induces non-local soundness conditions for a refiner** (very sad!).

1. **Changes the character of the implemented logic:** can make type theory anti-classical if not careful (cf. Agda).
 2. Probably **unsound in the presence of subtyping** and non-discrete equality (e.g. Nuprl).
- ★ Works out fine in Coq because the **refinement rules do not need to be sound**.
 - ★ Unification **must be integrated as a judgment** in your theory, not as part of a refinement framework. See Cockx/Devriese/Piessens ICFP 2016.

dependent lcf: example

Enables a straightforward encoding of sophisticated dependent refinement rules which are not expressible in **Classic LCF** or **Nuprl**.

dependent lcf: example

Enables a straightforward encoding of sophisticated dependent refinement rules which are not expressible in **Classic LCF** or **Nuprl**. For example...

$$\frac{\Gamma \vdash R \Rightarrow (x : A) \rightarrow B_x \quad \Gamma \vdash S \Leftarrow A}{\Gamma \vdash R(S) \Rightarrow [S/x]B_x} \text{ synth/ap}$$

dependent lcf: example

Enables a straightforward encoding of sophisticated dependent refinement rules which are not expressible in **Classic LCF** or **Nuprl**. For example...

$$\frac{\Gamma \vdash R \Rightarrow (x : A) \rightarrow B_x \quad \Gamma \vdash S \Leftarrow A}{\Gamma \vdash R(S) \Rightarrow [S/x]B_x} \text{ synth/ap}$$

$$\frac{\overset{(M)}{\Gamma \vdash A \text{ true}} \quad \Gamma \vdash [M/x]B_x \text{ true}}{\Gamma \vdash (x : A) \times B_x \text{ true}} \text{ intro}/\Sigma$$

use *dependent lcf* today!

Implemented as a modular **Standard ML** library, which you can use in your own project today!

<https://github.com/RedPRL/sml-dependent-lcf>


use *dependent lcf* today!

Implemented as a modular **Standard ML** library, which you can use in your own project today!

<https://github.com/RedPRL/sml-dependent-lcf>

Restricts automatically to **Classic LCF** when instantiated without dependency/substitution structure.

RedPRL's cubical type theory



RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

- ★ a type theory with both extensional *equality* and intensional *identification* (paths)

RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

- ★ a type theory with both extensional *equality* and intensional *identification* (paths)
- ★ higher inductive types: the circle

RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

- ★ a type theory with both extensional *equality* and intensional *identification* (paths)
- ★ higher inductive types: the circle
- ★ strict types: strict booleans (new)

RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

- ★ a type theory with both extensional *equality* and intensional *identification* (paths)
- ★ higher inductive types: the circle
- ★ strict types: strict booleans (new)
- ★ computational canonicity (previous Licata/Harper result established canonicity up to *judgmental equality* for 2D type theory)

RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

- ★ a type theory with both extensional *equality* and intensional *identification* (paths)
- ★ higher inductive types: the circle
- ★ strict types: strict booleans (new)
- ★ computational canonicity (previous Licata/Harper result established canonicity up to *judgmental equality* for 2D type theory)
- ★ an instance of *univalence*, not_x .


RedPRL's cubical type theory

Computational Higher-Dimensional Type Theory

[Angiuli/Harper/Wilson POPL 2017]

- ★ a type theory with both extensional *equality* and intensional *identification* (paths)
- ★ higher inductive types: the circle
- ★ strict types: strict booleans (new)
- ★ computational canonicity (previous Licata/Harper result established canonicity up to *judgmental equality* for 2D type theory)
- ★ an instance of *univalence*, not_x .
- ★ a *deterministic* and *type-free* operational semantics, amenable to cost analysis.

cubical meaning explanation



cubical meaning explanation



- ★ Computational **meaning explanations** à la Martin-Löf:
precise and coherent philosophical foundation.

cubical meaning explanation



- ★ Computational **meaning explanations** à la Martin-Löf: precise and coherent philosophical foundation.
- ★ Restricts approximately to **MLTT 1979** (**Constructive Mathematics and Computer Programming**) at dimension 0.

