

**School of Computer Science and Artificial Intelligence**

---

**Lab Assignment# 11.1**

---

<b>Program</b>	<b>:B.Tech (CSE)</b>
<b>Specialization</b>	<b>:-</b>
<b>Course Title</b>	<b>:AI Assisted Coding</b>
<b>Course Code</b>	<b>:23CS002PC304</b>
<b>Semester</b>	<b>II</b>
<b>Academic Session</b>	<b>:2025-2026</b>
<b>Name of Student</b>	<b>:R.Sai Kowshik</b>
<b>Enrollment No.</b>	<b>: 2403A51L23</b>
<b>Batch No</b>	<b>: 51</b>
<b>Date</b>	<b>:17/02/26</b>

---

**Task-1–Stack Implementation**

**Task:** Use AI to generate a Stack class with push, pop, peek, and is\_empty methods.

**Sample code:**

**class Stack:**

    Pass

**Prompt:** generate a Stack class with push, pop, peek, and is\_empty Methods and code.

**Code:**

```

1 class Stack:
2     def __init__(self):
3         """Initialize an empty stack."""
4         self.items = []
5
6     def push(self, item):
7         """Add an item to the top of the stack.
8
9         Args:
10            item: The item to be added to the stack.
11        """
12        self.items.append(item)
13
14    def pop(self):
15        """Remove and return the top item from the stack.
16
17        Returns:
18            The top item from the stack.
19
20        Raises:
21            IndexError: If the stack is empty.
22        """
23        if self.is_empty():
24            raise IndexError("Cannot pop from an empty stack")
25        return self.items.pop()
26
27    def peek(self):
28        """Return the top item from the stack without removing it.
29
30        Returns:
31            The top item from the stack.
32
33        Raises:
34            IndexError: If the stack is empty.
35        """
36        if self.is_empty():
37            raise IndexError("Cannot peek at an empty stack")
38        return self.items[-1]
39
40    def is_empty(self):
41        """Check if the stack is empty.
42
43        Returns:
44            True if the stack is empty, False otherwise.
45        """
46        return len(self.items) == 0
47
48    def size(self):
49        """Return the number of items in the stack.
50
51        Returns:
52            The number of items in the stack.
53        """
54        return len(self.items)
55
56    def __str__(self):
57        """Return a string representation of the stack.
58
59        Returns:
60            A string representation of the stack.
61        """
62        return f"Stack({self.items})"

```

```

63
64
65 # Example usage and testing
66 if __name__ == "__main__":
67     # Create a new stack
68     stack = Stack()
69
70     # Test is_empty on empty stack
71     print(f"Is stack empty? {stack.is_empty()}")
72     print(f"Stack size: {stack.size()}")
73     print()
74
75     # Push items onto the stack
76     print("Pushing items: 10, 20, 30")
77     stack.push(10)
78     stack.push(20)
79     stack.push(30)
80     print(f"Stack: {stack}")
81     print(f"Is stack empty? {stack.is_empty()}")
82     print(f"Stack size: {stack.size()}")
83     print()
84
85     # Peek at the top item
86     print(f"Peek at top: {stack.peak()}")
87     print(f"Stack after peek: {stack}")
88     print()
89
90     # Pop items from the stack
91     print("Popping items:")
92     print(f"Popped: {stack.pop()}")
93     print(f"Stack: {stack}")
94     print(f"Popped: {stack.pop()}")
95     print(f"Stack: {stack}")
96     print(f"Popped: {stack.pop()}")
97     print(f"Stack: {stack}")
98     print()
99
100     # Test is_empty after popping all items
101     print(f"Is stack empty? {stack.is_empty()}")
102     print(f"Stack size: {stack.size()}")

```

## Output:

```

Is stack empty? True
Stack size: 0

Pushing items: 10, 20, 30
Stack: Stack([10, 20, 30])
Is stack empty? False
Stack size: 3

Peek at top: 30
Stack after peek: Stack([10, 20, 30])

Popping items:
Popped: 30
Stack: Stack([10, 20])
Popped: 20
Stack: Stack([10])
Popped: 10
Stack: Stack([])

Is stack empty? True
Stack size: 0

```

## Task-2—Queue Implementation

**Task:** Use AI to implement a Queue using Python lists.

### Sample Input Code:

```
class Queue:
```

```
    pass
```

**Prompt:** complete the queue class within queue, dequeue, peek, and size methods and code.

## Code:

```

1  class Queue:
2      def __init__(self):
3          """Initialize an empty queue."""
4          self.items = []
5
6      def enqueue(self, item):
7          """Add an item to the rear of the queue.
8
9          Args:
10             item: The item to add to the queue
11          """
12          self.items.append(item)
13
14      def dequeue(self):
15          """Remove and return the front item from the queue.
16
17          Returns:
18             The front item of the queue
19
20          Raises:
21             IndexError: If the queue is empty
22          """
23          if self.is_empty():
24              raise IndexError("Cannot dequeue from an empty queue")
25          return self.items.pop(0)
26
27      def peek(self):
28          """Return the front item of the queue without removing it.
29
30          Returns:
31             The front item of the queue
32
33          Raises:
34             IndexError: If the queue is empty
35          """
36          if self.is_empty():
37              raise IndexError("Cannot peek at an empty queue")
38          return self.items[0]
39
40      def size(self):
41          """Return the number of items in the queue.
42
43          Returns:
44             The number of items in the queue
45          """
46          return len(self.items)
47
48      def is_empty(self):
49          """Check if the queue is empty.
50
51          Returns:
52             True if the queue is empty, False otherwise
53          """
54          return len(self.items) == 0
55
56
57 # Example usage and testing
58 if __name__ == "__main__":
59     # Create a new queue
60     q = Queue()
61
62     # Test enqueue
63     print("Enqueuing items: 1, 2, 3, 4, 5")
64     q.enqueue(1)
65     q.enqueue(2)
66     q.enqueue(3)
67     q.enqueue(4)
68     q.enqueue(5)
69
70     # Test size
71     print(f"Queue size: {q.size()}")
72
73     # Test peek
74     print(f"Peek at front: {q.peek()}")
75
76     # Test dequeue
77     print("Dequeuing items:")
78     while not q.is_empty():
79         print(f"Dequeued: {q.dequeue()}, Remaining size: {q.size()}")
80
81     # Test empty queue
82     print(f"Queue is empty: {q.is_empty()}")
83
84     # Test error handling
85     try:
86         q.dequeue()
87     except IndexError as e:
88         print(f"Error caught: {e}")
89
90     try:
91         q.peek()
92     except IndexError as e:
93         print(f"Error caught: {e}")

```

## Output:

```
Enqueuing items: 1, 2, 3, 4, 5
Queue size: 5
Peek at front: 1

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Enqueuing items: 1, 2, 3, 4, 5
Queue size: 5
Peek at front: 1
c
Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Peek at front: 1

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Dequeuing items:
Dequeued: 1, Remaining size: 4
Dequeued: 2, Remaining size: 3
Dequeued: 3, Remaining size: 2
Dequeued: 4, Remaining size: 1
Dequeued: 5, Remaining size: 0

Queue is empty: True
Error caught: Cannot dequeue from an empty queue
Error caught: Cannot peek at an empty queue
```

## Task-3–LinkedList

**Task:** Use Altogenerate a SinglyLinkedList with insert and display methods.

### SampleInput Code:

**class Node:**

Pass

**Prompt:** generate a Singly Linked List within insert and display methods with code.

**Code:**

```

1 class Node:
2     """Node class to represent a single node in the linked list"""
3     def __init__(self, data):
4         self.data = data # Data stored in the node
5         self.next = None # Reference to the next node
6
7
8 class SinglyLinkedList:
9     """Singly Linked List implementation with insert and display methods"""
10
11     def __init__(self):
12         self.head = None # Head pointer pointing to the first node
13
14     def insert(self, data):
15         """
16         Insert a new node at the end of the linked list
17
18         Args:
19             data: The data to be inserted into the linked list
20         """
21         new_node = Node(data)
22
23         # If the list is empty, make the new node the head
24         if self.head is None:
25             self.head = new_node
26         else:
27             # Traverse to the end of the list
28             current = self.head
29             while current.next is not None:
30                 current = current.next
31             # Insert the new node at the end
32             current.next = new_node
33
34     def insert_at_beginning(self, data):
35         """
36         Insert a new node at the beginning of the linked list
37
38         Args:
39             data: The data to be inserted into the linked list
40         """
41         new_node = Node(data)
42         new_node.next = self.head
43         self.head = new_node
44
45     def display(self):
46         """
47         Display all elements in the linked list
48         """
49         if self.head is None:
50             print("Linked List is empty")
51             return
52
53         current = self.head
54         elements = []
55         while current is not None:
56             elements.append(str(current.data))
57             current = current.next
58
59         # Display in format: data1 -> data2 -> data3 -> None
60         print(" -> ".join(elements) + " -> None")
61
62
63 # Example usage
64 if __name__ == "__main__":
65     # Create a new linked list
66     ll = SinglyLinkedList()
67
68     # Insert some elements
69     print("Inserting elements into the linked list...")
70     ll.insert(10)
71     ll.insert(20)
72     ll.insert(30)
73     ll.insert(40)
74
75     # Display the linked list
76     print("\nLinked List contents:")
77     ll.display()
78
79     # Insert at beginning
80     print("\nInserting 5 at the beginning...")
81     ll.insert_at_beginning(5)
82     ll.display()
83
84     # Create an empty list
85     print("\nCreating an empty linked list:")
86     empty_ll = SinglyLinkedList()
87     empty_ll.display()

```

**Output:**

```
Inserting elements into the linked list...
Inserting elements into the linked list...

Linked List contents:

Linked List contents:
Linked List contents:
10 -> 20 -> 30 -> 40 -> None
10 -> 20 -> 30 -> 40 -> None

Inserting 5 at the beginning...
Inserting 5 at the beginning...
5 -> 10 -> 20 -> 30 -> 40 -> None
5 -> 10 -> 20 -> 30 -> 40 -> None

Creating an empty linked list:
Linked List is empty
Linked List is empty
```

**Task-4—BinarySearch Tree (BST)**

**Task:** Use AI to create a BST within certain in-order traversal methods.

**Sample Input Code:**

```
class BS
    T: pass
```

**Prompt:** create a BST within certain in-order traversal methods and code.

**Code:**

```

1 class Node:
2     def __init__(self, key: int):
3         self.key = key
4         self.left: "Node | None" = None
5         self.right: "Node | None" = None
6
7
8 class BST:
9     def __init__(self):
10         self.root: Node | None = None
11
12     def insert(self, key: int) -> None:
13         """Insert key into the BST (duplicates go to the right)."""
14         if self.root is None:
15             self.root = Node(key)
16             return
17
18         cur = self.root
19         while True:
20             if key < cur.key:
21                 if cur.left is None:
22                     cur.left = Node(key)
23                     return
24                 cur = cur.left
25             else:
26                 if cur.right is None:
27                     cur.right = Node(key)
28                     return
29                 cur = cur.right
30
31     def inorder(self) -> list[int]:
32         """Return keys in in-order (sorted) order."""
33         result: list[int] = []
34
35         def dfs(n: Node | None) -> None:
36             if n is None:
37                 return
38             dfs(n.left)
39             result.append(n.key)
40             dfs(n.right)
41
42         dfs(self.root)
43         return result
44
45
46 if __name__ == "__main__":
47     bst = BST()
48     for x in [7, 3, 9, 1, 5, 8, 10]:
49         bst.insert(x)
50     print("In-order:", bst.inorder())

```

## Output:

```
In-order: [1, 3, 5, 7, 8, 9, 10]
```

## Task-5–HashTable

**Task:** Use AI to implement a hashtable with basic insert, search, and delete methods.

### Sample Input Code:

**Prompt:** implement a hashtable with basic insert, search, and delete methods with code.

### Code:



```

1 class HashTable:
2     """
3     Hash table using separate chaining (list of buckets).
4
5     Methods:
6     - insert(key, value): add/update a key
7     - search(key): return value or None if not found
8     - delete(key): remove key, return True if removed else False
9     """
10
11     def __init__(self, capacity: int = 8) -> None:
12         if capacity < 1:
13             raise ValueError("capacity must be >= 1")
14         self._capacity = capacity
15         self._buckets = [[] for _ in range(self._capacity)] # List[List[tuple[key, value]]]
16         self._size = 0
17
18     def _index(self, key) -> int:
19         return hash(key) % self._capacity
20
21     def _rehash(self, new_capacity: int) -> None:
22         old_items = []
23         for bucket in self._buckets:
24             old_items.extend(bucket)
25
26         self._capacity = new_capacity
27         self._buckets = [[] for _ in range(self._capacity)]
28         self._size = 0
29
30         for k, v in old_items:
31             self.insert(k, v)
32
33     def insert(self, key, value) -> None:
34         # Resize when load factor gets too high (simple rule-of-thumb)
35         if (self._size + 1) / self._capacity > 0.75:
36             self._rehash(self._capacity * 2)
37
38         idx = self._index(key)
39         bucket = self._buckets[idx]
40
41         for i, (k, _) in enumerate[Any](bucket):
42             if k == key:
43                 bucket[i] = (key, value) # update existing
44                 return
45
46         bucket.append((key, value))
47         self._size += 1
48
49     def search(self, key):
50         idx = self._index(key)
51         bucket = self._buckets[idx]
52         for k, v in bucket:
53             if k == key:
54                 return v
55         return None
56
57     def delete(self, key) -> bool:
58         idx = self._index(key)
59         bucket = self._buckets[idx]
60
61         for i, (k, _) in enumerate[Any](bucket):
62             if k == key:
63                 bucket.pop(i)
64                 self._size -= 1
65                 return True
66
67         return False
68
69     def __len__(self) -> int:
70         return self._size
71
72     def __contains__(self, key) -> bool:
73         return self.search(key) is not None
74
75     def __repr__(self) -> str:
76         return f"HashTable(size={self._size}, capacity={self._capacity})"
77
78
79 if __name__ == "__main__":
80     ht = HashTable()
81     ht.insert("name", "Alice")
82     ht.insert("age", 20)
83     ht.insert("age", 21) # update
84
85     print(ht) # HashTable(...)
86     print(ht.search("name")) # Alice
87     print(ht.search("age")) # 21
88     print(ht.search("x")) # None
89
90     print(ht.delete("age")) # True
91     print(ht.delete("age")) # False
92     print(len(ht)) # 1

```

**Output:**

```
HashTable(size=2, capacity=8)
Alice
21
None
HashTable(size=2, capacity=8)
Alice
21
None
21
None
True
False
1
True
False
1
False
1
```

## Task-6–Graph Representation

**Task:** Use AI to implement a graph using an adjacency list. Sample

**Input Code:**

**Class**

**Graph:**

pass

**Prompt:**

implement a graph using an adjacency list with code

**Code:**

```

1 class Graph:
2     """
3     Graph implemented using an adjacency list.
4
5     - By default the graph is undirected.
6     - Set directed=True for a directed graph.
7     """
8
9     def __init__(self, directed: bool = False):
10         self.directed = directed
11         # adjacency list: vertex -> set of neighbor vertices
12         self.adj: dict[object, set[object]] = {}
13
14     def add_vertex(self, v: object) -> None:
15         """Add a vertex if it doesn't already exist."""
16         if v not in self.adj:
17             self.adj[v] = set[object]()
18
19     def add_edge(self, u: object, v: object) -> None:
20         """Add an edge u -> v (and v -> u if undirected)."""
21         self.add_vertex(u)
22         self.add_vertex(v)
23         self.adj[u].add(v)
24         if not self.directed:
25             self.adj[v].add(u)
26
27     def remove_edge(self, u: object, v: object) -> None:
28         """Remove an edge u -> v (and v -> u if undirected), if present."""
29         if u in self.adj:
30             self.adj[u].discard(v)
31         if not self.directed and v in self.adj:
32             self.adj[v].discard(u)
33
34     def remove_vertex(self, v: object) -> None:
35         """Remove a vertex and all edges incident to it."""
36         if v not in self.adj:
37             return
38
39         # Remove edges from neighbors to v
40         for n in list(self.adj[v]):
41             self.remove_edge(v, n)
42
43         # In directed graphs, also remove incoming edges to v
44         if self.directed:
45             for u in self.adj:
46                 self.adj[u].discard(v)
47
48         del self.adj[v]
49
50     def neighbors(self, v: object) -> list[object]:
51         """Return neighbors of v as a sorted list when possible."""
52         if v not in self.adj:
53             return []
54         try:
55             return sorted(self.adj[v])
56         except TypeError:
57             return list(self.adj[v])
58
59     def bfs(self, start: object) -> list[object]:
60         """Breadth-first traversal order starting from start."""
61         if start not in self.adj:
62             return []
63
64         visited = {start}
65         queue = [start]
66         order: list[object] = []
67
68         while queue:
69             v = queue.pop(0)
70             order.append(v)
71             for n in self.neighbors(v):
72                 if n not in visited:
73                     visited.add(n)
74                     queue.append(n)
75
76         return order
77
78     def dfs(self, start: object) -> list[object]:
79         """Depth-first traversal order starting from start."""
80         if start not in self.adj:
81             return []
82
83         visited: set[object] = set[object]()
84         order: list[object] = []
85
86         def _visit(v: object) -> None:
87             visited.add(v)
88             order.append(v)
89             for n in self.neighbors(v):
90                 if n not in visited:
91                     _visit(n)
92
93         _visit(start)
94         return order
95
96     def __str__(self) -> str:
97         lines = []
98         for v in self.adj:
99             lines.append(f"{v} -> {self.neighbors(v)}")
100         return "\n".join(lines)
101
102 if __name__ == "__main__":
103     g = Graph(directed=False) # change to True for a directed graph
104     g.add_edge("A", "B")
105     g.add_edge("A", "C")
106     g.add_edge("B", "D")
107     g.add_edge("C", "D")
108     g.add_edge("D", "E")
109
110     print("Adjacency list:")
111     print(g)
112     print()
113     print("BFS from A:", g.bfs("A"))
114     print("DFS from A:", g.dfs("A"))

```

### Output:

```
Adjacency list:
A -> ['B', 'C']
B -> ['A', 'D']
Adjacency list:
A -> ['B', 'C']
B -> ['A', 'D']
A -> ['B', 'C']
B -> ['A', 'D']
B -> ['A', 'D']
C -> ['A', 'D']
D -> ['B', 'C', 'E']
E -> ['D']

BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
D -> ['B', 'C', 'E']
E -> ['D']

BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
E -> ['D']

BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
BFS from A: ['A', 'B', 'C', 'D', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
DFS from A: ['A', 'B', 'D', 'C', 'E']
```

## Task-7–Priority Queue

**Task:** Use `AI` to implement a priority queue using Python's `heapq` module.

### Sample Input Code:

**Class Priority**

**Queue:** pass

### Prompt:

implement a priority queue using Python's `heapq` module with code

### Code:

```

1 import heapq
2 from itertools import count
3
4 class PriorityQueue:
5     """
6     Min-priority queue by default (smaller priority value = served first).
7     For max-priority behavior, push with -priority.
8     """
9     def __init__(self):
10         self._heap = []
11         self._seq = count[int]() # tie-breaker for equal priorities (FIFO)
12
13     def push(self, item, priority: int):
14         heapq.heappush(self._heap, (priority, next(self._seq), item))
15
16     def pop(self):
17         if not self._heap:
18             raise IndexError("pop from empty PriorityQueue")
19         priority, _, item = heapq.heappop(self._heap)
20         return item, priority
21
22     def peek(self):
23         if not self._heap:
24             raise IndexError("peek from empty PriorityQueue")
25         priority, _, item = self._heap[0]
26         return item, priority
27
28     def __len__(self):
29         return len(self._heap)
30
31     def empty(self):
32         return len(self._heap) == 0
33
34
35 if __name__ == "__main__":
36     pq = PriorityQueue()
37     pq.push("low", 5)
38     pq.push("urgent", 1)
39     pq.push("medium", 3)
40     pq.push("also urgent (arrives later)", 1)
41
42     while not pq.empty():
43         item, pr = pq.pop()
44         print(pr, item)
45
46     # Max-priority example (bigger number = served first):
47     maxpq = PriorityQueue()
48     for item, pr in [("A", 10), ("B", 2), ("C", 10)]:
49         maxpq.push(item, -pr) # negate priority
50
51     print("max first:", maxpq.pop()) # returns (item, neg_priority)

```

## Output:

```

1 urgent
1 also urgent (arrives later)
3 medium
5 low
max first: ('A', -10)

```

## Task-8–Deque

**Task:** Use `collections.deque` to implement a double-ended queue.

### Sample Input Code:

**Class**

**DequeDS:**

pass

### Prompt:

implement a double-ended queue using `collections.deque` with code

### Code:

```

1  from __future__ import annotations
2
3  from collections import deque
4  from typing import Deque, Generic, Iterator, Optional, TypeVar
5
6  T = TypeVar("T")
7
8
9  class DequeDS(Generic[T]):
10     """
11     Double-ended queue (deque) implemented using collections.deque.
12     Supports O(1) append/pop operations on both ends.
13     """
14
15     def __init__(self, items: Optional[Iterator[T]] = None) -> None:
16         self._dq: Deque[T] = deque[T](items or [])
17
18     # --- Add operations ---
19     def add_front(self, item: T) -> None:
20         """Insert item at the front (left)."""
21         self._dq.appendleft(item)
22
23     def add_rear(self, item: T) -> None:
24         """Insert item at the rear (right)."""
25         self._dq.append(item)
26
27     # --- Remove operations ---
28     def remove_front(self) -> T:
29         """Remove and return the front (left) item."""
30         if self.is_empty():
31             raise IndexError("remove_front from empty deque")
32         return self._dq.popleft()
33
34     def remove_rear(self) -> T:
35         """Remove and return the rear (right) item."""
36         if self.is_empty():
37             raise IndexError("remove_rear from empty deque")
38         return self._dq.pop()
39
40     # --- Peek operations ---
41     def peek_front(self) -> T:
42         """Return the front (left) item without removing it."""
43         if self.is_empty():
44             raise IndexError("peek_front from empty deque")
45         return self._dq[0]
46
47     def peek_rear(self) -> T:
48         """Return the rear (right) item without removing it."""
49         if self.is_empty():
50             raise IndexError("peek_rear from empty deque")
51         return self._dq[-1]
52
53     # --- Utility ---
54     def is_empty(self) -> bool:
55         return len(self._dq) == 0
56
57     def size(self) -> int:
58         return len(self._dq)
59
60     def clear(self) -> None:
61         self._dq.clear()
62
63     def __len__(self) -> int:
64         return len(self._dq)
65
66     def __iter__(self) -> Iterator[T]:
67         return iter(self._dq)
68
69     def __repr__(self) -> str:
70         return f"DequeDS({list[T](self._dq)!r})"
71
72
73 if __name__ == "__main__":
74     d = DequeDS[int]()
75     d.add_front(10)    # [10]
76     d.add_rear(20)    # [10, 20]
77     d.add_front(5)    # [5, 10, 20]
78     print("Deque:", d)
79     print("Front:", d.peek_front())
80     print("Rear:", d.peek_rear())
81     print("Remove front:", d.remove_front()) # 5
82     print("Remove rear:", d.remove_rear())  # 20
83     print("Deque now:", d)

```

**Output:**

```
Deque: DequeDS([5, 10, 20])
Front: 5
Rear: 20
Remove front: 5
Remove rear: 20
Deque now: DequeDS([10])
```

## **Task-9 Real-Time Application Challenge—Choose the Right Data Structure**

**Prompt:**

Solve this clearly and concisely.

Design a Campus Resource Management System code with:

1. Student Attendance Tracking
2. Event Registration System
3. Library Book Borrowing
4. Bus Scheduling System
5. Cafeteria Order Queue

-----

Choose the best data structure for each feature from:

Stack, Queue, Priority Queue, Linked List, BST, Graph, Hash Table, Deque

**Output as a table:**

Feature | Data Structure | 2–3 sentence justification

**Code:**



```

1  # from typing import annotations
2
3  # from dataclasses import dataclass
4  # from collections import deque
5  # from typing import Dict, List, Optional, Set, Tuple
6
7
8  # =====
9  # 1) Student Attendance Tracking (Mock Task)
10 # =====
11
12 class AttendanceTracker:
13     """
14     Data structure: Mock Value (Python dict)
15     """
16     def __init__(self) -> None:
17         self._records: Dict[str, Dict[str, bool]] = {}
18
19     def mark(self, student_id: str, date: str, present: bool) -> None:
20         self._records.setdefault(student_id, {})[date] = present
21
22     def is_present(self, student_id: str, date: str) -> Optional[bool]:
23         return self._records.get(student_id, {}).get(date)
24
25     def attendance_percent(self, student_id: str) -> float:
26         days = self._records.get(student_id, {})
27         if not days:
28             return 0.0
29         present_count = sum(1 for v in days.values() if v)
30         return (present_count / len(days)) * 100.0
31
32 # =====
33 # 2) Event Registration System (Bonus)
34 # =====
35
36 class EventRegistrationSystem:
37     """
38     Data structure: Queue (collections.deque)
39     - FIFO registration requests = FIFO unenroll.
40     """
41     @dataclass(frozen=True)
42     class Event:
43         event_id: str
44         name: str
45         capacity: int
46
47     def __init__(self) -> None:
48         self._events: Dict[str, EventRegistrationSystem.Event] = {}
49         self._requests: Dict[str, Deque[str]] = {} # event_id -> queue(student_id)
50         self._unenroll: Dict[str, Deque[str]] = {} # event_id -> queue(student_id)
51
52     def create_event(self, event_id: str, name: str, capacity: int) -> None:
53         if capacity < 0:
54             raise ValueError("Capacity must be >= 0")
55         self._events[event_id] = self.Event(event_id, name, capacity)
56         self._requests.setdefault(event_id, deque())
57         self._unenroll.setdefault(event_id, deque())
58
59     def request_registration(self, event_id: str, student_id: str) -> None:
60         self._requests[event_id].append(student_id)
61         if student_id in self._unenroll[event_id]:
62             return
63         if student_id in self._requests[event_id] or student_id in self._unenroll[event_id]:
64             self._requests[event_id].append(student_id)
65
66     def process_next_request(self, event_id: str) -> Optional[str]:
67         """Process the pending request in FIFO order.
68         Returns the student_id that got confirmed (or None if no request)."""
69         self._process_event(event_id)
70         q = self._requests[event_id]
71         if not q:
72             return None
73         student_id = q.popleft()
74         if len(self._unenroll[event_id]) < self._events[event_id].capacity:
75             self._unenroll[event_id].append(student_id)
76             return student_id
77         self._unenroll[event_id].append(student_id)
78         return None
79
80     def cancel_registration(self, event_id: str, student_id: str) -> None:
81         self._process_event(event_id)
82         if student_id in self._unenroll[event_id]:
83             self._unenroll[event_id].remove(student_id)
84             self._process_from_unenroll(event_id)
85             return
86         self._requests[event_id].remove(student_id)
87         self._process_from_requests(event_id, student_id)
88
89     def cancel_event(self, event_id: str) -> List[str]:
90         self._process_event(event_id)
91         return sorted(self._unenroll[event_id])
92
93     def unenroll_list(self, event_id: str) -> List[str]:
94         self._process_event(event_id)
95         return sorted(self._unenroll[event_id])
96
97     def process_from_unenroll(self, event_id: str) -> None:
98         """If len(self._unenroll[event_id]) > self._events[event_id].capacity:
99         return"""
100         u1 = self._unenroll[event_id]
101         while u1 and len(self._unenroll[event_id]) < self._events[event_id].capacity:
102             self._unenroll[event_id].popleft()
103
104     def _process_from_requests(self, event_id: str) -> None:
105         """Process requests from the queue until capacity is reached for student_id.
106         If not q:
107             return
108         reqs = deque()
109         for s in q:
110             if s != student_id:
111                 reqs.append(s)
112         self._requests[event_id] = reqs
113
114     def _process_event(self, event_id: str) -> None:
115         """If event_id not in self._events:
116             raise ValueError(f"Unknown event_id: {event_id}")"""
117
118 # =====
119 # 3) Library Book Borrowing (BONUS)
120 # =====
121
122 @dataclass
123 class Book:
124     title: str
125     author: str
126     total_copies: int
127     available_copies: int
128
129 class BookBorrowing:
130     def __init__(self, library: List[Book]) -> None:
131         self.library = library
132         self.borrowed = {}
133         self.available_copies = {}
134         self.borrowed.setdefault(title, 0)
135         self.available_copies.setdefault(title, 0)
136
137     def borrow_book(self, title: str, copies: int) -> None:
138         if copies < 0:
139             raise ValueError("Copies must be >= 0")
140         existing = self._find_book(title)
141         if existing:
142             existing.available_copies -= copies
143             existing.borrowed_copies += copies
144             return
145         book = Book(title, title, 1, 1, 1)
146         self.library.append(book)
147         self.borrowed.setdefault(title, 0)
148         self.available_copies.setdefault(title, 0)
149         self.borrowed[title] += copies
150         self.available_copies[title] -= copies
151
152     def find_book(self, title: str) -> Optional[Book]:
153         for book in self.library:
154             if book.title == title:
155                 return book
156         return None
157
158     def return_book(self, title: str, copies: int) -> None:
159         existing = self._find_book(title)
160         if existing:
161             existing.available_copies += copies
162             existing.borrowed_copies -= copies
163             return
164         book = Book(title, title, 1, 1, 1)
165         self.library.append(book)
166         self.borrowed.setdefault(title, 0)
167         self.available_copies.setdefault(title, 0)
168         self.borrowed[title] -= copies
169         self.available_copies[title] += copies
170
171     def is_book_available(self, title: str, copies: int) -> bool:
172         existing = self._find_book(title)
173         if existing:
174             return existing.available_copies >= copies
175         return False
176
177     def total_copies(self, title: str) -> int:
178         existing = self._find_book(title)
179         if existing:
180             return existing.total_copies
181         return 0
182
183     def total_borrowed(self, title: str) -> int:
184         existing = self._find_book(title)
185         if existing:
186             return existing.borrowed_copies
187         return 0
188
189     def total_available(self, title: str) -> int:
190         existing = self._find_book(title)
191         if existing:
192             return existing.available_copies
193         return 0
194
195     def total_copies_and_borrowed(self, title: str) -> Tuple[int, int]:
196         existing = self._find_book(title)
197         if existing:
198             return existing.total_copies, existing.borrowed_copies
199         return 0, 0
200
199
200

```



[illegible]

## Output:

```
Attendance S1 %: 50.0
Confirmed E100: ['S1', 'S2']
Waitlist E100: ['S3']
After cancel S2, confirmed: ['S1', 'S3']
Borrow Fluent Python: True
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Attendance S1 %: 50.0
Confirmed E100: ['S1', 'S2']
Waitlist E100: ['S3']
After cancel S2, confirmed: ['S1', 'S3']
Borrow Fluent Python: True
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Waitlist E100: ['S3']
After cancel S2, confirmed: ['S1', 'S3']
Borrow Fluent Python: True
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Borrow Fluent Python again: False
Catalog in order: [('9780134685991', 2), ('9781492051367', 0)]
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Serve order: CafeteriaOrder(order_id=2, student_id='S2', item='Coffee', priority=2)
Shortest bus path Hostel->Library: ['Hostel', 'Cafeteria', 'Library'] minutes: 9
Serve order: CafeteriaOrder(order_id=2, student_id='S2', item='Coffee', priority=2)
Serve order: CafeteriaOrder(order_id=2, student_id='S2', item='Coffee', priority=2)
Serve order: CafeteriaOrder(order_id=3, student_id='S3', item='Burger', priority=1)
Serve order: CafeteriaOrder(order_id=3, student_id='S3', item='Burger', priority=1)
```

## Task-10:SmartE-CommercePlatform– DataStructure Prompt:

Solve this clearly and concisely.

Design a SmartE-Commerce Platform with:

ShoppingCartManagement–Add/remove products dynamically

Order Processing System – Process orders in placement order

Top-Selling Products Tracker – Rank products by sales count

Product Search Engine – Fast lookup using product ID

DeliveryRoutePlanning–Connect warehouses and delivery locations

Choose the most appropriate data structure for each feature from:

Stack, Queue, Priority Queue, Linked List, BST, Graph, HashTable, Deque

## Output as a table:

Feature | Data Structure | 2–3 sentence justification

## Code:

```

1 from collections import deque
2 import heapq
3 from typing import Dict, List, Tuple, Optional
4
5
6 # -----
7 # Product model
8 # -----
9 class Product:
10     def __init__(self, product_id: int, name: str, price: float):
11         self.id = product_id
12         self.name = name
13         self.price = price
14
15     def __repr__(self):
16         return f"Product(id={self.id}, name='{self.name}', price={self.price})"
17
18
19 # -----
20 # Product Search Engine (Hash Table)
21 # -----
22 class ProductSearchEngine:
23     def __init__(self):
24         # Hash Table: product_id -> Product
25         self.products: Dict[int, Product] = {}
26
27     def add_product(self, product: Product):
28         self.products[product.id] = product
29
30     def get_product(self, product_id: int) -> Optional[Product]:
31         return self.products.get(product_id)
32
33     def remove_product(self, product_id: int):
34         self.products.pop(product_id, None)
35
36
37 # -----
38 # Shopping Cart (Linked List)
39 # -----
40 class CartNode:
41     def __init__(self, product: Product, quantity: int):
42         self.product = product
43         self.quantity = quantity
44         self.next: Optional["CartNode"] = None
45
46
47 class ShoppingCart:
48     def __init__(self):
49         self.head: Optional[CartNode] = None
50
51     def add_product(self, product: Product, quantity: int = 1):
52         """
53         If product already exists in the list, increase quantity.
54         Otherwise, add new node at the front (O(1) insertion).
55         """
56         node = self.head
57         while node:
58             if node.product.id == product.id:
59                 node.quantity += quantity
60                 return
61             node = node.next
62
63         new_node = CartNode(product, quantity)
64         new_node.next = self.head
65         self.head = new_node
66
67     def remove_product(self, product_id: int, quantity: int = None):
68         """
69         Remove some or all quantity of a product.
70         If quantity is None or reaches 0, remove the node.
71         """
72         prev = None
73         node = self.head
74
75         while node:
76             if node.product.id == product_id:
77                 if quantity is None or node.quantity <= quantity:
78                     # delete the node
79                     if prev:
80                         prev.next = node.next
81                     else:
82                         self.head = node.next
83                 else:
84                     node.quantity -= quantity
85                 return
86             prev = node
87             node = node.next
88
89     def list_items(self) -> List[Tuple[Product, int]]:
90         result = []
91         node = self.head
92         while node:
93             result.append((node.product, node.quantity))
94             node = node.next
95         return result
96
97     def total_price(self) -> float:
98         return sum(node.product.price * node.quantity
99                    for node in self._iter_nodes())
100
101     def _iter_nodes(self):
102         node = self.head
103         while node:
104             yield node
105             node = node.next
106
107
108 # -----
109 # Order Processing System (Queue)
110 # -----
111 class Order:
112     _next_id = 1
113
114     def __init__(self, cart_snapshot: List[Tuple[Product, int]]):
115         self.id = Order._next_id
116         Order._next_id += 1
117         self.items = cart_snapshot # list of (Product, quantity)
118
119     def __repr__(self):
120         return f"Order(id={self.id}, items=[{(p.id, q) for p, q in self.items}])"
121
122
123 class OrderProcessingSystem:
124     def __init__(self):
125         # Queue of orders (FIFO)
126         self.queue: deque[Order] = deque.from_iter([])
127
128     def place_order(self, cart: ShoppingCart) -> Order:
129         order = Order(cart.list_items())
130         self.queue.append(order)
131         return order
132
133     def process_next_order(self) -> Optional[Order]:
134         if not self.queue:
135             return None
136         return self.queue.popleft()
137
138     def pending_orders(self) -> int:
139         return len(self.queue)
140
141
142 # -----
143 # Top-Selling Products Tracker (Priority Queue / Max-Heap)
144 # -----
145 class TopSellingProductTracker:
146     def __init__(self):
147         # product_id -> sales_count
148         self.sales: Dict[int, int] = {}
149         # priority queue entries (product_id, sales_count, product_id)
150         self.heap: List[Tuple[int, int]] = []
151
152     def record_sale(self, product_id: int, quantity: int = 1):
153         self.sales[product_id] = self.sales.get(product_id, 0) + quantity
154         # Push new priority entry; lazy update (we'll verify against self.sales on pop)
155         heapq.heappush(self.heap, (-self.sales[product_id], product_id))
156
157     def top_k(self, k: int) -> List[Tuple[int, int]]:
158         """
159         Returns list of (product_id, sales_count) for top k products.
160         Uses lazy removal from the heap to keep it consistent.
161         """

```

```

162     result = []
163     seen = set[bool]()
164
165     while self.heap and len(result) < k:
166         neg_sales, pid = heapq.heappop(self.heap)
167         current_sales = self.sales.get(pid, 0)
168
169         if current_sales == -neg_sales and pid not in seen:
170             result.append(pid, current_sales)
171             seen.add(pid)
172
173     # push back the elements we popped that are still valid
174     for pid in seen:
175         heapq.heappush(self.heap, (-self.sales[pid], pid))
176
177     return result
178
179
180 # -----
181 # Delivery Route Planning (Graph + Dijkstra)
182 # -----
183 class DeliveryRoutePlanner:
184     def __init__(self):
185         # Graph as adjacency list: node -> list of (neighbor, distance)
186         self.graph: Dict[str, List[Tuple[float, float]]] = {}
187
188     def add_location(self, name: str):
189         if name not in self.graph:
190             self.graph[name] = []
191
192     def add_route(self, from_loc: str, to_loc: str, distance: float, bidirectional: bool = True):
193         self.add_location(from_loc)
194         self.add_location(to_loc)
195         self.graph[from_loc].append((to_loc, distance))
196         if bidirectional:
197             self.graph[to_loc].append((from_loc, distance))
198
199     def shortest_path(self, start: str, end: str) -> Tuple[float, List[str]]:
200         """
201         Dijkstra's algorithm: returns (distance, path).
202         Distance is float('inf') if no path exists.
203         """
204         if start not in self.graph or end not in self.graph:
205             return float('inf'), []
206
207         # min-heap: (distance, node, path)
208         heap = [(0.0, start, [start])]
209         visited = set[bool]()
210
211         while heap:
212             dist, node, path = heapq.heappop(heap)
213             if node in visited:
214                 continue
215             visited.add(node)
216
217             if node == end:
218                 return dist, path
219
220             for neighbor, weight in self.graph[node]:
221                 if neighbor not in visited:
222                     heapq.heappush(heap, (dist + weight, neighbor, path + [neighbor]))
223
224         return float('inf'), []
225
226
227 # -----
228 # Example usage
229 # -----
230 if __name__ == "__main__":
231     # Product search engine
232     search_engine = ProductSearchEngine()
233     p1 = Product(1, "Laptop", 1000.0)
234     p2 = Product(2, "Phone", 500.0)
235     p3 = Product(3, "Headphones", 100.0)
236     for p in (p1, p2, p3):
237         search_engine.add_product(p)
238
239     # Shopping cart
240     cart = ShoppingCart()
241     cart.add_product(search_engine.get_product(1), 1)
242     cart.add_product(search_engine.get_product(2), 2)
243     cart.add_product(search_engine.get_product(1), 1)
244     cart.remove_product(3, 1) # remove 1 headphone
245
246     print("Cart items:", cart.list_items())
247     print("Total price:", cart.total_price())
248
249     # Order processing
250     ops = OrderProcessingSystem()
251     order1 = ops.place_order(cart)
252     print("Placed order:", order1)
253     print("Pending orders:", ops.pending_orders())
254     processed = ops.process_next_order()
255     print("Processed order:", processed)
256     print("Pending orders:", ops.pending_orders())
257
258     # Top-selling products
259     tracker = TopSellingProductsTracker()
260     tracker.record_sale(1, 10) # Laptop sold 10
261     tracker.record_sale(2, 5) # Phone sold 5
262     tracker.record_sale(3, 7) # Headphones sold 7
263     print("Top 2 products (id, sales):", tracker.top_k(2))
264
265     # Delivery route planner
266     planner = DeliveryRoutePlanner()
267     planner.add_route("WarehouseA", "City1", 10.0)
268     planner.add_route("WarehouseA", "City2", 20.0)
269     planner.add_route("City1", "City2", 5.0)
270     planner.add_route("City2", "City3", 7.0)
271
272     dist, path = planner.shortest_path("WarehouseA", "City3")
273     print("Shortest route WarehouseA -> City3:", path, "distance:", dist)

```

## Output:

```

Cart items: [(Product(id=3, name='Headphones', price=100.0), 2), (Product(id=2, name='Phone', price=500.0), 2), (Product(id=1, name='Laptop', price=1000.0), 1)]
Total price: 2200.0
Placed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 1
Processed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 0
Top 2 products (id, sales): [(1, 10), (3, 7)]
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0
PS C:\2403A51L03\3-2\AI_A_C\cursor AI>

Total price: 2200.0
Placed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 1
Processed order: Order(id=1, items=[(3, 2), (2, 2), (1, 1)])
Pending orders: 0
Top 2 products (id, sales): [(1, 10), (3, 7)]
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0
Pending orders: 0
Top 2 products (id, sales): [(1, 10), (3, 7)]
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0
Shortest route WarehouseA -> City3: ['WarehouseA', 'City1', 'City2', 'City3'] distance: 22.0

```