



**Corso di Laurea Magistrale in Ingegneria Informatica**  
**Università degli Studi di Parma**

---

## **Exercise 2: Programming Tools in Linux/UNIX**

Sistemi Operativi ed in Tempo Reale  
AA 2021/2022



# Exercise 2

---

- Random number generation
- Strings in C
- Pointers
- Structure
- Socket
- Linked List



# Pseudo-Random Numbers

---

- **rand()**: function for generating random number with uniform distribution on interval  $[0, \text{RAND\_MAX}]$
- **srand()** to set the seed of a sequence
  - sequences with the same seed are equal
  - usually initialized with time from libs *time.h* and *stdlib.h*

```
#include <stdlib.h>
#include <time.h>
...
int i;
...
srand(time(NULL));
i = rand() % 100 + 1; // genera un numero compreso tra 1 e 100
```



# Strings

---

- No predefined string type in C language
- String is an array of characters terminated by '\0' (ASCII code equal to 0)
- A string of N chars is represented by  
`char str[N+1]`
- N is the maximum length of the string not to exceed the array limit
  - a string with  $L < N$  chars is s.t. `str[L] = '\0'`
  - chars after L position have undefined values



# Strings

---

- Examples of string initialization

```
char S[6] = {'p','r','o','v','a','\0'}; // as an array of char
```

```
char S[6] = "prova"; // as a string: implicit '\0'
```

- Example of computation of string length

```
char S[6] = "prova";
```

```
int len=0;
```

```
while(S[len] != '\0')
```

```
    len++;
```

```
printf("String %s is long %d", S, len);
```



# Strings

---

- Reading string with **scanf()**
- **scanf()** requires pointers, but string have pointer form
  - first argument is a format string: string are identified by “%s”
  - second argument is a pointer

`scanf("%s",S);`

- Unfortunately, with **scanf()** strings are terminated at first occurrence of blank char “ ”
- Issues with strings longer than the string limit: they may not be terminated by a ‘\0’



# Strings

---

## ***char \*gets(char \*S)***

- Puts into the string pointed by S the chars read from STDIN until a char '\n'
- String is terminated by '\0'
- Returns either the pointer to the first char in the string or NULL when reading fails

### *Example:*

```
char string [256];  
printf ("Insert your full address: ");  
gets (string);  
printf ("Your address is: %s\n", string);
```



# Strings

---

## ***Standard functions***

`#include <string.h>`

- `int strcmp(char *string1, char *string2)` – Compare two strings string1 e string2
- `char *strcpy(char *string1, char *string2)` - Copy string2 in string1
- `int strlen(char *string)` – Computes the length of a string
- `char *strncat(char *string1, char *string2, size_t n)` – Add n chars of string2 to string1
- `int strncmp(char *string1, char *string2, size_t n)` – Compare only the first "n" chars of two strings
- `char *strncpy(char *string1, char *string2, size_t n)` - Copy only the first "n" chars of string2 in string1.

Example

```
char str[MAX_SIZE];  
strcpy(str, "esempio di stringa");
```





# Strings

---

- No assigning of strings, only initializations
- **Invalid** instructions: string must be copied

```
char greeting[10];  
greeting = "Hello";
```

- **Valid** instruction initialization

```
char greeting[10] = "Hello";
```

See example: `stringhe_esempi_c.c`



# Pointers and Dynamic Memory Allocation

---

- **Pointers:** variable storing the memory address of another variable
- Pointers can access the value of the pointed variable
- **Pointer declaration:** pointer type is the type of pointed variable

```
int* pi;    /* pointer to an integer variable */
```

- **Deferencing:** accessing the variable value

```
*pi = 10;   /* set the value of variable pointed by pi */
```

– pointer must be set to a correct address!



# Pointer: Getting the address


- Address of a variable obtained by operator '&'

```
int i, *pi;  
i = 42;           /* value assignment */  
pi = &i;          /* pi points to address of i */
```



```
*pi = 3;          /* changed the value of i */
```






# Memory Allocation/Deallocation

- Pointers support dynamic memory allocation
- **malloc()** function for allocation
  - reserve space for allocating the desired type, e.g. float
  - returns the address of the allocated memory

```
float* pf;      /* uninitialized pointer to float */  
pf = (float*)malloc(sizeof(float));
```







# Memory Leak

- Allocated area that are not pointed and cannot be used anymore

- Example:

```
pf1 = (float*)malloc(sizeof(float));  
pf2 = (float*)malloc(sizeof(float));  
pf1 = pf2;
```

- No reference to the area originally pointed by pf1!
  - no access to the area
- The unreferenced memory area is “garbage”






# Dangling Pointer

- Pointers pointing to an invalid memory area

- Memory area deallocated


```
free(punfloat);  
*punfloat = 1.0f;    /*error!*/
```



- Memory area not yet allocated

```
float* punfloat1;    /* undefined address */  
*punfloat = 1.0f;    pf
```

????





# Typedef

---

- Redefined label of an existing type
  - Hide the real type and add abstraction to the code
  - Avoid repetition of keyword *struct* (only for C)

• Syntax: **typedef** *ExistingType* *NewType*;

```
typedef int MyLabel;
```

```
typedef struct Node* LIST; /* pointer to first list item  
                           seen as a whole list*/
```

- Note: still used in C++, but now keyword **using** is recommended

```
using NewType = ExistingType;
```



# Structured Types

---

- Composite data types consisting of heterogeneous variables

- **field**: each variable of the structure
- keyword **struct**

- Example:

```
struct Person {  
    int year;  
    double height;  
    char name[10];  
};  
  
struct Person p1;  
p1.height = 178.2;
```

- Anonymous struct + typedef

```
typedef struct {  
    int year;  
    double height;  
    char name[10];  
} Person;  
  
Person p1;
```





# Structured Types

---

- Pointers to structured data and access to fields

```
typedef Person* PersonPtr;
```

```
Person alice;
```

```
PersonPtr p;
```

```
.....
```

```
p = &alice;
```

```
(*p).age=5;
```

```
p->height=180.0;
```



# Socket

---


- Software interface for communicating among processes
- It associates a channel to an integer **file descriptor**
- We focus on socket type STREAM for TCP
- **Client-Server**
  - Server is active and waiting for request from clients
  - Client connects to server
  - Client and server can exchange data on established connections
- Server supports *many* simultaneous connections



# Socket

---

- API in C sockets (inherited from Berkeley sockets 1983)
  - **socket**: create a socket on a given domain, type and protocol
  - **bind**: assign a name/address to the socket
  - **listen**: set maximum number of accepted simultaneous connections
  - **accept**: server socket accept incoming connection from client (blocking API!)
  - **connect**: client socket request to connect to server
  - **getsockname**: read local address of a socket
  - **close**: close a file descriptor associated to a socket (used also for files, other primitives, etc.)
  - **send**: to send data; it is an alias of *write()*
  - **recv**: to receive data (blocking API!); it is an alias of *read()*



# Socket: Client

---

## •Client: setting a connection

```
#include <unistd.h>
#include <netdb.h>

struct sockaddr_in serv_addr;
struct hostent* server;
char* host_name = "127.0.0.1"; /* address of the server as string*/
int port = 8000;
if ((server = gethostbyname(host_name)) == 0 ) { /* address */
    perror("Error resolving local host\n"); exit(1);
}
bzero(&serv_addr, sizeof(serv_addr));
serv_addr.sin_family = AF_INET;
serv_addr.sin_addr.s_addr = ((struct in_addr *) (server->h_addr))->s_addr;
serv_addr.sin_port = htons(port); /* htons() handle little and
                                   big endians*/
```




# Socket: Client

---

- **Client:** setting a connection

```
int sockfd = socket(PF_INET, SOCK_STREAM, 0);  /* file descriptor sockfd */
if ( sockfd == -1 ) {
    ... /* error */
}
if (connect(sockfd, (void*)&serv_addr, sizeof(serv_addr) ) == -1) {
    ... /* error */
}
```

- Hence after connect is established: communication with **send()** and **recv()** until the *sockfd* is closed



# Socket: Server


---

- Server: opening and waiting for client connections
  - this part is similar for server

```
#include <unistd.h>
#include <netdb.h>

struct sockaddr_in serv_addr;
struct sockaddr_in cli_addr;
int sockfd = socket(PF_INET, SOCK_STREAM, 0);
if ( sockfd == -1 ) { ... }
bzero(&serv_addr, sizeof(serv_addr));
serv_addr.sin_family = AF_INET;
serv_addr.sin_addr.s_addr = INADDR_ANY; /* the address is the local one */
serv_addr.sin_port = htons(port); /* htons() little and big endians*/

/* bind() associates the address to the socket */
if (bind(sockfd, (struct sockaddr *)&serv_addr, sizeof(serv_addr)) == -1){
    ...
}
```



# Socket: Server

---

```
/* maximum number of connection kept in the socket queue*/  
if (listen( sockfd, 20 ) == -1) { ... }  
socklen_t address_size = sizeof( cli_addr );
```

- Main server **loop** (infinite in this case)

```
while(1) {  
    /* new connection acceptance with a novel socket/file descriptor */  
    int newsockfd = accept( sockfd, (struct sockaddr *)&cli_addr, &address_size  
);  
    if (newsockfd == -1) { ... }  
    /* send/recv until close;  
        newsockfd must be stored to communicate on connection */  
}
```




# Fork

- UNIX/Linux API for starting a new process

```
#include <unistd.h>
int fork(void);
```

- An identical (child) process is created: same code and memory content of parent process
- Only difference: the **return value** of `fork()` is **0** for child and **PID** value of the child for the parent








# Fork

---

- The return value can be used to differentiate the code executed by father and child processes

```
int ret = fork();  
if (ret == 0) {  
    /* code executed by child */  
}  
else {  
    /* code executed by father */  
}
```

- After the fork() the two processes are independent, i.e. do not share memory



# Socket

## •Concurrent server:

- not blocked by servicing a client
- creates a child process to every request

```
int main(int argc, char *argv[]) {  
    ...  
    /* Initialize socket */  
    while (1) {  
        ...  
        if ( (conn_fd = accept(list_fd, (struct sockaddr *)&client, &len)) <0 ) {  
            perror("accept error");  
            exit(-1);  
        }  
        /* Fork to handle connection */  
        if ( (pid = fork()) < 0 ){  
            perror("fork error");  
            exit(-1);  
        }  
        if (pid == 0) { /* child servicing the request from conn_fd */ }  
        else { /* father code */ }  
    }  
}
```



# Linked List

---


- SORT exercises require a “container” storing items
  - arbitrary and dynamic size of container
- Linked list: simplest dynamic data structure in C language
- **Node** divided in two parts
  - data storage
  - reference to next item

```
/* Data contained in item */
typedef struct {
    double value; /** esempio */
} itemType;

/* Node of the list */
struct LINKED_LIST_NODE {
    itemType item;
    struct LINKED_LIST_NODE *next;
};


/* Alias for the node */
typedef struct LINKED_LIST_NODE NODE;

/* Pointer to first item of the list represents the whole list! */
typedef struct NODE * LIST;
```




# Linked List

- Example:



- List is represented by a pointer to the first node
- field ***next*** of last node point to NULL



# Linked List

---

## ***/\* Constructors \*/***

```
LIST NewList(); /* Initialization */
```

## ***/\* Selector \*/***

```
itemType getHead(LIST l); /* Returns first item */
```

```
itemType getTail(LIST l); /* Returns last item */
```

## ***/\* Predicates \*/***

```
#define BOOL int
```

```
BOOL isEmpty( LIST l ); /* TRUE if list is empty */
```

```
int getLength( LIST l ); /* computes the length of list */
```

```
itemType * Find( LIST l, itemType item ); /* Finds an element if it exists; otherwise returns NULL */
```

## ***\* Insertion and removal of items \*/***

```
LIST EnqueueFirst(LIST l, itemType item ); /* Inserts item in first position */
```

```
LIST EnqueueLast(LIST l, itemType item ); /* Inserts item in last position */
```

```
LIST EnqueueOrdered(LIST l, itemType item ); /* inserts element in order */
```

```
LIST DequeueLast( LIST l ); /* Removes the last item */
```

```
LIST DequeueFirst( LIST l ); /* Removes the first item */
```

```
LIST Dequeue(LIST l, itemType item ); /* Removes a given item if it is in the list */
```

## ***/\* Destructors \*/***

```
LIST DeleteList( LIST l );
```

## ***/\* Other \*/***

```
void PrintList(LIST l); /* Prints list */
```

```
void PrintItem(itemType item);
```



# Linked List

---

**/\* Costructor \*/**

```
LIST NewList()
{
    return NULL;
}
```

```
NODE * createNode( itemType item )
{
    NODE * p = (NODE *)malloc(sizeof(NODE));
    assert( p != NULL );
    p->item = item;
    p->next = NULL;
    return p;
}
```

```
/* alternative implementation */
NODE *createElement(itemType item) {
    NODE *p;
    p = (NODE *)malloc(sizeof(NODE));
    if (isEmpty(p)) {
        printf("create element fallita.\n");
        exit(0);
    }
    p->item = item;
    p->next = NULL;
    return p;
}
```



# Assert

---

- Macro **assert()** evaluates an expression and terminates if not true
- Used to check *invariants*, i.e. properties that must hold during execution
  - if an expression it fails unexpectedly there is a potential bug in our code or a function is wrongly used

```
#include <assert.h>
```

```
...
```

```
assert(x > 0);
```

- Possible implementation:

```
#define MY_ASSERT(X) \
    if (!(X)) { printf("failed %s\n", #X); exit(-1); }
```



# Linked List

---

***/\* Selectors \*/***

```
itemType getHead(LIST l) /* Returns item to first item in list l */
{
    assert( !isEmpty(l) );
    return l->item;
}
```

```
itemType getTail(LIST l) /* Returns item to last item in list l */
{
    NODE * tmp = l;
    assert( !isEmpty(l) );

    while( !isEmpty(tmp->next) )
        tmp = tmp->next;

    return tmp->item;
}
```






# Linked List

---

```
/* Predicates */
```

```
BOOL isEmpty( LIST l ) /* check if list is empty */  
{  
    return (l == NULL);  
}
```

```
int getLength(LIST l) /* computes the length of list */  
{  
    int size = 0;  
    LIST tmp = l;  
    while ( ! isEmpty(tmp) )  
    {  
        ++size;  
        tmp = tmp -> next;  
    }  
    return size;  
}
```



# Linked List

---

**/\* Insertion \*/**

```
/* Inserts item to last position in the list */
LIST EnqueueLast (LIST l, itemType item)
{
    NODE * new_node = createNode(item);
    if ( isEmpty( l ) )
    {
        /* empty list: item in head position */
        l = new_node;
    }
    else
    {
        LIST tmp = l;
        while ( !isEmpty( tmp -> next ) )
            tmp = tmp -> next;
        tmp -> next = new_node;
    }
    return l;
}
```




# Linked List

---

***/\* Removal \*/***

*/\* Removes the given item from list if it is in the list \*/*

```
LIST Dequeue( LIST l, itemType item ) {  
    if ( !isEmpty( l ) ) {  
        if ( itemCompare( l -> item, item ) == 0 ) { /* remove item from head */  
            NODE * todel = l;  
            l = l -> next;  
            deleteNode( todel );  
        } else {  
            LIST tmp = l;  
            while ( ! isEmpty( tmp -> next ) && itemCompare( tmp -> next -> item, item ) != 0 )  
                tmp = tmp -> next;  
            if ( ! isEmpty( tmp -> next ) ) {  
                /* if item is found, then it is removed */  
                NODE * todel = tmp -> next;  
                tmp -> next = tmp -> next -> next;  
                deleteNode( todel );  
            }  
        }  
    }  
    return l;  
}
```



# Linked List

---

```
/* General comparison function inspired by strcmp():
```


- return value >0 if item1 > item2;
- return value <0 if item1 < item2;
- return value ==0 if item1 == item2.

Note: used to sort, search or manage order

It must be adapted to the exercise

```
*/
```

```
int itemCompare( itemType item1, itemType item2 )
{
    if ( item1.value > item2.value ) /* example with float field */
        return 1;
    else if ( item1.value < item2.value )
        return -1;
    else
        return 0;
}
```




# Linked List

---

```
/* Destructer */
/* frees node p */
void deleteNode( NODE * p )
{
    free(p);
}

LIST DeleteList( LIST l )
{
    LIST tmp = l; /* deallocate all the nodes */
    while ( !isEmpty(tmp) ) {
        NODE * todel = tmp;
        tmp = tmp -> next;
        deleteNode( todel );
    } /* all node visited and freed */
    return NewList();
}
```



# Linked List

---

```
/* Print list */
void PrintList( LIST l )
{
    LIST tmp = l;
    while (!isEmpty(tmp)) {
        PrintItem( tmp->item );
        tmp = tmp->next;
        if ( ! isEmpty(tmp) )
            printf("\n");
    }
}
```

- Custom *PrintItem()*: it depends on the item used in your problem



# Linked List

---

- Exercise: implements the following functions

LIST EnqueueFirst(LIST l, itemType item );

*/\* Inserts item in first position of list \*/*

LIST DequeueLast( LIST l );

*/\* Removes the last item from list, if list is not empty \*/*

LIST EnqueueOrdered(LIST l, itemType item );

*/\* Inserts the item in the list according to an order \*/*

itemType \* Find( LIST l, itemType item );

*/\* Finds the given item in the list and returns a pointer to the item (note: pointer to the item, not to the node type!!!)*

*\*/*



# Problem Solving: Advices

---

Decompose your exercise into functions: possible criteria

- Decompose your problem into smaller problems
- A function must solve a single (sub)problem independent from the other parts
- It must be clear what a function does
- Keep the function as short as possible





# Problem Solving: Advices

---

- Minimum numbers of function parameters required to solve the problem
- No constraints on parameters
- If number of parameters is high, possible warning
  - use a structure to store parameters?
- If you are doing cut & paste of parts of your code, then you may need a function doing it instead
- Avoid non-local access to variables:
  - access to data external to function only through parameters (with few exceptions)
  - violation of black box principle (only in very specific cases)