

<b>Name:</b> Alexis Neil D. Deniega	<b>Date Performed:</b> September 12th, 2025
<b>Course/Section:</b> CPE 212 - CPE31S4	<b>Date Submitted:</b> September 12th, 2025
<b>Instructor:</b> Engr. Robin	<b>Semester and SY:</b> 2025-26 1st Sem
<b>Activity 5: Consolidating Playbook plays</b>	
<b>1. Objectives:</b> 1.1 Use <b>when</b> command in playbook for different OS distributions 1.2 Apply refactoring techniques in cleaning up the playbook codes	
<b>2. Discussion:</b>  <p>We are going to look at a way that we can differentiate a playbook by a host in terms of which distribution the host is running. It's very common in most Linux shops to run multiple distributions, for example, Ubuntu shop or Debian shop and you need a different distribution for a one off-case or perhaps you want to run plays only on certain distributions.</p> <p>It is a best practice in ansible when you are working in a collaborative environment to use the command git pull. git pull is a Git command used to update the local version of a repository from a remote. By default, git pull does two things. Updates the current local working branch (currently checked out branch) and updates the remote-tracking branches for all other branches. git pull essentially pulls down any changes that may have happened since the last time you worked on the repository.</p> <p><b>Requirement:</b>  In this activity, you will need to create a CentOS VM. Likewise, you need to activate the second adapter to a host-only adapter after the installations. Take note of the IP address of the CentOS VM. Make sure to use the command <b>ssh-copy-id</b> to copy the public key to CentOS. Verify if you can successfully SSH to CentOS VM.</p>	
<b>Task 1: Use when command for different distributions</b>  <ol style="list-style-type: none"> <li>1. In the local machine, make sure you are in the local repository directory (<b>CPE232_yourname</b>). Issue the command git pull. When prompted, enter the correct passphrase or password. Describe what happened when you issue this command. Did something happen? Why?</li> <li>2. Edit the inventory file and add the IP address of the Centos VM. Issue the command we used to execute the playbook (the one we used in the last</li> </ol>	

activity): *ansible-playbook --ask-become-pass install\_apache.yml*. After executing this command, you may notice that it did not become successful in the Centos VM. You can see that the Centos VM has failed=1. Only the two remote servers have been changed. The reason is that Centos VM does not support "apt" as the package manager. The default package manager for Centos is "yum."

3. Edit the *install\_apache.yml* file and insert the lines shown below.

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        when: ansible_distribution == "Ubuntu"
```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

If you have a mix of Debian and Ubuntu servers, you can change the configuration of your playbook like this.

```
- name: update repository index
  apt:
    update_cache: yes
    when: ansible_distribution in ["Debian", "Ubuntu"]
```

```
programmymain@workstation: ~/CPE232_Denies
GNU nano 7.2                                install_apache.yml
--
hosts: all
become: true
tasks:
- name: update repository index
  apt:
    update_cache: yes
  when: ansible_distribution in ["Debian", "Ubuntu"]

- name: install apache2 package
  apt:
    name: apache2
  when: ansible_distribution == "Ubuntu"

- name: add PHP support for apahce
  apt:
    name: libapache2-mod-php
  when: ansible_distribution == "Ubuntu"
```

*Note:* This will work also if you try. Notice the changes are highlighted.

4. Edit the *install\_apache.yml* file and insert the lines shown below.

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index
      apt:
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache2 package
      apt:
        name: apache2
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: add PHP support for apache
      apt:
        name: libapache2-mod-php
        state: latest
      when: ansible_distribution == "Ubuntu"

    - name: update repository index
      dnf:
        update_cache: yes
      when: ansible_distribution == "CentOS"

    - name: install apache2 package
      dnf:
        name: httpd
        state: latest
      when: ansible_distribution == "CentOS"

    - name: add PHP support for apache
      dnf:
        name: php
        state: latest
      when: ansible_distribution == "CentOS"
```

Make sure to save and exit.

```
- name: update repository index
  dnf:
    update_cache: yes
    when: ansible_distribution == "CentOS"

- name: install apache2 package
  dnf:
    name: httpd
    state: latest
    when: ansible_distribution == "CentOS"

- name: add PHP support for apahce
  dnf:
    name: php
    state: latest
    when: ansible_distribution == "CentOS"
```

[ Wrote 37 lines ]

^G Help ^O Write Out ^W Where Is ^K Cut ^T E

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

5. To verify the installations, go to CentOS VM and type its IP address on the browser. Was it successful? The answer is no. It's because the httpd service or the Apache HTTP server in the CentOS is not yet active. Thus, you need to activate it first.

5.1 To activate, go to the CentOS VM terminal and enter the following:

*systemctl status httpd*

The result of this command tells you that the service is inactive.

5.2 Issue the following command to start the service:

*sudo systemctl start httpd*

(When prompted, enter the sudo password)

*sudo firewall-cmd --add-port=80/tcp*

(The result should be a success)

```
~  
~  
lines 1-4/4 (END)  
[alexis-cent@vbox ~]$ sudo systemctl enable httpd  
[sudo] password for alexis-cent:  
Created symlink /etc/systemd/system/multi-user.target.wants/httpd.service → /usr  
/lib/systemd/system/httpd.service.  
[alexis-cent@vbox ~]$ sudo systemctl start httpd  
[alexis-cent@vbox ~]$
```

5.3 To verify the service is already running, go to CentOS VM and type its IP address on the browser. Was it successful? (Screenshot the browser)

## Task 2: Refactoring playbook

This time, we want to make sure that our playbook is efficient and that the codes are easier to read. This will also makes run ansible more quickly if it has to execute fewer tasks to do the same thing.

1. Edit the playbook *install\_apache.yml*. Currently, we have three tasks targeting our Ubuntu machines and 3 tasks targeting our CentOS machine. Right now, we try to consolidate some tasks that are typically the same. For example, we can consolidate two plays that install packages. We can do that by creating a list of installation packages as shown below:

```
---
- hosts: all
  become: true
  tasks:

    - name: update repository index Ubuntu
      apt:
        update_cache: yes
        when: ansible_distribution == "Ubuntu"

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        when: ansible_distribution == "Ubuntu"

    - name: update repository index for CentOS
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.

```
- name: install apache2 package
  apt:
    name:
      - apache2
      - libapache2-mod-php
    state: latest
  when: ansible_distribution == "Ubuntu"

- name: update repository index
  dnf:
    update_cache: yes
  when: ansible_distribution == "CentOS"

- name: install apache2 package
  dnf:
    name:
      - httpd
      - php
    state: latest
  when: ansible_distribution == "CentOS"
```

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

2. Edit the playbook *install\_apache.yml* again. In task 2.1, we consolidated the plays into one play. This time we can actually consolidated everything in just 2 plays. This can be done by removing the update repository play and putting the command *update\_cache: yes* below the command *state: latest*. See below for reference:



```
---
- hosts: all
  become: true
  tasks:

    - name: install apache2 and php packages for Ubuntu
      apt:
        name:
          - apache2
          - libapache2-mod-php
        state: latest
        update_cache: yes
      when: ansible_distribution == "Ubuntu"

    - name: install apache and php packages for CentOS
      dnf:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
      when: ansible_distribution == "CentOS"
```

Make sure to save the file and exit.

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

```

- name: install apache2 package
  apt:
    name:
      - apache2
      - libapache2-mod-php
    state: latest
    update_cache: yes
  when: ansible_distribution == "Ubuntu"

- name: update repository index
  dnf:
    update_cache: yes
  when: ansible_distribution == "CentOS"

- name: install apache2 package
  dnf:
    name:
      - httpd
      - php
    state: latest
    update_cache: yes
  when: ansible_distribution == "CentOS"

```

3. Finally, we can consolidate these 2 plays in just 1 play. This can be done by declaring variables that will represent the packages that we want to install. Basically, the `apache_package` and `php_package` are variables. The names are arbitrary, which means we can choose different names. We also take out the line `when: ansible_distribution`. Edit the playbook *install\_apache.yml* again and make sure to follow the below image. Make sure to save the file and exit.

```
---
- hosts: all
  become: true
  tasks:

    - name: install apache and php
      apt:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes
```

GNU nano 7.2

install\_apache.yml

```
---
- hosts: all
  become: true
  tasks:
    - name: update repository index
      apt:
        update_cache: yes
        when: ansible_distribution in ["Debian", "Ubuntu"]

    - name: install apache2 package
      package:
        name:
          - "{{ apache_package }}"
          - "{{ php_package }}"
        state: latest
        update_cache: yes

    - name: update repository index
      dnf:
        update_cache: yes
        when: ansible_distribution == "CentOS"
```

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

4. Unfortunately, task 2.3 was not successful. It's because we need to change something in the inventory file so that the variables we declared will be in place. Edit the *inventory* file and follow the below configuration:

```
192.168.56.120 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.121 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.122 apache_package=httpd php_package=php
```

Make sure to save the *inventory* file and exit.

```
GNU nano 7.2 inventory.ini
[hosts]
192.168.56.115 apache_package=apache2 php_package=libapache-mod-php

[vbox]
192.168.56.116 apache_package=apache2 php_package=libapache2-mod-php
192.168.56.117 apache_package=apache2 php_package=libapache2-mod-php

[centosvbox]
192.168.56.121 apache_package=httpd php_package=php
```

**Finally**, we still have one more thing to change in our *install\_apache.yml* file. In task 2.3, you may notice that the package is assign as *apt*, which will not run in CentOS. Replace the *apt* with *package*. Package is a module in ansible that is generic, which is going to use whatever package manager the underlying host or the target server uses. For Ubuntu it will automatically use *apt*, and for CentOS it will automatically use *dnf*. Make sure to save the file and exit. For more details about the ansible package, you may refer to this documentation: [ansible.builtin.package – Generic OS package manager — Ansible Documentation](#)

Run *ansible-playbook --ask-become-pass install\_apache.yml* and describe the result.

```

TASK [Gathering Facts] *****
fatal: [192.168.56.115]: UNREACHABLE! => {"changed": false, "msg": "Failed to connect to the host via ssh: no such identity: /home/programmymain/CPE232_Deniega/.ssh/id_rsa: No such file or directory\r\nprogrammymain@192.168.56.115: Permission denied (publickey,password).", "unreachable": true}
fatal: [192.168.56.121]: UNREACHABLE! => {"changed": false, "msg": "Failed to connect to the host via ssh: no such identity: /home/programmymain/CPE232_Deniega/.ssh/id_rsa: No such file or directory\r\nprogrammymain@192.168.56.121: Permission denied (publickey,gssapi-keyex,gssapi-with-mic,password).", "unreachable": true}
ok: [192.168.56.117]
ok: [192.168.56.116]

TASK [update repository index] *****
changed: [192.168.56.117]
changed: [192.168.56.116]

TASK [install apache2 package] *****
ok: [192.168.56.116]
ok: [192.168.56.117]

TASK [update repository index] *****
skipping: [192.168.56.116]
skipping: [192.168.56.117]

PLAY RECAP *****
192.168.56.115      : ok=0    changed=0    unreachable=1    failed=0    skipped=0    rescued=0
ignored=0
192.168.56.116      : ok=3    changed=1    unreachable=0    failed=0    skipped=1    rescued=0
ignored=0
192.168.56.117      : ok=3    changed=1    unreachable=0    failed=0    skipped=1    rescued=0
ignored=0
192.168.56.121      : ok=0    changed=0    unreachable=1    failed=0    skipped=0    rescued=0
ignored=0

```

### Supplementary Activity:

1. Create a playbook that could do the previous tasks in Red Hat OS.

```
GNU nano 7.2                                install_apache_redhat.yml
--
- hosts: all
  become: true
  tasks:
    - name: update repo index (redhat)
      package:
        update_cache: yes
      when: ansible_distribution == "Red Hat"

    - name: install apache2 package
      package:
        name:
          - httpd
          - php
        state: latest
        update_cache: yes
      when: ansible_distribution == "Red Hat"
```

### Reflections:

Answer the following:

1. Why do you think refactoring of playbook codes is important?

*Playbook codes are important to be refactored to make sure that it is still up to the standards of the team/admin maintaining it. Refactoring is also used to check for any bottlenecks that could hinder the performance time of a playbook command.*

2. When do we use the “when” command in the playbook?

*The 'when' command is used if control between the different remote nodes are necessary. The most used when conditionals are the distribution and the Ansible version numbers, where differing mechanics from different packages make it different from the others.*

