

Arduino-IOT

[wk06]

Arduino-node.js

Visualization of Signals using Arduino, Node.js & storing signals in MongoDB & mining data using Python

Drone-IoT-Comsi, INJE University

2nd semester, 2021

Email : chaos21c@gmail.com

My ID

ID를 확인하고 github에 repo 만들기

AA01	김준수	AA13	조재윤
AA02	김현서	AA14	고태승
AA03	박영훈	AA15	이한글
AA04	박윤호	AA16	장세진
AA05	성은지	AA17	장태호
AA06	손윤우	AA18	정지원
AA07	오세윤	AA19	진우태
AA08	우승철	AA20	황혁준
AA09	윤현석	AA21	장이제
AA10	이예주	AA22	박상현
AA11	강지환	AA23	정은성
AA12	성인제	AA24	김경영

위의 id를 이용해서 github에 repo를 만드시오.

Option: 아두이노응용 실습 과제 – AAnn

Public, **README.md** check



[Review]

- [wk05]
  - Arduino sensors
  - Complete your project
  - Upload folder: aann-rpt05
  - Use repo “aann” in github

wk05 : Practice-05 : aann-rpt05

- [Target of this week]
  - Complete your works
  - Save your outcomes and upload 4 figures in github

Upload folder : aann-rpt05

- 제출할 파일들
  1. **AAnn_AnalogVoltage.png**
  2. **AAnn_TMP36.png**
  3. **AAnn_LCD_hello.png**
  4. **AAnn_LCD_lux.png**
  5. **All *.ino**

Email : chaos21c@gmail.com

Purpose of AA

주요 수업 목표는 다음과 같다.

1. Node.js를 이용한 아두이노 센서 신호 처리
2. Plotly.js를 이용한 아두이노 센서 신호 시각화
3. MongoDB에 아두이노 센서 데이터 저장 및 처리

4. 저장된 IoT 데이터의 마이닝 (파이썬 코딩)

Layout [H S C]


Physical Layer
Photocell
Arduino
USB Cable
Light
Temperature
DHT22
Pressure
Gyro/Acc
Pulse/ECG
EEG
Photo
Video
Coordination Layer
Computer
Node.js server
WEB 서버
Socket 서버
Web Browser
Internet
Application Layer
Plotly
mongoDB
TensorFlow.js

Arduino Sensors + Node.js









IOT: HSC



Figure 3
Typical Construction of a Plastic Coated Photocell



Layout [H S C]


Physical Layer
Photocell
Arduino
USB Cable
Light
Temperature
DHT22
Pressure
Gyro/Acc
Pulse/ECG
EEG
Photo
Video
Coordination Layer
Computer
Node.js server
WEB 서버
Socket 서버
Web Browser
Internet
Application Layer
Plotly
mongoDB
TensorFlow.js

on WEB monitoring Arduino data

IoT Signal from Arduino

Real-time Signals

---

on Time: 2021-10-06 09:49:49.818

Signals (조도,습도,온도) : 166,60,-5

Arduino data + plotly



Single sensor: tmp36



TMP36

Node project



A3.1.1 Temperature sensor [TMP36]





Parts : TMP36



- **Size:** TO-92 package (about 0.2" x 0.2" x 0.2") with three leads
- **Price:** $2.00 at the Adafruit shop
- **Temperature range:** -40°C to 150°C / -40°F to 302°F
- **Output range:** 0.1V (-40°C) to 2.0V (150°C) but accuracy decreases after 125°C
- **Power supply:** 2.7V to 5.5V only, 0.05 mA current draw

A4.1.1 tmp36 node project

Start tmp36-node project

1. **Go to my working folder: aann-rpt06**
2. **md iot & cd iot**
3. **md tmp36**
4. **cd tmp36**
5. **Open terminal**
6. **npm init**

A4.1.2 tmp36 node project: npm init

문제 출력 디버그 콘솔 터미널 node

```
D:\aann\aann-rpt06\iot\tmp36>npm init
This utility will walk you through creating a package.json file.
It only covers the most common items, and tries to guess sensible defaul
ts.

See `npm help init` for definitive documentation on these fields
and exactly what they do.

Use `npm install <pkg>` afterwards to install a package and
save it as a dependency in the package.json file.

Press ^C at any time to quit.
package name: (tmp36)
version: (1.0.0)
description: tmp36-node project
entry point: (index.js) tmp36_node.js
test command:
git repository:
keywords: tmp36 node arduino
author: aa00
license: (ISC) MIT
```

A4.1.3 tmp36 node project: package.json



A4.1.4 tmp36 node project: install modules

npm install --save serialport

```
D:\aann\aann-rpt06\iot\tmp36>npm install --save serialport

> @serialport/bindings@9.2.4 install D:\aann\aann-rpt06\iot\tmp36\node_m
odules\@serialport\bindings
> prebuild-install --tag-prefix @serialport/bindings@ || node-gyp rebuil
d

npm notice created a lockfile as package-lock.json. You should commit th
is file.
npm WARN tmp36@1.0.0 No repository field.

+ serialport@9.2.4
added 74 packages from 45 contributors and audited 74 packages in 11.774
s

17 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities
```

A4.1.4 tmp36 node project: install modules

socket.io



https://socket.io/docs/v4/server-installation/

A4.1.4 tmp36 node project: install modules

npm install --save socket.io@2.3.0

```
D:\aann\aann-rpt06\iot\tmp36>npm install --save socket.io@2.3.0
npm WARN tmp36@1.0.0 No repository field.

+ socket.io@2.3.0
added 52 packages from 33 contributors and audited 126 packages in 3.878
s

17 packages are looking for funding
  run `npm fund` for details

found 4 vulnerabilities (2 moderate, 1 high, 1 critical)
  run `npm audit fix` to fix them, or `npm audit` for details

 D:\aann\aann-rpt06\iot\tmp36 디렉터리

2021-10-05  오전 10:23    <DIR>          .
2021-10-05  오전 10:23    <DIR>          ..
2021-10-05  오전 10:23    <DIR>          node_modules
2021-10-05  오전 10:23            28,477 package-lock.json
2021-10-05  오전 10:23               367 package.json
               2개 파일              28,844 바이트
               3개 디렉터리  2,424,474,251,264 바이트 남음
```

A4.1.4 tmp36 node project: install modules

npm install --save socket.io@2.3.0

```
found 4 vulnerabilities (2 moderate, 1 high, 1 critical)
  run `npm audit fix` to fix them, or `npm audit` for details

D:\aann\aann-rpt06\iot\tmp36>npm audit fix
npm WARN tmp36@1.0.0 No repository field.

+ socket.io@2.4.1
added 1 package, removed 11 packages, updated 11 packages and moved 1 pa
ckage in 1.33s

17 packages are looking for funding
  run `npm fund` for details

fixed 1 of 4 vulnerabilities in 126 scanned packages
  1 package update for 3 vulnerabilities involved breaking changes
  (use `npm audit fix --force` to install breaking changes; or refer to
`npm audit` for steps to fix these manually)
```

A4.1.4 tmp36 node project: install modules

npm install --save socket.io [N.A.]

4.x 버전 설치는 좀 더 검토가 필요.

```
D:\aann\aann-rpt06\iot\tmp36>npm install --save socket.io
npm WARN tmp36@1.0.0 No repository field.

+ socket.io@4.2.0
added 20 packages from 66 contributors and audited 94 packages in 2.046s

17 packages are looking for funding
  run `npm fund` for details

found 0 vulnerabilities


 D:\aann\aann-rpt06\iot\tmp36 디렉터리

2021-10-05  오전 10:23    <DIR>          .
2021-10-05  오전 10:23    <DIR>          ..
2021-10-05  오전 10:23    <DIR>          node_modules
2021-10-05  오전 10:23            28,477 package-lock.json
2021-10-05  오전 10:23               367 package.json
               2개 파일              28,844 바이트
               3개 디렉터리  2,424,474,251,264 바이트 남음
```

A4.1.4 tmp36 node project: install modules

정상 동작 버전을 설치!

npm install --save serialport

npm install --save socket.io@2.4.1

```
"author": "aa00",
"license": "MIT",
"dependencies": {
  "serialport": "^9.2.4",
  "socket.io": "^2.4.1"
}
```

A4.1.5 tmp36 node project (Arduino code)

AAnn_TMP36_NodeJS.ino

```
12 void loop() {
13   //getting the voltage reading from the temperature sensor
14   int value = analogRead(TEMP_INPUT);
15   Serial.print("value = ");
16   Serial.print(value);
17   Serial.print(" : ");
18
19   // converting that reading to voltage
20   float voltage = value * 5.0 * 1000;  // in mV
21   voltage /= 1023.0;
22
23   // print out the voltage
24   Serial.print(voltage);
25   Serial.print(" mV, ");
26
27   // now print out the temperature
28   float temperatureC = (voltage - 500) / 10 ;
29   Serial.print(temperatureC);
30   Serial.println(" degrees C");
31
32   delay(1000);
33 }
```

Serial monitor



A4.1.6 tmp36 node project (node code)

tmp36_node_start.js

```
3   var serialport = require("serialport");
4   var portName = "COM3"; // check your COM port!!
5   var port = process.env.PORT || 3000;
6
7   var io = require("socket.io").listen(port);
8
9   const Readline = require("@serialport/parser-readline");
10  // serial port object
11  var sp = new serialport(portName, {
12    baudRate: 9600, // 9600  38400
13    dataBits: 8,
14    parity: "none",
15    stopBits: 1,
16    flowControl: false,
17    parser: new Readline("\r\n"),
18  });
```

Node cmd

```
20  const parser = sp.pipe(new Readline({ delimiter: "\r\n" }));
21
22  // Read the port data
23  sp.on("open", () => {
24    console.log("serial port open");
25  });
26
27  var tdata = []; // Array
28
29  parser.on("data", (data) => {
30    // call back when data is received
31    // raw data only
32    //console.log(data);
33
34    tdata = data; // data
35    console.log("AA00," + tdata);
36    io.sockets.emit("message", tdata); // send data to all clie
37  });
```

A4.1.7 tmp36 node project (node cmd message)

[Terminal] node tmp36_node.js

```
D:\aann\aann-rpt06\iot\tmp36>node tmp36_node
serial port open
67.35 mV, 26.74 degrees C
67.35 mV, 26.74 degrees C
7 : 767.35 mV, 26.74 degrees C
7 : 767.35 mV, 26.74 degrees C
AA00, value = 157 : 767.35 mV, 26.74 degrees C
AA00, value = 157 : 767.35 mV, 26.74 degrees C
AA00, value = 157 : 767.35 mV, 26.74 degrees C
AA00, value = 157 : 767.35 mV, 26.74 degrees C
AA00, value = 155 : 757.58 mV, 25.76 degrees C
AA00, value = 155 : 757.58 mV, 25.76 degrees C
AA00, value = 156 : 762.46 mV, 26.25 degrees C
AA00, value = 156 : 762.46 mV, 26.25 degrees C
AA00, value = 156 : 762.46 mV, 26.25 degrees C
AA00, value = 156 : 762.46 mV, 26.25 degrees C
AA00, value = 155 : 757.58 mV, 25.76 degrees C
AA00, value = 155 : 757.58 mV, 25.76 degrees C
AA00, value = 156 : 762.46 mV, 26.25 degrees C
AA00, value = 156 : 762.46 mV, 26.25 degrees C
```

A4.1.8 tmp36 node project (all messages)

tmp36_node.js

```
var dStr = "";
var tdata = []; // Array

parser.on("data", (data) => {
  // call back when data is received
  // raw data only
//   console.log(data);

  dStr = getDateString();
  tdata[0] = dStr;
  tdata[1] = data; // data
  console.log("AA00," + tdata.toString());
  io.sockets.emit("message", tdata); // se
});

function getDateString() {
  var time = new Date().getTime();
  // 32400000 is (GMT+9 Korea, GimHae)
  // for your timezone just multiply +/-GMT by 3600000
  var datestr = new Date(time + 32400000)
    .toISOString()
    .replace(/T/, " ")
    .replace(/Z/, "");
  return datestr;
}
```

[Terminal] node tmp36_node

```
D:\aann\aann-rpt06\iot\tmp36>node tmp36_node
serial port open
AA00,2021-10-05 11:21:24.062,lue = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:24.062,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:24.062,value = 157 : 767.35 mV, 26.74 degrees C
AA00,2021-10-05 11:21:24.062,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:24.063,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:24.063,value = 157 : 767.35 mV, 26.74 degrees C
AA00,2021-10-05 11:21:25.644,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:26.648,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:27.651,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:28.651,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:29.655,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:30.658,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:31.662,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:32.661,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:33.665,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:34.669,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:35.672,value = 156 : 762.46 mV, 26.25 degrees C
AA00,2021-10-05 11:21:36.676,value = 155 : 757.58 mV, 25.76 degrees C
AA00,2021-10-05 11:21:37.675,value = 156 : 762.46 mV, 26.25 degrees C
```

AAnn_tmp36_message.png
로 저장

A4.1.9 tmp36 node project (only data)

AAnn_TMP36_NodeJS.ino 수정

AA00_TMP36_NodeJS

```
11
12 void loop() {
13   //getting the voltage reading from the temperature sensor
14   int value = analogRead(TEMP_INPUT);
15 //  Serial.print("AA00, value = ");
16 //  Serial.print(value);
17 //  Serial.print(" : ");
18
19   // converting that reading to voltage
20   float voltage = value * 5.0 * 1000;  // in mV
21   voltage /= 1023.0;
22
23   // print out the voltage
24 //   Serial.print(voltage);
25 //   Serial.print(" mV, ");
26
27   // now print out the temperature
28   float temperatureC = (voltage - 500) / 10 ;
29 //   Serial.print(" Temperature, ");
30   Serial.println(temperatureC);
31 //   Serial.println(" degrees C");
32
33   delay(1000);
34 }
```

실행 결과



A4.1.10 tmp36 node project (date & data → IOT)

[Terminal] node tmp36_node

```
D:\aann\aann-rpt06\iot\tmp36>node tmp36_node
serial port open
AA00,2021-10-05 11:31:03.941,26.25
AA00,2021-10-05 11:31:04.944,26.25
AA00,2021-10-05 11:31:05.945,26.25
AA00,2021-10-05 11:31:06.948,26.25
AA00,2021-10-05 11:31:07.951,26.25
AA00,2021-10-05 11:31:08.951,26.25
AA00,2021-10-05 11:31:09.954,25.76
AA00,2021-10-05 11:31:10.954,26.25
AA00,2021-10-05 11:31:11.958,26.25
AA00,2021-10-05 11:31:12.957,26.25
AA00,2021-10-05 11:31:13.961,26.25
AA00,2021-10-05 11:31:14.964,26.25
AA00,2021-10-05 11:31:15.964,26.25
```

시간 , 온도

IOT data format
시간, **data**
시간, 온도

AAnn_tmp36_IOT_data.png
로 저장

공백없이 “,”로
시간과 온도 구분

A4.1.11 tmp36 node project (web monitoring)

[Web monitoring] client_signal_tmp36.html



Single sensor: CdS



CdS (LDR)

Node project

A3.2.2 Luminosity sensor [Photocell LDR]

CdS 센서 회로





Parts : 20 mm photocell LDR, R (10 kΩ X 1)

광센서에서의 전압 강하 값을 **A0**로 측정

A3.2.6 Luminosity sensor [Photocell LDR]

CdS 센서 회로 - 측정 2.

AAnn_cds_start.ino

```
1  //  lux
2  #define CDS_INPUT 0
3
4  void setup() {
5  Serial.begin(9600);
6  }
7  void loop() {
8    int value = analogRead(CDS_INPUT);
9    Serial.println(int(luminosity(value)));
10   delay(1000);
11 }
12
13 //Voltage to Lux
14 double luminosity (int RawADC0){
15   double Vout=RawADC0*5.0/1023;  // 5/1023 (Vin = 5 V)
16   double lux=(2500/Vout-500)/10;
17   // lux = 500 / Rldr, Vout = Ildr*Rldr = (5/(10 + Rldr))*Rldr
18   return lux;
19 }
```



밝을수록 측정 값이 커지고
어두을수록 값이 작아진다 !!!

A4.2.1 Luminosity sensor [npm init]

Start cds-node project

1. **Go to my working folder**
2. **Go to iot folder**
3. **md cds**
4. **cd cds**
5. **Open terminal in cds**
6. **npm init**



"main": "cds_node.js"
"author": “aann"

A4.2.2 Luminosity sensor [install node modules]

npm install --save serialport

npm install --save socket.io@2.4.1

```
{
  "name": "cds",
  "version": "1.0.0",
  "description": "cds node project",
  "main": "cds_node.js",
  ▷ Debug
  "scripts": {
    "test": "echo \"Error: no test specified\" && exit 1"
  },
  "keywords": [
    "cds",
    "node"
  ],
  "author": "aa00",
  "license": "MIT",
  "dependencies": {
    "serialport": "^9.2.4",
    "socket.io": "^2.4.1"
  }
}
```

A4.2.3 Luminosity sensor [node code]



Save tmp36_node.js as cds_node.js in cds folder
(code 재활용)

```
D:\aann\aann-rpt06\iot\cds>node cds_node
serial port open
AA00,2021-10-06 11:22:58.665,82
AA00,2021-10-06 11:22:59.669,83
AA00,2021-10-06 11:23:00.668,82
AA00,2021-10-06 11:23:01.672,83
AA00,2021-10-06 11:23:02.672,82
AA00,2021-10-06 11:23:03.675,82
AA00,2021-10-06 11:23:04.675,82
AA00,2021-10-06 11:23:05.678,82
AA00,2021-10-06 11:23:06.678,83
```

A4.2.4 CdS node project (web monitoring)

[Web monitoring] client_signal_cds.html



Multiple sensors



Arduino

+ Node.js



Monitoring via Serial monitor & LCD


TMP
36GZ
#1410
823616
1
3


COM4
240.0
180.0
120.0
60.0
0.0
151
251
351
451
551
651
9600 보드레이트

A4.3.1 TMP36 + CdS : circuit



A4.3.2 TMP36 + CdS : code

AAnn_TMP36_CdS§

```
1  //  temperature & lux
2  #define TMP36_INPUT 0
3  #define CDS_INPUT 1
4
5  void setup() {
6    Serial.begin(9600);
7  }
```

AAnn_tmp36_cds.ino

```
8  void loop() {
9    // Temperature from TMP36
10   int temp_value = analogRead(TMP36_INPUT);
11   // converting that reading to voltage
12   float voltage = temp_value * 5.0 * 1000;  // in mV
13   voltage /= 1023.0;
14   float tempC = (voltage - 500) / 10 ;
15
16   // Lux from CdS (LDR)
17   int cds_value = analogRead(CDS_INPUT);
18   int lux = int(luminosity(cds_value));
19 //
20   Serial.print(tempC);
21   Serial.print(",");
22   Serial.println(lux);
23
24   delay(1000);
25 }
26
27 //Voltage to Lux
28 double luminosity (int RawADC0){
29   double Vout=RawADC0*5.0/1023.0;  // 5/1023 (Vin = 5 V)
30   int lux=(2500/Vout-500)/10;
31   // lux = 500 / Rldr, Vout = Ildr*Rldr = (5/(10 + Rldr))*Rldr
32   return lux;
33 }
```

A4.3.3 TMP36 + CdS : Monitoring

COM4

15.98,192
14.52,194
14.52,193
14.52,193
15.00,180
14.03,18
14.52,17
14.52,16
13.54,15
14.52,191
16.47,188
15.00,188
14.52,190
14.52,190



A4.4.1 TMP36 + CdS + LCD : circuit




```
1 //  temperature & lux
2 #define TMP36_INPUT 0
3 #define CDS_INPUT 1
```

A4.4.2 TMP36 + CdS + LCD : code-1

AAnn_tmp36_cds_lcd.ino

```
/*
 온도, 빛 입력 LCD 모니터링 및 제어
*/
 // LCD 라이브러리 설정
#include <LiquidCrystal_I2C.h>
#include<Wire.h>
// LCD 설정
LiquidCrystal_I2C lcd(0x27,16,2); // 0x3F
// 0번 아날로그핀을 TMP36 온도 입력으로 설정한다.
// 1번 아날로그핀을 CdS 조도 입력으로 설정한다.
#define TMP36_INPUT 0   // A0
#define CDS_INPUT 1     // A1

void setup() {
  Serial.begin(9600);
// 16X2 LCD 모듈 설정하고 백라이트를 켠다.
  lcd.init();
  lcd.backlight();
// 모든 메세지를 삭제한 뒤
// 숫자를 제외한 부분들을 미리 출력시킨다.
  lcd.clear();
  lcd.setCursor(0,0);
  lcd.print("AA00,Temp: ");
  lcd.setCursor(0,1);
  lcd.print("Light:  ");
  lcd.setCursor(13,1);
  lcd.print("lux");  //
}
```

A4.4.3 TMP36 + CdS + LCD : code-2

```
29 void loop(){
30   // Temperature from TMP36
31   int temp_value = analogRead(TMP36_INPUT);
32   // converting that reading to voltage
33   float voltage = temp_value * 5.0 * 1000;  // in mV
34   voltage /= 1023.0;
35   float tempC = (voltage - 500) / 10 ;
36
37   // Lux from CdS (LDR)
38   int cds_value = analogRead(CDS_INPUT);
39   int lux = int(luminosity(cds_value));
40
41   // 전에 표시했던 내용을 지운다.
42   lcd.setCursor(12,0);
43   lcd.print("    ");
44   // 온도를 표시한다
45   lcd.setCursor(12,0);
46   lcd.print(tempC);
47   // 전에 표시했던 내용을 지운다
48   lcd.setCursor(9,1);
49   lcd.print("    ");
50   // 조도를 표시한다
51   lcd.setCursor(9,1);
52   lcd.print(lux);
```

LCD output

```
56   // Serial output --> 온도,조도
57   Serial.print(tempC);
58   Serial.print(",");
59   Serial.println(lux);
60   delay(1000);
61 }
62
63 //Voltage to Lux
64 double luminosity (int RawADC0){
65   double Vout=RawADC0*5.0/1023;  // 5/1023 (Vin = 5 V)
66   double lux=(2500/Vout-500)/10;
67   // lux = 500 / Rldr,
68   // Vout = Ildr*Rldr = (5/(10 + Rldr))*Rldr
69   return lux;
70 }
```

Serial output

A4.4.4 TMP36 + CdS + LCD : result-1



Save as
AAnn_cds_tmp36_serial.png

A4.4.5 TMP36 + CdS + LCD : result-2



Save as
AAnn_cds_tmp36_lcd.png

Multiple sensors



CdS + TMP36

Node project



A4.5.1 CdS + TMP36 + Node project

1. Make cds_tmp36 node project
   - md cds_tmp36 in iot folder
2. Go to cds_tmp36 subfolder
   - Start terminal
   - npm init

"main": "cds_tmp36_node.js"
"author": “aann"

name : cds_tmp36

description : cds-tmp36-node project

entry point : cds_tmp36_node.js

author : hsnn

A4.5.2 CdS + TMP36 + Node project

- **npm install –save serialport**
- **npm install –save socket.io@2.4.1**

```
"keywords": [
  "cds",
  "tmp36",
  "node"
],
"author": "aa00",
"license": "MIT",
"dependencies": {
  "serialport": "^9.2.4",
  "socket.io": "^2.4.1"
}
```



A4.5.3 CdS + TMP36 + Node project

Recycling code:
코드 재활용

Save cds_node.js as
cds_tmp36_node.js



A4.5.4.1 CdS + TMP36 + Node project : code-1

cds_tmp36_node.js

```
1   // cds_tmp36_node.js
2
3   var serialport = require("serialport");
4   var portName = "COM3"; // check your COM port!!
5   var port = process.env.PORT || 3000;
6
7   var io = require("socket.io").listen(port);
8
9   const Readline = require("@serialport/parser-readline");
10  // serial port object
11  var sp = new serialport(portName, {
12    baudRate: 9600, // 9600  38400
13    dataBits: 8,
14    parity: "none",
15    stopBits: 1,
16    flowControl: false,
17    parser: new Readline("\r\n"),
18  });
19
20  const parser = sp.pipe(new Readline({ delimiter: "\r\n" }));
21
22  // Read the port data
23  sp.on("open", () => {
24    console.log("serial port open");
25  });
```

A4.5.4.2 CdS + TMP36 + Node project : code-2

cds_tmp36_node.js – parsing data

```
27  var dStr = "";
28  var readData = "";
29  var temp = "";
30  var lux = "";
31  var mdata = [];
32  var firstcommaidx = 0;
33
34  parser.on("data", (data) => {
35    // call back when data is received
36    readData = data.toString();
37    firstcommaidx = readData.indexOf(",");
38    if (firstcommaidx > 0) {
39      temp = readData.substring(0, firstcommaidx);
40      lux = readData.substring(firstcommaidx + 1);
41      readData = "";
42
43      dStr = getDateString();
44      mdata[0] = dStr; //date
45      mdata[1] = temp; //data
46      mdata[2] = lux;
47      console.log("AA00," + mdata).toString());
48      io.sockets.emit("message", mdata); // send data to all clients
49    } else {
50      console.log(readData);
51    }
52  });
```



A4.5.4.3 CdS + TMP36 + Node project : code-3

cds_tmp36_node.js

```
54  io.sockets.on("connection", function (socket) {
55    // If socket.io receives message from the client browser then
56    // this call back will be executed.
57    socket.on("message", function (msg) {
58      console.log(msg);
59    });
60    // If a web browser disconnects from Socket.IO then this callback is called.
61    socket.on("disconnect", function () {
62      console.log("disconnected");
63    });
64  });
65
66  // helper function to get a nicely formatted date string for IOT
67  function getDateString() {
68    var time = new Date().getTime();
69    // 32400000 is (GMT+9 Korea, GimHae)
70    // for your timezone just multiply +/-GMT by 3600000
71    var datestr = new Date(time + 32400000)
72      .toISOString()
73      .replace(/T/, " ")
74      .replace(/Z/, "");
75    return datestr;
76  }
```

A4.5.5 CdS + TMP36 + Node project : result

Terminal에서 실행

```
D:\aann\aann-rpt06\iot\cds_tmp36>node cds_tmp36_node
serial port open
AA00,2021-10-05 13:57:38.119,25.27,84
AA00,2021-10-05 13:57:39.119,25.27,84
AA00,2021-10-05 13:57:40.122,24.78,83
AA00,2021-10-05 13:57:41.125,24.78,84
AA00,2021-10-05 13:57:42.125,24.78,84
AA00,2021-10-05 13:57:43.129,25.27,84
AA00,2021-10-05 13:57:44.132,25.27,83
AA00,2021-10-05 13:57:45.132,25.76,83
AA00,2021-10-05 13:57:46.135,24.78,84
```

IOT data format

시간, 온도,조도

Save as
AAnn_cds_tmp36_IOT.png

A4.5.6 CdS + TMP36 + Node project : WEB

[Web monitoring] client_signal_cds_tmp36.html

Save as
AAnn_cds_tmp36_WEB.png

[DIY] Multi-signals

다중신호 시뮬레이션

+ node.js



DIY - 스케치



아두이노에서 **LED**와 저항을 모두 제거하고 **USB**만 컴퓨터와 연결한다.

전자 소자 연결 없이 마구잡이 수 생성 함수를 이용해서 조도, 습도, 온도에 해당되는 **3**개의 신호를 만든다.

온도는 값의 범위를 **–10 ~ 30**, 습도는 **40 ~ 90**, 그리고 조도는 **150 ~ 250** 으로 가상적 으로 설정한다.

직렬통신 모니터링을 이용해서 세 개의 신호의 변화를 모니터링 하는 코드를 만들어 결과를 확인한다.

▶ 스케치 구성

1. 3 개의 신호를 담을 변수를 초기화한다.
2. setup()에서 직렬 통신 속도를 9600 bps 로 설정하고 컴퓨터와 연결한다.
3. loop()에서 마구잡이 수를 세 개 발생시켜서 직렬 통신으로 3 개의 pwm 값을 각각 컴퓨터로 전송한다.

DIY - code

sketch05_multi_signals

```
/*
  Multi Signals
  Simulation of multiple random signals
*/
// signals
int humi=0;
int temp=0;
int lux=0;

// the setup routine runs once when you press reset:
void setup() {
  // initialize serial communication at 9600 bits per second:
  Serial.begin(9600);
}

// the loop routine runs over and over again forever:
void loop() {
  // Multi signals
  humi = random(40,90);
  temp = random(-10, 30);
  lux = random(150,250);
  Serial.print("AA00, Ambient lux: ");
  Serial.print(lux);
  Serial.print(" , Humidity: ");
  Serial.print(humi);
  Serial.print(" , Temperature: ");
  Serial.println(temp);
  delay(500);          // delay in between reads for stability
}
```

DIY - result

DIY 결과

가상적인 세 개의 센서신호 시뮬레이션:조도(위), 습도(중간), 온도(아래).





DIY – New result 1

DIY 결과 [1] : 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도



DIY – New result 2-1

DIY 결과 [2]: 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도를 Node.js로 처리

[1 단계] Node cmd

1. Make multi_signals node project

- md multi_signals in iot folder
- cd multi_signals

2. Go to multi_signals subfolder

- npm init

  name : multi_signals

  description : multi-signals-node project

  entry point : aann_multi_signals.js

  author : aann

3. Install node modules

- npm install –save serialport
- npm install –save socket.io@2.4.1



DIY – New result 2-2

DIY 결과 [2]: 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도를 Node.js로 처리

Recycling code:
Save cds_tmp36_node.js as
aann_multi_signals.js in multi_signals subfolder
Update code

```
var dStr ='';
var readData='';
var temp='';
var humi='';
var lux='';
var mdata=[];
var firstcommaidx = 0;
var secondcommaidx= 0;
```

DIY – New result 2-3

DIY 결과 [2]: 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도를 Node.js로 처리

```
parser.on("data", (data) => {
  // call back when data is received
  readData = data.toString();
  firstcommaidx = readData.indexOf(",");
  secondcommaidx = readData.indexOf(",", firstcommaidx + 1);
  if (firstcommaidx > 0) {
    console.log("AA00," + mdata);
    io.sockets.emit("message", mdata); // send data to all clients
  } else {
    console.log(readData);
  }
});
```

아두이노가 직렬통신으로 전송하는 2 개의 comma (,)로 구분된

조도,습도,온도 데이터 메시지를 **parsing**하여 **mdata** 배열에 담는 코드를 완성하시오.

substring() 함수에서 firstcommaidx, secondcommaidx를 잘 이용하시오.

DIY – New result 2-3

DIY 결과 [2]: 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도를 Node.js로 처리

```
parser.on("data", (data) => {
  // call back when data is received
  readData = data.toString();
  firstcommaidx = readData.indexOf(",");
  secondcommaidx = readData.indexOf(",", firstcommaidx + 1);
  if (firstcommaidx > 0) {
    lux = readData.substring(0, firstcommaidx);
    humi = readData.substring(firstcommaidx + 1, secondcommaidx);
    temp = readData.substring(secondcommaidx + 1);
    readData = "";

    dStr = getDateString();
    mdata[0] = dStr; //date
    mdata[1] = lux; //data
    mdata[2] = humi;
    mdata[3] = temp;
    console.log("AA00," + mdata.toString());
    io.sockets.emit("message", mdata); // send data to all clients
  } else {
    console.log(readData);
  }
});
```

DIY – New result 2-4 : js functions

DIY 결과 [2]: 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도를 Node.js로 처리

Hint:

javascript function : indexOf()

https://www.w3schools.com/jsref/jsref_indexof.asp

Syntax

```
string.indexOf(searchvalue, start)
```

Parameter Values

Parameter	Description
searchvalue	Required. The string to search for
start	Optional. Default 0. At which position to start the search

javascript function : substring()

```
string.substring(start, end)
```

Parameter Values

Parameter	Description
start	Required. The position where to start the extraction. First character is at index 0
end	Optional. The position (up to, but not including) where to end the extraction. If omitted, it extracts the rest of the string

DIY – New result 2-5

DIY 결과 [2]: 가상적인 세 개의 센서신호 시뮬레이션 → 조도,습도,온도를 Node.js로 처리

```
D:\aann\aann-rpt06\iot\multi_signals>node aann_multi_signals
serial port open
AA00,2021-10-05 14:21:10.805,223,47,-1
AA00,2021-10-05 14:21:11.804,222,48,0
AA00,2021-10-05 14:21:12.808,173,84,28
AA00,2021-10-05 14:21:13.811,215,49,-10
AA00,2021-10-05 14:21:14.811,237,82,-8
AA00,2021-10-05 14:21:15.815,179,43,-3
AA00,2021-10-05 14:21:16.814,153,80,2
AA00,2021-10-05 14:21:17.818,207,59,19
AA00,2021-10-05 14:21:18.817,249,50,3
AA00,2021-10-05 14:21:19.821,185,68,6
AA00,2021-10-05 14:21:20.820,162,87,16
```

ID,시간,조도,습도,온도

Save this result as
AAnn_multi_signals_node .png

A4.5.6 multi-signals + Node project : WEB

[Web monitoring] client_multi_signals.html

Save as
AAnn_multi_signals_WEB.png

Next week





Data visualization using ploy.ly

Real-time Temperature(°C) and Luminosity(lux) from sensors

on Time: 2017-11-14 17:14:53.321





[Practice]

- [wk06]
  - Arduino sensors + Node.js
  - Complete your project
  - Upload folder: aann-rpt06
  - Use repo “aann” in github

wk06 : Practice : aann-rpt06

- [Target of this week]
  - Complete your works
  - Save your outcomes and upload outputs in github repo.

제출폴더명 : **aann-rpt06**

- 압축할 파일들

① AAnn_tmp36_message.png

② AAnn_tmp36_IOT_data.png

③ AAnn_cds_tmp36_serial.png

④ AAnn_cds_tmp36_lcd.png

⑤ AAnn_cds_tmp36_IOT.png

⑥ AAnn_cds_tmp36_WEB.png

⑦ AAnn_multi_signals_node.png

⑧ AAnn_multi_signals_WEB.png

⑨ All *.ino

⑩ All *.js

⑪ NO node_modules folder

Lecture materials

References & good sites

- ✓ http://www.arduino.cc Arduino Homepage
- ✓ http://www.nodejs.org/ko Node.js
- ✓ https://plot.ly/ plotly
- ✓ https://www.mongodb.com/ MongoDB
- ✓ http://www.w3schools.com By w3schools
- ✓ http://www.github.com GitHub

Target of this class