

Warehouse Module: Responses

1. Add Warehouse:

The screenshot shows a REST client interface for the 'Add Warehouse' endpoint. The request is a POST to `{{url}}/warehouses` with a JSON body. The response is a 201 status with a success message.

Request:

```
POST {{url}}/warehouses
```

Body:

```
{
  "name": "Dummy Warehouse 6",
  "address": "PIECHS, Karachi",
  "isActive": false,
  "latitude": "13.3459",
  "longitude": "79.91012",
  "cityId": 1
}
```

Response:

```
{
  "status": 201,
  "message": "Created"
}
```

Status: 201 Created Time: 751 ms Size: 474 B

2. Update Warehouse

The screenshot shows a REST client interface for the 'Update Warehouse' endpoint. The request is a PUT to `{{url}}/warehouses` with a JSON body. The response is a 200 status with a success message and the updated warehouse details.

Request:

```
PUT {{url}}/warehouses
```

Body:

```
{
  "id": 8,
  "latitude": "10.12012"
}
```

Response:

```
{
  "status": 200,
  "message": "OK",
  "data": {
    "id": 8,
    "name": "Dummy Warehouse Updated",
    "address": "F-6 Markaz, Islamabad",
    "latitude": "10.12012",
    "longitude": "79.91012",
    "cityId": 1,
    "active": false
  }
}
```

Status: 200 OK Time: 565 ms Size: 618 B

3. Delete Warehouse

The screenshot shows a REST client interface for a project named "Apricart Saudi". The current endpoint is "Warehouse / Delete Warehouse". The HTTP method is set to "DELETE" and the URL is "{{url}}/warehouses/4". The "Send" button is visible. Below the request bar, the "Body" tab is selected, showing a JSON response in "Pretty" format. The response status is "200 OK" with a time of "464 ms" and a size of "504 B".

```
{
  "status": 200,
  "message": "OK",
  "data": "Warehouse removed successfully"
}
```

4. Get All Warehouses

The screenshot shows a REST client interface for a project named "Apricart Saudi". The current endpoint is "Warehouse / Get All Warehouse". The HTTP method is set to "GET" and the URL is "{{url}}/warehouses". The "Send" button is visible. Below the request bar, the "Body" tab is selected, showing a JSON response in "Pretty" format. The response status is "200 OK" with a time of "263 ms" and a size of "1.01 KB".

```
{
  "status": 200,
  "message": "OK",
  "data": [
    {
      "id": 7,
      "name": "Dummy Warehouse 5",
      "address": "DC Colony, Karachi",
      "latitude": "12.3456",
      "longitude": "78.91011",
      "cityId": 1,
      "active": true
    },
    {
      "id": 6,
      "name": "Dummy Warehouse 1",
      "address": "Saddar, Karachi",
      "latitude": "12.3458",
      "longitude": "78.91011",
      "cityId": 1,
      "active": false
    },
    {
      "id": 5,
      "name": "Dummy Warehouse",
      "address": "Shahrah e Faisal, Karachi",
      "latitude": "12.3457",
      "longitude": "78.91011",
      "cityId": 1,
      "active": false
    }
  ]
}
```

5. Get Active Warehouses

The screenshot shows a REST client interface for a project named 'Apricart Saudi'. The active tab is 'Warehouse' with the sub-tab 'Get Active Warehouse'. The HTTP method is 'GET' and the URL is '{{url}}/warehouses/active'. The 'Send' button is visible. Below the URL bar, tabs for 'Params', 'Authorization', 'Headers (8)', 'Body', 'Pre-request Script', 'Tests', and 'Settings' are shown. The 'Body' tab is selected, displaying the response in 'JSON' format. The response status is '200 OK' with a time of '301 ms' and size of '609 B'. The JSON body is as follows:

```
1 {
2   "status": 200,
3   "message": "OK",
4   "data": [
5     {
6       "id": 7,
7       "name": "Dummy Warehouse 5",
8       "address": "DC Colony, Karachi",
9       "latitude": "12.3456",
10      "longitude": "78.91011",
11      "cityId": 1,
12      "active": true
13    }
14  ]
15 }
```

6. Get Warehouse by Warehouse ID

The screenshot shows the same REST client interface, but for the endpoint 'Get Warehouse By Id'. The URL is '{{url}}/warehouses/8'. The response status is '200 OK' with a time of '286 ms' and size of '618 B'. The JSON body is as follows:

```
1 {
2   "status": 200,
3   "message": "OK",
4   "data": {
5     "id": 8,
6     "name": "Dummy Warehouse Updated",
7     "address": "F-6 Markaz, Islamabad",
8     "latitude": "10.12012",
9     "longitude": "79.91012",
10    "cityId": 1,
11    "active": false
12  }
13 }
```

7. Get Warehouse by Warehouse Name

The screenshot shows a REST client interface for a project named 'Apricart Saudi'. The endpoint is 'Warehouse / Get Warehouse By Name'. The request is a GET method to the URL '({url})/warehouses/name/Dummy Warehouse'. The response status is 200 OK, with a time of 1903 ms and a size of 613 B. The response body is a JSON object:

```
1 {
2   "status": 200,
3   "message": "OK",
4   "data": {
5     "id": 5,
6     "name": "Dummy Warehouse",
7     "address": "Shahrah e Faisal, Karachi",
8     "latitude": "12.3457",
9     "longitude": "78.91011",
10    "cityId": 1,
11    "active": false
12  }
13 }
```

8. Get Warehouses by City ID

The screenshot shows a REST client interface for a project named 'Apricart Saudi'. The endpoint is 'Warehouse / Get Warehouse By City Id'. The request is a GET method to the URL '({url})/warehouses/city/1'. The response status is 200 OK, with a time of 4.66 s and a size of 1.01 KB. The response body is a JSON array of warehouse objects:

```
1 {
2   "status": 200,
3   "message": "OK",
4   "data": [
5     {
6       "id": 7,
7       "name": "Dummy Warehouse 5",
8       "address": "DC Colony, Karachi",
9       "latitude": "12.3456",
10      "longitude": "78.91011",
11      "cityId": 1,
12      "active": true
13    },
14    {
15      "id": 6,
16      "name": "Dummy Warehouse 1",
17      "address": "Saddar, Karachi",
18      "latitude": "12.3458",
19      "longitude": "78.91011",
20      "cityId": 1,
21      "active": false
22    },
23    {
24      "id": 5,
25      "name": "Dummy Warehouse",
26      "address": "Shahrah e Faisal, Karachi",
27      "latitude": "12.3457",
28      "longitude": "78.91011",
29      "cityId": 1,
30      "active": false
31    }
32  ]
33 }
```

9. Get Warehouse by Coordinates

The screenshot shows a REST client interface for a project named "Apricart Saudi". The current endpoint is "Warehouse / Get Warehouse By Coordinates". The HTTP method is set to "GET". The URL is constructed as `{{url}}/warehouses/coordinates/12.3456/78.91011`. The "Send" button is visible. Below the URL bar, the "Body" tab is selected, displaying the response in JSON format. The response status is "200 OK" with a time of "260 ms" and a size of "651 B". The JSON body contains the following data:

```
1 {
2   "status": 200,
3   "message": "OK",
4   "data": {
5     "id": 7,
6     "name": "Dummy Warehouse 5",
7     "address": "DC Colony, Karachi",
8     "latitude": "12.3456",
9     "longitude": "78.91011",
10    "cityId": 1,
11    "active": true
12  }
13 }
```

10. Update Warehouse Status by Warehouse ID

The screenshot shows a REST client interface for a project named "Apricart Saudi". The current endpoint is "Warehouse / Update Warehouse Status". The HTTP method is set to "PUT". The URL is constructed as `{{url}}/warehouses/8/true`. The "Send" button is visible. Below the URL bar, the "Body" tab is selected, displaying the response in JSON format. The response status is "200 OK" with a time of "362 ms" and a size of "617 B". The JSON body contains the following data:

```
1 {
2   "status": 200,
3   "message": "OK",
4   "data": {
5     "id": 8,
6     "name": "Dummy Warehouse Updated",
7     "address": "F-6 Markaz, Islamabad",
8     "latitude": "10.12012",
9     "longitude": "79.91012",
10    "cityId": 1,
11    "active": true
12  }
13 }
```