

# Lecture 4: SQL Data Manipulation Basics

## Data Manipulation

---

Dr Kieran T. Herley

2019-2020

School of Computer Science & Information Technology  
University College Cork

# Data Manipulation

- **SELECT** statement extracts information from our DB, but leaves the DB unchanged
- SQL also includes data manipulation statements to alter DB contents

**INSERT** adds new rows to existing table

**DELETE** removes some rows from table

**UPDATE** changes some values within table

- Potentially destructive and irreversible, so caution advised with these

# Inserting a Single Row

- Add a new row with the details of a new student

```
INSERT INTO students
```

```
VALUES ('987654321', 'Graine', 'Gogerty', '1992-12-13', 'Skibbereen', 'ck401', 525)
```

- Values supplied must match table columns in number, order and type
- Note: id “number” treated as string

# Inserting a Multiple Rows

- Can insert multiple rows all at once

```
INSERT INTO students VALUES ( . . . );  
INSERT INTO students VALUES ( . . . );  
INSERT INTO students VALUES ( . . . );
```

or

```
INSERT INTO students  
VALUES  
    ( . . . ),  
    ( . . . ),  
    ( . . . );
```

i.e. multiple (...) separated by commas

# Populating a Database From Scratch

- Can “populate” an empty DB with a barrage of INSERTs
- File `students_populate.sql` contains

```
INSERT INTO students VALUES ( . . 'Aoife', 'Ahern'. . . .);  
INSERT INTO students VALUES ( . . 'Barry', 'Barry'. . . .);  
    . . .  
INSERT INTO students VALUES ( . . 'Fionn', 'Fitzgerald'. . . .);
```

- NB MySQL can accept SQL from a file, not just those typed in
- This is how we set your cs1106 DBs up (separate file for table-creating SQL statements)

# Inserting Partial Rows

- Can also perform insertions with only some column values are supplied

```
INSERT INTO students (id_number, first_name, last_name)  
VALUES ('987654321', 'Graine', 'Gogerty');
```

- “Missing” values (e.g. hometown) set to some default (typically NULL)

id_number	first_name	last_name	date_of_birth	hometown	course	points	
⋮	⋮	⋮	⋮	⋮	⋮	⋮	← old rows
987654321	Graine	Gogerty	NULL	NULL	NULL	NULL	← new row

# NULL

- NULL is a special marker that is compatible with any domain/type; is not a value *per se*
- Typically used to denote situations where a value
  - is not known
  - irrelevant
  - is not applicable
- Can be problematic; over-reliance on NULLs may suggest poor DB design

# Bad Insertions

- “Bad” insertions may be rejected (i.e. not take effect)
  - Attempt to insert duplicate key
  - Values incompatible with column type etc.
- However some “bad” insertions may be technically legal but nonsense; such insertions will contaminate your table
  - Mixing up columns (e.g. confusing first name and last name, or first name and hometown)
  - “Fat fingers” errors, types etc. e.g. 5000 points



# Deleting a Row

- Use DELETE to remove row(s)

```
DELETE  
FROM students  
WHERE id_number = '987654321';
```

specify victim(s) using SELECT-style WHERE condition

- What wrong with the following?

```
DELETE  
FROM students  
WHERE first_name = 'Graine' AND last_name = 'Gogerty';
```

# Deleting Multiple Rows

- Can also delete multiple rows

```
DELETE  
FROM students  
WHERE hometown = 'Tralee';
```

- Need to be very careful with this!

# Updating Values Within a Table

- Use UPDATE to modify existing values within table

```
UPDATE students  
SET points = 500  
WHERE id_number = '112356489';
```

- Uses SELECT-style WHERE condition to specify target

# Updating Multiple Values

- Can update multiple values all at once

```
UPDATE students  
SET points = 1.2*points  
WHERE hometown = 'Tralee';
```

- Increases all Tralee students' points by 20%
- Interpretation of

$$\text{points} = 1.2 * \text{points}$$

Left hand side indicates value to be updated; right hand side specifies number to be to be used (1.2 times existing points value of row)