

API Documentation

Base URL

Local development base URL:

`http://127.0.0.1:8000`

Authentication

The API uses JWT authentication for protected endpoints.

Register

POST `/api/auth/register/`

Example request:

```
json { "username": "testuser", "email": "user@example.com", "password": "SecurePass123"
}
```

Login

POST `/api/auth/token/`

Example response:

```
json { "access": "jwt_access_token", "refresh": "jwt_refresh_token" }
```

Refresh Token

POST `/api/auth/token/refresh/`

Protected endpoints require:

Authorization: Bearer `<access_token>`

1. API Root

GET `/api/`

Returns the main available API routes.

Example response:

```
json { "claims": "/api/claims/", "reports": "/api/reports/", "score": "/api/score/",
"register": "/api/auth/register/", "login": "/api/auth/token/" }
```

2. Claims Endpoints

GET /api/claims/

Returns a paginated list of claims.

Supported query parameters:

- search
- label
- ordering
- page

Example:

/api/claims/?search=vaccine

Example response structure:

```
json { "count": 123, "next": "http://127.0.0.1:8000/api/claims/?page=2", "previous":
null, "results": [ { "id": 12790, "liar_id": "example.json", "label": "false",
"statement": "Vaccines cause autism", "speaker": "example-speaker" } ] }
```

GET /api/claims/{id}/

Returns one claim by ID.

Path parameter:

- id (integer)

GET /api/claims/by-speaker/{speaker}/

Returns claims matching a speaker.

Path parameter:

- speaker (string)

Example:

/api/claims/by-speaker/trump/

3. Reports Endpoints

These endpoints require authentication.

GET /api/reports/

Returns reports for the authenticated user.

Admin users can view all reports.

Supported query parameters:

- status
- risk_level
- page

POST /api/reports/

Creates a new report.

Example request:

```
json { "statement_text": "vaccines cause autism", "speaker": "Unknown",
"report_reason": "false claim", "risk_score": 78, "risk_level": "medium", "status":
"open" }
```

Example response:

```
json { "id": 11, "statement_text": "vaccines cause autism", "speaker": "Unknown",
"report_reason": "false claim", "risk_score": 78, "risk_level": "medium", "status":
"open", "user": 1 }
```

GET /api/reports/{id}/

Returns one report by ID.

Path parameter:

- id (integer)

PUT /api/reports/{id}/

Replaces an existing report.

PATCH /api/reports/{id}/

Partially updates an existing report.

Example PATCH request:

```
json { "status": "reviewed" }
```

DELETE /api/reports/{id}/

Deletes a report.

Permissions:

- users can manage their own reports
- admins can manage all reports

4. Score Endpoint

This endpoint requires authentication.

POST /api/score/

Analyses a claim and returns a credibility/risk result.

Example request:

```
json { "text": "vaccines cause autism" }
```

Example response:

```
json { "claim": "vaccines cause autism", "summary": { "final_verdict": "likely_false",
"final_credibility_score": 18, "final_risk_score": 82, "final_confidence": 74 },
"local_analysis": {}, "external_analysis": {}, "fusion": {} }
```

Error Handling

Common status codes:

- 200 OK
- 201 Created
- 400 Bad Request
- 401 Unauthorized
- 403 Forbidden
- 404 Not Found
- 429 Too Many Requests

Example custom error response:

```
json { "error": "text is required" }
```

Example framework error response:

```
json { "detail": "Authentication credentials were not provided." }
```