

API Documentation

Base URL

Local development base URL:

http://127.0.0.1:8000

Deployed backend:

https://credibility-intelligence-api.onrender.com

Deployed frontend interacting with backend:

https://credibility-intelligence-frontend.onrender.com

Authentication

The API uses JWT authentication for protected endpoints.

Protected endpoints include /api/reports/ and /api/score .

Public endpoints include claims browsing and user registration/login.

Register

POST /api/auth/register/

Example request:

```
{
  "username": "testuser",
  "email": "user@example.com",
  "password": "SecurePass123"
}
```

Login

POST /api/auth/token/

Example response:

```
{
  "access": "jwt_access_token",
  "refresh": "jwt_refresh_token"
}
```

Refresh Token

POST /api/auth/token/refresh/

Protected endpoints require:

Authorization: Bearer <access_token>

1. API Root

GET /api/

Returns the main available API routes as URL strings.

Example response:

```
{
  "claims": "/api/claims/",
  "reports": "/api/reports/",
  "score": "/api/score/",
  "register": "/api/auth/register/",
  "login": "/api/auth/token/"
}
```

2. Claims Endpoints

GET /api/claims/

Returns a paginated list of claims.

Supported query parameters:

- search
- label
- ordering
- page

Example:

/api/claims/?search=vaccine

Example response structure:

```
{
  "count": 18,
  "next": http://127.0.0.1:8000/api/claims/?page=2,
  "previous": null,
  "results": [
    {
      "url": "https://credibility-intelligence-api.onrender.com/api/claims/9906/",
      "id": 9906,
      "liar_id": "11222.json",
      "label": "half-true",
      "statement": "Rhode Island will become just the second state to mandate the vaccine and the",
      "subjects": "government-regulation,health-care",
      "speaker": "rhode-island-center-freedom-and-prosperity",
      "speaker_job_title": "",
      "state": "Rhode Island",
      "party": "organization",
      "barely_true_count": 1,
      "false_count": 0,
      "half_true_count": 1,
      "mostly_true_count": 0,
      "pants_on_fire_count": 0,
      "context": "news release",
      "split": "train",
      "created_at": "2026-03-10T17:27:15.720754Z"
    },
    {...}
  ]
}
```

GET /api/claims/{id}/

Returns one claim by ID.

Path parameter:

- id (integer)

GET /api/claims/by-speaker/{speaker}/

Returns claims matching a speaker.

Path parameter:

- speaker (string)

Example:

/api/claims/by-speaker/trump/

3. Reports Endpoints

These endpoints require authentication.

GET /api/reports/

Returns reports for the authenticated user.

Admin users can view all reports.

Supported query parameters:

- status
- risk_level

- page

POST /api/reports/

Creates a new report.

Example request:

```
{
  "statement_text": "vaccines cause autism",
  "speaker": "Unknown",
  "report_reason": "false claim",
  "risk_score": 78,
  "risk_level": "medium",
  "status": "open"
}
```

Example response:

```
{
  "id": 11,
  "statement_text": "vaccines cause autism",
  "speaker": "Unknown",
  "report_reason": "false claim",
  "risk_score": 78,
  "risk_level": "medium",
  "status": "open",
  "created_at": "2026-03-11T03:41:00.268604Z",
  "updated_at": "2026-03-11T03:41:00.268613Z",
  "user": 1
}
```

GET /api/reports/{id}/

Returns one report by ID.

Path parameter:

- id (integer)

PUT /api/reports/{id}/

Replaces an existing report.

PATCH /api/reports/{id}/

Partially updates an existing report.

Example PATCH request:

```
{
  "status": "reviewed"
}
```

Note: report status moderation is intended for administrator use. Creator of the claim can modify the other fields.

DELETE /api/reports/{id}/

Deletes a report.

Permissions:

- users can manage their own reports
- admins can manage all reports

4. Score Endpoint

This endpoint requires authentication.

POST /api/score/

Analyses a claim and returns a credibility/risk result.

Example request:

```
{
  "text": "vaccines cause autism"
}
```

Example response:

```
{
  "claim": "vaccines cause autism",
  "summary": {
    "final_verdict": "likely_false",
    "final_credibility_score": 18,
    "final_risk_score": 82,
    "final_confidence": 74
  },
  "local_analysis": {},
  "external_analysis": {},
  "fusion": {}
}
```

Error Handling

Common status codes:

- 200 OK
- 201 Created
- 400 Bad Request
- 401 Unauthorized
- 403 Forbidden
- 404 Not Found
- 429 Too Many Requests

Example custom error response:

```
{
  "error": "text is required"
}
```

Example framework error response:

```
{
  "detail": "Authentication credentials were not provided."
}
```

Interactive Documentation

Swagger UI: api/schema/swagger-ui
ReDoc: /api/schema/redoc
OpenAPI schema file: schema.yml