

KNOCKOUT / HOSPITALITY

HOTEL MANAGEMENT SYSTEM (PMS)

Complete Technical, Architecture,
Deployment & Operations Documentation

DOCUMENT

Technical handover · version 1.0

GENERATED

4 October 2026 · Asia/Kolkata

APPLICATION

KnockOUT · root package 2.0.0

REPOSITORY

a8b3d69a9f0569d537d3d21bee32544a298d94a0

SNAPSHOT

Working tree, including uncommitted mobile changes

SCOPE

Source analysis; not live production certification

INTERNAL · No real credentials included

Observed implementation and proposed improvements are distinguished throughout.

Contents

1. Executive summary	4
2. System features	5
3. Technology stack	7
4. Project directory structure	8
5. System architecture	9
6. Application request flow	10
7. Database architecture	11
7.1 Startup migration mechanism	11
7.2 Schema drift	11
8. Entity relationship diagrams	12
8.1 Tenant base DDL	12
8.2 Master DDL	13
9. Database data flow	14
10. API documentation	15
11. Authentication	16
12. Authorization and RBAC	17
13. Security architecture	18
13.1 Implemented controls	18
13.2 Recommended improvements	18
14. Environment variables	19
15. Installation guide	20
16. Local development	21
17. Docker documentation	22
18. Production deployment	23
18.1 Current implementation	23

18.2 Recommended deployment	23
19. CI/CD	24
20. Observability	25
21. Backup and restore	26
21.1 Proposed manual database backup	26
21.2 Restore rehearsal	26
22. Disaster recovery	27
23. Performance and scalability	28
24. Business workflows	29
25. User guide	30
26. Administrator guide	31
27. Testing	32
28. Troubleshooting	33
29. Operations runbook	34
30. Known limitations	35
31. Prioritized improvements	36
32. Appendices and evidence	37
32.1 Complete API reference	37
32.2 Database table and column inventory	67
32.3 Environment-variable index	79
32.4 Package version inventory	87
32.5 Error codes and operational glossary	88
32.6 Deployment and production readiness checklist	89
32.7 Source evidence and inspection scope	89
32.8 Module keys and additional contract notes	91
32.9 External technical references	92

1. Executive summary

KnockOUT coordinates restaurant table service, kitchen preparation, takeaway orders, billing, stock, staff attendance and daily finances across multiple companies. The master console manages company onboarding, subscriptions and module entitlements. Although the requested title uses PMS, this codebase is predominantly a restaurant/hospitality operations platform. Guest-room inventory, overnight stays, room-rate plans and lodging folios: **Not identified from the current codebase**. Staff check-in/check-out is attendance, not a hotel stay.

Primary users are Super Admin, company Admin, Waiter, Head Chef, Juicer and registration applicants. The system addresses order coordination, service/payment handoff, stock visibility and multi-company access. Browser clients use React/Vite; mobile uses React Native/Expo. NestJS hosts Express handlers. A master API authenticates and proxies requests to four role processes. MariaDB stores a master catalog and separate tenant schemas; MinIO/S3 stores images/reports; Redis relays change events between master replicas.

Docker Compose is the only full-stack orchestration found. Application functionality is substantial, but production readiness is not established: functional automation, TLS ingress, backup scheduling, monitoring and CI/CD are missing. Material risks include plaintext PINs, incomplete authorization, schema drift, destructive startup updates and financial transaction edge cases. These findings are source-based, not a live penetration test or database audit.

2. System features

Every implemented capability below maps to actual screens, entities and APIs. Appendix 32.1 expands individual contracts; workflows and user instructions appear in sections 24–26.

Feature / purpose	Users and screens	Backend, entities and API family	Workflow, validation, dependencies and edge cases
Company applications	Applicant; public registration/onboarding	master-server.js; company_registration_requests; /public/company-registrations, /onboarding-status, /complete-registration	Business/contact details, starter/growth/complete, 1/6/12 months; temporary PIN, approval then setup/payment reference. Payment is not gateway-verified.
Tenant provisioning	Super Admin; company workspace	provisionCompany; companies/company_users and tenant schema; /companies	Normalize company database name, clone primary schema, copy menu/combos, zero stock, generate Hotel ID/Admin PIN. DDL and catalog/object writes are not atomic.
Company controls	Super Admin; network/controls	companies.modules/status; /companies/:id/modules, /status, DELETE /companies/:id	Ten module flags; suspend/reactivate; exact company name required for deletion; primary tenant protected. Deletion drops schema, not necessarily objects.
SaaS billing	Super Admin, applicant; pricing/billing/onboarding	saas_invoices, module_pricing, tenant_subscriptions	Six-month 5% and annual 10% discount, 18% tax; two-day grace, request-triggered suspension. Invoice paid status does not renew subscription dates.
Identity/profile	Portal roles; login/profile	master_users, company_users, users; /login, /public/resolve-login, /profile	Hotel ID/PIN lookup; HMAC token; profile name/phone/email/image. Email format validation; old photo removed after replacement.
Dashboard	Admin/role overview; mobile PremiumDashboard	GET /state; tables/orders/attendance	Live KPIs and shortcuts; mobile paid-order value selects orders created today, not payment timestamp. History is bounded.
Restaurant tables	Admin, Waiter; floor views	restaurant_tables; /tables, /tables/:id/status	Positive number/seats and area; duplicate number blocked; inactive table restored by number. Active order blocks deletion/release, cleaning blocks order.
Table bookings	Admin create/cancel; Waiter views	bookings; POST /bookings, DELETE /bookings/:id	Future date/time, phone, 30–240 minutes; lock table, overlap check, commit then SMS. No implemented arrival/seating transition.
Dine-in orders	Waiter; order builder/table drawer	orders/order_items/menu_items; /orders, /orders/:id/items	Available menu price snapshot; occupy table; additions use batch number. Billing/completed blocks additions. Initial quantities insufficiently validated.
Preparation	Chef/Juicer; kitchen and parcel queues	order_items.production_status; /orders/:id/items/status	New/preparing/ready per batch; Juicer owns normalized category juices, Chef others. Backend combo routing uses parent category.
Handoff	Chef, Waiter; round tickets	order_items.handoff_status/orders.status; /batches/:batchNo/handoff	Ready round → Chef collected → Waiter received. Legacy whole-order status route does not update line handoffs.
Parcels	Admin creates/pays/completes; kitchen prepares	orders.order_type=parcel; /parcels, /mark-paid, /finalize	No table; optional advance payment. Cash/Card / UPI are labels, not payment integrations. UI readiness rules exceed finalize guards.

Feature / purpose	Users and screens	Backend, entities and API family	Workflow, validation, dependencies and edge cases
Billing/printing	Waiter request; Admin finalization; web receipts	billFor, orders/order_items; /request-bill, /bill, /finalize	Stored line prices summed; tax/CGST/service zero. Completion sets table cleaning. Client estimates use current menu prices.
Menu/combos/photos	Admin; Chef/Juicer availability	menu_items/combo_components; /menu, /combos, /image	Create/edit dish or combo composition; delete means unavailable. Juicer only juice availability. Images require MIME prefix, max 5 MiB; object storage dependency.
Inventory	Admin; stock	inventory/inventory_transactions; /inventory, /movements	Opening stock and purchase/usage/adjustment/waste; positive movement, no negative resulting balance. History blocks delete; no recipe depletion.
Stock requests	Chef requests; Admin manages	stock_requests; /stock-requests and /:id/status	Existing inventory, positive quantity; pending/ordered duplicate check. Resolving does not automatically add stock.
Finance	Admin; daily finance/calendar	finance_entries; /finance	Income/expense, category, description, amount/date, payment label/reference. Not double-entry accounting.
Supplier balances	Admin; purchases/payments	supplier_purchases/supplier_payments; /supplier-purchases	Purchase and optional initial payment, subsequent partial payments with purchase lock and overpayment check. Purchase delete removes payment history.
Staff logins	Admin staff; Chef Juicer login	users; /staff, /juicer-login	Generated six-digit PIN, singleton Admin/Head Chef/Juicer rules, daily/monthly pay. Staff soft-delete preserves shifts; Admin protected.
Kitchen roster	Admin/Head Chef; chef management	kitchen_staff; /kitchen-staff	Non-login personnel with designation/specialization/pay. Hard delete; distinct from attendance users.
Attendance	Staff portal; Admin monitor/correction	staff_attendance; /attendance/:id, /staff/:id/check-in/out	Sequential duplicate/open-shift checks; no concurrent unique constraint. Same-role membership checked, not authenticated user ownership.
Settings	Admin screen	settings; PUT /settings	Hotel/currency/charge fields; no explicit role guard on handler. Charge fields do not enable restaurant taxes.
Reports	Web stock/finance/master export	storage.js; POST /reports	Client-supplied filename/content/type stored as object. No server report validation or immutable ledger export.
Realtime	Portal users	/ws; realtime.js; Redis	Token-bound channels, heartbeat and polling fallback. Events are transient invalidation, not audit history. AttendancePanel socket lacks token.

Room types, hotel stays, room housekeeping/maintenance, guest/corporate/travel-agent master profiles, rate plans, seasonal rates, refunds/deposits, OTA integration and full audit logs: **Not identified from the current codebase**. Table cleaning, staff shifts and SaaS discounts must not be described as corresponding lodging features. Currency is configurable in settings, but major formatters hardcode INR/en-IN; full localization is not implemented.

3. Technology stack

Component	Declared technology/version	Purpose
Runtime	Node 26.0.0; npm 11.12.1	Exact runtime checks in web/backend preinstall
Browser	React/React DOM ^19.1.1; Vite ^7.0.0	Unified role-aware web client
Browser UI	lucide-react ^0.536.0; motion 13.1.0	Icons and motion effects
Backend	NestJS 11.2.1; Express ^5.1.0	Express handlers via Nest ExpressAdapter
Languages	JavaScript, JSX; TypeScript ^5.8.3 dependency	Most application sources are JS/JSX
Database	MariaDB 11.4 image; mysql2 ^3.14.3	Raw SQL and pooled transactions; no ORM
Realtime	ws ^8.21.3; redis 5.12.1; Redis 7.4-alpine	WebSocket and cross-master pub/sub
Storage	minio ^8.0.5; minio/minio:latest	MinIO or S3 objects
Uploads/HTTP	multer ^2.0.2; cors ^2.8.5; native fetch	Memory uploads, CORS and proxy
Mobile	Expo ~57.0.24; React Native 0.86.3; React 19.2.3	iOS/Android; independent npm project
Database console	phpmyadmin:latest	Database administration
Testing	k6, runner version not pinned	Load test script, not functional suite
Distribution	eas.json, CLI >=12.0.0	Native development/preview/production profiles
Build	npm workspaces, Docker Compose	Root web/backend and service orchestration


Full package and lock-resolved versions are in Appendix 32.4. Lock versions do not establish deployed versions. Cloud compute, reverse-proxy product, monitoring vendor and CI/CD platform: **Not identified from the current codebase**. Optional S3 support is not proof of an AWS deployment.

4. Project directory structure



Generated dist bundles, node_modules, .git internals, Expo caches and historical mobile export-check directories are omitted. The root prototype uses localStorage and is not the React/MariaDB runtime. README links to TESTING_GUIDE.md, which was not found in this snapshot.

5. System architecture




Browser HTTP helpers target page hostname:5100 directly; browser WebSockets target page-origin /ws through Vite. Although Vite proxies /api, most HTTP calls bypass that proxy. Mobile uses EXPO_PUBLIC_API_HOST and EXPO_PUBLIC_API_PORT (default 5100), HTTP/ws transport.

Only master is published among API containers. It authenticates, checks company/module state and selects a role target from the token. Internal role APIs trust tenant/user headers and PORTAL_ROLE. AsyncLocalStorage scopes SQL to a tenant-specific pool. They must remain private.

A tenant is a company/schema; no nested property hierarchy exists. Master uses administrative credentials across schemas. Redis relays events, not database state or jobs. Role state cache is process-local. Objects use sanitized company-name prefixes. No TLS ingress, load balancer, cloud infrastructure or worker service is defined. Jobs run during startup or requests.

6. Application request flow



The order handler rejects non-Waiter roles, empty items, missing/cleaning tables, active orders and a current reservation. Prices are copied into order_items. Exceptions roll back the transaction, but a post-commit bill read can fail after the write succeeds. Blind POST retries are unsafe. Initial line quantities lack robust validation.

Change notifications use the request tenant header while proxy SQL identity uses the token tenant. This mismatch needs correction; events must not be treated as authoritative audit records. Cached state can briefly lag a committed mutation.

7. Database architecture

MariaDB via mysql2/promise, raw parameterized SQL, no ORM. Default schemas: knockout_master and knockout; new schemas tenant_<normalized_name>, with legacy knockout_<digits> also accepted. Runtime source declares 16 tenant and 9 master tables, plus views tenant_waiting_list and tenant_registrations. Appendix 32.2 lists columns, primary keys, FKs, indexes and constraints.

Most primary keys are AUTO_INCREMENT id. settings uses id=1; module_pricing uses module_key. No stored procedures, custom SQL functions, triggers or independent sequences were identified. Major indexes include booking_slot, request_status, order_live_history, order_payment_date, order_round_status, user_portal_login, registration_status, invoice_month and company_login. company_users has unique company/user and company/PIN; companies has unique company/database/cy_db/Hotel ID; invoices have unique company/month.

7.1 Startup migration mechanism

Role migrate() creates tables, executes repeated ALTER/UPDATE upgrades, scans recognized company schemas and seeds the default tenant if users is empty. Master initialize() independently upgrades catalog tables, syncs user directory, ensures finance tables, migrates image prefixes and generates invoices. There is no migration ledger or rollback command.

RUN_MIGRATIONS=false suppresses role migrate only. Compose does not inject that variable into role containers, despite its example-file presence; master initialize ignores it. Startup updates reset charge settings, translate salary types, backfill handoffs and release some reserved tables. These are data mutations, not harmless schema checks. Replicas can race.


7.2 Schema drift

knockout-production.sql is an older structure-only export with unsigned IDs and additional uniqueness/indexes, but missing newer fields/master tables. Combining it with runtime DDL can fail on FK type mismatches. Do not treat it as the authoritative current migration.

Provisioning uses CREATE TABLE LIKE; foreign keys are not preserved by this mechanism (MariaDB CREATE TABLE documentation, reference R1 below). ensureDailyFinanceTables also creates supplier_payments with an index instead of an FK when missing. ER relationships below describe explicit base DDL, not a verified constraint guarantee for every tenant. Inspect SHOW CREATE TABLE and information_schema before migration/recovery.


8. Entity relationship diagrams

8.1 Tenant base DDL



Parcels have nullable **table_id**. Base DDL cascades order-line, combo-component and supplier-payment deletion from parents. **restaurant_tables.order_id** is an application pointer without FK. **settings**, **finance_entries** and **kitchen_staff** are independent; **kitchen personnel** are not attendance users. No guest/payment master table exists for restaurant transactions.

8.2 Master DDL



company_users.tenant_user_id and usage_logins.user_id are logical cross-schema references without FK. Company deletion cascades catalog dependents, while registration company_id becomes null. master_users, module_pricing and notification_outbox are independent. Registration views partition by completion, not approval alone.

9. Database data flow

Operation	Reads/locks	Writes	Edge/failure boundary
Booking	Active table FOR UPDATE and same-date overlap	Confirmed booking; post-commit notification status	SMS failure retains booking; cross-midnight overlap risk
New order	Table/current booking, available menu	orders/lines; occupied table	Bill lookup after commit may fail
Additional round	Order and maximum batch	New lines; order reset new	No idempotency key
Kitchen/handoff	Batch lines and order locks	Production/handoff/aggregate state	Parent category owns combo routing
Finalize	Bill before transaction; then order lock	Paid totals/completion; table cleaning	Early returns after BEGIN require rollback review
Stock	Inventory row lock	Quantity and movement history	No recipe link; adjustment adds or subtracts according to adjustmentDirection
Supplier payment	Purchase lock and previous payment sum	Payment record	Overpayment rejected; no external settlement
Staff	Tenant user queries	users then company_users replacement	Directory sync can fail after tenant write
Onboarding	Approval/name/schema validation	Tenant DDL, company, subscription, invoice	Cross-schema/object/notification flow is non-atomic

10. API documentation

Default public base: `http://localhost:5100/api`. Use Authorization: Bearer <ACCESS_TOKEN>. Client tenant/role headers also exist, but the gateway derives internal role/user/schema from the token. Internal role routes are not safe unauthenticated public endpoints.

JSON limit is 6 MB. Image endpoints accept multipart field image, maximum 5 MiB. Error format is usually {message}; company suspension/module denial also returns code. Generic exceptions return status 500 and error.message. There is no OpenAPI specification, API version prefix, pagination contract or idempotency mechanism.

Appendix 32.1 documents all 76 explicit Express handlers separately, plus Nest GET `/api/framework`, middleware GET `/api/session` and `/ws`. Duplicate master/role paths have different responses. Tenant authenticated requests are intercepted before master handlers.


```
{ "paymentMethod": "Cash" }
```

Booking returns 201 {ok,id,notificationStatus,notificationDetail}. Order returns 201 {id,bill}; bill contains items/subtotal/tax/cgst/service/total. Bill item fields include menuId, qty, note, price, name, icon, imageUrl. Finalization returns {id,paymentStatus,paymentMethod,bill}. Replace placeholders and IDs with authorized test-tenant data.

11. Authentication

Staff login resolves four-digit Hotel ID and six-digit PIN through company_users and active companies. Master can use its PIN with no Hotel ID or reserved master identifier. Applicants use temporary PIN without Hotel ID and receive no portal bearer token.

Tokens are custom payload.signature, not JWT: base64url JSON {id,role,companyDatabase,exp} signed with HMAC-SHA256, twelve-hour expiry in milliseconds. Verification checks timing-safe signature equality, expiry, role and tenant format. MASTER_SESSION_SECRET has a fallback derived from DB root configuration; production should supply a strong independent secret.



PINs are plaintext, duplicated in user directories. Hashing, refresh tokens, OAuth, server logout, password reset, MFA and login rate limiting: **Not identified from the current codebase**. User PIN changes/deactivation do not revoke every existing token. Browser logout clears sessionStorage; mobile uses AsyncStorage for persisted identity and an in-memory token. AsyncStorage is not an encrypted vault. No authentication cookies/cookie configuration exists.

12. Authorization and RBAC

Role	Module	Read	Create	Update	Delete	Special actions
Super Admin	Companies/catalog	Yes	Company	Status/modules/ PIN/pricing	Non-primary company	Approve/reject application, invoice status
Admin	Tables/bookings/ menu	Yes	Yes	Table state/menu /combo	Table soft-delete, cancel, menu hide	Photos/reports
Admin	Orders	Yes	Parcels only	Payment/finalize	No endpoint	Not waiter dine-in creation
Admin	Stock/finance/su ppliers	Yes	Yes	Stock/request	Guarded stock, finance/purchase	Supplier paymen ts
Admin	Staff/roster	Yes	Staff/roster	Staff/roster	Soft staff except Admin; hard roster	Attendance correction endpoints
Waiter	Tables/orders	State	Order/round	Table status/rece ipt	No	Bill request
Chef	Kitchen/stock/tea m	State and stock	Stock request, roster, Juicer login	Food production, availability, roster	Roster	Confirm collectio n
Juicer	Juice	State	No orders	Juice production/ availability	No	Attendance
Staff	Attendance/profil e	Same-role attendance; own profile	Shift	Checkout/profile	No	No ownership check on attenda nce ID
Tenant roles	Unguarded handlers	Bill/state	Reports/images	Settings	Menu image	Access gap, not intended policy

Gateway maps module checks for bookings, tables, finance/suppliers, inventory/stock, menu/combo and staff/attendance/kitchen-staff. Chef/Juicer portal flags are enforced. Billing/parcels paths are not mapped to their flags. UI hiding is not API authorization. Non-Admin state filtering removes some fields, but supplier data and other broad projections remain.

Role APIs trust private network and forwarded headers; they do not validate bearer signatures. Master tokens route to master handlers, not arbitrary tenant impersonation via headers. Tenant DB credentials remain broadly privileged, so logical schema isolation is not an independent credential boundary.

13. Security architecture

13.1 Implemented controls

HMAC/expiry/timing-safe comparison; token-derived proxy identity; company/partial module gates; many role checks; validated dynamic database identifiers; SQL placeholders; locks/transactions for key workflows; MIME and upload-size limits; filename sanitization; internal-only role ports; x-powered-by disabled; authenticated WebSockets with heartbeat.

13.2 Recommended improvements

Replace plaintext PIN storage with reviewed credential hashing and throttling; remove seed/fallback credentials and credential-bearing state responses. Add revocation, secure mobile credential storage and explicit secrets management. Enforce action/record ownership and complete module checks; minimize state by role; authenticate internal services and reduce DB grants.

TLS, CORS allowlists, CSP/HSTS/security middleware, CSRF controls, secret rotation and API throttling are absent. Bearer headers reduce traditional cookie-CSRF but not XSS/token theft. React escapes text; legacy prototype innerHTML and receipt HTML need separate escaping review. General-purpose sanitization is not identified.

Validate finite numeric ranges, dates and transitions server-side. Verify decoded image bytes/dimensions rather than MIME alone. Keep reports/profile images private with signed URLs and stable tenant IDs; default MinIO policy covers the entire bucket. CSV formula protection was not identified. Avoid raw database errors and redact PINs, tokens and PII in logs. Query-string WebSocket tokens can enter URL logs. Dependency vulnerability status is not established by source inspection; no zero-vulnerability claim is made.

14. Environment variables

Appendix 32.3 lists all discovered application/Compose/Expo/k6 variables, safe examples, requirements and sources. No private .env values are reproduced. VITE_ and EXPO_PUBLIC_ values are public configuration, not secret storage.

Development requires reviewed database/storage credentials, DB_NAME, public object URL and signing secret. Raw Node scripts do not automatically load .env; export configuration or use Node --env-file. Compose substitutes root .env; Expo loads mobile/.env. Testing requires a disposable tenant and test PIN. Staging/production require explicit secrets, reachable TLS endpoints, selected storage and recovery controls. Separate staging/prod manifests were not found.

RUN_MIGRATIONS, NOTIFICATION_WEBHOOK_URL, REDIS_EVENTS_CHANNEL, INSTANCE_ID, MINIO_SSL and AWS aliases are read by code but not all injected by Compose. Adding variables to .env alone is insufficient. VITE_API_URL is set in Compose but ignored by frontend/src/api.js, which fixes port 5100.

15. Installation guide

Prerequisites: Git, Docker with Compose, Node 26.0.0 and npm 11.12.1. Native builds need platform tooling (Xcode/macOS for iOS; Android SDK for Android). Exact platform SDK minimum versions: **Not identified from the current codebase.**

Do not overwrite an existing environment file. Review the example locally and replace credentials before first start. Avoid printing expanded Compose configuration, which includes secrets.

```
curl --fail http://localhost:5100/api/health
```

Startup performs schema creation/upgrades and demo seeding when empty. Seed PINs are deliberately omitted; obtain credentials through an authorized operator. Changing .env passwords does not rotate existing initialized DB accounts.

```
npm run start:clear
```

Mobile is outside root npm workspaces and uses its own lock. Set EXPO_PUBLIC_API_HOST to the workstation LAN IP for a physical phone; keep API reachable. This is the current HTTP development path, not a recommended production transport.

16. Local development

Compose is the complete runnable topology because master proxy targets Docker service names. Root npm run dev starts one role API and Vite, not master plus all roles; it does not provide full unified login. Direct backend defaults to 4000 while Vite fallback proxy is 6000, requiring explicit configuration.

Run Compose dependencies/APIs, then host Vite for hot reload:

127.0.0.1

Vite prints its chosen address (normally 5173). HTTP still uses hostname:5100; WebSocket /ws uses the configured proxy. Compose has no source bind mounts, so container code is a build snapshot. Backend watch command exists, but host processes do not automatically replace the master's Docker targets.

Service	Default local address
Compose web	http://localhost:5200
Master API	http://localhost:5100/api
WebSocket	ws://localhost:5100/ws
MariaDB host	localhost:3307
phpMyAdmin	http://localhost:9200
MinIO API / console	http://localhost:9100 / http://localhost:9101
Metro	Usually 8081; use printed Expo address

Use browser network/console, container stdout/stderr and Expo bundler output for debugging. Redact bearer values, query tokens and personal data before sharing logs.

17. Docker documentation

Both Dockerfiles use node:26.0.0-alpine and install npm 11.12.1. Backend uses npm install --omit=dev; master overrides start to start:master. Frontend installs packages and runs Vite dev, not a production static server. Image EXPOSE 4000 does not override Compose PORT values.

Service	Internal port	Host port	Persistence / health
mariadb	3306	3307	knockout_mariadb; connect/InnoDB check
redis	6379	None	knockout_redis; ping, AOF, 512 MB allkeys-lru
minio	9000/9001	9100/9101	knockout_minio; live endpoint
phpmyadmin	80	9200	Database dependency
admin-backend	6001	None	/api/health
waiter-backend	7000	None	/api/health
chef-backend	8000	None	/api/health
juicer-backend	9000	None	/api/health
superadmin-backend	5000	5100	/api/health
superadmin-frontend	5000	5200	No explicit healthcheck

Implicit Compose network, restart unless-stopped, three named volumes with project-prefix actual names. No resource limits/custom network declaration. Host ports bind without loopback restriction. Health dependencies sequence startup but do not provide runtime failover.

```
docker compose down
```

Do not use --volumes for routine shutdown. Restrict DB/storage administration interfaces. latest image tags reduce reproducibility.

18. Production deployment

18.1 Current implementation

Single-host Compose plus scaling port-range override (5100–5102, !override syntax). SCALING.md proposes replicas, TLS load balancing and managed infrastructure; it is not an infrastructure deployment. TLS/DNS, Kubernetes, Terraform, registry publishing, production static hosting and automated rollback: **Not identified from the current codebase.**

18.2 Recommended deployment

Close critical findings; pin source/images; build frontend static assets; create production static hosting separately. Rehearse versioned migrations and backup/restore before replicas start. Introduce TLS ingress for static assets, /api and /ws; replace hardcoded browser port and mobile transport with configurable URLs. Keep role APIs, DB, Redis and admin consoles private; use least privilege and secret injection.

Deploy immutable images, verify liveness/readiness then safe login/state and role workflows. Retain previous image plus schema-compatible rollback plan. Reverting code does not revert startup DDL/data updates. Suggested topology: Internet → DNS/TLS ingress → frontend/master replicas → private role APIs → managed DB/Redis/objects. No deployment was executed for this documentation.

19. CI/CD

No pipeline files/triggers, registry automation, runner secrets or rollback automation found. EAS profiles are build settings, not CI or store submission evidence.

Recommended: PR → pinned install → source checks/unit/API isolation tests → browser/native bundle build → dependency/image/secret scans → immutable artifacts → staging migration rehearsal → functional smoke tests → approved production rollout → health validation. Use isolated credentials, no production secrets in PR jobs, and backup evidence before destructive migration. Native signing and release versioning need their own secured pipeline.

20. Observability

Existing: console startup/error logging, Nest logs, Redis errors and startup retry messages, captured by Docker stdout/stderr. No central retention/rotation, metrics, dashboards, alert rules or tracing configuration found.

/api/live is process liveness. Role /api/health queries SQL and reports provider; master /api/health queries catalog and reports realtimeStatus. It does not deeply probe every API/storage/SMS dependency. /api/framework is metadata, not full readiness. usage_logins is usage tracking, not a complete audit log. notification_outbox statuses are not updated by queueNotice delivery handling.

Recommend redacted structured request IDs, latency/error rates, DB pool/locks, WebSocket counts, Redis errors, object failures and operational alerts. Protect logs that might contain query tokens, raw SQL errors or customer details.

21. Backup and restore

Scheduled backups, retention, encryption, off-site copies and restore-test evidence: **Not identified from the current codebase**. Volumes are persistence, not backups; structure-only SQL has no business records.

Recommended: encrypted daily DB backups, verified binlog/PITR if needed, independent/versioned object backups, protected configuration/secret recovery and image references. Preserve catalog and all tenant schemas together. Pause provisioning/DDL during logical snapshots.

21.1 Proposed manual database backup

The following is a proposed procedure, not an existing automation. Run only against an approved target. Output contains sensitive records/PINs; restrict, encrypt and transfer it using organization-approved tooling. The password is taken from the existing container environment and not printed.

```
shasum -a 256 backups/pms-all.sql
```

Do not commit backups. --single-transaction does not make concurrent DDL safe (MariaDB mariadb-dump documentation, reference R2 below). A concrete off-site destination/KMS configuration is not identified.

21.2 Restore rehearsal

Restore only to an isolated MariaDB 11.4 recovery stack; all-database dumps can replace schemas/accounts. Keep APIs stopped to prevent migration. Validate checksum/decrypt, restore, recover object keys and bucket policy, compare catalog/tenant/FK counts, test sampled bills/stock/shifts, then start a controlled app instance and verify authorized login/isolation. Re-enable writes/notifications only after validation.

```
all.sql
```

DB backups contain object references, not image/report bytes. No MinIO/S3 backup CLI or versioning configuration exists here; select and test an object-backup procedure before declaring recoverability. Copying a live MinIO directory is not automatically consistent. Redis carries transient events, not authoritative business data; reconnect/refetch after loss.

22. Disaster recovery

No established RPO/RTO. Suggested targets after automation: database RPO 15 minutes with proven binlogs, otherwise up to 24 hours for daily backups; RTO 4 hours. These require business agreement and drills, not guarantees.

Scenario	Detection / immediate action	Recovery / validation	Prevention
App failure	Health/error alerts; stop rollout	Known-good image, verify roles/login/state	Tested redundancy and drain
DB failure	SQL readiness/connectivity; stop writes	Failover/restore; reconcile master and tenants	HA, PITR and drills
Disk failure/full	Capacity or I/O errors; contain writes	Replace/expand storage, verify DB/object integrity	Alerts, rotation, redundancy
Accidental deletion	Missing data; preserve evidence	Isolated point-in-time copy and reviewed reconciliation	Audits and destructive-action controls
Bad release	Errors/billing discrepancies; halt	Compatible image rollback or forward fix/restore	Migration/compatibility tests
Credential breach	Suspicious access; restrict ingress	Rotate keys/passwords, revoke sessions, assess exposure	Strong auth and secret manager
Region/host loss	Broad outage; declare incident	Recreate approved target, restore DB/objects/config, DNS switch	Off-site backups, infrastructure as code

Signing-key rotation affects subsequent validation but does not alone close all already-authorized sockets. Validate isolation, credentials and storage policy before reopening access.

23. Performance and scalability

Existing controls: pooled SQL, bounded queues, keepalive, tenant idle-pool cleanup, process-local state promise coalescing (1-second default), 90-day history default clamped 7–365, operational indexes and Redis cross-master event relay. These do not prove a user-capacity claim.

getState issues 16 parallel queries: max 5,000 orders; 300 attendance/movement/request rows; 500 finance/purchase rows; 1,000 supplier payments. Order items are not limited to the same 5,000 orders; matching repeatedly filters arrays. Daily order sequence uses correlated counts. Master state fans out per company, enforces subscriptions and creates invoices; login also enforces subscriptions.

Pool budget is active tenants × role replicas × pool limit, plus master pools. Large state responses, memory uploads, fully buffered proxy bodies and no explicit fetch timeouts are likely bottlenecks. Request-triggered jobs can race between replicas. No shared state cache or pagination API exists.

Recommend smaller role projections, pagination, reporting summaries, worker/outbox processing, explicit timeouts, tenant connection budgets and measured staging load tests. Replication/HA/load balancing described in SCALING.md remains proposed infrastructure.

24. Business workflows

Reservation: Admin selects future date/table → enters phone/time/duration → locked overlap validation → confirmed row → SMS attempt → active slot projects reserved table → cancel to release. A seated enum exists but no arrival/seating endpoint; active reservation blocks ordering. Modification/no-show/room-change/early check-in/late checkout: **Not identified from the current codebase.**

Dine-in: Waiter selects available table and food → create order → Chef/Juicer prepare batches → all round items ready → Chef collected → Waiter received → optional extra round → Waiter bill request → Admin payment/finalize → table cleaning → available. Finalization does not enforce every UI predecessor.

Parcel: Admin enters customer/items → optional advance Cash/Card / UPI → preparation → ready → Admin records unpaid balance and completes. No table; no implemented refund/provider settlement.

Stock/supplier: Chef requests → Admin marks ordered → separately records stock movement and supplier purchase → partial/full payments → request resolved. These are human-coordinated actions, not linked automatic procurement. No ingredient recipe depletion.

SaaS: apply → temporary PIN → approval → setup/payment reference → provision → paid invoice/subscription → expiry → grace → suspension on enforcement request. A complete verified renewal flow updating subscription dates is absent.

25. User guide

Sign in with assigned identity, keep PIN private, and use role navigation. Module visibility follows company settings; refresh after writes if cache briefly lags. Do not infer accounting totals beyond loaded history.

Screen	Access / action / fields	Expected result / common error
Registration	Public web Register; business/admin/email/phone/package/duration	Pending application; duplicate name/email conflicts
Onboarding	Temporary PIN login; approval, address/type/payment reference	Hotel/Admin credentials after completion; approval required
Master workspace	Choose company; status/modules/users/revenue/billing	Company controls; deletion removes tenant database
Admin overview	Dashboard; inspect metrics and shortcuts	Operational snapshot, not audited ledger
Tables	Add number/seats/area; choose table/status	Active bill prevents release/delete
Bookings	Select date, table/time/duration/phone	Confirmed even if SMS fails; overlap conflicts
Waiter orders	Select table/dishes/quantities/notes; send or add round	Kitchen round; unavailable dish rejected
Kitchen/Juice	Select ticket/batch; preparing/ready	Other station may still block handoff
Handoff	Chef collection then Waiter receipt	Premature transition rejected
Billing	Waiter requests; Admin reviews/records payment	Completed bill and table cleaning
Parcels	Admin creates customer/items, chooses pay timing	Takeaway completion without table
Food & Photos	Create/edit dish or combo, upload photo	Hidden items preserve history; max 5 MiB
Stock	Item/unit/min/cost; movement and request status	History updated; historical item cannot delete
Finance	Calendar day, entry or supplier purchase/payment	Balances; overpayment rejected
Staff	Admin creates role/pay/active; edits or deletes	Generated PIN, singleton role rules
Chef Management	Non-login team roster; Juicer login	Separate personnel/login concepts
Attendance	Shift start/end and recent history	Duplicate/no-open-shift conflicts
Profile	Web profile, name/phone/email/image	Email validation and replacement photo
Settings	Hotel/currency/charge values	Saved fields do not activate tax calculation
Reports/print	Web finance/stock export and receipt controls	Client file/print; compare authoritative server bill

Mobile implements role operations and a simpler master view; full web public onboarding/master-control parity is not established. No useful screen captures were identified in source assets; logos/watermarks are not screenshots, so no UI evidence is fabricated.

26. Administrator guide

Super Admin provisions or approves companies, checks generated identity/schema, privately distributes access and configures modules. Company Admin creates tables/menu, Waiters and Head Chef, salary basis, stock/finance. Head Chef creates Juicer login and kitchen roster. Deactivation affects subsequent PIN resolution after sync but does not guarantee token revocation.

Do not claim Settings activates restaurant taxes: billFor disables them. SaaS tax is distinct. Integrations are environment-configured. Room/rate configuration and full audit administration are absent. Tenant/finance/supplier deletion needs an organizational approval/backup procedure because application controls do not provide a full approval history. Verify orphaned objects after tenant deletion.

27. Testing

Discovered: runtime checks, Vite build, Expo export check and k6 script. Unit/API integration/UI/E2E/migration suites were not identified. Old export directories are not functional test suites; TESTING_GUIDE.md link is unresolved.

capacity.js

Use approved secret injection to avoid PIN shell history. k6 ramps HTTP to 500 VUs and runs 100 WebSocket VUs; thresholds include failure <1%, p95 <500 ms, p99 <1200 ms. These are thresholds, not measured results. It logs in/reads state; it does not validate financial mutations or 15,000 users.

Coverage to add	Critical scenarios
Auth/isolation	Tampered/expired tokens, suspended users/companies, cross-tenant headers, same-role attendance IDs
Module/role	Settings/images/reports, billing/parcels disable, minimal state payload
Reservations	Concurrent same slot, midnight overlap, cancellation, arrival blocker, SMS failure
Orders/billing	Concurrent creation, quantities, extra rounds, mixed combos, price changes, repeat finalize, rollback branches
Stock/finance	NaN/negative input, concurrent supplier payments, movement/delete history
Provision/recovery	Partial provisioning, duplicate completion, FK drift, old dump migration and full object restore

VERIFICATION.md records checks actually executed for documentation. No production mutation, capacity run or restore was performed.

28. Troubleshooting

Problem	Likely cause	Diagnose	Resolve
Install fails	Exact Node/npm mismatch	Version commands	Use declared runtimes
App not ready	DB/storage or migration failure	Compose ps/logs	Fix dependency/DDL first
DB connection	Wrong port/credentials or existing account	DB health; 3307 host vs 3306 internal	Secure account/config correction
Login	Wrong ID/PIN, inactive/suspended, stale directory	Safe response and user state	Authorized identity/sync repair
401	Expiry/token mismatch/master privilege	Redacted request headers	Sign in; align replica secret
403	Role/module/suspension	Error code	Authorized policy review
404	Wrong method/path/record	Appendix contract and ID	Correct route/tenant record
409	Booking/state/balance conflict	Inspect current state	Follow predecessor or choose other slot
500	SQL/input/storage exception	Sanitized log/schema	Fix cause; avoid blind POST retries
502	External ingress/upstream	Proxy logs and health	Not app-defined; repair target
CORS/mixed content	Fixed API URL/TLS mismatch	Browser network	Consistent TLS/configuration
Migration fails	Old export/type drift/parallel DDL	First SQL error, SHOW CREATE TABLE	Backed-up single controlled migration
Port conflict	Existing listener	Compose ps, host sockets	Change port and client together
Restart loop	Exhausted startup retries	Service logs	Fix dependency, not volume reset
Disk full	DB/objects/logs	df -h; docker system df	Expand/archive approved data
CPU/memory/slow API	State fan-out, buffered requests	Stats, payload, SQL	Pagination/profile/limits
Pool exhaustion	Tenant × replica connections	Processlist/pool metrics	Connection budgets/query fixes
Missing image	Public URL/port/policy	Object URL/key	Reachable URL, private asset policy
Attendance stale	Missing WebSocket token	WS close 1008	Fix socket token; polling fallback
Mobile offline	LAN host/transport	Expo/device connectivity	Set host/port, restart Metro

29. Operations runbook

```
docker compose exec mariadb mariadb -u root -p
```

Inspect SHOW DATABASES/PROCESSLIST/CREATE TABLE and information_schema FK/index metadata. Avoid dumping user/outbox tables into shared logs. Backups/restores follow section 21 on approved targets. Before rollout record image/source, backup reference and health; afterward validate roles and financial flows. Roll back images only with schema compatibility; startup changes are not automatically undone.

Certificate renewal: **Not identified from the current codebase.** Add provider-specific instructions when ingress is selected. Disk cleanup must not use broad volume pruning or down --volumes. Incident sequence: record impact/time → dependency/recent-change checks → preserve redacted evidence → restrict writes if needed → single-owner recovery → validate isolation/totals → communicate and track follow-up.

30. Known limitations

PMS scope does not include lodging rooms/stays. Plaintext PINs and development fallback credentials exist; state can expose PINs. Revocation/MFA/rate limits are missing. Some handler guards and module checks are incomplete; attendance ownership and state minimization are weak. Private role networking is mandatory.

Restaurant taxes are disabled; client/server bill price sources differ. Finalization reads bill before lock; some transaction paths return without rollback. Payment references are unverified. Renewal/delivery workers are incomplete. Startup DDL/data rewriting and schema cloning/export drift create recovery risk.

History truncation, query fan-out, memory buffering, hardcoded endpoints and development frontend hosting constrain operations. Storage prefixes/privacy and event-header routing need review. No automated functional suite, CI, recovery schedule or measured capacity. Large frontend file and compressed backend/mobile handlers make maintenance harder. No literal TODO/FIXME was found in scanned authored sources; absence of markers does not imply completeness.

31. Prioritized improvements

Priority	Problem/risk	Recommendation	Complexity / benefit
P0	Credential theft/guessing	Strong auth, hashing/throttling, explicit secrets, remove PIN exposure	High; tenant protection
P0	Privilege/ownership gaps	Central role/object guards, internal auth, minimal state	Medium-high; access integrity
P0	Financial/schema inconsistency	Version migrations/FKs, transaction cleanup, immutable bills/idempotency	High; data integrity
P0	Unverified recovery	Encrypted off-site DB/object backups and restore drill	Medium; recoverability
P1	Dev/public deployment	Production hosting, TLS, private ports, least privilege	Medium; lower attack surface
P1	Payment/onboarding gaps	Verified/manual-approved payment and durable renewal	High; correct entitlements
P1	No regression evidence	Isolation/concurrency and UI tests in CI	High; safer releases
P1	Missing telemetry	Redacted structured logs, metrics, alerts/audit	Medium; faster incidents
P2	Scaling/jobs	Pagination/report summaries, outbox workers/timeouts	High; predictable latency
P2	Endpoint/parity debt	Configurable API transport, shared contracts, parity map	Medium; maintainability
P2	Storage coupling/privacy	Stable tenant IDs, signed links/retention	Medium; privacy
P3	Monolithic code/docs drift	Split/format modules and generate docs in CI	Medium; reviewability
P3	Future lodging PMS	Define room/stay/rate/folio requirements separately	High; accurate scope

32. Appendices and evidence

Inventories describe inspected source, not a guarantee that every migration ran or endpoint was exercised. Fields read by a handler are not automatically required; validation/defaults are distinguished. No real credential values are included.

32.1 Complete API reference

Authentication descriptions apply to the public master gateway unless explicitly internal. All standard endpoints below have no query parameters unless listed. IDs are path identifiers, not permission grants. A 500 {message} is possible from shared error middleware on every asynchronous handler. Extracted shapes use <computed> for derived values and <name> for local variables; these are documentation notation, not literal response strings. Success status defaults to 200; 201 is called out by explicit status lists. Validation messages are actual source guards; not every guard is a complete schema.

A01. GET /api/live — role

Process liveness. Source: backend/src/server.js:56.

Contract	Observed behavior
Authentication / role	Internal role service: no token validator; network-restricted. Public master path differs.
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, service: <computed>}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A02. GET /api/health — role

SQL readiness and runtime metadata. Source: backend/src/server.js:57.

Contract	Observed behavior
Authentication / role	Internal role service: no token validator; network-restricted. Public master path differs.
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, service: <computed>, portal: <portalRole>, database: "mariadb", storage: <storageProvider>}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A03. GET /api/state — role

Read role/company aggregate state. Source: backend/src/server.js:58.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	<state>
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

Tenant response: settings, users, attendance, kitchenStaff, tables, bookings, menu (components), orders (items), inventory, inventoryTransactions, stockRequests, financeEntries, supplierPurchases, supplierPayments, companyDatabase. Non-Admin removes users/attendance/financeEntries/inventoryTransactions; non-Chef also removes inventory/stockRequests.

A04. POST /api/login — role

PIN identity lookup (master issues signed access token). Source: backend/src/server.js:59.

Contract	Observed behavior
Authentication / role	Internal role service: no token validator; network-restricted. Public master path differs.
Path parameters	None
Query parameters	None
Request fields	pin
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	<user>
Explicit HTTP statuses	401
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A05. GET /api/profile — role

Read/update current user profile. Source: backend/src/server.js:60.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	No JSON fields read

Contract	Observed behavior
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	<user>
Explicit HTTP statuses	404
Validation / important errors	Your profile could not be found

A06. PATCH /api/profile — role

Read/update current user profile. Source: backend/src/server.js:61.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	name, phone, email
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <userId>, name: <name>, role: <portalRole>, phone: <phone>, email: <email>, profileImageUrl: <computed>}
Explicit HTTP statuses	400, 404
Validation / important errors	Your name is required; Enter a valid email address; Your profile could not be found

Multipart/form-data accepts name, phone, email and optional image; name required, nonempty email must match email regex.

A07. POST /api/bookings — role

Create/cancel a future table slot. Source: backend/src/server.js:62.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	tableId, bookingDate, bookingTime, durationMinutes, customerPhone
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, id: <bookingId>, notificationStatus: <computed>, notificationDetail: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Only Admin can create table bookings; Table, future date, time, 30–240 minute duration, and a valid customer phone are required; Table is not available; Choose a future booking date and time

A08. DELETE /api/bookings/:id — role

Create/cancel a future table slot. Source: backend/src/server.js:85.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true}
Explicit HTTP statuses	403, 404
Validation / important errors	Only Admin can cancel table bookings; Active booking not found

A09. POST /api/orders — role

Create a dine-in order. Source: backend/src/server.js:86.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Waiter. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	items, tableId, guestName, waiter
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <computed>, bill: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Table orders must be created from the Waiter portal; Add at least one food item; Table not found; This table is under cleaning. Mark it Available or Reserved before ordering.; This table already has an active order; This table is locked for a confirmed reservation at the current time; Menu item unavailable

Nested items: array of {menuId, qty, note}; first orders/parcels accept supplied qty, additional rounds normalize to at least one. Menu must exist and be available.

A10. POST /api/orders/:id/items — role

Add a new order round. Source: backend/src/server.js:87.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Waiter. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None

Contract	Observed behavior
Request fields	items
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <computed>, batchNo: <batchNo>, bill: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Additional table orders must come from the Waiter portal; Add at least one item; Order not found; This order is already in billing; Menu item unavailable

Nested items: array of {menuId, qty, note}; first orders/parcels accept supplied qty, additional rounds normalize to at least one. Menu must exist and be available.

A11. PATCH /api/tables/:id/status — role

Create/deactivate restaurant table. Source: backend/src/server.js:88.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin / Waiter. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	status, bookingTime
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, status: <status>}
Explicit HTTP statuses	400, 403
Validation / important errors	Only Admin or Waiter can update tables; Invalid table status; Table not found; Finalize the active bill before changing this table; Create an order to mark this table occupied

A12. POST /api/tables — role

Create/deactivate restaurant table. Source: backend/src/server.js:89.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	number, seats, area
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <computed>, restored: true}; {id: <computed>}
Explicit HTTP statuses	201, 400, 403, 409
Validation / important errors	Admin access required; Table number, seats, and service area are required

A13. DELETE /api/tables/:id — role

Create/deactivate restaurant table. Source: backend/src/server.js:90.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, number: <computed>}
Explicit HTTP statuses	403, 404, 409
Validation / important errors	Admin access required; Table not found; Finalize the active bill before deleting this table

A14. POST /api/parcels — role

Create takeaway order. Source: backend/src/server.js:91.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	items, paymentMethod, customerName, customerPhone, adminName
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <computed>, paymentStatus: <computed>, bill: <bill>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Parcel orders are created by Admin; Add at least one food item; Invalid payment method; Menu item unavailable

Nested items: array of {menuId, qty, note}; first orders/parcels accept supplied qty, additional rounds normalize to at least one. Menu must exist and be available.

A15. POST /api/orders/:id/mark-paid — role

Record advance parcel payment. Source: backend/src/server.js:92.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	paymentMethod

Contract	Observed behavior
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <computed>, paymentStatus: "paid", paymentMethod: <computed>, bill: <bill>}
Explicit HTTP statuses	400, 403, 404, 409
Validation / important errors	Only Admin can record parcel payments; Choose Cash or Card / UPI; Order not found; Advance payment is only available for parcel orders; Parcel is already completed

A16. PATCH /api/orders/:id/items/status — role

Set department preparation status for a round. Source: backend/src/server.js:93.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Chef / Juicer, department filtered. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	status, batchNo
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, status: <status>, orderStatus: <orderStatus>, batchNo: <batchNo>, updatedItems: <computed>}
Explicit HTTP statuses	400, 403
Validation / important errors	Chef or Juicer access required; Invalid preparation status

A17. PATCH /api/orders/:id/batches/:batchNo/handoff — role

Confirm ready-round collection or receipt. Source: backend/src/server.js:94.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Chef for collected; Waiter for received. Internal role service trusts gateway/network.
Path parameters	batchNo, id
Query parameters	None
Request fields	status
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, status: <status>, batchNo: <batchNo>, orderStatus: <orderStatus>}
Explicit HTTP statuses	400, 403
Validation / important errors	Invalid round handoff status; Order not found; Parcel orders use the Admin handoff flow; Kitchen round not found; Wait until every item in this round is ready; The Chef must confirm this round was collected first

A18. PATCH /api/orders/:id/status — role

Legacy whole-order collection/receipt transition. Source: backend/src/server.js:95.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Chef for collected; Waiter for received. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	status
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, status: <next>}
Explicit HTTP statuses	400, 403, 404, 409
Validation / important errors	Invalid service handoff status; Order not found; Parcel orders use the Admin handoff flow

A19. POST /api/orders/:id/request-bill — role

Ask Admin to bill received order. Source: backend/src/server.js:96.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Waiter. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, orderId: <computed>, tableId: <computed>, bill: <computed>}
Explicit HTTP statuses	403, 404, 409
Validation / important errors	Billing requests must come from the Waiter portal; Order not found; This order is already completed; Confirm that the order was received at the table first

A20. GET /api/orders/:id/bill — role

Read authoritative bill and raw order record. Source: backend/src/server.js:97.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role: no explicit handler role guard. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read

Contract	Observed behavior
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{spread <computed>, order: <order>}
Explicit HTTP statuses	404
Validation / important errors	Order not found

A21. POST /api/orders/:id/finalize — role

Record completion/payment and release table to cleaning. Source: backend/src/server.js:98.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	paymentMethod
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{id: <computed>, paymentStatus: "paid", paymentMethod: <paymentMethod>, bill: <bill>}
Explicit HTTP statuses	400, 403, 404
Validation / important errors	Only Admin can finalize payments; Order not found; Record Cash or Card / UPI payment before completing this order

A22. POST /api/inventory — role

Create/edit/delete inventory item. Source: backend/src/server.js:99.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	name, category, quantity, unit, min, cost, createdBy
Destructured defaults	category=""; quantity=0; min=0; cost=0
Response shape	{id: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin access required; Name, unit, and valid quantities are required

A23. PUT /api/inventory/:id — role

Create/edit/delete inventory item. Source: backend/src/server.js:100.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	name, category, unit, min, cost
Destructured defaults	category=""; min=0; cost=0
Response shape	{ok: true}
Explicit HTTP statuses	403
Validation / important errors	Admin access required

A24. POST /api/inventory/:id/movements — role

Apply signed stock delta and history. Source: backend/src/server.js:101.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	movementType, quantity, adjustmentDirection, unitCost, note, createdBy
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, quantity: <newQuantity>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin access required; Choose a movement type and enter a positive quantity; Stock item not found; Not enough stock for this movement

purchase adds; usage/waste subtract; adjustment subtracts only when Number(adjestmentDirection) equals -1, otherwise adds. quantity must be finite and positive. unitCost defaults to stored cost; purchase updates cost.

A25. DELETE /api/inventory/:id — role

Create/edit/delete inventory item. Source: backend/src/server.js:102.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true}

Contract	Observed behavior
Explicit HTTP statuses	403, 409
Validation / important errors	Admin access required; Items with stock history cannot be deleted

A26. POST /api/stock-requests — role

Request kitchen replenishment or change request status. Source: backend/src/server.js:103.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Chef. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	inventoryId, requestedQuantity, requestedBy, note
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{id: <computed>, itemName: <computed>, currentQuantity: <computed>, unit: <computed>}
Explicit HTTP statuses	201, 400, 403, 404, 409
Validation / important errors	Only Chef can request kitchen stock; Choose an item and enter the quantity required; Stock item not found

A27. PATCH /api/stock-requests/:id/status — role

Request kitchen replenishment or change request status. Source: backend/src/server.js:104.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	status
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, status: <status>}
Explicit HTTP statuses	400, 403, 404
Validation / important errors	Only Admin can manage stock requests; Invalid stock request status; Stock request not found

A28. POST /api/finance — role

Record/delete income or expense. Source: backend/src/server.js:105.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None

Contract	Observed behavior
Query parameters	None
Request fields	entryType, category, description, amount, paymentMethod, entryDate, reference, createdBy
Destructured defaults	paymentMethod="Cash"; reference=""; createdBy="Admin"
Response shape	{id: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin access required; Type, category, description, amount, and date are required

A29. DELETE /api/finance/:id — role

Record/delete income or expense. Source: backend/src/server.js:106.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true}
Explicit HTTP statuses	403
Validation / important errors	Admin access required

A30. POST /api/supplier-purchases — role

Record/delete supplier purchase. Source: backend/src/server.js:107.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	supplierName, invoiceNumber, description, purchaseDate, totalAmount, paidAmount, paymentMethod, reference, notes, createdBy
Destructured defaults	invoiceNumber=""; paidAmount=0; paymentMethod="Cash"; reference=""; notes=""; createdBy="Admin"
Response shape	{id: <computed>, totalAmount: <total>, paidAmount: <paid>, dueAmount: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin access required; Supplier, description, date, valid total, and paid amount are required

A31. POST /api/supplier-purchases/:id/payments — role

Record supplier payment against outstanding balance. Source: backend/src/server.js:108.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	amount, paymentDate, paymentMethod, reference, notes, createdBy
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{id: <computed>, paidAmount: <computed>, dueAmount: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin access required; A positive payment amount and payment date are required; Supplier purchase not found

A32. DELETE /api/supplier-purchases/:id — role

Record/delete supplier purchase. Source: backend/src/server.js:109.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true}
Explicit HTTP statuses	403
Validation / important errors	Admin access required

A33. PUT /api/settings — role

Update hotel and charge settings. Source: backend/src/server.js:110.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role: no explicit handler role guard. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	hotelName, taxRate, cgstRate, serviceCharge, currency
Deconstructed defaults	See validation and workflow; no deconstructed defaults

Contract	Observed behavior
Response shape	{ok: true}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A34. GET /api/attendance/:id — role

Read/start/end staff shift. Source: backend/src/server.js:112.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Same-role staff; Admin can read, not use attendance self check-in/out. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{staff: <staff>, shifts: <shifts>, activeShift: <computed>}
Explicit HTTP statuses	403
Validation / important errors	This staff account does not belong to this portal

A35. POST /api/attendance/:id/check-in — role

Read/start/end staff shift. Source: backend/src/server.js:113.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Same-role staff; Admin can read, not use attendance self check-in/out. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	notes
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{id: <computed>, checkIn: <computed>}
Explicit HTTP statuses	201, 403, 409
Validation / important errors	This staff account does not belong to this portal; Staff must check in from their own portal; You are already checked in

A36. POST /api/attendance/:id/check-out — role

Read/start/end staff shift. Source: backend/src/server.js:114.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Same-role staff; Admin can read, not use attendance self check-in/out. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	notes
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, checkOut: <computed>}
Explicit HTTP statuses	403, 409
Validation / important errors	This staff account does not belong to this portal; Staff must check out from their own portal; You are not currently checked in

A37. POST /api/staff — role

Manage portal users or Admin attendance action. Source: backend/src/server.js:115.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	name, role, phone, payType, payRate
Destructured defaults	phone=""; payType="monthly"; payRate=0
Response shape	{id: <computed>, pin: <pin>}
Explicit HTTP statuses	201, 400, 403, 409
Validation / important errors	Admin access required; Name, role, and Daily/Monthly salary basis are required

A38. PUT /api/staff/:id — role

Manage portal users or Admin attendance action. Source: backend/src/server.js:116.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	name, role, pin, phone, payType, payRate, active
Destructured defaults	phone=""; payType="monthly"; payRate=0; active=true
Response shape	{ok: true}
Explicit HTTP statuses	400, 403, 404, 409

Contract	Observed behavior
Validation / important errors	Admin access required; Valid role, unique 6-digit PIN, and Daily/Monthly salary basis are required; Staff member not found

A39. DELETE /api/staff/:id — role

Manage portal users or Admin attendance action. Source: backend/src/server.js:117.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, id: <computed>, name: <computed>, attendancePreserved: true}
Explicit HTTP statuses	403, 404, 409
Validation / important errors	Admin access required; Staff member not found; The company Admin login is protected and cannot be deleted here

A40. GET /api/juicer-login — role

Read/create singleton Juicer login. Source: backend/src/server.js:118.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Chef. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	<computed>
Explicit HTTP statuses	403
Validation / important errors	Head Chef access required

A41. POST /api/juicer-login — role

Read/create singleton Juicer login. Source: backend/src/server.js:119.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Chef. Internal role service trusts gateway/network.
Path parameters	None

Contract	Observed behavior
Query parameters	None
Request fields	name, phone, payType, payRate
Destructured defaults	phone=""; payType="monthly"; payRate=0
Response shape	{id: <computed>, role: "juicer", pin: <pin>}
Explicit HTTP statuses	201, 400, 403, 409
Validation / important errors	Only the Head Chef can create the Juicer login; Name and salary basis are required; This company already has its single Juicer login. Admin can edit it from Staff Management.

A42. POST /api/kitchen-staff — role

Manage non-login kitchen personnel. Source: backend/src/server.js:120.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin / Chef. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	name, designation, phone, specialization, payType, payRate, joinedOn, notes, createdBy
Destructured defaults	designation="Chef"; phone=""; specialization=""; payType="monthly"; payRate=0; joinedOn=null; notes=""; createdBy=<computed>
Response shape	{id: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin or Head Chef access required; Chef name, designation, and Daily/Monthly salary basis are required

A43. PUT /api/kitchen-staff/:id — role

Manage non-login kitchen personnel. Source: backend/src/server.js:121.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin / Chef. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	name, designation, phone, specialization, payType, payRate, joinedOn, notes, active
Destructured defaults	designation="Chef"; phone=""; specialization=""; payType="monthly"; payRate=0; joinedOn=null; notes=""; active=true
Response shape	{ok: true}
Explicit HTTP statuses	400, 403, 404
Validation / important errors	Admin or Head Chef access required; Chef name, designation, and Daily/Monthly salary basis are required; Kitchen staff member not found

A44. DELETE /api/kitchen-staff/:id — role

Manage non-login kitchen personnel. Source: backend/src/server.js:122.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin / Chef. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true}
Explicit HTTP statuses	403, 404
Validation / important errors	Admin or Head Chef access required; Kitchen staff member not found

A45. POST /api/staff/:id/check-in — role

Manage portal users or Admin attendance action. Source: backend/src/server.js:123.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	notes
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{id: <computed>}
Explicit HTTP statuses	201, 403, 404, 409
Validation / important errors	Admin access required; Active staff member not found; Staff member is already checked in

A46. POST /api/staff/:id/check-out — role

Manage portal users or Admin attendance action. Source: backend/src/server.js:124.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	notes
Deconstructed defaults	See validation and workflow; no deconstructed defaults

Contract	Observed behavior
Response shape	{ok: true}
Explicit HTTP statuses	403, 409
Validation / important errors	Admin access required; No active check-in found

A47. POST /api/menu — role

Create/edit/hide menu item. Source: backend/src/server.js:125.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	name, category, description, price, icon, available
Destructured defaults	description=""; icon="□□"; available=true
Response shape	{id: <computed>}
Explicit HTTP statuses	201, 400, 403
Validation / important errors	Admin access required; Name, category, and valid price are required

A48. PUT /api/menu/:id — role

Create/edit/hide menu item. Source: backend/src/server.js:126.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	name, category, description, price, icon, available
Destructured defaults	description=""; icon="□□"; available=true
Response shape	{ok: true}
Explicit HTTP statuses	403
Validation / important errors	Admin access required

A49. DELETE /api/menu/:id — role

Create/edit/hide menu item. Source: backend/src/server.js:127.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.

Contract	Observed behavior
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true}
Explicit HTTP statuses	403
Validation / important errors	Admin access required

A50. PATCH /api/menu/:id/availability — role

Toggle available flag. Source: backend/src/server.js:128.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin / Chef / Juicer (juice only). Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	available
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, id: <computed>, available: <computed>}
Explicit HTTP statuses	400, 403, 404
Validation / important errors	Admin, Head Chef, or Juicer access required; Availability must be true or false; Juicer can only update juice availability; Dish not found

A51. POST /api/combos — role

Create/replace sellable combo composition. Source: backend/src/server.js:129.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	name, description, price, icon, components
Destructured defaults	description=""; icon="□"; components=[]
Response shape	{id: <computed>}
Explicit HTTP statuses	201, 400, 403

Contract	Observed behavior
Validation / important errors	Admin access required; Combo name, price, and at least one item are required; A selected combo item is invalid

Nested components: array of {menuId, quantity}; create checks selected non-combo items, quantities normalized to at least one. Update replaces all component rows and validates less strictly.

A52. PUT /api/combos/:id — role

Create/replace sellable combo composition. Source: backend/src/server.js:130.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Admin. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	name, description, price, icon, components
Destructured defaults	description=""; icon="□"; components=[]
Response shape	{ok: true}
Explicit HTTP statuses	403
Validation / important errors	Admin access required

Nested components: array of {menuId, quantity}; create checks selected non-combo items, quantities normalized to at least one. Update replaces all component rows and validates less strictly.

A53. POST /api/menu/:id/image — role

Upload/remove menu photo. Source: backend/src/server.js:131.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role: no explicit handler role guard. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{imageUrl: <computed>, objectName: <computed>}
Explicit HTTP statuses	400, 404
Validation / important errors	Please select an image file; Menu item not found

Request is multipart/form-data with required image file. MIME must begin image/, maximum 5 MiB. Response {imageUrl,objectName}.

A54. DELETE /api/menu/:id/image — role

Upload/remove menu photo. Source: backend/src/server.js:132.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role: no explicit handler role guard. Internal role service trusts gateway/network.
Path parameters	id
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A55. POST /api/reports — role

Store client-generated report object. Source: backend/src/server.js:133.

Contract	Observed behavior
Authentication / role	Tenant bearer required through master; Any tenant role: no explicit handler role guard. Internal role service trusts gateway/network.
Path parameters	None
Query parameters	None
Request fields	filename, content, contentType
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{spread <stored>, provider: <storageProvider>}
Explicit HTTP statuses	201, 400
Validation / important errors	Report filename and content are required

filename and string content required; optional contentType defaults text/csv;charset=utf-8. Response 201 {objectName,url,provider}.

A56. GET /api/live — master

Process liveness. Source: backend/src/master-server.js:207.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None

Contract	Observed behavior
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, service: "knockout-master-api"}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A57. GET /api/health — master

SQL readiness and runtime metadata. Source: backend/src/master-server.js:208.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, service: "knockout-master-api", database: <masterDb>, realtime: <computed>}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A58. GET /api/public/companies — master

List/provision/manage tenant company. Source: backend/src/master-server.js:209.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	<rows>
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A59. POST /api/public/company-registrations — master

Apply/review company registration. Source: backend/src/master-server.js:210.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	companyName, adminName, email, phone, packageCode, periodMonths
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{id: <computed>, status: "pending", temporaryPin: <temporaryPin>, message: "Sent for approval. Your temporary onboarding PIN has been queued to your email and mobile."}
Explicit HTTP statuses	201, 400, 409
Validation / important errors	Enter valid business details, package, and subscription period; This hotel/business name is already registered; An active application already uses this business name or email; Sent for approval. Your temporary onboarding PIN has been queued to your email and mobile.

A60. POST /api/public/resolve-login — master

Resolve Hotel ID/PIN to role and signed token. Source: backend/src/master-server.js:211.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	hotelId, pin
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{spread <user>, accessToken: <computed>}; {spread <application>, role: "applicant", temporaryPin: <pin>}
Explicit HTTP statuses	400, 401, 403
Validation / important errors	Invalid Super Admin or temporary onboarding PIN. Hotel staff must enter their Hotel ID.; Invalid Master Hotel ID or PIN; Enter your 4-digit Hotel ID and 6-digit PIN; Invalid Hotel ID, PIN, or inactive account

Staff response includes id,name,role,companyDatabase,companyName,hotelId,modules and accessToken plus selected account/company status fields. Master returns master identity/token; applicant returns application id/company/name/status/completedAt, role applicant and temporaryPin. No PIN values are documented here.

A61. POST /api/public/onboarding-status — master

Read temporary application status and calculated price. Source: backend/src/master-server.js:212.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	id, pin

Contract	Observed behavior
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{spread <row>, monthly: <monthly>, discount: <discount>, subtotal: <subtotal>, tax: <tax>, total: <computed>}
Explicit HTTP statuses	401
Validation / important errors	Temporary onboarding session is invalid

A62. POST /api/public/complete-registration — master

Provision approved paid-reference application. Source: backend/src/master-server.js:213.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	pin, id, paymentReference, businessType, address, gstNumber
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{success: true, hotelId: <computed>, adminPin: <computed>, companyName: <computed>, expiresAt: <expires>}
Explicit HTTP statuses	201, 400, 401, 409
Validation / important errors	Temporary onboarding session is invalid; Master approval is required before completing registration; A valid payment reference is required; Business type and address are required

A63. POST /api/login — master

PIN identity lookup (master issues signed access token). Source: backend/src/master-server.js:214.

Contract	Observed behavior
Authentication / role	Public; no bearer required
Path parameters	None
Query parameters	None
Request fields	pin
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{spread <result>, accessToken: <computed>}
Explicit HTTP statuses	401
Validation / important errors	Invalid KnockOUT Master PIN

A64. GET /api/state — master

Master network snapshot, invoices, subscriptions, usage and registration requests; also runs enforcement/invoice generation. Source: backend/src/master-server.js:215.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{companies: <computed>, masterUsers: <masterUsers>, registrationRequests: <computed>, invoices: <computed>, subscriptions: <subscriptions>, usage: <usage>, moduleCatalog: <computed>, masterName: "KnockOUT Master"}
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

Master response: companies with users/staffCount/adminLoginActive/activeOrders/revenue/dailyRevenue/lowStock/online, masterUsers, registrationRequests, invoices, subscriptions, usage, moduleCatalog, masterName. PIN fields are currently returned in privileged projections.

A65. POST /api/companies — master

List/provision/manage tenant company. Source: backend/src/master-server.js:216.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	None
Query parameters	None
Request fields	companyName, adminName, email, phone, selectedModules
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	<computed>
Explicit HTTP statuses	201
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

companyName must normalize to a valid unused schema; adminName required. email/phone default empty, selectedModules optional array of module keys. Response includes id,companyName,databaseName,hotelId,adminPin,modules,adminName,email,phone,status.

A66. POST /api/company-registrations/:id/approve — master

Apply/review company registration. Source: backend/src/master-server.js:217.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	id
Query parameters	None
Request fields	reviewNote
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, status: "approved", request: <request>}
Explicit HTTP statuses	404, 409
Validation / important errors	Registration request not found

A67. PATCH /api/companies/:id/modules — master

Toggle company module entitlement. Source: backend/src/master-server.js:218.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	id
Query parameters	None
Request fields	module, enabled
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, modules: <modules>}
Explicit HTTP statuses	400, 404
Validation / important errors	Invalid module setting; Company not found

A68. PATCH /api/saas-invoices/:id/status — master

Update subscription invoice paid/due status. Source: backend/src/master-server.js:219.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	id
Query parameters	None
Request fields	status
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, status: <computed>}
Explicit HTTP statuses	400, 404
Validation / important errors	Invalid invoice status; Invoice not found

A69. POST /api/company-registrations/:id/reject — master

Apply/review company registration. Source: backend/src/master-server.js:220.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	id
Query parameters	None
Request fields	reviewNote
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, status: "rejected"}
Explicit HTTP statuses	409
Validation / important errors	Registration request is missing or already reviewed

A70. PATCH /api/companies/:id/status — master

List/provision/manage tenant company. Source: backend/src/master-server.js:221.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	id
Query parameters	None
Request fields	status
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, status: <computed>, companyName: <computed>, loginsEnabled: <computed>}
Explicit HTTP statuses	400, 404
Validation / important errors	Invalid company status; Company not found

A71. PATCH /api/companies/:companyId/users/:userId/pin — master

List/provision/manage tenant company. Source: backend/src/master-server.js:222.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	companyId, userId
Query parameters	None
Request fields	pin
Deconstructed defaults	See validation and workflow; no deconstructed defaults

Contract	Observed behavior
Response shape	{ok: true, userId: <computed>, name: <computed>, pin: <pin>}
Explicit HTTP statuses	400, 404, 409
Validation / important errors	PIN must contain exactly 6 digits; Company not found; User not found

A72. PATCH /api/master-users/:userId/pin — master

Rotate master PIN. Source: backend/src/master-server.js:223.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	userId
Query parameters	None
Request fields	pin
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, userId: <computed>, name: <computed>, pin: <pin>}
Explicit HTTP statuses	400, 404, 409
Validation / important errors	PIN must contain exactly 6 digits; Master user not found

A73. DELETE /api/companies/:id — master

List/provision/manage tenant company. Source: backend/src/master-server.js:224.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	id
Query parameters	None
Request fields	companyName
Destructured defaults	See validation and workflow; no destructured defaults
Response shape	{ok: true, deleted: <computed>}
Explicit HTTP statuses	400, 404, 409
Validation / important errors	Company not found; The protected primary tenant cannot be deleted; Invalid tenant database; Type the exact hotel name to confirm deletion

A74. GET /api/module-pricing — master

Read/update monthly module prices. Source: backend/src/master-server.js:225.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	None
Query parameters	None
Request fields	No JSON fields read
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	<computed>
Explicit HTTP statuses	200; unhandled errors 500
Validation / important errors	Shared authentication/error rules; SQL/storage failures may surface as 500

A75. PATCH /api/module-pricing/:key — master

Read/update monthly module prices. Source: backend/src/master-server.js:226.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	key
Query parameters	None
Request fields	price
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{ok: true, key: <key>, price: <price>}
Explicit HTTP statuses	400
Validation / important errors	Enter a valid module price

A76. POST /api/reports — master

Store client-generated report object. Source: backend/src/master-server.js:227.

Contract	Observed behavior
Authentication / role	Super Admin bearer required
Path parameters	None
Query parameters	None
Request fields	filename, content, contentType
Deconstructed defaults	See validation and workflow; no deconstructed defaults
Response shape	{spread <stored>, provider: <storageProvider>}
Explicit HTTP statuses	201, 400
Validation / important errors	Report filename and content are required

filename and string content required; optional contentType defaults text/csv;charset=utf-8. Response 201 {objectName,url,provider}.

Supplemental routes and transport

GET /api/session: tenant bearer; returns {modules,companyDatabase,role} from gateway middleware after active-company lookup, before normal module-path enforcement. Not a Super Admin session endpoint.

GET /api/framework: Nest controller in backend/src/nest/app.module.js; {ok,framework,service,architecture}; public on master, internal on role processes.

/ws: WebSocket on master HTTP server; query database and token required. Tenant token can subscribe only to its database, Super Admin to master. Invalid session closes 1008. Server sends connected then state.changed messages with database/resource/at and optional module details. Heartbeat 25 seconds. No durable replay or revalidation of token expiry on every existing socket message.

32.2 Database table and column inventory

Runtime base definitions are primary evidence. Columns added through later ALTER statements are listed separately. FKs below are base DDL declarations, not guaranteed for cloned schemas.

Table	Purpose	PK	Foreign keys / major relationships
Tenant.settings	Singleton property presentation/charge settings	id	None declared
Tenant.users	Portal login identities and salary basis	id	None declared
Tenant.kitchen_staff	Non-login kitchen personnel	id	None declared
Tenant.staff_attendance	User shift history	id	user_id → users.id
Tenant.restaurant_tables	Seating, status and current-order pointer	id	None declared
Tenant.menu_items	Dishes and sellable combos	id	None declared
Tenant.combo_components	Composition of combo menu items	id	combo_id → menu_items.id; menu_id → menu_items.id
Tenant.orders	Dine-in/takeaway sale and payment state	id	table_id → restaurant_tables.id
Tenant.order_items	Priced sale lines and production/handoff rounds	id	order_id → orders.id; menu_id → menu_items.id
Tenant.inventory	Stock quantities, minimum and cost	id	None declared
Tenant.inventory_transactions	Signed stock movement history	id	inventory_id → inventory.id
Tenant.stock_requests	Chef replenishment requests	id	inventory_id → inventory.id
Tenant.finance_entries	Standalone income/expense records	id	None declared
Tenant.supplier_purchases	Supplier invoice/purchase amounts	id	None declared

Table	Purpose	PK	Foreign keys / major relationships
Tenant.supplier_payments	Payments against purchases	id	purchase_id → supplier_purchases.id
Tenant.bookings	Future table slot reservations	id	table_id → restaurant_tables.id
Master.master_users	Platform operator credentials	id	None declared
Master.companies	Tenant schema and module registry	id	None declared
Master.company_users	Synchronized tenant login directory	id	company_id → companies.id
Master.company_registration_requests	Application, approval and setup tracking	id	company_id → companies.id
Master.saas_invoices	Company subscription charge snapshots	id	company_id → companies.id
Master.notification_outbox	Notice content and nominal delivery status	id	None declared
Master.tenant_subscriptions	Package term, grace and expiry	id	company_id → companies.id
Master.usage_logins	Company user login counts/history	id	company_id → companies.id
Master.module_pricing	Monthly module price catalog	module_key	None declared

Tenant: settings

Evidence: backend/src/database.js:39.

Column or constraint	Definition
id	INT PRIMARY KEY DEFAULT 1
hotel_name	VARCHAR(120) NOT NULL
tax_rate	DECIMAL(5,2) NOT NULL DEFAULT 2.5
cgst_rate	DECIMAL(5,2) NOT NULL DEFAULT 2.5
service_charge	DECIMAL(5,2) NOT NULL DEFAULT 18
currency	VARCHAR(8) NOT NULL DEFAULT 'INR'
updated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP

Tenant: users

Evidence: backend/src/database.js:40.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY

Column or constraint	Definition
name	VARCHAR(120) NOT NULL
role	ENUM('admin','waiter','chef','juicer') NOT NULL
pin	VARCHAR(80) NOT NULL
phone	VARCHAR(30) DEFAULT ''
email	VARCHAR(160) DEFAULT ''
profile_image_url	VARCHAR(500) NULL
profile_image_object	VARCHAR(255) NULL
pay_type	ENUM('daily','monthly') DEFAULT 'monthly'
pay_rate	DECIMAL(10,2) DEFAULT 0
active	BOOLEAN DEFAULT TRUE
deleted_at	DATETIME NULL
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Tenant: kitchen_staff

Evidence: backend/src/database.js:41.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
name	VARCHAR(120) NOT NULL
designation	VARCHAR(100) NOT NULL DEFAULT 'Chef'
phone	VARCHAR(30) DEFAULT ''
specialization	VARCHAR(120) DEFAULT ''
pay_type	ENUM('daily','monthly') DEFAULT 'monthly'
pay_rate	DECIMAL(10,2) DEFAULT 0
joined_on	DATE NULL
notes	VARCHAR(255) DEFAULT ''
active	BOOLEAN DEFAULT TRUE
created_by	VARCHAR(120) DEFAULT 'Head Chef'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
updated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP

Tenant: staff_attendance

Evidence: backend/src/database.js:42.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
user_id	INT NOT NULL
check_in	DATETIME NOT NULL
check_out	DATETIME NULL
notes	VARCHAR(255) DEFAULT "
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
FOREIGN	KEY (user_id) REFERENCES users(id)

Tenant: restaurant_tables

Evidence: backend/src/database.js:43.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
table_number	INT NOT NULL UNIQUE
seats	INT NOT NULL
area	VARCHAR(80) NOT NULL
status	ENUM('available','occupied','reserved','cleaning') DEFAULT 'available'
guest_name	VARCHAR(120) DEFAULT "
booking_time	VARCHAR(10) DEFAULT "
order_id	INT NULL
active	BOOLEAN DEFAULT TRUE

Tenant: menu_items

Evidence: backend/src/database.js:44.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
name	VARCHAR(160) NOT NULL
category	VARCHAR(80) NOT NULL
description	VARCHAR(500) DEFAULT "
price	DECIMAL(10,2) NOT NULL
icon	VARCHAR(20) DEFAULT '□□'
image_url	VARCHAR(500) NULL
image_object	VARCHAR(255) NULL

Column or constraint	Definition
is_combo	BOOLEAN DEFAULT FALSE
available	BOOLEAN DEFAULT TRUE
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Tenant: combo_components

Evidence: backend/src/database.js:45.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
combo_id	INT NOT NULL
menu_id	INT NOT NULL
quantity	INT NOT NULL DEFAULT 1
FOREIGN	KEY (combo_id) REFERENCES menu_items(id) ON DELETE CASCADE
FOREIGN	KEY (menu_id) REFERENCES menu_items(id)

Tenant: orders

Evidence: backend/src/database.js:46.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
table_id	INT NULL
order_type	ENUM('dine_in','parcel') NOT NULL DEFAULT 'dine_in'
guest_name	VARCHAR(120)
customer_phone	VARCHAR(30) DEFAULT ''
waiter	VARCHAR(120)
status	ENUM('new','preparing','ready','collected','received','served','billing_requested','completed') DEFAULT 'new'
payment_status	ENUM('unpaid','paid') DEFAULT 'unpaid'
payment_method	VARCHAR(30) NULL
subtotal	DECIMAL(10,2) NULL
tax	DECIMAL(10,2) NULL
service_charge	DECIMAL(10,2) NULL
total	DECIMAL(10,2) NULL
created_at	DATETIME NOT NULL

Column or constraint	Definition
completed_at	DATETIME NULL
FOREIGN	KEY (table_id) REFERENCES restaurant_tables(id)

Tenant: order_items

Evidence: backend/src/database.js:47.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
order_id	INT NOT NULL
menu_id	INT NOT NULL
quantity	INT NOT NULL
note	VARCHAR(255) DEFAULT "
price	DECIMAL(10,2) NOT NULL
production_status	ENUM('new','preparing','ready') NOT NULL DEFAULT 'new'
batch_no	INT NOT NULL DEFAULT 1
handoff_status	ENUM('pending','collected','received') NOT NULL DEFAULT 'pending'
FOREIGN	KEY (order_id) REFERENCES orders(id) ON DELETE CASCADE
FOREIGN	KEY (menu_id) REFERENCES menu_items(id)

Tenant: inventory

Evidence: backend/src/database.js:48.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
name	VARCHAR(160) NOT NULL
category	VARCHAR(80)
quantity	DECIMAL(10,2) NOT NULL
unit	VARCHAR(20) NOT NULL
min_quantity	DECIMAL(10,2) NOT NULL
cost	DECIMAL(10,2) NOT NULL
updated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP

Tenant: inventory_transactions

Evidence: backend/src/database.js:49.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
inventory_id	INT NOT NULL
movement_type	ENUM('purchase','usage','adjustment','waste') NOT NULL
quantity	DECIMAL(10,2) NOT NULL
unit_cost	DECIMAL(10,2) NULL
note	VARCHAR(255) DEFAULT "
created_by	VARCHAR(120) DEFAULT 'Admin'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
FOREIGN	KEY (inventory_id) REFERENCES inventory(id)

Tenant: stock_requests

Evidence: backend/src/database.js:50.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
inventory_id	INT NOT NULL
requested_quantity	DECIMAL(10,2) NOT NULL
note	VARCHAR(255) DEFAULT "
requested_by	VARCHAR(120) NOT NULL
status	ENUM('pending','ordered','resolved') NOT NULL DEFAULT 'pending'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
updated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
resolved_at	DATETIME NULL
FOREIGN	KEY (inventory_id) REFERENCES inventory(id)
INDEX	request_status (status,created_at)

Tenant: finance_entries

Evidence: backend/src/database.js:51.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
entry_type	ENUM('income','expense') NOT NULL
category	VARCHAR(100) NOT NULL
description	VARCHAR(255) NOT NULL

Column or constraint	Definition
amount	DECIMAL(12,2) NOT NULL
payment_method	VARCHAR(40) DEFAULT 'Cash'
entry_date	DATE NOT NULL
reference	VARCHAR(100) DEFAULT ''
created_by	VARCHAR(120) DEFAULT 'Admin'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Tenant: **supplier_purchases**

Evidence: backend/src/database.js:52.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
supplier_name	VARCHAR(160) NOT NULL
invoice_number	VARCHAR(100) DEFAULT ''
description	VARCHAR(255) NOT NULL
purchase_date	DATE NOT NULL
total_amount	DECIMAL(12,2) NOT NULL
notes	VARCHAR(255) DEFAULT ''
created_by	VARCHAR(120) DEFAULT 'Admin'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Tenant: **supplier_payments**

Evidence: backend/src/database.js:53.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
purchase_id	INT NOT NULL
amount	DECIMAL(12,2) NOT NULL
payment_method	VARCHAR(40) DEFAULT 'Cash'
payment_date	DATE NOT NULL
reference	VARCHAR(100) DEFAULT ''
notes	VARCHAR(255) DEFAULT ''
created_by	VARCHAR(120) DEFAULT 'Admin'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Column or constraint	Definition
FOREIGN	KEY (purchase_id) REFERENCES supplier_purchases(id) ON DELETE CASCADE

Tenant: bookings

Evidence: backend/src/database.js:54.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
table_id	INT NOT NULL
guest_name	VARCHAR(120) NOT NULL DEFAULT 'Customer'
customer_phone	VARCHAR(30) NOT NULL DEFAULT "
booking_date	DATE NOT NULL
booking_time	VARCHAR(10) NOT NULL
duration_minutes	INT NOT NULL DEFAULT 90
status	ENUM('confirmed','seated','cancelled') DEFAULT 'confirmed'
notification_status	ENUM('queued','sent','failed') DEFAULT 'queued'
notification_message	VARCHAR(500) DEFAULT "
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
FOREIGN	KEY (table_id) REFERENCES restaurant_tables(id)
INDEX	booking_slot (table_id,booking_date,status)

Master: master_users

Evidence: backend/src/master-server.js:89.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
name	VARCHAR(120) NOT NULL
pin	VARCHAR(20) NOT NULL
active	BOOLEAN DEFAULT TRUE
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Master: companies

Evidence: backend/src/master-server.js:90.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY

Column or constraint	Definition
company_name	VARCHAR(160) NOT NULL UNIQUE
database_name	VARCHAR(64) NOT NULL UNIQUE
cy_db	VARCHAR(64) NULL UNIQUE
hotel_id	CHAR(4) NULL UNIQUE
modules	JSON NULL
admin_name	VARCHAR(120) NOT NULL
email	VARCHAR(160) DEFAULT "
phone	VARCHAR(30) DEFAULT "
status	ENUM('active','suspended') DEFAULT 'active'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP

Master: company_users

Evidence: backend/src/master-server.js:91.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
company_id	INT NOT NULL
tenant_user_id	INT NOT NULL
name	VARCHAR(120) NOT NULL
role	ENUM('admin','waiter','chef','juicer') NOT NULL
pin	VARCHAR(80) NOT NULL
phone	VARCHAR(30) DEFAULT "
email	VARCHAR(160) DEFAULT "
profile_image_url	VARCHAR(500) NULL
active	BOOLEAN DEFAULT TRUE
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
updated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP
UNIQUE	KEY company_tenant_user (company_id,tenant_user_id)
UNIQUE	KEY company_pin (company_id,pin)
FOREIGN	KEY (company_id) REFERENCES companies(id) ON DELETE CASCADE

Master: company_registration_requests

Evidence: backend/src/master-server.js:96.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
company_name	VARCHAR(160) NOT NULL
hotel_id	CHAR(4) NULL
admin_name	VARCHAR(120) NOT NULL
admin_pin	VARCHAR(20) NULL
email	VARCHAR(160) NOT NULL
phone	VARCHAR(30) NOT NULL
status	ENUM('pending','approved','rejected') NOT NULL DEFAULT 'pending'
review_note	VARCHAR(255) DEFAULT "
company_id	INT NULL
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
reviewed_at	DATETIME NULL
INDEX	registration_status (status,created_at)
FOREIGN	KEY (company_id) REFERENCES companies(id) ON DELETE SET NULL

Master: **saas_invoices**

Evidence: backend/src/master-server.js:97.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
company_id	INT NOT NULL
billing_month	DATE NOT NULL
line_items	JSON NOT NULL
subtotal	DECIMAL(12,2) NOT NULL
tax_rate	DECIMAL(5,2) NOT NULL DEFAULT 18
tax	DECIMAL(12,2) NOT NULL
total	DECIMAL(12,2) NOT NULL
status	ENUM('due','paid') NOT NULL DEFAULT 'due'
paid_at	DATETIME NULL
generated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
UNIQUE	KEY company_billing_month(company_id,billing_month)
INDEX	invoice_month(billing_month,status)
FOREIGN	KEY(company_id) REFERENCES companies(id) ON DELETE CASCADE

Master: notification_outbox

Evidence: backend/src/master-server.js:98.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
recipient	VARCHAR(180) NOT NULL
channel	ENUM('email','sms') NOT NULL
subject	VARCHAR(180) DEFAULT "
message	TEXT NOT NULL
status	ENUM('queued','sent','failed') DEFAULT 'queued'
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
sent_at	DATETIME NULL

Master: tenant_subscriptions

Evidence: backend/src/master-server.js:99.

Column or constraint	Definition
id	INT AUTO_INCREMENT PRIMARY KEY
company_id	INT NOT NULL
package_code	VARCHAR(30) NOT NULL
period_months	INT NOT NULL
started_at	DATETIME NOT NULL
expires_at	DATETIME NOT NULL
grace_ends_at	DATETIME NOT NULL
status	ENUM('active','grace','expired') DEFAULT 'active'
last_reminder_at	DATETIME NULL
created_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
FOREIGN	KEY(company_id) REFERENCES companies(id) ON DELETE CASCADE

Master: usage_logins

Evidence: backend/src/master-server.js:100.

Column or constraint	Definition
id	BIGINT AUTO_INCREMENT PRIMARY KEY
company_id	INT NOT NULL

Column or constraint	Definition
user_id	INT NOT NULL
role	VARCHAR(30) NOT NULL
logged_in_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP
INDEX	company_login(company_id,logged_in_at)
FOREIGN	KEY(company_id) REFERENCES companies(id) ON DELETE CASCADE

Master: module_pricing

Evidence: backend/src/master-server.js:101.

Column or constraint	Definition
module_key	VARCHAR(30) PRIMARY KEY
module_name	VARCHAR(100) NOT NULL
monthly_price	DECIMAL(12,2) NOT NULL
updated_at	TIMESTAMP DEFAULT CURRENT_TIMESTAMP ON UPDATE CURRENT_TIMESTAMP

Upgrade-only columns, indexes and SQL-export differences

company_registration_requests adds temporary_pin CHAR(6) UNIQUE, package_code, period_months, selected_modules JSON, setup_data JSON, payment_reference and completed_at. The full temporary_pin unique constraint covers completed rows too, while generation checks only unfinished rows: a reused completed PIN can cause an insert conflict.

Tenant upgrades add booking_slot, order_live_history, order_payment_date, order_round_status and user_portal_login. Salary values hourly are converted to daily. Master upgrades add columns already in newer CREATE forms and remove the older global PIN index. Master views: tenant_waiting_list WHERE completed_at IS NULL; tenant_registrations WHERE completed_at IS NOT NULL. No triggers/procedures/functions/sequences were identified. SQL export table index: master_users, companies, settings, users, kitchen_staff, staff_attendance, restaurant_tables, menu_items, combo_components, orders, order_items, inventory, inventory_transactions, finance_entries, supplier_purchases, supplier_payments, bookings. This export omits stock_requests, company_users, company_registration_requests, saas_invoices, notification_outbox, tenant_subscriptions, usage_logins, module_pricing. Runtime CREATE uses signed IDs while export uses unsigned IDs for many entities; compare types before mixing paths. Export-only unique constraints include uq_master_users_pin, uq_users_pin and uq_combo_component.

32.3 Environment-variable index

Requiredness is contextual: a code fallback does not make a secret safe. Variables must be supplied to the process, not merely listed in a template. Dev/staging/prod use the same variable names; isolated values are required per environment. k6-only variables are for testing.

Variable	Purpose	Required / scope	Safe example
AWS_ACCESS_KEY_ID	Fallback S3 access ID	Optional alias	<AWS_ACCESS_KEY_ID>
AWS_REGION	Fallback client region; URL region logic differs	Optional alias	<AWS_REGION>

Variable	Purpose	Required / scope	Safe example
AWS_SECRET_ACCESS_KEY	Fallback S3 secret	Optional alias	<AWS_SECRET_ACCESS_KEY>
BACKEND_PORT	Published master API port	Optional	5100
BACKEND_PORT_RANGE	Scale override host range	Optional	5100-5102
BASE_URL	k6 target only	Optional	http://localhost:5100
COMPOSE_PROJECT_NAME	Compose resource prefix	Optional	knockout
DB_CONNECT_TIMEOUT_MS	SQL connection timeout	Optional	10000
DB_EXTERNAL_PORT	Published DB host port	Optional	3307
DB_HOST	SQL hostname	Yes for nondefault topology	mariadb
DB_NAME	Primary tenant database	Yes in Compose	knockout
DB_PASSWORD	Role SQL password	Yes; replace fallback	<DATABASE_PASSWORD>
DB_POOL_IDLE_TIMEOUT_MS	Idle connection timeout	Optional	60000
DB_POOL_MAX_IDLE	Pool idle connection maximum	Optional	10
DB_POOL_SIZE	Per-tenant role connection maximum	Optional	20
DB_PORT	SQL port; role direct default 3307, master 3306	Default exists	3306
DB_QUEUE_LIMIT	Maximum queued connection requests	Optional	500
DB_ROOT_PASSWORD	Master/root SQL password	Yes	<DATABASE_ROOT_PASSWORD>
DB_ROOT_USER	Provisioning SQL administrator	Default exists	<DATABASE_ADMIN>
DB_USER	Role database account; grants hardcoded knockout	Yes in Compose	<DATABASE_USER>
EXPO_PUBLIC_API_HOST	Phone-reachable API hostname	For physical device	<WORKSTATION_LAN_IP>
EXPO_PUBLIC_API_PORT	Mobile unified API port	Optional	5100
FRONTEND_PORT	Published frontend port	Optional	5200
HOTEL_ID	k6 disposable tenant identity	Set for test tenant	<TEST_HOTEL_ID>
INSTANCE_ID	Publisher identity for echo suppression	Optional; generated UUID	<INSTANCE_ID>
MARIADB_DATABASE	Image initial schema from DB_NAME	Compose-derived	knockout

Variable	Purpose	Required / scope	Safe example
MARIADB_PASSWORD	Image role password from DB_PASSWORD	Compose-derived	<DATABASE_PASSWORD>
MARIADB_ROOT_HOST	Allowed root host pattern	Compose-defined	%
MARIADB_ROOT_PASSWORD	Image root password mapped from DB_ROOT_PASSWORD	Compose-derived	<DATABASE_ROOT_PASSWORD>
MARIADB_USER	Image role account from DB_USER	Compose-derived	<DATABASE_USER>
MASTER_ADMIN_POOL_SIZE	Provisioning/admin pool maximum	Optional	20
MASTER_DB_NAME	Catalog schema	Default exists	knockout_master
MASTER_DB_POOL_SIZE	Catalog pool maximum	Optional	30
MASTER_SESSION_SECRET	HMAC signing secret shared by replicas	Explicit value required for secure deployment	<RANDOM_SIGNING_SECRET>
MINIO_ACCESS_KEY	MinIO client/admin username	Yes for MinIO	<MINIO_ACCESS_KEY>
MINIO_API_PORT	Published MinIO API port	Optional	9100
MINIO_BUCKET	MinIO bucket fallback	Default exists	food-images
MINIO_CONSOLE_PORT	Published storage admin console	Optional	9101
MINIO_ENDPOINT	MinIO hostname	Required for chosen topology	minio
MINIO_PORT	MinIO service API port	Default exists	9000
MINIO_PUBLIC_URL	Browser-reachable storage base; bucket appended	Needed for reachable client images	http://localhost:9100
MINIO_ROOT_PASSWORD	Storage image admin from secret key	Compose-derived	<MINIO_SECRET>
MINIO_ROOT_USER	Storage image admin from access key	Compose-derived	<MINIO_ACCESS_KEY>
MINIO_SECRET_KEY	MinIO client/admin secret	Yes for MinIO	<MINIO_SECRET>
MINIO_SSL	Enable MinIO SSL only if true	Optional; not injected by Compose	false
NOTIFICATION_WEBHOOK_URL	Registration/subscription notice webhook	Optional; not injected by Compose	https://notify.example.invalid/send
PHPMYADMIN_PORT	Published database console	Optional	9200
PHPMYADMIN_UPLOAD_LIMIT	Database UI import limit	Optional	64M
PMA_ARBITRARY	Disable arbitrary database target entry	Compose-defined	0

Variable	Purpose	Required / scope	Safe example
PMA_HOST	phpMyAdmin database target	Compose-defined	mariadb
PMA_PORT	phpMyAdmin SQL target port	Compose-defined	3306
PORT	Internal HTTP listen port	Service-defined	5000
PORTAL_ROLE	Role process policy identity	Required for correct role process	admin
REDIS_EVENTS_CHANNEL	Pub/sub channel	Optional; not injected in Compose	knockout:state-events
REDIS_REQUIRED	Fail startup on caught Redis initialization error	Optional	true
REDIS_URL	Pub/sub connection URL	For cross-replica events	<REDIS_CONNECTION_URL>
RUN_MIGRATIONS	Skip role migrations only when false	Optional; NOT injected by Compose	false
S3_ACCESS_KEY_ID	S3 access ID	For S3 unless AWS alias	<S3_ACCESS_KEY_ID>
S3_BUCKET	S3 bucket if no STORAGE_BUCKET	For S3	<ASSET_BUCKET>
S3_ENDPOINT	S3-compatible hostname	For S3; default exists	s3.amazonaws.com
S3_PATH_STYLE	Use path-style S3 requests	Optional	false
S3_PORT	S3 TCP port	Optional	443
S3_PUBLIC_URL	Custom public base, bucket appended	Optional	https://assets.example.invalid
S3_REGION	S3 region	For S3	<AWS_REGION>
S3_SECRET_ACCESS_KEY	S3 secret	For S3 unless AWS alias	<S3_SECRET_ACCESS_KEY>
S3_SSL	S3 TLS unless false	Optional	true
SMS_WEBHOOK_TOKEN	SMS bearer credential	If provider requires	<SMS_TOKEN>
SMS_WEBHOOK_URL	Table booking SMS provider URL	Optional; otherwise queued	https://sms.example.invalid/send
STATE_CACHE_TTL_MS	Process-local state cache lifetime	Optional	1000
STATE_HISTORY_DAYS	Operational history window, clamp 7–365	Optional	90
STORAGE_BUCKET	Bucket override	Optional	<ASSET_BUCKET>
STORAGE_PROVIDER	minio or s3 selection	Optional	minio
STORAGE_PUBLIC_READ	MinIO whole-bucket public-read policy	Optional; review privacy	false

Variable	Purpose	Required / scope	Safe example
TENANT_POOL_IDLE_MS	Inactive tenant pool retirement	Optional	300000
TZ	Container timezone	Optional	Asia/Kolkata
UPLOAD_LIMIT	phpMyAdmin import size	Compose-derived	64M
USER_PIN	k6 nonproduction account PIN	Required for k6	<TEST_PIN>
VITE_API_URL	Compose value not consumed by api.js	Unused by current HTTP helper	/api
VITE_PORTAL_ROLE	Browser build portal role mode	Optional	unified
VITE_PROXY_TARGET	Vite API/WebSocket proxy target	For correct dev topology	http://localhost:5100

Environment evidence map

Variable	Source locations
AWS_ACCESS_KEY_ID	backend/src/storage.js
AWS_REGION	backend/src/storage.js
AWS_SECRET_ACCESS_KEY	backend/src/storage.js
BACKEND_PORT	.env.example, docker-compose.yml
BACKEND_PORT_RANGE	.env.example, docker-compose.scale.yml
BASE_URL	load-tests/api-capacity.js
COMPOSE_PROJECT_NAME	.env.example
DB_CONNECT_TIMEOUT_MS	.env.example, backend/src/database.js, backend/src/master-server.js, docker-compose.yml
DB_EXTERNAL_PORT	.env.example, docker-compose.yml
DB_HOST	.env.example, backend/src/database.js, backend/src/master-server.js, docker-compose.yml
DB_NAME	.env.example, backend/src/database.js, backend/src/server.js, docker-compose.yml
DB_PASSWORD	.env.example, backend/src/database.js, docker-compose.yml
DB_POOL_IDLE_TIMEOUT_MS	.env.example, backend/src/database.js, backend/src/master-server.js, docker-compose.yml
DB_POOL_MAX_IDLE	.env.example, backend/src/database.js, backend/src/master-server.js, docker-compose.yml
DB_POOL_SIZE	.env.example, backend/src/database.js, docker-compose.yml
DB_PORT	.env.example, backend/src/database.js, backend/src/master-server.js, docker-compose.yml
DB_QUEUE_LIMIT	.env.example, backend/src/database.js, backend/src/master-server.js, docker-compose.yml
DB_ROOT_PASSWORD	.env.example, backend/src/master-server.js, docker-compose.yml
DB_ROOT_USER	.env.example, backend/src/master-server.js, docker-compose.yml
DB_USER	.env.example, backend/src/database.js, docker-compose.yml
EXPO_PUBLIC_API_HOST	mobile/.env.example, mobile/App.js
EXPO_PUBLIC_API_PORT	mobile/App.js
FRONTEND_PORT	.env.example, docker-compose.yml
HOTEL_ID	load-tests/api-capacity.js
INSTANCE_ID	backend/src/realtime.js
MARIADB_DATABASE	docker-compose.yml (container setting)
MARIADB_PASSWORD	docker-compose.yml (container setting)
MARIADB_ROOT_HOST	docker-compose.yml (container setting)
MARIADB_ROOT_PASSWORD	docker-compose.yml (container setting)
MARIADB_USER	docker-compose.yml (container setting)

Variable	Source locations
MASTER_ADMIN_POOL_SIZE	.env.example, backend/src/master-server.js, docker-compose.yml
MASTER_DB_NAME	.env.example, backend/src/master-server.js, docker-compose.yml
MASTER_DB_POOL_SIZE	.env.example, backend/src/master-server.js, docker-compose.yml
MASTER_SESSION_SECRET	.env.example, backend/src/master-server.js, docker-compose.yml
MINIO_ACCESS_KEY	.env.example, backend/src/storage.js, docker-compose.yml
MINIO_API_PORT	.env.example, docker-compose.yml
MINIO_BUCKET	.env.example, backend/src/storage.js, docker-compose.yml
MINIO_CONSOLE_PORT	.env.example, docker-compose.yml
MINIO_ENDPOINT	.env.example, backend/src/storage.js, docker-compose.yml
MINIO_PORT	.env.example, backend/src/storage.js, docker-compose.yml
MINIO_PUBLIC_URL	.env.example, backend/src/storage.js, docker-compose.yml
MINIO_ROOT_PASSWORD	docker-compose.yml (container setting)
MINIO_ROOT_USER	docker-compose.yml (container setting)
MINIO_SECRET_KEY	.env.example, backend/src/storage.js, docker-compose.yml
MINIO_SSL	backend/src/storage.js
NOTIFICATION_WEBHOOK_URL	backend/src/master-server.js
PHPMYADMIN_PORT	.env.example, docker-compose.yml
PHPMYADMIN_UPLOAD_LIMIT	.env.example, docker-compose.yml
PMA_ARBITRARY	docker-compose.yml (container setting)
PMA_HOST	docker-compose.yml (container setting)
PMA_PORT	docker-compose.yml (container setting)
PORT	backend/src/master-server.js, backend/src/server.js
PORTAL_ROLE	backend/src/nest/app.module.js, backend/src/server.js
REDIS_EVENTS_CHANNEL	.env.example, backend/src/realtime.js
REDIS_REQUIRED	.env.example, backend/src/master-server.js, docker-compose.yml
REDIS_URL	.env.example, backend/src/realtime.js, docker-compose.yml
RUN_MIGRATIONS	.env.example, backend/src/server.js
S3_ACCESS_KEY_ID	.env.example, backend/src/storage.js, docker-compose.yml
S3_BUCKET	.env.example, backend/src/storage.js, docker-compose.yml
S3_ENDPOINT	.env.example, backend/src/storage.js, docker-compose.yml
S3_PATH_STYLE	.env.example, backend/src/storage.js, docker-compose.yml

Variable	Source locations
S3_PORT	.env.example, backend/src/storage.js, docker-compose.yml
S3_PUBLIC_URL	.env.example, backend/src/storage.js, docker-compose.yml
S3_REGION	.env.example, backend/src/storage.js, docker-compose.yml
S3_SECRET_ACCESS_KEY	.env.example, backend/src/storage.js, docker-compose.yml
S3_SSL	.env.example, backend/src/storage.js, docker-compose.yml
SMS_WEBHOOK_TOKEN	.env.example, backend/src/server.js, docker-compose.yml
SMS_WEBHOOK_URL	.env.example, backend/src/server.js, docker-compose.yml
STATE_CACHE_TTL_MS	.env.example, backend/src/server.js, docker-compose.yml
STATE_HISTORY_DAYS	.env.example, backend/src/database.js, docker-compose.yml
STORAGE_BUCKET	.env.example, backend/src/storage.js, docker-compose.yml
STORAGE_PROVIDER	.env.example, backend/src/storage.js, docker-compose.yml
STORAGE_PUBLIC_READ	.env.example, backend/src/storage.js, docker-compose.yml
TENANT_POOL_IDLE_MS	.env.example, backend/src/database.js, docker-compose.yml
TZ	.env.example, docker-compose.yml
UPLOAD_LIMIT	docker-compose.yml (container setting)
USER_PIN	load-tests/api-capacity.js
VITE_API_URL	docker-compose.yml (container setting)
VITE_PORTAL_ROLE	frontend/src/App.jsx, frontend/src/api.js
VITE_PROXY_TARGET	frontend/vite.config.js

32.4 Package version inventory

Manifest	Package	Declared	Locked	Category
package.json	concurrently	^9.2.1	9.2.4	devDependencies
backend/package.json	@nestjs/common	11.2.1	11.2.1	dependencies
backend/package.json	@nestjs/core	11.2.1	11.2.1	dependencies
backend/package.json	@nestjs/platform-express	11.2.1	11.2.1	dependencies
backend/package.json	cors	^2.8.5	2.8.6	dependencies
backend/package.json	express	^5.1.0	5.2.1	dependencies
backend/package.json	minio	^8.0.5	8.0.7	dependencies
backend/package.json	multer	^2.0.2	2.2.0	dependencies
backend/package.json	mysql2	^3.14.3	3.23.2	dependencies
backend/package.json	redis	5.12.1	5.12.1	dependencies
backend/package.json	reflect-metadata	0.2.2	0.2.2	dependencies
backend/package.json	rxjs	7.8.2	7.8.2	dependencies
backend/package.json	ws	^8.21.3	8.21.3	dependencies
frontend/package.json	@vitejs/plugin-react	^5.0.0	5.2.0	dependencies
frontend/package.json	lucide-react	^0.536.0	0.536.0	dependencies
frontend/package.json	motion	13.1.0	13.1.0	dependencies
frontend/package.json	react	^19.1.1	19.2.8	dependencies
frontend/package.json	react-dom	^19.1.1	19.2.8	dependencies
frontend/package.json	typescript	^5.8.3	5.9.3	dependencies
frontend/package.json	vite	^7.0.0	7.3.6	dependencies
mobile/package.json	@expo/vector-icons	^15.0.3	15.1.1	dependencies
mobile/package.json	@react-native-async-storage/async-storage	2.2.0	2.2.0	dependencies
mobile/package.json	expo	~57.0.24	57.0.24	dependencies
mobile/package.json	expo-asset	~57.0.18	57.0.18	dependencies
mobile/package.json	expo-blur	~57.0.3	57.0.3	dependencies
mobile/package.json	expo-constants	~57.0.19	57.0.19	dependencies
mobile/package.json	expo-font	~57.0.4	57.0.4	dependencies
mobile/package.json	expo-image-picker	~57.0.19	57.0.19	dependencies
mobile/package.json	expo-linear-gradient	~57.0.2	57.0.2	dependencies
mobile/package.json	expo-status-bar	~57.0.1	57.0.1	dependencies

Manifest	Package	Declared	Locked	Category
mobile/package.json	react	19.2.3	19.2.3	dependencies
mobile/package.json	react-native	0.86.3	0.86.3	dependencies
mobile/package.json	react-native-safe-area-context	~5.7.0	5.7.0	dependencies
mobile/package.json	babel-preset-expo	~57.0.0	57.0.12	devDependencies

32.5 Error codes and operational glossary

Code/status	Meaning
400	Input or unsupported state value
401	Invalid/expired identity or missing master approval
403 / COMPANY_SUSPENDED	Company inactive/suspended
403 / MODULE_DISABLED	Mapped module/portal disabled
403	Role/ownership guard denial
404	Referenced record missing
409	Slot, balance, singleton-role or transition conflict
500	Uncaught SQL/storage/runtime error
503	Exhausted random identifier allocation attempts
WS 1008	Unauthorized subscription

Term	Meaning here
Tenant	Company and dedicated database schema
Hotel ID	Company login identifier, not room identifier
PIN	Static access credential; not a delivered one-time OTP
Batch / round	Additional group of order lines under one order
Handoff	Chef collection then Waiter receipt
PMS	Requested project umbrella; lodging modules absent
RPO / RTO	Acceptable data loss window / time to restore
Outbox	Persisted notifications; delivery/retry worker absent
State cache	Short process-local promise/result reuse
RBAC	Role-based access control; route checks, with documented gaps

32.6 Deployment and production readiness checklist

- Confirm reviewed source/image and lockfile versions; preserve working-tree diff privately.
- Remove seeded/fallback credentials; configure independent signing secret and secure credential storage.
- Close route/ownership/module gaps and isolate internal APIs/data services.
- Rehearse migrations across actual tenant variants; inspect foreign keys and back up all schemas/objects.
- Configure production frontend, TLS/DNS/WebSocket ingress and configurable clients.
- Pin images, inject secrets, restrict storage and administration consoles.
- Pass authentication, tenant isolation, billing, reservation and concurrency regression suites.
- Measure load in staging; confirm DB connection budgets and recovery targets.
- Set logs/metrics/alerts, backup retention and tested rollback/runbooks.
- Verify native behavior on real iOS/Android devices; bundle success alone is insufficient.

32.7 Source evidence and inspection scope

All authored source/configuration paths in the manifest were inventoried; routing, SQL, startup, auth, storage, realtime, UI calls, deployment and scripts were inspected. Generated bundles were treated as artifacts, not separate authoritative implementations. Actual .env files and credential directories are not copied. The manifest hashes files without publishing their contents.

Source	Responsibility / evidence
.env.example	1360 bytes; SHA-256 732c5326c104191c...
.gitignore	42 bytes; SHA-256 9a8e02820889147e...
.node-version	8 bytes; SHA-256 73771b301eb6d0b0...
.npmrc	35 bytes; SHA-256 3b88d1057add6f92...
.nvmrc	7 bytes; SHA-256 e8e8584c09cc1d8f...
README.md	4460 bytes; SHA-256 350935f27de61cd4...
SCALING.md	2958 bytes; SHA-256 24cf3215396b70bb...
app.js	24577 bytes; SHA-256 d64a7afa1fc1ae87...
backend/Dockerfile	285 bytes; SHA-256 3668cc5a5e5f8fd4...
backend/package.json	714 bytes; SHA-256 8ebec6648c1f4858...
backend/scripts/check-runtime-versions.mjs	596 bytes; SHA-256 df03de710e8772da...
backend/src/database.js	25160 bytes; SHA-256 f14fa4651ff63dcc...
backend/src/main-master.js	56 bytes; SHA-256 2f6275277d1174b0...
backend/src/main.js	49 bytes; SHA-256 4a409437cb2ad8e4...
backend/src/master-server.js	52340 bytes; SHA-256 df0a5421a59a709b...
backend/src/nest/app.module.js	580 bytes; SHA-256 78e8663571a87ac6...

Source	Responsibility / evidence
backend/src/nest/platform.js	644 bytes; SHA-256 9913a32e5fe69506...
backend/src/realtime.js	1446 bytes; SHA-256 968f51d4d469e08c...
backend/src/server.js	53726 bytes; SHA-256 584dbc7240f8620d...
backend/src/storage.js	3275 bytes; SHA-256 5a3badbb8ce4b5f5...
backend/src/store.js	3648 bytes; SHA-256 8bd6428633701df0...
docker-compose.scale.yml	101 bytes; SHA-256 abc0f15032678a2e...
docker-compose.yml	8605 bytes; SHA-256 ee917908619a48f2...
frontend/Dockerfile	288 bytes; SHA-256 969e4612866cfe4d...
frontend/index.html	408 bytes; SHA-256 99166e448ef36c84...
frontend/package.json	567 bytes; SHA-256 9a5c135a308c211f...
frontend/scripts/check-runtime-versions.mjs	596 bytes; SHA-256 df03de710e8772da...
frontend/src/AnimatedUI.jsx	5709 bytes; SHA-256 5f514a6ab69bde54...
frontend/src/App.jsx	283379 bytes; SHA-256 e29e4f3512329493...
frontend/src/AttendancePanel.jsx	4163 bytes; SHA-256 67e4a9c96fed5431...
frontend/src/api.js	5528 bytes; SHA-256 418d36c1bdb86050...
frontend/src/knockout.css	203105 bytes; SHA-256 3217142c26042fa7...
frontend/src/main.jsx	314 bytes; SHA-256 4f0574bd8b469010...
frontend/src/styles.css	23826 bytes; SHA-256 455cfbba77c5b25...
frontend/vite.config.js	445 bytes; SHA-256 7657e86ec9cf8f59...
index.html	2529 bytes; SHA-256 782597a5d9f32a4e...
knockout-production.sql	11977 bytes; SHA-256 93a89ab078f243f8...
load-tests/api-capacity.js	1741 bytes; SHA-256 cfe436a0ffc421d3...
mobile/.env.example	144 bytes; SHA-256 f8f56545cb9993a9...
mobile/.gitignore	7 bytes; SHA-256 73986a2384fd8425...
mobile/AdminModules.js	65875 bytes; SHA-256 fd365134e72ee394...
mobile/App.js	114190 bytes; SHA-256 d8bf5cf322e23777...
mobile/PremiumDashboard.js	8727 bytes; SHA-256 311469dbd25ffb3f...
mobile/README.md	626 bytes; SHA-256 484ed4fbca33ffab...
mobile/app.config.js	889 bytes; SHA-256 1508c2bb450576e2...
mobile/babel.config.js	87 bytes; SHA-256 6c5f09a4f422350e...
mobile/eas.json	198 bytes; SHA-256 8fad88a0911fd7a8...

Source	Responsibility / evidence
mobile/package-lock.json	255781 bytes; SHA-256 f2c0261a4330f167...
mobile/package.json	869 bytes; SHA-256 d9aae3366b6785b8...
package-lock.json	138433 bytes; SHA-256 7a2889264bd7b75a...
package.json	577 bytes; SHA-256 ad0320b390e0f8b5...
scripts/check-runtime-versions.mjs	596 bytes; SHA-256 df03de710e8772da...
styles.css	13686 bytes; SHA-256 7c87ff39cef76229...

Detailed reproducibility files: source-manifest.json, api-inventory.json, database-inventory.json, environment-inventory.json and VERIFICATION.md. Inventories are tied to this source snapshot. Recheck before production changes.

32.8 Module keys and additional contract notes

Key	UI module	Gateway prefix check
tables	Tables and Waiters	/tables
bookings	Table Bookings	/bookings
billing	Orders and Billing	Not mapped to /orders
parcels	Parcel Orders	Not mapped to /parcels
menu	Food and Photos	/menu and /combos
stock	Stock Management	/inventory and /stock-requests
finance	Finance Management	/finance and /supplier-*
staff	Staff Management	/staff, /attendance, /kitchen-staff
kitchen	Chef Portal	Whole Chef role
juicer	Juicer Portal	Whole Juicer role

POST /bookings requires tableId, bookingDate, bookingTime, customerPhone; durationMinutes defaults to 90. Phone is normalized then validated as optional plus and 8–15 digits. Date must match YYYY-MM-DD and be in the future according to database time; duration must be an integer 30–240. Overlap considers confirmed bookings with the same booking_date.

POST /tables requires positive integer number/seats and nonempty area. PATCH status allows available/occupied/reserved/cleaning; bookingTime optional. Occupied requires an active order; an active order cannot be released by changing status.

POST /orders requires nonempty items and tableId; guestName/waiter have fallback labels. POST /orders/:id/items requires items; POST /parcels requires items, with customerName/customerPhone/adminName defaults and optional paymentMethod. Initial items use menuId/qty/note without a complete numeric schema. /mark-paid accepts only Cash or Card / UPI; /finalize requires a payment method only when unpaid, but does not validate it to the same enum or enforce a ready/billing-requested predecessor.

PATCH preparation accepts status new/preparing/ready and batchNo default 1. Batch handoff accepts collected or received; path batchNo is normalized to at least 1. Legacy whole-order status accepts collected/received but should not replace batch handoff in new clients.

POST /inventory requires name/unit and nonnegative quantity/min/cost checks; PUT fields are less strictly validated. Movement requires finite positive quantity and movementType purchase/usage/adjustment/waste. Stock request requires positive finite

requestedQuantity, valid inventoryId and nonempty requestedBy (defaults Chef). Duplicate pending/ordered requests are checked, not uniquely constrained.

POST /finance requires entryType income/expense, category, description, positive amount and entryDate. Supplier purchase requires supplierName/description/purchaseDate, positive totalAmount and paidAmount between zero and total. Supplier payment requires positive amount/paymentDate and rejects amount above due. Some numeric predicates omit Number.isFinite; malformed numeric inputs can pass application checks and fail at SQL.

POST /staff accepts name, role admin/waiter/chef, optional phone/payType/payRate; payType daily/monthly, PIN generated. PUT additionally accepts juicer, requires six-digit pin and active defaults true. Juicer creation requires name and valid payType. Kitchen staff requires trimmed name/designation and valid payType; joinedOn optional, other text fields default empty.

POST /menu requires name/category and nonnegative price check; PUT has fewer guards. Availability requires boolean available. POST /combos requires name, price and nonempty components; PUT replaces component rows without equivalent create validation. No immutable versioning of menu descriptions/labels exists.

Public registration requires companyName/adminName, email format, normalized phone, valid packageCode and periodMonths 1/6/12 (defaults starter/1). Onboarding status requires id/pin matching an incomplete request. Completion requires approved matching request, paymentReference length at least five, businessType and address; gstNumber optional. Response contains generated hotelId/adminPin/companyName/expiresAt; treat credential fields as sensitive.

Master module change requires known module key and boolean enabled. Company status is active/suspended; invoice status due/paid. PIN edits require six digits and uniqueness checks. Module pricing requires known key and finite nonnegative price. Master DELETE company requires exact companyName and rejects primary knockout schema. These are destructive operations, not examples to execute during verification.

32.9 External technical references

R1. MariaDB CREATE TABLE: confirms LIKE copies columns/indexes/options but not foreign-key definitions.
<https://mariadb.com/docs/server/server-usage/tables/create-table>

R2. MariaDB mariadb-dump: documents --single-transaction behavior and concurrent DDL limitations.
<https://mariadb.com/docs/server/clients-and-utilites/backup-restore-and-import-clients/mariadb-dump>

These references validate database-engine semantics only. Application feature claims and configuration derive from repository source. References checked 4 October 2026.