

gForce Ultra



精准肌电识别

Precise EMG Recognition

基于八通道肌电干电极传感器，实时捕捉前臂肌肉电信号，实现对手部动作的高精度识别。

Based on an 8-channel dry electrode EMG sensor, it captures forearm muscle signals in real time, enabling high-accuracy recognition of hand movements.



自然交互

Natural Interaction

用户无需学习复杂操作，通过自然肌肉发力即可完成控制，让交互更直觉、更高效。

No complex learning required—users can control the system through intuitive muscle activation, making interaction more natural and efficient.



轻量便携

Lightweight & Portable

腕带式设计，轻巧贴合手臂，佩戴无负担。

Wristband design that fits comfortably on the arm, ensuring a lightweight and effortless wearing experience.



实时数据输出

Real-time Data Output

提供稳定的肌电数据与识别结果输出，支持多种应用场景拓展。

Provides stable EMG data and recognition output, supporting a wide range of application scenarios.



技术规格 / SPECIFICATIONS

主机尺寸 / Main Unit Dimensions (L × W × H)	53 mm × 28 mm × 17 mm
腕带长度 - XS 款 / Wristband Length (XS Size)	190 mm (±2 mm)
腕带长度 - S 款 / Wristband Length (S Size)	202 mm (±2 mm)
腕带长度 - M 款 / Wristband Length (M Size)	216 mm (±2 mm)
腕带长度 - L 款 / Wristband Length (L Size)	230 mm (±2 mm)
ADC 采样率 / ADC Sampling Rate	1000 Hz
ADC 分辨率 / ADC Resolution	24 Bit
EMG 通道数 / EMG Channels	8 通道 / 8 Channels
EMG 采样率 / EMG Sampling Rate	500 Hz
电池类型 / Battery Type	锂聚合物电池 / Lithium Polymer Battery
电池大小 / Battery Size	200 mAh
工作时长 / Operating Time	5h
额定电流 / Rated Current	30 mA
IMU 方向数 / IMU Axes	6轴 / 6-Axis
IMU 采样率 / IMU Sampling Rate	50 Hz
LED	绿色状态指示灯; 橙色充电指示灯 Green Status LED; Orange Charging LED
按键 / Button	电源按键; 设备电源开 / 关 Power Button; Device Power On/Off
通信方式 / Communication Method	BLE4.2

联系我们 / Contact Us

☎ +86 21 63210200 ✉ info@oymotion.com 🌐 www.oymotion.com

📍 上海市浦东新区紫萍路788号 / No. 788 Ziping Road, Pudong New Area, Shanghai, China

