

Fundamentals of Machine Learning:

Linear Models for Classification: Probabilistic Models

Prof. Andrew D. Bagdanov (andrew.bagdanov AT unifi.it)



UNIVERSITÀ
DEGLI STUDI
FIRENZE

DINFO
DIPARTIMENTO DI
INGEGNERIA
DELL'INFORMAZIONE

Introduction

Probabilistic Generative Models

Probabilistic Discriminative Models

Bayesian Logistic Regression

Concluding Remarks

Introduction

Probabilistic approaches to classification

- In the last lecture we looked at **linear** models for classification from a purely **geometric** perspective.
- Like **least squares regression**, these lack the ability to quantify **belief** in their predictions.
- In this lecture we will look at linear classification from three **probabilistic** perspectives:
 - **Generative**: in which a class-conditional data **likelihood** and class **priors** will be used to derive a classification rule.
 - **Discriminative**: in which the **posterior** class distribution is **directly** estimated.
 - **Bayesian**: in which we approximate the **parameter** distribution from the data likelihood and **prior** and then **integrate** to make predictions.

Lecture objectives

At the end of this lecture you will:

- Understand the **generative** approach to classification and how the **linear** and **quadratic** discriminants derive from assumptions about class-conditional likelihoods.
- Understand the discriminative **logistic regression** approach to classification and how the **negative log-likelihood** loss can be used to train it.
- Understand the basics (and limits) of the **Bayesian** approach to classification and why **approximate** inference is needed.

Probabilistic Generative Models

Again, where are the probabilities?!

- Again, we find ourselves with a nice **model**, but one entirely unable to provide any measure of **belief**.
- We will now consider a specific type of **generative** view that will naturally lead (via Bayes rule) to just such a measure.
- As we saw for **linear regression models**, we will also find connections between the **probabilistic** and **geometric** views.

A generative model


- For $K = 2$ class problems, we can write the posterior for class \mathcal{C}_1 as:

$$\begin{aligned} p(\mathcal{C}_1 | \mathbf{x}) &= \frac{p(\mathbf{x} | \mathcal{C}_1)p(\mathcal{C}_1)}{p(\mathbf{x} | \mathcal{C}_1)p(\mathcal{C}_1) + p(\mathbf{x} | \mathcal{C}_2)p(\mathcal{C}_2)} \\ &= \frac{1}{1 + \exp(-a)} \equiv \sigma(a(\mathbf{x})) \\ \text{for } a &= \ln \frac{p(\mathbf{x} | \mathcal{C}_1)p(\mathcal{C}_1)}{p(\mathbf{x} | \mathcal{C}_2)p(\mathcal{C}_2)} \end{aligned}$$

- Writing the **posterior** in this way might seem like a waste of time.
- However, we will see that this helps **generalize** our results, especially when $a(\mathbf{x})$ has a simple form.

σ , a familiar friend

- The $\sigma(\cdot)$ function is known as the **logistic sigmoid** function.
- It plays an important role in many **classification** models.
- It is **very** important for Artificial Neural Networks.



K-class problems

- For the case of $K > 2$:

$$\begin{aligned} p(\mathcal{C}_k | \mathbf{x}) &= \frac{p(\mathbf{x} | \mathcal{C}_k)p(\mathcal{C}_k)}{\sum_j p(\mathbf{x} | \mathcal{C}_j)p(\mathcal{C}_j)} \\ &= \frac{\exp(a_k)}{\sum_j \exp(a_j)} \end{aligned}$$

- This is known as the **normalized exponential** or **softmax** function.
- Let's see what happens for a **specific** choice for a_k ...

Generative models with continuous inputs

- We can assume that the class-conditional densities (another name for the **likelihood**) are Gaussian with **equal covariance matrices**:
- Thus, the density for class \mathcal{C}_k is:

$$p(\mathbf{x} | \mathcal{C}_k) = \frac{1}{(2\pi)^{D/2} |\Sigma|^{-1}} \exp \left\{ -\frac{1}{2} (\mathbf{x} - \boldsymbol{\mu}_k)^T \Sigma^{-1} (\mathbf{x} - \boldsymbol{\mu}_k) \right\}$$

- If we consider only the **first** class, and recalling the analysis we made about the **form** of the posterior, we have:



$$p(\mathcal{C}_1 | \mathbf{x}) = \sigma(\mathbf{w}^T \mathbf{x} + w_0)$$

$$\text{where } \mathbf{w} = \Sigma^{-1}(\boldsymbol{\mu}_1 - \boldsymbol{\mu}_2)$$

$$\text{and } w_0 = -\frac{1}{2} \boldsymbol{\mu}_1^T \Sigma^{-1} \boldsymbol{\mu}_1 + \frac{1}{2} \boldsymbol{\mu}_2^T \Sigma^{-1} \boldsymbol{\mu}_2 + \ln \frac{p(\mathcal{C}_1)}{p(\mathcal{C}_2)}$$

Generative models with continuous inputs

- The **quadratic terms** in \mathbf{x} have canceled (due to the **common Σ**).
- The **decision boundaries** are linear in input space.



Generative models with continuous inputs



- For the general case of K classes, we use the **softmax** instead of sigmoid.
- We have:

$$\begin{aligned}a_k(\mathbf{x}) &= \mathbf{w}_k^T \mathbf{x} + w_{k0} \\ \text{where } \mathbf{w}_k &= \Sigma^{-1} \boldsymbol{\mu}_k \\ \text{and } w_{k0} &= \frac{1}{2} \boldsymbol{\mu}_k^T \Sigma^{-1} \boldsymbol{\mu}_k + \ln p(\mathcal{C}_k)\end{aligned}$$

- The resulting **decision boundaries** are where two of the posteriors are **equal**.
- This corresponds to the minimum misclassification rate (again a linear function of \mathbf{x}).

Generative models with continuous inputs

- If we relax the requirement that all covariance matrices are **equal**, the quadratic terms no longer cancel.
- The result is a **quadratic** Bayes classifier.





Probabilistic Discriminative Models

Generative versus discriminative

- We have seen that the **posterior** probability in a 2-class problem can be written as a **logistic sigmoid** of a **linear** function of \mathbf{x} .
- Similarly, for the **multi-class** case we have a **softmax** function on a **linear** function of \mathbf{x} .
- These are instances of what are known as **generalized linear models**.
- For specific choices of the **class-conditional distributions** we can use maximum likelihood to estimate their parameters (and those of the **priors**).
- These are sometimes called **generative models**, because we could **generate** samples \mathbf{x} by sampling from the **marginal** $p(\mathbf{x})$.
- What if, instead, we use the **functional** form of the generalized linear model **directly** to discriminate?

Fixed basis functions

- We have developed all of classifiers to work directly on the **original** input \mathbf{x} .
- However, **everything** we have derived works equally well if we use a vector of basis functions $\phi(\mathbf{x})$.
- The resulting boundaries are **linear** in feature space ϕ , but **nonlinear** in the original space.



Logistic regression

- We have just seen that we can write the **posterior** for a 2-class problem as:

$$p(\mathcal{C}_1 \mid \phi) = \sigma(\mathbf{w}^T \phi)$$

- This is called (confusingly) a **logistic regression** model.
- For an M -dimensional feature space, this model has **M parameters**.
- The **generative model** would require $2M$ parameters for the means, plus $M(M + 1)/2$ parameters for the covariance matrix.
- We can use Maximum Likelihood to fit the parameters of this model, the convenient form of the **derivative** of the logistic sigmoid:

$$\frac{d}{da} \sigma(a) = \sigma(a)(1 - \sigma(a))$$

Logistic regression

- For dataset $\mathcal{D} = \{ \phi_n, t_n \}$, where $t_n \in \{0, 1\}$ and $\phi_n = \phi(\mathbf{x})$, the likelihood is:

$$p(\mathbf{t} \mid \mathbf{w}) = \prod_{n=0}^N y_n^{t_n} \{1 - y_n\}^{1-t_n}$$

$$\text{where } \mathbf{t} = (t_1, t_2, \dots, t_N)^T$$

$$\begin{aligned} \text{and } y_n &= p(\mathcal{C}_1 \mid \phi_n) \\ &= \sigma(\mathbf{w}^T \phi_n) \end{aligned}$$

- For our **error function** we will use the **Negative Log-likelihood**:

$$E(\mathbf{w}) = -\ln p(\mathbf{t} \mid \mathbf{w}) = -\sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\}$$

Logistic regression

- Writing the error function in this way:

$$E(\mathbf{w}) = - \sum_{n=1}^N \{t_n \ln y_n + (1 - t_n) \ln(1 - y_n)\}$$

- And recalling that $y_n = \sigma(\mathbf{w}^T \phi_n)$.
- And using our observation about the derivative of the **logistic sigmoid**:

$$\frac{d}{da} \sigma(a) = \sigma(a)(1 - \sigma(a))$$

- Lets us see the connection more explicitly between **likelihood** and **weights \mathbf{w}** :

$$\nabla_{\mathbf{w}} E(\mathbf{w}) = \sum_{n=1}^N (y_n - t_n) \phi_n$$

Logistic regression

- Here we see why the model is called **logistic regression**:

$$\nabla_{\mathbf{w}}(\mathbf{w}) = \sum_{n=1}^N (y_n - t_n) \phi_n$$

- This is the **same** sequential learning update for **linear regression** with fixed basis functions ϕ .
- And we see that the objective is to **regress** the target $t_n \in \{0, 1\}$ from $\phi(\mathbf{x})$.
- **Note**: this Maximum Likelihood solution is highly prone to **overfitting** when \mathcal{C}_1 and \mathcal{C}_2 are **linearly separable**.
- In this case, $\|\mathbf{w}\|_2$ will go to infinity, converging to a **posterior** estimate in which for all \mathbf{x} , and for **some** k , $p(\mathcal{C}_k | \mathbf{x}) = 1$.

Bayesian Logistic Regression

The recipe for Bayesian ML

- We developed a step towards a **recipe** for **full** Bayesian learning in our discussion about regression.
- Let's try to apply it to our classification problem:
 1. Decide on a **prior** $p(\mathbf{w})$.
 2. Maximize the resulting **posterior** to arrive at a **parameter distribution** $p(\mathbf{w} \mid \mathbf{t})$.
 3. Derive the **predictive** distribution $p(\mathcal{C}_k \mid \Phi, \mathbf{t})$ that we can use on new data $\phi(\mathbf{x})$.
- Step 1 is “easy” – although it is one of the primary **criticisms** of Bayesian learning.
- Steps 2 and 3 are, unfortunately, **intractable**: the **posterior** distribution over the parameters is no longer Gaussian.
- Let's see what we **can** do.

The Laplace approximation


- First, assume a **Gaussian prior**: $p(\mathbf{w}) = \mathcal{N}(\mathbf{w} \mid \mathbf{m}_0, \mathbf{S}_0)$.
- First step, **approximate** the parameter distribution.
- A simple method is known as the **Laplace Approximation** that uses the best **Gaussian** approximation.

$$q(\mathbf{w}) = \mathcal{N}(\mathbf{w} \mid \mathbf{w}_{\text{MAP}}, \mathbf{S}_N)$$

- Where the parameters are derived from the Maximum a Posteriori (MAP) estimate of the **mean** and covariance given by minimizing a second-order approximation of the **true** posterior.

The Laplace approximation

- Here is an example of approximating $p(z) \propto \exp(-z^2/2)\sigma(20z + 4)$:



The predictive distribution

- Armed with this **approximation** we can now write the (approximate) predictive distribution:

$$p(\mathcal{C}_1 | \phi, \mathbf{t}) = \int p(\mathcal{C}_1 | \phi, \mathbf{w})p(\mathbf{w} | \mathbf{t})d\mathbf{w} \approx \int \sigma(\mathbf{w}^T \phi)q(\mathbf{w})d\mathbf{w}$$

- This is a **convolution** of a **logistic sigmoid** and a **Gaussian**, which can be approximated (after **very** lengthy derivations) as:

$$\begin{aligned} p(\mathcal{C}_1 | \phi, \mathbf{t}) &\approx \sigma(\kappa(\sigma_a^2)\mu_a) \\ \text{where } \kappa(\sigma^2) &= (1 + \pi\sigma_a^2/8)^{-1/2} \\ \text{for } \sigma_a^2 &= \text{var}[a] = \phi^T \mathbf{S}_N \phi \\ \text{and } \mu_a &= \mathbf{w}_{\text{MAP}}^T \phi \end{aligned}$$

Concluding Remarks

Probabilistic generative models

- The **generative** view of $p(\mathcal{C}_k | \mathbf{x})$ is appealing for a number of reasons.
- Under **Maximum Likelihood** estimation of parameters, we just estimate a distribution for **class-conditional likelihoods** $p(\mathbf{x}|\mathcal{C}_k)$ and **posteriors** $p(\mathcal{C}_k)$.
- For the **Gaussian** case, these estimates turn out to be the “usual” ones.
- If we assume **equal** covariance for all classes, the result is a **linear** classifier.
- Instead, if we estimate a Σ_k for each class the resulting classifier is **quadratic** in the input.

Logistic Regression

- Logistic regression is an extremely important model because nearly all **Deep Neural Networks** for classification are performing multi-class **logistic regression**.
- A **Deep Network** estimates the **feature embedding** $\phi\mathbf{x}$, then a linear function and **softmax** are applied.
- Then a Negative Log Likelihood – also known as a **Cross Entropy** – loss is applied.
- Despite its problems, it is a model quite suited to **incremental, gradient-based** optimization.
- **Important:** the fact that the outputs **sum to one**, means little in terms of probabilistic interpretation of the result.

Bayesian Logistic Regression

- Exact Bayesian inference is **intractable** due to the complexity of the data likelihood.
- And the need to **normalize** the posterior – we can't just ignore the **evidence** factor in Bayes rule any longer.
- There are very sophisticated techniques to **approximate** normalized posteriors:
 - **Laplace's Method**: approximate with a Gaussian.
 - **Variational Inference**: match a **proxy** distribution to posterior.
 - **Monte Carlo Methods**: use Markov chain sampling for integration.

Reading and Homework Assignments

Reading Assignment:

- Bishop: Chapter 4 (4.2, 4.3, 4.4*, 4.5*)