

See chapter 5 in Regression and Other Stories.

.....

Widen the notebook.

```
• # ed172871-fa4d-4111-ac0a-341898917948
• html"""
• <style>
•     main {
•         margin: 0 auto;
•         max-width: 2000px;
•         padding-left: max(160px, 10%);
•         padding-right: max(160px, 10%);
•     }
• </style>
• """
```

```
• using Pkg ✓ , DrWatson ✓
```

A typical set of Julia packages to include in
notebooks.

```

• begin
•   # Specific to this notebook
•   using GLM ✓
•   using PlutoUI ✓
•
•   # Specific to ROSTuringPluto
•   using Optim ✓
•   using Logging ✓
•   using Turing ✓
•
•   # Graphics related
•   using GLMakie ✓
•
•   # Common data files and functions
•   using RegressionAndOtherStories ✓
•   import RegressionAndOtherStories: link
•
•   Logging.disable_logging(Logging.Warn)
• end;

```


5.1 Simulations of discrete events.



```
• @bind nsim PlutoUI.Slider(2:5, default=3)
```

3

```
• nsim
```



```

• let
•   f = Figure()
•   ax = Axis(f[1, 1]; xlabel="n_girls",
•           ylabel="Frequency")
•   n_girls = rand(Binomial(400, 0.488),
•               10^nsim)
•   hist!(n_girls; strokewidth = 1,
•         strokecolor = :black)
•   f
• end

```

prob_girls (generic function with 1 method)

```

• function prob_girls(bt)
•   res = if bt == :single_birth
•         rand(Binomial(1, 0.488), 1)
•       elseif bt == :fraternal_twin
•         2rand(Binomial(1, 0.495), 1)
•       else
•         rand(Binomial(2, 0.495), 1)
•       end
•   return res[1]
• end

```

girls (generic function with 2 methods)

```

• function girls(no_of_births = 400;
•   birth_types = [:fraternal_twin,
•   :identical_twin, :single_birth],
•   probabilities = [1/125, 1/300, 1 -
•   1/125 - 1/300])
•
•   return prob_girls.(sample(birth_types,
•   Weights(probabilities), no_of_births))
• end


```

```
► [1, 1, 1, 0, 1, 0, 1, 1, 0, 0, 1, 0, 0, 1, 0, 0, (
```

```
• girls()
```


204

```
• sum(girls())
```



```
• let  
•   #Random.seed!(1)  
•   f = Figure()  
•   ax = Axis(f[1, 1]; xlabel="n_girls",  
•   ylabel="Frequency")  
•   girls_sim = [sum(girls()) for i in  
•   1:1000]  
•   hist!(f[1, 1], girls_sim; strokewidth =  
•   1, strokecolor = :black, xlabel="Girls")  
•   f  
end
```

5.2 Simulation of continuous and mixed/continuous models.



```

• let
•   n_sims = 1000
•   y1 = rand(Normal(3, 0.5), n_sims)
•   y2 = [Exponential(y1[i]).θ for i in
•         1:length(y1)]
•   y3 = rand(Binomial(20, 0.5), n_sims)
•   y4 = rand(Poisson(5), n_sims)
•
•   f = Figure()
•   ax = Axis(f[1, 1]; title="1000 draws
• from Normal(3, 0.5)", xlabel="n_girls",
• ylabel="Frequency")
•   hist!(y1; bins=20)
•   ax = Axis(f[1, 2]; title="1000 draws
• from Exponential(y1)",
• xlabel="n_girls", ylabel="Frequency")
•   hist!(y2; bins=20)
•
•   ax = Axis(f[2, 1]; title="1000 draws
• from Binomial(20, 0.5)",
• xlabel="n_girls", ylabel="Frequency")
•   hist!(y3; bins=15)
•
•   ax = Axis(f[2, 2]; title="1000 draws
• from Poisson(5)", xlabel="n_girls",
• ylabel="Frequency")
•   hist!(y4; bins=10)
•   f
• end


```

```
sim (generic function with 1 method)
```

```
• function sim()  
•     N = 10  
•     male = rand(Binomial(1, 0.48), N)  
•     height = male == 1 ? rand(Normal(69.1,  
•         2.9), N) : rand(Normal(63.7, 2.7), N)  
•     avg_height = mean(height)  
• end
```

```
63.83323320045789
```

```
• sim()
```



```
• let  
•     n_sim = 1000  
•     avg_height = Float64[]  
•     for i in 1:n_sim  
•         append!(avg_height, [sim()])  
•     end  
•     hist(avg_height)  
• end
```

5.3 Summarizing a set of simulations using median and median absolute deviation.

```

▶ (mean = 5.03, median = 5.03, std = 1.98, mad = :
• let
•   N = 10000
•   z = rand(Normal(5, 2), N)
•   vals = round.([mean(z), median(z),
•                 std(z), mad(z), 1.483 .* median(abs.(z
•                 .- median(z))), std(z)/sqrt(N)];
•                 digits=2)
•   (mean=vals[1], median=vals[2],
•    std=vals[3], mad=vals[4],
•    mad_sd=vals[5], std_mean = vals[6])
end

```

Standard deviation of the mean:

```

▶ [3.62872, 6.31693]
• quantile(rand(Normal(5, 2), 10000), [0.25,
•   0.75])

```

5.4 Bootstrapping to simulate a sampling distribution.

```
earnings =
```

	height	weight	male	earn	earnk
1	74	"210"	1	50000.0	50.0
2	66	"125"	0	60000.0	60.0
3	64	"126"	0	30000.0	30.0
4	65	"200"	0	25000.0	25.0
5	63	"110"	0	50000.0	50.0
6	68	"165"	0	62000.0	62.0
7	63	"190"	0	51000.0	51.0
8	64	"125"	0	9000.0	9.0
9	62	"200"	0	29000.0	29.0
10	73	"230"	1	32000.0	32.0
⋮	more				
1816	68	"150"	1	6000.0	6.0

```
• earnings = CSV.read(ros_datadir("Earnings",  
  "earnings.csv"), DataFrame)
```

```
ratio = 0.6
```

```
• ratio = median(earnings[earnings.male .==  
  0, :earn]) / median(earnings[earnings.male  
  .== 1, :earn])
```

```
take_df_sample (generic function with 1 method)
```

```
• function take_df_sample(df, size; replace =  
  true, ordered = true)  
• df[sample(axes(df, 1), size; replace,  
  ordered), :]  
end
```


	height	weight	male	earn	earnk	ε
1	64	"115"	0	16400.0	16.4	"
2	68	"NA"	0	15000.0	15.0	"
3	69	"140"	1	20000.0	20.0	"

- `take_df_sample(earnings, 3)`

boot_ratio (generic function with 1 method)


- `function boot_ratio(df::DataFrame,`
- `sym::Symbol; draws=1000, replace=true)`
- `df = take_df_sample(df, draws; replace`
- `ratio = median(df[df.male .== 0, sym])`
- `/ median(df[df.male .== 1, sym])`
- `end`

	height	weight	male	earn	earnk
1	61	"150"	0	5000.0	5.0
2	74	"160"	1	15000.0	15.0
3	73	"210"	1	3000.0	3.0
4	66	"133"	0	20000.0	20.0
5	68	"180"	0	5000.0	5.0
6	61	"110"	0	25000.0	25.0
7	71	"185"	1	87000.0	87.0
8	65	"130"	0	30000.0	30.0
9	64	"128"	0	4000.0	4.0
10	68	"150"	0	50000.0	50.0

- `take_df_sample(earnings, 10)`

1.6785714285714286

- `boot_ratio(earnings, :earn; draws=5)`



```

• let
•   n_sims = 10000
•   global boot_output =
•   [boot_ratio(earnings, :earn; draws=500)
•   for _ in 1:n_sims]
•   hist(boot_output)
end

```

```
► [0.636364, 0.56, 0.6, 0.719512, 0.518519, 0.714286]
```

```
• boot_output
```

```
0.054282833424528554
```

```
• std(boot_output)
```

5.5 Fake-data simulations as a way of life.

Not done yet.

Note

Quick math notation test.

$$\begin{cases} x + y = 7 \\ -x + 3y = 1 \end{cases}$$

```
• md"""  
•   \\math  
•     \begin{cases}  
•       x+y=7\\  
•       -x+3y=1  
•     \end{cases}  
•   \\  
•   """
```