



Performance

Values are estimated and may vary. The <u>performance score</u> <u>is calculated</u> directly from these metrics. <u>See calculator.</u>

0-49

50-89

90-100



METRICS Expand view

First Contentful Paint

 $0.3 \, s$

Speed Index

0.3 s

Largest Contentful Paint

0.4 s

Time to Interactive

0.3 s

Total Blocking Time

0 ms

Cumulative Layout Shift

0.005



Show audits relevant to: All FCP TBT LCP CLS



Opportunity Estimated Savings

Reduce unused JavaScript

0.16 s ^

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity.

<u>Learn more</u>. [LCP]

URL Transfer Potential Size Savings

chrome-extension://lhdoppojpmngadmnindnejefpokejbdd/axe-versions/latest/axe.js 425.9 KiB 214.6 KiB

These suggestions can help your page load faster. They don't directly affect the Performance score.

DIAGNOSTICS

▲ Image elements do not have explicit width and height

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn more CLS

img
...img/atlanta%20web%20design%20logo.png (127.0.0.1)

Avoid chaining critical requests — 2 chains found

^

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more. (FCP) (LCP)

Maximum critical path latency: 120 ms

Initial Navigation

/updated%20website/page2.html (127.0.0.1)

...css/bootstrap.min.css (127.0.0.1) - 100 ms, 0.00 KiB

/updated%20website/style.css (127.0.0.1) - 0 ms, 20.61 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. <u>Learn more</u>.

Resource Type	Requests	Transfer Size
Total	10	485.1 KiB
Script	3	446.1 KiB
Stylesheet	2	20.6 KiB
Document	1	7.7 KiB
Other	1	6.3 KiB
Image	3	4.4 KiB
Media	0	0.0 KiB
Font	0	0.0 KiB
Third-party	2	443.4 KiB

 Largest Contentful Paint element – 	- 1	element found
--	-----	---------------

This is the largest contentful element painted within the viewport. <u>Learn More (LCP)</u>

Element	
	p.text-center.mg-lg.tc-white.tight-width-whitespace

O Avoid large layout shifts — 4 elements found

These DOM elements contribute most to the CLS of the page. CLS

Element CLS Contribution

Element	C	LS Contribution
div.page-container > main.main > div#t	bloc-6 > ::before	0.004
div#bloc-7.bloc.bgc-white.l-bloc		
		0
div.navbar-header		0
button#nav-toggle.ui-navbar-tog	igle.navbar-toggle	
		0
Avoid long main-thread tasks — 1 long task found		^
ists the longest tasks on the main thread, useful for identifying wo	orst contributors to input delay. <u>Learn mo</u>	re TBT
URL	Start Time	Duration
/updated%20website/page2.html (127.0.0.1)	174 ms	91 ms

More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

PASSED AUDITS (33)

Hide

Eliminate render-blocking resources — Potential savings of 10 ms

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. FCP LCP

	Transfer Size	Potentia Saving
/updated%20website/style.css (127.0.0.1)	20.6 KiB	120 m
Properly size images		
Serve images that are appropriately-sized to save cellular data and improve loa	d time. <u>Learn more</u> .	
Defer offscreen images		
Consider lazy-loading offscreen and hidden images after all critical resources hanteractive. <u>Learn more</u> .	ave finished loading to lower tir	ne to
Minify CSS — Potential savings of 5 KiB		
Minifying CSS files can reduce network payload sizes. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>		
URL	Transfer Size	Potentia Saving
/updated%20website/style.css (127.0.0.1)	20.6 KiB	5.1 Kil
Minify JavaScript		
Minifying JavaScript files can reduce payload sizes and script parse time. Learn	more. FCP LCP	
Reduce unused CSS — Potential savings of 16 KiB		
Reduce unused rules from stylesheets and defer CSS not used for above-the-fo	old content to decrease bytes c	onsumed b
Reduce unused rules from stylesheets and defer CSS not used for above-the-fo	old content to decrease bytes o Transfer Size	Potentia Saving
Reduce unused rules from stylesheets and defer CSS not used for above-the-fonetwork activity. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>	Transfer	Potentia

Optimized images load faster and consume less cellular data. Learn more.

Serve images in next-gen formats

Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. <u>Learn more</u>.

Enable text compression — Potential savings of 22 KiB

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. <u>Learn</u> <u>more</u>. <u>FCP</u> <u>LCP</u>

URL	Transfer Size	Potential Savings
/updated%20website/style.css (127.0.0.1)	20.3 KiB	16.1 KiB
/updated%20website/page2.html (127.0.0.1)	7.3 KiB	4.8 KiB
js/formHandler.js (127.0.0.1)	2.3 KiB	1.4 KiB

Preconnect to required origins

Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. <u>Learn more</u>. (FCP) (LCP)

Initial server response time was short — Root document took 0 ms

Keep the server response time for the main document short because all other requests depend on it. <u>Learn more</u>. <u>FCP</u>

URL Time Spent
/updated%20website/page2.html (127.0.0.1) 0 ms

Avoid multiple page redirects

Preload key requests

Redirects introduce additional delays before the page can be loaded. Learn more. FCP LCP

Consider using `k rel=preload>` to prioritize fetching resources that are currently requested later in page load. <u>Learn</u> <u>more</u>. FCP (LCP)

Use HTTP/2

HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more.

Use video formats for animated content

Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. <u>Learn more</u> [LCP]

Remove duplicate modules in JavaScript bundles

Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. [TBT]

Avoid serving legacy JavaScript to modern browsers — Potential savings of 37 KiB

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. <u>Learn More (TBT)</u>

URL	Potential Savings
<pre>chrome-extension://lhdoppojpmngadmnindnejefpokejbdd/axe- versions/latest/axe.js</pre>	37.0 KiB
axe.js:12	<pre>@babel/plugin-transform- classes</pre>
axe.js:12	Array.prototype.find
axe.js:12	Array.prototype.findInde
axe.js:12	Array.prototype.includes
axe.js:12	Array.prototype.some
axe.js:12	Array.from

Preload Largest Contentful Paint image

Avoids enormous network payloads — Total size was 485 KiB

Large network payloads cost users real money and are highly correlated with long load times. <u>Learn more</u>. <u>LCP</u>

URL	Transfer Size
<pre>chrome-extension://lhdoppojpmngadmnindnejefpokejbdd/axe-versions/latest/axe.js</pre>	425.9 KiB
/updated%20website/style.css (127.0.0.1)	20.6 KiB
<pre>chrome-extension://lhdoppojpmngadmnindnejefpokejbdd/highlighter.js</pre>	17.5 KiB
/updated%20website/page2.html (127.0.0.1)	7.7 KiB
/updated%20website/favicon.jpg (127.0.0.1)	6.3 KiB
img/atlanta%20web%20design%20logo.png (127.0.0.1)	3.8 KiB
js/formHandler.js (127.0.0.1)	2.7 KiB
img/dots-bg.png (127.0.0.1)	0.4 KiB
img/texture-paper.png (127.0.0.1)	0.2 KiB

Uses efficient cache policy on static assets — 0 resources found

A long cache lifetime can speed up repeat visits to your page. Learn more.

Avoids an excessive DOM size — 77 elements

A large DOM will increase memory usage, cause longer <u>style calculations</u>, and produce costly <u>layout reflows</u>. <u>Learn more</u>. <u>TBT</u>

Statistic	Element	Value
Total DOM Elements		77
Maximum DOM Depth	br	11

Statistic	Element		Value
		form#form_1	
Maximum Child Elements			9

User Timing marks and measures

Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. <u>Learn more</u>.

JavaScript execution time — 0.1 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>. (TBT)

URL	Total CPU Time	Script Evaluation	Script Parse
/updated%20website/page2.html (127.0.0.1)	167 ms	35 ms	40 ms
Unattributable	61 ms	20 ms	0 ms

Minimizes main-thread work — 0.3 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn more (TBT)

Category	Time Spent
Other	73 ms
Script Parsing & Compilation	68 ms
Script Evaluation	56 ms
Style & Layout	46 ms
Parse HTML & CSS	26 ms

Category	Time Spent
Rendering	9 ms
All text remains visible during webfont loads	^
Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Lea	arn more. FCP LCP
Minimize third-party usage	^
Third-party code can significantly impact load performance. Limit the number of redundant third-part load third-party code after your page has primarily finished loading. <u>Learn more</u> . <u>(TBT)</u>	rty providers and try to
Lazy load third-party resources with facades	^
Some third-party embeds can be lazy loaded. Consider replacing them with a facade until they are TBT	required. <u>Learn more</u> .
Largest Contentful Paint image was not lazily loaded	^
Above-the-fold images that are lazily loaded render later in the page lifecycle, which can delay the Learn more.	argest contentful paint.
Uses passive listeners to improve scrolling performance	^
Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll p	performance. <u>Learn more</u> .
Avoids document.write()	^
For users on slow connections, external scripts dynamically injected via `document.write()` can dela seconds. Learn more.	ay page load by tens of
 Avoid non-composited animations 	^
Animations which are not composited can be janky and increase CLS. Learn more CLS	
Has a <meta name="viewport"/> tag With width or initial-scale	^
A ` <meta name="viewport"/> ` not only optimizes your app for mobile screen sizes, but also prevents to user input. Learn more. (TBT)	a 300 millisecond delay

The `unload` event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Use `pagehide` or `visibilitychange` events instead. <u>Learn more</u>



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)	Hide
O The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. Learn more.	
Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
O Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .	
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
O Custom controls have associated labels	^

Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more.

0	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
0	Visual order on the page follows DOM order	^
	DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
0	Offscreen content is hidden from assistive technology	^
	Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn more</u> .	
0	HTML5 landmark elements are used to improve navigation	^
	Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technological more.</nav></main>	ogy.
Thes	se items address areas which an automated testing tool cannot cover. Learn more in our guide on <u>conducting an accessil</u>	<u>bility</u>
PAS	SSED AUDITS (15)	Hide
	[aria-hidden="true"] is not present on the document <body></body>	^
	Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document ` <body <a="" href="Learn more">Learn more.</body>	/>`.
	Buttons have an accessible name	^
	When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users very on screen readers. Learn more.	vho
	ARIA IDs are unique	^
	The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Lea more.	<u>arn</u>
	Image elements have [alt] attributes	^
	Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty attribute. <u>Learn more</u> .	alt

Form elements have associated labels	^
Labels ensure that form controls are announced properly by assistive technologies, like screen readers. <u>Learn more</u> .	
[user-scalable="no"] is not used in the <meta name="viewport"/> element and the [maximum-scale] attribute is not less than 5.	^
Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents web page. Learn more.	of a
The page contains a heading, skip link, or landmark region	^
Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more.	
Background and foreground colors have a sufficient contrast ratio	^
Low-contrast text is difficult or impossible for many users to read. <u>Learn more</u> .	
Document has a <title> element</td><td>^</td></tr><tr><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.</td><td></td></tr><tr><td>[id] attributes on active, focusable elements are unique</td><td>^</td></tr><tr><td>All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. Learn more.</td><td></td></tr><tr><td><html> element has a [lang] attribute</td><td>^</td></tr><tr><td>If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might announce the page's text correctly. Learn more.</td><td></td></tr><tr><td>html> element has a valid value for its [lang] attribute</td><td>^</td></tr><tr><td>Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more.</td><td></td></tr><tr><td>Links have a discernible name</td><td>^</td></tr><tr><td>Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the</td><td></td></tr></tbody></table></title>	

navigation experience for screen reader users. Learn more.

Lists contain only <1i> elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more. List items () are contained within or parent elements Screen readers require list items ('') to be contained within a parent '' or '' to be announced properly. Learn more. NOT APPLICABLE (29) Hide [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more. [aria-*] attributes match their roles Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. Learn more. button, link, and menuitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more [aria-hidden="true"] elements do not contain focusable descendents Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn more. ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA meter elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more.

ARIA progressbar elements have accessible names	^
When a `progressbar` element doesn't have an accessible name, screen readers announce it with a generic name it unusable for users who rely on screen readers. <u>Learn more</u> .	e, making
O [role]s have all required [aria-*] attributes	^
Some ARIA roles have required attributes that describe the state of the element to screen readers. <u>Learn more</u> .	
O Elements with an ARIA [role] that require children to contain a specific [role] have all required children.	^
Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn n	nore.
O [role]s are contained by their required parent element	^
Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility to Learn more.	unctions.
O [role] values are valid	^
ARIA roles must have valid values in order to perform their intended accessibility functions. <u>Learn more</u> .	
ARIA toggle fields have accessible names	^
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it for users who rely on screen readers. <u>Learn more</u> .	unusable
 ARIA tooltip elements have accessible names 	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it users who rely on screen readers. <u>Learn more</u> .	nusable
O ARIA treeitem elements have accessible names	^
When an element doesn't have an accessible name, screen readers announce it with a generic name, making it users who rely on screen readers. <u>Learn more</u> .	nusable
O [aria-*] attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn more</u> .	
☐ [aria-*] attributes are valid and not misspelled	^

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more.	
	^
When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Lea	<u>arn more</u> .
O Definition list items are wrapped in <d1> elements</d1>	^
Definition list items (` <dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers properly announce them. <u>Learn more</u>.</dl></dd></dt>	can
No form fields have multiple labels	^
Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which the first, the last, or all of the labels. <u>Learn more</u> .	ı use either
<frame/> or <iframe> elements have a title</iframe>	^
Screen reader users rely on frame titles to describe the contents of frames. Learn more.	
Heading elements appear in a sequentially-descending order	^
Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to na and understand when using assistive technologies. <u>Learn more</u> .	avigate
<pre>cinput type="image"> elements have [alt] text</pre>	^
When an image is being used as an ` <input/> ` button, providing alternative text can help screen reader users under purpose of the button. Learn more.	erstand the
The document does not use <meta http-equiv="refresh"/>	^
Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This create a frustrating or confusing experience. <u>Learn more</u> .	s may
O <object> elements have alternate text</object>	^
Screen readers cannot translate non-text content. Adding alternate text to ` <object>` elements helps screen reade meaning to users. <u>Learn more</u>.</object>	ers convey
No element has a [tabindex] value greater than 0	^

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u>.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn</u> more.

video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



Best Practices

GENERAL

Browser errors were logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. <u>Learn more</u>

Source Description

Source	Description
texture - paper. png:1	Failed to load resource: the server responded with a status of 404 (Not Found)
formHa ndler.js :1	ReferenceError: \$ is not defined at http://127.0.0.1:5500/updated%20website/js/formHandler.js:1:1
page2. html:13	Refused to apply style from 'http://127.0.0.1:5500/updated%20website/css/bootstrap.min.css' because its MIME type ('text/html') is not a supported stylesheet MIME type, and strict MIME checking is enabled.
page2. html:1	Refused to apply style from 'http://127.0.0.1:5500/updated%20website/css/bootstrap.min.css' because its MIME type ('text/html') is not a supported stylesheet MIME type, and strict MIME checking is enabled.

TRUST AND SAFETY

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn more

Description	Directive	Severity
No CSP found in enforcement mode		High

PASSED AUDITS (12)

Uses HTTPS ^

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. <u>Learn more</u>.

Avoids requesting the geolocation permission on page load

action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Avoids front-end JavaScript libraries with known security vulnerabilities Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more. Avoids deprecated APIs Deprecated APIs will eventually be removed from the browser. Learn more. No issues in the Issues panel in Chrome Devtools

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user

Issues logged to the 'Issues' panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. <u>Learn more</u>.

NOT APPLICABLE (2)

Hide

Fonts with font-display: optional are preloaded

.

Preload 'optional' fonts so first-time visitors may use them. Learn more

Detected JavaScript libraries

^

All front-end JavaScript libraries detected on the page. Learn more.



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more.

CRAWLING AND INDEXING



Links are not crawlable

^

Search engines may use 'href' attributes on links to crawl websites. Ensure that the 'href' attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. <u>Learn More</u>

Uncrawlable Link

Uncrawlable Link	
a.bloc-button.btn.btn-d.scrollToTop	
To appear in search results, crawlers need access to your app.	
ADDITIONAL ITEMS TO MANUALLY CHECK (1)	Hide
O Structured data is valid	^
Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. <u>Learn more</u> .	
Run these additional validators on your site to check additional SEO best practices.	
PASSED AUDITS (9)	Hide
Has a <meta name="viewport"/> tag with width or initial-scale	^
A ` <meta name="viewport"/> ` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond de to user input</u> . <u>Learn more</u> . <u>(TBT)</u>	<u>lay</u>
Document has a <title> element</td><td>^</td></tr><tr><td>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.</td><td></td></tr><tr><td>Document has a meta description</td><td>^</td></tr><tr><td>Meta descriptions may be included in search results to concisely summarize page content. Learn more.</td><td></td></tr><tr><td>Page has successful HTTP status code</td><td>^</td></tr><tr><td>Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more.</td><td></td></tr><tr><td>Links have descriptive text</td><td>^</td></tr><tr><td>Descriptive link text helps search engines understand your content. <u>Learn more</u>.</td><td></td></tr></tbody></table></title>	

Page isn't blocked from indexing	^
Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn mo	ore.
Image elements have [alt] attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty attribute. <u>Learn more</u> .	alt
Document has a valid hreflang	^
hreflang links tell search engines what version of a page they should list in search results for a given language or region Learn more.	
Document avoids plugins	^
Search engines can't index plugin content, and many devices restrict plugins or don't support them. Learn more.	
NOT APPLICABLE (4)	Hide
o robots.txt is valid	^
If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <u>Learn more</u> .	
O Document has a valid rel=canonical	^
Canonical links suggest which URL to show in search results. <u>Learn more</u> .	
O Document uses legible font sizes	^
Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive have >60% of page text ≥12px. <u>Learn more</u> .	∍ to
Tap targets are sized appropriately	^
Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to leasy enough to tap without overlapping onto other elements. Learn more.	ре



PWA

These checks validate the aspects of a Progressive Web App. Learn more.

INSTALLABLE

INSTALLABLE	
▲ Web app manifest or service worker do not meet the installability requirements — 1 reason	^
Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactive prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u> .	
Failure reason	
Page has no manifest <link/> URL	
PWA OPTIMIZED	
▲ Does not register a service worker that controls page and start_url	^
The service worker is the technology that enables your app to use many Progressive Web App features, such as offline to homescreen, and push notifications. <u>Learn more</u> .	, add
▲ Is not configured for a custom splash screen Failures: No manifest was fetched.	^
A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn more</u> .	
Does not set a theme color for the address bar. Failures: No manifest was fetched, No ` <meta name="theme-color"/> ` tag found.	^
The browser address bar can be themed to match your site. <u>Learn more</u> .	
O Content is sized correctly for the viewport	^

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u>.

Has a <meta name="viewport"> tag with width or initial-scale A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents a 300 millisecond delay to user input. Learn more. TBT Does not provide a valid apple-touch-icon For ideal appearance on iOS when users add a progressive web app to the home screen, define an 'apple-touch-icon'. It must point to a non-transparent 192px (or 180px) square PNG. Learn More. Manifest doesn't have a maskable icon No manifest was fetched A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. Learn more. ADDITIONAL ITEMS TO MANUALLY CHECK (3) Hide Site works cross-browser To reach the most number of users, sites should work across every major browser. Learn more. Page transitions don't feel like they block on the network Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. Learn more. Each page has a URL Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. Learn more. These checks are required by the baseline PWA Checklist but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually. Captured at Aug 10, 2022, **Emulated Desktop with** Single page load 11:35 AM EDT Lighthouse 9.6.1 Initial page load Custom throttling Using Chromium 103.0.0.0 with devtools