

Calculation of Mountain Bike Suspension Setup through Mobile Image Analysis

Joe Barrett - 40117680

**Submitted in partial fulfilment of the requirements of Edinburgh Napier University for
the Degree of BEng (Hons) Software Engineering**

School of Computing

07/10/2016

Abstract

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Etiam lobortis facilisis sem. Nullam nec mi et neque pharetra sollicitudin. Praesent imperdiet mi nec ante. Donec ullamcorper, felis non sodales commodo, lectus velit ultrices augue, a dignissim nibh lectus placerat pede. Vivamus nunc nunc, molestie ut, ultricies vel, semper in, velit. Ut porttitor. Praesent in sapien. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Duis fringilla tristique neque. Sed interdum libero ut metus. Pellentesque placerat. Nam rutrum augue a leo. Morbi sed elit sit amet ante lobortis sollicitudin. Praesent blandit blandit mauris. Praesent lectus tellus, aliquet aliquam, luctus a, egestas a, turpis. Mauris lacinia lorem sit amet ipsum. Nunc quis urna dictum turpis accumsan semper.

Contents

1	Introduction	1
1.1	Context	1
1.2	Background	1
1.3	Aims and Objectives	2
1.4	Thesis Structure	2
2	Literature Review	3
2.1	Mountain Bike Suspension Concepts	3
2.2	Image Analysis	7
3	Approach	9
4	Results	10
5	Critical Evaluation	11
6	Conclusion	12
	References	13
	Acronyms	15
	Glossary	15

List of Tables

1	Table of common suspension travels and intended disciplines	3
---	---	---

List of Figures

1	Full suspension and hardtail mountain bikes	1
2	Diagram showing travel and stroke on a full suspension bike	3
3	Leverage curves of three modern suspension designs	4
4	Maestro suspension	5
5	Uses of image analysis, from top left clockwise: An MRI brain scan, automotive night vision with pedestrian recognition, infrared image taken with a smartphone, chemical rock analysis from mars	7

1 Introduction

1.1 Context

The suspension on a mountain bike plays a vital part in the rider's performance, comfort and overall enjoyment of the sport. With some suspension units costing upwards of £1000 it is vital that they are setup to function correctly. The objective of this thesis is to research the characteristics of mountain bike suspension, look at methods and applications of image analysis, and produce a prototype mobile application which utilises image analysis to aid the user in setting up their suspension.

1.2 Background

A survey carried out by the International Mountain Bike Association shows the average price of mountain bikes owned in Europe to be €2546 (£2206) (IMBA Europe, 2015). Starting at around £1000 (Giant Manufacturing Co. Ltd., 2017), enthusiast level mountain bikes can be purchased with suspension for both the front and rear wheels, known as Full Suspension (FS) bikes whereas Hard Tail (HT) bikes have only front suspension. Even at this comparably low cost, the suspension units have multiple adjustments available to tune and personalize how they operate.



Figure 1: Full suspension and hardtail mountain bikes

To ensure the fork and shock function correctly they must be set up for the rider's weight and intended use of the bike. As this is considered a specialist area, many entry and mid level riders will lack the knowledge of this process or be unsure of how the suspension should operate meaning the rider could use the bike without the suspension set up correctly.

It has been proven that using a FS over a HT offers a performance advantage to the rider (Titlestad, Fairlie-Clarke, Davie, Whittaker, & Grant, 2003). However if the suspension fork and/or shock have not been set up, it can be detrimental to the rider's performance and potentially lead to injury. For example, if a shock has too little rebound damping set and the rider goes off a jump, the excessive speed at which the rear of the bike extends can create forwards rotation, causing the rider to go over the handlebars of the bike.

Additionally, an incorrect suspension setup can cause excessive wear and tear on the bike's frame and components. Suspension which is set too soft can allow for bottoming out which expends excess forces into the frame and potentially cracks the frame's structure. Suspension set too hard forces energy, which it would normally soak up, into the wheels and tires causing denting and warping of the wheel rims.

Many bicycle retailers will set up the suspension on a newly purchased mountain bike for the customer on delivery. Most of the time this will be enough to avoid incident but due to the extra weight of the equipment riders use, i.e. helmet, hydration pack, body armor which the customer will not be wearing at the time of delivery, this setup is regularly inaccurate. Furthermore, with some manufacturers choosing direct sales over local retailers (Harker, 2010; Staff, 2015), this setup can be circumnavigated altogether.

Since the birth of the modern smartphone in 2007 brought along by the first generation Apple® iPhone® and introduction of the Android™ mobile operating system, the use of mobile computing in everyday life has grown rapidly. Google™ stated that there were approximately 1.4 active Android users worldwide in 2015 (Callaham, 2015).

The introduction of activity tracking devices and mobile applications such as FitBit (Diaz et al., 2015) and Strava (West, 2015) and their growing popularity (Formosa, 2012) shows that individuals are welcome to the idea of using smartphones to aid or augment their participation in hobbies or sports. Due to this popularity and in a bid to give every rider the ability to setup and tune their own suspension, either at home or while out on a ride, companies have set about producing small devices (Aston, 2016; Hwang, 2016) and mobile applications (Benedict, 2012) which aid riders in the process.

1.3 Aims and Objectives

The aim of this project is to create a prototype mobile application for the Android operating system capable of providing the user with a suggested suspension setup using image analysis techniques. This will be achieved by meeting the following objectives:

- Complete a literature review of mountain bike suspension and image analysis techniques.
- Investigate current applications and products with similar aims
- Design the prototype application
- Implement the prototype application
- Evaluate the produced application against current products

1.4 Thesis Structure

Chapter 1 - Introduction - Outlines the context of the project and states the major aims and objectives

Chapter 2 - Literature Review -

Chapter 3 -

2 Literature Review

2.1 Mountain Bike Suspension Concepts

The purpose of suspension on a mountain bike is to divert energy from bumps and rough features in a trail away from the rider to improve comfort and performance by maintaining contact between the tires and the ground. This requires the use of a spring and damper, collectively known as a shock absorber, which allows the wheel to move away from the feature when it makes contact and make a controlled return once it has been passed.

2.1.1 Travel and Stroke

Travel is the distance which the bike's fork or frame allow the wheel to move in and upward direction. Stroke is the distance that the shock absorber can compress before it bottoms out. Travel is measured in inches or millimeters and can range from 80mm to 210mm. The amount of travel which a bike has normally denotes which discipline it was intended for. Typically less suspension is required for endurance oriented riding and more for aggressive and rough situations.

Table 1: Table of common suspension travels and intended disciplines

Travel (mm)	Cross Country	Trail	Enduro	Downhill
80				
100				
120				
140				
160				
180				
+200				




Figure 2: Diagram showing travel and stroke on a full suspension bike

2.1.2 Front Suspension

Front suspension commonly employs a linear telescoping shock absorber, known as a fork due to its dual sided construction. On nearly all suspension forks the stroke is 1:1 with the potential travel of the wheel. Front suspension is found on all FS and HT bikes.

2.1.3 Rear Suspension

Rear suspension uses a shock absorber much smaller than a fork and does not operate on a 1:1 ratio. Bike frames incorporate one or more pivot points and linkages which allows the wheel to move and act as multipliers for the suspension. Rear ratios are expressed as n:1 where n is the distance the rear wheel moves for every 1mm the shock compresses through its stroke. Though this is only the average leverage ratio for the entire travel.

As all rear suspension designs are different and the rear wheel must rotate around the main pivot, or in some cases virtual pivot, as opposed to moving linearly, the frame will behave differently through its travel and depending on the type of shock it is using. Because of this the average ratio is normally dismissed in favour of a leverage curve.




Figure 3: Leverage curves of three modern suspension designs

Figure 3 shows the leverage curves of three modern suspension designs. Each of

these designs have between 150mm and 170mm of travel and uses the 27.5 inch wheel size however it can be seen that their suspension hosts drastically different characteristics.

The Virtual Pivot Point (VPP) design of the Giant Reign (shown blue) has an initial falling rate, meaning the shock can be compressed easily, but slows down and even rises slightly towards the end of its travel. This means the suspension will feel soft most of the time but feel stiffer on large compressions. This is emphasised by the horst link system of the Lapierre Spicy (shown magenta) which has a large rise at the end of its travel.

In contrast, the curve of the single pivot Empire MX-6 Evo (shown green) is considered linear. This is due to the MX-6 having only one pivot and swinging arm, as opposed to multiple pivots and linkages of the VPP and horst link designs, so there is an almost direct input from the rear wheel to the shock.

For this project the bike used for development and testing of the application will be a 2015 Giant Reign, shown on figure 3 in blue, as there will be constant access to it during the project. The frame uses Giant's Maestro™ suspension system which is a variation of VPP. Like all VPP systems Maestro uses two links, an upper and lower, to create a virtual main pivot point, however unlike other VPP systems, Maestro creates its virtual pivot as close to the rear of the frame as possible. Indicated by the red circle in figure 4, the location of this virtual pivot is unique and, many believe, creates the most efficient suspension system on the market.




Figure 4: Maestro suspension

2.1.4 Sag

Sag is the amount that the suspension sits into its travel when the rider is in their neutral position, it is calculated using the rider's weight, available travel, and intended riding style. Sag is required so the suspension is able to drop into holes as well as soak up bumps.

To adjust sag, the stiffness of the spring must be adjusted as required. This is done by changing the air pressure when using an air spring or replacing the coil and adjusting the spring pre-load on traditional coil shocks. Depending on discipline and the amount of travel the bike has, sag can vary between 15% and 40% of the available travel though is commonly set between 25% and 35% for the average rider. 15% and 40% are reserved for competitive situations.

2.1.5 Damping

Suspension damping is carried out by forcing oil within the shock absorber through an arrangement of holes in the absorber's damping circuit. Reducing the size or number of holes making the travel of oil through the circuit slower and therefore increases the damping effect making compression or rebound slower.

2.1.5.1 Compression Damping This is applied while the shock absorber is being compressed. More damping forces the wheel to remain in contact with the ground which makes the suspension feel stiffer. Too much compression damping can make the suspension too stiff so it does not soften bumps or rough sections correctly. Too little can cause the suspension to "blow through" its travel prematurely potentially leaving none when it would be required.

2.1.5.2 Rebound Damping This is used to control the speed at which the shock absorber extends once it has been compressed. An optimal setting will allow the suspension to track the ground, returning after a bump as well as dropping into any holes. Too much rebound damping causes the suspension to return slowly and sometimes pack down meaning the absorber gradually runs out of travel. Too little can cause the suspension to buck the rider and lead to an accident.

2.1.5.3 High and Low Speed Damping Depending on the manufacturer and model of the shock absorber, the unit can include up to two adjustable speeds for each damping circuit making four adjustable damping settings in total. High speed adjustments are used in high impact situations such as large jumps or drops, compression tends to be set softer to remove impact and rebound slower so rider has time to recover and the bike is not made unstable.

Low speed adjustments are used against small movements such as rider weight shifts or long, slow compressions. Optimally compression is set stiffer as this type of feature can use a lot of travel and rebound damping set faster to deal with multiple features in quick succession.

2.1.6 Optimal Setup

Although setups will vary between rider, suspension system, and discipline there are some key aspects which all riders should aim to achieve. Sag should be set to an appropriate measurement by adjusting the air pressure on air shocks or spring rating on coil shocks. Compression damping should feel soft and soak up bumps efficiently

without excessive bottoming out. Rebound damping should be set to return as fast as possible without bucking the rider, this is normally in the middle of the two extremes of setting with a slight bias to the fast option.

2.2 Image Analysis

Image Analysis (IA) is the use of various techniques such as pattern recognition, geometry calculations, and signal processing to extract information from digital images for later use. Image processing however is the application of various processes on an image to change or improve the way it looks. The processing stage normally comes before the analysis stage in an effort to simplify the analysis processes and improve their success.




Figure 5: Uses of image analysis, from top left clockwise: An MRI brain scan, automotive night vision with pedestrian recognition, infrared image taken with a smartphone, chemical rock analysis from mars

2.2.1 Usages

Image processing and analysis has been applied to multiple areas with its value and effectiveness rapidly improving alongside camera technology and computing power. These applications range from recognising faces in social media uploads (Zuckerberg, Sittig, & Marlette, 2011) to the utilisation of satellite imagery to tracking the changing shape of coastlines (Potter, 2013).

2.2.1.1 Medical Arguably one of the most important uses of IA, advances in medical imaging have reduced costs in healthcare, diagnosis time, recovery time, and improved the ability to localise and personalise treatments (European Science Foundation, 2007). Major uses of IA in medical applications are the use of Magnetic Reso-

nance Imaging (MRI) and Computerised Topography Scanning (CT Scan) to create detailed images of the human body and identify illness before some symptoms arise.

2.2.1.2 Transport Image analysis has been included in the consumer automotive market on various models since 2004 when Honda introduced an thermographic night vision camera with pedestrian detection on the Legend (Honda Motor Co., 2004). Since this initial introduction many vehicle manufacturers have included image analysis and recognition features as options such as speed limit sign recognition, lane departure warning systems, and automatic braking systems based on hazard recognition.

2.2.1.3 Engineering The use of image analysis in engineering has pushed to create more stable and efficient structures by looking at the materials used in their construction (Masad, Muhunthan, Shashidhar, & Harman, 1999) and monitoring their stresses and potential weak areas (Kim & Kim, 2013). Using image analysis by engineers on site has become more common with the advances in mobile computing and some manufacturers aiming their products at an engineering demographic with features like improved durability and built in infrared imaging (Liszewski, 2016).

2.2.1.4 Space While some industries make use of satellite imagery to monitor changes on our own planet, agencies such as NASA and ESA make use of image analysis to look at planets and other celestial bodies. The Martian rover, Curiosity, uses multiple cameras for navigation, hazard avoidance, and scientific imaging the products of which are streamed back to Earth for analysis. Major uses for the various types of images returned include identification of geological formations and compositions (Blake et al., 2013; Garvin, Malin, & Miniti, 2014) and chemical location and identification using the "ChemCam" (Schröder et al., 2015).

2.2.2 Image Analysis Techniques

2.2.2.1 Edge Detection

2.2.2.2 BLOB Analysis

2.2.2.3 Taking Measurements

3 Approach

4 Results

5 Critical Evaluation

6 Conclusion

References

- Aston, P. (2016). Sussmybike data acquisition - eurobike 2016. Retrieved 24/09/2016, from <http://www.pinkbike.com/news/sussmybike-data-acquisition-eurobike-2016.html>
- Benedict, T. (2012). Fox ird smartphone app sets ups shocks, forks for you. Retrieved 24/09/2016, from <http://www.bikerumor.com/2012/08/29/fox-ird-smartphone-app-sets-ups-shocks-forks-for-you/>
- European Science Foundation. (2007). *Medical imaging for improved patient care* [Policy Briefing]. Retrieved 03/10/2016, from http://www.esf.org/fileadmin/links/EMRC/ESF_POLICY28_V09_HD.pdf
- Giant Manufacturing Co. Ltd. (2012). *frame_maestro.jpg* [Image]. Retrieved 29/09/2016, from https://www.giant-bicycles.com/images/technology/2012/frame_maestro.jpg
- Giant Manufacturing Co. Ltd. (2017). *Giant stance* [Product Listing]. Retrieved from <https://www.giant-bicycles.com/en-gb/bikes/model/stance/28553/99239/>
- Honda Motor Co. (2004). Honda develops world's first intelligent night vision system able to detect pedestrians and provide driver cautions-available on legend model to be released in fall 2004 [Press Release]. Retrieved 03/10/2016, from <http://world.honda.com/news/2004/4040824a-eng.html>
- Image Analysis Group. (2016). *Ramri* [Image].
- IMBA Europe. (2015). *Imba european mountain bike survey* (Survey). International Mountain Bike Association. Retrieved 24/09/2015, from http://www.imba-europe.com/sites/default/files/IMBA_INFOGRAPHIC_final.pdf
- Blake, D. F., Morris, R. V., Kocurek, G., Morrison, S. M., Downs, R. T., Bish, D., ... Sarrazin, P. (2013). Curiosity at gale crater, mars: Characterization and analysis of the rocknest sand shadow. *Science*, 341(6153). Retrieved from <http://science.sciencemag.org/content/341/6153/1239505> doi: 10.1126/science.1239505
- Callaham, J. (2015). Google says there are now 1.4 billion active android devices worldwide. Retrieved 25/09/2016, from <http://www.androidcentral.com/google-says-there-are-now-14-billion-active-android-devices-worldwide>
- Diaz, K. M., Krupka, D. J., Chang, M. J., Peacock, J., Ma, Y., Goldsmith, J., ... Davidson, K. W. (2015). Fitbit®: An accurate and reliable device for wireless physical activity tracking. *International Journal of Cardiology*, 185, 138-140. Retrieved 24/09/2016, from <http://dx.doi.org.ezproxy.napier.ac.uk/10.1016/j.ijcard.2015.03.038>
- Formosa, N. (2012). Social fitness apps storm cycling world. *Bicycle Retailer and Industry News*, 21, 28-29. Retrieved 24/09/2016, from http://search.proquest.com.ezproxy.napier.ac.uk/docview/1018189163?rfr_id=info%3Axri%2Fsid%3Aprimo
- Garvin, J. B., Malin, M. C., & Minitti, M. E. (2014, March 17). *Sedimentology of marine gravels from mardi twilight imaging: Techniques* (Tech. Rep. No. GSFC-E-DAA-TN13878). Retrieved 04/10/2016, from <http://hdl.handle.net/2060/20150001290>
- Harker, J. (2010). German brand rose hopes to bloom in britain. Re-

- trieved 24/09/2016, from <http://www.bikebiz.com/news/read/german-brand-rose-hopes-to-bloom-in-britain/08815>
- Hwang, J. C. B. (2016, 05 19). *Shockwiz* (Trademark Application No. 87042899). 1000 West Fulton Market, 4th Floor, Chicago, Illinois, 60607, USA. Retrieved 25/09/2016, from <https://trademarks.justia.com/870/42/shockwiz-87042899.html>
- Kim, S.-W., & Kim, N.-S. (2013). Dynamic characteristics of suspension bridge hanger cables using digital image processing. *NDT & E International*, 59, 25 - 33. Retrieved from <http://www.sciencedirect.com/science/article/pii/S0963869513000807> doi: <http://dx.doi.org/10.1016/j.ndteint.2013.05.002>
- Liszewski, A. (2016). Caterpillar's new s60 is the first smartphone with flir thermal imaging built right in. Retrieved 04/10/2016, from <http://gizmodo.com/caterpillars-new-s60-is-the-first-smartphone-with-flir-1759685817>
- Masad, E., Muhunthan, B., Shashidhar, N., & Harman, T. (1999). Internal structure characterization of asphalt concrete using image analysis. *Journal of Computing in Civil Engineering*, 13(2), 88-95. Retrieved from [http://dx.doi.org/10.1061/\(ASCE\)0887-3801\(1999\)13:2\(88\)](http://dx.doi.org/10.1061/(ASCE)0887-3801(1999)13:2(88)) doi: 10.1061/(ASCE)0887-3801(1999)13:2(88)
- Potter, C. (2013). Ten years of land cover change on the california coast detected using landsat satellite image analysis: part 1—marin and san francisco counties. *Journal of Coastal Conservation*, 17(4), 697–707. Retrieved from <http://dx.doi.org/10.1007/s11852-013-0255-2> doi: 10.1007/s11852-013-0255-2
- Schröder, S., Meslin, P.-Y., Gasnault, O., Maurice, S., Cousin, A., Wiens, R., ... Vaniman, D. (2015). Hydrogen detection with chemcam at gale crater. *Icarus*, 249, 43 - 61. Retrieved from <http://www.sciencedirect.com/science/article/pii/S001910351400445X> (Special Issue: First Year of MSL) doi: <http://dx.doi.org/10.1016/j.icarus.2014.08.029>
- Staff, B. (2015). Yt industries launches consumer-direct sales in north america, oceania. Retrieved 24/09/2015, from <http://www.bicycleretailer.com/industry-news/2015/01/30/yt-industries-launches-consumer-direct-sales-north-america-oceania>
- Titlestad, J., Fairlie-Clarke, T., Davie, M., Whittaker, A., & Grant, S. (2003). Experimental evaluation of mountain bike suspension systems. *Acta Polytechnica*, 43, 15-20.
- West, L. R. (2015). Strava: challenge yourself to greater heights in physical activity/cycling and running. *British Journal of Sports Medicine*, 49, 1024. Retrieved 24/09/2016, from <http://bjsm.bmjjournals.com.ezproxy.napier.ac.uk/content/49/15/1024.full>
- Zuckerberg, M., Sittig, A., & Marlette, S. (2011, May 17). *Tagging digital media*. Google Patents. Retrieved from [\(US Patent 7,945,653\)](https://www.google.com/patents/US7945653)

Acronyms

FS Full Suspension.

HT Hard Tail.

VPP Virtual Pivot Point.

Glossary

Fork The front suspension unit on a mountain bike.

Full Suspension A mountain bike with both front and rear suspension.

Hard Tail A mountain bike with only front suspension.

Horst Link A suspension system utilising a pivot point located near to and below the rear wheel axle.

IA Image Analysis.

Rebound Damping Controls the speed at which a suspension unit extends once it has been compressed. Less damping means the unit extends faster.

Sag The distance which the suspension sits into its travel when the rider is in their neutral position.

Shock The rear suspension unit. Only found on full suspension mountain bikes.

Single Pivot A suspension system which rotates around a physical main pivot point.

Stroke The distance a shock absorber can compress before bottoming out.

Travel The distance a wheel can move before bottoming out.

Virtual Pivot Point A rear suspension utilising an upper and lower link to create a simulated pivot a physical one would be impossible.