

Ordered fragments of first-order logic

Reijo Jaakkola

University of Helsinki, Tampere University

Funding: Theory of computational logics – Academy of Finland grants 324435
and 328987

The satisfiability problem

- ▶ An important invariant of a logic \mathcal{L} is the complexity of its satisfiability problem, i.e., the problem of determining whether a given sentence of \mathcal{L} is satisfiable (in other words has a model).

The satisfiability problem

- ▶ An important invariant of a logic \mathcal{L} is the complexity of its satisfiability problem, i.e., the problem of determining whether a given sentence of \mathcal{L} is satisfiable (in other words has a model).
- ▶ A classical result of Church and Turing is that the satisfiability problem for full first-order logic FO is undecidable.

The satisfiability problem

- ▶ An important invariant of a logic \mathcal{L} is the complexity of its satisfiability problem, i.e., the problem of determining whether a given sentence of \mathcal{L} is satisfiable (in other words has a model).
- ▶ A classical result of Church and Turing is that the satisfiability problem for full first-order logic FO is undecidable. This result led researches to focus their study on *fragments* of FO (essentially computable sets $\mathcal{L} \subseteq \text{FO}$) with the hope that expressive logics with decidable satisfiability problem could be identified.

The satisfiability problem

- ▶ An important invariant of a logic \mathcal{L} is the complexity of its satisfiability problem, i.e., the problem of determining whether a given sentence of \mathcal{L} is satisfiable (in other words has a model).
- ▶ A classical result of Church and Turing is that the satisfiability problem for full first-order logic FO is undecidable. This result led researches to focus their study on *fragments* of FO (essentially computable sets $\mathcal{L} \subseteq \text{FO}$) with the hope that expressive logics with decidable satisfiability problem could be identified.
- ▶ An important example of an interesting decidable fragment of FO is the two-variable logic FO^2 (every sentence can contain at most two variables).

- ▶ An important invariant of a logic \mathcal{L} is the complexity of its satisfiability problem, i.e., the problem of determining whether a given sentence of \mathcal{L} is satisfiable (in other words has a model).
- ▶ A classical result of Church and Turing is that the satisfiability problem for full first-order logic FO is undecidable. This result led researches to focus their study on *fragments* of FO (essentially computable sets $\mathcal{L} \subseteq \text{FO}$) with the hope that expressive logics with decidable satisfiability problem could be identified.
- ▶ An important example of an interesting decidable fragment of FO is the two-variable logic FO^2 (every sentence can contain at most two variables). This logic is decidable because it has the following *bounded model property*: if $\varphi \in \text{FO}^2$ is satisfiable, then it has a model of size at most $2^{|\varphi|}$.

Ordered fragments

- ▶ Recently there has been an increasing interest in studying fragments that we will refer to as the *ordered fragments* of FO.

- ▶ Recently there has been an increasing interest in studying fragments that we will refer to as the *ordered fragments* of FO. These were originally introduced independently by Quine and Herzig.

- ▶ Recently there has been an increasing interest in studying fragments that we will refer to as the *ordered fragments* of FO. These were originally introduced independently by Quine and Herzog.
- ▶ **Main idea:** Restrict the order in which variables can be quantified, the way variables can be permuted in atomic formulas and the manner in which boolean combinations of formulas can be formed.

- ▶ Recently there has been an increasing interest in studying fragments that we will refer to as the *ordered fragments* of FO. These were originally introduced independently by Quine and Herzog.
- ▶ **Main idea:** Restrict the order in which variables can be quantified, the way variables can be permuted in atomic formulas and the manner in which boolean combinations of formulas can be formed.
- ▶ **This talk:** We will go through the syntax of the two most well-known ordered fragments (ordered logic, fluted logic) and their complexities. In addition, we will take a brief look at some recent results on the complexities of their variants (with respect to the satisfiability problem).

Definition

Let $\bar{v}_\omega = (v_1, v_2, \dots)$ be an infinite sequence of variables and let τ be a vocabulary. For every $k \in \mathbb{N}$ we define sets $OL^k[\tau]$ as follows.

1. Let $R \in \tau$ be an k -ary relational symbol and consider the prefix

$$(v_1, \dots, v_k)$$

of \bar{v}_ω . Now $R(v_1, \dots, v_k) \in OL^k[\tau]$.

2. If $\varphi, \psi \in OL^k[\tau]$, then $\neg\varphi, (\varphi \wedge \psi) \in OL^k[\tau]$.

3. If $\varphi \in OL^{k+1}[\tau]$, then $\exists v_{k+1}\varphi \in OL^k[\tau]$.

Finally we define $OL[\tau] := \bigcup_k OL^k[\tau]$.

Definition

Let $\bar{v}_\omega = (v_1, v_2, \dots)$ be an infinite sequence of variables and let τ be a vocabulary. For every $k \in \mathbb{N}$ we define sets $OL^k[\tau]$ as follows.

1. Let $R \in \tau$ be an k -ary relational symbol and consider the prefix

$$(v_1, \dots, v_k)$$

of \bar{v}_ω . Now $R(v_1, \dots, v_k) \in OL^k[\tau]$.

2. If $\varphi, \psi \in OL^k[\tau]$, then $\neg\varphi, (\varphi \wedge \psi) \in OL^k[\tau]$.

3. If $\varphi \in OL^{k+1}[\tau]$, then $\exists v_{k+1}\varphi \in OL^k[\tau]$.

Finally we define $OL[\tau] := \bigcup_k OL^k[\tau]$.

Example

$\forall v_1 (\neg P(v_1) \wedge \exists v_2 R(v_1, v_2))$ is a sentence of $OL[\{P, R\}]$, while $\exists v_1 \exists v_2 R(v_2, v_1)$, $\exists v_2 \exists v_1 R(v_1, v_2)$ and $\exists v_1 \exists v_2 (P(v_2) \wedge R(v_1, v_2))$ are not.

Complexity of ordered logic

- ▶ One can prove that OL has the following bounded model property: if $\varphi \in \text{OL}$ has a model, then it has one of size at most $|\varphi|$.

Complexity of ordered logic

- ▶ One can prove that OL has the following bounded model property: if $\varphi \in \text{OL}$ has a model, then it has one of size at most $|\varphi|$.
- ▶ **Main idea:** OL can't enforce that there exists more than $|\varphi|$ -many elements with distinct (quantifier-free) unary types.

- ▶ One can prove that OL has the following bounded model property: if $\varphi \in \text{OL}$ has a model, then it has one of size at most $|\varphi|$.
- ▶ **Main idea:** OL can't enforce that there exists more than $|\varphi|$ -many elements with distinct (quantifier-free) unary types.

Theorem (J.)

Over bounded vocabularies the satisfiability problem of OL is NP-complete.

- ▶ One can prove that OL has the following bounded model property: if $\varphi \in \text{OL}$ has a model, then it has one of size at most $|\varphi|$.
- ▶ **Main idea:** OL can't enforce that there exists more than $|\varphi|$ -many elements with distinct (quantifier-free) unary types.

Theorem (J.)

Over bounded vocabularies the satisfiability problem of OL is NP-complete.

Theorem (Herzig, J.)

The satisfiability problem of OL is PSPACE-complete.

Definition

Let $\bar{v}_\omega = (v_1, v_2, \dots)$ be an infinite sequence of variables and let τ be a vocabulary. For every $k \in \mathbb{N}$, we define sets $\text{FL}^k[\tau]$ as follows.

1. Let $R \in \tau$ be an n -ary relation symbol and consider the subsequence

$$(v_{k-n+1}, \dots, v_k)$$

of \bar{v}_ω . Now $R(v_{k-n+1}, \dots, v_k) \in \text{FL}^k[\tau]$.

2. For every $\varphi, \psi \in \text{FL}^k[\tau]$, we have that $\neg\varphi, (\varphi \wedge \psi) \in \text{FL}^k[\tau]$.
3. If $\varphi \in \text{FL}^{k+1}[\tau]$, then $\exists v_{k+1}\varphi \in \text{FL}^k[\tau]$.

Finally, we define $\text{FL}[\tau] := \bigcup_k \text{FL}^k[\tau]$.

Definition

Let $\bar{v}_\omega = (v_1, v_2, \dots)$ be an infinite sequence of variables and let τ be a vocabulary. For every $k \in \mathbb{N}$, we define sets $\text{FL}^k[\tau]$ as follows.

1. Let $R \in \tau$ be an n -ary relation symbol and consider the subsequence

$$(v_{k-n+1}, \dots, v_k)$$

of \bar{v}_ω . Now $R(v_{k-n+1}, \dots, v_k) \in \text{FL}^k[\tau]$.

2. For every $\varphi, \psi \in \text{FL}^k[\tau]$, we have that $\neg\varphi, (\varphi \wedge \psi) \in \text{FL}^k[\tau]$.
3. If $\varphi \in \text{FL}^{k+1}[\tau]$, then $\exists v_{k+1}\varphi \in \text{FL}^k[\tau]$.

Finally, we define $\text{FL}[\tau] := \bigcup_k \text{FL}^k[\tau]$.

Note that $\text{OL} \subseteq \text{FL}$.

Definition

Let $\bar{v}_\omega = (v_1, v_2, \dots)$ be an infinite sequence of variables and let τ be a vocabulary. For every $k \in \mathbb{N}$, we define sets $\text{FL}^k[\tau]$ as follows.

1. Let $R \in \tau$ be an n -ary relation symbol and consider the subsequence

$$(v_{k-n+1}, \dots, v_k)$$

of \bar{v}_ω . Now $R(v_{k-n+1}, \dots, v_k) \in \text{FL}^k[\tau]$.

2. For every $\varphi, \psi \in \text{FL}^k[\tau]$, we have that $\neg\varphi, (\varphi \wedge \psi) \in \text{FL}^k[\tau]$.
3. If $\varphi \in \text{FL}^{k+1}[\tau]$, then $\exists v_{k+1}\varphi \in \text{FL}^k[\tau]$.

Finally, we define $\text{FL}[\tau] := \bigcup_k \text{FL}^k[\tau]$.

Note that $\text{OL} \subseteq \text{FL}$.

Example

$\exists v_1 \exists v_2 (P(v_2) \wedge R(v_1, v_2))$ is a sentence of $\text{FL}[\{P, R\}]$, while $\exists v_1 \exists v_2 \exists v_3 (R(v_1, v_2) \wedge R(v_2, v_3))$ is not.

Complexity of fluted logic

- FL also has a bounded model property: if $\varphi \in \text{FL}$ has a model, then it has one of size at most

$$\underbrace{2^{2^{\dots 2}}}_{|\varphi|^k\text{-times}},$$

for some constant k .

- ▶ FL also has a bounded model property: if $\varphi \in \text{FL}$ has a model, then it has one of size at most

$$\underbrace{2^{2^{\dots 2}}}_{|\varphi|^k\text{-times}},$$

for some constant k .

- ▶ **Main idea of proof:** For each $k \geq 2$ and $\varphi \in \text{FL}^{(k+1)}$, there exists $\varphi' \in \text{FL}^k$ so that φ has a model iff φ' has, $|\varphi'| = 2^{O(|\varphi|)}$ and if φ' has a model of size N , then φ has a model of size at most $|\varphi|N$.

- ▶ FL also has a bounded model property: if $\varphi \in \text{FL}$ has a model, then it has one of size at most

$$\underbrace{2^{2^{\dots^2}}}_{|\varphi|^k\text{-times}},$$

for some constant k .

- ▶ **Main idea of proof:** For each $k \geq 2$ and $\varphi \in \text{FL}^{(k+1)}$, there exists $\varphi' \in \text{FL}^k$ so that φ has a model iff φ' has, $|\varphi'| = 2^{O(|\varphi|)}$ and if φ' has a model of size N , then φ has a model of size at most $|\varphi|N$.

Theorem (Pratt-Hartmann, Swast, Tendera)

The satisfiability problem of FL is TOWER-complete.

Algebraic view on ordered fragments

- ▶ Originally some of the ordered fragments were discovered by Quine as a by-product of his (eventually successful) attempt at giving a variable-free syntax for FO (predicate functor logic(s)).

Algebraic view on ordered fragments

- ▶ Originally some of the ordered fragments were discovered by Quine as a by-product of his (eventually successful) attempt at giving a variable-free syntax for FO (predicate functor logic(s)).
- ▶ OL can be seen as consisting of three (relational) algebraic operators: complement \neg , intersection \cap and projection \exists .

Algebraic view on ordered fragments

- ▶ Originally some of the ordered fragments were discovered by Quine as a by-product of his (eventually successful) attempt at giving a variable-free syntax for FO (predicate functor logic(s)).
- ▶ OL can be seen as consisting of three (relational) algebraic operators: complement \neg , intersection \cap and projection \exists .
- ▶ Similarly, FL consists of \neg, \exists and the so-called suffix intersection $\dot{\cap}$ (allows one to compute intersections of relations that have different arities).

- ▶ Originally some of the ordered fragments were discovered by Quine as a by-product of his (eventually successful) attempt at giving a variable-free syntax for FO (predicate functor logic(s)).
- ▶ OL can be seen as consisting of three (relational) algebraic operators: complement \neg , intersection \cap and projection \exists .
- ▶ Similarly, FL consists of \neg, \exists and the so-called suffix intersection $\dot{\cap}$ (allows one to compute intersections of relations that have different arities).
- ▶ This point of view suggests naturally several syntactical variants of, say, OL and FL (simply add or remove algebraic operators).

Brief summary of recent complexity results

- ▶ Adding (restricted) use of equality either to OL or FL does not affect complexity.

Brief summary of recent complexity results

- ▶ Adding (restricted) use of equality either to OL or FL does not affect complexity.
- ▶ Adding a swap operator (swap the last two elements in every tuple) increases complexity significantly: OL becomes NEXPTIME-complete while FL becomes undecidable.

Brief summary of recent complexity results

- ▶ Adding (restricted) use of equality either to OL or FL does not affect complexity.
- ▶ Adding a swap operator (swap the last two elements in every tuple) increases complexity significantly: OL becomes NEXPTIME-complete while FL becomes undecidable.
- ▶ Replacing \exists with one-dimensional quantification (select at most the first element from every tuple) decreases complexity: OL becomes NP-complete while FL becomes NEXPTIME-complete. One-dimensional FL remains NEXPTIME-complete even in the presence of equality and swap.

- ▶ Ordered fragments present a fresh viewpoint on the question of what makes satisfiability problems decidable (feasible).

- ▶ Ordered fragments present a fresh viewpoint on the question of what makes satisfiability problems decidable (feasible).
- ▶ Looking at intersections of ordered fragments with *guarded fragments* seems to be a very promising research direction (modal logics often have variable-free syntax).

- ▶ Ordered fragments present a fresh viewpoint on the question of what makes satisfiability problems decidable (feasible).
- ▶ Looking at intersections of ordered fragments with *guarded fragments* seems to be a very promising research direction (modal logics often have variable-free syntax).
- ▶ How much can we extend the expressive power of the fluted logic while preserving its decidability?

- ▶ Ordered fragments present a fresh viewpoint on the question of what makes satisfiability problems decidable (feasible).
- ▶ Looking at intersections of ordered fragments with *guarded fragments* seems to be a very promising research direction (modal logics often have variable-free syntax).
- ▶ How much can we extend the expressive power of the fluted logic while preserving its decidability?

Thanks! :-)