

SemanticDistance: Compute Semantic Relatedness between Constituents of Sequential Continuous Text

Jamie Reilly^{1, 2}, Emily B. Myers^{3, 4}, Hannah Mechtenberg⁴, and Jonathan E. Peelle^{5, 6, 7}

1 Department of Communication Sciences and Disorders, Temple University, United States **2** Department of Psychology and Neuroscience, Temple University, United States **3** Department of Speech, Language, and Hearing Sciences, University of Connecticut, United States **4** Department of Psychological Sciences, University of Connecticut, United States **5** Institute for Cognitive and Brain Health, Northeastern University, United States **6** Department of Communication Sciences and Disorders, Northeastern University, United States **7** Department of Psychology, Northeastern University, United States

DOI:

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Submitted:

Published:

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC-BY](#)).

Summary

SemanticDistance computes pairwise distance between units of language (e.g., word-to-word, ngram-to-word, turn-to-turn) in both structured language samples and unstructured word lists. **SemanticDistance** has cleaning and formatting options including stop-word removal and lemmatization. The package computes two complementary cosine distance indices for each pairwise contrast of interest. **SemanticDistance** can also be used to examine clustering properties within unstructured word lists, generating dendrograms and simple igraph network plots.

Statement of need

There are many compelling theoretical and clinical applications for measuring conceptual similarity between words and larger chunks of language (e.g., detection of subtle semantic impairments based on naturalistic language sampling, designing controlled word pair stimuli for language experiments). Although word embeddings such as Word2Vec (Mikolov et al. 2013), LSA (Landauer et al. 1998), and GloVe (Pennington et al. 2014) are widely available, **SemanticDistance** is unique in its capacity to compute rolling measures of semantic distance (e.g., one word to the previous word in continuous text) using qualitatively different sources (e.g., experiential norms vs. embeddings) in addition to executing text cleaning within the package itself. **SemanticDistance** is also capable of producing network visualizations from word lists, offering a potentially useful tool for visualizing structure and relatedness within given sets of words.

State of the field

We know of no software application that computes running measures of semantic distance in continuous unstructured language samples. In addition, **SemanticDistance** computes different but complementary pairwise semantic distance metrics over the same set of

stimuli, allowing researchers to examine semantic flow across continuous stories and narratives.

Software design

SemanticDistance is an open-source R package designed to accommodate a wide range of user expertise (e.g., neuroscience, linguistics, computer science). The software does not leverage artificial intelligence or use any proprietary dependencies. It instead derives mathematical indices of semantic distance between constituents (e.g., words, ngrams) by extracting their respective vectors from two static lookup databases. The first dataset contains GloVE-derived word embeddings for many English words. The second dataset contains experiential semantic norms for sensory, motor, and emotion salience (e.g., color, sound, motor).

Research impact statement

SemanticDistance has supported one peer-reviewed publication to date in the journal, *Cortex* (Mechtenberg et al. 2026) along with one refereed conference presentation at the annual conference of the Society for the Neurobiology of Language. One novel advance of **SemanticDistance** is its capacity to model rolling semantic distance in continuous text by transforming each constituent's distance to the previous word or ngram to a continuous time series.

Description

Semantic distance is an empirical measure of conceptual relatedness between two or more words situated within an n-dimensional space (Reilly et al. 2025). Semantic spaces differ in their dimensionality and biological plausibility. As an R package, **SemanticDistance** bundles text cleaning and formatting options (e.g., stopword removal, lemmatization) with two complementary semantic distance metrics that characterize/quantify similarity between pairs of language constituents (e.g., words, ngrams, turns). **CosDist_Glo** reflects cosine distance between vectors derived from training a GLOVE word embedding model (Pennington et al. 2014). **CosDist_SD15** reflects cosine distances derived from a 15 dimension sensorimotor and affective space derived from explicit human ratings (Reilly et al. 2023).

SemanticDistance computes indices of relatedness between lexical constituents within the following text formats: 1: **monologues**: stories, narratives, and structured text
2: **dialogues**: turn-to-turn within two-person conversation transcripts.
3: **word pairs in columns**: word pairs
4: **unordered lists**: bags-of-words

One of the most innovative functions of **SemanticDistance** is its capacity to generate rolling measures of semantic distance within stories or narratives with chunk sizes (e.g., word-to-word, turn-to-turn). Chunk size is an optional argument for many of the software's functions. For example, if a user specified a chunk or n-gram size of 5 words,

the software would automatically compute a rolling measure of semantic distance between each new word in a language sample relative to the five words that preceded it. One consideration of applying `SemanticDistance` to naturalistic language samples relates to coverage of contemporary English. `SemanticDistance` relies on an internal lookup dataframe populated with semantic vectors for >60k frequent and familiar English words.

Users should exercise caution regarding potential bias from missing observations (NAs) (e.g., proper nouns, low frequency or obscure words), especially in small corpora.

We envision a number of potential use cases for the `SemanticDistance` package as applied to naturalistic discourse. For example, a researcher interested in the effects of Alzheimer’s Disease on semantic cohesion between words could model running measures of distance across entire language transcripts, allowing a glimpse into how cohesion changes over time. Other applications involve dissociations in semantic distance type (i.e., experiential vs. embedding) and ngram kernel size (e.g., rolling distance from larger chunks of words to each new word). Other potential uses include matching stimuli for relatedness in language experiments.

We invite the user community to contribute suggestions for functionality along with code using the package’s bug reporting features and by contacting the maintainers directly.

AI usage disclosure

`SemanticDistance` uses an internal database composed of many words with a fixed set of embeddings. The software does not use AI or rely on proprietary package dependencies. We did use GPT 4.0 (OpenAI) to troubleshoot R coding errors and assist with generating complex regular expressions (regex) used for cleaning text data.

References

- Landauer, T K, P W Foltz, and D Laham. 1998. “An Introduction to Latent Semantic Analysis.” *Discourse Processes* 25 (2-3): 259–84.
- Mechtenberg, H, J Reilly, J E Peelle, and E B. Myers. 2026. “Measuring Brain Sensitivity to Semantic Distance in Spoken Narrative Comprehension.” *Cortex* 195 (February): 28–42. <https://doi.org/10.1016/j.cortex.2025.12.004>.
- Mikolov, Tomas, Ilya Sutskever, Kai Chen, Greg S. Corrado, and Jeff Dean. 2013. “Distributed Representations of Words and Phrases and Their Compositionality.” *Advances in Neural Information Processing Systems*, 3111–19. <http://papers.nips.cc/paper/5021-distributed-representations-of-words-and-phrases-and-their-compositionality>.
- Pennington, J, R Socher, and C D Manning. 2014. “Glove: Global Vectors for Word Representation.” *Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 1532–43. <https://doi.org/10/gfshwg>.
- Reilly, J, A M Finley, C P Litovsky, and Y N Kenett. 2023. “Bigram Semantic Distance as an Index of Continuous Semantic Flow in Natural Language: Theory, Tools, and

Applications.” *Journal of Experimental Psychology: General* 152 (9): 2578–90. <https://doi.org/10.1037/xge0001389>.

Reilly, J, C Shain, V Borghesani, et al. 2025. “What We Mean When We Say Semantic: Toward a Multidisciplinary Semantic Glossary.” *Psychonomic Bulletin & Review* 32 (1): 243–80. <https://doi.org/10.3758/s13423-024-02556-7>.