

# Files, Errors and Warnings of `pythontex` 0.18

Ernst Reissner (rei3ner@arcor.de)

## Contents

<b>List of Figures</b>	<b>1</b>
<b>1 Introduction</b>	<b>1</b>
<b>2 The converter <code>pythontex</code></b>	<b>2</b>
2.1 The Input File <code>xxx.pytxcode</code> . . . . .	2
2.2 The Output Files . . . . .	2
2.3 Errors and Warnings at standard/error output . . . . .	3
2.4 Failure codes . . . . .	3
<b>3 The converter <code>depythontex</code></b>	<b>3</b>
3.1 The Input File <code>xxx.dpytx</code> . . . . .	3
3.2 The Output Files . . . . .	3
3.3 Errors and Warnings at standard/error output . . . . .	3
3.4 Failure codes . . . . .	3

## List of Figures

1 Conversion of a <code>pytxcode</code> -file using <code>pythontex</code> . . . . .	3
2 Conversion of a <code>depytx</code> -file using <code>depythontex</code> . . . . .	3

## 1 Introduction

This document is created with `lualatex` or that like with output format pdf. The package `tex4ht` is not loaded.

The `pythontex` package together with the auxiliary program with the same name `pythontex`, allows including code, e.g. in Python into a  $\text{\LaTeX}$  document. This document describes the input/output behavior of the auxiliary program `pythontex`, version 0.18 which includes all files read and written and uses `pythontex`. For example, `1+1=2` has been computed by python. bla

Interaction of `pythontex` with a  $\text{\LaTeX}$ -to-pdf converter like `lualatex` is comparable to that of other auxiliary programs like `makeindex`: A latex package makes the  $\text{\LaTeX}$ -to-pdf converter extract information for the auxiliary program into a separate file or more. Then the auxiliary program is run which creates further files which the  $\text{\LaTeX}$ -to-pdf converter reads in a second run.

Both, the package `pythontex` and the auxiliary programs `pythontex` and `depythontex`, are described in [?]. Moreover, there is an introduction [?] and a gallery [?]. For background on the intentions of package `pythontex`, consult [?].

The integration of `pythontex` into the latex maven plugin in this project is given in [?], Section 5.5.

Another source of knowledge on `pythontex` is the source code hosted at <https://github.com/gpoore/pythontex>.

At least the following properties are special to package `pythontex`:

- The number of files `pythontex` may create is variable and so by default they are put into a subfolder.
- The output files generated are highly configurable.
- There is more than one auxiliary program tied to the package, besides `pythontex` also `depythontex`.
- The errors and warnings of a `pythontex` run and of a `depythontex` run are not written into a log file.

In [?], Section 5.5 a wrapper for `pythontex` is suggested writing the errors and warnings normally coming at standard output or error output into a log file `xxx.plg`. Nevertheless, currently no log file is written.

The package `pythontex` is highly configurable, more than this software allows. Thus, also in this document we assume that neither `\setpythontexoutputdir` setting the output directory nor `\setpythontexworkingdir` setting the working directory are used, because this software assumes the default that the working directory is the directory containing the L<sup>A</sup>T<sub>E</sub>X main file `xxx.tex` and the output directory is in the working directory and its name is `pythontex-files-xxx`.

## 2 The converter `pythontex`

As already pointed out in the introduction, we restrict ourselves to the default case in which `pythontex` writes output files only in folder `pythontex-files-xxx`.

Under these assumptions, Figure 1 shows the input and output files of `pythontex`.

The input file is described in Section 2.1 in full detail. Section 2.2 is devoted to the output files of `pythontex`. Note that unlike the wrapper `pythontexW`, the original `pythontex` just prints errors and warnings. These are all collected in Section 2.3. Finally, Section 2.4 is on the failure codes.

### 2.1 The Input File `xxx.pytxcode`

### 2.2 The Output Files

Figure 1 shows that the output files of `pythontex` are all in folder `pythontex-files-xxx`. Temporary files in dotted boxes, so these can be seen only if the `pythontex` run is interrupted, e.g. by failure. The other files are called *final*. The Figure also indicates, that the wrapper `pythontexW` writes a log file in addition.

Among the final files, there is `xxx.pytxmcr` which starts something like

```
%Last time of file creation: 1656851667.5282867
```

and contains processed pygments code according to [?], page 107.

Although indicates the time of the last `pythontex` wrote the file, seemingly, `pythontex` does not update if it is unchanged. So it does not indicate the last run.




Figure 1: Conversion of a pytxcode-file using pythontex

### 2.3 Errors and Warnings at standard/error output

### 2.4 Failure codes

## 3 The converter depyhtontex




Figure 2: Conversion of a depytx-file using depyhtontex

### 3.1 The Input File xxx.dpytx

### 3.2 The Output Files

### 3.3 Errors and Warnings at standard/error output

### 3.4 Failure codes