Highlights

Rank or threshold? Why fake-news detectors fail on new corpora

Dewan Fahad Chowdhury, Md. Rejaul Korim Sadi

- Ten audited corpora, seven detectors and a zero-shot LLM, tested across corpora.
- About 70% of the cross-corpus F1 gap is lost ranking; the rest is the threshold.
- EM label-shift correction worsens the threshold because calibration breaks.
- Flagging the source base rate fixes most of the threshold loss without labels.
- Domain-generalisation methods do not beat pooling: corpus and label are entangled.

Rank or threshold? Why fake-news detectors fail on new corpora

Dewan Fahad Chowdhury[a,1,*], Md. Rejaul Korim Sadi[a,1]

[a] *Department of Computer Science and Engineering, Metropolitan University, Sylhet, Bangladesh*

Abstract

Fake-news detectors score near-perfectly on their training corpus and much worse elsewhere. Cross-corpus studies report this with accuracy or F1, which mixes two failures: ranking new items badly, and ranking them well but thresholding them wrongly. We separate the two. Ten public corpora of articles, headlines, claims and tweets in English and Bengali are audited for label direction and near-duplicates; seven detectors, including a partially fine-tuned RoBERTa, are trained on one and tested on all, with repeated seeds, bootstrap intervals and controls. WELFake's documentation contradicts its own label coding; following it inverts every label and turns moderate transfer into an apparent collapse. Mean ROC-AUC falls from 0.914 in-domain to 0.567 across corpora. Of the lost macro-F1, 70% (corpus-bootstrap interval [63%, 79%]) is a ranking deficit and the rest a misplaced operating point. EM prior adaptation, the usual label-shift correction, makes the operating point worse because calibration breaks across corpora, whereas flagging new items at the source base rate recovers 81% of that loss without target labels; we state when this rule is exact and show how it degrades once the base rate shifts. A zero-shot language model ranks unseen corpora better than transferred detectors do on average but loses mostly its operating point, which the same rule repairs. Pooling training corpora is the only representation change that helps; corpus-invariance methods and re-implemented EANN, MDFEND and ENDEF do not, because corpus and label are entangled. Bengali clickbait, by contrast, transfers across publishers. Code, scores and a reporting protocol are released.

Keywords: misinformation detection, fake news, cross-corpus generalisation, dataset audit, label shift, shortcut learning, Bengali

1. Introduction

False stories spread farther and faster than true ones on social platforms (Vosoughi et al., 2018), and public health, elections and trust in institutions pay for that difference (Lazer et al., 2018). Automatic detection is one response. On the standard benchmarks it looks close to solved, with content-based classifiers routinely reporting accuracies above 95% (Shu et al., 2017; Zhou and Zafarani, 2020; Kaliyar et al., 2021).

*Corresponding author.
Email address: dewanfahadc@gmail.com (Dewan Fahad Chowdhury)
[1] These authors contributed equally to this work and share first authorship.




Figure 1: Study design and main results. Numbers are for TF-IDF with logistic regression unless stated; "rate rule" is rate transfer (Section 4.5), and a negative share means the method made macro-F1 worse than the default cut-off.

But a detector is always deployed on data it was not trained on, and a growing body of work shows that these scores do not survive a change of corpus (Pérez-Rosas et al., 2018; Janicka et al., 2019; Suprem and Pu, 2022; Dell'Oglio et al., 2026), partly because some of them reflect dataset artefacts rather than veracity (Asr and Taboada, 2019; Thibault et al., 2025; Verma, 2026).

What is still missing is an account of *why* the gap arises that also tells a practitioner what to do about it. A detector can fail on a new corpus in two ways. It can *order* the new items badly, giving fabricated stories no higher scores than genuine ones. Or it can order them well and still put its decision threshold in the wrong place, because the new corpus has a different base rate or because its scores come out on a different scale. The first failure calls for a better representation. The second only calls for a better operating point, which is far cheaper. Accuracy and F1, the metrics nearly every cross-domain study reports, cannot tell the two apart.

This paper separates them. We assemble ten public corpora in two languages, covering four text units (articles, headlines, claims and tweets) and three constructs (veracity, rumour and clickbait). We audit them for label direction and for duplication within and across corpora, then train seven detectors on each corpus and test them on every other, with repeated seeds, bootstrap confidence intervals and permutation controls. The macro-F1 a detector loses on a new corpus is split into a ranking deficit, which no threshold can recover, and an operating-point loss, which the right threshold would recover. Each part is then attacked with a matching label-free repair. Figure 1 summarises the design and the main numbers. The contributions are as follows.

1. **An audited multi-corpus benchmark.** The documentation of WELFake, one of the two most used article corpora, gives the opposite of the label coding its file uses (0 = fake in the legend, 1 = fake in the data). A copy built from the legend has every label inverted, which leaves in-domain scores intact

but makes transfer look like a below-chance collapse; it did in our own first pipeline. Simple signature probes reveal the error. Near-duplicate detection finds label-conflicting headlines in GossipCop and source tweets shared between PHEME and Twitter15/16 (Section 3).

2. **A decomposition of the transfer gap.** Across 42 directed corpus pairs, 70% of the lost macro-F1 is a ranking deficit (corpus-bootstrap interval [63%, 79%]) and 30% is operating-point loss. Ranking remains the larger part with balanced accuracy, with a cross-fitted oracle and for every trained detector, including a partially fine-tuned transformer. A zero-shot language model shows the reverse pattern: it ranks new corpora better than detectors transferred from other corpora do on average, and most of what it loses is the operating point (Sections 5.2, 5.3 and 5.5).
3. **A label-free operating point, and why the standard one fails.** Expectation–maximisation (EM) prior adaptation, the textbook correction for label shift, enlarges the operating-point loss (−64% recovered), because the source model's calibration breaks on the new corpus. Fixing the *rate* at which items are flagged, at the source base rate, recovers 81%. We state the conditions under which this rule is exact, show that our corpora approximately meet them, and map how it degrades when the base rate moves (Sections 4.5 and 5.4).
4. **Evidence on what the detectors learn.** A gradient-boosting model of 22 surface statistics and a publisher-identity baseline each recover much of the in-domain signal, and 64 examples suffice on the article and tweet corpora. The heaviest cues are outlet signatures and time expressions. On the ranking side, pooling six training corpora raises held-out AUC from 0.567 to 0.660, whereas making the representation invariant to corpus identity lowers it, and re-implementations of three published generalisation methods (EANN, MDFEND and ENDEF) do no better than pooling, because corpus and label are entangled in these benchmarks (Sections 5.6 and 5.7).
5. **A low-resource extension.** Bengali clickbait detection replicates the published baseline, holds up on unseen publishers and partly transfers across languages through translation, which points to a difference between cues that *are* the construct and cues that merely correlate with it (Section 5.8).
6. **A reporting protocol and a full release** of code, seeds, per-cell results and per-item scores (Section 6).

2. Related work

Cross-domain failure of fake-news detectors. Content-based detectors have been known to degrade across domains since the first multi-domain corpora appeared. Models trained on one news domain lose much of their accuracy on another (Pérez-Rosas et al., 2018; Janicka et al., 2019), and fine-tuning on one COVID-19 corpus often hurts performance on related ones (Suprem and Pu, 2022). Bozarth and Budak (2020) showed that which model looks best depends on the dataset, the evaluation type and the metric. Dell'Oglio et al.

(2026) recently benchmarked twelve approaches on ten English corpora and found cross-dataset median F1 close to 0.5 for classical and fine-tuned models, with zero-shot large language models more stable; Hoy and Koulouri (2025) found stylistic and "social-monetisation" features to transfer better than token representations. Calvo and Laureano (2026) attribute the near-ceiling scores on ISOT, WELFake and similar corpora to structural homogeneity and provenance-based separability and find strongly asymmetric transfer between them, and Verhoeven et al. (2026) built a benchmark that tests generalisation along six axes (time, event, topic, publisher, political bias and misinformation type) and showed that standard metrics hide many of the failures. For Urdu, Haroon (2026) found transfer between two corpora to be strongly asymmetric, with one direction collapsing because the model labelled almost every article as fake, a length confound being part of the reason. That collapse is exactly the kind of operating-point failure our decomposition isolates. These studies show *that* detectors fail to transfer, almost always through a single threshold-dependent score such as accuracy or F1. They do not ask whether the loss is one of discrimination or of a mis-set threshold, and that question is the basis of this paper.

Multi-domain and debiased detectors. A separate line of work builds detectors that cope with several domains or with drift by design. EANN trains an event discriminator adversarially so that features carry less event-specific information (Wang et al., 2018); MDFEND mixes domain experts with a domain gate (Nan et al., 2021), and MERMAID merges domain-specific experts for unseen domains (Liguori et al., 2025); and ENDEF removes the contribution of an entity-only model at test time to generalise to future news (Zhu et al., 2022). All of them assume that the domain-specific part of the signal is a nuisance that can be separated from the veracity part. Our repair experiments test that assumption directly on public benchmarks and find that, in these corpora, the two are largely the same thing (Section 5.7).

Shortcuts and dataset artefacts. Shortcut learning, in which a model exploits a cue that predicts the label only in the training distribution, affects deep and shallow models alike (Geirhos et al., 2020; Gururangan et al., 2018; McCoy et al., 2019). For misinformation, Horne and Adali (2017) and Schuster et al. (2020) showed how much of the signal is style rather than veracity, and Asr and Taboada (2019) documented topical imbalance across fake-news corpora. Verma (2026) audited ISOT in depth: subject metadata alone separate the classes perfectly, a newswire tag marks 99.2% of real articles, duplicates contaminate 19.4% of a naive test split, deleting the 1,000 highest-weight unigrams leaves F1 at 0.926, and ISOT-trained models rank LIAR claims at close to chance. Thibault et al. (2025) surveyed 75 misinformation datasets and found keyword–label correlations and temporal leakage in several, including Twitter15/16, ISOT and BanFakeNews. We build on these audits but with a different scope and aim. We audit ten corpora jointly, including duplication across corpora and label direction, and use the audit to explain and repair the transfer gap rather than only to document it.

Rumour benchmarks. Rumour-detection benchmarks have the same problem. On Twitter15/16 and PHEME, event-level spurious correlations inflate scores (Wu and Hooi, 2022), chronological splits lower them (Mu et al., 2023), and simple text baselines rival propagation-based models (Pelrine et al., 2021). We therefore treat the source posts of these corpora as one more text unit and do not re-evaluate propagation models, which these works already cover.

Label shift, quantification and invariant representations. Two families of methods from domain adaptation map onto the two parts of our decomposition. Label-shift adaptation re-estimates the target class prior from unlabelled predictions and adjusts the posteriors (Saerens et al., 2002; Lipton et al., 2018). With calibrated scores, this EM procedure is hard to beat (Alexandari et al., 2020). The quantification literature studies the closely related task of estimating class prevalence in a new sample; adjusted classify-and-count, which corrects the share of predicted positives with the classifier's source error rates, is its standard baseline (Forman, 2008). Both families assume that the class-conditional distribution of inputs, or at least of scores, stays the same between source and target. Representation methods try instead to remove domain information: correlation alignment matches feature covariances (Sun et al., 2016), adversarial training removes domain-predictive directions (Ganin et al., 2016), and iterative nullspace projection deletes linearly decodable attributes (Ravfogel et al., 2020). Domain-adaptation theory bounds target error by source error plus a divergence that a domain classifier can estimate (Ben-David et al., 2010). We know of no misinformation study that measures how much of the cross-corpus gap is a prior or threshold effect and how much a representation effect, or that tests each family on the part it is meant to fix.

Large language models. Zero-shot and few-shot large language models are less exposed to dataset-specific shortcuts because they are not trained on the benchmark (Pelrine et al., 2023; Thibault et al., 2025; Dell'Oglio et al., 2026), and they can advise smaller detectors (Hu et al., 2024). They also change the target: machine-written misinformation can be harder for both people and detectors to spot than human-written misinformation (Chen and Shu, 2024), which makes generalisation beyond the training distribution more pressing. Supervised detectors nonetheless remain the cheapest and most widely deployed option, and our decomposition applies to any detector that outputs a score, a prompted language model included.

Position of this work. Table 1 compares our study with the closest prior audits. What we add is the combination of a two-language, multi-unit transfer matrix; a decomposition that assigns the gap to ranking or to the operating point; label-free repairs aimed at each part, with conditions under which they hold; and audit findings (label inversion, cross-corpus duplication) that change measured transfer.

Table 1: Comparison with the closest prior audits: S&P = Suprem and Pu (2022); T = Thibault et al. (2025); V = Verma (2026); D = Dell'Oglio et al. (2026) (✓ reported, – not reported; units: a = article, h = headline, c = claim, t = tweet).

	S&P	T	V	D	**This work**
Corpora (languages)	9 (en)	75 (survey)	2 (en)	10 (en)	10 (en, bn)
Text units	mixed	mixed	a, c	mixed	a, h, c, t
Full train×test transfer matrix	✓	–	–	✓	✓
Within- and cross-corpus near-duplicate control	–	partial	✓	–	✓
Label-direction verification	–	–	–	–	✓
Threshold-free metrics (AUC, AP)	–	–	✓	–	✓
Ranking vs. operating-point decomposition	–	–	partial	–	✓
Seeds, bootstrap CIs, permutation control	–	–	✓	tests only	✓
Label-free repairs evaluated	reject opt.	–	–	MERMAID	EM, rate, INLP, CORAL, EANN, MDFEND, ENDEF
Low-resource language	–	–	–	–	Bengali

3. Corpora and data audit

3.1. Corpora

We use ten public corpora (Table 2). Seven share the veracity construct and form the main transfer matrix: two article corpora, ISOT (Ahmed et al., 2017, 2018) and WELFake (Verma et al., 2021a); two headline corpora from FakeNewsNet, PolitiFact and GossipCop (Shu et al., 2020), for which the public release contains titles and URLs; the claim corpus LIAR (Wang, 2017), obtained through LIAR-PLUS (Alhindi et al., 2018), binarised as {pants-fire, false} versus {mostly-true, true} with the two middle grades dropped; and the source tweets of Twitter15 and Twitter16 (Ma et al., 2017), using their false and true classes. Three further corpora extend the analysis to other constructs and to Bengali: the source tweets of PHEME rumour/non-rumour threads (Zubiaga et al., 2016, 2017); an English clickbait headline corpus (Chakraborty et al., 2016); and BanglaBait (Mahtab et al., 2023), 15,056 labelled Bengali news articles with machine-translated English titles. Labels differ in what they assert: LIAR rates individual claims, FakeNewsNet and Twitter15/16 rate a story through a fact-check, and ISOT and WELFake label articles largely by the outlet they came from. We keep these distinctions explicit and draw the strongest conclusions from four *same-task pairs* that hold unit and construct fixed: ISOT↔WELFake (articles), PolitiFact↔GossipCop (headlines, politics vs. entertainment), Twitter15↔Twitter16 (tweets, two collection windows), and LIAR↔PolitiFact (claims vs. headlines from the same fact-checker). Every label is mapped to 1 = fake, false, rumour or

Table 2: Corpora after harmonisation and deduplication. "Exact" and "near" count removed duplicates; "conflict" counts items removed because duplicates disagreed on the label; "pos." is the share labelled fake, false, rumour or clickbait. For LIAR and Twitter15/16, "raw" counts the items in the binary view (LIAR: pants-fire/false vs. mostly-true/true; Twitter: false vs. true).

Corpus	Unit	Construct	Lang.	Raw	Exact	Near	Conflict	Final	Pos.
ISOT	article	veracity	en	38,833	0	79	0	38,749	0.46
WELFake	article	veracity	en	24,530	0	815	6	23,708	0.43
PolitiFact	headline	veracity	en	1,056	71	3	6	976	0.43
GossipCop	headline	veracity	en	22,140	1,174	26	380	20,560	0.23
LIAR	claim	veracity	en	8,090	21	11	3	8,055	0.44
Twitter15	tweet	veracity	en	742	55	14	0	673	0.51
Twitter16	tweet	veracity	en	412	51	3	0	358	0.46
PHEME	tweet	rumour	en	5,802	124	98	25	5,555	0.34
ClickbaitEN	headline	clickbait	en	32,000	2	123	0	31,875	0.50
BanglaBait	headline	clickbait	bn	15,056	850	124	41	14,041	0.34

clickbait.

Provenance of the article files. For the two article corpora we start from cleaned working copies made at an earlier stage of this project, and we reconstructed both from the original releases to document exactly how they were made (the script is in the repository). The ISOT release has 44,898 articles in two files, one per class. Our copy keeps 38,833 of them, all with their release labels: it lacks 5,795 exact title-and-text duplicates and 270 further articles, 267 of which repeat the title of an article that was kept. The 447 articles with an empty body keep their headline and are scored on it. The WELFake release (Zenodo, MD5 `73c9675a4b3d09f86a6933d0b8d7d908`) has 72,134 articles merged from four earlier collections, one of them a Reuters-based news set like ISOT's real class (Verma et al., 2021a,b). Our copy keeps 24,530. Removing 8,458 exact duplicates, the 38,656 articles whose text also appears in the ISOT release and 480 more whose title does reproduces it up to 10 articles, and no article of our copy lies outside this reconstruction. The overlap step matters: without it, about three in five deduplicated WELFake articles would be ISOT articles, and ISOT↔WELFake transfer would be inflated. After it, only 18 near-duplicates of ISOT remain, and those are excluded from every test (Section 3.2). The repository includes loaders for both releases, so the whole pipeline, including this cleaning, can be rerun from the public files.

3.2. Audit

Label direction. Corpora disagree on which value denotes "fake", and nothing in a CSV file says which convention it follows. We therefore verify label direction with *signature probes*: strings that only a reliable




Figure 2: Data audit. (a) Label-direction probes: share of the items carrying an outlet signature that sit under raw label 0 or 1 (signatures found in at least 100 items). A reliable-outlet signature should sit under "real" and a fake-site signature under "fake". ISOT and the WELFake release both code 1 = fake, although the WELFake record documents 0 = fake; our working copy of WELFake, made by following that legend, has every label inverted. (b) Share of items removed by deduplication: exact copies, near copies (MinHash, Jaccard ≥ 0.8) and items whose duplicates carried both labels.

or only a fabricating outlet produces. Figure 2a shows the result for the two article corpora. In ISOT, 20,761 of the 20,768 "(Reuters)" datelines carry label 0 and all 6,098 texts with the fake-site template "Featured image via" carry label 1, so 1 = fake. WELFake is more treacherous, because its documentation and its file disagree. The release record gives the legend 0 = fake, 1 = real (Verma et al., 2021b), but the file uses the opposite coding: all 6,223 titles ending in "- The New York Times" carry label 0, all 6,261 texts with "Featured image via" carry label 1, and 21,270 of the 21,289 "(Reuters)" datelines carry label 0. The class sizes say the same. Label 1 holds 37,106 articles and label 0 35,028, which are the numbers of fake and real articles stated in the same record. Our working copy was made by following the legend: every label is the inverse of the release label, and a class-name column calls the inverted label 1 "fake". Our first pipeline trusted that column. Read that way, every ISOT↔WELFake score is inverted and ISOT→WELFake looks like a below-chance collapse, while in-domain accuracy and macro-F1 are unaffected, which is why the error is easy to miss. The probes exposed it, and the loader now reverses the labels of the copy (or reads the release with the coding its file actually uses). A ranking metric below 0.5 on a same-task pair should be treated as a symptom to investigate before it is reported as a finding.

Duplicates. Within each corpus we removed exact duplicates of the normalised text and then near-duplicates found by MinHash locality-sensitive hashing (Broder, 1997) (128 permutations, Jaccard ≥ 0.8; word 3-grams

for articles, character 5-grams otherwise). Groups whose members disagree on the label were dropped entirely. Table 2 and Figure 2b report the counts. Two corpora stand out. GossipCop contains 1,174 redundant exact copies of headlines, and a further 356 rows whose headline appears under *both* labels; BanglaBait contains 850 redundant exact copies of titles and, after deduplication, 14,041 items. Even the cleaned WELFake copy still contained 815 near-duplicates.

Cross-corpus overlap. Near-duplicates across corpora inflate transfer. ISOT and WELFake share only 18 near-duplicate articles, so the removal of shared articles from the WELFake copy worked. PHEME, however, shares 58 source tweets with Twitter15 and 128 with Twitter16, because the corpora were collected around overlapping breaking-news events; Twitter15 and Twitter16 share 169 tweet identifiers, all labelled *unverified*. Every transfer test excludes target items that are near-duplicates of the source corpus.

4. Methodology

4.1. Evaluation protocol

For every corpus and every seed $s \in \{0, \ldots, 4\}$ we draw a stratified 70/10/20 train/validation/test split. The seed also fixes model initialisation and any subsampling. Training splits are capped at 8,000 items, validation at 1,500 and test at 3,000 (stratified) so that the largest corpora do not dominate run time, and every cap is applied in the same way to every model. Featurisers (vocabularies, IDF weights, SVD bases) are fitted on the source training split only. Hyperparameters (the inverse regularisation strength $C \in \{0.25, 1, 4\}$, the number of boosting rounds, or the fine-tuning epoch) are selected on the source validation split by ROC-AUC. The selected model's scores are then Platt-calibrated (Platt, 1999) on the same validation split, which makes the default operating point $t = 0.5$ the Bayes decision under the source prior. No hyperparameter, threshold or calibration step sees a target label. When a model trained on corpus A is tested on corpus B, test items of B that are near-duplicates of any item of A (Section 3.2) are removed.

Three training regimes are run for every model except the fine-tuned transformer. *Full* uses the capped training split. *Matched* subsamples every source to $n = 250$ training items (248 for Twitter16), which removes the size difference between Twitter16 (250 training items) and the article corpora (8,000). *Permuted* shuffles the source training and validation labels; it is a sanity control, and its transfer and in-domain AUC should both be close to 0.5.

4.2. Models

We use seven detectors that span sparse, dense and pretrained representations. Six have a linear or tree-based decision layer, which keeps their behaviour interpretable and their training reproducible on a CPU; the seventh is a fine-tuned transformer: (i) TF-IDF word 1–2-grams with logistic regression (TFIDF-LR), the primary instrument; (ii) the same features with a linear SVM (TFIDF-SVM); (iii) NB-SVM, logistic

regression on naive-Bayes-weighted binary n-grams (Wang and Manning, 2012); (iv) averaged GloVe 100-d embeddings (Pennington et al., 2014) with logistic regression (GLOVE-LR); (v) a style model, gradient boosting on 22 surface statistics (length, punctuation and casing rates, digit and stop-word ratios, pronoun rates, weekday mentions, "said" rate, dateline, URL, handle and hashtag rates; STYLE-GB), which sees no vocabulary beyond counts of stop words, pronouns, weekday names and "said", and therefore measures how far a corpus is separable by surface form; (vi) RoBERTa-base (Liu et al., 2019) mean-pooled last-layer representations with logistic regression (ROBERTA-LR), computed on a stratified subset of at most 1,500 items per corpus (first 600 characters); (vii) RoBERTa-base fine-tuned for the task (ROBERTA-FT). Full fine-tuning was out of reach on our hardware, so the embeddings and the lower eight of the twelve layers are frozen, their outputs are computed once per text and cached, and the upper four layers are trained together with a mean-pooling linear head (AdamW, learning rates 3×10^{-5} for the layers and 10^{-3} for the head, batch 16, three epochs with the epoch chosen on validation AUC, class-weighted loss, at most 128 word pieces for articles and 64 otherwise). It is trained on 800 items per source, validated on 200 and tested on 300 per target, all stratified subsets of the regular splits, for seeds 0–2. For both transformer models, TFIDF-LR is refitted on exactly the same items and characters for a paired comparison. As a reference that sees no training corpus at all, we also prompt an instruction-tuned language model, Qwen3-0.6B (Qwen Team et al., 2025) (4-bit Q4_K_M weights, reasoning mode off), with "Is the following {news article / news headline / claim / tweet} real or fake? Answer with one word: real or fake." followed by the first 600 characters of the item. Its score is the difference between the log-probabilities of the next token being "fake" or "real" (case variants pooled), and its own answer corresponds to a cut-off of zero on that score. It is applied to the same 300 test items per corpus and seed as the fine-tuned model. The linear models use scikit-learn (Pedregosa et al., 2011); RoBERTa weights are those packaged in spaCy's `en_core_web_trf` 3.8.0 (Honnibal et al., 2020), fine-tuned with PyTorch.

4.3. Metrics

For every (model, regime, source, target, seed) cell we report threshold-free ranking metrics (ROC-AUC, average precision), threshold-dependent metrics at the default operating point (macro-F1, per-class F1, balanced accuracy, Matthews correlation, predicted-positive rate), calibration (expected calibration error, 15 bins), and macro-F1 at four further operating points described next. Two reference levels help when reading macro-F1: random guessing gives about 0.5, and predicting a single class gives about 0.33. For a single cell, uncertainty is reported as mean $\pm$ standard deviation over seeds and as a pooled seed-bootstrap 95% confidence interval (200 resamples of the target test set per seed, pooled over seeds), which captures both split and test-sampling variability. Quantities averaged over the matrix (the ranking share, the recovery rates) depend more on which corpora were collected than on test sampling, and the 42 cells are not independent, since every corpus appears in twelve of them. For these we resample the seven *corpora*

with replacement (2,000 draws), keep every directed pair of distinct drawn corpora with its multiplicity, and report the 2.5th and 97.5th percentiles. Paired model comparisons use McNemar's test (McNemar, 1947) per cell and seed; repair comparisons use Wilcoxon signed-rank tests over (target, seed) pairs; families of tests are Holm-corrected (Holm, 1979).

4.4. Transfer gap decomposition

Let $F_{AB}(\tau)$ be the macro-F1 on target B of a model trained on source A, at operating point τ. We consider three operating points on the target scores: the default threshold $\tau_0 = 0.5$; the prior-matched threshold τ_π, which makes the predicted-positive rate equal to the true target prior; and the oracle threshold $\tau^\star = \arg\max_\tau F_{AB}(\tau)$, an upper bound that any thresholding rule could at best reach given the model's ranking of target items. The loss a user experiences when deploying the source model on B, relative to what an in-domain model of B achieves, then decomposes exactly:

$$\underbrace{F_{BB}(\tau_0) - F_{AB}(\tau_0)}_{\text{transfer gap}} = \underbrace{\big[F_{BB}(\tau_0) - F_{AB}(\tau^\star)\big]}_{\text{ranking deficit}} + \underbrace{\big[F_{AB}(\tau^\star) - F_{AB}(\tau_\pi)\big]}_{\text{threshold residual}} + \underbrace{\big[F_{AB}(\tau_\pi) - F_{AB}(\tau_0)\big]}_{\text{prior / calibration loss}}. \tag{1}$$

Figure 3 illustrates the two kinds of loss and shows the measured split for the main detector. No choice of threshold can recover the first term. It measures how much worse the source model *orders* target items than the target's own model does. The last two terms are *operating-point* losses and would vanish with the right threshold. Adding $F_{AA}(\tau_0) - F_{BB}(\tau_0)$ gives the gap relative to the source's own in-domain score, which is what a benchmark user is promised; this difficulty term averages to zero over a full matrix and is reported per cell only.

Two details of Eq. (1) could bias the split, and we check both. First, the ranking term compares the transfer oracle with the in-domain model at its *default* threshold, so it also contains the in-domain threshold slack $F_{BB}(\tau^\star_{BB}) - F_{BB}(\tau_0)$. Second, $\tau^\star$ is chosen on the same items it is scored on, which flatters $F_{AB}(\tau^\star)$ on small test sets and so inflates the operating-point share. We report the slack, and we recompute the decomposition with a *cross-fitted* oracle, whose threshold is tuned on a random half of the target test set and scored on the other half (five repeats, both halves). We also repeat the decomposition with balanced accuracy, which, unlike macro-F1, does not depend on the class prior.

4.5. Label-free operating points

We compare four ways of choosing a threshold without target labels. (a) *EM prior adaptation* (Saerens et al., 2002) re-estimates the target prior from the source-calibrated posteriors by expectation–maximisation, adjusts the posteriors and thresholds them at 0.5. With Platt-calibrated scores this is the bias-corrected recipe recommended by Alexandari et al. (2020), and it is optimal under pure label shift. (b) *Rate transfer* sets the threshold so that the share of target items flagged equals the source base rate π_A. It transfers the model's ranking-based decision rule rather than its score scale. We also report the variant that flags the




Figure 3: Two ways a detector can fail on a new corpus. (a) A ranking deficit: real and fake items receive overlapping scores, so no cut-off separates them. (b) An operating-point loss: the scores separate the classes, but the cut-off learned on the training corpus (0.5) flags almost every item; a cut-off chosen by rate recovers most of the loss. Panels a and b use illustrative simulated scores. (c) The measured decomposition of Eq. (1) for TF-IDF with logistic regression, averaged over the 42 transfer cells and five seeds.

share q_A the source model flags on its own held-out test split. (c) *Adjusted classify-and-count* (Forman, 2008) estimates the target prior as $\hat{\pi}_B = (\hat{r}_B - \mathrm{FPR}_A)/(\mathrm{TPR}_A - \mathrm{FPR}_A)$, where $\hat{r}_B$ is the share of target items above 0.5 and the error rates come from the source test split, and then flags the top $\hat{\pi}_B$ of target items. (d) A *two-component Gaussian mixture* on the target logits places the threshold where the components' posteriors cross. As references, we report the share 0.5, which needs no information at all, and the true target prior π_B, which needs one number about the target but no item labels.

Rate transfer is a quantile threshold, and quantile thresholds are an old idea in quantification (Forman, 2008). We do not claim the rule as new. What matters here is *when* it should beat EM, and that can be stated exactly. Let F_y^A and F_y^B be the distributions of the source model's scores for class y on source and target.

Proposition 1. *Suppose (i) there is a strictly increasing map g with $F_y^B(g(u)) = F_y^A(u)$ for both classes and all u, and (ii) $\pi_B = \pi_A$. Then flagging the top q_A share of target items reproduces on B the true- and false-positive rates that the threshold τ_0 has on A, whereas the fixed threshold τ_0 does so only if $g(\tau_0) = \tau_0$. If instead g is the identity and $\pi_B \neq \pi_A$ (pure label shift), EM prior adaptation with calibrated scores is*

consistent and rate transfer is not.

The proof is in Appendix A. The two rules thus suit two different kinds of shift. EM assumes the score distributions within each class stay fixed while the class balance changes. Rate transfer assumes the reverse: the class balance stays roughly fixed while the scores are distorted by an order-preserving map. When the distortion is not order-preserving, part of the loss becomes a ranking deficit that no threshold can recover, which is the first term of Eq. (1). Section 5.4 checks which assumption our corpora come closer to, and a controlled experiment maps what happens when (ii) fails: each target test set is resampled (1,000 items, three draws) to a base rate of $\pi_A + \delta$ for $\delta \in \{-0.3, \ldots, 0.3\}$, clipped to $[0.05, 0.95]$, and every operating point is recomputed.

4.6. Mechanism probes

To identify what signal carries in-domain performance, we use eight probes, each run with TFIDF-LR unless stated: *surface statistics only* (STYLE-GB above); *group-only*, out-of-fold smoothed target encoding of group identity (publisher domain for PolitiFact, GossipCop and BanglaBait; speaker for LIAR; event for PHEME), i.e. how well the label is predicted by *who* published an item; *learning curves* from 32 training items to the full split; *top-K deletion*, removing the $K \in \{10, \ldots, 3000\}$ highest-$|w|$ features and retraining (cf. Verma, 2026); *masking* of source tags and datelines, of time expressions and numbers, of named entities (spaCy `en_core_web_sm`), or of all three; *topic-balanced training*, where classes are subsampled to equal size inside each of 50 k-means topic clusters, removing topic–label correlation from the training set; *corpus separability*, the proxy $\mathcal{A}$-distance $2(1-2\epsilon)$ between two corpora, with ϵ the cross-validated error of a classifier that tells them apart from text alone (Ben-David et al., 2010); and *feature attribution*, the largest-weight n-grams per class and their linear-SHAP magnitudes $|w_j|\,\mathbb{E}|x_j - \bar{x}_j|$. For the more expensive probes (top-K, masking, vocabulary ablation) training is capped at 4,000 and test at 1,500 items; masking and vocabulary ablation use three seeds.

4.7. Representation repairs

The ranking deficit can only be reduced by a better representation. We test repairs in a leave-one-corpus-out (LOCO) setting: for each held-out veracity corpus, the model is trained on the union of the other six (each capped at 1,500 training and 300 validation items) and evaluated on the held-out test split, with near-duplicates of any training corpus removed. Methods are: *pooled* training; pooled training with sample weights that equalise every (corpus, class) cell (*balanced*); balanced training on texts with source tags, datelines, URLs, handles and time expressions *masked*; balanced training after deleting the 2,000 features most predictive of *corpus identity* (from a one-vs-rest corpus classifier); and three dense variants on a 300-d SVD of the TF-IDF space: the SVD baseline, *INLP* (Ravfogel et al., 2020), which projects out 15 iterations

of linear corpus-identity directions, and *CORAL* (Sun et al., 2016), which aligns source feature covariance to the (unlabelled) target. None uses target labels; CORAL alone uses unlabelled target text.

We also re-implement three published generalisation methods for fake-news detection on one shared backbone, the frozen RoBERTa vectors of the 1,500-item subsets, in the same leave-one-corpus-out design (three seeds): EANN-style adversarial training, in which a corpus discriminator behind a gradient-reversal layer removes corpus information from a two-layer encoder (Wang et al., 2018; Ganin et al., 2016); an MDFEND-style mixture of five expert networks combined by a learned gate (Nan et al., 2021), fed the text vector because the domain of a new corpus is unknown; and ENDEF-style entity debiasing, in which an entity-only model over the named entities found by spaCy is trained jointly with the main model and dropped at test time (Zhu et al., 2022). Pooled logistic regression and a pooled two-layer network on the same vectors are the references. All networks are trained with AdamW and early stopping on pooled validation AUC.

5. Results

5.1. The size of the gap

Figure 4 shows the seven-corpus veracity matrix. With TFIDF-LR, mean in-domain ROC-AUC is 0.914, mean off-diagonal AUC is 0.567, and on the eight same-task cells it is 0.624. The sanity controls behave as they should. With permuted labels, transfer AUC is 0.502 ($\pm$0.067 across cells and seeds) and in-domain AUC 0.514. With every source cut to 250 training items the gap remains (in-domain 0.861, off-diagonal 0.556), so it does not come from the very different corpus sizes.

The gap is real, but it is not a collapse to chance. On the cleanest pair, ISOT$\rightarrow$WELFake, AUC is 0.69 [0.66, 0.71], and in the reverse direction 0.85 [0.82, 0.87] (Figure 5a). Two pairs carry almost no transferable ranking: PolitiFact$\rightarrow$LIAR (0.50 [0.47, 0.54]) and LIAR$\rightarrow$PolitiFact (0.51 [0.42, 0.60]). Both are labelled by the same fact-checker, but one rates claims and the other news stories. In 8 of the 42 off-diagonal cells (19%) the mean AUC is below 0.5, meaning that the cue a source teaches points the wrong way on that target.

Threshold-dependent metrics look much worse than AUC. Off-diagonal macro-F1 at the default threshold averages 0.439, not far above the one-class level of 0.33, against 0.854 in-domain. The predicted-positive rates show why (exact values in the Supplementary Material). An ISOT model flags 0.78 of WELFake as fake although the fake rate is 0.43, and a GossipCop model flags only 0.07 of PolitiFact although its fake rate is 0.43. Scores that were well calibrated in-domain are badly calibrated on the target.

5.2. Where the gap goes

Applying Eq. (1) cell by cell (Figures 6 and 7) splits the loss into a part that no threshold can recover and a part that the right threshold would. For TFIDF-LR on the same-task pairs, the mean transfer gap is 0.31




Figure 4: Transfer ROC-AUC of TFIDF-LR (mean of five seeds). Rows are training corpora, columns test corpora; the diagonal is in-domain. Blue is above chance, red below; the midpoint is 0.5.

macro-F1 points, of which 0.24 (79%) is a ranking deficit and the rest an operating-point loss. On the other cells the gap is 0.44, and 68% of it is ranking. Over all cells, 70% of the loss is ranking (corpus-bootstrap 95% interval [63%, 79%]) and 30% is operating point. Most of the gap is ranking, then, and part of it is threshold. Both parts matter. The operating-point share is large enough to change which of two detectors looks better, and it is the cheaper one to fix.

5.3. How robust is the split?

The split survives every check we ran. Dropping any one corpus from the matrix leaves the ranking share between 67% and 72%. The in-domain threshold slack that the ranking term absorbs is small, 0.014 macro-F1 on average (at most 0.037). The in-sample oracle is optimistic, as expected: a threshold tuned on one half of the target and scored on the other reaches 0.537, which is 0.028 below the in-sample oracle on average and 0.056 below it on the targets with fewer than 250 test items. With the cross-fitted oracle the ranking share rises to 76%, so if anything Eq. (1) overstates the operating-point part. With balanced accuracy in place of macro-F1, the ranking share is 84%. Across detectors the ranking share varies more (Figure 7): it is lowest for the style model on the non-paired cells and for the fine-tuned transformer (59% overall; Section 5.5), but ranking is the larger part for every trained detector.




Figure 5: The eight same-task pairs (TFIDF-LR, five seeds). (a) ROC-AUC of the source model on its own test set and on the target, with pooled seed-bootstrap 95% intervals. (b) Target macro-F1 at the default cut-off, at the cut-off whose flag rate equals the true target base rate, and at the best possible cut-off. The dotted line marks the one-class level (0.33) and the dashed line chance (0.5).

5.4. Repairing the operating point without labels

Figure 8 compares operating points for every detector, and the Supplementary Material shows them cell by cell. EM prior adaptation, the textbook remedy, *lowers* off-diagonal macro-F1 from 0.439 to 0.358. It recovers −64% of the operating-point loss (interval [−154%, −27%]), and it does so for every detector (−87% to −41%). Rate transfer, which flags the same share of target items as the source base rate, raises macro-F1 to 0.541 and recovers 81% ([56%, 91%]), close to the 86% reached when the true target base rate is known (0.547). It recovers between 66% and 81% across the seven detectors, and it is at least as good as the cross-fitted oracle, that is, as a threshold tuned on half of the labelled target set (recovery 104% against that oracle). Flagging the share q_A that the source model flags in-domain recovers 76%, and the mixture model 57%. Rate transfer is worse than the default threshold in 10% of the cell-seed combinations.

Two observations keep these numbers in proportion. First, flagging exactly half of the items recovers 80%, almost as much as rate transfer. The source base rates of our corpora lie between 0.23 and 0.51, so in this benchmark most of the gain comes from switching from a score threshold to *any* sensible rate threshold, and only a small part from knowing the source rate. Second, the source base rate is a good guess of the target base rate here (mean absolute error 0.09), which is condition (ii) of Proposition 1.

Why does EM fail? The answer is in the calibration. EM is optimal when only $p(y)$ changes and calibrated posteriors stay meaningful. Here calibration does not survive the move: expected calibration error is 0.046 in-domain but 0.328 on the target. EM's prior estimates therefore drift towards 0 or 1 (mean absolute error 0.46), far worse than simply assuming the source prior (0.09). Adjusted classify-and-count




Figure 6: Transfer gap decomposition for TFIDF-LR (macro-F1 points relative to the source's in-domain score, mean of five seeds). Grey: target harder or easier than source; blue: ranking deficit; green and orange: operating-point losses. Diamonds mark the total; red ticks show what EM prior adaptation recovers (negative values make things worse).

fails for the same reason, because the source error rates it inverts do not hold on the target either (prior error 0.41, recovery −27%). The shift is in $p(x \mid y)$, that is, in style, topic and source, much more than in $p(y)$. That is the regime in which Proposition 1 favours transferring the rate over transferring the scores.

When the base rate moves. Condition (ii) will not always hold, so we resampled every target to base rates between 0.3 below and 0.3 above the source rate (Figure 9). Rate transfer degrades as the shift grows: it recovers 81% of the operating-point loss with no shift, 58% at −0.3 and 22% at +0.3, where its macro-F1 (0.491) falls well below that of a threshold set at the true rate (0.541). It still beats the default threshold at every shift we tried, by 0.02 to 0.11 macro-F1. The two label-free prior estimators do not help: EM and adjusted classify-and-count stay below the default threshold at every shift, because both rely on score distributions that do not transfer. In practice, then, rate transfer is a safe default, but when the base rate of the new feed is expected to differ from the training data, an estimate of that rate from a small labelled sample is worth more than any label-free correction we tested.

5.5. The gap across models

The picture does not depend on the detector (Figure 10; full matrices for every model are in the Supplementary Material). The four content models reach in-domain AUC between 0.864 and 0.914 and off-diagonal




Figure 7: Share of the lost macro-F1 that is a ranking deficit, a threshold residual and a prior or calibration loss, for every detector (sums over the 42 cells and all seeds). † 1,500-item subsets; ‡ 800 training and 300 test items per corpus, three seeds; § zero-shot, decomposed against the in-domain TF-IDF model on the same test items.

AUC between 0.547 and 0.567, and all of them split their loss between ranking and operating point in about the same way (Figure 7). Averaged word embeddings (GLOVE-LR) are weaker in-domain (0.864) and transfer no better (0.564).

The style model is the most revealing. With only 22 surface statistics it reaches an average in-domain AUC of 0.745 (0.999 on ISOT, 0.951 on WELFake), and its transfer AUC (0.535) is only a few points below that of the lexical models. A large part of what these benchmarks reward is form: length, casing, punctuation and attribution habits (Section 5.6).

Pretrained encoders do not change the conclusion. On identical 1,500-item subsets, frozen RoBERTa features give in-domain AUC 0.861 and off-diagonal AUC 0.544, against 0.895 and 0.549 for TFIDF-LR refitted on the same splits. The paired off-diagonal difference is -0.005 AUC (Wilcoxon $p = 0.44$), and RoBERTa is better in 17 of the 42 cells. Fine-tuning the upper four layers does not change this either. On the same 800 training and 300 test items per corpus (3 seeds), ROBERTA-FT reaches in-domain AUC 0.867 and off-diagonal AUC 0.559, against 0.892 and 0.558 for the paired TFIDF-LR; the off-diagonal difference is $+0.001$ (Wilcoxon $p = 0.98$, better in 23 of 42 cells). Its gap is again mostly ranking (59%), EM again makes the operating point worse (-51% recovered), and rate transfer again recovers most of it (77%). With only four layers trained on 800 items, the fine-tuned model is slightly weaker than TFIDF-LR in-domain (-0.025 AUC), so this is not the strongest transformer one could build; but its transfer matches that of the lexical model, and the shape of its gap is the same. This agrees with Verma (2026) and Dell'Oglio et al. (2026), who found that fully fine-tuned transformers gain in-domain but not, or not reliably, across corpora. Pairwise McNemar tests on the same target items (Holm-corrected over all comparisons) find significant differences




Figure 8: Share of the operating-point loss (best-cut-off macro-F1 minus default-cut-off macro-F1, off-diagonal cells) recovered by each label-free rule, per detector. 0% is the default cut-off and 100% the best cut-off chosen with target labels; points in the shaded area are worse than doing nothing. Markers are offset vertically for legibility.

from TFIDF-LR in the following share of (cell, seed) comparisons: GLOVE-LR 36%, NB-SVM 21%, ROBERTA-LR 17%, STYLE-GB 47%, TFIDF-SVM 12%.

A zero-shot language model. A model that was never trained on any of these corpora cannot have learned their collection signatures, so it is a natural check on whether the gap is specific to supervised training. We prompted Qwen3-0.6B (Qwen Team et al., 2025), an instruction-tuned model small enough for our hardware, to answer whether each test item is real or fake, and used the log-odds of the answer "fake" against "real" as its score (Section 4.2). On the same 300 test items per corpus used for the fine-tuned model, its ROC-AUC is 0.657 on average (0.574 to 0.730 across corpora). That is +0.099 higher than the average detector transferred from another corpus (Wilcoxon $p = 9.5e-7$ over corpus–seed pairs), and higher on all 7 corpora, though far below a detector trained on the target itself (0.892). Its operating point, by contrast, is useless: the model answers "fake" for 0% of the items, so its macro-F1 is 0.364, the one-class level (Figure 11b). Flagging half of the items instead raises it to 0.610, which recovers 90% of the operating-point loss, close to the best possible cut-off (0.638). Measured against the in-domain detector on the same items, only 41% of the zero-shot model's loss is ranking (Figure 7). The two families therefore fail in opposite proportions. Trained detectors mostly lose ranking, and a zero-shot model mostly loses its operating point, which is the cheap part to repair. The model's pretraining data may include some of these public benchmarks, so its ranking ability is an upper estimate for genuinely new content, and a 0.6-billion-parameter model is far from the strongest available; we report it to show that the decomposition and the rate-based repair apply unchanged to a prompted model.




Figure 9: Off-diagonal macro-F1 of TFIDF-LR when every target test set is resampled to the source base rate plus a shift (42 cells, five seeds, three draws of 1,000 items). Rate transfer is best when the base rate is unchanged and degrades as it moves; the label-free prior estimators (EM, adjusted classify-and-count) stay below the default threshold throughout.

5.6. What the detectors learn

Cheap signals go a long way. Figure 12 shows four shortcut indicators per corpus. The surface-statistics model recovers on average 57% of the above-chance in-domain AUC of the full lexical model, and on the article corpora almost all of it (ISOT 0.999, WELFake 0.951). Sixty-four training examples are enough for an in-domain AUC of 0.983 on ISOT and 0.894 on WELFake; the claim and celebrity-headline corpora, whose in-domain scores are lower to begin with, learn much more slowly (LIAR 0.567, GossipCop 0.610). On the headline and claim corpora, publisher or speaker identity alone predicts the label with AUC 0.840 (PolitiFact), 0.807 (GossipCop) and 0.664 (LIAR). When a label can be predicted from form, from a few dozen examples or from who published an item, a high in-domain score says little about veracity.

The strongest cues are collection signatures. Figure 13 shows the highest-weight n-grams. In ISOT, the real class is signalled by Reuters wire conventions (“reuters”, “said”, “washington reuters”, weekday attributions such as “on thursday”) and the fake class by the template of the sites it was collected from (“featured image”, “image via”, “read more”, “video”). In WELFake, the real class is signalled by publisher suffixes inherited from one of its source collections (“breitbart”, “york times”, “mr”) and the fake class by the window in which fake items were gathered (“2016”, “october”, “november”, “hillary”). Each corpus teaches its own proxy, which is why the sign of a cue can flip from one corpus to the next (Section 5.1).




Figure 10: In-domain and transfer ROC-AUC per detector (means over cells; five seeds unless marked). † frozen RoBERTa features on 1,500-item subsets; ‡ RoBERTa with the upper four layers fine-tuned, 800 training and 300 test items per corpus, three seeds; § Qwen3-0.6B prompted zero-shot on the same 300 test items as ‡. Compare † and ‡ with their paired TF-IDF baselines in the text, not with the rows above them.

Removing cues does not remove the signal. Deleting the top-K features and retraining barely moves in-domain AUC: on ISOT it goes from 0.999 with all features to 0.991 after deleting 1,000 and 0.985 after 3,000, and on WELFake from 0.984 to 0.962 and 0.949; transfer to the paired corpus, in contrast, falls from 0.673 to 0.580 (ISOT→WELFake) and from 0.827 to 0.718 (WELFake→ISOT). So the highest-weight features carry most of what transfers, while the signal that keeps in-domain AUC near its ceiling is spread over thousands of corpus-specific features. Masking source tags, datelines, time expressions, numbers and named entities together (Figure 14) leaves in-domain AUC at 0.996 (ISOT) and 0.964 (WELFake), and moves ISOT→WELFake from 0.679 to 0.650 and WELFake→ISOT from 0.808 to 0.810. Balancing classes within each of 50 topic clusters, whose class purity averages 0.82 in ISOT and 0.81 in WELFake, leaves in-domain AUC unchanged (ISOT 0.998→0.999, WELFake 0.984→0.986) and transfer unchanged (0.604→0.606, 0.622→0.622); only GossipCop loses in-domain AUC (0.846→0.799). The separating signal is diffuse. It is spread through the style and register of the whole text rather than sitting in a list of tokens or topics that could be removed, as Verma (2026) also found for ISOT.

Corpus divergence does not predict transfer. Every pair of corpora can be told apart from text alone (proxy $\mathcal{A}$-distance between 1.28 and 1.98, maximum 2; ISOT–WELFake 1.45), yet across the 42 cells we find no association between source–target divergence and transfer AUC (Spearman $\rho = -0.01$). With seven corpora the corpus-bootstrap 95% interval is wide ([-0.61, 0.69]), so a moderate association cannot be excluded, but label-free divergence is clearly not a usable predictor of transfer here. What matters for transfer is less how




Figure 11: A zero-shot LLM (Qwen3-0.6B) against trained detectors on the same 300 test items per corpus (three seeds). (a) ROC-AUC of a TF-IDF model trained on the corpus itself, of TF-IDF and fine-tuned RoBERTa models transferred from the six other corpora (mean over sources), and of the zero-shot model. (b) Macro-F1 of the zero-shot model when its own answer is used, when half of the items are flagged, and at the best cut-off.

different two corpora look than whether the cue that separates the classes in one also separates them, with the same sign, in the other.

5.7. Repairing the ranking

Figure 15a reports the leave-one-corpus-out repairs (exact values per held-out corpus are in the Supplementary Material). Training on the six other corpora at once is the only change that helps ranking. Held-out AUC rises to 0.660, against 0.567 for the average single source. That is slightly below the best single source chosen with hindsight (0.671), which cannot be identified without target labels, and far below the targets' own in-domain AUC of 0.914. Nothing we added on top of pooling helped on average. Balancing every (corpus, class) cell (0.659, Δ-0.001, $p = 1.000$) and masking collection signatures (0.661, Δ+0.001, $p = 1.000$) leave AUC unchanged on average; masking helps clearly only on ISOT, the corpus whose signatures it was written for.

Methods that make the representation *invariant to corpus identity* make ranking worse: deleting the 2,000 most corpus-predictive features gives 0.636 (Δ-0.023, $p = 0.006$), CORAL 0.621 (Δ-0.038, $p < 0.001$) and INLP 0.605 (Δ-0.054, $p = 0.001$). INLP does what it is designed to do, reducing linear corpus-identity accuracy from 0.87 to 0.25 (six classes), but it removes veracity information with it. In these benchmarks corpus identity and label are entangled. Each corpus collected its fake and real items from different outlets, periods and formats, so the directions that identify a corpus are partly the directions that separate its classes. Making a model blind to the corpus does not make it blind to the shortcut. This is also the assumption




Figure 12: How much of the in-domain signal cheap cues recover (in-domain ROC-AUC, TFIDF-LR unless stated). Surface statistics: the style model; 64 training items: the learning-curve point at $n = 64$; publisher or speaker only: out-of-fold target encoding of the group (only where the corpus records it). The dashed line marks chance.

behind domain-adversarial and domain-gated detectors (Wang et al., 2018; Nan et al., 2021), and on these corpora it does not hold. The ranking gap that remains looks like a property of the data more than of the learner.

Published generalisation methods. The same pattern holds for methods designed to generalise across news domains (Figure 15b). On frozen RoBERTa vectors, pooled logistic regression reaches a held-out AUC of 0.660. The EANN-style adversarial model reaches 0.632 ($\Delta -0.028$, Holm-corrected Wilcoxon $p = 0.384$), the MDFEND-style mixture of experts 0.614 ($\Delta -0.046$, $p = 0.070$), ENDEF-style entity debiasing 0.643 ($\Delta -0.018$, $p = 0.683$), and a plain pooled network 0.639. None improves on pooling, and none is significantly different from it after correction. EM prior adaptation again lowers macro-F1 on top of every one of them (-221% of the operating-point loss recovered). Removing the corpus or entity signal from the representation, which is what these methods do, cannot help when that signal is also what separates the classes.

5.8. A low-resource language: Bengali clickbait

Replication and duplicates. On the official BanglaBait split, character 3–5-gram logistic regression reaches a clickbait-class F1 of 64.37 (Figure 16a), within two points of the 66.28 reported for the same model by Mahtab et al. (2023), and a linear SVM reaches 63.79. Removing the near-duplicates found by MinHash from the official splits lowers the same model to 59.15 (AUC 0.834→0.823): even after the original authors' Levenshtein filter, duplicated titles inflate the benchmark. Over five random re-splits of the deduplicated corpus the model reaches AUC 0.821 ± 0.011.




Figure 13: Highest-weight n-grams of TFIDF-LR (seed 0) for the real (blue) and fake (orange) classes. Both corpora are separated mainly by outlet conventions and collection-period vocabulary.

Publisher identity. The 19 publishers with at least 100 articles have clickbait rates from 7% to 66%, so publisher identity alone predicts the label with AUC 0.687 (Section 5.6). Leave-one-publisher-out evaluation nevertheless costs little: across 20 held-out publishers (the smallest ones pooled), mean AUC is 0.791 (range 0.651–0.911), close to the random-split value. Bengali clickbait detection survives a change of source that English veracity detection does not. One reading is that this is a construct effect rather than a language effect. Clickbait *is* a property of a headline's style, so a style-sensitive detector can learn the construct itself, whereas for veracity, style is only a correlate of the label that changes from corpus to corpus. The comparison is not fully controlled, though: BanglaBait was labelled by annotators reading each headline, while the English veracity labels come from fact-checks or from the outlet an article was taken from, so how the labels were made differs as well as what they mean.

Across languages. A translate-test probe uses BanglaBait's machine-translated English titles. A detector trained on English clickbait headlines (Chakraborty et al., 2016) ranks translated Bengali titles with AUC 0.707, against 0.777 for a detector trained on the translated titles themselves and 0.813 for one trained on the original Bengali; translation costs about 0.04 AUC and most of the in-language ranking ability carries over. In the other direction, the translated-Bengali detector reaches 0.931 on English headlines (in-domain 0.994). Clickbait carries over across languages much better than veracity carries over across English corpora, although translation and the change of collection still cost about 0.1 AUC (0.707 against 0.813 in-language).




Figure 14: Masking ablation for the article pair (TFIDF-LR, three seeds, first 3,000 characters). Each row masks one family of cues in every corpus; blue is in-domain AUC, orange is transfer AUC to the other article corpus.

6. Discussion

What the benchmarks measure. Every corpus in our suite can be told apart from every other with high accuracy (proxy $\mathcal{A}$-distance 1.28–1.98 on a scale whose maximum is 2). On the article corpora a model of surface statistics recovers nearly all of the in-domain signal, and on average more than half of it. The article and tweet corpora reach most of their final AUC with 64 training examples, and the heaviest feature weights point to outlet signatures and to the time window in which the fake class was collected (Section 5.6). To a large extent, then, in-domain scores measure how well a model recognises the *collection process* behind each class. Verma (2026) reached the same conclusion for ISOT alone. Our matrix shows that it holds across units and constructs, and that what is lost on a new corpus is mostly ranking, with calibration a smaller part.

What to do about it. The decomposition separates a cheap problem from a hard one. The operating-point part is cheap. Rate transfer needs no target labels and one line of code, and it recovered 81% of that loss for TFIDF-LR and between 66% and 81% across detectors, while the textbook label-shift correction made things worse for all of them. Someone deploying a detector on a new feed should therefore fix the *share* of items they flag, not a score threshold. If the base rate of the feed is expected to differ from the training data, labelling a small sample to estimate it is the better investment, since neither label-free prior estimator we tested could do it (Section 5.4).

The ranking part is hard. Source diversity helped: pooled training reached 0.660 held-out AUC against 0.567 for a single source. But label-free invariance methods made ranking worse, published generalisation methods did no better than pooling, and the pooled model is still far below the in-domain ceiling of 0.914. A zero-shot language model, which has seen none of these collections, ranked new corpora better than the average transferred detector, which suggests that models that do not learn a corpus's collection signatures




Figure 15: Leave-one-corpus-out repairs of the ranking. Each grey dot is one held-out corpus, the diamond the mean. (a) TF-IDF-based repairs, five seeds; red diamonds are significantly worse than pooled training (Holm-corrected Wilcoxon over corpus–seed pairs). Dotted line: the average single source; dashed line: the best single source, which can only be chosen with target labels. (b) Published generalisation methods re-implemented on frozen RoBERTa vectors of the 1,500-item subsets, three seeds; none differs significantly from pooled logistic regression.

are the more promising route to better ranking, provided their operating point is set by rate. Invariance to corpus identity is not enough when the label itself is tied to how each corpus was put together. Better ranking will need better data, in particular corpora whose real and fake items come from the same outlets and time windows, or evidence-based detectors that do not lean on style (Pelrine et al., 2023; Thibault et al., 2025). Multi-domain architectures (Nan et al., 2021; Zhu et al., 2022) should be evaluated on held-out corpora with this entanglement in mind.

Style as construct and as shortcut. The Bengali results add a distinction that the English matrix alone would not show. Clickbait detection held up on unseen publishers and partly across a change of language, while veracity detection did not survive a change of corpus. A plausible explanation is that a style-sensitive model transfers when style *is* the construct, as with clickbait headlines, and fails when style is only correlated with the label inside one collection, as with fake news. With a single Bengali corpus and labels made in different ways, we offer this as a hypothesis for benchmark designers, not a settled result: they should say which kind of cue their labels license.

Reporting protocol. For any claim that a misinformation detector generalises: (1) *verify label direction* with signature probes, and treat a same-task AUC below 0.5 as a data error until shown otherwise; (2) *deduplicate* within and across corpora with near-duplicate matching, and drop label-conflicting groups; (3) report at least one *same-task cross-corpus* result, with a ranking metric (ROC-AUC or AP) next to F1; (4) report the *decomposition*: F1 at the default, prior-matched and (cross-fitted) oracle thresholds; (5) run three cheap




Figure 16: Bengali clickbait. (a) Clickbait-class F1 on the official BanglaBait split, as released and after removing near-duplicates, against the published value for character LR (Mahtab et al., 2023). (b) ROC-AUC on each held-out publisher (dot size: number of articles) against the random-split value. (c) Translate-test: training and test corpora in Bengali (BN), machine-translated Bengali titles (BN-tr) or English clickbait headlines (EN).

shortcut probes: a surface-statistics model, a group-identity baseline where metadata exist, and a 64-example learning-curve point; (6) report a *permutation control*, several seeds, and intervals that resample corpora when averaging over a matrix; (7) deploy with a *rate-based* operating point unless target labels are available, and estimate the target base rate from a labelled sample if it is expected to change.

6.1. Limitations and threats to validity

Models. Six of our detectors are linear or tree-based on sparse, static-embedding and frozen RoBERTa features. The seventh fine-tunes only the upper four layers of RoBERTa-base, on 800 training items per corpus and three seeds, because the study ran on a two-core CPU; full fine-tuning on the complete splits might do better in-domain, though prior work found that it does not reliably help across corpora (Verma, 2026; Dell'Oglio et al., 2026). The zero-shot language model is a small one (0.6 billion parameters, 4-bit weights) and was prompted once, without prompt tuning; larger models rank better (Pelrine et al., 2023; Dell'Oglio et al., 2026; Verhoeven et al., 2026), and their pretraining may have seen these public benchmarks. Our claim for that family is narrower: its loss splits differently, and the same rate-based repair applies. The published generalisation methods were re-implemented on one frozen backbone rather than run with their original encoders and hyperparameters. *Corpora.* Labels differ in kind (claims, stories, outlets), which is why we lean on same-task pairs. FakeNewsNet is used through its public titles only. NELA-GT and BanFakeNews could not be obtained in our environment, so the Bengali analysis uses one Bengali corpus and a translate-test rather than a second native corpus. PHEME labels rumours, not falsehood, and serves only as an

additional unit. The article corpora enter as cleaned working copies (Section 3). Deduplication thresholds (Jaccard ≥ 0.8) trade recall for precision, and looser thresholds would remove more items. *Statistics.* Twitter15/16 and PolitiFact test sets are small, so their cells have wide intervals (Figure 5). We report pooled seed-bootstrap intervals per cell, resample corpora for matrix-level quantities, and avoid conclusions from single small cells. Seven corpora are still few, and the corpus-level intervals are correspondingly wide. *Operating points.* Rate transfer worked here partly because the base rates of our corpora are similar. The prior-shift experiment shows how it degrades when they are not; that experiment resamples existing test sets and does not reproduce every way a real feed can change. *Scope.* Our results concern text-only detection. Propagation-based detectors face related spurious-correlation problems on Twitter15/16 and PHEME (Wu and Hooi, 2022; Mu et al., 2023; Pelrine et al., 2021), which we did not re-evaluate. *Ethics.* We use only released text of public posts, with no user identifiers and no re-collection. Tweet content remains subject to the platform's terms, so we release code, per-cell results and saved scores but no post text.

7. Conclusion

Misinformation detectors that look near-perfect in-domain lose much of their value on a new corpus, though not all of it, and not for a single reason. Across ten audited corpora and seven detectors, 70% of the macro-F1 they lose is a ranking deficit that only better data or representations can address. The remaining 30% is a misplaced operating point, and most of it can be repaired without a single target label by transferring the share of items the detector flags rather than trusting its scores or a label-shift correction. That repair is exact when target scores are an order-preserving distortion of source scores and the base rate is unchanged, and it weakens as the base rate moves. A zero-shot language model shows the opposite balance, ranking unseen corpora better than transferred detectors do on average while losing mostly its operating point, which the same rule repairs; published domain-generalisation methods, by contrast, do not improve on simply pooling the training corpora. Much of what in-domain benchmarks reward is the collection process behind each class: outlet signatures, attribution style, time windows. Where style is the construct itself, as with clickbait, detection travels across publishers and in part across languages; where it is a by-product of how a corpus was assembled, as with veracity, it does not. Papers that claim generalisation should report transfer, ranking metrics and the decomposition next to in-domain accuracy, and the protocol and code released with this paper make that cheap to do.

CRediT authorship contribution statement

Dewan Fahad Chowdhury: Conceptualization (equal), Methodology (equal), Software (lead), Formal analysis (lead), Investigation (equal), Data curation (equal), Visualization (lead), Writing – original draft

(lead), Writing – review & editing (equal). **Md. Rejaul Korim Sadi:** Conceptualization (equal), Methodology (equal), Validation (lead), Investigation (equal), Data curation (equal), Writing – review & editing (equal), Project administration (lead).

Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

Data and code availability

All corpora are publicly available from their original releases (Section 3 and the repository's `DATA.md`); none is redistributed. Code, fixed seeds, per-cell results, saved predictions, logs and a one-command reproduction script are released under the MIT licence at `https://github.com/RejaulKorimSadi/Decomposing-and-repairing-the-cross-corpus-generalisation-gap-of-misinformation-detectors` (archived release DOI to be added on acceptance).

Declaration of generative AI and AI-assisted technologies in the manuscript preparation process

The research questions, study design, choice of corpora and interpretation of the results are the authors' own. During the preparation of this work the authors used Claude (Anthropic) in order to help implement and check the analysis code, organise the manuscript, typeset it in LaTeX and edit its language. After using this tool, the authors reviewed, verified and edited all code, results and text as needed and take full responsibility for the content of the published article.

References

Ahmed, H., Traore, I., Saad, S., 2017. Detection of online fake news using n-gram analysis and machine learning techniques, in: Intelligent, Secure, and Dependable Systems in Distributed and Cloud Environments (ISDDC 2017), Springer. pp. 127–138. doi:10.1007/978-3-319-69155-8_9.

Ahmed, H., Traore, I., Saad, S., 2018. Detecting opinion spams and fake news using text classification. Security and Privacy 1, e9. doi:10.1002/spy2.9.

Alexandari, A., Kundaje, A., Shrikumar, A., 2020. Maximum likelihood with bias-corrected calibration is hard-to-beat at label shift adaptation, in: Proceedings of the 37th International Conference on Machine Learning, pp. 222–232.

Alhindi, T., Petridis, S., Muresan, S., 2018. Where is your evidence: Improving fact-checking by justification modeling, in: Proceedings of the First Workshop on Fact Extraction and VERification (FEVER), pp. 85–90. doi:10.18653/v1/W18-5513.

Asr, F.T., Taboada, M., 2019. Big data and quality data for fake news and misinformation detection. Big Data & Society 6. doi:10.1177/2053951719843310.

Ben-David, S., Blitzer, J., Crammer, K., Kulesza, A., Pereira, F., Vaughan, J.W., 2010. A theory of learning from different domains. Machine Learning 79, 151–175. doi:10.1007/s10994-009-5152-4.

Bozarth, L., Budak, C., 2020. Toward a better performance evaluation framework for fake news classification. Proceedings of the International AAAI Conference on Web and Social Media 14, 60–71. doi:10.1609/icwsm.v14i1.7279.

Broder, A.Z., 1997. On the resemblance and containment of documents, in: Proceedings of Compression and Complexity of SEQUENCES 1997, IEEE. pp. 21–29. doi:10.1109/SEQUEN.1997.666900.

Calvo, H., Laureano, M.H., 2026. High accuracy, low generalization: Structural homogeneity and cross-dataset evaluation in fake-news benchmarks, in: Proceedings of the 1st Workshop on Information Disorder (InDor) at LREC 2026, ELRA. pp. 25–33.

Chakraborty, A., Paranjape, B., Kakarla, S., Ganguly, N., 2016. Stop clickbait: Detecting and preventing clickbaits in online news media, in: Proceedings of the 2016 IEEE/ACM International Conference on Advances in Social Networks Analysis and Mining (ASONAM), pp. 9–16. doi:10.1109/ASONAM.2016.7752207.

Chen, C., Shu, K., 2024. Can LLM-generated misinformation be detected?, in: International Conference on Learning Representations (ICLR).

Dell'Oglio, P., Bondielli, A., Marcelloni, F., Passaro, L.C., 2026. An experimental comparison of the most popular approaches to fake news detection. arXiv preprint arXiv:2603.25501 (preprint of an article in *Information Sciences*).

Forman, G., 2008. Quantifying counts and costs via classification. Data Mining and Knowledge Discovery 17, 164–206. doi:10.1007/s10618-008-0097-y.

Ganin, Y., Ustinova, E., Ajakan, H., Germain, P., Larochelle, H., Laviolette, F., Marchand, M., Lempitsky, V., 2016. Domain-adversarial training of neural networks. Journal of Machine Learning Research 17, 1–35.

Geirhos, R., Jacobsen, J.H., Michaelis, C., Zemel, R., Brendel, W., Bethge, M., Wichmann, F.A., 2020. Shortcut learning in deep neural networks. Nature Machine Intelligence 2, 665–673. doi:10.1038/s42256-020-00257-z.

Gururangan, S., Swayamdipta, S., Levy, O., Schwartz, R., Bowman, S., Smith, N.A., 2018. Annotation artifacts in natural language inference data, in: Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers), pp. 107–112. doi:10.18653/v1/N18-2017.

Haroon, M.A., 2026. When benchmarks mislead: Shortcut learning, length confounds, and the limits of cross-dataset generalization in multilingual fake news and sarcasm detection. arXiv preprint arXiv:2607.14131.

Holm, S., 1979. A simple sequentially rejective multiple test procedure. Scandinavian Journal of Statistics 6, 65–70.

Honnibal, M., Montani, I., Van Landeghem, S., Boyd, A., 2020. spaCy: Industrial-strength natural language processing in Python. Zenodo. doi:10.5281/zenodo.1212303.

Horne, B., Adali, S., 2017. This just in: Fake news packs a lot in title, uses simpler, repetitive content in text body, more similar to satire than real news. Proceedings of the International AAAI Conference on Web and Social Media 11, 759–766. doi:10.1609/icwsm.v11i1.14976.

Hoy, N., Koulouri, T., 2025. An exploration of features to improve the generalisability of fake news detection models. arXiv preprint arXiv:2502.20299.

Hu, B., Sheng, Q., Cao, J., Shi, Y., Li, Y., Wang, D., Qi, P., 2024. Bad actor, good advisor: Exploring the role of large

language models in fake news detection. Proceedings of the AAAI Conference on Artificial Intelligence 38, 22105–22113. doi:10.1609/aaai.v38i20.30214.

Janicka, M., Pszona, M., Wawer, A., 2019. Cross-domain failures of fake news detection. Computación y Sistemas 23. doi:10.13053/cys-23-3-3281.

Kaliyar, R.K., Goswami, A., Narang, P., 2021. FakeBERT: Fake news detection in social media with a BERT-based deep learning approach. Multimedia Tools and Applications 80, 11765–11788. doi:10.1007/s11042-020-10183-2.

Lazer, D.M.J., Baum, M.A., Benkler, Y., Berinsky, A.J., Greenhill, K.M., Menczer, F., Metzger, M.J., Nyhan, B., Pennycook, G., Rothschild, D., Schudson, M., Sloman, S.A., Sunstein, C.R., Thorson, E.A., Watts, D.J., Zittrain, J.L., 2018. The science of fake news. Science 359, 1094–1096. doi:10.1126/science.aao2998.

Liguori, A., Pisani, F.S., Comito, C., Guarascio, M., Manco, G., 2025. Breaking domain barriers: Mixture of experts for cross-domain fake news detection. Machine Learning 114, 188. doi:10.1007/s10994-025-06827-9.

Lipton, Z., Wang, Y.X., Smola, A., 2018. Detecting and correcting for label shift with black box predictors, in: Proceedings of the 35th International Conference on Machine Learning, pp. 3122–3130.

Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., Stoyanov, V., 2019. RoBERTa: A robustly optimized BERT pretraining approach. arXiv preprint arXiv:1907.11692.

Ma, J., Gao, W., Wong, K.F., 2017. Detect rumors in microblog posts using propagation structure via kernel learning, in: Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), pp. 708–717. doi:10.18653/v1/P17-1066.

Mahtab, M.M., Haque, M., Hasan, M., Sadeque, F., 2023. BanglaBait: Semi-supervised adversarial approach for clickbait detection on Bangla clickbait dataset, in: Proceedings of the 14th International Conference on Recent Advances in Natural Language Processing (RANLP), pp. 748–758. URL: https://aclanthology.org/2023.ranlp-1.81.

McCoy, T., Pavlick, E., Linzen, T., 2019. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference, in: Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics, pp. 3428–3448. doi:10.18653/v1/P19-1334.

McNemar, Q., 1947. Note on the sampling error of the difference between correlated proportions or percentages. Psychometrika 12, 153–157. doi:10.1007/BF02295996.

Mu, Y., Bontcheva, K., Aletras, N., 2023. It's about time: Rethinking evaluation on rumor detection benchmarks using chronological splits, in: Findings of the Association for Computational Linguistics: EACL 2023, pp. 736–743. doi:10.18653/v1/2023.findings-eacl.55.

Nan, Q., Cao, J., Zhu, Y., Wang, Y., Li, J., 2021. MDFEND: Multi-domain fake news detection, in: Proceedings of the 30th ACM International Conference on Information and Knowledge Management (CIKM), pp. 3343–3347. doi:10.1145/3459637.3482139.

Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D., Brucher, M., Perrot, M., Duchesnay, É., 2011. Scikit-learn: Machine learning in Python. Journal of Machine Learning Research 12, 2825–2830.

Pelrine, K., Danovitch, J., Rabbany, R., 2021. The surprising performance of simple baselines for misinformation detection, in: Proceedings of the Web Conference 2021 (WWW), pp. 3432–3441. doi:10.1145/3442381.3450111.

Pelrine, K., Imouza, A., Thibault, C., Reksoprodjo, M., Gupta, C., Christoph, J., Godbout, J.F., Rabbany, R., 2023. Towards reliable misinformation mitigation: Generalization, uncertainty, and GPT-4, in: Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, pp. 6399–6429. doi:10.18653/v1/2023.emnlp-main.395.

Pennington, J., Socher, R., Manning, C., 2014. GloVe: Global vectors for word representation, in: Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), pp. 1532–1543. doi:10.3115/v1/D14-1162.

Pérez-Rosas, V., Kleinberg, B., Lefevre, A., Mihalcea, R., 2018. Automatic detection of fake news, in: Proceedings of the 27th

International Conference on Computational Linguistics (COLING), pp. 3391–3401.

Platt, J.C., 1999. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods, in: Advances in Large Margin Classifiers. MIT Press, pp. 61–74.

Qwen Team, Yang, A., et al., 2025. Qwen3 technical report. arXiv preprint arXiv:2505.09388.

Ravfogel, S., Elazar, Y., Gonen, H., Twiton, M., Goldberg, Y., 2020. Null it out: Guarding protected attributes by iterative nullspace projection, in: Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pp. 7237–7256. doi:10.18653/v1/2020.acl-main.647.

Saerens, M., Latinne, P., Decaestecker, C., 2002. Adjusting the outputs of a classifier to new a priori probabilities: A simple procedure. Neural Computation 14, 21–41. doi:10.1162/089976602753284446.

Schuster, T., Schuster, R., Shah, D.J., Barzilay, R., 2020. The limitations of stylometry for detecting machine-generated fake news. Computational Linguistics 46, 499–510. doi:10.1162/coli_a_00380.

Shu, K., Mahudeswaran, D., Wang, S., Lee, D., Liu, H., 2020. FakeNewsNet: A data repository with news content, social context, and spatiotemporal information for studying fake news on social media. Big Data 8, 171–188. doi:10.1089/big.2020.0062.

Shu, K., Sliva, A., Wang, S., Tang, J., Liu, H., 2017. Fake news detection on social media: A data mining perspective. ACM SIGKDD Explorations Newsletter 19, 22–36. doi:10.1145/3137597.3137600.

Sun, B., Feng, J., Saenko, K., 2016. Return of frustratingly easy domain adaptation, in: Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence, pp. 2058–2065.

Suprem, A., Pu, C., 2022. Evaluating generalizability of fine-tuned models for fake news detection. arXiv preprint arXiv:2205.07154.

Thibault, C., Tian, J.J., Péloquin-Skulski, G., Curtis, T.L., Zhou, J., Laflamme, F., Guan, L.Y., Rabbany, R., Godbout, J.F., Pelrine, K., 2025. A guide to misinformation detection data and evaluation, in: Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining (KDD), pp. 5801–5809. doi:10.1145/3711896.3737437.

Verhoeven, I., Mishra, P., Shutova, E., 2026. Yesterday's news: Benchmarking multi-dimensional out-of-distribution generalization of misinformation detection models. Computational Linguistics 52, 620–645. doi:10.1162/COLI.a.585.

Verma, P.K., Agrawal, P., Amorim, I., Prodan, R., 2021a. WELFake: Word embedding over linguistic features for fake news detection. IEEE Transactions on Computational Social Systems 8, 881–893. doi:10.1109/TCSS.2021.3068519.

Verma, P.K., Agrawal, P., Prodan, R., 2021b. WELFake dataset for fake news detection in text data. Zenodo. doi:10.5281/zenodo.4561253.

Verma, Y., 2026. What does 99% accuracy measure? A reproducible audit of shortcut learning in a widely used fake news corpus. arXiv preprint arXiv:2609.25006.

Vosoughi, S., Roy, D., Aral, S., 2018. The spread of true and false news online. Science 359, 1146–1151. doi:10.1126/science.aap9559.

Wang, S., Manning, C., 2012. Baselines and bigrams: Simple, good sentiment and topic classification, in: Proceedings of the 50th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), pp. 90–94.

Wang, W.Y., 2017. "Liar, liar pants on fire": A new benchmark dataset for fake news detection, in: Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), pp. 422–426. doi:10.18653/v1/P17-2067.

Wang, Y., Ma, F., Jin, Z., Yuan, Y., Xun, G., Jha, K., Su, L., Gao, J., 2018. EANN: Event adversarial neural networks for multi-modal fake news detection, in: Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining, pp. 849–857. doi:10.1145/3219819.3219903.

Wu, J., Hooi, B., 2022. Probing spurious correlations in popular event-based rumor detection benchmarks, in: Machine Learning and Knowledge Discovery in Databases (ECML PKDD 2022), Springer. pp. 274–290. doi:10.1007/978-3-031-26390-3_17.

Zhou, X., Zafarani, R., 2020. A survey of fake news: Fundamental theories, detection methods, and opportunities. ACM Computing Surveys 53, 109:1–109:40. doi:10.1145/3395046.

Zhu, Y., Sheng, Q., Cao, J., Li, S., Wang, D., Zhuang, F., 2022. Generalizing to the future: Mitigating entity bias in fake news detection, in: Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval. doi:10.1145/3477495.3531816.

Zubiaga, A., Liakata, M., Procter, R., 2017. Exploiting context for rumour detection in social media, in: Social Informatics (SocInfo 2017), Springer. pp. 109–123. doi:10.1007/978-3-319-67217-5_8.

Zubiaga, A., Wong Sak Hoi, G., Liakata, M., Procter, R., 2016. PHEME dataset of rumours and non-rumours. figshare, https://figshare.com/articles/dataset/PHEME_dataset_of_rumours_and_non-rumours/4010619.

Appendix A. Proof of Proposition 1

Write $M^A(u) = \pi_A F_1^A(u) + (1-\pi_A)F_0^A(u)$ for the distribution function of source scores and M^B for that of target scores, and assume M^A is continuous and strictly increasing around τ_0, so that quantiles are unique. The source model flags $q_A = 1 - M^A(\tau_0)$ of the source items.

Rate transfer under (i) and (ii). By (i) and (ii), $M^B(g(u)) = \pi_A F_1^B(g(u)) + (1-\pi_A)F_0^B(g(u)) = M^A(u)$ for every u. The threshold that flags the top q_A share of target items is the t with $M^B(t) = 1-q_A = M^A(\tau_0)$, that is, $t = g(\tau_0)$. Its true-positive rate on B is $1 - F_1^B(g(\tau_0)) = 1 - F_1^A(\tau_0)$, the source true-positive rate at τ_0, and the same argument holds for the false-positive rate. With equal priors, equal error rates give the same expected confusion matrix, and hence the same population macro-F1 and balanced accuracy. The fixed threshold τ_0 has true-positive rate $1 - F_1^A(g^{-1}(\tau_0))$ on B, which equals the source rate for every pair of class distributions only if $g^{-1}(\tau_0) = \tau_0$. EM is also misled under (i): it assumes $F_y^B = F_y^A$, so a monotone distortion of the scores is read as a change of class balance.

Pure label shift. If g is the identity and $\pi_B \neq \pi_A$, then $p_B(x \mid y) = p_A(x \mid y)$, calibrated source posteriors are related to target posteriors by Bayes' rule with the two priors, and the EM fixed point of Saerens et al. (2002) is the true π_B in the population limit. The share of target items above τ_0 is $\pi_B \mathrm{TPR}_A + (1-\pi_B)\mathrm{FPR}_A$, which differs from q_A whenever $\mathrm{TPR}_A \neq \mathrm{FPR}_A$. Rate transfer therefore moves the threshold away from τ_0 even though the class-conditional score distributions have not changed, so it no longer reproduces the source error rates, and in general it does not coincide with the Bayes threshold for π_B either. □

Appendix B. Implementation details and compute

Hyperparameters. Logistic regression and linear SVM: $C \in \{0.25, 1, 4\}$ (SVM: $C/4$), liblinear, selected by validation ROC-AUC; TF-IDF word 1–2-grams, `min_df`=2, 100,000 features, sublinear term frequency, texts truncated to 20,000 characters. NB-SVM: binary 1–2-grams, add-one smoothed log-count ratios. GloVe: 100-d `glove-wiki-gigaword`, mean of in-vocabulary tokens. Style model: histogram gradient boosting with 100 or 300 iterations, learning rate 0.1. Frozen RoBERTa: mean of last-layer piece states, standardised,

logistic regression with $C \in \{0.025, 0.1, 0.4\}$. Fine-tuned RoBERTa: lower eight layers frozen and cached, upper four layers and a linear head trained with AdamW for three epochs (details in the Supplementary Material). Platt scaling on the validation split for every model. Bengali: character 3–5-grams (`char_wb`), 200,000 features.

Deduplication. MinHash with 128 permutations (seed 1) and LSH at Jaccard 0.8; word 3-gram shingles over the first 400 words for articles, character 5-grams otherwise; text normalised with NFKC, lower-casing, URL and punctuation removal.

Compute. All experiments ran on a 2-core CPU with 8 GB RAM and no GPU. The full pipeline (`run_all.sh`) takes about ten to twelve hours, plus roughly four hours for caching and fine-tuning the transformer. Software: Python 3.13, scikit-learn 1.9.1, spaCy 3.8, PyTorch 2 (CPU), datasketch, statsmodels.

Appendix C. Reproducibility checklist

- Data: public sources, licences and expected layout in `DATA.md`; label harmonisation and its verification in `src/label_probe.py`; deduplication counts in `results/dedup_report.json`.
- Splits and seeds: five seeds (0–4; three for the fine-tuned transformer) fix splits, subsampling and model initialisation; vectorisers and calibrators are fitted on source training and validation data only.
- Every number in this paper is written by `src/paper_numbers.py` from the files in `results/`; no number is typed by hand.
- Saved per-item scores for every (model, source, target, seed) cell allow any metric or threshold rule to be recomputed without retraining.
- Sanity controls: permutation regime (AUC ≈ 0.5) and size-matched regime are part of the main grid.
- The Supplementary Material contains the full matrices for every model, per-cell decompositions and operating points, learning curves, the vocabulary ablation, per-publisher Bengali results and the deduplication report.