

FD شركة نفط أبوظبي المحدودة (إمباراز) Abu Dhabi Oil Co., Ltd (Japan)			DETAILED ENGINEERING FOR MUBARRAZ REDEVELOPMENT PROJECT (EPC PHASE)														AREJLERS			
			EQUIPMENT LIST – MUBARRAZ ISLAND																	
COMPANY DOC NO : PJ6-EXD-MRI-BZ0L-0001																REV. 1				
S.No.	Rev.	EQPT. TAG No.	DESCRIPTION	DESIGN FLOWRATE / DESIGN DUTY / VOLUME	OPER. PRESS. (PSIG)	OPER. TEMP. (DEG. F)	DESIGN / SET PRESS. (PSIG)		DESIGN TEMP. (DEG. F)		MOC	INSULATION	DIMENSIONS (NOTE 1)		MOTOR RATING (kW)	P&ID No.	QTY REQD.	PHASE	REMARKS	
							MIN	MAX.	MIN.	MAX.			Length TL/TL or Height (mm)	Diameter or Width (mm)						
1	1	V-806-TF	MRD MEA Inlet Scrubber	4.24 m³	45	Min: 110 Max: 120	FV	185	29.8	185	CS + SS316 Clad	No	3350	1200	-	PJ6-EXD-MRI-BQDA-0021	1	Vapor + Liquid	Vertical	
2	1	V-805-TF	MRD Pig Receiver	-	160-180	Min: 60 Max: 105	FV	600	36	259	CS	No	Minor barrel length: 6600 Reducer length: 610 Major barrel length: 5300 Total Length: 12510	Major barrel: 36" in Minor barrel: 30" in	-	PJ6-EXD-MRI-BQDA-0022	1	Vapor + Liquid	-	
3	1	V-803-TF	MRD Oil Slug Catcher	327 m³	150	Min: 60 Max: 105	FV	195	-13.2	185	CS + Lining	No	15000	5000	-	PJ6-EXD-MRI-BQDA-0023	1	Vapor + Liquid	Horizontal	
4	1	V-804-TF	MRD Three Phase Separator	120 m³	110	Min: 60 Max: 105	FV	185	25	185	CS + Lining	No	12000	3400	-	PJ6-EXD-MRI-BQDA-0024	1	Vapor + Liquid	Horizontal	
5	0	C-010C-TF	MRD Sour Gas Compressor (Note 6)	4 MMSCFD	Suction: 3 Discharge: 50	Min: 130 Max: 140	FV	94.27	28	350.6	Note 2	No	-	-	355	PJ6-EXD-MRI-BQDA-0025	1	Vapor	Type: Reciprocating	
6	0	K-101E-TF	MRD Sweet Gas Compressor (Note 7)	7 MSCFD	Suction: 35 Discharge: 403	Min: 115 Max 140	FV	469	8	338	Note 2	No	-	-	850	PJ6-EXD-MRI-BQDA-0026	1	Vapor	Type: Reciprocating	
7	1	PX-851-TF	MRD Produced Water Treatment Package (Note 5)	81,440 BWPD	49.3 - 105.9	60 - 140	-	120	-	176	Note 2	-	-	-	-	PJ6-EXD-MRI-BQDA-0028	1	Vapor + Liquid	-	
8	1	P-851A/B/C-TF	MRD Produced Water Disposal Pumps	270 m³/Hr	Suction: 14.5 Discharge: 1061	60-105	-	1412	-	176	Note 2	No	-	-	900	PJ6-EXD-MRI-BQDA-0042	3	Liquid	-	
9	1	H-120-TF and H-801-TF	Oil Heater Package (Note 8)	41.53 MMBtu/hr	Inlet Pressure : 64.85 Outlet Pressure : 52.09	Inlet Temperature : 61 Outlet Temperature : 145	-	225	-	180 (Note 8)	Note 2	Note 8	-	-	-	PJ6-EXD-MRI-BQDA-0007	1+1	Vapor + Liquid	-	
NOTES:										HOLD LIST:										
1. All dimensional units are in mm unless otherwise specified.										1. Deleted										
2. Refer Vendor document for component level MOC.										2. Deleted										
3. Deleted										3. Deleted										
4. Deleted.																				
5. Produced Water Treatment Package consists of PCFI Separators (3 x 50%), Degasser (1 x 100%) and Educator.																				
6. New Sour Gas Compressor Package consists of single-stage reciprocating compressor, inlet scrubber, aftercooler and outlet scrubber.																				
7. New Sweet Gas Compressor Package consists of two-stage reciprocating compressor, 1st stage scrubber, 1st stage aftercooler, 2nd stage inlet scrubber, 2nd stage aftercooler and 2nd stage outlet scrubber.																				
8. Refer Heater Pacakge document for details of component level design condition.										Abbreviation: VTA - Vendor To Advice VTC - Vendor To Confirm										