

OIL INDIA LIMITED (SIMULATED OPERATIONS)

SYNTHETIC DATA — NOT OIL INDIA DATA · DEMO USE ONLY

DAILY DRILLING REPORT — Nahorkatiya Exploration DEMO-WELL-106 (DEMO-WELL-106) — PAGE 1

Field / Block:	Nahorkatiya Basin	Well Status:	ACTIVE
Coordinates:	Lat 27.248972 N, Lon 95.329907 E	Total Depth:	3683.0 m
Spud Date:	2025-04-30	Current Report Page:	Page 1 of 5

Operations Log (Depth interval: 0m - 700m):

Drilling string operated with PDC bit. Rotational speed maintained between 100-120 RPM. Circulated drilling fluid; monitored flow-out and return temperatures. Continuous mud-gas chromatograph readings recorded. Formation markers evaluated against seismic prognoses.

Routine drilling progress maintained with no critical incidents logged during this reporting window.

OIL INDIA LIMITED (SIMULATED OPERATIONS)

SYNTHETIC DATA — NOT OIL INDIA DATA · DEMO USE ONLY

DAILY DRILLING REPORT — Nahorkatiya Exploration DEMO-WELL-106 (DEMO-WELL-106) — PAGE 2

Field / Block:	Nahorkatiya Basin	Well Status:	ACTIVE
Coordinates:	Lat 27.248972 N, Lon 95.329907 E	Total Depth:	3683.0 m
Spud Date:	2025-04-30	Current Report Page:	Page 2 of 5

Operations Log (Depth interval: 700m - 1400m):

Drilling string operated with PDC bit. Rotational speed maintained between 100-120 RPM. Circulated drilling fluid; monitored flow-out and return temperatures. Continuous mud-gas chromatograph readings recorded. Formation markers evaluated against seismic prognoses.

CRITICAL DRILLING INCIDENTS & ACTIONS TAKEN ON THIS PAGE:

- **EVENT:** TORQUE_ANOMALY at 2740.0m (Severity: MEDIUM)
Description: Severe rotational torque oscillation (up to 28,000 ft-lbs) at 2740.0m.
Mitigation Action: Reduced WOB, adjusted RPM to eliminate torsional stick-slip.
Outcome: Drilling smoothed out.

OIL INDIA LIMITED (SIMULATED OPERATIONS)

SYNTHETIC DATA — NOT OIL INDIA DATA · DEMO USE ONLY

DAILY DRILLING REPORT — Nahorkatiya Exploration DEMO-WELL-106 (DEMO-WELL-106) — PAGE 3

Field / Block:	Nahorkatiya Basin	Well Status:	ACTIVE
Coordinates:	Lat 27.248972 N, Lon 95.329907 E	Total Depth:	3683.0 m
Spud Date:	2025-04-30	Current Report Page:	Page 3 of 5

Operations Log (Depth interval: 1400m - 2100m):

Drilling string operated with PDC bit. Rotational speed maintained between 100-120 RPM. Circulated drilling fluid; monitored flow-out and return temperatures. Continuous mud-gas chromatograph readings recorded. Formation markers evaluated against seismic prognoses.

CRITICAL DRILLING INCIDENTS & ACTIONS TAKEN ON THIS PAGE:

- **EVENT:** MUD_LOSS at 2829.3m (Severity: HIGH)
Description: Partial mud loss of 35 bbl/hr encountered in Barail at 2829.3m.
Mitigation Action: Added fine nut-plug and fiber sealants to active system.
Outcome: Losses cured; resumed controlled drilling.

OIL INDIA LIMITED (SIMULATED OPERATIONS)

SYNTHETIC DATA — NOT OIL INDIA DATA · DEMO USE ONLY

DAILY DRILLING REPORT — Nahorkatiya Exploration DEMO-WELL-106 (DEMO-WELL-106) — PAGE 4

Field / Block:	Nahorkatiya Basin	Well Status:	ACTIVE
Coordinates:	Lat 27.248972 N, Lon 95.329907 E	Total Depth:	3683.0 m
Spud Date:	2025-04-30	Current Report Page:	Page 4 of 5

Operations Log (Depth interval: 2100m - 2800m):

Drilling string operated with PDC bit. Rotational speed maintained between 100-120 RPM. Circulated drilling fluid; monitored flow-out and return temperatures. Continuous mud-gas chromatograph readings recorded. Formation markers evaluated against seismic prognoses.

CRITICAL DRILLING INCIDENTS & ACTIONS TAKEN ON THIS PAGE:

- **EVENT: MUD_LOSS at 144.7m (Severity: HIGH)**
Description: Partial mud loss of 38 bbl/hr encountered in Alluvium at 144.7m.
Mitigation Action: Added fine nut-plug and fiber sealants to active system.
Outcome: Losses cured; resumed controlled drilling.

OIL INDIA LIMITED (SIMULATED OPERATIONS)

SYNTHETIC DATA — NOT OIL INDIA DATA · DEMO USE ONLY

DAILY DRILLING REPORT — Nahorkatiya Exploration DEMO-WELL-106 (DEMO-WELL-106) — PAGE 5

Field / Block:	Nahorkatiya Basin	Well Status:	ACTIVE
Coordinates:	Lat 27.248972 N, Lon 95.329907 E	Total Depth:	3683.0 m
Spud Date:	2025-04-30	Current Report Page:	Page 5 of 5

Operations Log (Depth interval: 2800m - 3500m):

Drilling string operated with PDC bit. Rotational speed maintained between 100-120 RPM. Circulated drilling fluid; monitored flow-out and return temperatures. Continuous mud-gas chromatograph readings recorded. Formation markers evaluated against seismic prognoses.

Routine drilling progress maintained with no critical incidents logged during this reporting window.