The Code-Video Playbook

Make explainer videos entirely from code, in Antigravity

7 motion styles | your own footage | voiceover and sound design
CLIs, GitHub repos and copy-paste prompts

Prepared 28 October 2026

1. The big picture

Every video in your gallery (Kinetic Type, Chalk Talk, Clean Tech, Software Walkthrough, Data Story, Warm Canvas, Pop Info) is the same pipeline with a different look. The video is **a program**: layout and motion are code, a headless browser draws each frame, FFmpeg stitches frames and audio into an MP4. Nothing is dragged on a timeline, so an AI agent in Antigravity can write it, preview it, fix it and re-render it.

Layer	What it does	Tools covered here
1. Authoring	Scenes, text, shapes, motion, transitions written as code	HyperFrames (HTML), Remotion (React), Revideo / Motion Canvas (TypeScript)
2. Footage	Your own clips, screen recordings, talking head, b-roll	FFmpeg for prep; <video> / OffthreadVideo / Video components to place it
3. Voice	Narration and captions	Kokoro, Piper, Edge TTS (voice); Whisper (captions)
4. Sound	Music, whooshes, impacts, ducking, loudness	FFmpeg + royalty-free music + generated SFX
5. Render	MP4 out, optionally batch or cloud	CLI render, headless Chrome + FFmpeg

Your two modes (matches the gallery panel)
No voiceover: finished video with music, impacts and effects only. **With voiceover**: same video plus narration, with the music ducked under the voice. Both come from the same project; you only switch the audio mix at render time.

2. Setting up Antigravity

Google Antigravity is an agent-first IDE built on a VS Code foundation with deep Gemini integration, a Manager view for parallel agent tasks, a built-in browser and an MCP Store. It launched in November 2025. There is also a CLI, described as the direct successor of Gemini CLI, which works the same way as the desktop app for skills and MCP.

2.1 Where skills live

Scope	Folder	Notes
Workspace	.agent/skills/<name>/SKILL.md	Only this project. Overrides a global skill of the same name.
Global	~/.gemini/antigravity/skills/<name>/SKILL.md	Every project.

2.2 Where MCP servers live

In the agent pane open the "..." menu, then MCP Servers, Manage MCP Servers, View raw config. That opens `~/.gemini/antigravity/mcp_config.json`. Save, reload the MCP panel, and restart if a tool does not appear. Skills are the strategy and MCP tools are the hands, so use skills for video knowledge and MCP only if you want external services (image, stock or cloud-render APIs).

2.3 Install the video skills

Run these in the Antigravity terminal inside your project. Skills use the open SKILL.md format, so the same packs also work in Claude Code, Cursor, Codex and Gemini CLI.

```
# HyperFrames (HTML video): authoring, CLI, media (TTS + Whisper), registry
npx skills add heygen-com/hyperframes

# Remotion (React video): official skill pack from remotion-dev
npx remotion skills add            # run inside a Remotion project
# or, global install through the skills CLI:
npx skills add https://github.com/remotion-dev/skills -y -g --skill remotion-best-practices
```

Check before you trust a command
Tooling in this space changes monthly. After installing, run each CLI with `--help` and let the agent read the installed SKILL.md. If a flag below differs, the installed docs win.

3. The toolbox: frameworks, CLIs and repos

3.1 Video frameworks (pick one per project)

Tool	You write	Best for	Notes
HyperFrames github.com/heygen-com/hyperframes	HTML + CSS + GSAP (or Lottie, Three.js, WAAPI)	Agent-driven projects; fastest from idea to MP4; all 7 styles	Apache 2.0. Needs Node 22+ and FFmpeg. No build step. Ships TTS (Kokoro), Whisper transcribe, background removal, shader transitions, a block catalog and an AWS Lambda render path.
Remotion github.com/remotion-dev/remotion	React components (TSX)	Teams that know React; huge ecosystem; cloud rendering on Lambda	Source-available: custom licence that needs a paid company licence above small-team thresholds. Official agent skills (12 as of Aug 2026) incl. captions and render.
Revideo github.com/redotvideo/revideo (now under midrender)	TypeScript generator functions on HTML Canvas	Drawn animation, parameterised templates, render-as-API	Forked from Motion Canvas with audio support, headless and parallel rendering. Start with `npm init @revideo@latest`.
Motion Canvas motioncanvas.io	TypeScript + live editor	Hand-authored animations with a visual timeline editor	Standalone editor rather than a library; render is started from its UI.

3.2 Command-line tools you will actually use

CLI	Job	Install
ffmpeg / ffprobe	Trim, crop to 9:16, extract audio, mix, loudness, burn captions, final encode	Package manager (apt, brew, winget)
hyperframes	init, lint, check, snapshot, preview, render, transcribe, tts, doctor, add	npx hyperframes ...
remotion	Studio preview and render to MP4/WebM	npx create-video, then npx remotion ...
whisper / faster-whisper	Speech to text with timestamps for captions (SRT/VTT)	pip install faster-whisper (or openai-whisper)
edge-tts	Free cloud neural voices (400+), writes MP3 and subtitle file	pip install edge-tts
piper	Fast local CPU TTS, no account	pip install piper-tts
Kokoro (82M)	Small, fast local TTS; good default narrator; runs on CPU or GPU	via HyperFrames tts or pip
git, gh	Clone template repos; HyperFrames has a PR-to-video skill that reads PRs through gh	git-scm.com, cli.github.com

3.3 Repos worth cloning or watching

- **heygen-com/hyperframes** - HTML-native video engine, CLI, skills and a catalog of ready blocks (shader transitions, social overlays, animated charts). Packages: core, engine, producer, studio, player, shader-transitions.
- **remotion-dev/remotion** and **remotion-dev/skills** - React video framework and its official agent skills.
- **redotvideo/revideo** (midrender/revideo) - open-source TypeScript video framework, render-as-API.
- **motion-canvas/motion-canvas** - the animation library Revideo was forked from.
- **vercel-labs/skills** - the `npx skills` installer used above.
- **Not verified in this research (check each repo before relying on it):** MoviePy (Python editing), Manim (math-style animation), Editly (declarative FFmpeg editing).

> **Which one should you start with?**
> Start with **HyperFrames**. Plain HTML is what AI agents write best, it needs no bundler, and it already bundles TTS, Whisper and a transition catalog. Choose **Remotion** if you already think in React or need its Lambda scale-out and can accept the licence. Choose **Revideo** for drawn, canvas-style scenes (Chalk Talk, Pop Info) or if you want a render API with a permissive licence.

4. Quick starts

4.1 HyperFrames

```
npx hyperframes init my-video      # scaffold (also installs skills)
cd my-video
npx hyperframes preview            # live-reload preview in the browser
npx hyperframes lint               # catch invalid timing or tracks
npx hyperframes render             # MP4 out
npx hyperframes add data-chart     # pull a ready block from the catalog
npx hyperframes doctor             # diagnose Node / FFmpeg / Chrome issues
```

A composition is an HTML file where data attributes give timing and layering:

```
<div id="stage" data-composition-id="my-video"
     data-start="0" data-width="1920" data-height="1080">
  <video id="clip-1" data-start="0" data-duration="5" data-track-index="0"
         src="intro.mp4" muted playsinline></video>
  <!-- text, shapes, SVG, audio tags and GSAP timelines go here -->
</div>
```

Then ask the agent in plain language: *"Using /hyperframes, make a 45-second 9:16 hook video about X with bouncy captions synced to a TTS narration."* Iterate like an editor: "make the title 2x bigger", "add a lower third at 0:03".

4.2 Remotion

```
npx create-video --yes --blank my-video
cd my-video && npm install
npx remotion skills add             # teaches the agent the real API
npm run dev                         # Remotion Studio preview
# in a second terminal, start your agent, then render:
npx remotion render                 # prompts for composition; see --help for flags
```

4.3 Revideo

```
npm init @revideo@latest            # example project with Video, Audio, Img
npm run start                       # editor / preview
# render via the Revideo CLI or a render API endpoint (see its docs)
```

5. Using your own footage

Footage is just another layer. The rule: **prep with FFmpeg, place with the framework**. Prep means the clip is the right size, frame rate and loudness before the code touches it. Placing means a video element with a start time, duration and track.

Footage type	Where it fits	Styles
Talking head (A-roll)	Full frame with captions, then shrink to a rounded picture-in-picture on a canvas	Warm Canvas (built around it); Kinetic Type for punchy cuts
Screen recording	Inside a tilted browser or phone mockup, or full-window with cursor zoom	Software Walkthrough, Kinetic Type, Clean Tech
B-roll / stock	Background video behind big type, or a quick flash-cut insert	Kinetic Type, Data Story intros
Your voice only	Record audio, transcribe, animate captions and scenes to the timestamps	Any style (voiceover mode with your real voice)
None (all code)	Everything is drawn as vector or UI built in code	Chalk Talk, Pop Info, Clean Tech, Data Story

5.1 FFmpeg recipes for prep

```
# trim a section (re-encode so cuts are frame accurate)
ffmpeg -ss 00:00:05 -to 00:00:20 -i in.mp4 -c:v libx264 -preset veryfast \
       -crf 20 -c:a aac clip.mp4

# crop landscape to vertical 9:16 for Shorts / Reels / TikTok
ffmpeg -i in.mp4 -vf "crop=ih*9/16:ih,scale=1080:1920" -c:a copy vertical.mp4

# lock to 30 fps so timing math is predictable
ffmpeg -i in.mp4 -r 30 -c:v libx264 -preset veryfast -crf 20 -c:a copy cfr.mp4

# pull audio for transcription (mono 16 kHz is plenty for Whisper)
ffmpeg -i in.mp4 -vn -ac 1 -ar 16000 audio.wav

# normalise loudness to a social-friendly level
ffmpeg -i in.mp4 -af loudnorm=I=-16:TP=-1.5:LRA=11 -c:v copy loud.mp4

# burn an SRT in (quick option; animated captions look better in code)
ffmpeg -i in.mp4 -vf subtitles=captions.srt captioned.mp4
```

5.2 Placing footage in code

- **HyperFrames**: a <video> tag with data-start, data-duration and data-track-index (see 4.1). Mute the clip and add audio as its own tag if you want separate control.
- **Remotion**: the Video / OffthreadVideo and Audio components, with files in the public folder. The skill pack includes a rule for checking a clip can be decoded before a long render.
- **Revideo**: a Video component with src, size and play, plus an Audio component.
- Put raw files in `assets/` or `public/` and never edit originals; write prepped copies next to them.

> **Warm Canvas tip**
> This style depends on your footage. Record in good light, speak to camera, leave a one-second pause between ideas, and keep a clean take of each section. Transcribe first, then ask the agent to map each sentence to a caption beat or a canvas card using the timestamps.

6. Voiceover, captions and sound

6.1 Voiceover options

Option	Quality / speed	Cost and setup	Use when
Your real voice	Best authenticity	Phone or mic recording; clean with FFmpeg loudnorm	Personal-brand creator videos
Kokoro (local)	Very natural for its size; fast on CPU or GPU	Free, runs offline, also built into HyperFrames tts	Default narrator, private scripts
Piper (local)	Fast, CPU only, plainer	Free, offline, many voice files	Low-power machines, quick drafts
Edge TTS (cloud)	Good, 400+ voices, many languages	Free but needs internet for every request	Multilingual, fast iteration
Paid APIs (e.g. ElevenLabs)	Top-end expressiveness / cloning	Key and billing; wire in via MCP or a script	Final high-stakes narration

```
# Edge TTS: voice + subtitle file in one go
pip install edge-tts
edge-tts --text "Your first client is one message away." \
         --voice en-US-AriaNeural --write-media vo.mp3 --write-subtitles vo.vtt

# Piper: local, offline
echo "Your first client is one message away." | \
  piper --model en_US-lessac-medium --output_file vo.wav

# Whisper: turn any recording into timestamped captions
pip install faster-whisper      # or: pip install openai-whisper
whisper audio.wav --model base --output_format srt
```

With HyperFrames you can instead ask the agent to use its `tts` and `transcribe` commands (Kokoro and Whisper), so timings flow straight into the composition. Run `npx hyperframes tts --help` for the current options.

6.2 The script-to-sync loop

- Write the script as short lines, one idea per line (one beat per line).
- Generate the voice for the whole script, then transcribe it back with Whisper to get word-level timestamps.
- Have the agent drive every scene start, caption word and counter from those timestamps, not from guesses.
- If you edit a line, regenerate audio and transcript and the whole video re-times itself.

6.3 Sound design in code

The gallery calls it the "full mix: music, impacts and effects". Build it from four small assets plus FFmpeg. You can synthesise basic effects with no downloads:

```
# whoosh: filtered pink noise with a fade shape
ffmpeg -f lavfi -i "anoisesrc=d=0.6:c=pink:a=0.5" \
  -af "highpass=f=300,lowpass=f=4000,afade=t=in:d=0.3,afade=t=out:st=0.3:d=0.3" whoosh.wav

# boom / impact: low sine that decays
ffmpeg -f lavfi -i "sine=f=55:d=1.2" -af "afade=t=out:d=1.2,volume=3" boom.wav

# duck music under the voice, then mix
ffmpeg -i vo.wav -i music.mp3 -filter_complex \
 "[0:a]asplit=2[v1][v2];[1:a]volume=0.8[m];[m][v1]sidechaincompress=threshold=0.05:ratio=8[d];\
  [v2][d]amix=inputs=2:duration=first[out]" -map "[out]" mix.wav

# put the final mix on the rendered video
ffmpeg -i video.mp4 -i mix.wav -map 0:v -map 1:a -c:v copy -c:a aac -shortest final.mp4
```

- **Music**: use a licensed or royalty-free track you have the rights to. Keep it 12 to 18 dB under the voice.
- **Impacts and whooshes**: place one on every cut and every key-number lock. Fewer, better-timed hits beat constant noise.
- **Loudness**: finish at about -14 to -16 LUFS for social platforms (the loudnorm recipe above).
- Ask the agent to expose each sound as a timed audio element in the composition, so moving a scene moves its sound.

7. The seven styles, translated to code

For each style: what to build, the best-fit tool, how footage and voice fit, and the sound palette. All seven can be done in HyperFrames; the 'Best fit' column is where another tool has an edge.

#01 Kinetic Type (Creator motion graphics)

Look	Huge condensed caps slam in word by word, yellow serif accent word, highlighter swipes, hand-drawn circles and arrows, tilted browser/phone mockups, rolling green counters, grain and light leaks on near-black.
Build it with	GSAP word-by-word timelines; CSS transforms for punch zoom and shake; SVG stroke-draw for circles and arrows; code-drawn mockups; SVG noise or a grain overlay; RGB-split via CSS or a shader transition from the catalog.
Best fit	HyperFrames or Remotion (fast, punchy cuts).
Footage / voice	Screen recordings inside the tilted mockups; talking head optional as a cut-in. Voice: energetic, fast narration or your own voice; words land on the beat.
Sound palette	Kick-heavy beat, a bass boom on number lock, whoosh on whip pans, glitch zap on RGB cuts, short riser before flash cuts.

#02 Chalk Talk (Hand-drawn)

Look	Green slate, grainy chalk strokes, coloured chalk, falling dust, ghost writing from old lessons, wooden frame and tray.
Build it with	SVG paths animated with stroke-dashoffset; a chalk-texture filter (SVG turbulence/displacement) for the skipping edge; a chalk stick element that follows the drawn path; camera pan by translating one very wide scene; an eraser wipe as a mask.
Best fit	Revideo / Motion Canvas (path drawing is natural) or HyperFrames with GSAP.
Footage / voice	Mostly all code. Voice: calm teacher narration (Kokoro or Piper). Best with voiceover so lines are drawn as they are spoken.
Sound palette	Chalk scratch loop while drawing, soft tap on dots and rings, felt-eraser swipe, very quiet piano or no music.

#03 Clean Tech (Kinetic type, product explainer)

Look	Cool off-white, drifting dot grid, Inter Tight words that rise into place, white UI cards with soft shadows, one electric blue accent, mono labels, green check for finished things.
Build it with	HTML/CSS cards and flex layouts; a typing effect on a prompt card; SVG nodes with a dot travelling a path; task rows that tick; a counter; push and zoom-through transitions.
Best fit	HyperFrames (plain HTML is ideal) or Remotion.
Footage / voice	Optional screen recording in a card. Voice: friendly, medium pace.
Sound palette	Soft pad, light UI ticks and pops, gentle swoosh on pushes, a bright chime on each check.

#04 Software Walkthrough (Screen and UI)

Look	App window on a soft gradient, real-feeling cursor with click ripples, camera zoom, yellow-edged spotlights, numbered step pill, calm pad.
Build it with	Either build a fake app UI in HTML or use a real screen recording; overlay a cursor that follows a path; camera zoom by scaling and translating a wrapper; a step-pill component that counts up; end on a lower third.
Best fit	HyperFrames or Remotion. If using a real recording, trim with FFmpeg first.
Footage / voice	Real recording is the best source; keep the cursor visible while recording. Voice: clear tutorial narration.
Sound palette	Mouse click ticks, keyboard typing loop, soft whoosh on zoom, success chime on the final result.

#05 Data Story (Data)

Look	Deep ink background, one warm accent per idea (coral, teal, sand), Archivo headlines, IBM Plex Mono numbers, charts that draw themselves, source always on screen.
Build it with	Load a CSV or JSON; draw charts with SVG or D3 (line draw, bar grow); count-up numbers; ringed highlights; side-by-side comparison cards; a persistent source line.
Best fit	Remotion (React plus D3 is a natural fit) or HyperFrames with the data-chart block.
Footage / voice	Rarely uses footage. Voice: measured, editorial narration; keep numbers exactly as in the data file.
Sound palette	Low drone, tick per bar, soft rising tone while a line draws, one clean hit on the takeaway.

#06 Warm Canvas (Talking head)

Look	Full-frame talking head with serif captions, then a warm off-white canvas with white cards, you in a rounded picture-in-picture, Fraunces headlines in ink and sky blue, pastel chips.
Build it with	Two compositions: A-roll (video + word-by-word captions with key words in blue) and Canvas (title chip, cards with dashed arrow, table with count-up numbers, planner window with flagged blocks, three takeaway pills). Rounded PiP via CSS border-radius on the video.
Best fit	HyperFrames or Remotion. Whisper timestamps drive everything.
Footage / voice	Needs your footage. Voice is your own audio from the clip; clean it and loudness-normalise.
Sound palette	Very light bed music, subtle paper-slide sounds for cards, soft pop for chips; keep your voice dominant.

#07 Pop Info (Illustrated)

Look	Flat-vector cartoon scene (e.g. grocery aisle), one small character with a big feeling, teal thought bubble, counter, dotted path, iris wipe in and out, Fredoka type.
Build it with	Inline SVG scenes built from simple shapes; character poses swapped per beat; a bubble that scales in; dotted path via stroke-dashoffset; iris wipe with a circular clip-path; slow camera push.
Best fit	Revideo / Motion Canvas (Canvas/SVG) or HyperFrames with GSAP.
Footage / voice	All code. Voice: warm, friendly narrator or character-style voice (Edge TTS has many).
Sound palette	Playful ukulele or marimba loop, pops and boings on appearances, shopping-cart rattle, iris whoosh.

8. The workflow inside Antigravity

Step	What you do	What the agent does
1. Brief	Topic or script, target length, 16:9 or 9:16, style #, voice or no voice, any footage	Reads the style, picks the framework, asks only what it cannot guess
2. Storyboard	Approve or redirect the still frames	Writes a beat-by-beat list (one idea per beat) with a still for each; waits for your OK
3. Assets	Drop footage in assets/, add music	Preps clips with FFmpeg; generates TTS; transcribes for timestamps
4. Build	Open preview and watch	Writes scenes, wires timings to the transcript, adds sounds
5. Review	Give notes in plain language ("slower on beat 4")	Edits code, re-previews, takes snapshots
6. Render	Choose resolution and audio mode	Renders MP4 (and both audio versions if asked), verifies duration and loudness

Why storyboard first
A wrong idea caught on a still frame costs seconds. The same mistake found after a full render costs minutes and tokens. Keep the rule: no building until you say OK.

8.1 Make Antigravity work in parallel

- Use the Manager view to run one agent on audio (TTS, transcript, SFX) and another on scenes at the same time.
- Use the built-in browser to look at the preview and let the agent check its own frames.
- Save your style rules (fonts, colours, easing, caption look) as a workspace skill in `.agent/skills/my-style/SKILL.md` so every new video starts consistent.

8.2 Quality checklist before you render

- Text is readable on a phone (nothing smaller than about 5% of frame height).
- Every cut has an impact or whoosh; no sound without a visual reason.
- Voice is clear against music (ducked), loudness at about -14 to -16 LUFS.
- Frame rate is consistent (30 fps is a safe default) and footage is constant frame rate.
- Numbers on screen match your source file; the source is shown on screen for data videos.
- Safe margins respected for 9:16 (platform UI covers the bottom and right edges).

9. Copy-paste prompts

9.1 Master prompt for Antigravity

```
Make a [length]-second [16:9 | 9:16] explainer video about: [topic or script].
Style: [Kinetic Type | Chalk Talk | Clean Tech | Software Walkthrough |
        Data Story | Warm Canvas | Pop Info] - [paste the look description].
Framework: HyperFrames (HTML). Use the installed skills.
Audio: [no voiceover: music + impacts + effects only] or
       [voiceover: local Kokoro TTS, music ducked under the voice].
Footage: [list files in assets/ and how to use them, or "none"].
Process: 1) Write the beat list and sketch every beat as a still frame, then STOP
and wait for my OK. 2) After OK: prep assets, generate voice, transcribe for
timestamps, build scenes, add sound, lint, preview. 3) Render MP4 and tell me
the file path, duration and loudness. Do not change my original files.
```

9.2 Add your footage

```
I put talk.mp4 in assets/. Transcribe it with Whisper, trim dead air, then build
a Warm Canvas edit: A-roll with word-by-word captions for the hook, then a canvas
section where I shrink into a rounded picture-in-picture and cards explain the
three ideas. Use the transcript timestamps for every caption and card.
```

9.3 Voiceover only, no footage

```
Here is my script (one idea per line). Generate narration with Kokoro, transcribe
it back for word timings, and drive every scene start and caption from those
timings. Output two MP4s: with voiceover, and music-and-effects only.
```

9.4 Clone a look from screenshots

```
Attached are 3 screenshots of the style I want. Describe the look as a style spec
(palette, fonts, motion rules, transitions, sound), save it as a workspace skill
.agent/skills/my-style/SKILL.md, then build a 20-second test video about
[topic] in that style and show me stills before rendering.
```

10. Troubleshooting, licences and cost

Problem	Fix
Render fails or Chrome not found	Run `npx hyperframes doctor`, or reinstall Node 22+ and FFmpeg; Remotion downloads its own Chrome on first render.
Animation looks jerky or off-sync	Use constant frame rate footage, drive animations from the framework clock (seekable timelines), not wall-clock timers.
Audio drifts from video	Re-encode the clip to a fixed fps and 48 kHz audio, and drive scene times from transcript timestamps.
Captions out of sync	Transcribe the final mixed voice track, not the raw clip, and regenerate when the script changes.
Agent invents API calls	Install the official skills first and tell it to read the installed SKILL.md before coding.
Skill or MCP not showing in Antigravity	Restart the IDE after editing config; confirm the folder is .agent/skills/<name>/SKILL.md or the global path.
Large file or slow render	Render a low-res draft first, then final; HyperFrames and Remotion both support cloud render on AWS Lambda.

Licences and rights

- **HyperFrames** is Apache 2.0 (permissive). **Remotion** is source-available under its own licence, with a paid company licence above small-team thresholds. Read it before commercial use.
- Music, fonts, stock clips and voice models each have their own licences. Keep a short credits file in the project.
- Do not clone a voice without the speaker's permission.
- Do not use brand logos, characters or copyrighted artwork in your videos unless you own the rights.

What costs money

The frameworks and local voice tools above are free. Costs appear with cloud render, paid TTS, and your Antigravity or model usage plan. A local render uses your own CPU/GPU time.

11. One-page cheat sheet

```
SETUP     npx skills add heygen-com/hyperframes
          (or) npx create-video --yes --blank my-video && npx remotion skills add
FOOTAGE   ffmpeg -i in.mp4 -r 30 -c:v libx264 -crf 20 clip.mp4
VOICE     edge-tts / piper / Kokoro  ->  vo.wav
CAPTIONS  whisper vo.wav --model base --output_format srt
SOUND     whoosh.wav + boom.wav + music.mp3 -> duck -> mix.wav
BUILD     npx hyperframes preview     (or: npm run dev for Remotion)
RENDER    npx hyperframes render      (or: npx remotion render)
FINISH    ffmpeg -i video.mp4 -i mix.wav -map 0:v -map 1:a -c:v copy -c:a aac final.mp4
```

Sources

HyperFrames README and docs, github.com/heygen-com/hyperframes; Remotion skills coverage (horadecodar.com.br, motionbox.io, skillselion.com); Revideo, github.com/redotvideo/revideo; Antigravity skills and MCP setup (agentskill.sh/antigravity, Medium article on Antigravity CLI and IDE, docs.coingecko.com Antigravity page); local TTS options (Kokoro, Piper, Edge TTS, Whisper) from public project pages. MoviePy, Manim, Editly and the FFmpeg/TTS command examples come from general knowledge and were not verified against live docs in this session.