BRAC UNIVERSITY
Department of Computer Science and Engineering

Examination: Mid Term
Duration: 1 hour 15 minutes

Semester: Spring 2023
Full Marks: 25

CSE 340: Computer Architecture

Answer the following questions.
Figures in the right margin indicate marks.
Understanding the question is part of the exam.

Name: Abdullah Khondoker   ID: 20301065   Section: 03

1. CO1 **a)** Is MIPS a RISC or CISC architecture? **State** the differences between these two architectures based on what we have learned about MIPS.   **3**

b) Consider an implementation of MIPS ISA with a 500 MHz clock and   **3**
– each ALU instruction takes 2 clock cycles,
– each branch/jump instruction takes 3 clock cycles,
– each *sw* instruction takes 5 clock cycles,
– each *lw* instruction takes 4 clock cycles.
Also, consider a program that, during its execution, executes:
– x = 200 million ALU instructions
– y = 55 million branch/jump instructions
– z = 20 million *sw* instructions
– w = 25 million *lw* instructions
Identify the CPU time.

c) Suppose you are developing two new machine learning systems where System 1 takes   **3**
3 days, and System 2 takes 5 days. System 2 heavily depends on text processing, which takes 67% of the total time. What will be the new execution time for System 2 if you want to improve that specific process by 4 times?

If the Reference time for both System 1 and 2 is 7 days, what is the SPEC Ratio for System 1 and System 2 after the improvement? *Find their Geometric mean.*

2. CO2 **a)** **Convert** the following MIPS instruction to 32-bit machine code. Show your answer in hex format.   **2**

sll $17, $18, 11

Consider the identifying value for the instruction is (56.)   ~Correction 5

b) **Calculate** the target address in hexadecimal for the given instruction: **3**
j Label_Exit
Consider PC contains 0xD7A431BF, and the offset value (in decimal) is 455.

c) Suppose, C[] is a character array. **Convert** the following C code to MIPS code. Assume a, b, and the base address of C[] is located in $s1, $s2, and $s0, respectively. Your code should be as optimized as possible.   5

```
for (int a = 3; C[a] >= C[a + 7]; a = a + 2){
        int b = 1
        while ( b < 7 ) {
                C[b + 9] = C[b];
                b++;
        }
}
```

d) **Translate** the following code written in C programming language into MIPS Assembly instructions. You may assume that the values in the variables a and b inside the maze function are stored in the argument registers $a0 and $a1, respectively. Also, the value in the variable z is in $s7.   6

```
int maze(int a, int b){
    if (a < b){
        int z = 0xBE031C71;
        b = (b * 33) + 2;
        if (z == b){
            return z;
        }
        else{
            return b;
        }
    }

    return a;

}
```