


5th Edition

Elmasri / Navathe

Chapter 5

The Relational Data Model and Relational Database Constraints



5th Edition

Elmasri / Navathe



Chapter Outline

- Relational Model Concepts
- Relational Model Constraints and Relational Database Schemas
- Update Operations and Dealing with Constraint Violations

Relational Model Concepts

- The relational Model of Data is based on the concept of a *Relation*
- A Relation is a mathematical concept based on the ideas of sets
- The model was first proposed by Dr. E.F. Codd of IBM Research in 1970 in the following paper:
 - "A Relational Model for Large Shared Data Banks,"
Communications of the ACM, June 1970
- The above paper caused a major revolution in the field of database management and earned Dr. Codd the coveted ACM Turing Award

Informal Definitions

- Informally, a **relation** looks like a **table** of values.
- A relation typically contains a **set of rows**.
- The data elements in each **row** represent certain facts that correspond to a real-world **entity** or **relationship**
 - In the formal model, rows are called **tuples**
- Each **column** has a column header that gives an indication of the meaning of the data items in that column
 - In the formal model, the column header is called an **attribute name** (or just **attribute**)

Example of a Relation




Figure 5.1

The attributes and tuples of a relation STUDENT.

Formal Definitions - Schema

- The **Schema** (or description) of a Relation:
 - Denoted by $R(A_1, A_2, \dots, A_n)$
 - R is the **name** of the relation
 - The **attributes** of the relation are A_1, A_2, \dots, A_n
- Example:
CUSTOMER (Cust-id, Cust-name, Address, Phone#)
 - CUSTOMER is the relation name
 - Defined over the four attributes: Cust-id, Cust-name, Address, Phone#
- Each attribute has a **domain** or a set of valid values.
 - For example, the domain of Cust-id is 6 digit numbers.
 - The domain may have a data-type and/or format

Formal Definitions - Tuple

- A **tuple** is an ordered set of values (enclosed in angled brackets '< ... >')
- Each value is derived from an appropriate *domain*.
- A row in the CUSTOMER relation is a 4-tuple and would consist of four values, for example:
 - <632895, "John Smith", "101 Main St. Atlanta, GA 30332", "(404) 894-2000">
 - This is called a 4-tuple as it has 4 values
 - A tuple (row) in the CUSTOMER relation.
- A relation is a **set** of such tuples (rows)

Formal Definitions - State

- The **relation state** is a subset of the Cartesian product of the domains of its attributes
 - each domain contains the set of all possible values the attribute can take.
- Example: attribute Cust-name is defined over the domain of character strings of maximum length 25
 - $\text{dom}(\text{Cust-name})$ is `varchar(25)`

Formal Definitions - Summary

- Formally,
 - Given $R(A_1, A_2, \dots, A_n)$
 - $r(R) \subset \text{dom}(A_1) \times \text{dom}(A_2) \times \dots \times \text{dom}(A_n)$
- $R(A_1, A_2, \dots, A_n)$ is the **schema** of the relation
- R is the **name** of the relation
- A_1, A_2, \dots, A_n are the **attributes** of the relation
- $r(R)$: a specific **state** (or "value" or "population") of relation R – this is a *set of tuples* (rows)
 - $r(R) = \{t_1, t_2, \dots, t_n\}$ where each t_i is an n -tuple
 - $t_i = \langle v_1, v_2, \dots, v_n \rangle$ where each v_j *element-of* $\text{dom}(A_j)$

Formal Definitions - Example

- Let $R(A1, A2)$ be a relation schema:
 - Let $\text{dom}(A1) = \{0,1\}$
 - Let $\text{dom}(A2) = \{a,b,c\}$
- Then: $\text{dom}(A1) \times \text{dom}(A2)$ is all possible combinations:
 $\{ \langle 0,a \rangle, \langle 0,b \rangle, \langle 0,c \rangle, \langle 1,a \rangle, \langle 1,b \rangle, \langle 1,c \rangle \}$
- The relation state $r(R) \subset \text{dom}(A1) \times \text{dom}(A2)$
- For example: $r(R)$ could be $\{ \langle 0,a \rangle, \langle 0,b \rangle, \langle 1,c \rangle \}$
 - this is one possible state (or “population” or “extension”) r of the relation R , defined over $A1$ and $A2$.
 - It has three 2-tuples: $\langle 0,a \rangle, \langle 0,b \rangle, \langle 1,c \rangle$

Definition Summary

<u>Informal Terms</u>		<u>Formal Terms</u>
Table		Relation
Column Header		Attribute
All possible Column Values		Domain
Row		Tuple
Table Definition		Schema of a Relation
Populated Table		State of the Relation

Example – A relation STUDENT




Figure 5.1

The attributes and tuples of a relation STUDENT.

Characteristics Of Relations

- Ordering of tuples in a relation $r(R)$:
 - The tuples are *not considered to be ordered*, even though they appear to be in the tabular form.
- Ordering of attributes in a relation schema R (and of values within each tuple):
 - We will consider the attributes in $R(A_1, A_2, \dots, A_n)$ and the values in $t = \langle v_1, v_2, \dots, v_n \rangle$ to be ordered.

Same state as previous Figure (but with different order of tuples)

Figure 5.2

The relation STUDENT from Figure 5.1 with a different order of tuples.

STUDENT

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21

Characteristics Of Relations

- Values in a tuple:
 - All values are considered atomic (indivisible).
 - Each value in a tuple must be from the domain of the attribute for that column
 - If tuple $t = \langle v_1, v_2, \dots, v_n \rangle$ is a tuple (row) in the relation state r of $R(A_1, A_2, \dots, A_n)$
 - Then each v_i must be a value from $dom(A_i)$
- A special **null** value is used to represent values that are unknown or inapplicable to certain tuples.

Characteristics Of Relations

- Notation:
 - We refer to **component values** of a tuple t by:
 - $t[A_i]$ or $t.A_i$
 - This is the value v_i of attribute A_i for tuple t
 - Similarly, $t[A_u, A_v, \dots, A_w]$ refers to the subtuple of t containing the values of attributes A_u, A_v, \dots, A_w , respectively in t

Relational Integrity Constraints

- Constraints are **conditions** that must hold on **all** valid relation states.
- There are three *main types* of constraints in the relational model:
 - **Key** constraints
 - **Entity integrity** constraints
 - **Referential integrity** constraints
- Another implicit constraint is the **domain** constraint
 - Every value in a tuple must be from the *domain of its attribute* (or it could be **null**, if allowed for that attribute)

Key Constraints

- **Superkey of R:**
 - Is a set of attributes SK of R with the following condition:
 - No two tuples in any valid relation state $r(R)$ will have the same value for SK
 - That is, for any distinct tuples $t1$ and $t2$ in $r(R)$, $t1[SK] \neq t2[SK]$
- **Key of R:**
 - A "minimal" superkey
 - That is, a key is a superkey K such that removal of any attribute from K results in a set of attributes that is not a superkey (does not possess the superkey uniqueness property)

Key Constraints (continued)

- Example: Consider the CAR relation schema:
 - CAR(State, Reg#, SerialNo, Make, Model, Year)
 - CAR has two keys:
 - Key1 = {State, Reg#}
 - Key2 = {SerialNo}
 - Both are also superkeys of CAR
 - {SerialNo, Make} is a superkey but *not* a key.
- In general:
 - Any *key* is a *superkey* (but not vice versa)
 - Any set of attributes that *includes a key* is a *superkey*
 - A *minimal* superkey is also a key

Key Constraints (continued)

- If a relation has several **candidate keys**, one is chosen arbitrarily to be the **primary key**.
 - The primary key value is used to *uniquely identify* each tuple in a relation
 - The primary key attributes are underlined.
 - General rule: Choose as primary key the smallest of the candidate keys (in terms of size)
- Example: Consider the CAR relation schema:
 - CAR(State, Reg#, SerialNo, Make, Model, Year)
 - We chose SerialNo as the primary key
- Key constraint statement:
 - Not two tuples in a relation must have the same value for the key attribute(s).

CAR table with two candidate keys – LicenseNumber chosen as Primary Key

CAR

<u>License_number</u>	Engine_serial_number	Make	Model	Year
Texas ABC-739	A69352	Ford	Mustang	02
Florida TVP-347	B43696	Oldsmobile	Cutlass	05
New York MPO-22	X83554	Oldsmobile	Delta	01
California 432-TFY	C43742	Mercedes	190-D	99
California RSK-629	Y82935	Toyota	Camry	04
Texas RSK-629	U028365	Jaguar	XJS	04

Figure 5.4

The CAR relation, with two candidate keys: License_number and Engine_serial_number.

Relational Database Schema

- A set S of relation schemas that belong to the same database.
- S is the name of the whole **database schema**
- $S = \{R_1, R_2, \dots, R_n\}$
- R_1, R_2, \dots, R_n are the names of the individual **relation schemas** within the database S

COMPANY Database Schema

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

DEPT_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

WORKS_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

Figure 5.5
Schema diagram for
the COMPANY
relational database
schema.

Entity Integrity

- The *primary key attributes* PK of each relation schema R in S cannot have null values in any tuple of $r(R)$.
 - This is because primary key values are used to *identify* the individual tuples.
 - $t[PK] \neq \text{null}$ for any tuple t in $r(R)$
 - If PK has several attributes, null is not allowed in any of these attributes
- Note: Other attributes of R may be constrained to disallow null values, even though they are not members of the primary key.

Referential Integrity

- A constraint used to specify a **relationship** among tuples in two relations:
 - The **referencing relation** and the **referenced relation**.
- Tuples in the **referencing relation** R1 have attributes FK (called **foreign key** attributes) that reference the primary key attributes PK of the **referenced relation** R2.
 - A tuple t1 in R1 is said to **reference** a tuple t2 in R2 if $t1[FK] = t2[PK]$.
- A referential integrity constraint can be displayed in a relational database schema as a directed arc from R1.FK to R2.

Referential Integrity (or foreign key) Constraint

- Statement of the constraint
 - The value in the foreign key column (or columns) FK of the the **referencing relation** R1 can be **either**:
 - (1) a value of an existing primary key value of a corresponding primary key PK in the **referenced relation** R2, or
 - (2) a **null** (if it is not part of its own primary key)


Displaying a relational database schema and its constraints

- Each relation schema can be displayed as a row of attribute names
- The name of the relation is written above the attribute names
- The primary key attribute (or attributes) will be underlined
- A foreign key (referential integrity) constraints is displayed as a directed arc (arrow) from the foreign key attributes to the referenced table
 - Can also point to the primary key of the referenced relation for clarity

Referential Integrity Constraints for COMPANY database

Figure 5.7

Referential integrity constraints displayed on the COMPANY relational database schema.



Other Types of Constraints

- Semantic Integrity Constraints:
 - based on application semantics and cannot be expressed by the model per se
 - Example: “the max. no. of hours per employee for all projects he or she works on is 56 hrs per week”
- SQL-99 allows triggers and **ASSERTIONS** to express for some of these

Populated database state

- Each *relation* will have many tuples in its current relation state
- The *relational database state* is the union of all the individual relation states
- Whenever the database is changed, a new state arises
- Basic operations for changing the database:
 - INSERT a new tuple in a relation
 - DELETE an existing tuple from a relation
 - MODIFY an attribute of an existing tuple

Populated database state for COMPANY

Figure 5.6
One possible database state for the COMPANY relational database schema.

EMPLOYEE

Fname	Minit	Lname	Ssn	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	Dnumber	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT_LOCATIONS

Dnumber	Dlocation
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS_ON

Essn	Pno	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

PROJECT

Pname	Pnumber	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

DEPENDENT

Essn	Dependent_name	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse

Update Operations on Relations

- Integrity constraints should not be violated by the update operations: INSERT, DELETE, MODIFY
- In case of integrity violation, several actions can be taken:
 - Cancel the operation that causes the violation (RESTRICT or REJECT option)
 - Perform the operation but inform the user of the violation
 - Trigger additional updates so the violation is corrected (CASCADE option, SET NULL option)
 - Execute a user-specified error-correction routine

The INSERT operation

- INSERT may violate any of the constraints:
 - Domain constraint:
 - if one of the attribute values provided for the new tuple is not of the specified attribute domain
 - Key constraint:
 - if the value of a key attribute in the new tuple already exists in another tuple in the relation
 - Referential integrity:
 - if a foreign key value in the new tuple references a primary key value that does not exist in the referenced relation
 - Entity integrity:
 - if the primary key value is null in the new tuple

The DELETE operation

- DELETE may violate only referential integrity:
 - If the primary key value of the tuple being deleted is referenced from other tuples in the database
 - Can be remedied by several actions: RESTRICT, CASCADE, SET NULL (see Chapter 8 for more details)
 - RESTRICT option: reject the deletion
 - CASCADE option: delete the tuples that reference the tuple that is being deleted
 - SET NULL option: set the foreign keys of the referencing tuples to NULL
 - One of the above options must be specified during database design for each foreign key constraint

The UPDATE operation

- UPDATE (or MODIFY) may violate domain constraint and NOT NULL constraint on an attribute being modified
- Any of the other constraints may also be violated, depending on the attribute being updated:
 - Updating the primary key (PK):
 - Similar to a DELETE followed by an INSERT
 - Need to specify similar options to DELETE
 - Updating a foreign key (FK):
 - May violate referential integrity
 - Updating an ordinary attribute (neither PK nor FK):
 - Can only violate domain constraints