

Correspondence and Logical Matrices: A Boolean Operator Calculus

Formula-valued logical matrices, valuation, pairing, and coherent operator superposition

Brian Theory*

LM-centered post-audit revised foundations draft, 22 September 2026

Abstract

We develop a typed Boolean operator calculus centered on formula-valued logical matrices (LMs) and their relation to numeric correspondence matrices (CMs). For a binary connective Θ , the LM

$$[M_{X\Theta Y}] = \begin{bmatrix} X\Theta Y & X\Theta\neg Y \\ \neg X\Theta Y & \neg X\Theta\neg Y \end{bmatrix}$$

records the complete polarity orbit of the logical operands X, Y . It admits the invertible Boolean-frame normal form

$$[M_{X\Theta Y}] = S_X[\Theta]S_Y, \quad S_X = \begin{bmatrix} X & \neg X \\ \neg X & X \end{bmatrix}, \quad S_X^2 = I,$$

so valuation sends the symbolic operator to the corresponding numeric CM in its valued signed frame. Logical pairing has the exact agreement-bit semantics

$$\langle A|[M_{X\Theta Y}][B] \rangle \equiv (A \Leftrightarrow X) \Theta (Y \Leftrightarrow B),$$

and labelled basis pairings reconstruct the connective.

The central operation is Boolean superposition of aligned logical operators. If an outer Boolean operation g is applied pointwise to formula-valued LMs, the LM lift, valuation, common signed input-frame transport, and logical pairing all preserve the same operation. The corresponding CM-level entrywise law is a valued corollary and has direct antecedents in truth-vector Boolean calculus; the focus here is the formula-valued LM architecture and the coherence of its symbolic, relational, and numeric semantics. We extend the construction to arbitrary-arity logical tensors and rectangular correspondence maps, give conditional block constructions, and characterize conjunctive/XOR separability by ordinary $\mathbb{F}_2$ matrix rank.

The underlying truth-table, Boolean-algebra, group-action, and pointwise-composition ingredients are classical. The paper therefore claims a unified formula-valued symbolic/numeric representation calculus and precise compatibility laws rather than a new underlying Boolean algebra. No physical measurement interpretation, truth-table compression, or computational speedup is assumed.

Status of this draft. The binary CM selection, signed-frame transformations, same-frame fusion, formula-valued LM construction, valuation map, and binary logical-pairing identity have already been developed in the companion computational manuscript. The present paper reorganizes those

*Research draft. This manuscript reorganizes and extends material from the author's earlier correspondence-matrix work and a companion computational manuscript. Priority claims remain subject to a dedicated literature audit.

results around the CM/LM mathematics and develops the higher-arity tensor, frame-action, closure, and block-lift formulation that is natural for a foundations paper. The literature comparisons below are deliberately conservative and inherit several bibliographic leads from the companion manuscript; they are not a certification of historical priority.

1 Introduction

Every binary Boolean connective has four output values. A truth table records those values as data; a correspondence matrix records them in a 2×2 array whose row and column axes are tied to declared operands. The information content is unchanged, but the array can participate in an operator calculus. True-first Boolean state vectors select entries; transposition exchanges operand axes; row and column reversals absorb input negations; output complement negates the connective; and compatible operators can be combined before any particular operands are evaluated.

The notation follows the author’s original manuscript [10]. A Greek letter such as Θ denotes a logical operator variable, and $[\Theta]$ denotes the correspondence matrix representing that operator. Thus $\Theta \Leftrightarrow$ is a connective while

$$[\Leftrightarrow] = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

is its CM. When arbitrary arity is required we use ordinary function notation $f : \mathbb{B}^n \rightarrow \mathbb{B}$; for a binary named connective, $f_\Theta(x, y) = x\Theta y$. This separates the connective from its matrix representation without introducing a second unrelated symbol for the binary CM.

Throughout the paper, uppercase symbols such as X, Y, A, B denote logical operands or formulas, while lowercase symbols such as x, y, a, b, c, d denote Boolean values, assignments, or scalar coefficients. The uppercase operands need not be atomic propositional variables: they may be arbitrary formulas. The present theory nevertheless keeps LM entries in the Boolean formula algebra; an enrichment in which the operands or entries are themselves matrix-valued operators is a separate extension and is not assumed here.

The historical manuscript already contained several seeds of the present theory: a complete set of sixteen binary CMs, matrix transformations of logical operators, same-operands operator superposition, formula-valued LMs, logical pairing, support-style “quotient” operations, single-variable factorization, and tentative 4×4 constructions [10]. The present paper retains the sound parts in a more explicit type system. In particular, the old arithmetic-modulo analogy is not retained; its useful core is an ordinary Boolean support difference. The earlier higher-dimensional language is replaced by a 2^n -entry tensor with explicitly declared matrix flattenings.

The central structural claim is not that truth tables, Boolean matrices, tensor flattenings, or pointwise composition are new. The distinctive focus is the formula-valued LM layer and the compatibility of its semantics with the numeric CM layer. The architecture organizes several levels of the same Boolean function:

1. **formula-valued logical operators:** for example $[M_{X \vee Y}]$, whose four entries are $X \vee Y$, $X \vee \neg Y$, $\neg X \vee Y$, and $\neg X \vee \neg Y$;
2. **valuation to numeric correspondence operators:** a valuation sends an LM to a four-bit CM such as $[\Rightarrow] = \begin{bmatrix} 1 & 0 \\ 1 & 1 \end{bmatrix}$, with the valued operand polarities recorded by row/column reversals;
3. **logical pairing:** contraction of a formula-valued LM against formula states, producing an exact relationship formula rather than merely selecting a stored bit;

4. **LM operator superposition:** aligned formula-valued logical operators themselves become operands of another Boolean operation, producing a new LM; the familiar CM entrywise law is its valued numeric image;
5. **signed-frame actions:** input permutations and polarity changes realized coherently as symbolic substitutions and numeric matrix/tensor reindexings; and
6. **higher-arity logical tensors and correspondence maps:** the same construction extends to 2^n symbolic polarity slots and to typed rectangular flattenings.

The point of the calculus is that these maps and operations are linked by commuting identities rather than merely listed side by side.

A further goal is to make the binary construction scale cleanly. An n -variable function has a canonical $2 \times \cdots \times 2$ correspondence tensor. A formula-valued version is its symbolic polarity orbit. A row/column bipartition of p and q variables reshapes the tensor into a $2^p \times 2^q$ correspondence map. Square flattenings are endomorphisms; rectangular flattenings are linear maps between different Boolean state spaces. Both still support a typed bra–matrix–ket contraction.

Matrix representations of logic have extensive antecedents. Boolean matrix methods predate CMs [1]; matrix and vector logic treat logical connectives as operators [2, 3, 4]; semi-tensor-product methods use logical structure matrices [5, 7]; and explicit XOR–AND Boolean matrix calculi also exist [6]. Most importantly for the raw numeric operator-on-operator law, Cheng, Zhao, and Xu state that if two Boolean functions of the same ordered variables have truth vectors m_f, m_g , then the truth vector of $f \Phi g$ is obtained by applying the outer logical operator Φ entrywise to m_f, m_g [6, Prop. 3.3]. Under a 2×2 reshape this is the numeric same-frame identity used here. In the inspected Cheng source, however, the relevant construction is expressed in truth-vector/Boolean-matrix language; we did not locate a formula-valued LM polarity lift, the present logical-pairing identity, or a bra–matrix–ket semantic layer there. Accordingly, pointwise combination of aligned numeric truth values is not claimed as new; the present paper centers the formula-valued LM architecture and the way valuation, pairing, and typed frame transport preserve the same operation.

Bricken’s internally dated March 1997 notes are another close antecedent: they arrange the sixteen binary Boolean relations as 2×2 matrices, use Boolean matrix algebra, explicitly evaluate logical operators in bra–matrix–ket form $\langle x|B|y\rangle$, and treat logical matrices as operands of matrix operations [15]. The original public-release date and peer-reviewed status of that technical note should not be inferred from the current website alone. Thus neither Dirac-style notation, 2×2 logical matrices, nor the broad idea that matrices representing logic can themselves be manipulated is claimed as new. NPN transformations and packed truth-function manipulation are likewise standard in logic synthesis [16, 17].

Eigenlogic supplies a second important boundary. It represents logical propositions by commuting projection operators whose truth values are eigenvalues and whose canonical input interpretations are eigenvectors [8, 9]. The 2015 Eigenlogic preprint explicitly discusses Dirac notation but deliberately uses ordinary vector notation; the later quantum-oriented treatment uses Dirac-style states. The CM/LM contribution pursued here is therefore narrower: formula-valued polarity operators, their valuation to numeric CMs, exact logical pairing, typed frame alignment, and a coherence law showing that Boolean operations on operators are respected by valuation, frame changes, and pairing. The abstract orbit embedding and polarity-equivariance facts are standard group-action structure and are used for characterization rather than historical priority.

2 Boolean scalar algebra and correspondence operators

2.1 Three distinct compositions

The same finite arrays participate in several different operations, and the paper keeps them explicitly separate.

1. *XOR-AND matrix product* AB contracts an intermediate matrix index over $\mathbb{F}_2$.
2. *Pointwise Boolean operator superposition* $A\hat{\Phi}B$ applies an outer Boolean connective Φ to corresponding entries of two operators in the same declared frame.
3. *Boolean-function superposition* $h = g(f_1, \dots, f_m)$ substitutes the outputs of Boolean functions into an outer Boolean function g .

The representation theorems below realize the third operation by the second when the operators are aligned; they do not identify either of those operations with ordinary matrix multiplication. A separate matched-intermediate-frame theorem later explains when the first operation also transports cleanly through the LM representation.

2.2 States, one-hot selection, and binary CMs

Let $\mathbb{B} = \{0, 1\}$ and regard it as $\mathbb{F}_2$ when addition and multiplication are used. Addition is XOR, written $\uplus$, and multiplication is conjunction. The nonstandard XOR glyph is intentional: in the declared true-first CM frame, the XOR matrix is the literal quarter-turn rotation of the XNOR matrix,

$$[\Leftrightarrow] = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, \quad [\uplus] = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} = \text{rot}([\Leftrightarrow]). \quad (1)$$

The notation is paper-specific rather than a claim of standard usage. Logical equivalence of formulas is written $\equiv$; the connective itself is written $\Leftrightarrow$.

For a bit $x \in \mathbb{B}$, define the true-first state

$$|x\rangle = \begin{bmatrix} x \\ \neg x \end{bmatrix}, \quad \langle x| = \begin{bmatrix} x & \neg x \end{bmatrix}. \quad (2)$$

These are *one-hot* states: exactly one component is 1. Thus $|1\rangle = (1, 0)^T$ and $|0\rangle = (0, 1)^T$. Bra-ket notation is used only as compact row/map/column notation in a Boolean algebra; no Hilbert-space or physical interpretation is assumed.

Let Θ be a binary logical operator variable. Its correspondence matrix is

$$[\Theta] := \begin{bmatrix} 1\Theta 1 & 1\Theta 0 \\ 0\Theta 1 & 0\Theta 0 \end{bmatrix} = \begin{bmatrix} \Theta_{11} & \Theta_{10} \\ \Theta_{01} & \Theta_{00} \end{bmatrix}. \quad (3)$$

The brackets are part of the notation: Θ is the logical operator, while $[\Theta]$ is its CM representation. For general functional notation, write $f_\Theta(x, y) = x\Theta y$.

Proposition 2.1 (Unique binary representation). *Once the operand axes and true-first order are fixed, $\Theta \mapsto [\Theta]$ is a bijection between the sixteen binary Boolean operators and the sixteen matrices in $\mathbb{B}^{2 \times 2}$.*

Proof. A binary operator is determined by its four values on $(1, 1), (1, 0), (0, 1), (0, 0)$, exactly the four entries of $[\Theta]$. $\square$

For any $C \in \mathbb{B}^{2 \times 2}$ define the XOR–AND contraction

$$E_C(x, y) = \langle x | C | y \rangle = \biguplus_{r, s \in \{1, 0\}} \chi_x(r) \wedge C_{rs} \wedge \chi_y(s), \quad (4)$$

where $\chi_x(r) = 1$ exactly when $r = x$.

Proposition 2.2 (CM selection). *For every binary operator Θ and $x, y \in \mathbb{B}$,*

$$\langle x | [\Theta] | y \rangle = x \Theta y.$$

Proof. Both states are one-hot. Every term in (4) vanishes except the term indexed by $(r, s) = (x, y)$. $\square$

Remark 2.3 (Why XOR–AND rather than OR–AND?). For one-hot basis states, XOR–AND and OR–AND selection return the same selected coefficient because at most one product term can be nonzero. For example, if $[\Theta] = \begin{bmatrix} a & b \\ c & d \end{bmatrix}$, then $\langle 1 | [\Theta] | 0 \rangle = b$ under either reduction. This observation already appears in the historical manuscript [10].

The two algebras are not interchangeable in general. With $u = (1, 1)$ and $v = (1, 1)^T$,

$$u \cdot_{\text{XOR/AND}} v = 1 \biguplus 1 = 0, \quad u \cdot_{\text{OR/AND}} v = 1 \vee 1 = 1.$$

Thus arbitrary vector or matrix multiplication can differ as soon as more than one term survives. XOR is retained because it gives the $\mathbb{F}_2$ coefficient algebra, coefficient-space linearity, cancellation, and a single convention shared by the numeric and symbolic calculus. Short-circuit evaluation of the logical connective OR is a separate implementation issue and does not justify replacing the contraction algebra globally.

2.3 Basis decomposition and Boolean closure at the coefficient level

Let $E_{rs} = |r\rangle\langle s|$ for $r, s \in \{1, 0\}$. These four one-feature matrices form the standard basis of $\mathbb{F}_2^{2 \times 2}$.

Proposition 2.4 (CM basis decomposition). *Every binary CM has the unique expansion*

$$[\Theta] = \biguplus_{r, s \in \{1, 0\}} \Theta_{rs} E_{rs}. \quad (5)$$

This recovers one of the original CM constructions in a conventional vector-space form: a connective is the XOR sum of exactly those minterm positions on which it is true [10].

The contraction is linear in the coefficients of $[\Theta]$ over $\mathbb{F}_2$ for fixed states. This does not imply that the represented Boolean function is affine in its logical inputs.

2.4 Operand frames and the internal swap matrix

A CM occurrence is typed by its operand frame: row expression, column expression, input polarities, and truth-state order. Define the transformed connectives by their truth functions

$$\Theta^T(x, y) := y \Theta x, \quad \Theta^{-L}(x, y) := (\neg x) \Theta y, \quad \Theta^{-R}(x, y) := x \Theta (\neg y).$$

Then

$$[\Theta^T] = [\Theta]^T, \quad [\Theta^{-L}] = [\mathbb{I}][\Theta], \quad [\Theta^{-R}] = [\Theta][\mathbb{I}]. \quad (6)$$

The matrix products in (6) are XOR–AND products. Here $[\mathbb{I}]$ plays two compatible roles: as the CM of the XOR connective and, under matrix multiplication, as the two-state permutation matrix that exchanges true and false. This removes the need to introduce an unrelated symbol P or S for the same 2×2 array.

Output complement is entrywise. If J is the all-ones 2×2 matrix, then

$$[\neg \Theta] = J \biguplus [\Theta]. \quad (7)$$

2.5 Support order and Boolean difference

The original manuscript used the language of operator containment and “quotienting.” The sound part is most cleanly stated as a support order. For CMs $A, B \in \mathbb{B}^{2 \times 2}$ write

$$A \preceq B \iff A_{rs} \leq B_{rs} \text{ for every } r, s,$$

so $\text{supp}(A) \subseteq \text{supp}(B)$. Define the Boolean support difference

$$B \setminus A := B \wedge \neg A \tag{8}$$

entrywise. For example,

$$[\vee] \setminus [\wedge] = [\nabla].$$

This is ordinary Boolean set difference on truth support, not arithmetic remainder or modulo. It is useful for decompositions and comparisons, but it is not a new scalar operation.




Figure 1: Binary CM/LM architecture. The connective Θ , its numeric matrix $[\Theta]$, and its formula-valued LM are distinct typed objects. For free reference generators the all-true valuation returns $[\Theta]$; arbitrary valuations return signed-frame versions.

3 Formula-valued logical matrices

3.1 Binary symbolic lift

Let $\mathcal{F}$ be the Boolean algebra of formulas modulo logical equivalence. Unless stated otherwise, X and Y in the defining LM are distinct free reference generators. The same formulas may later be specialized to compound operands; in that case general valuation remains valid, but an “all-true” valuation exists only when those substituted references are jointly satisfiable. For a formula A and polarity bit $b \in \mathbb{B}$, write

$$A^{(b)} = \begin{cases} A, & b = 1, \\ \neg A, & b = 0. \end{cases} \tag{9}$$

For a binary operator Θ , define the formula-valued logical matrix

$$[M_{X\Theta Y}] := \begin{bmatrix} X\Theta Y & X\Theta\neg Y \\ \neg X\Theta Y & \neg X\Theta\neg Y \end{bmatrix}. \tag{10}$$

Its entries are formulas, not numeric coefficients. For example,

$$[M_{X \vee Y}] = \begin{bmatrix} X \vee Y & X \vee \neg Y \\ \neg X \vee Y & \neg X \vee \neg Y \end{bmatrix}.$$

Thus the LM packages the complete polarity orbit of one reference formula.

3.2 Formula-valued frame normal form

There is a compact matrix factorization behind the four displayed formulas. In this subsection only, juxtaposition of formula-valued matrices means XOR-AND matrix multiplication over the Boolean ring $(\mathcal{F}, \uplus, \wedge)$; this is distinct from pointwise operator superposition. Define the formula-valued frame matrix

$$S_X := \begin{bmatrix} X & \neg X \\ \neg X & X \end{bmatrix}. \quad (11)$$

Because $X \wedge \neg X = 0$ and $X \uplus \neg X = 1$,

$$S_X^T = S_X, \quad S_X^2 = I. \quad (12)$$

Theorem 3.1 (Binary LM frame normal form). *For every binary connective Θ ,*

$$\boxed{[M_{X\Theta Y}] = S_X[\Theta]S_Y}. \quad (13)$$

Consequently,

$$\boxed{[\Theta] = S_X[M_{X\Theta Y}]S_Y}. \quad (14)$$

The reconstruction identity holds in the formula Boolean ring and therefore does not require an all-true valuation of X and Y .

Proof. The upper-left entry of $S_X[\Theta]S_Y$ is the disjoint-minterm expansion

$$\Theta_{11}XY \uplus \Theta_{10}X\neg Y \uplus \Theta_{01}\neg XY \uplus \Theta_{00}\neg X\neg Y,$$

which is $X\Theta Y$. The remaining three entries are obtained by reversing the Y polarity, the X polarity, or both. Equation (14) follows from $S_X^2 = S_Y^2 = I$. $\square$

The normal form will also make valuation and logical pairing transparent: valuating S_X gives either I or $[\uplus]$, while multiplication by S_X converts an external formula state into its agreement state relative to X . Orthogonal Boolean expansions and Boolean matrix/inner-product constructions provide close classical mechanisms for such partition-valued decompositions [19, 18]; Equation (13) is used here as a structural normal form for the specific CM/LM polarity architecture, not as a priority claim for orthogonal expansion itself.

3.3 Valuation to correspondence matrices

Let $v : \mathcal{F} \rightarrow \mathbb{B}$ be a Boolean valuation with $v(X) = x$ and $v(Y) = y$.

Theorem 3.2 (LM-to-CM valuation architecture). *For every binary operator Θ and every valuation v with $v(X) = x$, $v(Y) = y$,*

$$v([M_{X\Theta Y}]) = [\uplus]^{1-x}[\Theta][\uplus]^{1-y}. \quad (15)$$

If X, Y are free reference generators, the all-true valuation $v_T(X) = v_T(Y) = 1$ exists and gives

$$v_T([M_{X\Theta Y}]) = [\Theta].$$

For substituted reference formulas U, V , the corresponding all-true specialization is available only when U and V are jointly satisfiable; Equation (15) remains valid for every actual valuation regardless.

Proof. Apply v to the frame normal form. Since

$$v(S_X) = [\Downarrow]^{1-x}, \quad v(S_Y) = [\Downarrow]^{1-y},$$

Equation (15) follows immediately from Equation (13). $\square$

This map is conceptually important because it connects two different types of object without changing the logical operator: a symbolic polarity matrix becomes the numeric CM for the same connective. It is not a Möbius transform and does not produce ANF coefficients.

4 Logical pairing

For a formula $A \in \mathcal{F}$, define

$$|A\rangle = \begin{bmatrix} A \\ \neg A \end{bmatrix}, \quad \langle A| = \begin{bmatrix} A & \neg A \end{bmatrix}.$$

The Boolean contraction of two formula states is XNOR/equivalence:

$$\langle A|B\rangle = (A \wedge B) \Downarrow (\neg A \wedge \neg B) \equiv A \Leftrightarrow B. \quad (16)$$

Theorem 4.1 (Logical-pairing identity). *For every binary logical operator Θ and formulas A, B, X, Y ,*

$$\langle A|[M_{X\Theta Y}]|B\rangle \equiv (A \Leftrightarrow X) \Theta (Y \Leftrightarrow B). \quad (17)$$

Proof. The frame matrices turn the external states into agreement states:

$$\langle A|S_X = \langle A \Leftrightarrow X|, \quad S_Y|B\rangle = |Y \Leftrightarrow B\rangle.$$

Using Equation (13) and the numeric/formula selection rule therefore gives

$$\langle A|[M_{X\Theta Y}]|B\rangle = \langle A \Leftrightarrow X|[\Theta]|Y \Leftrightarrow B\rangle \equiv (A \Leftrightarrow X) \Theta (Y \Leftrightarrow B).$$

$\square$

Corollary 4.2 (Labelled basis reconstruction). *For $i, j \in \mathbb{B}$,*

$$\langle X^{(i)}|[M_{X\Theta Y}]|Y^{(j)}\rangle \equiv \Theta_{ij}. \quad (18)$$

Hence the four labelled basis pairings recover the complete truth table and uniquely determine the binary connective. This is an elementary reconstruction statement, not a claim of new quantum tomography.

Example 4.3 (Pairing an implication LM). For $\Theta \Rightarrow$,

$$\langle A|[M_{X \Rightarrow Y}]|B \rangle \equiv (A \Leftrightarrow X) \Rightarrow (Y \Leftrightarrow B).$$

Taking $A = \neg X$ and $B = Y$ gives $0 \Rightarrow 1 = 1$. Taking instead $A = X$ and leaving B arbitrary gives

$$\langle X|[M_{X \Rightarrow Y}]|B \rangle \equiv Y \Leftrightarrow B,$$

so the output records whether the right paired formula agrees with the reference conclusion Y .

Logical pairing and operator-on-operator Boolean superposition are different operations. Pairing places an LM between formula states and returns a formula describing their relationship. Pointwise operator superposition, developed next, uses one or more aligned CMs or LMs themselves as operands of another Boolean operation and returns a new operator. Ordinary XOR–AND matrix composition is treated separately.

Theorem 4.4 (Valuation commutes with logical pairing). *For every valuation v ,*

$$v(\langle A|[M_{X \Theta Y}]|B \rangle) = \langle v(A)|v([M_{X \Theta Y}])|v(B) \rangle. \quad (19)$$

Proof. The pairing is built from complement, conjunction, and XOR, all preserved by Boolean valuation. $\square$

Valuation therefore acts as a semantics-preserving bridge: one may pair formulas symbolically and then valuate, or valuate the LM and states first and perform the corresponding numeric contraction.

4.1 Partition selectors and preservation of Boolean operations

Logical pairing is a special case of a more general selector mechanism. Let I be a finite index set and let $w_i \in \mathcal{F}$ be selector weights. Define

$$q_w(T) := \biguplus_{i \in I} w_i \wedge T_i, \quad T \in \mathcal{F}^I. \quad (20)$$

Theorem 4.5 (Partition-of-unity selector characterization). *Suppose the weights satisfy*

$$w_i \wedge w_j = 0 \quad (i \neq j), \quad \biguplus_{i \in I} w_i = 1. \quad (21)$$

Then q_w is a unital Boolean-algebra homomorphism from the pointwise Boolean algebra $\mathcal{F}^I$ to $\mathcal{F}$: it preserves $\biguplus$, $\wedge$, complement, and therefore every Boolean term operation. Conversely, among $\mathcal{F}$ -linear maps of the form (20), unital Boolean-algebra homomorphisms have exactly such partition-of-unity weights.

Proof. XOR preservation is immediate. For conjunction,

$$q_w(T) \wedge q_w(U) = \biguplus_{i,j} (w_i \wedge w_j \wedge T_i \wedge U_j) = \biguplus_i w_i \wedge T_i \wedge U_i = q_w(T \wedge U),$$

because the cross terms vanish. Equation (21) gives $q_w(1) = 1$, so complement is preserved as well. Conversely, the coordinate idempotents force pairwise orthogonality and unitality forces the weights to sum to 1. $\square$

For binary logical pairing the four weights are

$$A^{(r)} \wedge B^{(s)}, \quad (r, s) \in \mathbb{B}^2.$$

They form a Boolean partition of unity even when A and B are dependent formulas. This theorem is the structural reason pairing can be moved through an arbitrary pointwise outer Boolean operation later in the coherence theorem; no special distributive law for that outer operation is required.

5 Formula-valued operators as operands: aligned Boolean superposition

The historical manuscript emphasized a same-operands result: once two subexpressions have the same ordered operand frame, the represented operators may themselves be operands of another Boolean connective [10]. The raw numeric truth-table law has direct antecedents: Cheng, Zhao, and Xu state for truth vectors on the same ordered variables that an arbitrary binary outer operation acts entrywise [6, Prop. 3.3]. The present paper therefore treats the CM identity as established numerical structure and places the formula-valued LM statement first.

The reason the LM formulation is useful is that it makes the symbolic operands, their reference frame, and their later valuation explicit. A pointwise outer operation is sound only when corresponding cells describe the same logical polarity state. Frame agreement is therefore part of the type contract rather than an informal convention.

For formula-valued matrices M_1, M_2 in one declared frame and a binary Boolean connective Φ , define

$$(M_1 \hat{\Phi} M_2)_{rs} := (M_1)_{rs} \Phi (M_2)_{rs}. \quad (22)$$

The same notation is used after valuation for numeric CMs. This is not matrix multiplication; it is the outer connective Φ applied cell by cell.

Theorem 5.1 (Aligned LM operator superposition and CM valuation). *Let Θ_1, Θ_2 be binary connectives represented in the same reference frame (X, Y) , and define the derived connective Ω by*

$$x\Omega y := (x\Theta_1 y)\Phi(x\Theta_2 y). \quad (23)$$

Then the formula-valued operators satisfy

$$\boxed{[M_{X\Omega Y}] = [M_{X\Theta_1 Y}] \hat{\Phi} [M_{X\Theta_2 Y}].} \quad (24)$$

For every valuation v ,

$$v([M_{X\Omega Y}]) = v([M_{X\Theta_1 Y}]) \hat{\Phi} v([M_{X\Theta_2 Y}]). \quad (25)$$

For free reference generators under the all-true valuation this reduces to the numeric CM identity

$$\boxed{[\Omega] = [\Theta_1] \hat{\Phi} [\Theta_2].} \quad (26)$$

Consequently, for bits $x, y \in \mathbb{B}$,

$$\boxed{(x\Theta_1 y) \Phi (x\Theta_2 y) = \langle x | ([\Theta_1] \hat{\Phi} [\Theta_2]) | y \rangle.} \quad (27)$$

Proof. Each LM cell is a formula in one fixed polarity position. Applying Φ to corresponding cells therefore gives the polarity orbit of the derived connective Ω , proving (24). Boolean valuation is a homomorphism, giving (25); the all-true specialization yields (26). Finally, one-hot CM selection gives (27). $\square$

Corollary 5.2 (Alignment before operator superposition). *Suppose two LM or CM occurrences arrive in signed frames F_1, F_2 and typed frame transforms T_1, T_2 transport them to one common frame F . Their sound pointwise combination in frame F is*

$$(T_1 M_1) \hat{\Phi} (T_2 M_2),$$

or, after valuation,

$$(T_1[\Theta_1]) \hat{\Downarrow} (T_2[\Theta_2]).$$

The operation is generally unsound if the same array position refers to different assignments before alignment.

Example 5.3 (Why the frame condition matters). Consider $(X \Rightarrow Y) \hat{\Downarrow} (Y \Rightarrow X)$. Each local connective is implication, but the second occurrence uses the reversed operand frame (Y, X) . Naively applying XOR to the two unaligned arrays would give the zero matrix. Transporting the second occurrence to the common (X, Y) frame gives $[\Rightarrow]^T$, and

$$[\Rightarrow] \hat{\Downarrow} [\Rightarrow]^T = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix} = [\Downarrow],$$

which correctly represents

$$(X \Rightarrow Y) \hat{\Downarrow} (Y \Rightarrow X) = X \hat{\Downarrow} Y.$$

The same alignment requirement applies to the formula-valued LMs before superposition. This isolates the practical value of the typed frame contract from the classical pointwise-combination identity itself.

Example 5.4 (LM operators as first-class operands). In ordinary propositional logic,

$$(X \vee Y) \hat{\Downarrow} (X \wedge Y) = X \hat{\Downarrow} Y.$$

At the symbolic operator level the same calculation is

$$[M_{X \vee Y}] \hat{\Downarrow} [M_{X \wedge Y}] = [M_{X \hat{\Downarrow} Y}]. \quad (28)$$

Valuating either before or after Equation (28) gives

$$[\vee] \hat{\Downarrow} [\wedge] = [\hat{\Downarrow}]$$

in the corresponding valued frame. Thus the LM operators themselves—not merely their evaluated truth vectors—serve as operands of the outer Boolean operation, while valuation preserves the result.

The raw numeric equality is therefore not the novelty claim. The structural focus is that formula-valued logical operators can be combined as first-class operands in a typed common frame, and the resulting symbolic operation is transported coherently through valuation and, as proved later, through logical pairing and higher-arity LM lifts.

5.1 A distinct operation: matched-intermediate-frame matrix composition

Pointwise superposition should not be confused with XOR–AND matrix multiplication. The frame normal form nevertheless yields a separate clean law when the output reference frame of one LM is the input reference frame of the next.

Theorem 5.5 (Matched-frame kernel composition). *Let Θ, Ψ be binary connectives and define Ω by the XOR–AND matrix product*

$$[\Omega] := [\Theta][\Psi], \quad x\Omega z := \hat{\Downarrow}_{y \in \mathbb{B}} (x\Theta y) \wedge (y\Psi z). \quad (29)$$

Then, over the formula Boolean ring,

$$\boxed{[M_{X\Theta Y}][M_{Y\Psi Z}] = [M_{X\Omega Z}].} \quad (30)$$

Proof. Using the frame normal form and $S_Y^2 = I$,

$$[M_{X\Theta Y}][M_{Y\Psi Z}] = S_X[\Theta]S_Y S_Y[\Psi]S_Z = S_X([\Theta][\Psi])S_Z = [M_{X\Omega Z}].$$

□

This is parity-based kernel composition through the matched intermediate frame Y . It is neither existential relational composition nor the pointwise outer operation $\widehat{\Phi}$. Without a matched intermediate frame, arbitrary products of formula-valued LMs need not remain in the same fixed-frame LM family.

6 Higher-arity correspondence and logical tensors

The binary notation extends to arbitrary finite arity. The primary higher-arity object is a 2^n -entry tensor; a matrix appears after a declared bipartition of the variables.

6.1 Canonical Boolean term extension

Let $\mathcal{B}_n$ be the set of Boolean functions $f : \mathbb{B}^n \rightarrow \mathbb{B}$, and let $\mathcal{F}_{\mathbf{X}}$ denote the Boolean algebra of formulas generated by $\mathbf{X} = (X_1, \dots, X_n)$ modulo logical equivalence. Every such function has a canonical disjoint-minterm extension to formulas:

$$\tilde{f}(A_1, \dots, A_n) := \biguplus_{\alpha \in \mathbb{B}^n} f(\alpha) \wedge \bigwedge_{i=1}^n A_i^{\langle \alpha_i \rangle}. \quad (31)$$

Distinct minterms are logically disjoint, so OR could replace XOR in this one expansion without changing its Boolean meaning. The XOR form keeps the expression inside the declared $\mathbb{F}_2$ coefficient calculus.

6.2 Correspondence and logical tensors

Index assignments by $\alpha = (\alpha_1, \dots, \alpha_n) \in \mathbb{B}^n$, using true-first order on every axis.

Definition 6.1 (Correspondence tensor). The correspondence tensor of f is

$$\mathcal{C}_f[\alpha] := f(\alpha). \quad (32)$$

It has shape $2 \times \dots \times 2$ and exactly 2^n Boolean entries. For a binary connective Θ , displaying $\mathcal{C}_{f_\Theta}$ as a 2×2 matrix gives the abbreviated notation $[\Theta]$.

Definition 6.2 (Logical tensor and LM lift). For formal variables $\mathbf{X} = (X_1, \dots, X_n)$ define

$$\mathcal{M}_f(\mathbf{X})[\alpha] := \tilde{f}(X_1^{\langle \alpha_1 \rangle}, \dots, X_n^{\langle \alpha_n \rangle}). \quad (33)$$

Equivalently define the LM lift

$$\mathcal{L}_{\mathbf{X}} : \mathcal{B}_n \longrightarrow \mathcal{F}_{\mathbf{X}}^{\mathbb{B}^n}, \quad \mathcal{L}_{\mathbf{X}}(f) := \mathcal{M}_f(\mathbf{X}). \quad (34)$$

The binary object $[M_{X\Theta Y}]$ is the case $n = 2$ and $f = f_\Theta$.

Remark 6.3 (The lift as a polarity pullback). If formulas in $\mathcal{F}_{\mathbf{X}}$ are identified with their Boolean functions of an assignment $x \in \mathbb{B}^n$, then

$$\mathcal{M}_f(x, \alpha) = f(x \uparrow \alpha \uparrow \mathbf{1}). \quad (35)$$

Thus the LM lift is a concrete polarity pullback of the ordinary truth function. This makes clear why its injectivity and equivariance are standard function-algebra consequences; the additional content developed here is the typed interaction with valuation, pairing, frame transport, and operator superposition.

Define the higher contraction

$$\mathcal{E}_{\mathcal{C}}(x_1, \dots, x_n) = \biguparrow_{\alpha \in \mathbb{B}^n} \mathcal{C}[\alpha] \wedge \bigwedge_{i=1}^n \chi_{x_i}(\alpha_i). \quad (36)$$

Exactly one one-hot product survives, so $\mathcal{E}_{\mathcal{C}_f}(x) = f(x)$.

For $\delta \in \mathbb{B}^n$, define the one-triggered axis-reversal operator

$$(\pi_{\delta}T)[\alpha] := T[\alpha \uparrow \delta], \quad (37)$$

where $\uparrow$ is componentwise on assignment indices. Thus $\delta_i = 1$ means that axis i is reversed.

Theorem 6.4 (General valuation theorem). *If $v(X_i) = x_i$ and $\mathbf{1} = (1, \dots, 1)$, then*

$$v(\mathcal{M}_f(\mathbf{X})) = \pi_{\mathbf{1} \uparrow x} \mathcal{C}_f. \quad (38)$$

In particular, for the free reference generators the all-true valuation satisfies

$$v_{\mathbf{1}}(\mathcal{L}_{\mathbf{X}}(f)) = \mathcal{C}_f.$$

Proof. At polarity index α , the valued argument $X_i^{(\alpha_i)}$ equals the bit $\alpha_i \uparrow (1 \uparrow x_i)$. Hence the valued tensor entry is $\mathcal{C}_f[\alpha \uparrow (\mathbf{1} \uparrow x)]$, which is exactly Equation (38). $\square$

6.3 LM orbit lift and Boolean superposition

Definition 6.5 (Pointwise lift). For $g : \mathbb{B}^m \rightarrow \mathbb{B}$ and tensors $T_1, \dots, T_m$ with the same index set, define

$$\widehat{g}(T_1, \dots, T_m)[\alpha] := g(T_1[\alpha], \dots, T_m[\alpha]).$$

For formula-valued tensors, g is interpreted through its canonical Boolean term extension.

Theorem 6.6 (LM lift and superposition law). *For every n , the map $\mathcal{L}_{\mathbf{X}}$ is injective and preserves arbitrary Boolean superposition. If $f_1, \dots, f_m \in \mathcal{B}_n$, $g : \mathbb{B}^m \rightarrow \mathbb{B}$, and*

$$h(x) = g(f_1(x), \dots, f_m(x)),$$

then

$$\mathcal{C}_h = \widehat{g}(\mathcal{C}_{f_1}, \dots, \mathcal{C}_{f_m}), \quad (39)$$

$$\mathcal{L}_{\mathbf{X}}(h) = \widehat{g}(\mathcal{L}_{\mathbf{X}}(f_1), \dots, \mathcal{L}_{\mathbf{X}}(f_m)). \quad (40)$$

Hence the image of $\mathcal{L}_{\mathbf{X}}$ is closed under every pointwise Boolean operation.

Proof. The identities hold at each assignment/polarity index by substitution into g . For injectivity, if $\mathcal{L}_{\mathbf{X}}(f) = \mathcal{L}_{\mathbf{X}}(h)$, apply the all-true valuation. Equation (38) gives $\mathcal{C}_f = \mathcal{C}_h$, so $f = h$. $\square$

Corollary 6.7 (The LM image is a Boolean subalgebra). *For fixed arity n , $\text{Im}(\mathcal{L}_{\mathbf{X}})$ is a Boolean subalgebra of the pointwise formula-tensor algebra $\mathcal{F}_{\mathbf{X}}^{\mathbb{B}^n}$ and is isomorphic to the Boolean algebra $\mathcal{B}_n$ of n -ary Boolean functions. Under the identification of a function with its truth tensor, all-true valuation is the inverse of the lift on this image.*

Remark 6.8 (Priority boundary for the orbit lift). The map $f \mapsto (\tau_{\mathbf{1} \uparrow \alpha} f)_{\alpha \in (C_2)^n}$ is an instance of standard function-algebra/group-action structure associated with the polarity group [20]: an equivariant orbit-valued object is determined by its value at the identity element. Injectivity, orbit generation, and the resulting equivariance are therefore used here to identify the LM image cleanly, not as standalone novelty claims. The distinctive question for the present framework is what additional operations—valuation to CMs, logical pairing, typed frame transport, and Boolean superposition of the operators themselves—coexist on that orbit object and satisfy common coherence laws.

6.4 Polarity-equivariance characterization

For $\delta \in \mathbb{B}^n$, let τ_{δ} negate X_i exactly when $\delta_i = 1$. Write $\alpha \uparrow \delta$ for componentwise XOR of polarity indices.

Theorem 6.9 (Polarity-equivariance characterization). *Every LM lift satisfies*

$$\tau_{\delta}(\mathcal{L}_{\mathbf{X}}(f)[\alpha]) \equiv \mathcal{L}_{\mathbf{X}}(f)[\alpha \uparrow \delta]. \quad (41)$$

Conversely, a formula tensor $T \in \mathcal{F}_{\mathbf{X}}^{\mathbb{B}^n}$ belongs to the image of $\mathcal{L}_{\mathbf{X}}$ if and only if it satisfies (41) for every α, δ .

Proof. Negating X_i flips exactly the i th polarity choice, proving the forward identity. Conversely, an equivariant tensor is determined by its all-positive cell $T[\mathbf{1}]$. That formula defines an n -ary Boolean function f modulo logical equivalence, and equivariance reconstructs every other cell as the corresponding polarity substitution, hence $T = \mathcal{L}_{\mathbf{X}}(f)$. $\square$

This characterization is stronger than merely observing a “negative dual” matrix, but its group-theoretic mechanism is standard: an equivariant orbit is determined by one reference element. Its value here is classificatory. It gives an intrinsic membership test for formula-valued LMs, shows that the entire 2^n -cell symbolic object is generated from one reference formula by polarity changes, and makes closure under pointwise Boolean superposition transparent.

Remark 6.10 (Boolean clones and superposition). A Boolean clone is a family of finitary Boolean functions containing projections and closed under superposition. Equations (39)–(40) say that the LM lifts respect ordinary superposition whenever the displayed functions share the declared input arity: compose functions first and lift later, or lift the constituent functions and compose the operators pointwise. A fully internal clone representation across arities would additionally specify the projection operators and cross-arity substitution maps. That universal-algebra formulation is a natural extension rather than a prerequisite here [21].

Remark 6.11 (Valuation as an intertwining map). The phrase *intertwining* means that a map respects two parallel actions. Here positive valuation intertwines symbolic polarity change with numeric axis reversal:

$$v_1(\tau_{\delta} \mathcal{L}_{\mathbf{X}}(f)) = \pi_{\delta} \mathcal{C}_f,$$

and valuation also respects every pointwise superposition:

$$v(\widehat{g}(T_1, \dots, T_m)) = \widehat{g}(vT_1, \dots, vT_m).$$

Thus the symbolic and numeric levels are not merely analogous; the declared operations are carried consistently from one level to the other.

Theorem 6.12 (CM/LM coherence under Boolean operator superposition). *Let $M_1, \dots, M_m$ be formula-valued logical tensors in the same declared frame, let $g : \mathbb{B}^m \rightarrow \mathbb{B}$, and let $\widehat{g}$ act pointwise. Then the following operations are compatible with operator superposition.*

1. Lift: if $M_i = \mathcal{L}_{\mathbf{X}}(f_i)$ and $h = g(f_1, \dots, f_m)$, then

$$\mathcal{L}_{\mathbf{X}}(h) = \widehat{g}(M_1, \dots, M_m).$$

2. Valuation: for every Boolean valuation v ,

$$v(\widehat{g}(M_1, \dots, M_m)) = \widehat{g}(vM_1, \dots, vM_m).$$

3. Common input-frame change: for every common signed input reindexing T (permutation and/or input polarity reversal, excluding output complement),

$$T\widehat{g}(M_1, \dots, M_m) = \widehat{g}(TM_1, \dots, TM_m),$$

with the corresponding variable substitution on the symbolic level.

4. Logical pairing: in the binary case, for formula states A, B and pairing map $\mathfrak{p}_{A,B}(M) := \langle A|M|B \rangle$,

$$\mathfrak{p}_{A,B}(\widehat{g}(M_1, \dots, M_m)) \equiv \widetilde{g}(\mathfrak{p}_{A,B}(M_1), \dots, \mathfrak{p}_{A,B}(M_m)).$$

Thus Boolean operations may be performed on the aligned operators themselves without creating an inconsistency between symbolic LM semantics, numeric CM semantics, frame transport, and logical pairing.

Proof. The lift, valuation, and common input-frame statements hold pointwise. Logical pairing is the partition selector q_w of Equation (20) with weights supplied by the formula states. The partition-of-unity selector theorem therefore preserves every Boolean term operation, including the canonical term $\widetilde{g}$, which proves the fourth identity directly. $\square$

Remark 6.13 (Output complement is a different symmetry). Output negation is not one of the unchanged- g input-frame actions in the theorem. If

$$g^d(b_1, \dots, b_m) := \neg g(\neg b_1, \dots, \neg b_m),$$

then

$$\neg \widehat{g}(M_1, \dots, M_m) = \widehat{g^d}(\neg M_1, \dots, \neg M_m).$$

In general one cannot complement every input and the output while leaving the same outer operation g unchanged.

Remark 6.14 (Pairing preserves the LM operator calculation). Applying Theorem 6.12 to the LM superposition example in Equation (28) gives, for arbitrary formula states A, B ,

$$\langle A|[M_{X \uparrow Y}]|B \rangle \equiv \langle A|[M_{X \vee Y}]|B \rangle \uparrow \langle A|[M_{X \wedge Y}]|B \rangle.$$

Thus the same LM operator computation survives not only valuation but also relational pairing.




Figure 2: LM-centered coherence under valuation. The same outer Boolean operation may be applied to aligned formula-valued operators before valuation or to their valued CMs afterward. Logical pairing and common input-frame pullbacks satisfy analogous squares because they are Boolean homomorphisms on the pointwise operator algebra.

6.5 Higher-arity logical pairing

For formula tuples $\mathbf{A} = (A_1, \dots, A_n)$ define

$$\mathcal{P}_f(\mathbf{A}; \mathbf{X}) = \biguplus_{\alpha \in \mathbb{B}^n} \mathcal{M}_f(\mathbf{X})[\alpha] \wedge \bigwedge_{i=1}^n A_i^{\langle \alpha_i \rangle}. \quad (42)$$

Theorem 6.15 (Higher-arity pairing and reconstruction). *For every $f : \mathbb{B}^n \rightarrow \mathbb{B}$,*

$$\mathcal{P}_f(\mathbf{A}; \mathbf{X}) \equiv \tilde{f}(A_1 \Leftrightarrow X_1, \dots, A_n \Leftrightarrow X_n). \quad (43)$$

Valuation commutes with this contraction. Moreover, for each assignment $\beta \in \mathbb{B}^n$,

$$\mathcal{P}_f((X_1^{\langle \beta_1 \rangle}, \dots, X_n^{\langle \beta_n \rangle}); \mathbf{X}) \equiv f(\beta), \quad (44)$$

so the complete labelled basis-pairing table reconstructs the truth tensor.

Proof. The weights $\bigwedge_i A_i^{\langle \alpha_i \rangle}$ form a Boolean partition of unity indexed by α . The partition-selector theorem therefore evaluates the logical tensor at the tuple of agreement bits, yielding Equation (43); valuation preservation follows from the same homomorphism property. Setting $A_i = X_i^{\langle \beta_i \rangle}$ makes the i th agreement bit equal to the constant β_i , proving Equation (44). $\square$

7 Matrix flattenings and higher-dimensional CMs

A tensor becomes a matrix after the variables are split into a row block and a column block. This is the clean higher-dimensional generalization of the binary CM, and it also answers a terminology question: a matrix need not be square to act as a typed map.

Let $R = (i_1, \dots, i_p)$ and $C = (j_1, \dots, j_q)$ be an ordered partition of $\{1, \dots, n\}$, with $p + q = n$. For row bits $r \in \mathbb{B}^p$ and column bits $c \in \mathbb{B}^q$, let

$$\text{assemble}_{R|C}(r, c) \in \mathbb{B}^n$$




Figure 3: The LM embedding is faithful because all-true valuation recovers the numeric correspondence tensor. Boolean superposition may be performed before or after the lift.

be the unique complete assignment whose coordinates i_a equal r_a and whose coordinates j_b equal c_b . This explicit assembly map avoids any ambiguity when the two blocks are noncontiguous or use a nonstandard order.

Definition 7.1 (Correspondence-map flattening). The $(R \mid C)$ flattening is the $2^p \times 2^q$ array

$$[f]_{R|C}[r, c] := f(\text{assemble}_{R|C}(r, c)). \quad (45)$$

Its formula-valued counterpart $[M_f(\mathbf{X})]_{R|C}$ is defined by the same ordered assembly of the logical tensor. Computationally this is an axis permutation followed by a reshape of $\mathcal{C}_f$.

The notation $[\Theta]$ remains reserved as the binary shorthand. For higher arity, the subscript $R \mid C$ is preferable to a bare size such as $[\Theta]_4$: two different constructions can both be 4×4 while having different types. In particular, a four-variable $2 \mid 2$ correspondence map is not the same object as the 4×4 coefficient-permutation matrix introduced later to rotate the four cells of a binary CM.

Under XOR–AND multiplication, $[f]_{R|C}$ is a linear map

$$\mathbb{F}_2^{2^q} \longrightarrow \mathbb{F}_2^{2^p}.$$

It is an endomorphism only when $p = q$. We use “operator” in the broad typed sense of an acting map; when strict endomorphism terminology matters, we say *correspondence map* for a rectangular flattening.

Let

$$|x_R\rangle = \bigotimes_{k=1}^p |x_{i_k}\rangle, \quad |x_C\rangle = \bigotimes_{\ell=1}^q |x_{j_\ell}\rangle.$$

These Kronecker products are one-hot states of lengths 2^p and 2^q .

Theorem 7.2 (Rectangular bra–map–ket selection). *For every bipartition $R \mid C$,*

$$\langle x_R | [f]_{R|C} | x_C \rangle = f(x_1, \dots, x_n). \quad (46)$$

Thus square shape is not required for a scalar bra–matrix–ket contraction; the left and right state spaces simply have different dimensions when $p \neq q$.

Proof. The grouped row and column states are one-hot and select the single matrix entry indexed by the complete assignment. $\square$

Remark 7.3 (Comparison with quantum terminology). In ordinary linear algebra, a rectangular matrix is a linear map between different vector spaces, whereas a square matrix is an endomorphism. Quantum observables and POVM effects on one Hilbert space are square; more general quantum processes can involve maps between input and output spaces of different dimensions. A tensor reshaping does not automatically preserve a physical-observable interpretation. The present Boolean construction requires only the typed linear-map statement in (46), not a quantum measurement analogy.

Remark 7.4 (Exact size boundary). The tensor, a length- 2^n truth vector, and every $2^p \times 2^q$ flattening contain the same 2^n Boolean entries. Reshaping may change computational locality, cache behavior, or available algorithms, but it does not compress an arbitrary truth relation. Any benchmark advantage of rectangular rather than square flattenings is therefore an implementation result rather than a smaller information content.




Figure 4: Higher-dimensional CMs are typed matrix flattenings of the same 2^n -entry correspondence tensor. Rectangular maps remain valid operands in a bra-map-ket contraction.

8 Building higher-dimensional operators from lower-dimensional ones

Let $g : \mathbb{B}^p \rightarrow \mathbb{B}$ and $h : \mathbb{B}^q \rightarrow \mathbb{B}$ act on disjoint variable blocks, and let Θ be a binary outer connective. If t_g, t_h are the true-first truth vectors, define

$$\mathcal{O}_\Theta(t_g, t_h)[a, b] := t_g[a] \Theta t_h[b]. \quad (47)$$

For formula variables on the two blocks, let $\mathbf{X}_A^{(a)}$ denote componentwise polarity substitution, so its i th component is $X_i^{(a_i)}$. Define the polarity vectors

$$\ell_g(\mathbf{X}_A)[a] := \tilde{g}(\mathbf{X}_A^{(a)}), \quad \ell_h(\mathbf{X}_B)[b] := \tilde{h}(\mathbf{X}_B^{(b)}). \quad (48)$$

Theorem 8.1 (Block-lift theorem). *If*

$$f(a, b) = g(a) \Theta h(b),$$

then

$$[f]_{A|B} = \mathcal{O}_\Theta(t_g, t_h), \quad (49)$$

$$[M_f(\mathbf{X})]_{A|B} = \mathcal{O}_{\tilde{\Theta}}(\ell_g(\mathbf{X}_A), \ell_h(\mathbf{X}_B)). \quad (50)$$

Valuation commutes with both constructions.

Proof. At the entry indexed by (a, b) , the numeric right side is $g(a)\Theta h(b) = f(a, b)$. The formula-valued statement is the same identity after polarity substitution, and valuation preserves Θ . $\square$

Theorem 8.2 (Rank and conjunctive/XOR separability). *For a fixed bipartition $A \mid B$:*

1. $f(a, b) = g(a) \wedge h(b)$ for some Boolean functions g, h if and only if

$$\text{rank}_{\mathbb{F}_2}[f]_{A|B} \leq 1.$$

For a nonzero function the factorization is the ordinary rank-one factorization

$$[f]_{A|B} = t_g t_h^T, \tag{51}$$

and over $\mathbb{F}_2$ the nonzero factors are unique.

2. *More generally, the minimum k for which*

$$f(a, b) = \biguplus_{i=1}^k g_i(a) \wedge h_i(b) \tag{52}$$

equals $\text{rank}_{\mathbb{F}_2}[f]_{A|B}$.

The formula-valued flattening of a rank-one term factorizes analogously as the outer product of the two polarity vectors.

Proof. A conjunctive factor $g(a) \wedge h(b)$ has matrix $t_g t_h^T$ and therefore rank at most one. Conversely, every nonzero rank-one matrix over $\mathbb{F}_2$ is uv^T for nonzero Boolean vectors u, v , which are the truth vectors of unique Boolean functions on the two blocks; the zero matrix is obtained by taking one factor identically zero. For the second statement, every summand in (52) has rank at most one, so k is at least the matrix rank. A rank factorization supplies exactly that many rank-one outer products, proving equality. $\square$

This gives a precise modern form of the separability/factorization idea already present in the original LM manuscript [10]. The statement concerns ordinary $\mathbb{F}_2$ rank and XOR decomposition, not the different OR-based notion usually called Boolean rank. The value also depends on the chosen bipartition: repartitioning the variables can change the flattening rank.

Example 8.3 (A 4×4 correspondence map). Let

$$g(W, X) = W \uplus X, \quad h(Y, Z) = \neg Y \wedge Z, \quad f = g \Rightarrow h.$$

In true-first order $(11, 10, 01, 00)$,

$$t_g = (0, 1, 1, 0), \quad t_h = (0, 0, 1, 0).$$

The $2 \mid 2$ block lift gives

$$[f]_{(W,X)|(Y,Z)} = \begin{bmatrix} 1 & 1 & 1 & 1 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 1 & 0 \\ 1 & 1 & 1 & 1 \end{bmatrix}. \tag{53}$$

This recovers the useful content of the historical four-variable construction without claiming that four variables intrinsically require a unique 4×4 shape.

9 Signed variable frames in arbitrary arity

For numeric truth tensors, input permutations and polarity changes form the signed-permutation action. Let $\sigma \in S_n$ and $\epsilon \in \mathbb{B}^n$, and define

$$\phi_{\sigma,\epsilon}(x)_i = x_{\sigma(i)} \uparrow \epsilon_i. \quad (54)$$

Define the numeric pullback $T_{\sigma,\epsilon}$ by

$$(T_{\sigma,\epsilon}C)[x] := C[\phi_{\sigma,\epsilon}(x)].$$

With this convention the pullbacks form a right action: $T_\phi T_\psi = T_{\psi \circ \phi}$. This fixes the composition direction rather than leaving it implicit.

Theorem 9.1 (Signed-frame action). *For every $f : \mathbb{B}^n \rightarrow \mathbb{B}$,*

$$C_{f \circ \phi_{\sigma,\epsilon}} = T_{\sigma,\epsilon} C_f. \quad (55)$$

The transformations form the standard signed-permutation group $(C_2)^n \rtimes S_n$ on the input frame. Output negation is a separate C_2 action on the coefficients.

Under a matrix flattening, the same action appears as row/column permutations, transpositions or block transpositions, and—when a variable moves across the chosen bipartition—a reshape. The symbolic LM level carries the corresponding variable renaming and polarity substitution.

Theorem 9.2 (Frame changes commute with pointwise composition). *For any common numeric reindexing T and outer Boolean operation g ,*

$$T \hat{g}(C_{f_1}, \dots, C_{f_m}) = \hat{g}(TC_{f_1}, \dots, TC_{f_m}). \quad (56)$$

The formula-valued version holds when the same frame change includes the corresponding variable relabeling/polarity substitution.

9.1 Relation to NPN transformations

NPN stands for *input Negation, input Permutation, output Negation*. Two Boolean functions are NPN-equivalent when one can be obtained from the other by these transformations. NPN classification is standard in logic synthesis, where it is useful for canonicalizing small truth functions and reusing optimized implementations [16, 17].

For binary CMs the transformations are visually explicit:

input permutation	$[\Theta] \mapsto [\Theta]^T,$
negate left input	$[\Theta] \mapsto [\uparrow][\Theta],$
negate right input	$[\Theta] \mapsto [\Theta][\uparrow],$
negate output	$[\Theta] \mapsto J \uparrow [\Theta] \text{ entrywise.}$

Thus the CM frame calculus realizes the binary NPN moves as simple matrix transformations. This is useful for frame normalization and comparison, but the existence of NPN equivalence itself is not a novelty claim.

10 Relationship to ANF and other coordinate representations

The CM/LM architecture should not be confused with an algebraic-normal-form coefficient vector. A correspondence tensor stores truth values; ANF stores coefficients of square-free monomials. The two are related by Boolean Möbius inversion.

Write

$$f(x_1, \dots, x_n) = \biguplus_{S \subseteq [n]} a_S \bigwedge_{i \in S} x_i. \quad (57)$$

If $t_T = f(1_T)$ denotes the truth value on the assignment whose support is T , then

$$t_T = \biguplus_{S \subseteq T} a_S, \quad a_S = \biguplus_{T \subseteq S} t_T. \quad (58)$$

Proposition 10.1 (Top ANF coefficient as correspondence parity). *For every Boolean function of positive arity $n \geq 1$,*

$$a_{[n]} = \biguplus_{x \in \mathbb{B}^n} f(x). \quad (59)$$

Hence $\deg f = n$ if and only if the correspondence tensor has odd Hamming weight.

Proof. The second relation in (58), applied to $S = [n]$, XORs every truth value. The coefficient $a_{[n]}$ is one exactly when the full monomial is present. $\square$

Corollary 10.2 (Binary nonlinearity parity criterion). *For the binary correspondence matrix*

$$[f]_{X|Y} = \begin{bmatrix} f_{11} & f_{10} \\ f_{01} & f_{00} \end{bmatrix},$$

the coefficient of XY is

$$a_{XY} = f_{11} \uplus f_{10} \uplus f_{01} \uplus f_{00}.$$

Thus a two-variable Boolean function has algebraic degree exactly 2 if and only if its CM has odd Hamming weight.

This parity result belongs naturally in a CM/LM foundations paper because it relates an immediately visible operator invariant to ordinary Boolean degree. A stronger statement available in the separate cyclic-lift program says that, after the four truth coefficients are embedded into a particular rotation-generated algebra, the same parity becomes the unit criterion. That conclusion depends on the additional algebra and is not used here.

For two variables, one may also compare with an STP logical structure matrix. Under the common delta encoding $1 \mapsto (1, 0)^T$, $0 \mapsto (0, 1)^T$ and column order $(11, 10, 01, 00)$, if

$$t = \text{vec}([f]_{X|Y}) = (f_{11}, f_{10}, f_{01}, f_{00}),$$

then one binary-output structure matrix is

$$M_f^{\text{STP}} = \begin{bmatrix} t \\ \neg t \end{bmatrix}.$$

This is an external representation of the same truth function, not a component of the formula-valued LM. Likewise ANF coefficients are reached by (58), not by positive valuation.

11 A boundary around literal CM rotation

Literal quarter-turn rotation of a displayed 2×2 CM is already part of the signed frame geometry. It should be distinguished from the later step of imposing a cyclic multiplication on the four coefficient positions.

Define clockwise rotation by

$$\text{rot} \begin{bmatrix} a & b \\ c & d \end{bmatrix} = \begin{bmatrix} c & a \\ d & b \end{bmatrix}. \quad (60)$$

If $[\Theta'] := \text{rot}([\Theta])$, then the associated truth functions satisfy

$$f_{\Theta'}(x, y) = f_{\Theta}(\neg y, x). \quad (61)$$

Thus $\text{rot}^4 = I$ and the quarter turn is a signed coordinate transformation.

To make the coefficient action explicit, use true-first row-major vectorization

$$\text{vec}([\Theta]) = (\Theta_{11}, \Theta_{10}, \Theta_{01}, \Theta_{00})^T.$$

Then the 4×4 permutation matrix

$$\mathcal{R}_{\circlearrowright} := \begin{bmatrix} 0 & 0 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 0 \end{bmatrix} \quad (62)$$

satisfies

$$\mathcal{R}_{\circlearrowright} \text{vec}([\Theta]) = \text{vec}(\text{rot}([\Theta])).$$

For XNOR,

$$\text{vec}([\Leftrightarrow]) = \begin{bmatrix} 1 \\ 0 \\ 0 \\ 1 \end{bmatrix},$$

so

$$\mathcal{R}_{\circlearrowright} \begin{bmatrix} 1 \\ 0 \\ 0 \\ 1 \end{bmatrix} = \begin{bmatrix} 0 \\ 1 \\ 1 \\ 0 \end{bmatrix} = \text{vec}([\Updownarrow]).$$

This is the worked meaning of

$$\mathcal{R}_{\circlearrowright} \text{vec}([\Leftrightarrow]) = \text{vec}([\Updownarrow]).$$

The symbol $\mathcal{R}_{\circlearrowright}$ is intentionally not written as $[\Theta]_4$: it is an operator acting on the four coefficients of a *binary* CM, whereas a 4×4 four-variable correspondence map such as $[f]_{(W,X)|(Y,Z)}$ acts between grouped logical state spaces. Equal matrix size does not imply equal type.

The historical Impax observation also sits naturally here. Since $[\Leftrightarrow]$ and $[\Updownarrow]$ have complementary supports,

$$[\Leftrightarrow] \Updownarrow [\Updownarrow] = J,$$

the all-ones tautological CM. The old overlay glyph may be retained as historical notation, while J or $[\top]$ is algebraically unambiguous.

A separate phase construction begins only after an additional multiplication is imposed on the four cyclic coefficient positions. Identifying those positions with $1, g, g^2, g^3$ and adding cyclic convolution yields

$$\mathbb{F}_2[C_4] \cong \mathbb{F}_2[g]/(g^4 - 1) \cong \mathbb{F}_2[u]/(u^4), \quad u = 1 + g.$$

That convolution is not the original 2×2 CM matrix product, not pointwise conjunction, and not LM pairing. Its units, nilpotents, filtration, interference interpretation, and modal applications therefore belong in the companion phase-algebra paper. The present paper supplies the logical origin of the quarter-turn action.

12 Computational interpretation without a performance claim

The operator calculus has an immediate compiler interpretation. If two subexpressions depend on the same variables but use different operand order or polarity, the signed-frame action can normalize both to one declared frame. Section 5 then permits the outer connective to be evaluated pointwise on their operators. This can collapse repeated Boolean work before later expansion or evaluation.

The companion computational manuscript [11] develops this idea as a typed pair compiler with pure-structural, hybrid-retabulation, whole-retabulation, and fallback paths. The mathematical content needed here is only the invariant: fusion is sound when the operands refer to the same assignments in the same declared frame.

This structural simplification should not be confused with a claim of unique or universal speedup. Packed truth-function optimizers and logic-synthesis methods can perform closely related local reductions, and the raw same-frame pointwise law itself has prior art. The computational question is therefore empirical: whether explicit typed frame recognition and fusion provide a useful implementation boundary on relevant workloads. Timing, memory, comparator design, and any positive or negative performance evidence belong to the companion computational paper and are not used as evidence for the foundations claims here.

13 Relationship to prior operator formalisms and claim boundary

The CM/LM calculus sits among several established representations. Table 1 is a type map rather than a novelty verdict.

13.1 Boolean closure as a claim boundary

Proposition 13.1 (Core Boolean closure). *Starting from a formula-valued LM or logical tensor, polarity substitution, logical-state construction, XOR–AND contraction, pointwise Boolean superposition, block outer composition, support difference, and signed-frame reindexing remain internal to Boolean algebra. After valuation, the corresponding numeric operations remain in $\mathbb{F}_2$.*

Proof. Each symbolic construction is formed from Boolean term operations, substitution, finite indexing, or reindexing. Boolean valuation preserves the term operations and yields only 0 or 1 coefficients. No step requires an extension of the scalar domain. $\square$

No real, complex, negative, or otherwise non-Boolean scalar is needed for the core calculus. This closure is not by itself a historical priority claim. Its value is to state exactly which transformations belong to the CM/LM system before any optional extension—for example the cyclic phase multiplication—is added.

Family	Primary object	Typical operation	Relation here
Boolean matrices	Binary matrices	Boolean products and transformations	Broad Boolean-matrix antecedent [1].
Matrix/vector logic	Truth vectors and matrix gates	Linear or multilinear operator action	Strong antecedent for connective-as-operator viewpoints [2, 3, 4].
Bricken matrix-logic notes	2×2 Boolean relation matrices and two-component truth vectors	Explicit $\langle x B y \rangle$ evaluation, Boolean matrix algebra, complements, transforms, and operations on logical matrices	Internally dated March 1997; direct antecedent for logical bra-matrix-ket notation and binary operator matrices. Public-release chronology remains to be verified [15].
STP logic	2×2^n logical structure matrices	Semi-tensor products and logical structure operations	External numeric representation, not the same type as a formula-valued LM [5, 7].
Boolean matrix calculus	Boolean matrices and truth vectors over XOR/AND	Matrix calculus plus arbitrary binary outer operation on corresponding truth-vector entries	Direct antecedent for the raw same-frame numerical superposition law; Prop. 3.3 states $m_{f\Phi g} = m_f \Phi m_g$ [6].
NPN/LUT synthesis	Packed truth functions and shared DAGs	Input/output phase, input permutation, cut matching	Strong operational antecedent for frame transformations and small-function reuse [16, 17].
ANF	Square-free polynomial coefficients	Möbius transform and polynomial arithmetic	Different coordinates, related by Boolean Möbius inversion.
Eigenlogic	Commuting projectors on interpretation space	Truth values as eigenvalues and logical interpretations as eigenvectors	Direct prior art for spectral logical observables; raw 2×2 CMs have a different $\mathbb{F}_2$ spectrum, while D_Θ gives the diagonal truth-observable bridge [8, 9].
CM/LM calculus	Typed truth tensor plus polarity-equivariant formula tensor	Valuation, pairing, frame transport, aligned pointwise superposition, matched-frame kernel product, and block lift	Integrated object studied in this paper.

Table 1: Representation and operation types. Individual matrix, truth-table, frame, and pointwise operations have substantial prior art; the paper studies their particular integration in the CM/LM architecture.

The strongest defensible mathematical claim of the present draft is therefore architectural and structural rather than a claim that any one elementary operation is new. Numeric correspondence tensors and formula-valued LMs provide two typed realizations of the same Boolean functions; aligned operators can themselves be operands of arbitrary Boolean superposition; and Theorem 6.12 shows that valuation, common frame transport, and logical pairing all respect that superposition. Higher-dimensional block construction and Boolean closure complete the calculus. The orbit-lift and polarity-equivariance theorems identify the symbolic object cleanly, but their underlying group-action mechanism is treated as standard.

14 Discussion

14.1 What makes this a calculus rather than a list of identities

The formula-valued LM is the organizing symbolic object of the calculus. Boolean superposition acts directly on aligned LMs; valuation sends the result to numeric correspondence tensors; signed input-frame changes reindex the symbolic and numeric levels consistently; and logical pairing is itself a Boolean homomorphism for the same pointwise operation. The raw cellwise truth-vector law is classical, but the LM layer records which formulas and polarities each cell means, so the frame condition becomes an explicit semantic type rather than an implicit ordering convention. Theorem 6.12 collects these compatibility laws.

Two structural results explain why the pieces fit. The frame normal form $[M_{X\Theta Y}] = S_X[\Theta]S_Y$ identifies the symbolic polarity matrix as an invertible change of Boolean frame, while the partition-selector theorem explains why pairing preserves arbitrary outer Boolean operations. Ordinary matrix multiplication then has its own matched-intermediate-frame law, separate from pointwise superposition. Together these distinguish a typed calculus from a mere list of matrix-decorated truth identities without claiming a new underlying Boolean algebra.

Higher-dimensional matrices then arise from variable grouping rather than from a new truth domain. The order- n tensor is primary; a $2^p \times 2^q$ matrix is one flattening. This removes ambiguity from historical higher-dimensional descriptions and makes recursive block structure explicit.

14.2 Why the sixteen-element phase algebra is deferred

The cyclic phase algebra is mathematically interesting, but including its full development here would change the paper’s question. The CM/LM calculus uses XOR–AND selection, formula valuation, logical pairing, signed reindexing, and Boolean pointwise/outer composition. The phase construction adds a second multiplication—cyclic convolution of coefficient positions—and with it units, nilpotents, an augmentation filtration, and modal interpretations. Those are valuable consequences of the four-position geometry, but they are not needed to define or prove the CM/LM results above.

The clean paper boundary is therefore:

- this paper proves that literal CM rotation is a logical signed-frame action and develops the CM/LM calculus independent of any phase multiplication;
- the phase paper may begin from that action, choose the cyclic coefficient order, introduce convolution, and study the resulting algebra $\mathbb{F}_2[C_4] \cong \mathbb{F}_2[u]/(u^4)$ and its applications.

This separation lets the phase paper refer back to a fully developed logical foundation rather than forcing the foundations paper to justify a new scalar interpretation.

14.3 Open structural questions

Several directions now become sharply formulable.

1. **Clone and categorical formulation.** The faithful preservation of Boolean superposition suggests a clone-theoretic representation, while valuation and frame actions suggest an equivariant or functorial formulation.
2. **Minimal generating operations.** Which subset of frame actions, pointwise lifts, outer lifts, contractions, support differences, and substitutions generates the full finite CM/LM calculus?

3. **Equivalence and canonical forms.** Signed permutations give one natural orbit relation; NPN equivalence adds output phase. Their relation to formula-level equivalence and efficient canonicalization should be separated carefully.
4. **Higher-dimensional block algorithms.** The block-lift theorem gives a recursive construction of large correspondence matrices. It remains an empirical question when a symbolic block representation avoids materializing all 2^n entries.
5. **Rotation-derived algebra.** Once cyclic convolution is intentionally added, the C_4 algebra and its higher-arity analogues raise separate questions involving group algebras, finite differences, ANF degree, and modal resource theories.
6. **Operator-valued enrichment.** The present uppercase operands X, Y, A, B are arbitrary Boolean formulas, but the LM entries still live in one Boolean formula algebra. A separate extension could ask when formula slots may themselves carry matrix- or operator-valued objects while preserving frame normalization, pairing, and superposition.

15 Conclusion

The binary notation Θ versus $[\Theta]$ distinguishes a logical operator from its compact numeric representation, while the formula-valued LM $[M_{X\Theta Y}]$ supplies the symbolic polarity layer that organizes the present calculus. Its valuation recovers $[\Theta]$ in the appropriate signed operand frame, and its logical pairing returns an exact relationship formula.

The central structural statement is therefore LM-centered coherence. Aligned formula-valued logical operators may themselves be combined as first-class operands of arbitrary Boolean outer operations; valuation transports that computation to numeric CMs, logical pairing preserves it relationally, and signed input-frame actions preserve its typing. The frame normal form and selector characterization explain this coherence structurally; the orbit/equivariance results classify the LM image; Boolean closure states the scalar boundary. The CM-level pointwise law remains important computationally, but it is treated as the valued numeric image of the broader symbolic construction rather than as the principal novelty claim.

An n -variable correspondence tensor may be flattened into a $2^p \times 2^q$ correspondence map for any declared bipartition. Rectangular maps remain genuine typed linear maps from $\mathbb{F}_2^{2^q}$ to $\mathbb{F}_2^{2^p}$ and still participate in bra-map-ket selection. Block lifts and the rank/separability theorem recover useful higher-dimensional structure from lower-dimensional subfunctions without changing the 2^n information bound: the flattening rank is exactly the minimum number of conjunctive factors in an XOR decomposition across the declared bipartition.

The paper also clarifies several boundaries. OR-AND and XOR-AND agree on one-hot selection but differ for general linear combinations; XOR is retained to preserve the $\mathbb{F}_2$ coefficient algebra. NPN transformations are standard and are realized here as explicit frame operations rather than claimed as new. ANF is a different coordinate system. Ordinary $\mathbb{F}_2$ eigenanalysis supplies algebraic signatures of square CMs, but those eigenvalues are not the truth values of the connective; an Eigenlogic-style diagonal truth observable lives instead on the four-dimensional interpretation space. Finally, the 4×4 quarter-turn permutation $\mathcal{R}_\odot$ acts on the four coefficients of a binary CM and must not be confused with a 4×4 four-variable correspondence map. Adding cyclic convolution to that coefficient rotation produces the separate phase algebra rather than another axiom of the CM/LM foundations.

A Spectral boundary and compact-CM atlas

Because a binary CM is a square matrix over $\mathbb{F}_2$, ordinary finite-field eigenanalysis is available. It should, however, be distinguished both from the older eigenproblem for matrices over a Boolean algebra and from the quantum-mechanical notion of an observable. Boolean-matrix eigenproblems have been studied since at least Rutherford and Blyth [13, 14]; those works use Boolean-algebra matrix operations rather than necessarily the XOR–AND field algebra fixed here.

For $A \in M_2(\mathbb{F}_2)$, define the characteristic polynomial in the ordinary field sense,

$$\chi_A(\lambda) = \det(\lambda I - A) = \lambda^2 + \text{tr}(A)\lambda + \det(A),$$

where subtraction and addition coincide in characteristic two. The resulting spectrum is an algebraic signature of the CM, but it is not the truth table of the connective.

CM	characteristic polynomial over $\mathbb{F}_2$	$\mathbb{F}_2$ eigenstructure	interpretation of the example
$[\wedge] = \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix}$	$\lambda(\lambda + 1)$	$ 1\rangle$ has eigenvalue 1; $ 0\rangle$ has eigenvalue 0	idempotent projection in the $\mathbb{F}_2$ linear-algebra sense.
$[\Leftrightarrow] = I$	$(\lambda + 1)^2$	every nonzero vector has eigenvalue 1	identity operator.
$[\Downarrow] = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$	$(\lambda + 1)^2$	only the line spanned by $(1, 1)^T$ is an eigenspace	involutory but not diagonalizable over $\mathbb{F}_2$; the true/false basis states are exchanged rather than observed as eigenstates.
$[\vee] = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}$	$\lambda^2 + \lambda + 1$	no eigenvalue in $\mathbb{F}_2$; roots lie in $\mathbb{F}_4$	a valid logical connective despite having no $\mathbb{F}_2$ eigenvector.

Table 2: Representative $\mathbb{F}_2$ spectra of binary CMs. The examples show why the raw CM spectrum is useful algebraically but cannot by itself serve as the truth-value spectrum of a logical observable.

Table 2 gives a decisive boundary. If raw CM eigenvalues were to be interpreted directly as logical measurement outcomes, OR would already be problematic: it has no eigenvalue in $\mathbb{F}_2$, while XOR has only the repeated eigenvalue 1. The four truth values of a binary connective are therefore not, in general, the eigenvalues of its 2×2 CM.

There is nevertheless a small projector-like subclass. Under the declared XOR–AND matrix product, exactly eight of the sixteen binary CMs satisfy $A^2 = A$. Exactly four are also symmetric: the four diagonal CMs

$$[0], \quad [\neg\vee], \quad [\wedge], \quad [\Leftrightarrow].$$

These are algebraic projection matrices over $\mathbb{F}_2$ (and the same 0–1 arrays are orthogonal projectors over ordinary real scalars when viewed in the standard basis). The fact that only a proper subset of the sixteen compact CMs has this form is another reason not to identify the raw CM family wholesale with quantum observables. This finite classification is an elementary structural observation rather than a novelty claim. Indeed, for $A = \begin{bmatrix} a & b \\ c & d \end{bmatrix}$, the equation $A^2 = A$ is equivalent over $\mathbb{F}_2$ to $bc = 0$ together with $b(a \Downarrow d \Downarrow 1) = c(a \Downarrow d \Downarrow 1) = 0$, which has eight binary solutions. Adding $A^T = A$ forces $b = c = 0$, leaving the four diagonal matrices above.

A.1 Matrix-element semantics versus spectral truth values

The native CM/LM semantics has already been established in Proposition 2.2 and Corollary 4.2: truth coefficients are recovered as labelled bra–operator–ket matrix elements, and arbitrary logical

pairing returns a Boolean relationship formula. This is relational matrix-element semantics, not spectral measurement; it supplies neither Born probabilities nor state collapse. Bricken’s technical note provides direct prior art for the numeric bra–matrix–ket viewpoint [15]. The formula-valued LM, its frame normal form, and the agreement-bit pairing architecture are the additional structures studied here.

Eigenlogic takes a different route. On the four-dimensional interpretation space with canonical assignment basis $|11\rangle, |10\rangle, |01\rangle, |00\rangle$, a binary connective Θ canonically determines the diagonal operator

$$D_\Theta := \text{diag}(\Theta_{11}, \Theta_{10}, \Theta_{01}, \Theta_{00}). \quad (63)$$

This 4×4 operator is a projector over ordinary real or complex scalars because its diagonal entries are 0 or 1; its eigenvectors are the four interpretation basis states and its eigenvalues are exactly the truth-table outputs. That is the spectral logic used by Eigenlogic in a more general operator setting [8, 9]. Equation (63) therefore gives a useful *spectral truth-observable representation* associated with a CM if a spectral interpretation is desired, but D_Θ is a different representation from the compact 2×2 CM $[\Theta]$. In the native CM representation, truth is read through the labelled matrix elements of Proposition 2.2 and Corollary 4.2, not through the spectrum.

Formula-valued LMs also admit algebraic eigenvalue questions, since their entries lie in a commutative Boolean ring. Ring-valued spectra are less rigid than field spectra, so the safest intrinsic object at present is the *valuation spectral profile*

$$\Sigma_M : v \mapsto \text{Spec}_{\mathbb{F}_2}(v(M)). \quad (64)$$

For $M = [M_{X\Theta Y}]$, valuation produces row and column reversals of $[\Theta]$. Independent left and right reversals need not be similarity transformations, so the $\mathbb{F}_2$ spectrum can vary with the valuation; simultaneous conjugate reversals preserve it. Whether this profile supplies a useful invariant of formula-valued LMs is an open algebraic question. Nothing in this paper interprets it as a physical observable without additional state, effect, and probability postulates.

B Binary LM basis expansion

Let $b_1 = 1$, $b_2 = 0$, $X_1 = X$, $X_2 = \neg X$, $Y_1 = Y$, $Y_2 = \neg Y$, and $c_{ij} = b_i \Theta b_j$. Define the formula-valued outer product

$$|X_i\rangle\langle Y_j| = \begin{bmatrix} X_i \wedge Y_j & X_i \wedge \neg Y_j \\ \neg X_i \wedge Y_j & \neg X_i \wedge \neg Y_j \end{bmatrix}.$$

Then

$$[M_{X\Theta Y}] = \biguplus_{i,j \in \{1,2\}} c_{ij} |X_i\rangle\langle Y_j|. \quad (65)$$

The upper-left entry is the disjoint-minterm expansion

$$c_{11}XY \uplus c_{12}X\neg Y \uplus c_{21}\neg XY \uplus c_{22}\neg X\neg Y,$$

which is exactly $X\Theta Y$. Exchanging the Y polarity gives the upper-right entry, exchanging the X polarity gives the lower-left entry, and exchanging both gives the lower-right entry. Thus (65) is equivalent to the direct binary definition (10).

C Compatibility identities

The principal maps of the calculus satisfy the following compatibility relations whenever the displayed expressions are typed:

$$\begin{aligned} v(\hat{g}(T_1, \dots, T_m)) &= \hat{g}(vT_1, \dots, vT_m), \\ T\hat{g}(\mathcal{C}_{f_1}, \dots, \mathcal{C}_{f_m}) &= \hat{g}(T\mathcal{C}_{f_1}, \dots, T\mathcal{C}_{f_m}), \\ v_1(\tau_\delta \mathcal{L}_\mathbf{X}(f)) &= \pi_\delta \mathcal{C}_f. \end{aligned}$$

The first says that valuation commutes with Boolean superposition; the second that a common frame reindexing commutes with pointwise composition; and the third that valuation intertwines symbolic polarity changes with numeric axis reversals. These identities are the concise algebraic content behind the commuting diagrams used in the main text.

D Notation and convention table

Symbol	Meaning
Θ	Binary logical operator variable/connective.
$[\Theta]$	Numeric 2×2 CM representing Θ in true-first order.
$[M_{X\Theta Y}]$	Formula-valued binary LM for the polarity orbit of $X\Theta Y$.
S_X	Formula-valued involutory frame matrix with $[M_{X\Theta Y}] = S_X[\Theta]S_Y$.
$\mathcal{C}_f$	n -variable numeric correspondence tensor with 2^n entries.
$\mathcal{M}_f(\mathbf{X})$	Formula-valued n -variable logical tensor.
$\mathcal{L}_\mathbf{X}$	Faithful LM lift $f \mapsto \mathcal{M}_f(\mathbf{X})$.
$[f]_{R C}$	$2^p \times 2^q$ matrix flattening for a declared variable bipartition.
$\hat{g}$	Pointwise lift of an outer Boolean function to aligned operators.
$\mathcal{O}_\Theta$	Block/outer lift constructing a correspondence map from disjoint subfunctions.
$T_{\sigma, \epsilon}$	Signed input-frame reindexing.
π_δ	One-triggered numeric axis reversal: $(\pi_\delta T)[\alpha] = T[\alpha \updownarrow \delta]$.
q_w	Partition selector $T \mapsto \updownarrow_i w_i \wedge T_i$.
$[\updownarrow]$	XOR CM; also the 2×2 true/false swap matrix under XOR-AND multiplication.
$\mathcal{R}_\circ$	Quarter-turn coefficient permutation acting on the four vectorized entries of a binary CM.

E Finite verification note

An independent standard-library checker accompanies this revision. It does not import the manuscript’s computational implementation. The current revision executes 20,873 exact finite checks covering: the binary frame normal form and valuation; all $16^3 = 4096$ binary outer-superposition triples on all assignments; the explicit frame-alignment example; all 16^2 matched-frame products under all eight valuations of X, Y, Z ; the corrected one-triggered valuation/axis convention through arity three; and every 2×4 Boolean matrix for the rank-one/conjunctive-separability equivalence. These checks are regression tests for conventions and finite examples, not substitutes for the arbitrary-arity proofs or evidence of historical priority.

References

- [1] C. R. Edwards. The logic of Boolean matrices. *The Computer Journal*, 15(3):247–253, 1972.

- [2] August Stern. *Matrix Logic: Theory and Applications*. North-Holland, 1988.
- [3] Eduardo Mizraji. Vector logics: The matrix–vector representation of logical calculus. *Fuzzy Sets and Systems*, 50(2):179–185, 1992.
- [4] Eduardo Mizraji. Vector logic: A natural algebraic representation of the fundamental logical gates. *Journal of Logic and Computation*, 18(1):97–121, 2008.
- [5] Daizhan Cheng and Hongsheng Qi. A linear representation of dynamics of Boolean networks. *IEEE Transactions on Automatic Control*, 55(10):2251–2258, 2010.
- [6] Daizhan Cheng, Yin Zhao, and Xiangru Xu. Matrix approach to Boolean calculus. In *Proceedings of the 50th IEEE Conference on Decision and Control and European Control Conference*, pages 6950–6955, 2011. DOI: 10.1109/CDC.2011.6160289.
- [7] Yin Zhao, Xu Gao, and Daizhan Cheng. Semi-tensor product approach to Boolean functions. Unpublished preprint, available from the AMSS Logical Systems and Control group. Bibliographic details to be checked before submission.
- [8] Zeno Toffano. Eigenlogic in the spirit of George Boole. arXiv:1512.06632, 2015.
- [9] François Dubois and Zeno Toffano. Eigenlogic: A quantum view for multiple-valued and fuzzy systems. arXiv:1607.03509, 2016.
- [10] Brian Droncheff. Correspondence matrices; algorithms for propositional logic. ResearchGate preprint, version 1.0.1. The public record lists May 2018 and states that the content was uploaded 1 October 2018; these dates should not be conflated. DOI: 10.13140/RG.2.2.28036.37764.
- [11] Brian Theory. Operator-Level Boolean Computation with Correspondence Matrices. Unpublished companion manuscript, 2026.
- [12] Brian Theory. Correspondence Matrices and Cyclic Phase: Rotation-Generated Boolean Operator Algebra. Research draft in preparation, 2026.
- [13] D. E. Rutherford. The eigenvalue problem for Boolean matrices. *Proceedings of the Royal Society of Edinburgh Section A*, 67(1):25–38, 1965.
- [14] T. S. Blyth. On eigenvectors of Boolean matrices. *Proceedings of the Royal Society of Edinburgh Section A*, 67(3):196–204, 1967.
- [15] William Bricken. Notes on Matrix Techniques for Logic. Technical note internally dated March 1997. Original public-release date and peer-reviewed status not established. Available at <https://wbricken.com/pdfs/01bm/01math/03math-supporting/math-tangential/04matrix-tech.pdf>.
- [16] Alan Mishchenko, Satrajit Chatterjee, and Robert K. Brayton. DAG-aware AIG rewriting: A fresh look at combinational logic synthesis. In *Proceedings of the 43rd Design Automation Conference*, pages 532–536, 2006.
- [17] Xuegong Zhou, Lingli Wang, and Alan Mishchenko. Fast adjustable NPN classification using generalized symmetries. *ACM Transactions on Reconfigurable Technology and Systems*, 12(2):7, 2019.

- [18] Stan Gudder and Frederic Latrémolière. Boolean inner-product spaces and Boolean matrices. arXiv:0902.1290, 2009.
- [19] Yoemon Sampei. On the orthogonal expansion of the Boolean polynomial and its applications I. *Journal of the Faculty of Science, Hokkaido University, Series I*, 11(3):113–125, 1950. DOI: 10.14492/hokmj/1530864050.
- [20] Stanley Burris and H. P. Sankappanavar. *A Course in Universal Algebra*. Springer, 1981; corrected author-hosted edition 2012.
- [21] Emil L. Post. *The Two-Valued Iterative Systems of Mathematical Logic*. Annals of Mathematics Studies 5, Princeton University Press, 1941.