

Correspondence Matrices, Cyclic Phase, and Exact Quantum Encodings

What survives in Boolean arithmetic,
what requires a signed lift, and where the framework may be useful

Prepared for Brian Droncheff

17 September 2026 · Version 1.0

Abstract

This paper consolidates and audits an exploration beginning with Droncheff’s correspondence matrices (CMs), which encode two-input Boolean predicates as binary 2×2 arrays. Clockwise rotation supplies a faithful C_4 action on the four atomic CM features. With an explicitly added cyclic-convolution product, these arrays form $\mathbb{F}_2[C_4]$. XOR cancellation, rotational correlations, and a conditional uniqueness theorem for normalized Hamming measure are established. Fresh exhaustive checks of all 65,536 two-branch operators confirm that global Hamming and full integer-correlation preservation leave only 32 phase-permutation operators. Thus these particular Boolean metrics do not provide a Hadamard-like mixer.

An integral lift and the quotient identifying opposite phase directions produce $\mathbb{Z}[i]$, with the explicit intertwiner $QP = JQ$ connecting CM rotation to the real quarter-turn matrix. The resulting phase-count representation reproduces conventional quantum gates and extends to exact Clifford+ T arithmetic. A separate, faithful compilation maps original CM predicates to reversible oracles and diagonal phase gates. Proofs and new computations distinguish this semantic bridge from a claim that ordinary CM truth-table operations already constitute quantum mechanics. Related matrix logics, finite-field models, path-sum calculi, cyclotomic synthesis, and model-counting methods substantially precede the general ideas. Plausible contributions lie in typed CM-based explanation, certified local rewrites, and structure-aware compilation; neither physical novelty nor a new simulation speedup is established.

Status and provenance. An AI-assisted research draft prepared from the supplied manuscript and this investigation, with independently rerun computational checks. It is not peer reviewed and is not a claim of new physical laws. The original manuscript is attributed to its author; the present text is a proposed extension and audit, not a silent revision of that manuscript. All numerical search summaries are generated by the accompanying code. Literature review cutoff: 17 September 2026.

Contents

1	Scope, claims, and the question being answered	3
2	Original correspondence matrices and their types	3
2.1	Boolean semantics and the basis convention	3
2.2	The four atomic CMs	4
2.3	Three different products must not be conflated	4
2.4	Single states, tensor states, and operators	5
2.5	An explicit bridge to logical gate matrices	5
3	What the four rotations actually represent	5
4	XOR interference, counting, and the limits of measurement	6
4.1	A well-defined interference-like experiment	6
4.2	What can be derived about Hamming measurement?	7
4.3	Integer correlation retains orientation but is not XOR-bilinear	8
5	The finite operator audit and no-go results	8
5.1	The exact search universe	8
5.2	Why the global answer is exactly 32	8
5.3	The shell is richer, but still does not yield the target fringe	9
5.4	Two explicit failures that must not be hidden	10
6	The integral lift: the precise bridge from CMs to J	10
6.1	A common source, not an embedding of characteristic two	10
6.2	The intertwining equation	11
6.3	How a general CM amplitude becomes an operator	11
6.4	What is lost, and the exact correction for XOR	12
7	The signed phase norm and visible CM gate operations	12
7.1	A quotient norm, not a new Boolean Born rule	12
7.2	An S gate that really rotates a CM amplitude	13
7.3	A CM-native splitter and recombiner	13
7.4	Tensor products and the location of entanglement	14
8	A direct compiler from original CM predicates to quantum operators	14
8.1	All sixteen two-input sign oracles have a simple normal form	15
8.2	Why the typed distinction matters	15
9	Exact gates, coefficient domains, and the C_8 extension	15
9.1	The common-denominator C_4 format	15
9.2	Four integer coordinates for exact 45° phases	16
9.3	Closure and equivalence theorem	16
9.4	Measurement and projective caveats	17

10 A Boolean phase-path theorem and its computational meaning	17
11 Fresh verification of the lifted calculations	18
11.1 Independent implementations and exactness	18
11.2 What the algorithm examples do and do not demonstrate	18
12 Literature review: what is already known, and what is distinctive?	19
12.1 Search scope and evidence standard	19
12.2 Matrix logic and vector logic: direct predecessors	19
12.3 Finite-field and set-based models: close to the Boolean stage	20
12.4 Boolean paths and exact amplitudes: strong prior overlap	21
12.5 Graphical and categorical calculi	21
12.6 Exact synthesis and known coefficient rings	21
12.7 Existing computational bridges and a recent close neighbor	21
12.8 A conservative novelty assessment	22
13 Applications, human benefit, and a concrete research agenda	23
13.1 The most immediate use: making reasoning and software more reliable	23
13.2 A candidate useful result: certified local phase rewrites	23
13.3 Safe compression: quotient late, or quotient with a proof	23
13.4 Benchmarkable questions rather than unbounded promises	23
13.5 Further mathematical questions worth investigating	24
13.6 What “useful to humanity” can responsibly mean here	25
14 Conclusion	25
A Correction ledger: claims that needed qualification or replacement	25
B Reproducibility, verification boundaries, and data encoding	26
B.1 Files and commands	26
B.2 Notation and normalization checks	27
B.3 Additional verified bridge facts	27
C The four complete Boolean interference tables	28
References	31

1 Scope, claims, and the question being answered

The motivating question is concrete: can a logical calculus with AND and XOR in the roles of multiplication and addition support something analogous to multiplication by i , and can rotations of correspondence matrices provide that operation? An answer must distinguish a four-cycle of pictures from a representation of a group, and a group representation from an amplitude algebra with a positive norm. It must also distinguish a numerical simulation of quantum equations from a physical quantum computer.

The starting manuscript, *Correspondence Matrices; Algorithms for Propositional Logic*, develops CMs, their rotations and complements, XOR composition, logical measurement matrices (LMs), and higher-dimensional constructions [1]. Its measurement discussion explicitly does not incorporate probability densities. Here we retain those definitions when discussing the original calculus and mark every change of coefficients, multiplication, or measurement interpretation. We verify the identities needed below; this is not a line-by-line certification of every statement in the original manuscript.

Four levels of evidence. A *proof* establishes an identity for its stated mathematical domain. An *exhaustive check* covers a precisely specified finite universe. A *regression test* checks representative circuits but is not a universal proof. A *research proposal* identifies an untested possibility. The attached scripts implement the finite checks and regression tests afresh; prior conversational assertions are not treated as evidence.

Question	Answer established here	Evidence / limitation
Does CM rotation realize C_4 ?	Yes, as a faithful linear permutation representation.	Explicit matrix and proof.
Does XOR reproduce complex addition?	No: identical terms cancel, and $-1 = 1$ in characteristic two.	Algebraic obstruction.
Can a phase-sensitive quotient be defined?	Yes, after an integral lift and an added opposite-phase relation.	$QP = JQ$ and quotient proof.
Do the lifted gates reproduce quantum circuits?	Yes, within the standard exact coefficient domain.	Intertwining proof and fresh tests.
Is the Born rule derived from logic?	No. A support measure is conditionally unique; quantum probabilities use an additional Hilbert-space interpretation.	Assumptions stated explicitly.
Is a new algorithmic or physical advantage shown?	No. A concrete compiler/rewrite research program is available.	Benchmarks remain future work.

Table 1: A map of the main conclusions. Positive representation results do not erase the negative results or their assumptions.

2 Original correspondence matrices and their types

2.1 Boolean semantics and the basis convention

We use $\oplus$ for XOR. The supplied manuscript uses a rotated-biconditional glyph for XOR; text extraction and the earlier discussion rendered that glyph as m . It is not a new operation. Products of Boolean scalar entries mean AND. In the original convention,

$$|1\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix}, \quad |0\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}, \quad |x\rangle = \begin{pmatrix} x \\ \neg x \end{pmatrix}. \quad (2.1)$$

Consequently, the *first/left* column of a CM is indexed by $y = 1$, and the second/right column by $y = 0$. The analogous row order is $x = 1, 0$. For

$$A = \begin{pmatrix} a & b \\ c & d \end{pmatrix}, \quad (2.2)$$

the associated predicate is

$$f_A(x, y) = axy \oplus bx\neg y \oplus c\neg xy \oplus d\neg x\neg y = \langle x|A|y \rangle. \quad (2.3)$$

For a fixed valuation, exactly one of the four minterms can be true. Thus the contraction reads one entry of A . This is the essential content of the truth-table representation in [1, Sections 2.2–3].

Proposition 2.1 (Pointwise CM composition). *Let A, B encode predicates on the same two ordered inputs, and let Φ be any binary Boolean operation. Applying Φ entrywise gives*

$$f_{A \Phi B}(x, y) = f_A(x, y) \Phi f_B(x, y). \quad (2.4)$$

In particular the representation is linear for XOR.

Proof. At each fixed input pair, both sides apply Φ to the same two selected entries. Since the four input pairs exhaust the truth table, the predicates agree. $\square$

This proof also makes the scope clear: one must align the inputs and their ordering before combining truth tables. A generic pair of quantum state vectors is not a pair of one-hot truth assignments, so the entry-selection argument does not automatically extend to them.

2.2 The four atomic CMs

For phase discussions it is useful to order the atomic features clockwise:

$$E_0 = [\wedge] = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}, \quad E_1 = [\Uparrow] = \begin{pmatrix} 0 & 1 \\ 0 & 0 \end{pmatrix}, \quad (2.5)$$

$$E_2 = [\neg\vee] = \begin{pmatrix} 0 & 0 \\ 0 & 1 \end{pmatrix}, \quad E_3 = [\Downarrow] = \begin{pmatrix} 0 & 0 \\ 1 & 0 \end{pmatrix}. \quad (2.6)$$

Then

$$A = a_0 E_0 \oplus a_1 E_1 \oplus a_2 E_2 \oplus a_3 E_3, \quad A = \begin{pmatrix} a_0 & a_1 \\ a_3 & a_2 \end{pmatrix}. \quad (2.7)$$

The reordered coordinates are $v(A) = (a_0, a_1, a_2, a_3)^T = (a, b, d, c)^T$. The existence of the four basis features and the XOR expansion are source results [1, Figure 1 and Section 3.2.1]; the cyclic ordering is a presentational choice.

2.3 Three different products must not be conflated

The same array can inhabit different algebras. Its shape alone does not specify its multiplication. A Boolean truth-table CM is generally neither invertible nor unitary. The all-ones truth table, the ordinary identity matrix, and the convolution identity are three different objects. In particular, an equation such as “ i AND i ” cannot be reinterpreted as convolution or gate composition without saying so.

Operation	Definition / role	Multiplicative unit
Entrywise AND $A \wedge B$	Combines truth predicates pointwise.	$\mathbb{T} = \begin{pmatrix} 1 & 1 \\ 1 & 1 \end{pmatrix}$
AND/XOR matrix product AB	$(AB)_{ij} = \bigoplus_k A_{ik} B_{kj}$. Acts on two-component Boolean vectors.	$I_2 = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$
Cyclic convolution $A \star B$	$E_j \star E_k = E_{j+k \bmod 4}$, extended distributively. Added in this paper's phase interpretation.	$E_0 = \begin{pmatrix} 1 & 0 \\ 0 & 0 \end{pmatrix}$

Table 2: Three distinct algebras on related arrays. Neither the identities nor the products are interchangeable.

2.4 Single states, tensor states, and operators

The tensor product, not XOR, combines two registers:

$$|10\rangle = |1\rangle \otimes |0\rangle = (0, 1, 0, 0)^T \quad (2.8)$$

in the source's ordering (11, 10, 01, 00). More generally

$$|X\rangle \otimes |Y\rangle = (XY, X\neg Y, \neg XY, \neg X\neg Y)^T. \quad (2.9)$$

The outer product $|X\rangle\langle Y|$ is instead a 2×2 operator-shaped array. The two contain related products but have different types. A 2×2 CM cannot directly multiply a four-component ket without a specified conversion. Later quantum computations use bitstring labels and the standard ascending storage order (00, 01, 10, 11); this is only a permutation of coordinates, not a change of truth convention.

2.5 An explicit bridge to logical gate matrices

The same predicate has a truth-valued linear gate representation

$$M_{f_A} = \begin{pmatrix} a & b & c & d \\ \neg a & \neg b & \neg c & \neg d \end{pmatrix}, \quad M_{f_A}(|x\rangle \otimes |y\rangle) = |f_A(x, y)\rangle. \quad (2.10)$$

The tensor input order is (11, 10, 01, 00). Each column is a one-hot truth vector. The identity follows by selecting the column indexed by (x, y) , and converting back to the CM simply reshapes the first row. Thus there is a bijection between the sixteen predicate CMs and these sixteen 2×4 deterministic logical gate matrices. This is a concrete translation into the dyadic vector-logic viewpoint [2]; it is not merely a visual resemblance. The rectangular gate can erase its inputs and is generally not reversible. The oracle construction in section 8 retains those inputs to obtain a unitary permutation embedding.

3 What the four rotations actually represent

Clockwise rotation is

$$\mathcal{R} \begin{pmatrix} a & b \\ c & d \end{pmatrix} = \begin{pmatrix} c & a \\ d & b \end{pmatrix}, \quad v(\mathcal{R}A) = Pv(A), \quad P = \begin{pmatrix} 0 & 0 & 0 & 1 \\ 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \end{pmatrix}. \quad (3.1)$$

Thus $\mathcal{R}E_j = E_{j+1 \bmod 4}$. The matrix has $P^4 = I_4$ and $P^2 \neq I_4$ over both $\mathbb{F}_2$ and $\mathbb{Z}$.

Proposition 3.1 (Faithful rotation representation). *The map $C_4 \rightarrow GL(4, \mathbb{F}_2)$ sending a generator to P is faithful. With cyclic convolution, the sixteen arrays form*

$$\mathcal{A}_2 = \mathbb{F}_2[C_4] \cong \mathbb{F}_2[g]/(g^4 - 1), \quad E_j \leftrightarrow g^j, \quad (3.2)$$

and $g \star A = \mathcal{R}A$.

Proof. The orbit of E_0 has length four, so no smaller positive power of P is the identity. The convolution rule is precisely multiplication of the four group elements, extended over $\mathbb{F}_2$. $\square$

The new product is circular convolution: if $A = \sum a_j g^j$ and $B = \sum b_j g^j$, then

$$(A \star B)_k = \bigoplus_{j=0}^3 (a_j \wedge b_{k-j \bmod 4}). \quad (3.3)$$

Although multiplication by g is an invertible linear map, it is not a unital algebra automorphism of this convolution algebra. The phrase “rotation symmetry” should not obscure that distinction.

Transpose induces the involution $g \mapsto g^{-1}$. It is a natural phase-reversal operation for convolution, not a claim that Boolean complement is complex conjugation. The Boolean ring has

$$g^4 - 1 = (g + 1)^4, \quad (3.4)$$

so it contains nilpotents. Its order-four units are not four distinct complex scalar eigenphases; in characteristic two, $-1 = 1$.

There is also a purely logical reading of the same rotation:

$$f_{\mathcal{R}A}(x, y) = f_A(\neg y, x). \quad (3.5)$$

Equivalently, a feature indexed by (x, y) moves to $(y, \neg x)$. That motion is a classical basis permutation, expressible as a swap followed by a NOT. It becomes a phase operation only after an additional amplitude interpretation is specified. This provides a useful guard against reasoning from the geometry of the drawing alone.

4 XOR interference, counting, and the limits of measurement

4.1 A well-defined interference-like experiment

For two CMs, define

$$I_k(A, B) = A \oplus \mathcal{R}^k B, \quad k \in \mathbb{Z}/4\mathbb{Z}. \quad (4.1)$$

This is a useful Boolean cancellation experiment. It is not yet a quantum superposition. Coincident features cancel, since $1 \oplus 1 = 0$; two contributions in different positions survive separately. Surviving distinct features should not be described as amplitude doubling.

Let $\text{wt}(A)$ count the ones using ordinary integers. Directly from $a \oplus b = a + b - 2ab$ for bits,

$$\text{wt}(I_k) = \text{wt}(A) + \text{wt}(B) - 2C_{A,B}(k), \quad C_{A,B}(k) = \text{wt}(A \wedge \mathcal{R}^k B). \quad (4.2)$$

This identity is exact and is also the familiar relationship between Hamming distance and overlap of binary supports. All four 16×16 interference tables are included in [section C](#). The table for k is simply the XOR table with its second argument permuted by $\mathcal{R}^k$; it does not by itself establish a new additive law.

For $r = [R] = E_0 \oplus E_3$, the clockwise orbit is

$$[R] \longrightarrow [L] \longrightarrow [\neg R] \longrightarrow [\neg L] \longrightarrow [R]. \quad (4.3)$$

Its self-overlap and XOR-weight profiles are

$$C_{r,r} = (2, 1, 0, 1), \quad \text{wt}(r \oplus \mathcal{R}^k r) = (0, 2, 4, 2). \quad (4.4)$$

Thus dividing the latter by four gives the four values of $\sin^2(\phi/2)$ at $\phi = 0, \pi/2, \pi, 3\pi/2$. This is a four-sample agreement caused by the support geometry, not a derivation of continuous sinusoidal phase dynamics. Other carriers give different profiles: E_0 gives $(0, 2, 2, 2)$.

4.2 What can be derived about Hamming measurement?

The original LM formalism gives coefficient extraction,

$$\langle X_i | M_{X \otimes Y} | Y_j \rangle = \Theta_{ij} \quad (4.5)$$

[1, Section 4.1.4]. Counting the four positive elementary results therefore gives $\text{wt}(\Theta)$. The count is an integer-valued aggregate of Boolean observations, not their XOR.

Theorem 4.1 (Conditional uniqueness of normalized support measure). *Suppose μ is a nonnegative real-valued function on the sixteen CMs with $\mu(0) = 0$, $\mu(\mathbb{T}) = 1$, rotation invariance, and finite additivity for disjoint supports:*

$$A \wedge B = 0 \implies \mu(A \oplus B) = \mu(A) + \mu(B). \quad (4.6)$$

Then $\mu(A) = \text{wt}(A)/4$ for every CM.

Proof. The rotation acts transitively on the four atoms E_j , so their measures are equal to some p . Their disjoint sum is $\mathbb{T}$, hence $4p = 1$. Each CM is the disjoint union of its occupied atoms. $\square$

The assumption of rotation invariance is an equal-weight assumption about the four elementary positions. Operationally, $\mu(A)$ is the probability that $f_A(X, Y)$ is true if the input pair is sampled uniformly. With a nonuniform input distribution one obtains a weighted count instead. Boolean logic alone does not select a physical sampling distribution.

It is valid, after embedding bit entries in $\mathbb{R}$, that

$$\text{wt}(A) = \|A\|_F^2 = \text{tr}(A^T A). \quad (4.7)$$

The products and trace in this equation are ordinary real or integer arithmetic. Under AND/XOR arithmetic, the analogous contraction returns parity and can vanish for a nonzero vector. This distinction prevents an apparent squared-norm formula from being mistaken for a derivation of the physical Born rule. Ellerman's set-based model provides a particularly close prior comparison: it also combines symmetric difference with an external counting interpretation of overlaps [3].

The count itself is implementable using Boolean gates. For four entries a, b, c, d , its three binary digits are

$$q_0 = a \oplus b \oplus c \oplus d, \quad (4.8)$$

$$q_1 = ab \oplus ac \oplus ad \oplus bc \oplus bd \oplus cd, \quad (4.9)$$

$$q_2 = abcd, \quad \text{wt}(A) = q_0 + 2q_1 + 4q_2. \quad (4.10)$$

All sixteen cases were checked. The last equality interprets a multi-bit register as an integer; it does not make the scalar addition characteristic two. Likewise $\text{wt}(A \otimes B) = \text{wt}(A) \text{wt}(B)$ for binary support arrays. This tensor-count identity is not a substitute for defining a quantum tensor product of amplitudes.

4.3 Integer correlation retains orientation but is not XOR-bilinear

Writing the bit coefficients as ordinary integers, define

$$C_{A,B}(k) = \sum_{j=0}^3 a_j b_{j-k \bmod 4}, \quad C(A, B) = \sum_{k=0}^3 C_{A,B}(k) g^k \in \mathbb{Z}[C_4]. \quad (4.11)$$

With $\bar{g} = g^{-1}$ this is $A \star \bar{B}$ in the integral group algebra. Thus

$$C(B, A) = \overline{C(A, B)}, \quad C(g^r A, g^s B) = g^{r-s} C(A, B). \quad (4.12)$$

The correlation convention is linear in the first argument after integral lifting; conjugating the evaluated form gives the usual Dirac convention. These are genuine conjugation and covariance identities. However, the embedding of Boolean arrays as 0/1 integer arrays is not additive for XOR: $C(A \oplus A, B) = 0$, whereas $2C(A, B)$ need not vanish. Hence this is not an $\mathbb{F}_2$ -sesquilinear inner product. Usual polarization arguments relating norm preservation to inner-product preservation cannot be assumed in that mixed arithmetic.

5 The finite operator audit and no-go results

5.1 The exact search universe

Let $\mathcal{A}_2 = \mathbb{F}_2[C_4]$ with the convolution product. A two-branch state is $\Psi = (A, B)^T \in \mathcal{A}_2^2$. We enumerate all $16^4 = 65,536$ matrices

$$U = \begin{pmatrix} u_{11} & u_{12} \\ u_{21} & u_{22} \end{pmatrix}, \quad U\Psi = \begin{pmatrix} u_{11} \star A \oplus u_{12} \star B \\ u_{21} \star A \oplus u_{22} \star B \end{pmatrix}. \quad (5.1)$$

Every operator is tested on all 256 states. These are all two-by-two $\mathcal{A}_2$ -linear operators, not all possible binary circuits, nonlinear maps, measurement models, or operators in arbitrary dimensions. As binary matrices they form a structured subset of the 8×8 matrices.

Define $W(A, B) = \text{wt}(A) + \text{wt}(B)$ and the weight-four shell

$$\Sigma = \{(A, B) : W(A, B) = 4\}, \quad |\Sigma| = \binom{8}{4} = 70. \quad (5.2)$$

Also define the full self-correlation $C(A, A) + C(B, B)$ and its signed quotient, whose real value is $C_0 - C_2$. Full pair-correlation preservation means equality on every pair of states, not merely on self-pairs.

5.2 Why the global answer is exactly 32

Theorem 5.1 (Global Hamming isometries). *On $\mathcal{A}_2^d$, every $\mathcal{A}_2$ -linear transformation preserving total Hamming weight on all vectors is a permutation of the d branches followed by an independent cyclic rotation within each branch. The group is $C_4 \wr S_d$, of order $4^d d!$. For $d = 2$ it consists of the 32 matrices*

$$\text{diag}(g^a, g^b), \quad \begin{pmatrix} 0 & g^a \\ g^b & 0 \end{pmatrix}, \quad a, b \in \{0, 1, 2, 3\}. \quad (5.3)$$

Proof. Regard the map as an $\mathbb{F}_2$ -linear map on $4d$ binary coordinates. Each unit vector has weight one, so its image must be a unit vector. Images of two different unit vectors cannot coincide, since then their weight-two sum would map to zero. Thus the map is a coordinate permutation. $\mathcal{A}_2$ -linearity means that it commutes with simultaneous multiplication by g , which is a permutation with d disjoint cycles of length four. A commuting permutation sends a cycle to a cycle and chooses a cyclic offset within it. There are $d!$ cycle permutations and 4^d offsets. Conversely these maps plainly preserve weight. $\square$

Freshly checked property	Count
All two-by-two $\mathcal{A}_2$ -linear operators	65,536
Invertible operators	24,576
Involutions $U^2 = I$	640
Involutions sending $(0, r)$ to (r, r)	4
Preserve W on all 256 states	32
Preserve full integer self-correlation on all states	32
Preserve full integer pair-correlation on all state pairs	32
Map the weight-four shell into itself	512
Shell preservers invertible on the full space	512
Shell-preserving involutions	96
Distinct actions on the shell / kernel size	128 / 4
Preserve full self-correlation on the shell	512
Preserve signed self-form globally / on the shell	2,048 / 8,192
Preserve full signed pair-correlation globally	32

Table 3: Recomputed classifications. The two shell-preserver sets (weight and full self-correlation) coincide exactly. Data: `finite_summary.json`; membership masks: `finite_classification.npz`.

Full integer-correlation preservation includes the zero-lag self-correlation, which is Hamming weight. Thus it cannot *enlarge* this global group. Every listed phase-permutation does preserve the full correlation, so the classification remains exactly 32. Earlier motivation suggesting that preservation of a richer form might enlarge the isometry group was incorrect: adding preservation constraints can only retain or remove operators.

The larger signed-self-form class does not contradict this theorem. That form forgets some information, has null directions on raw arrays, and is not a quadratic form over the original XOR addition. Requiring the complete pair form reduces it to the same 32 maps in this finite test.

5.3 The shell is richer, but still does not yield the target fringe

The shell admits the involutory mixer

$$K = \begin{pmatrix} 1 & 1 \oplus g^2 \\ 1 \oplus g^2 & 1 \end{pmatrix}, \quad K^2 = I. \quad (5.4)$$

It is not a global Hamming isometry: $(E_0, 0)$ has weight one, whereas its image has weight three. All 512 shell preservers are invertible, and their restrictions form a group of 128 permutations of Σ .

The four-element kernel has a transparent explanation. The binary span of the weight-four vectors in eight coordinates is the even-parity subspace. A linear map equal to the identity on that subspace has the form $I + v\epsilon$, where ϵ is total parity. Commutation with the two four-cycles requires v to be constant on each cycle, giving four choices. In ring notation they are

$$I + \begin{pmatrix} \alpha\mathbb{T} & \alpha\mathbb{T} \\ \beta\mathbb{T} & \beta\mathbb{T} \end{pmatrix}, \quad \alpha, \beta \in \mathbb{F}_2. \quad (5.5)$$

Each is invertible because $\epsilon(v) = 0$. This explains the observed ratio $512/4 = 128$ without assigning a new physical meaning to the shell.

For every U in the shell-preserving set, every $\Psi \in \Sigma$, and every $S_k = \text{diag}(g^k, 1)$, we computed W branch by branch after $US_k\Psi$. Only seven sequences of first-branch weights occurred:

$$(0, 0, 0, 0), (1, 1, 1, 1), (2, 2, 2, 2), (3, 3, 3, 3), (4, 4, 4, 4), \quad (5.6)$$

$$(1, 3, 1, 3), (3, 1, 3, 1). \quad (5.7)$$

There is no sequence $(0, 2, 4, 2)$ or $(4, 2, 0, 2)$, including cyclic changes of phase origin. The search covers $512 \cdot 70$ operator/state cases, each at four phases. This is a complete negative result for that experiment, not a prohibition on all finite-field quantum-like theories. Modal quantum theory deliberately uses different measurement assumptions [4].

5.4 Two explicit failures that must not be hidden

The first attempted conditional rotation used the masks $[R] = \begin{pmatrix} 1 & 0 \\ 1 & 0 \end{pmatrix}$ and $[\neg R] = \begin{pmatrix} 0 & 1 \\ 0 & 1 \end{pmatrix}$:

$$F(A) = (A \wedge [\neg R]) \oplus (RA \wedge [R]). \quad (5.8)$$

For $A = \begin{pmatrix} a & b \\ c & d \end{pmatrix}$ this is

$$F(A) = \begin{pmatrix} c & b \\ d & d \end{pmatrix}. \quad (5.9)$$

It deletes a , sends E_0 to zero, and cannot satisfy $F^4 = I$. It does not rotate one column as a reversible phase gate. The earlier assertion that its order follows from $R^4 = I$ was false.

A later toy splitter in the convolution algebra was

$$B = \begin{pmatrix} 1 & g^2 \\ 1 & 1 \end{pmatrix}, \quad B^2 = (1 \oplus g^2)I, \quad B^4 = 0. \quad (5.10)$$

It can generate the desired four output weights from a specially chosen carrier, but is nilpotent rather than unitary. Also, $r|0\rangle$ has $W/4 = 1/2$ before splitting, not one. Apparent conservation at the final detector does not establish conservation through the circuit. No scalar normalization repairs B : if $s^2(1 + g^2) = 1$, squaring gives $0 = 1$.

There is an independent obstruction to a familiar Hadamard identity. Over this commutative ring, similarity preserves trace. But $Z_B = \text{diag}(g^2, 1)$ has trace $g^2 + 1 \neq 0$, while $X = \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$ has trace zero. Hence no invertible H can satisfy $HZ_BH^{-1} = X$. These failures motivate changing the amplitude algebra explicitly, rather than relabeling the failed maps as quantum gates.

6 The integral lift: the precise bridge from CMs to J

6.1 A common source, not an embedding of characteristic two

The successful construction changes the amplitude arithmetic. Retain the four atomic CM positions, but allow an integer number of contributions at each position:

$$\tilde{A} = n_0E_0 + n_1E_1 + n_2E_2 + n_3E_3, \quad n_j \in \mathbb{Z}. \quad (6.1)$$

Positive counts can describe accumulated paths; negative counts are a useful reduced representation. Addition is now ordinary integer addition. With cyclic convolution these objects form $\mathbb{Z}[C_4]$. Reducing their coefficients modulo two recovers $\mathcal{A}_2$, but this reduction discards multiplicity information.

Next impose an additional phase relation: opposite positions represent opposite amplitudes. In algebraic terms, quotient by $1 + g^2$. The construction is the diagram

$$\begin{array}{ccc} & \mathbb{Z}[C_4] & \\ \swarrow \text{mod } 2 & & \searrow g^2 = -1 \\ \mathbb{F}_2[C_4] & & \mathbb{Z}[g]/(g^2 + 1) \cong \mathbb{Z}[i]. \end{array} \quad (6.2)$$

The opposite-phase relation is *a new semantic choice*, not a theorem of Boolean truth tables. There is no unital ring homomorphism from the characteristic-two algebra on the left into the characteristic-zero algebra on the right: the equality $1 + 1 = 0$ would have to remain true. Consequently the diagram must not be replaced with a purported inclusion $\mathbb{F}_2[C_4] \subset \mathbb{Z}[i]$.

6.2 The intertwining equation

Define

$$Q = \begin{pmatrix} 1 & 0 & -1 & 0 \\ 0 & 1 & 0 & -1 \end{pmatrix}, \quad J = \begin{pmatrix} 0 & -1 \\ 1 & 0 \end{pmatrix}. \quad (6.3)$$

Then $Q\tilde{A} = (n_0 - n_2, n_1 - n_3)^T$. The four elementary images are

$$QE_0 = (1, 0), \quad QE_1 = (0, 1), \quad QE_2 = (-1, 0), \quad QE_3 = (0, -1). \quad (6.4)$$

Here QE_j abbreviates $Qv(E_j)$.

Theorem 6.1 (CM rotation induces the quarter-turn). *The CM rotation matrix P and the signed quarter-turn matrix J satisfy*

$$QP = JQ. \quad (6.5)$$

The kernel of Q is the ideal generated by $1 + g^2$, so J is the action induced by rotation on the quotient $\mathbb{Z}[C_4]/(1 + g^2)$.

Proof. For $n = (n_0, n_1, n_2, n_3)^T$, $Pn = (n_3, n_0, n_1, n_2)^T$, hence

$$QPn = (n_3 - n_1, n_0 - n_2)^T = JQn. \quad (6.6)$$

The kernel consists of (a, b, a, b) , corresponding to $(a + bg)(1 + g^2)$. This is precisely the relation identifying E_2 with $-E_0$ and E_3 with $-E_1$. $\square$

This is the missing bridge behind the initial analogy. It is stronger than observing that two transformations both have period four. It also makes the limitation unambiguous: J is not one of the sixteen binary CMs. It is a two-dimensional signed representation *induced from* their four-position rotation after lifting and quotienting.

6.3 How a general CM amplitude becomes an operator

For integer coefficients n_j , let

$$L_{\tilde{A}} = n_0I + n_1P + n_2P^2 + n_3P^3 \quad (6.7)$$

act by convolution on another lifted CM. Put $u = n_0 - n_2$ and $v = n_1 - n_3$. Iterating equation (6.5) gives

$$QL_{\tilde{A}} = \underbrace{\begin{pmatrix} u & -v \\ v & u \end{pmatrix}}_{uI + vJ} Q. \quad (6.8)$$

Thus multiplication by a CM-valued phase coefficient is not merely a verbal analogy: it is a four-position convolution operator whose quotient is multiplication by the pair (u, v) . On pairs, the induced product is

$$(u, v) \cdot (s, t) = (us - vt, ut + vs). \quad (6.9)$$

This is the usual Gaussian-integer product in real coordinates. Writing pairs instead of i removes a symbol from the implementation, not the mathematical complex structure.

6.4 What is lost, and the exact correction for XOR

The map Q is not injective. Among the sixteen binary arrays its image contains nine pairs in $\{-1, 0, 1\}^2$. The zero CM, I_2 , the XOR truth-table matrix, and the all-ones CM all map to $(0, 0)$. These are different predicates. Therefore *one must not use Q as a semantics-preserving compression of arbitrary truth-table CMs*.

Nor does Q preserve the original Boolean operations. For example, $E_0 \oplus E_0 = 0$ while $QE_0 + QE_0 = (2, 0)$. Similarly $E_0 \wedge E_1 = 0$, whereas $(QE_0)(QE_1) = (0, 1)$. The exact additive defect is useful:

Proposition 6.2 (Carry/overlap correction). *For binary CMs embedded coefficientwise in the integer lift,*

$$Q(A \oplus B) = QA + QB - 2Q(A \wedge B). \quad (6.10)$$

Proof. Apply the integer identity $a \oplus b = a + b - 2ab$ at each coordinate, then the integer-linear map Q . $\square$

This formula is one practical way to detect an invalid “Boolean-to-amplitude” rewrite. Dropping its overlap term changes the semantics.

Transpose satisfies $Q(A^T) = \overline{QA}$, where pair conjugation sends (u, v) to $(u, -v)$. For a binary array, complement happens to satisfy $Q(\neg A) = -QA$ because $Q(\mathbf{T}) = 0$. That last identity is a consequence of the information-losing quotient; it does not identify Boolean NOT with complex conjugation or with a general physical phase operation.

7 The signed phase norm and visible CM gate operations

7.1 A quotient norm, not a new Boolean Born rule

The squared length of the quotient coordinates is

$$N_Q(n) = \|Qn\|^2 = (n_0 - n_2)^2 + (n_1 - n_3)^2 = n^T(I - P^2)n. \quad (7.1)$$

The matrix $Q^T Q = I - P^2$ is positive semidefinite with rank two. It is a seminorm on the four raw count coordinates and a positive norm on their quotient. In terms of integer self-correlation,

$$N_Q(n) = C_{n,n}(0) - C_{n,n}(2). \quad (7.2)$$

Unlike Hamming weight, it regards opposite contributions as cancelling. For example, $N_Q(E_0 + E_2) = 0$ but $N_Q(2E_0) = 4$. For 0/1 entries it equals

$$\text{wt}(A) - 2(a_0 a_2 + a_1 a_3), \quad (7.3)$$

not $\text{wt}(A)$ in general.

Proposition 7.1 (Conditional uniqueness of the phase quadratic form). *Let a real positive-semidefinite quadratic form on $\mathbb{R}^4$ be invariant under P , vanish on $\ker Q$, and assign squared length one to E_0 . Then it is exactly N_Q .*

Proof. Positive semidefiniteness implies that null vectors lie in the kernel of the representing symmetric matrix, so the form descends to $\mathbb{R}^4 / \ker Q \cong \mathbb{R}^2$. Its symmetric matrix G must satisfy $J^T G J = G$. Writing out a symmetric two-by-two G forces equal diagonal entries and zero off-diagonal entries: $G = \lambda I$. The value at QE_0 fixes $\lambda = 1$. $\square$

The theorem has substantive assumptions. In particular, specifying $\ker Q$ as physically null selects the primitive quarter-phase sector. Rotation invariance alone also permits contributions from the trivial and sign sectors of the regular representation. In Fourier language, Q selects evaluation at $g = i$ (with its conjugate); the full coefficient squared length instead averages the energies of all four characters. Changing from one form to the other is not merely remembering more phase data. It is changing which directions carry measurable amplitude.

For a collection of branch amplitudes $z_x = Qn_x$, define

$$\Psi = 2^{-h/2} \sum_x z_x |x\rangle, \quad \|\Psi\|^2 = 2^{-h} \sum_x |z_x|^2. \quad (7.4)$$

If we identify this representation with the usual Hilbert-space quantum model, its outcome probabilities are the usual squared moduli. This is a *pullback of the Born rule under an explicit representation*, not a derivation of that empirical probability law from AND, XOR, or rotational symmetry alone.

7.2 An S gate that really rotates a CM amplitude

Each logical branch carries an entire lifted CM, rather than one column of a shared CM. In the branch order $(|0\rangle, |1\rangle)$, define

$$S_{\text{CM}}(A, B) = (A, PB). \quad (7.5)$$

Applying Q separately to both branches gives

$$(QA, QB) \mapsto (QA, JQB). \quad (7.6)$$

A common rotation of every quotient branch multiplies the whole state by a global phase and does not change its physical predictions. Only relative rotations between branches are observable; four phase labels are not four distinguishable physical states of a lone occupied basis branch.

This is the exact operator meaning of multiplying the $|1\rangle$ amplitude by a quarter phase. The controlled choice concerns the *branch label*; the rotation acts on all four phase coordinates of its coefficient. This resolves the earlier masked-column confusion.

7.3 A CM-native splitter and recombiner

One can keep the geometry visible even for Hadamard. Define on raw counts

$$H_{\text{CM}} : (A, B; h) \mapsto (A + B, A + P^2 B; h + 1). \quad (7.7)$$

The $+$ signs here count paths over $\mathbb{Z}$, not modulo two. By $QP^2 = -Q$, its quotient is

$$H : (u, v; h) \mapsto (u + v, u - v; h + 1). \quad (7.8)$$

It preserves the normalized quotient norm because

$$|u + v|^2 + |u - v|^2 = 2(|u|^2 + |v|^2). \quad (7.9)$$

The raw four-phase map is not required to be invertible on directions annihilated by Q ; the induced map on the quotient is unitary. An alternative raw representation uses signed subtraction directly. The two are equivalent after Q , not as operations on original Boolean truth tables.

Worked example with every CM visible. Start with $E_0|0\rangle$. Splitting gives $(E_0|0\rangle + E_0|1\rangle)/\sqrt{2}$. A quarter-turn on the second branch gives

$$\frac{E_0|0\rangle + E_1|1\rangle}{\sqrt{2}}. \quad (7.10)$$

Recombination by equation (7.7) gives raw coefficients $E_0 + E_1$ and $E_0 + E_3$, with denominator two. Their quotient coordinates are $(1, 1)$ and $(1, -1)$, with squared lengths two each. Thus both outcomes have probability $1/2$ in the quantum interpretation.

With no phase shift, the raw outputs are $2E_0$ and $E_0 + E_2$. Their quotient lengths are four and zero. With a half-turn the outputs reverse. This is the precise distinction that XOR could not supply: equal directions reinforce by retaining multiplicity, while opposite directions cancel under the quotient.

7.4 Tensor products and the location of entanglement

For independent registers, tensor their branch labels and multiply their amplitude coefficients using convolution before quotienting, or Gaussian multiplication afterward. The compatibility follows from $Q(A \star B) = QAQB$ in the *integer* convolution algebra. Consequently

$$\|\Psi \otimes \Phi\|^2 = \|\Psi\|^2 \|\Phi\|^2. \quad (7.11)$$

CNOT sends $|x, y\rangle$ to $|x, x \oplus y\rangle$ and simply permutes the carried coefficients. Applying a splitter and CNOT to $|00\rangle$ yields $(|00\rangle + |11\rangle)/\sqrt{2}$ in the quotient representation. This is an exact encoding of a standard entangled state, not evidence that a classical array implementation has become a nonlocal physical system.

A previous strict-ring state, $[\neg R]|11\rangle + [R]|00\rangle$, was also nonfactorable over $\mathcal{A}_2$: all 16^4 possible two-factor assignments failed. Its coefficient matrix has determinant $[\neg R] \star [R] = 1 + g^2 \neq 0$, whereas an outer product over a commutative ring has zero determinant. This algebraic nonseparability is correctly distinguished from the Hilbert-space and experimental senses of entanglement.

8 A direct compiler from original CM predicates to quantum operators

The preceding quotient explains a phase coordinate system, but it intentionally loses Boolean truth-table information. There is a second bridge that retains that information and makes direct use of CMs *as specifications of logical operators*. It is particularly important for avoiding the impression that the CMs disappear as soon as Gaussian coordinates are introduced.

Definition 8.1 (Reversible CM oracle and CM phase gate). For the original predicate f_A in equation (2.3), define

$$O_A|x, y, z\rangle = |x, y, z \oplus f_A(x, y)\rangle, \quad (8.1)$$

$$D_A^{(k)}|x, y\rangle = \zeta_8^{kf_A(x, y)}|x, y\rangle, \quad \zeta_8 = e^{i\pi/4}. \quad (8.2)$$

These act on three and two qubits respectively. They are not the original 2×2 truth-table array acting on a ket of the wrong dimension.

Theorem 8.2 (Faithful Boolean oracle embedding and exact phase correction). *For all two-input CMs A, B :*

$$O_A^2 = I, \quad O_A O_B = O_{A \oplus B}, \quad (8.3)$$

$$D_{A \oplus B}^{(k)} = D_A^{(k)} D_B^{(k)} D_{A \wedge B}^{(-2k)}. \quad (8.4)$$

The map $A \mapsto O_A$ is injective. For $k = 4$, the final factor in equation (8.4) is the identity, so XOR of predicates translates exactly into composition of their sign-phase oracles.

Proof. The oracle preserves x, y and toggles z by its predicate, so two applications cancel and two different oracles toggle by $f_A \oplus f_B$. Distinct predicates differ on some pair and hence produce distinct permutations. For phase gates, apply $f_A \oplus f_B = f_A + f_B - 2f_A f_B$ as an integer equality and compare exponents modulo eight. At $k = 4$, the overlap correction is a multiple of eight. $\square$

This is an operational use of the original CM composition law, not merely a relation between two four-cycles. It also explains why one cannot transfer an XOR rewrite unchanged to arbitrary 45° phase gates. The correction factor may be essential.

8.1 All sixteen two-input sign oracles have a simple normal form

For $A = \begin{pmatrix} a & b \\ c & d \end{pmatrix}$, write its algebraic normal form as

$$f_A(x, y) = d \oplus px \oplus qy \oplus rxy, \quad (8.5)$$

where

$$p = b \oplus d, \quad q = c \oplus d, \quad r = a \oplus b \oplus c \oplus d. \quad (8.6)$$

Then

$$D_A^{(4)} = (-1)^d Z_x^p Z_y^q C Z_{xy}^r. \quad (8.7)$$

All sixteen cases were checked independently on all four inputs. As a worked example, OR has $d = 0$ and $p = q = r = 1$; therefore its sign oracle is $Z_x Z_y C Z$. AND gives CZ as a phase oracle and Toffoli as the reversible oracle O_A .

For a general angle the integer expansion is also useful:

$$f_A(x, y) = d + (b - d)x + (c - d)y + (a - b - c + d)xy. \quad (8.8)$$

It factors a diagonal phase predicate into constant, one-variable, and two-variable phases. This is a semantic identity, not an assertion that every controlled phase is a cost-free primitive or admits a particular ancilla-free synthesis. Synthesis constraints must be checked separately [5, 6].

8.2 Why the typed distinction matters

The array E_0 can mean the predicate $x \wedge y$, or it can mean one unit of zero-phase amplitude. In the first role it compiles to O_{E_0} or $D_{E_0}^{(k)}$; in the second it maps to $QE_0 = (1, 0)$. These are different interpretations of the same array. A compiler must distinguish at least *predicate CM*, *phase-count CM*, and *linear operator*. Their allowed rewrites are different. This type discipline is a practical contribution of the audit even if the underlying oracle constructions and Boolean phase identities are established mathematics.

9 Exact gates, coefficient domains, and the C_8 extension

9.1 The common-denominator C_4 format

For circuits built from H, S, CNOT , and Boolean basis permutations, integer Gaussian numerators with a shared denominator $2^{h/2}$ remain a valid representation. Each Hadamard adds or subtracts numerators and increments h ; S rotates pairs; a permutation reassigns branch labels. This proves closure under those gate rules, and the quotient intertwining proves agreement with the corresponding standard quantum gates.

There are two qualifications. First, the union of the common-denominator formats is not itself closed under arbitrary scalar addition. For example $1 + 1/\sqrt{2}$ cannot be written as a single Gaussian integer divided by one power of $\sqrt{2}$. The format is closed under the specified synchronized circuit updates, not

an unrestricted coefficient ring. Second, allowing *arbitrary* reversible Boolean oracles adds gates such as Toffoli, which are not Clifford. Hadamard and Toffoli already support universal quantum computation with the standard real-amplitude encoding [7]. A C_4 phase alphabet alone therefore does not characterize the computational power of a gate set.

For precisely H , S , and CNOT, the gates generate the Clifford group; efficient stabilizer descriptions are established and generally preferable to dense state vectors in that sector [8]. Our exact group checks generate 24 one-qubit and 11,520 two-qubit elements modulo global phase. They are checks of the representation, not discoveries of new group orders.

9.2 Four integer coordinates for exact 45° phases

Let

$$\mathcal{A}_8 = \mathbb{Z}[z]/(z^4 + 1), \quad z \mapsto \zeta_8. \quad (9.1)$$

An element is uniquely represented by (a, b, c, d) , meaning $a + bz + cz^2 + dz^3$. Multiplication by z is the signed cyclic shift

$$(a, b, c, d) \mapsto (-d, a, b, c). \quad (9.2)$$

Thus $z^2 = i$, $z^4 = -1$, and $z^8 = 1$. This 45° phase is not an ordinary geometric 45° rotation of a four-cell binary CM: the original array does not have eight distinct positions. It is an explicitly enlarged coefficient representation. One can use eight phase bins with opposite-bin reduction, or the four independent signed coordinates above.

Conjugation is

$$\overline{(a, b, c, d)} = (a, -d, -c, -b). \quad (9.3)$$

The squared modulus has the exact form

$$\begin{aligned} |a + bz + cz^2 + dz^3|^2 &= u + v\sqrt{2}, \\ u &= a^2 + b^2 + c^2 + d^2, \\ v &= ab + bc + cd - ad. \end{aligned} \quad (9.4)$$

These identities follow by multiplication with the conjugate and reduction using $z^4 = -1$ and $\sqrt{2} = z - z^3$.

The implementation uses the ring

$$\mathcal{D} = \mathbb{Z}[z, 1/2] = \mathbb{Z}[i, 1/\sqrt{2}]. \quad (9.5)$$

An amplitude is a four-integer numerator divided by 2^s . For Hadamard, multiply each sum or difference by $\delta = z - z^3 = \sqrt{2}$ and increment s ; this implements division by $\sqrt{2}$ without floating point. The T gate applies the signed shift on the selected branch, while $S = T^2$ applies two shifts. The exact synthesis literature studies precisely this coefficient domain [5, 6].

An important correction about the hierarchy. Once $1/\sqrt{2}$ has been adjoined for normalized Hadamards, $\zeta_8 = (1 + i)/\sqrt{2}$ is already in the ambient scalar ring. Accordingly, adding T is not necessarily a new *number-field* extension beyond the normalized C_4 setting. It is an additional local gate and a richer convenient numerator format. It extends Clifford dynamics because T is not a Clifford generator, not because the normalization-free label C_4 by itself forbids every eighth-root number.

9.3 Closure and equivalence theorem

Theorem 9.1 (Exact phase-count encoding of Clifford+ T). *Using bitstring-indexed branch vectors over $\mathcal{D}$, ordinary tensor products, and the integer update rules above, every finite Clifford+ T circuit has an exact phase-count representation. Evaluating z at $e^{i\pi/4}$ intertwines every encoded gate with the standard*

quantum gate and therefore preserves all circuit amplitudes and their Born probabilities. The same statement holds when additional Boolean permutation oracles are supplied exactly.

Proof. Evaluation is a ring homomorphism because $\zeta_8^4 + 1 = 0$. The gate updates agree entrywise with H , S , T , and CNOT; a Boolean permutation agrees by its basis action. Sums, products, and tensor products commute with evaluation. Induction on the gate sequence proves amplitude equality. Standard gate unitarity, or the pairwise Hadamard norm identity and phase/permutation invariance, proves norm preservation. The probability statement uses the usual Hilbert-space measurement rule under this identification. $\square$

This theorem is an exact encoding of known quantum arithmetic, not a distinct physical theory. The primitive character quotient is the reason the encoding has complex structure, even when the code uses no complex-number datatype.

For $HS^kH|0\rangle$, one obtains

$$P(0) = \left(1, \frac{1}{2}, 0, \frac{1}{2}\right)_k, \quad P(1) = \left(0, \frac{1}{2}, 1, \frac{1}{2}\right)_k. \quad (9.6)$$

For $HTH|0\rangle$,

$$P(0) = \frac{2 + \sqrt{2}}{4}, \quad P(1) = \frac{2 - \sqrt{2}}{4}. \quad (9.7)$$

Unlike the earlier Hamming-only toy splitter, these circuits preserve the appropriate normalized norm at every step.

9.4 Measurement and projective caveats

The representation covers unitary circuits and computes their measurement probabilities exactly. A normalized state obtained by conditioning on an arbitrary outcome may require division by $\sqrt{p}$, which need not belong to $\mathcal{D}$. A measurement-capable implementation should therefore keep unnormalized branch vectors and an exact probability record, or explicitly extend its scalar domain. Closure under unitary updates does not silently prove closure under every normalized postselection.

Global phase may also change the apparent required field of a particular matrix representation. For maximal CHSH measurements, real eigenvectors involving $\cos(\pi/8)$ suggest a larger field if that real gauge is insisted upon. However the actual observables are implemented already by Clifford+ T circuits:

$$U_+ = SHTHS^\dagger, \quad U_+^\dagger Z U_+ = (Z - X)/\sqrt{2}, \quad (9.8)$$

$$U_- = SHT^\dagger HS^\dagger, \quad U_-^\dagger Z U_- = (Z + X)/\sqrt{2}. \quad (9.9)$$

Thus a C_{16} lift is not necessary for that experiment. The earlier field-degree argument neglected projective equivalence.

10 A Boolean phase-path theorem and its computational meaning

The gate rules have a second exact implementation: enumerate Boolean paths and accumulate integer phase counts. This is directly related to established polynomial and sum-over-paths formulations [9–11].

Theorem 10.1 (Phase-path representation). *Consider a circuit built from H , diagonal powers of T , and reversible Boolean gates, with h Hadamard occurrences. For computational basis input x there are Boolean functions F_x and a phase function p_x with values in $\mathbb{Z}/8\mathbb{Z}$ such that*

$$\langle y | U | x \rangle = 2^{-h/2} \sum_{\lambda \in \{0,1\}^h: F_x(\lambda)=y} \zeta_8^{p_x(\lambda)}. \quad (10.1)$$

Proof. A Hadamard acting on a bit a introduces a new output bit b and contributes the factor $2^{-1/2} \zeta_8^{4ab}$. A T^k gate on bit a contributes ζ_8^{ka} without changing the bit. A reversible Boolean gate updates bit values deterministically; CNOT uses XOR and Toffoli uses an AND-controlled XOR. Following these rules produces F_x and the sum of all phase contributions modulo eight. Multiplying gate factors along a path and summing paths ending at y gives equation (10.1). $\square$

The resulting program has Boolean control expressions, but its amplitudes are *integer-weighted sums of phases*. They are not obtained by XORing all paths. With eight counts $n_0, \dots, n_7$ for each output, opposite-phase cancellation reduces the numerator to

$$(n_0 - n_4) + (n_1 - n_5)z + (n_2 - n_6)z^2 + (n_3 - n_7)z^3. \quad (10.2)$$

This is the C_8 version of the four-position quotient.

Phase kickback is an especially transparent example. Since $|-\rangle = (|0\rangle - |1\rangle)/\sqrt{2}$ is an eigenvector of the bit flip,

$$U_f|x\rangle|-\rangle = (-1)^{f(x)}|x\rangle|-\rangle = J^{2f(x)}|x\rangle|-\rangle. \quad (10.3)$$

The logical predicate is converted into a half-turn phase. The signed phase sum after final Hadamards is a Walsh-type transform of $(-1)^{f(x)}$, not the original truth-table XOR sum.

Complexity is not removed by notation. Direct enumeration may take 2^h paths; dense state propagation has 2^n amplitudes. Counts need growing integers, so an honest analysis must include both arithmetic-operation count and bit complexity. Polynomial-size Boolean descriptions can encode hard counting tasks [9]. Any claim of a faster CM method must exploit a stated structural restriction and compare against existing path-sum, stabilizer, tensor-network, decision-diagram, or model-counting methods [8, 12–14]. The present algorithms establish semantics and reproducibility, not a new general simulation bound.

11 Fresh verification of the lifted calculations

11.1 Independent implementations and exactness

The supplementary code contains an integer-only cyclotomic backend and an independently organized path enumerator. Amplitudes are tuples of integers, denominators are powers of two, and probabilities are rational pairs $r + s\sqrt{2}$. Equality and normalization tests in this backend are exact. A separate complex-double backend supplies a numerical cross-check; that check is explicitly not used to certify exact identities.

The Pauli-conjugation group enumeration uses exact signed bit representations rather than floating-point matrix matching. The random circuits include phase powers, CNOT, and where possible Toffoli; this is intentionally broader than the Clifford-only group check. The independent path tests use at most eight Hadamards so that all paths are actually enumerated. Full definitions and commands are given in section B.

11.2 What the algorithm examples do and do not demonstrate

For Deutsch–Jozsa, the all-zero output amplitude is

$$2^{-n} \sum_x (-1)^{f(x)}. \quad (11.1)$$

It has magnitude one for constant functions and vanishes for balanced ones. Exhausting the promise sets for two and three inputs verifies the implementation against this identity. The oracle is supplied explicitly in the test; constructing it efficiently from an arbitrary external problem remains a separate task.

Check	Newly obtained result
Parallelogram identity on small integer tuples	6,561 exact cases, no failures
Exact projective Clifford enumeration	24 one-qubit; 11,520 two-qubit elements
Random exact circuit propagation	240 circuits, 1–4 qubits, 24 gates each
Intermediate exact normalization	5,760 checks, no failures
Independent exact paths versus exact state propagation	120 circuits, no discrepancies
Numerical cross-check against complex doubles	Maximum amplitude difference 1.12×10^{-15}
Deutsch–Jozsa, all promised functions	8/8 at $n = 2$; 72/72 at $n = 3$
Grover, one iteration, every marked input	$P = 1$ at $n = 2$; $P = 25/32$ at $n = 3$
Bell correlations	$E(ZZ) = E(XX) = 1$; $E(ZX) = E(XZ) = 0$
Optimal CHSH via exact C_8 gates	$2\sqrt{2}$; both local marginals $1/2$
CM phase carry identity	8,192 input/phase/CM cases
Two-input sign-oracle normal forms	All 16 CMs verified on all inputs

Table 4: Recomputed regression results. Randomized tests use a fixed seed. Gate closure and the intertwining identities have separate proofs; finite tests do not replace them.

For Grover with one marked item among N , one iteration gives marked amplitude $\sin(3\theta)$ with $\sin \theta = 1/\sqrt{N}$. Direct gate propagation gives success probabilities one for $N = 4$ and $25/32$ for $N = 8$, matching this elementary amplitude calculation. The three-qubit marked-state phase uses a nonlinear oracle outside the Clifford-only subgroup.

For CHSH, the Bell state and the observables $A_0 = Z$, $A_1 = X$, $B_0 = (Z + X)/\sqrt{2}$, $B_1 = (Z - X)/\sqrt{2}$ give correlations $(1, 1, 1, -1)/\sqrt{2}$. The exact circuit calculation also checks that changing the remote setting leaves each local marginal equal to $1/2$. This is a centralized calculation of quantum probabilities. It is not an experimental Bell test, a local-hidden-variable explanation, or evidence that Boolean hardware can evade Bell’s assumptions. The conclusion is representational agreement, as guaranteed by theorem 9.1.

12 Literature review: what is already known, and what is distinctive?

12.1 Search scope and evidence standard

The review was conducted through 17 September 2026. Searches covered the supplied title and author; correspondence matrices and matrix logic; vector logic and square roots of NOT; finite-field and set-based quantum models; Boolean polynomial path sums; exact cyclotomic synthesis; ZH and categorical calculi; and tensor, decision-diagram, model-counting, and semi-tensor-product methods. Primary author papers, repository versions, and publisher records were preferred. The bibliography identifies the inspected version when version changes matter.

This is a targeted deep review, not a systematic review with a provably complete citation corpus or a patent/priority search. No absence-of-results claim is used as proof of novelty. The search did not establish that the precise package of CM notation, audits, and translations here has appeared before; equally, it did not establish that it is new. Several of the central mathematical ideas have close, explicit predecessors. The recent semi-tensor-product preprint is reported as an adjacent proposal, not as independently verified performance evidence.

12.2 Matrix logic and vector logic: direct predecessors

Stern’s matrix logic. August Stern’s 1988 book *Matrix Logic* already develops a matrix/operator formulation of logical transformations [15]. The publisher preview establishes historical overlap with the

broad idea of representing logic in vector spaces. A full technical comparison with that book has not been completed here, and its broader physical interpretations are not adopted. It is enough to rule out treating “logic represented by matrices” as a novel general principle.

Mizraji’s vector logic. Mizraji’s vector logic maps truth values to orthonormal vectors, monadic operations to square matrices, and dyadic operations to rectangular matrices acting on Kronecker products [2]. In a two-dimensional truth space, a dyadic truth-valued gate is naturally a 2×4 map. Droncheff’s two-input CM is instead a 2×2 table whose contraction with two one-hot vectors returns a scalar truth value. The dimensions and operational semantics differ, but equation (2.10) explicitly translates every predicate CM into such a deterministic dyadic gate. This strengthens the prior-art connection: the name “correspondence matrix” does not by itself establish mathematical separation.

Mizraji also studies counterfactual vector logic using square roots of NOT [16]. This is a close conceptual predecessor to extending a logical operator calculus beyond its original Boolean values. It is not the same as the integral phase quotient here, and its logical interpretation need not be the interpretation used in a physical quantum circuit.

A particularly close imaginary-unit analogue. The revised manuscript on generalized square roots of NOT explicitly discusses matrix extensions of the imaginary unit, Deutsch-type reasoning, and matrix circular functions [17]. On a two-valued truth space, with NOT represented by X , one familiar root is

$$V = \frac{1+i}{2}I + \frac{1-i}{2}X, \quad V^2 = X, \quad V^4 = I. \quad (12.1)$$

This is close to the motivating question, but differs from $J^2 = -I$ and from the strictly Boolean convolution model. It uses complex coefficients; it does not make i a new Boolean truth value. The distinction is instructive: both V and J have period four, but their squares and representations differ. The present contribution must therefore be judged by the explicit quotient and compiler identities, not by fourfold periodicity or the generic use of matrices for phase.

12.3 Finite-field and set-based models: close to the Boolean stage

Modal quantum theory. Schumacher and Westmoreland formulate quantum-like structures over finite fields with a modal distinction between possible and impossible outcomes [4]. This line of work demonstrates that superposition-like algebra, tensor structure, and nonclassical-looking logical properties can be investigated without the usual complex Hilbert-space probability model. It is an important counterweight to an overbroad conclusion that characteristic two forbids every useful quantum analogue. Our no-go theorem concerns Hamming-preserving $\mathbb{F}_2[C_4]$ -linear maps under a specified measurement functional. It does not invalidate modal models with different measurement axioms.

Quantum mechanics over sets. Ellerman’s set-based program uses the correspondence between subsets and binary vectors, symmetric difference, and an integer-valued overlap count such as $|S \cap T|$ [3]. It also explicitly discusses a sets-to-vector-spaces lifting principle. This is especially close to the Hamming/counting portion of the present investigation. The lesson is twofold: an external non-modular count on binary data is an established construction, and its status depends on the model’s probability assumptions. Our integral C_4 lift and opposite-phase quotient specify a particular character representation; the cited set program has a different organization and interpretation. Neither adjacency justifies deriving empirical quantum probabilities from truth values without additional premises.

12.4 Boolean paths and exact amplitudes: strong prior overlap

Dawson and collaborators express quantum outputs through counts of solutions to polynomial equations over $\mathbb{Z}_2$ [9]. Their connection between Boolean path constraints and signed amplitude counts is a direct predecessor of theorem 10.1. Thus “AND/XOR descriptions plus integer signed counting can represent quantum computation” is not a new conclusion of the CM route.

Amy develops path-sum semantics for functional quantum-circuit verification, including rewrite methods and a tractable Clifford case [10]. Later work gives complete equational theories for sum-over-paths expressions with unbalanced amplitudes, including coefficient-domain distinctions [11]. These are particularly relevant to any proposed CM simplifier: a new rule should be translated into existing path-sum syntax and tested for whether it is genuinely stronger, more local, more efficient to implement, or merely an equivalent presentation.

The useful distinction here is representational granularity. A CM can serve as a small truth-table object for a local predicate, while a path sum expresses global amplitude contributions. Equation (8.4) is an exact interface between the two. Its value would be demonstrated by a verified compiler or a benchmark in which local CM decomposition reduces an actual verification or contraction cost.

12.5 Graphical and categorical calculi

The ZH calculus was developed to handle quantum computations involving classical nonlinearity, with compact representations related to Boolean AND and non-Clifford structure [18]. It is therefore a strong neighboring formalism for the proposed Boolean-predicate phase translation, especially when higher-degree monomials and controlled phases are involved. A CM-oriented graphical notation would need to compare against ZH’s semantic and equational results rather than present graphical Boolean/quantum unification as new in itself.

Categorical quantum semantics separates compositional structure from particular matrix coordinates and scalar choices [19]. That viewpoint clarifies why changing scalars, tensor operations, and adjoints must be explicit. It also suggests the right architectural goal for a CM compiler: preserve composition under a typed interpretation. It does not remove the need to state which probability model is being interpreted.

12.6 Exact synthesis and known coefficient rings

The ring $\mathbb{Z}[1/\sqrt{2}, i]$ is central to exact Clifford+ T synthesis. Giles and Selinger characterize multiqubit exact synthesis with local ancillas in terms of this ring [5], while Kliuchnikov, Maslov, and Mosca study exact single-qubit synthesis [6]. Consequently the Gaussian/cyclotomic phase-count arithmetic here is a standard exact quantum coefficient domain in a CM-motivated coordinate system. No novelty is claimed for its closure or for implementing H , S , T , and CNOT within it.

Aaronson and Gottesman’s stabilizer algorithms give a strong baseline whenever the permitted gate set is Clifford [8]. A dense CM count array will generally not compete with a compact stabilizer tableau simply because it uses Boolean data. Conversely, Aharonov’s Hadamard–Toffoli universality result shows why adding nonlinear reversible gates changes the computational story even without adding a literal 45° phase instruction [7]. Gate-set restrictions and coefficient representations must be analyzed separately.

12.7 Existing computational bridges and a recent close neighbor

Markov and Shi show how tensor-network contraction exploits circuit structure, with complexity controlled by a graph-width parameter [12]. Hong and collaborators combine tensor representations with decision diagrams [13]. Both are natural baselines for a CM proposal that uses local decomposition,

shared subexpressions, or factorization. The relevant questions concern intermediate tensor size, ordering, graph sharing, and exact arithmetic growth, rather than array dimension in isolation.

Mei, Bonsangue, and Laarman investigate quantum simulation through model counting [14]. This is a modern practical neighbor of the Boolean path-count interpretation. Replacing Boolean formulas by small CM objects could be useful as a front-end encoding or rewrite layer, but the hard weighted-counting task does not disappear. A credible claim would compare solver size and end-to-end cost on the same instances.

A particularly relevant recent preprint by Li and collaborators uses semi-tensor products for exact synthesis of CNOT and phase-polynomial circuits [20]. Its approach separates topology enumeration from matrix-based instantiation and factorization. This is direct evidence that Boolean/matrix formalisms are actively being used as quantum compilation tools. It is not the same representation as the CM phase quotient, and the performance claims in that preprint were not reproduced here. The correct research response is to investigate a translation and compare synthesis kernels, not infer that either framework automatically dominates the other.

Prior line of work	Closest overlap	Main distinction to preserve
Matrix / vector logic	Logical operators as matrices and tensors; roots of NOT.	A truth-valued gate matrix is not the same object as a scalar predicate table or phase-count coefficient.
Modal and set models	Binary superposition-like structures; counting overlaps; lifting language.	Measurement axioms differ; physical equivalence is not automatic.
Boolean polynomial paths	Boolean constraints plus signed path counts.	The global representation is established; CM-local compilation may be a useful interface.
ZH / path-sum rewriting	Boolean nonlinearities and quantum phase in a formal calculus.	New CM rules need semantic proofs and comparative evaluation.
Exact cyclotomic synthesis	Gaussian and eighth-root coefficient rings.	Pair/array notation does not create a new scalar theory.
Tensor / decision diagrams / model counting	Structure-aware exact simulation.	Any advantage must beat appropriate existing backends on stated instance families.
Semi-tensor-product synthesis	Matrix factorization applied to quantum circuit compilation.	A close 2026 preprint, not an independently confirmed performance benchmark here.

Table 5: A comparison map. Similarity is not identity, but it substantially narrows defensible novelty claims.

12.8 A conservative novelty assessment

The following are established mathematical ingredients, not discoveries claimed here: regular cyclic representations; group algebras; Gaussian and cyclotomic quotients; complex arithmetic in pairs; Boolean path-sum descriptions; and exact Clifford+ T simulation. The finite classifications are reproducible results for a particular explicitly defined CM phase model. They may be useful to document, but priority for such small algebraic classifications has not been established.

The most defensible present contribution is a *verified synthesis*: it locates the precise semantic changes in a CM-to-phase construction, proves its intertwining and no-go statements, corrects misleading shortcuts, and gives a typed route from original predicate CMs to reversible and phase oracles. Potential algorithmic novelty is deferred to measurable compiler or rewriting improvements. This narrower claim is stronger scientifically than calling an isomorphic encoding a new theory of quantum mechanics.

13 Applications, human benefit, and a concrete research agenda

13.1 The most immediate use: making reasoning and software more reliable

The investigation repeatedly encountered errors caused by conflating a truth table, an amplitude array, and a gate matrix. A typed implementation that makes those distinctions explicit can prevent such errors mechanically. A small verified reference interpreter could be valuable for teaching and testing: a user can see a logical predicate, its CM, its reversible embedding, the phase counts accumulated by paths, and the final quotient amplitude in one trace.

This is a plausible near-term benefit even without a speed advantage. Correct explanations reduce conceptual barriers; exact arithmetic avoids numerical ambiguity in small examples; independently checkable certificates make compiler transformations easier to audit. Existing path-sum verification work demonstrates that exact semantics is a substantive engineering problem, not only a pedagogical concern [10, 11]. The present prototype supplies an arithmetic and testing core, not a production verifier.

13.2 A candidate useful result: certified local phase rewrites

The compiler law

$$D_{A \oplus B}^{(k)} = D_A^{(k)} D_B^{(k)} D_{A \wedge B}^{(-2k)} \quad (13.1)$$

provides a small, exact rule whose correctness can be certified by four input evaluations. A research implementation could enumerate two- and three-input predicate rewrites, attach the necessary phase corrections, and send the resulting alternatives to a gate-cost optimizer. At half-turn phases the correction disappears; at eighth-root phases it carries the extra information that naive XOR translation loses.

The rule is not claimed as a new Boolean identity. The untested proposition is that *packaging local identities as CM certificates* may make a synthesis or verification workflow smaller, easier to check, or easier to explain. A certificate should contain the two predicate tables, the phase modulus, the correction table, and the resource accounting for the synthesized circuit. That would separate semantic correctness from optimizer heuristics.

13.3 Safe compression: quotient late, or quotient with a proof

Because Q is a ring homomorphism for *integer convolution*, quotienting each factor before contracting a purely convolutional expression gives the same quotient as contracting first. This may reduce four raw phase bins to two signed coordinates, or eight bins to four. It is a constant-factor representation improvement, not an asymptotic simulation result.

The same move is unsafe across Boolean XOR without the carry correction, or across an operation whose type is not respected. A compiler pass should therefore prove that a subexpression is in the integer phase algebra before reducing its bins. This supplies a concrete correctness criterion for a future CM-based simplifier. Whether it lowers end-to-end cost beyond existing exact cyclotomic arithmetic remains to be measured.

13.4 Benchmarkable questions rather than unbounded promises

The benchmark suite should include Clifford circuits, nonlinear Boolean oracles, phase-polynomial circuits, low-width tensor networks, and deliberately difficult instances. Appropriate baselines include stabilizer tableaux, established path-sum reductions, ZH methods, tensor/decision-diagram engines, and model counters [8, 10, 12–14, 18]. Report gate count, logical ancillas, exact coefficient bit lengths, peak memory, and wall time; report failures and unfavorable instances as well as successes. A compiler comparison must include the overhead of converting to and from CM form.

Direction	Experiment	Evidence that would count as progress
Typed CM compiler	Implement separate predicate, phase-count, and operator types; compile O_A and $D_A^{(k)}$.	All translations checked against an independent exact backend; invalid cross-type rewrites rejected.
Local rewrite library	Enumerate bounded-input CM decompositions and translate phase corrections.	Smaller circuits or smaller verification expressions than a stated baseline, including correction-gate costs.
Structure-aware paths	Use CM factorization to expose shared predicates and low-width interaction graphs.	Reduced intermediate counts, tensor width, or model-counting instance size on specified circuit families.
Proof certificates	Encode the quotient, gate intertwiners, and compiler rules in a proof assistant.	Machine-checked statements with explicit domains; no reliance on informal array-shape equivalence.
Phase-count arithmetic	Compare raw-bin accumulation, early quotienting, and existing cyclotomic backends.	Lower memory or bit-operation cost at identical exact outputs, measured over reproducible instances.
Education	Build a traceable CM-to-oracle-to-phase visual notebook.	Independent learners correctly distinguish XOR cancellation, signed interference, and measurement assumptions.

Table 6: Proposed investigations with a falsifiable success criterion. None is reported as a completed benchmark.

13.5 Further mathematical questions worth investigating

Classifying quotient-compatible maps. Rather than asking which raw maps preserve an unnecessarily strong Hamming norm, classify integer block operators U satisfying

$$U(\ker Q) \subseteq \ker Q, \quad (13.2)$$

then determine which induced maps preserve the quotient quadratic form. This separates well-definedness from unitarity and may yield useful normal forms for implementations. The basic H and conditional rotations here are examples. It is a problem in representation and module theory, not an assertion that every such map is physically implementable with low cost.

Comparing cyclic sectors. The real regular C_4 representation decomposes into a trivial sector, a sign sector, and a two-dimensional quarter-turn sector. Our quotient selects the last. Other sector choices give different toy theories or signal representations. Studying their norms and operational assumptions could clarify precisely which ingredients are responsible for the observed interference pattern. This is an explanatory classification question; selecting a sector alone does not derive nature’s choice.

Exact measurement and conditioning. Unitary closure is simpler than normalized postselection. A rigorous extension should define outcome effects, unnormalized state updates, conditioning, and mixed states while stating the scalar domain required at each stage. This would prevent accidental claims that all measurements remain within a fixed power-of-two numerator format.

A resource-sensitive oracle theory. The map $A \mapsto O_A$ proves semantic implementability, but useful algorithms require efficient oracles. Extending CM decomposition to many variables should track Boolean circuit size, phase-polynomial degree, interaction width, and ancilla reuse. The aim would be to identify a family where CM decomposition provably improves a resource bound, not to infer tractability from the existence of a binary encoding.

13.6 What “useful to humanity” can responsibly mean here

The strongest immediate possibilities are accessible mathematical education, more reliable quantum-software validation, and reproducible exact small-circuit computation. A later compiler improvement could reduce wasted computation or help researchers check designs before running expensive experiments. These are plausible pathways, not measured societal impacts of this prototype.

Applications to chemistry, materials, sensing, or other scientific domains would require a chain of additional evidence: a useful compiler improvement, integration into a relevant algorithm, and a demonstrated practical gain under realistic hardware or simulation constraints. The present work does not solve those scientific problems, establish a new energy-efficient device, or provide a shortcut around known simulation complexity. Framing the contribution honestly makes its potential benefits more credible and helps avoid diverting effort on the basis of an attractive but incorrect analogy.

14 Conclusion

The original question has a precise two-part answer. Strict Boolean CMs do support a faithful fourfold rotation action and useful XOR-cancellation experiments, but the tested Hamming and correlation-preserving operator models do not supply a quantum Hadamard. The successful phase construction changes the coefficient arithmetic: an integral CM-count algebra is quotiented so that opposite positions represent additive negatives. The equation $QP = JQ$ then makes the role of CM rotation exact. Standard quantum amplitudes, gates, and circuit probabilities follow as an encoding in Gaussian or cyclotomic coordinates, with the usual quantum measurement interpretation stated rather than derived from truth values.

A second bridge is more directly computational: original CM truth predicates specify reversible oracles and phase gates, with exact correction rules relating XOR decomposition to phase composition. This avoids confusing truth-table equivalence with amplitude equivalence. Extensive prior work already covers matrix logic, finite-field models, Boolean path sums, graphical calculi, and exact quantum rings. The next credible contribution is therefore a verified, resource-aware CM interface to those methods, supported by public code, explicit assumptions, and comparative benchmarks.

A Correction ledger: claims that needed qualification or replacement

This appendix records material changes to the exploratory discussion. Keeping the corrections visible is part of the scientific result; a polished consolidation should not quietly preserve the exciting claims and omit their failed premises.

Table 7: Audit of the main conceptual and computational shortcuts.

Earlier claim or ambiguity	Verified replacement
The symbol m is a separate operator.	It was a text-extraction rendering of the manuscript’s rotated-biconditional XOR glyph. This paper consistently uses $\oplus$ for that operation.
The right column is $Y = 1$.	Under the supplied convention, $Y = 1$ selects the first/left column. The column entries are whatever the CM contains there, not the ket $ 1\rangle$ itself.
A masked rotation gives an order-four controlled phase.	The proposed map is $\begin{pmatrix} a & b \\ c & d \end{pmatrix} \mapsto \begin{pmatrix} c & b \\ d & d \end{pmatrix}$. It destroys information; $F(E_0) = 0$. See equation (5.9).
A half-turn is Boolean negation.	Rotation permutes positions. Complement flips values. They agree on some arrays, but not in general. In the signed quotient a half-turn induces additive negation by an added relation.

Earlier claim or ambiguity	Verified replacement
J is one of the original sixteen CMs.	J has a negative entry and is not a binary CM. It is the induced operator satisfying $QP = JQ$.
The four CM phases are complex scalars inside $\mathbb{F}_2$.	They are group elements or operators. The scalar identities of $\mathbb{C}$ do not hold in characteristic two.
CM multiplication is unambiguous.	Pointwise AND, AND/XOR matrix multiplication, and convolution have different units and meanings.
XOR reinforcement happens when equal paths meet.	Equal Boolean contributions cancel. Signed amplitude reinforcement requires keeping multiplicities.
Truth uncertainty is already quantum superposition.	An unvaluated predicate is not automatically a coherent quantum state. A state space, amplitude rules, and measurement interpretation must be specified.
The four sampled weights prove a sinusoidal phase law.	They agree with four samples for a particular carrier. No continuous phase law or general Born behavior follows.
$w/4$ is derived from logic alone as a physical probability.	It is unique given disjoint additivity, normalization, and equal rotational weighting. Those statistical assumptions are additional.
An integer correlation is an $\mathbb{F}_2$ inner product.	Integer counting of binary coefficients is not additive for XOR; ordinary polarization arguments cannot be used without checking the coefficient domain.
A richer preserved form may enlarge the global isometry group.	Preserving a form that contains the old norm adds constraints. The full correlation preserves the zero-lag Hamming norm and gives the same 32 global maps.
The toy splitter is a normalized reversible analogue of H .	It has $B^4 = 0$. Its special initial carrier has $W/4 = 1/2$, and matching final weights do not prove stepwise normalization.
The finite search covers every possible Boolean quantum theory.	It covers all 2×2 operators over one specified sixteen-element convolution ring and specified measurement conditions.
The lift embeds the entire Boolean algebra into complex amplitudes.	The two algebras share an integral source. The quotient is not XOR-additive and loses truth-table information; equation (6.10) gives the defect.
Hamming norm is the same norm after the signed lift.	The lifted quotient norm is $C_0 - C_2$, not C_0 . Some nonzero binary CMs become null under Q .
Keeping four phases means computation is only Clifford.	That is true only with the Clifford gate restriction. Nonlinear reversible oracles such as Toffoli change the available gate set.
Adding C_8 necessarily introduces a new ambient scalar field.	Normalized Hadamards already adjoin $1/\sqrt{2}$, so $\zeta_8 = (1+i)/\sqrt{2}$ is present. T is a new local gate; the four-coordinate format supports it conveniently.
The optimal CHSH measurement requires C_{16} .	Clifford+ T implements it exactly up to the relevant global phases. A real eigenvector gauge created the apparent extra requirement.
Algorithm agreement demonstrates a physical quantum device or a speedup.	It verifies a classical exact encoding of standard quantum amplitudes. No physical nonlocal device or new complexity advantage was tested.
Every normalised post-measurement state stays in the same integer format.	Conditioning can require division by $\sqrt{p}$ outside the original domain. Use unnormalised states or enlarge the domain explicitly.
The matrix/Boolean-to-quantum idea is new.	The literature contains direct predecessors. Novelty of specific CM-based software or identities requires comparison beyond a naming distinction.

B Reproducibility, verification boundaries, and data encoding

B.1 Files and commands

The source package contains the LaTeX manuscript, bibliography, two main verification scripts, a supplementary bridge-check script, generated JSON results, and finite-set membership data. No third-party paper or font files are redistributed. The supplied original manuscript is cited rather than

bundled.

From the project directory, run:

```
python code/verify_finite.py
python code/verify_quantum.py
python code/verify_bridges.py
python code/make_tables.py
latexmk -pdf -interaction=nonstopmode paper.tex
```

The exact amplitude backend in `phase_calculus.py` uses Python integers and rational pairs. NumPy is needed for the finite search and independent numerical comparisons. LaTeX compilation uses standard mathematical packages and BibLaTeX with Biber. The README records the tested environment. Elapsed times in the JSON files are diagnostics, not comparative performance benchmarks.

Finite search details. An element is encoded by the integer $\sum_{j=0}^3 a_j 2^j$; its displayed CM is $\begin{pmatrix} a_0 & a_1 \\ a_3 & a_2 \end{pmatrix}$. A matrix is a tuple (a, b, c, d) in row-major *operator* order. A two-branch state is ordered $(|1\rangle, |0\rangle)$ in this finite model. The code builds the full 16×16 multiplication table directly from circular convolution. Every candidate is applied to all 256 states; the full pair forms are checked on all state pairs for every surviving candidate. Pre-filters only discard candidates that already fail necessary conditions. Invertibility is tested by whether the determinant is a unit; in $\mathbb{F}_2[g]/((g+1)^4)$, this is equivalent to odd coefficient parity.

Exact quantum tests. The quantum backend uses ascending bitstrings, with qubit zero the leftmost bit. Amplitudes are polynomials modulo $z^4 + 1$ divided by 2^s . A fixed seed, 20260917, generates the random tests. Exact integer state propagation is cross-checked against an independently structured exhaustive path sum on 120 bounded-Hadamard circuits. The complex-double comparison is separately labelled; its small numerical discrepancy is not substituted for exact equality.

What was not verified. No formal proof-assistant certification was performed. The original manuscript was not audited in its entirety. No optimizer, hardware implementation, practical speedup, or physical experiment was benchmarked. The small-circuit tests do not by themselves prove arbitrary-size closure; that conclusion follows from the algebraic gate-intertwining proof. The literature review does not establish priority or exhaust all related work.

B.2 Notation and normalization checks

The zero object is 0; T is the all-ones truth table; I_2 is the ordinary two-dimensional identity; E_0 is the convolution identity. A coefficient “1” inside $\mathcal{A}_2$ denotes E_0 , not T. This distinction is essential in the finite search tables.

A phase-count state in the common Gaussian format has denominator $2^{h/2}$. The exact C_8 backend instead uses denominator 2^s . Thus its squared probabilities have denominator 2^{2s} . These are equivalent representations when applicable; the exponent variables must not be interchanged. The code canonically removes common factors of two from all numerator coefficients.

B.3 Additional verified bridge facts

The supplementary checks verify $QP = JQ$, $Q^T Q = I - P^2$, integral convolution compatibility, the XOR carry correction, the four-element shell-action kernel, and the raw CM Hadamard’s quotient action. They also verify the truth-coordinate permutation under rotation and that the reversible CM oracle embeddings

are permutations and satisfy equation (8.3). These checks are small, exact regressions for identities that also have direct proofs.

One useful corollary of the lift is worth emphasizing. Reducing the Gaussian quotient modulo two produces

$$\mathbb{Z}[i]/2\mathbb{Z}[i] \cong \mathbb{F}_2[g]/((g+1)^2). \quad (\text{B.1})$$

It does not retain four distinct complex scalar phases: $g^2 = 1$ there. Moving back to parity arithmetic after imposing the signed relation cannot restore the lost amplitude multiplicities.

C The four complete Boolean interference tables

The entry in row A , column B of table k is the integer encoding of $A \oplus \mathcal{R}^k B$. Encodings are defined below. These are binary support-interference tables, not tables of complex amplitude addition.

Code	Cyclic polynomial	CM label
0	0	0
1	1	$[\wedge]$
2	g	$[\uparrow\uparrow]$
3	$1 \oplus g$	$[L]$
4	g^2	$[\neg\vee]$
5	$1 \oplus g^2$	$[\Leftrightarrow]$
6	$g \oplus g^2$	$[\neg R]$
7	$1 \oplus g \oplus g^2$	$[\Leftarrow]$
8	g^3	$[\Downarrow]$
9	$1 \oplus g^3$	$[R]$
10	$g \oplus g^3$	$[\text{XOR}]$
11	$1 \oplus g \oplus g^3$	$[\vee]$
12	$g^2 \oplus g^3$	$[\neg L]$
13	$1 \oplus g^2 \oplus g^3$	$[\Rightarrow]$
14	$g \oplus g^2 \oplus g^3$	$[\neg\wedge]$
15	$1 \oplus g \oplus g^2 \oplus g^3$	T

Clockwise coordinate order is (a_0, a_1, a_2, a_3) around the square, with the displayed array $\begin{pmatrix} a_0 & a_1 \\ a_3 & a_2 \end{pmatrix}$. The names are only labels for the arrays; all computation uses the encoded coefficients.

$A \setminus B$	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1	1	0	3	2	5	4	7	6	9	8	11	10	13	12	15	14
2	2	3	0	1	6	7	4	5	10	11	8	9	14	15	12	13
3	3	2	1	0	7	6	5	4	11	10	9	8	15	14	13	12
4	4	5	6	7	0	1	2	3	12	13	14	15	8	9	10	11
5	5	4	7	6	1	0	3	2	13	12	15	14	9	8	11	10
6	6	7	4	5	2	3	0	1	14	15	12	13	10	11	8	9
7	7	6	5	4	3	2	1	0	15	14	13	12	11	10	9	8
8	8	9	10	11	12	13	14	15	0	1	2	3	4	5	6	7
9	9	8	11	10	13	12	15	14	1	0	3	2	5	4	7	6
10	10	11	8	9	14	15	12	13	2	3	0	1	6	7	4	5
11	11	10	9	8	15	14	13	12	3	2	1	0	7	6	5	4
12	12	13	14	15	8	9	10	11	4	5	6	7	0	1	2	3
13	13	12	15	14	9	8	11	10	5	4	7	6	1	0	3	2
14	14	15	12	13	10	11	8	9	6	7	4	5	2	3	0	1
15	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1	0

Table 8: Complete table for $k = 0$: $A \oplus \mathcal{R}^0 B$.

$A \setminus B$	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	2	4	6	8	10	12	14	1	3	5	7	9	11	13	15
1	1	3	5	7	9	11	13	15	0	2	4	6	8	10	12	14
2	2	0	6	4	10	8	14	12	3	1	7	5	11	9	15	13
3	3	1	7	5	11	9	15	13	2	0	6	4	10	8	14	12
4	4	6	0	2	12	14	8	10	5	7	1	3	13	15	9	11
5	5	7	1	3	13	15	9	11	4	6	0	2	12	14	8	10
6	6	4	2	0	14	12	10	8	7	5	3	1	15	13	11	9
7	7	5	3	1	15	13	11	9	6	4	2	0	14	12	10	8
8	8	10	12	14	0	2	4	6	9	11	13	15	1	3	5	7
9	9	11	13	15	1	3	5	7	8	10	12	14	0	2	4	6
10	10	8	14	12	2	0	6	4	11	9	15	13	3	1	7	5
11	11	9	15	13	3	1	7	5	10	8	14	12	2	0	6	4
12	12	14	8	10	4	6	0	2	13	15	9	11	5	7	1	3
13	13	15	9	11	5	7	1	3	12	14	8	10	4	6	0	2
14	14	12	10	8	6	4	2	0	15	13	11	9	7	5	3	1
15	15	13	11	9	7	5	3	1	14	12	10	8	6	4	2	0

Table 9: Complete table for $k = 1$: $A \oplus \mathcal{R}^1 B$.

$A \setminus B$	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	4	8	12	1	5	9	13	2	6	10	14	3	7	11	15
1	1	5	9	13	0	4	8	12	3	7	11	15	2	6	10	14
2	2	6	10	14	3	7	11	15	0	4	8	12	1	5	9	13
3	3	7	11	15	2	6	10	14	1	5	9	13	0	4	8	12
4	4	0	12	8	5	1	13	9	6	2	14	10	7	3	15	11
5	5	1	13	9	4	0	12	8	7	3	15	11	6	2	14	10
6	6	2	14	10	7	3	15	11	4	0	12	8	5	1	13	9
7	7	3	15	11	6	2	14	10	5	1	13	9	4	0	12	8
8	8	12	0	4	9	13	1	5	10	14	2	6	11	15	3	7
9	9	13	1	5	8	12	0	4	11	15	3	7	10	14	2	6
10	10	14	2	6	11	15	3	7	8	12	0	4	9	13	1	5
11	11	15	3	7	10	14	2	6	9	13	1	5	8	12	0	4
12	12	8	4	0	13	9	5	1	14	10	6	2	15	11	7	3
13	13	9	5	1	12	8	4	0	15	11	7	3	14	10	6	2
14	14	10	6	2	15	11	7	3	12	8	4	0	13	9	5	1
15	15	11	7	3	14	10	6	2	13	9	5	1	12	8	4	0

Table 10: Complete table for $k = 2$: $A \oplus \mathcal{R}^2 B$.

$A \setminus B$	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
0	0	8	1	9	2	10	3	11	4	12	5	13	6	14	7	15
1	1	9	0	8	3	11	2	10	5	13	4	12	7	15	6	14
2	2	10	3	11	0	8	1	9	6	14	7	15	4	12	5	13
3	3	11	2	10	1	9	0	8	7	15	6	14	5	13	4	12
4	4	12	5	13	6	14	7	15	0	8	1	9	2	10	3	11
5	5	13	4	12	7	15	6	14	1	9	0	8	3	11	2	10
6	6	14	7	15	4	12	5	13	2	10	3	11	0	8	1	9
7	7	15	6	14	5	13	4	12	3	11	2	10	1	9	0	8
8	8	0	9	1	10	2	11	3	12	4	13	5	14	6	15	7
9	9	1	8	0	11	3	10	2	13	5	12	4	15	7	14	6
10	10	2	11	3	8	0	9	1	14	6	15	7	12	4	13	5
11	11	3	10	2	9	1	8	0	15	7	14	6	13	5	12	4
12	12	4	13	5	14	6	15	7	8	0	9	1	10	2	11	3
13	13	5	12	4	15	7	14	6	9	1	8	0	11	3	10	2
14	14	6	15	7	12	4	13	5	10	2	11	3	8	0	9	1
15	15	7	14	6	13	5	12	4	11	3	10	2	9	1	8	0

Table 11: Complete table for $k = 3$: $A \oplus \mathcal{R}^3 B$.

References

- [1] B. Droncheff. *Correspondence Matrices; Algorithms for Propositional Logic*. User-supplied manuscript, 29 pages. The attached version is the primary source for the CM definitions used here; no publication date is asserted. URL: <https://www.b-theory.com/CorrespondenceMatrices.pdf> (visited on 09/17/2026).
- [2] E. Mizraji. “Vector Logic: A Natural Algebraic Representation of the Fundamental Logical Gates”. In: *Journal of Logic and Computation* 18.1 (2008). Published online 23 October 2007. DOI: 10.1093/logcom/exm057.
- [3] D. Ellerman. *Quantum mechanics over sets*. The repository metadata records a 2013 submission; the PDF served at review time bears a 22 June 2021 date. The comparison concerns its set/vector lifting and counting constructions. 2013. arXiv: 1310.8221. URL: <https://arxiv.org/abs/1310.8221> (visited on 09/17/2026).
- [4] B. Schumacher and M. D. Westmoreland. “Modal Quantum Theory”. In: *Foundations of Physics* 42 (2012), pp. 918–925. DOI: 10.1007/s10701-012-9650-z. arXiv: 1010.2929.
- [5] B. Giles and P. Selinger. “Exact synthesis of multiqubit Clifford+T circuits”. In: *Physical Review A* 87 (2013), p. 032332. DOI: 10.1103/PhysRevA.87.032332. arXiv: 1212.0506.
- [6] V. Kliuchnikov, D. Maslov, and M. Mosca. *Fast and efficient exact synthesis of single qubit unitaries generated by Clifford and T gates*. 2012. arXiv: 1206.5236. URL: <https://arxiv.org/abs/1206.5236> (visited on 09/17/2026).
- [7] D. Aharonov. *A Simple Proof that Toffoli and Hadamard are Quantum Universal*. 2003. arXiv: quant-ph/0301040. URL: <https://arxiv.org/abs/quant-ph/0301040> (visited on 09/17/2026).
- [8] S. Aaronson and D. Gottesman. “Improved Simulation of Stabilizer Circuits”. In: *Physical Review A* 70 (2004), p. 052328. DOI: 10.1103/PhysRevA.70.052328. arXiv: quant-ph/0406196.
- [9] C. M. Dawson, H. L. Haselgrove, A. P. Hines, D. Mortimer, M. A. Nielsen, and T. J. Osborne. “Quantum computing and polynomial equations over the finite field Z_2 ”. In: *Quantum Information and Computation* 5.2 (2005), pp. 102–112. arXiv: quant-ph/0408129.
- [10] M. Amy. “Towards Large-scale Functional Verification of Universal Quantum Circuits”. In: *Electronic Proceedings in Theoretical Computer Science* 287 (2019), pp. 1–21. DOI: 10.4204/EPTCS.287.1. arXiv: 1805.06908.
- [11] M. Amy. “Complete Equational Theories for the Sum-Over-Paths with Unbalanced Amplitudes”. In: *Electronic Proceedings in Theoretical Computer Science* 384 (2023), pp. 127–141. DOI: 10.4204/EPTCS.384.8. arXiv: 2306.16369.
- [12] I. L. Markov and Y. Shi. “Simulating quantum computation by contracting tensor networks”. In: *SIAM Journal on Computing* 38.3 (2008), pp. 963–981. DOI: 10.1137/050644756. arXiv: quant-ph/0511069.
- [13] X. Hong, X. Zhou, S. Li, Y. Feng, and M. Ying. *A Tensor Network based Decision Diagram for Representation of Quantum Circuits*. 2020. arXiv: 2009.02618. URL: <https://arxiv.org/abs/2009.02618> (visited on 09/17/2026).
- [14] J. Mei, M. Bonsangue, and A. Laarman. *Simulating Quantum Circuits by Model Counting*. 2024. arXiv: 2403.07197. URL: <https://arxiv.org/abs/2403.07197> (visited on 09/17/2026).
- [15] A. Stern. *Matrix Logic*. Historical comparison based on the publisher’s preview, not a complete audit of the book. North-Holland, 1988. URL: https://api.pageplace.de/preview/DT0400.9781483295497_A23889179/preview-9781483295497_A23889179.pdf (visited on 09/17/2026).

- [16] E. Mizraji. “Vector logic allows counterfactual virtualization by the square root of NOT”. In: *Logic Journal of the IGPL* 29.5 (2021), pp. 859–870. doi: 10.1093/jigpal/jzaa026. arXiv: 2003.11519.
- [17] E. Mizraji. *Generalized “Square roots of Not” matrices, their application to the unveiling of hidden logical operators and to the definition of fully matrix circular Euler functions*. Version 5, 10 June 2024; first submitted in 2021. 2024. arXiv: 2107.06067. URL: <https://arxiv.org/abs/2107.06067v5> (visited on 09/17/2026).
- [18] M. Backens and A. Kissinger. “ZH: A Complete Graphical Calculus for Quantum Computations Involving Classical Non-linearity”. In: *Electronic Proceedings in Theoretical Computer Science* 287 (2019), pp. 23–42. doi: 10.4204/EPTCS.287.2. arXiv: 1805.02175.
- [19] S. Abramsky and B. Coecke. *A categorical semantics of quantum protocols*. 2004. arXiv: quant-ph/0402130. URL: <https://arxiv.org/abs/quant-ph/0402130> (visited on 09/17/2026).
- [20] C. Li, D. Gao, X. Zhou, J. Guan, P. Zhu, and Z. Chu. *Parallelizable Exact Synthesis of Quantum Circuits via Semi-Tensor Product*. Version 2, 16 August 2026. Recent preprint; its performance claims were not independently reproduced in this study. 2026. arXiv: 2607.24195. URL: <https://arxiv.org/abs/2607.24195v2> (visited on 09/17/2026).