```
!
! Last configuration change at 00:19:41 UTC Mon Mar 1 1993
version 15.0
no service pad
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
hostname SW-1
boot-start-marker
boot-end-marker
enable secret 5 $1$n7vN$yjNYr1KIOsjDJc9/SubWq0
no aaa new-model
system mtu routing 1500
spanning-tree mode rapid-pvst
spanning-tree extend system-id
vlan internal allocation policy ascending
!
!
interface Port-channel2
switchport trunk native vlan 777
switchport trunk allowed vlan 10,20,30,40,50,60
switchport mode trunk
interface FastEthernet0/1
switchport access vlan 20
switchport mode access
spanning-tree portfast
interface FastEthernet0/2
switchport access vlan 20
```

```
switchport mode access
spanning-tree portfast
interface FastEthernet0/3
switchport access vlan 20
switchport mode access
spanning-tree portfast
interface FastEthernet0/4
switchport access vlan 20
switchport mode access
spanning-tree portfast
interface FastEthernet0/5
switchport access vlan 20
switchport mode access
spanning-tree portfast
interface FastEthernet0/6
switchport access vlan 20
switchport mode access
spanning-tree portfast
interface FastEthernet0/7
switchport access vlan 30
switchport mode access
spanning-tree portfast
interface FastEthernet0/8
switchport access vlan 30
switchport mode access
spanning-tree portfast
interface FastEthernet0/9
switchport access vlan 30
switchport mode access
spanning-tree portfast
interface FastEthernet0/10
switchport access vlan 30
switchport mode access
spanning-tree portfast
interface FastEthernet0/11
switchport access vlan 30
switchport mode access
spanning-tree portfast
interface FastEthernet0/12
switchport access vlan 30
switchport mode access
spanning-tree portfast
```

```
interface range FastEthernet 0/13 - 24
shutdown
interface GigabitEthernet0/1
descriptin Interface ver SW-3750 port 13
switchport trunk native vlan 777
switchport trunk allowed vlan 10,20,30,40,50,60
switchport mode trunk
channel-protocol lacp
channel-group 2 mode active
interface GigabitEthernet0/2
descriptin Interface ver SW-3750 port 15
switchport trunk native vlan 777
switchport trunk allowed vlan 10,20,30,40,50,60
switchport mode trunk
channel-protocol lacp
channel-group 2 mode active
interface Vlan1
no ip address
vlan 777
!
!
no ip http server
no ip http secure-server
!
vstack
!
!
```