

Designed by Remus Teodorescu 2026

LECTURE 5.2


RNN and LSTM

Remus Teodorescu

With support from Research Assistant Noman Khan - nomank@energy.aau.dk

Aalborg University · ret@et.aau.dk

Deep Learning for Engineering · 2026



A recurrent network reads a sequence one step at a time and carries a memory, its hidden state, from each step to the next with the same weights: here from four days of substation demand to the fifth. An LSTM adds a cell state guarded by three gates, so that the memory lasts for days rather than hours.

Learning Objectives

SECTIONS, IN ORDER

1. **Sequences** — data in time, and the baseline to beat
2. **RNN** — a network with a memory
3. **LSTM** — a memory that lasts, and how to use it

READ, AND WHAT EACH ANSWERS

UDL ch. 12.1	what makes a sequence different, and what must a model beat?
GBC ch. 10.1	how does a network keep a memory?
GBC ch. 10.10	how does a memory last, and how is it tuned?


Sequences

Sequence — data whose order carries meaning, such as a load measured every hour. Each value is read together with the ones before it; shuffle the order and the meaning is gone.

DATA IN TIME

- **examples** — grid demand, a sensor trace, a sentence
- **order matters** — shuffle the hours and the pattern is gone
- **the task in notebook 04** — an hourly load forecast
- **persistence** — the next hour equals this hour
- **the baseline to beat** — any model must do better than that

FIVE DAYS OF DEMAND



WHAT A SEQUENCE MODEL NEEDS

read in order	one step after another
remember	what came before

Recurrent Network

Recurrent network — a network that reads a sequence one step at a time and carries a hidden state from step to step, using the same weights at every step.


KIND, FUNCTION, ARCHITECTURE, APPLICATIONS

- **kind** — a network with a memory, fed back at every step
- **function** — a sequence in, one answer at the end
- **architecture** — one cell, applied at every step
- **applications** — load and wind forecasting, control signals, speech

AGAINST A DENSE NETWORK

	dense network	recurrent network
input	one vector, fixed length	a sequence of any length
memory	none between inputs	the hidden state h
weights	one set per input position	one cell, shared over time
parameters	grow with the window	independent of the length
order	an ordinary input index	built in: step t follows t − 1

THE SAME CELL, STEP AFTER STEP



$$\mathbf{h}_t = f(\mathbf{h}_{t-1}, \mathbf{x}_t; \theta)$$

$\mathbf{h}_t$ the memory after step t, $\mathbf{x}_t$ the input at step t, f the cell, θ its weights

A RECURRENT NETWORK IN PYTORCH

```
rnn = nn.RNN(1, 16)   # the cell f, the same every step
out, h = rnn(x)       # the memory h, carried through
```

Hidden State

Hidden state — the internal vector $\mathbf{h}(t)$ an RNN updates at each time step from the current input and its previous value, acting as a learned memory that summarises the sequence seen so far.

A SUMMARY OF THE PAST, UPDATED EACH STEP

- **the hidden state** — a short summary of everything seen so far
- **each step** — the new input and the state, weighted and summed
- **tanh** — the activation function, squashing into −1 … 1


$$\mathbf{h}_t = \tanh\left(\mathbf{W}_h \mathbf{h}_{t-1} + \mathbf{W}_x \mathbf{x}_t + \mathbf{b}\right)$$

$$\hat{y} = \mathbf{W}_y \mathbf{h}_T + b_y$$

$\mathbf{x}_t$ the input at step t, $\mathbf{h}_t$ the state, $\mathbf{W}_h, \mathbf{W}_x$ shared every step, $\hat{y}$ read from the last state

TALK · 2 MIN In your own words, why can one set of weights read a sequence of any length? Then, in the unfolded chain on the right, which inputs has h(t+1) seen, and along which arrows did they reach it?

FOLDED AND UNFOLDED



z^{-1} in the black box: one step of delay

THE SAME, AS A LOOP

```
h = h0                      # start: an empty memory
for t in 1 ... T:           # one step per hour
  h = tanh(Wx@x[t] + Wh@h + b)  # new memory
y = Wy @ h + by             # read out the forecast
```

Wx reads the input, Wh reads the memory — two jobs, two matrices, both the same at every step


LSTM

LSTM — keeps two memories: the cell state, a long-term memory carried along the whole sequence and changed only slightly at each step, and the hidden state, a short-term working memory that reads out the parts of the long-term memory relevant right now and passes them to the next step and to the output.

KIND, FUNCTION, ARCHITECTURE, APPLICATIONS

- **kind** — a recurrent network with a longer memory
- **function** — a sequence in, an output per step or at the end
- **architecture** — a cell state and three gates that control it
- **applications** — forecasting, speech, text, state estimation


	plain recurrence	LSTM
memory	one vector h	h, and a cell state c beside it
each step	h is rewritten	c is kept, then added to
gates	none	forget, input, output
how long	short	much longer
parameters	one set	four sets, four times as many



LSTM Cell

LSTM cell — a recurrent unit with a cell state controlled by three learned gates: the forget gate decides how much of the previous cell state to keep, the input gate how much new information to write in, and the output gate which parts of the cell state to expose as the hidden state. This additive memory path preserves gradients over long sequences.

A BELT, AND THREE GATES THAT CONTROL IT



$$\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \mathbf{g}_t$$

$\mathbf{c}_t$ the cell state, $\mathbf{f}_t$ the forget gate, $\mathbf{i}_t$ the input gate, $\mathbf{g}_t$ the candidate, $\odot$ elementwise

the belt is kept and added to, not rewritten: the memory lasts

THE SIX EQUATIONS, GATE BY GATE

f $\mathbf{f}_t = \sigma(\mathbf{W}_f[\mathbf{x}_t,\ \mathbf{h}_{t-1}] + \mathbf{b}_f)$

forget gate — how much of the belt to keep

i $\mathbf{i}_t = \sigma(\mathbf{W}_i[\mathbf{x}_t,\ \mathbf{h}_{t-1}] + \mathbf{b}_i)$

input gate — how much new to add

g $\mathbf{g}_t = \tanh(\mathbf{W}_g[\mathbf{x}_t,\ \mathbf{h}_{t-1}] + \mathbf{b}_g)$

candidate — new content from x and h, not x itself

o $\mathbf{o}_t = \sigma(\mathbf{W}_o[\mathbf{x}_t,\ \mathbf{h}_{t-1}] + \mathbf{b}_o)$

output gate — how much to show as h

c $\mathbf{c}_t = \mathbf{f}_t \odot \mathbf{c}_{t-1} + \mathbf{i}_t \odot \mathbf{g}_t$

cell update — the line drawn on the left

h $\mathbf{h}_t = \mathbf{o}_t \odot \tanh(\mathbf{c}_t)$

hidden state — the output

THE LSTM CELL IN PYTORCH

```
cell = nn.LSTMCell(1, 16)      # the six lines, one call
h, c = cell(x[:, t], (h, c))  # σ gates 0–1, tanh −1–1
```

LSTM Hyperparametrization


Hyperparameters — an LSTM cell contains input weights, recurrent weights and biases for the forget, input and output gates, each acting as a learned gain between 0 and 1, and for the candidate cell value; these are learned in training. The main hyperparameters are the hidden layer width, the number of stacked layers, and whether to use dropout or bidirectionality.

SIZE, INITIALISE, AND KNOW THE COST

- **hidden width** — start small, 16 here; grow only if it underfits
- **layers** — one, or two at most
- **forget bias at one** — it remembers by default
- **compare** — against persistence, on held-out hours

TALK · 2 MIN In your own words, what does a memory give a forecaster that a fixed window does not? Then, in the plot on the right, after about how many hours has a forget gate of 0.95 kept only half of the cell state?

HOW LONG THE CELL REMEMBERS



computed as f to the k · grid: one half, one day

HYPERPARAMETRIZATION IN PYTORCH

```
lstm = nn.LSTM(input_size=1,    # one value per hour
               hidden_size=16,  # width of h and c
               num_layers=1,    # LSTM layers stacked
               batch_first=True)  # x: (batch, 24, 1)
head = nn.Linear(16, 1)  # dense layer: h -> forecast
out, (h, c) = lstm(x)    # h at every hour, last c
y = head(out[:, -1])     # forecast from the last h
```

Advanced Topics

RELATED TOPICS LEFT OUT, AND WHERE THEY MATTER

topic	what it adds	read	where it makes a difference
self-attention	every step looks at every other	UDL ch. 12.2	machine translation
transformer	attention and dense layers stacked	UDL ch. 12.4	large language models
vanishing gradient	why a plain RNN forgets the past	GBC ch. 10.7	long speech and text
gated recurrent unit	a lighter cell: two gates	GBC ch. 10.10	speech recognition
bidirectional network	reads forwards and backwards	GBC ch. 10.3	transcribing speech
sequence to sequence	one network reads, one writes	GBC ch. 10.4	machine translation

WHY THEY ARE LEFT OUT

These pay off on huge collections of text and speech, where the sequences are long and the data plentiful. A substation forecast from 24 hours of load is neither: persistence, a recurrent network or an LSTM is enough.

Exercise 5

NOTEBOOK 04, AND THE REPORT

- **04** — an hourly load forecast: persistence, a recurrent network and an LSTM, each in its own cell
- **compare** — held-out error against persistence, and the forecast plot, where the models differ
- **01 to 03** — from L5.1: the CNN, graphs from scratch, the graph network on the power flow
- **05** — the report: the answers of notebooks 01 to 04, gathered, and one question to conclude

THE QUESTIONS NOTEBOOK 04 ANSWERS

baseline	how good is persistence already?
RNN	does a memory beat it?
LSTM	worth its extra parameters?

REPORT QUESTION, TO CONCLUDE

Across a grid, a graph and a sequence: when did building the data's structure into the network beat a dense network, and what did it cost?

SUMMARY

Key Takeaways

RECURRENT NETWORK	
what it is	a network that reads a sequence step by step, with a memory
function	a sequence in; one answer at the end, or one per step
train, tune	Adam through the unrolled steps; window, hidden width, layers
vs dense	one set of weights for any length; 321 parameters here
used for	load and wind forecasting, control signals, speech

LSTM	
what it is	a recurrent network with two memories: cell state and h
function	three gates decide what to keep, what to add, what to show
train, tune	as the RNN; forget bias at one; width 16, one layer here
vs dense	any length, a longer memory; 1,233 parameters, lowest error
used for	forecasting, speech, text, state estimation

Next — L6.1: loss functions and gradients.

Questions

1 – 2 · RECURRENT NETWORK

1 **What is a recurrent network, and what function does it implement?**

A network that reads a sequence one step at a time and keeps a hidden state as its memory. At each step the new state is computed from the input and the previous state, with the same weights, and a read-out gives an answer at the end or at every step. *GBC ch. 10.1 – 10.2; Ex_05 notebook 04*

2 **How does it differ from a dense network, and what must a forecast beat?**

One set of weights serves a sequence of any length, and the order of the samples is part of the input, where a dense network sees a fixed row. A forecast has to beat persistence, the guess that the next value equals the last one. *GBC ch. 10.2; Ex_05 notebook 04*

3 – 4 · LSTM

3 **What is an LSTM, and what do its gates do?**

A recurrent network with two memories: a cell state that is carried along and a hidden state that is shown. Three gates decide what to keep of the cell state, what to add to it and what to show. The forget bias starts at one, so the cell keeps by default. *GBC ch. 10.10; Ex_05 notebook 04*

4 **Why does an LSTM remember longer than a plain recurrent network?**

In a plain recurrent network the gradient is multiplied by the same weights at every step and vanishes over a long sequence. The LSTM's cell state is updated by addition, so the gradient passes along it nearly unchanged. In notebook 04 it had the lowest held-out error. *GBC ch. 10.7, 10.10; Ex_05 notebook 04*

NEXT

L6.1 — Loss Functions and Gradients

Every architecture this course uses is now in hand: dense, convolutional, graph, recurrent and LSTM. Next: how they are trained.

BEFORE THE NEXT SESSION

read	UDL ch. 5.1 – 5.3
run	Ex_05 notebooks 04 and 05
bring	your forecast plot
think about	which forecast to deploy, and why

bring your held-out errors from notebook 04