

Spectra: a Framework for Decomposing Logical Atomicity of LTS Composition

Gregory Malecha, Jonas K. Hinrichsen, Gordon Stewart,
Abhishek Anand, Paolo Giarrusso, Yoichi Hirai, Hai Dang

BedRock Systems (soon to be BlueRock.io)


Iris Workshop
June 3, 2024

BlueRock's Spectra Framework

- v1 (2020) by G. Malecha and J.K. Hinrichsen
- v2 (2021) by G. Stewart
- further developments by A. Anand, P. Giarrusso, Y. Hirai, H. Dang and others

To prove: refinement

The Bare-metal Property: "any guest behavior possible on the BedRock virtualization stack is also possible on the bare-metal"



Horizontal decomposition of $\text{impl} \subseteq \text{spec}$

specification models

big_spec

=

machine

||

switch

||

uart

this talk focuses on
horizontal decomposition
for specification models
in separation logic

UI

UI

UI

VMM
(C++)

\oplus

vSwitch
(C++)

\oplus

UMX
(C++)

=

big_impl

Q: $\text{impl} \subseteq \text{spec}$ in separation logic, how?

CaReSL-
style
[Turón et al. 2013]

$$\{ \boxed{(p, s)} * \text{relate}(s, \sigma) \}$$
$$(\rho, \sigma)$$
$$\{ (\rho', \sigma'). \exists (p, s) \rightarrow (p', s') * \boxed{(p', s')} * \text{relate}(s', \sigma') \}$$

triple of impl program

spec program as ghost

\Rightarrow Logic's adequacy gives $\text{impl} \subseteq \text{spec}$

ReLoC-
TADA-
style
[Frumin et al. 2021]

$$\langle \boxed{(p, s)} * \text{relate}(s, \sigma) \rangle$$
$$(\rho, \sigma)$$
$$\langle (\rho', \sigma'). \exists \dots * \boxed{(p', s')} * \text{relate}(s', \sigma') \rangle$$

logically atomic triple

Decomposing Specification Models

To decompose *atomic updates* (logical atomicity) of specification state

AU \langle big_s * ... \rangle \langle big_s' * ... \rangle

\vdash wp big_σ

into

(this talk)

into

(last year's talk)

AU \langle s1 * ... \rangle \langle s1' * ... \rangle

\vdash wp i1

AU \langle s2 * ... \rangle \langle s2' * ... \rangle


\vdash wp i2

AU \langle s3 * ... \rangle \langle s3' * ... \rangle

\vdash wp i3

Spec Model Decomposition: A Modular Interface

- Decomposition of not just state, but also steps, of *communicating* specification models
- Hierarchical decomposition, incrementally as needed
- Local specs for communications:
 - one needs not know who is on the other side
 - **A1** can talk to **B2** without worrying about traversing the tree of decomposition invariants



BlueRock's **Spectra** Framework

- An Iris library to provide separation logic analogs of standard process calculi reasoning principles, on ghost state.
- With separating conjunction and *logically atomic updates*, we can decompose and prove, e.g. parallel composition, communication, and simulation.
- We have applied the framework in several large ongoing verification efforts, including a virtual machine monitor and a virtual network switch.
- Publicly available as part of <https://github.com/bedrocksystems/BRiCk>

Parallel Composition: State

- $Cs = || Cs[n]$ — Cs is an LTS, parallel composed of LTSes $Cs[n]$
- n : Name — set of names for each constituent LTS $Cs[n]$
- $Cs.state := \bigtimes_n Cs[n].state$
- State (de)composition: \times can be encoded as separating conjunction

$$Cs.state \vdash | = \{E\} \Rightarrow *n \quad Cs[n].state$$

Decompose_inv

Parallel Composition: Semantics

$$\text{tau step} \frac{Cs.state[n] \sim\{\tau\}\sim s'}{Cs.state \sim\{\tau\}\sim Cs.state[n := s']}$$

- A step is reflected as an AU

$$AU \langle \exists Cs, \boxed{Cs} * \dots \rangle \langle \forall Cs', Cs \sim\{\tau\}\sim Cs' * \boxed{Cs'} * \dots \rangle$$

\vdash

Decompose_inv

$-*$

the direction is due to contravariance
 $(AU \ s \ -* \ WP \ \sigma) \vdash (AU \ Cs \ -* \ WP \ C\sigma)$

$$AU \langle \exists s, \boxed{s}^n * \dots \rangle \langle \forall s', s \sim\{\tau\}\sim s' * \boxed{s'}^n * \dots \rangle$$

Parallel Composition: Communication

- Communications are through events (labels) with input & output arguments
- External communications produce externally visible events

$$\text{external comm step} \frac{\text{Cs.state}[n] \sim\{e\}\sim s' \quad \text{is_external}(e, ex)}{\text{Cs.state} \sim\{ex\}\sim \text{Cs.state}[n := s']}$$

External Communication as AU entailment

$$\text{external comm step} \frac{\text{Cs.state}[n] \sim\{e\}\sim s' \quad \text{is_external}(e, \text{ex})}{\text{Cs.state} \sim\{\text{ex}\}\sim \text{Cs.state}[n := s']}$$

- A step is reflected as an AU with event

$$\text{AU} \langle \exists \text{Cs}, \boxed{\text{Cs}} * \dots \rangle \quad \langle \forall \text{Cs}', \text{Cs} \sim\{\text{ex}\}\sim \text{Cs}' * \boxed{\text{Cs}'} * \dots \rangle$$

⊢

$$\vdash \text{is_external}(e, \text{ex}) \vdash \quad -*$$

$$\boxed{\text{Decompose_inv}} \quad -*$$

$$\text{AU} \langle \exists s, \boxed{s}^n * \dots \rangle \quad \langle \forall s', s \sim\{e\}\sim s' * \boxed{s'}^n * \dots \rangle$$

Parallel Composition: Internal Communication

- Internal communications among constituent LTSes result in silent τ events

$$\begin{array}{c} \text{internal} \\ \text{comm step} \end{array} \frac{\begin{array}{c} \text{Cs.state}[n1] \sim\{e1\}\sim s1' \quad \text{Cs.state}[n2] \sim\{e2\}\sim s2' \\ (e1, e2) \text{ is matching (request, response)} \end{array}}{\text{Cs.state} \sim\{\tau\}\sim \text{Cs.state}[n1 := s1'][n2 := s2']}$$

Internal Communications with 2 AUs

$$\begin{array}{c} \text{Cs.state}[n1] \sim \{e1\} \leadsto s1' \quad \text{Cs.state}[n2] \sim \{e2\} \leadsto s2' \\ \text{internal comm step} \quad \frac{(e1, e2) \text{ is matching (request, response)}}{\text{Cs} \sim \{\tau\} \leadsto \text{Cs}[n1 := s1'] [n2 := s2']} \end{array}$$

- This requires 2 AUs, for $e1$ ($n1$) and $e2$ ($n2$), that are *matching* and *atomic*

$\text{AU} \langle \exists \text{Cs}, \boxed{\text{Cs}} * \dots \rangle \langle \forall \text{Cs}', \text{Cs} \sim \{\tau\} \leadsto \text{Cs}' * \boxed{\text{Cs}'} * \dots \rangle$

\vdash

$\vdash (e1, e2) \text{ matching} \vdash \quad -*$

???

$\boxed{\text{Decompose_inv}} \quad -*$

$\text{AU} \langle \boxed{s1}^{n1} * \dots \rangle \langle \dots \rangle * \text{AU} \langle \boxed{s2}^{n2} * \dots \rangle \langle \dots \rangle$

Internal Communications with 2 AUs

$$\begin{array}{c} \text{internal} \\ \text{comm step} \end{array} \frac{\begin{array}{l} \text{Cs.state}[n1] \sim \{e1\} \leadsto s1' \quad \text{Cs.state}[n2] \sim \{e2\} \leadsto s2' \\ (e1, e2) \text{ is matching (request, response)} \end{array}}{\text{Cs} \sim \{\tau\} \leadsto \text{Cs}[n1 := s1'] [n2 := s2']}$$

- **Matching** is asymmetric: the *caller* n1 first makes the request (with e1) and then, the *callee* n2 makes the corresponding response (with e2)
 - AU of callee **depends on** and **is atomic** with AU of caller
- ⇒ AU of callee **helps** committing AU of caller

Internal Communications as helping AUs

$$\text{AU} \langle \exists Cs, \boxed{Cs} * \dots \rangle \langle \forall Cs', Cs \sim \{\tau\} \sim Cs' * \boxed{Cs'} * \dots \rangle$$

\vdash

$\vdash (e1, e2) \text{ matching } \vdash \quad -*$

$\boxed{\text{Decompose_inv}} \quad -*$

$\text{AU} \langle \boxed{s1}^{n1} * \dots \rangle \langle \dots \rangle \quad -*$

$\text{AU} \langle \boxed{s2}^{n2} * \dots \rangle \langle \dots \rangle$

Reading this “transport” lemma:

- The caller needs to show $\text{AU } e1$, i.e. shows how it wants to step $n1$;
- The lemma, by the decomposition, transforms $\text{AU } e1$ to $\text{AU } e2$;
- The callee consumes $\text{AU } e2$, and commits $e1$ and $e2$ together.

Parallel Composition ($Cs = || Cs[n]$)

tau step $\frac{Cs.state[n] \sim\{\tau\}\sim s'}{Cs.state \sim\{\tau\}\sim Cs.state[n := s']}$

$AU^{Cs} \tau \vdash AU^{Cs[n]} \tau$

external comm step $\frac{Cs.state[n] \sim\{e\}\sim s' \quad is_external}{Cs.state \sim\{ex\}\sim Cs.state[n := s']}$

$AU^{Cs} ex \vdash AU^{Cs[n]} e$

$AU^{Cs} \tau \vdash AU^{Cs[n1]} e1 \text{ } -* \text{ } AU^{Cs[n2]} e2$

internal comm step $\frac{Cs.state[n1] \sim\{e1\}\sim s1' \quad Cs.state[n2] \sim\{e2\}\sim s2' \quad (e1, e2) \text{ is matching (request, response)}}{Cs \sim\{\tau\}\sim Cs[n1 := s1'][n2 := s2']}$

Actually ...

not all AUs are created equal

Due to the asymmetry in communication, and the se

- **Updaters**: update for τ steps

$$\boxed{\circ s} \Rightarrow \boxed{\circ \{s' \mid s \sim \{\tau\} \rightarrow s'\}}$$

- **Requesters**: AU for request side of communication

$$\text{AU} \langle \boxed{\circ s} * \dots \rangle \langle \boxed{\circ \{s' \mid s \sim \{e\} \rightarrow s'\}} \dots \rangle$$

- **Committers**: AU for response side of communications

$$\text{AU} \langle \boxed{\bullet s} * \dots \rangle \langle \boxed{\bullet \{s' \mid s \sim \{e\} \rightarrow s'\}} * \dots \rangle$$

The decomposition uses the AUTH construction:

- fragmentary elements are given to clients,
- while authoritative ones are maintained by the decomposition.

Parallel Composition ($Cs = || Cs[n]$)

$\text{Committer}^{Cs} \text{ ex} \vdash \text{Committer}^{Cs[n]} e$
 $\text{Requester}^{Cs[n]} e \vdash \text{Requester}^{Cs} \text{ ex}$

external
 comm step $\frac{Cs.state[n] \sim \{e\} \leadsto s'}{Cs.state \sim \{ex\} \leadsto Cs.state[n := s']}$

$\text{Updater}^{Cs} \vdash \text{Updater}^{Cs[n]}$

tau step $\frac{Cs.state[n] \sim \{\tau\} \leadsto s'}{Cs.state \sim \{\tau\} \leadsto Cs.state[n := s']}$

$\text{Updater}^{Cs} \vdash \text{Requester}^{Cs[n1]} e1 -* \text{Committer}^{Cs[n2]} e2$

internal
 comm step $\frac{\begin{array}{l} Cs.state[n1] \sim \{e1\} \leadsto s1' \quad Cs.state[n2] \sim \{e2\} \leadsto s2' \\ (e1, e2) \text{ is matching (request, response)} \end{array}}{Cs \sim \{\tau\} \leadsto Cs[n1 := s1'][n2 := s2']}$

The Decomposition Theorem

State decomposed

τ steps
decomposed

$\circ \text{Cs.state} * \square \text{Updater}^{Cs}$

$\vdash \models \{E\} \Rightarrow$

$[* \text{list}] n \in \text{Name}, \circ \text{Cs.state}[n] * \square \text{Updater}^{Cs[n]}$

$* \square (\forall n1 \neq n2, e1, e2. (e1, e2) \text{ matching} \rightarrow \text{Requester}^{Cs[n1]} e1 -* \text{Committer}^{Cs[n2]} e2)$ **internal comm steps**

$* \square (\forall n, e, ex. \text{is_external}(e, ex) \rightarrow \text{Requester}^{Cs[n]} e -* \text{Requester}^{Cs} ex)$ **external request steps**

$* \square (\forall n, e, ex. \text{is_external}(e, ex) \rightarrow \text{Committer}^{Cs} ex -* \text{Committer}^{Cs[n]} e)$ **external response steps**

Together with Refinement Adequacy

$\text{refine_inv}(R, \text{TR}) :=$
 $\exists s \text{ tr}, \bullet s_{\text{init}} * s_{\text{init}} \sim \{\text{tr}\} \leadsto s *$
 $\text{Forall2 } R \text{ (no_}\tau \text{ TR) (no_}\tau \text{ tr)}$

decomposable with
this framework

- instantiate Iris with the **big_impl** LTS
- encode **big_spec** as ghost state
- define a refinement inv that relates traces
- prove WP σ while maintaining the refinement inv

decomposable
with WPio

$\circ s_{\text{init}} * \text{impl_resources} \vdash \text{WP } \sigma_{\text{init}} \{ \lambda_, \text{False} \}$

Enters separation logic


Iris adequacy

big_impl trace_refines^R **big_spec**

$\forall \sigma' \text{ TR}, \sigma_{\text{init}} \sim \{\text{TR}\} \leadsto \sigma' \Rightarrow \exists s' \text{ tr}, s_{\text{init}} \sim \{\text{tr}\} \leadsto s' \wedge \text{Forall2 } R \text{ (no_}\tau \text{ TR) (no_}\tau \text{ tr)}$

Spectra: A Modular Interface

- Decomposition of state and steps (as AUs)
- Decomposition theorem can be applied multiple times as needed
- Local specs for comm: with **Requesters** & **Committers**, one needs not know the other side
 - A CPU issuing a request doesn't know who can serve it (main memory or devices)
- Seamless comm across levels of decomposition
 - **A1** can talk to **B2** without worrying about traversing the tree of decomposition invariants



each node applies the decomposition theorem (allocate a new invariant)

Conclusions

- A BI-general library to reflect LTS (de)composition into AUs on ghost state
- Publicly available as part of <https://github.com/bedrocksystems/BRiCk>
- Technical points not mentioned in this talk:
 - hiding
 - masks
 - the decomposition invariant
 - non-determinism (set of states)
 - simulation
- Limitations:
 - Dynamic topology
 - Stateful communication
 - Multi-party sync communication

Updaters

- Updates to make any τ steps
- Proven by clients, consumed by the decomposition

Updater $\text{Its } \gamma : \text{PROP} :=$

$\square \forall (\text{sset} : \text{propset Its.State})$

$(_ : \exists s, s \in \text{sset})$

$(_ : \text{tau_safe Its sset}),$

$\circ \text{sset}^Y = \{E\} = *$

$\circ \{[s' \mid \exists s, s \in \text{sset} \wedge s \sim_{\{\tau\}}^{\text{Its}} s']\}^Y .$

sset is non-empty

sset can make τ steps

set of states
 τ -reachable from sset

Requesters

- Updates to initiate external communication request steps
- Proven by clients, transported by the decomposition

Requester $lts \gamma$ (EV : propset $lts.(Event)$) (Q : $lts (Event) \rightarrow PROP$) : PROP :=

AC $\langle \exists sset, \boxed{\circ sset}^Y * [\mid \exists s, s \in sset \mid] *$

$[\mid \forall s \in sset, e \in STEP, \exists s', s \sim_{\{e\}}^{lts} s' \mid] \rangle$

$Eo \setminus E, Ei$

$\langle \forall e \in STEP, \boxed{\circ \{ [s' \mid \exists s \in sset, s \sim_{\{e\}}^{lts} s'] \}}^Y,$

$COMM Q e \rangle$

sset is non-empty

sset can make EV-steps

set of states
e-reachable from sset

local (private)
post-condition

Committers

- Updates to make external communication response steps
- Transported by the decomposition from requesters, consumed by clients

Committer lts γ (EV : propset lts.(Event)) (Q : lts.(Event) \rightarrow PROP) : PROP :=

AU $\langle \exists \text{ sset}, \boxed{\bullet \text{ sset}}^Y \rangle$

Eo, Eo \ E

$\langle \forall \text{ sset}', e \in \text{STEP}, [\mid \exists s, s \in \text{sset}' \mid] *$

$[\mid \forall s' \in \text{sset}', \exists s \in \text{sset}, s \sim_{\{e\}}^{\sim} s' \mid] * \boxed{\bullet \text{ sset}'}^Y ,$

COMM Q e \rangle

set of states
e-reachable from sset

Requesters & Committers

Requester :=

AC $\langle \exists sset, \boxed{\circ sset}^Y * [\mid \exists s, s \in sset \mid] * [\mid \forall s \in sset, e \in STEP, \exists s', s \sim\{e\}\sim_{lts} s' \mid] \rangle$

caller picks a set STEP
of events to step

$Eo \setminus E, Ei$

$\langle \forall e \in STEP, \boxed{\circ \{s' \mid \exists s \in sset, s \sim\{e\}\sim_{lts} s'\}}^Y, COMM Q e \rangle$

callee picks a concrete
event e in the set STEP

Committer :=

AU $\langle \exists sset, \boxed{\bullet sset}^Y \rangle$

$Eo, Eo \setminus E$

$\langle \forall sset', e \in STEP, [\mid \exists s, s \in sset' \mid] * [\mid \forall s' \in sset', \exists s \in sset, s \sim\{e\}\sim_{lts} s' \mid] * \boxed{\bullet sset'}^Y, COMM Q e \rangle$

Requesters & Committers

Requester :=

$$\text{AC} \langle \exists \text{sset}, \boxed{\circ \text{sset}}^Y * [|\exists s, s \in \text{sset}|] * [|\forall s \in \text{sset}, e \in \text{STEP}, \exists s', s \sim \{e\} \leadsto_{\text{ts}} s'|] * \text{Eo} \setminus \text{E}, \text{Ei} \langle \forall e \in \text{STEP}, \boxed{\circ \{[s' | \exists s \in \text{sset}, s \sim \{e\} \leadsto_{\text{ts}} s']\}}^Y, \text{COMM } Q \ e \rangle$$

caller provides an update with caller's frag

the decomposition ties that update to caller's auth

the decomposition ties caller's auth to callee's auth

Committer :=

$$\text{AU} \langle \exists \text{sset}, \boxed{\bullet \text{sset}}^Y \rightarrow \text{Eo}, \text{Eo} \setminus \text{E} \langle \forall \text{sset}', e \in \text{STEP}, [|\exists s, s \in \text{sset}'|] * [|\forall s' \in \text{sset}', \exists s \in \text{sset}, s \sim \{e\} \leadsto_{\text{ts}} s'|] * \boxed{\bullet \text{sset}'}^Y, \text{COMM } Q \ e \rangle$$

callee consumes this update using callee's frag

When callee commits, all updates for caller, callee, and the composed are committed

The Decomposition Invariant

`Decompose_inv (γ : gname) (γs : Name -> gname) : PROP :=`

`∃ sset,`

`[*list] n ∈ Name, [• sset n](γs n)`

`* [○ sset]γ`

`* [| ∃ s, s ∈ sset |].`

Recall the decomposition theorem:
the decomposition

- consumes the frag of the whole (γ)
- produces the frags of the components (γs n)

Simulation also as AU entailment

$$\begin{array}{c}
 \text{AU } \langle \exists Cs. \boxed{Cs} * \dots \rangle \text{ex} \langle \forall Cs'. Cs \sim \{ex\} \sim Cs' * \boxed{Cs'} * \dots \rangle \\
 \vdash \\
 \text{AU } \langle \exists s. \boxed{s}^n * \dots \rangle e \langle \forall s'. s \sim \{e\} \sim s' * \boxed{s'}^n * \dots \rangle
 \end{array}$$

Diagram illustrating the simulation of AU entailment. The top formula is $\text{AU } \langle \exists Cs. \boxed{Cs} * \dots \rangle \text{ex} \langle \forall Cs'. Cs \sim \{ex\} \sim Cs' * \boxed{Cs'} * \dots \rangle$ and the bottom formula is $\text{AU } \langle \exists s. \boxed{s}^n * \dots \rangle e \langle \forall s'. s \sim \{e\} \sim s' * \boxed{s'}^n * \dots \rangle$. Red arrows indicate the mapping from the top formula to the bottom formula: $\boxed{Cs} \rightarrow \boxed{s}^n$, $\text{ex} \rightarrow e$, and $\boxed{Cs'} \rightarrow \boxed{s'}^n$.

Application at BedRock

