

# Multris:

## Functional Verification of Multiparty Message Passing in Separation Logic

Jonas Kastberg Hinrichsen

Aarhus University

Jules Jacobs


Cornell University

Robbert Krebbers

Radboud University  
Nijmegen

Jesper Bengtson   Daniël Louwring   Léon Gondelman  
Mário Pereira   Amin Timany   Lars Birkedal

# Me, Actris, and The Iris Workshop



## Future work

- ✓ Semantic model of Session Types via logical relations

$$\begin{aligned} [ - ] &: \tau \rightarrow \text{Val} \rightarrow \text{iProp} \\ [N] &\triangleq \lambda v. \exists n \in \mathbb{N}. v = n \\ [st] &\triangleq ??? \end{aligned}$$

- Multi-party Dependent Separation Protocols (Based on [Honda et al., POPL'08])
- ✓ Linearity of channels through Iron
  - Preventing dropping of channel obligation
- ✓ Communication between distributed systems

19

Jonas Kastberg Hinrichsen

Actris: Session-Type Based Reasoning in Separation Logic

[POPL'20] Actris, 1st Iris Workshop

[CPP'21] Semantic Session Types

[LMCS'22] Actris 2.0, 2nd Iris Workshop

[ICFP'23a] Actris in Distributed Systems, 2nd/3rd Iris Workshop (Léon/Me)

[ICFP'23b] MiniActris, 3rd Iris Workshop (Jules)

[POPL'24] LinearActris

Multris = Multiparty Actris



Actris = Verification system for message passing in Iris

# Message Passing

## **Well-structured approach to writing concurrent (/distributed) programs**

- ▶ Individual components behave as individual actors
- ▶ Actors interact based on predetermined global protocol
- ▶ We consider reliable channels: Messages are never duplicated or reordered

## **Message passing is not a silver bullet**

- ▶ Often mixed with other programming mechanisms
  - ▶ Such as: shared memory, higher-order functions, recursion
- ▶ Many bugs happen when these mechanisms intersect
- ▶ We want functional verification that spans these intersections

## **Actris: program logic for verifying message passing programs**

- ▶ Actris (via Iris) supports all of the above

## **But what about multiparty message passing?**

# Multiparty Message Passing

## **Multiparty message passing**

- ▶ Message passing with dependent interactions between multiple actors
- ▶ Like a game of telephone! Or leader election

## **Dependencies are hard to get right**

- ▶ Few results exists for functional verification
- ▶ Multiple unsound results in the literature

## **Idea: Modify Actris to support multiparty message passing**

- ▶ Inheriting verification alongside other programming mechanisms
- ▶ Inheriting foundationally proven soundness theorem (via Iris)

## **Scope: Synchronous message passing in shared memory**

- ▶ Synchronous: Sender and receiver block until exchange
- ▶ Shared memory: Channels implemented via references in ML-like language

# Multiparty Message Passing in Shared Memory

## Multiparty channels in shared memory:

- new\_chan( $n$ )**      Creates a multiparty channel with  $n$  parties, returning a tuple  $(c_0, \dots, c_{n-1})$  of endpoints
- $c_i[j].\mathbf{send}(v)$       Sends a value  $v$  via endpoint  $c_i$  to party  $j$  (synchronously)
- $c_i[j].\mathbf{recv}()$       Receives a value via endpoint  $c_i$  from party  $j$

## Example Program: Roundtrip

```
let ( $c_0, c_1, c_2$ ) = new_chan(3) in  
fork {let  $x = c_1[0].\mathbf{recv}()$  in  $c_1[2].\mathbf{send}(x + 1)$ } ;  
fork {let  $x = c_2[1].\mathbf{recv}()$  in  $c_2[0].\mathbf{send}(x + 1)$ } ;  
 $c_0[1].\mathbf{send}(40)$ ; let  $x = c_0[2].\mathbf{recv}()$  in assert( $x = 42$ )
```

# Safety and Functional Correctness

## Example Program: Roundtrip

```
let (c0, c1, c2) = new_chan(3) in
fork {let x = c1[0].recv() in c1[2].send(x + 1)} ;
fork {let x = c2[1].recv() in c2[0].send(x + 1)} ;
c0[1].send(40); let x = c0[2].recv() in assert(x = 42)
```

**Goal:** Prove crash-freedom (safety) and verify asserts (functional correctness)

Safety	Functional Correctness
Type systems	Program logics
Multipart session types	???
c <sub>0</sub> : ![1]ℤ. ?[2]ℤ. end c <sub>1</sub> : ?[0]ℤ. ![2]ℤ. end c <sub>2</sub> : ?[1]ℤ. ![0]ℤ. end	???

---

! is send, ? is receive

# Key Idea

**Prior Work:** Binary protocols

- ▶ **Session Types:**  $!\mathbb{Z}. ?\mathbb{Z}. \text{end}$
- ▶ **Actris protocols:**  $!(x : \mathbb{Z}) \langle x \rangle. ?\langle x + 2 \rangle. \text{end}$

**Key Idea:** Multiparty protocols!

- ▶ **Multiparty Session Types:**  $![i]\mathbb{Z}. ?[j]\mathbb{Z}. \text{end}$
- ▶ **Multiparty Actris protocols:**  $![i](x : \mathbb{Z}) \langle x \rangle. ?[j] \langle x + 2 \rangle. \text{end}$

**Example Program:** Roundtrip

$c_0[1].\text{send}(40); \text{let } x = c_0[2].\text{recv}() \text{ in assert}(x = 42)$

**Challenge:** How to guarantee consistent global communication?



# Challenge

**Challenge:** How to guarantee consistent global communication?

```
let ( $c_0, c_1, c_2$ ) = new_chan(3) in  
fork {let  $x = c_1[0].\text{recv}()$  in  $c_1[2].\text{send}(x + 1)$ } ;  
fork {let  $x = c_2[1].\text{recv}()$  in  $c_2[0].\text{send}(x + 1)$ } ;  
 $c_0[1].\text{send}(40)$ ; let  $x = c_0[2].\text{recv}()$  in assert( $x = 42$ )
```

**Prior work:** Syntactic duality

$$\begin{aligned}c_0 &: ![1]\mathbb{Z}.?[2]\mathbb{Z}.\text{end} \\c_1 &: ?[0]\mathbb{Z}.![2]\mathbb{Z}.\text{end} \\c_2 &: ?[1]\mathbb{Z}.![0]\mathbb{Z}.\text{end}\end{aligned}$$

**This work:** Semantic duality

$$\begin{aligned}c_0 &\multimap ![1] (x : \mathbb{Z}) \langle x \rangle.?[2] \langle x + 2 \rangle.\text{end} \\c_1 &\multimap ?[0] (x : \mathbb{Z}) \langle x \rangle.![2] \langle x + 1 \rangle.\text{end} \\c_2 &\multimap ?[1] (x : \mathbb{Z}) \langle x \rangle.![0] \langle x + 1 \rangle.\text{end}\end{aligned}$$

**Key Idea:** Define and prove consistency via separation logic!

## **Multiparty Actris protocols**

- ▶ Rich specification language for describing multiparty message passing
- ▶ Protocol consistency defined and proven in separation logic

## **Foundational functional verification via Multris**

- ▶ Program logic for verifying multiparty message passing in Iris
- ▶ Support for language-parametric instantiation of Multiparty Actris

## **Verification of suite of multiparty programs**

- ▶ Increasingly intricate variations of the roundtrip program
- ▶ Chang and Roberts ring leader election algorithm

## **Full mechanisation in Coq**

- ▶ With tactic support for channels primitives and protocol consistency

# Roadmap of this talk

## **Tour of Multiparty Actris**

- ▶ Multiparty dependent separation protocols and protocol consistency
- ▶ Program logic rules
- ▶ Verification of suite of roundtrip variations

## **Verification of Chang and Roberts ring leader election algorithm**

- ▶ Overview of algorithm
- ▶ Ring leader election protocol
- ▶ Verification of algorithm

## **Language-parametricity of Multiparty Actris**

- ▶ Multiparty Actris ghost theory

## **Conclusion and Future Work**

# Tour of Multiparty Actris

# Roundtrip Example

**Roundtrip program:**

```
let ( $c_0, c_1, c_2$ ) = new_chan(3) in  
fork {let  $x = c_1[0].\text{recv}()$  in  $c_1[2].\text{send}(x + 1)$ } ;  
fork {let  $x = c_2[1].\text{recv}()$  in  $c_2[0].\text{send}(x + 1)$ } ;  
 $c_0[1].\text{send}(40)$ ; let  $x = c_0[2].\text{recv}()$  in assert( $x = 42$ )
```

**Goal:** Prove crash-freedom (safety) and verify asserts (functional correctness)

# Multiparty Actris

**Channel endpoint ownership:**  $c \multimap p$

**Protocols:**  $![i] (\vec{x}:\vec{\tau}) \langle v \rangle . p \mid ?[i] (\vec{x}:\vec{\tau}) \langle v \rangle . p \mid \mathbf{end}$

**Example:**  $![1] (x : \mathbb{Z}) \langle x \rangle . ?[2] \langle x + 2 \rangle . \mathbf{end}$

**Rules:**

HT-SEND

$$\{c \multimap ![i] (\vec{x}:\vec{\tau}) \langle v \rangle . p\} c[i].\mathbf{send}(v[\vec{t}/\vec{x}]) \{c \multimap p[\vec{t}/\vec{x}]\}$$

HT-RECV

$$\{c \multimap ?[i] (\vec{x}:\vec{\tau}) \langle v \rangle . p\} c[i].\mathbf{recv}() \{w. \exists \vec{t}. w = v[\vec{t}/\vec{x}] * c \multimap p[\vec{t}/\vec{x}]\}$$

HT-NEW

$$\{\mathbf{CONSISTENT} \vec{p} * |\vec{p}| = n + 1\} \mathbf{new\_chan}(|\vec{p}|) \{(c_0, \dots, c_n). c_0 \multimap \vec{p}_0 * \dots * c_n \multimap \vec{p}_n\}$$

# Protocol Consistency

For any synchronised exchange from  $i$  to  $j$ , given the binders of  $i$ , we must:

1. Instantiate the binders of  $j$
2. Prove equality of exchanged values
3. Prove protocol consistency where  $i$  and  $j$  are updated to their respective tails

Repeat until no more synchronised exchanges exist.

$$\begin{array}{c}
 (\forall i, j. \text{semantic\_dual } \vec{p} \ i \ j) \\
 \hline
 \text{CONSISTENT } \vec{p}
 \end{array}
 \begin{array}{c}
 \vec{p}_i = ![j] (\vec{x}_1 : \vec{\tau}_1) \langle v_1 \rangle. p_1 \ * \ \vec{p}_j = ?[i] (\vec{x}_2 : \vec{\tau}_2) \langle v_2 \rangle. p_2 \ * \\
 \forall \vec{x}_1 : \vec{\tau}_1. \exists \vec{x}_2 : \vec{\tau}_2. v_1 = v_2 \ * \triangleright (\text{CONSISTENT } (\vec{p}[i := p_1][j := p_2])) \\
 \hline
 \text{semantic\_dual } \vec{p} \ i \ j
 \end{array}$$

# Protocol Consistency - Example

Protocol consistency example:

$$\vec{p}_0 := ![1] (x : \mathbb{Z}) \langle x \rangle. ?[2] \langle x + 2 \rangle. \mathbf{end}$$
$$\vec{p}_1 := ?[0] (x : \mathbb{Z}) \langle x \rangle. ![2] \langle x + 1 \rangle. \mathbf{end}$$
$$\vec{p}_2 := ?[1] (x : \mathbb{Z}) \langle x \rangle. ![0] \langle x + 1 \rangle. \mathbf{end}$$

Protocol consistency:

$$\frac{(\forall i, j. \text{semantic\_dual } \vec{p} \ i \ j)}{*}$$

CONSISTENT  $\vec{p}$

$$\frac{\begin{array}{l} \vec{p}_i = ![j] (x_1 : \vec{\tau}_1) \langle v_1 \rangle. p_1 \quad * \quad \vec{p}_j = ?[i] (x_2 : \vec{\tau}_2) \langle v_2 \rangle. p_2 \quad * \\ \forall x_1 : \vec{\tau}_1. \exists x_2 : \vec{\tau}_2. v_1 = v_2 \quad * \triangleright (\text{CONSISTENT } (\vec{p}[i := p_1][j := p_2])) \end{array}}{*} \text{semantic\_dual } \vec{p} \ i \ j$$



# Roundtrip Example - Verified

Roundtrip program:

```
let (c0, c1, c2) = new_chan(3) in  
fork {let x = c1[0].recv() in c1[2].send(x + 1)} ;  
fork {let x = c2[1].recv() in c2[0].send(x + 1)} ;  
c0[1].send(40); let x = c0[2].recv() in assert(x = 42)
```

Protocols:

$$\begin{aligned} c_0 &\multimap ! [1] (x : \mathbb{Z}) \langle x \rangle . ? [2] \langle x + 2 \rangle . \mathbf{end} \\ c_1 &\multimap ? [0] (x : \mathbb{Z}) \langle x \rangle . ! [2] \langle x + 1 \rangle . \mathbf{end} \\ c_2 &\multimap ? [1] (x : \mathbb{Z}) \langle x \rangle . ! [0] \langle x + 1 \rangle . \mathbf{end} \end{aligned}$$

Verified Safety!

# Roundtrip Reference Example

Roundtrip reference program:

```
let ( $c_0, c_1, c_2$ ) = new_chan(3) in  
fork {let  $\ell = c_1[0].\text{recv}()$  in  $\ell \leftarrow (!\ell + 1); c_1[2].\text{send}(\ell)$ } ;  
fork {let  $\ell = c_2[1].\text{recv}()$  in  $\ell \leftarrow (!\ell + 1); c_2[0].\text{send}()$ } ;  
let  $\ell = \text{ref } 40$  in  $c_0[1].\text{send}(\ell); c_0[2].\text{recv}();$  let  $x = !\ell$  in assert( $x = 42$ )
```

**Goal:** Prove crash-freedom (safety) and verify asserts (functional correctness)

# Multiparty Actris with Resources

**Protocols:**  $![i] (\vec{x} : \vec{\tau}) \langle v \rangle \{P\}.p \mid ?[i] (\vec{x} : \vec{\tau}) \langle v \rangle \{P\}.p$

**Example:**  $![1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{\ell \mapsto x\}. ?[2] \langle () \rangle \{\ell \mapsto (x + 2)\}.\text{end}$

**Rules:**

HT-SEND

$$\{c \multimap ![i] (\vec{x} : \vec{\tau}) \langle v \rangle \{P\}.p * P[\vec{t}/\vec{x}]\} c[i].\text{send}(v[\vec{t}/\vec{x}]) \{c \multimap p[\vec{t}/\vec{x}]\}$$

HT-RECV

$$\{c \multimap ?[i] (\vec{x} : \vec{\tau}) \langle v \rangle \{P\}.p\} c[i].\text{recv}() \{w. \exists \vec{t}. w = v[\vec{t}/\vec{x}] * c \multimap p[\vec{t}/\vec{x}] * P[\vec{t}/\vec{x}]\}$$

HT-NEW

$$\{\text{CONSISTENT } \vec{p} * |\vec{p}| = n + 1\} \text{new\_chan}(|\vec{p}|) \{(c_0, \dots, c_n). c_0 \multimap \vec{p}_0 * \dots * c_n \multimap \vec{p}_n\}$$

# Protocol Consistency with Resources

For any synchronised exchange from  $i$  to  $j$ , given the binders and resources of  $i$ :

1. Instantiate the binders of  $j$
2. Prove equality of exchanged values and the resources of  $j$
3. Prove protocol consistency where  $i$  and  $j$  are updated to their respective tails

Repeat until no more synchronised exchanges exist.

$$\begin{array}{c}
 (\forall i, j. \text{semantic\_dual } \vec{p} \ i \ j) \\
 \hline
 \text{CONSISTENT } \vec{p}
 \end{array}
 \quad *$$

$$\begin{array}{c}
 \vec{p}_i = ! [j] (x_1 : \vec{\tau}_1) \langle v_1 \rangle \{P_1\}. p_1 \multimap \vec{p}_j = ? [i] (x_2 : \vec{\tau}_2) \langle v_2 \rangle \{P_2\}. p \multimap \\
 \forall x_1 : \vec{\tau}_1. P_1 \multimap \exists x_2 : \vec{\tau}_2. v_1 = v_2 * P_2 * \triangleright (\text{CONSISTENT } (\vec{p}[i := p_1][j := p_2])) \\
 \hline
 \text{semantic\_dual } \vec{p} \ i \ j
 \end{array}
 \quad *$$

# Protocol Consistency with Resources - Example

## Protocol consistency example:

$$\begin{aligned}\vec{p}_0 &:= ![1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ?[2] \langle () \rangle \{ \ell \mapsto (x + 2) \}. \text{end} \\ \vec{p}_1 &:= ?[0] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ![2] \langle \ell \rangle \{ \ell \mapsto (x + 1) \}. \text{end} \\ \vec{p}_2 &:= ?[1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ![0] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \text{end}\end{aligned}$$

## Protocol consistency:

$$\frac{(\forall i, j. \text{semantic\_dual } \vec{p} \ i \ j)}{\text{CONSISTENT } \vec{p}} *$$
$$\frac{\begin{aligned} &\vec{p}_i = ![j] (\vec{x}_1 : \vec{\tau}_1) \langle v_1 \rangle \{ P_1 \}. p_1 \text{ } * \vec{p}_j = ?[i] (\vec{x}_2 : \vec{\tau}_2) \langle v_2 \rangle \{ P_2 \}. p_2 \text{ } * \\ &\forall \vec{x}_1 : \vec{\tau}_1. P_1 \text{ } * \exists \vec{x}_2 : \vec{\tau}_2. v_1 = v_2 \text{ } * P_2 \text{ } * \triangleright (\text{CONSISTENT } (\vec{p}[i := p_1][j := p_2])) \end{aligned}}{\text{semantic\_dual } \vec{p} \ i \ j} *$$

# Roundtrip Reference Example - Verified

Roundtrip reference program:

```
let (c0, c1, c2) = new_chan(3) in  
fork {let ℓ = c1[0].recv() in ℓ ← (!ℓ + 1); c1[2].send(ℓ)} ;  
fork {let ℓ = c2[1].recv() in ℓ ← (!ℓ + 1); c2[0].send()} ;  
let ℓ = ref 40 in c0[1].send(ℓ); c0[2].recv(); let x = !ℓ in assert(x = 42)
```

Protocols:

$$\begin{aligned} c_0 &\longrightarrow ! [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ? [2] \langle () \rangle \{ \ell \mapsto (x + 2) \}. \text{end} \\ c_1 &\longrightarrow ? [0] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ! [2] \langle \ell \rangle \{ \ell \mapsto (x + 1) \}. \text{end} \\ c_2 &\longrightarrow ? [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ! [0] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \text{end} \end{aligned}$$

# Protocol Consistency - Recursion

Protocols are contractive in the tail:

$$\mu\text{rec}. ! [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ? [2] \langle () \rangle \{ \ell \mapsto (x + 2) \}. \text{rec}$$

Protocols:

$$\vec{p}_0 = \mu\text{rec}. ! [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ? [2] \langle () \rangle \{ \ell \mapsto (x + 2) \}. \text{rec}$$

$$\vec{p}_1 = \mu\text{rec}. ? [0] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ! [2] \langle \ell \rangle \{ \ell \mapsto (x + 1) \}. \text{rec}$$

$$\vec{p}_2 = \mu\text{rec}. ? [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ! [0] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \text{rec}$$

Recursion via Löb induction ( $\triangleright$ ):

$$\frac{\vec{p}_i = ! [j] (\vec{x}_1 : \vec{\tau}_1) \langle v_1 \rangle \{ P_1 \}. p_1 \multimap \vec{p}_j = ? [i] (\vec{x}_2 : \vec{\tau}_2) \langle v_2 \rangle \{ P_2 \}. p_2 \multimap \forall \vec{x}_1 : \vec{\tau}_1. P_1 \multimap \exists \vec{x}_2 : \vec{\tau}_2. v_1 = v_2 \multimap P_2 \multimap \triangleright (\text{CONSISTENT } (\vec{p}[i := p_1][j := p_2]))}{\text{semantic\_dual } \vec{p} \, i \, j}^*$$

# Protocol Consistency - Framing

Consider the replacement of process 1 with a forwarder:

**let**  $v = c_1[0].\text{recv}()$  **in**  $c_1[1].\text{send}(v)$

Protocols:

$\vec{p}_0 = \mu\text{rec}. ! [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ? [2] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \text{rec}$

$\vec{p}_1 = \mu\text{rec}. ? [0] (v : \text{Val}) \langle v \rangle. ! [2] \langle v \rangle. \text{rec}$

$\vec{p}_2 = \mu\text{rec}. ? [1] (\ell : \text{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ! [0] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \text{rec}$

Protocol consistency owns resources while in transit:

$$\frac{\vec{p}_i = ! [j] (\vec{x}_1 : \vec{\tau}_1) \langle v_1 \rangle \{ P_1 \}. p_1 \multimap \vec{p}_j = ? [i] (\vec{x}_2 : \vec{\tau}_2) \langle v_2 \rangle \{ P_2 \}. p_2 \multimap \forall \vec{x}_1 : \vec{\tau}_1. P_1 \multimap \exists \vec{x}_2 : \vec{\tau}_2. v_1 = v_2 \multimap P_2 \multimap \triangleright (\text{CONSISTENT } (\vec{p}[i := p_1][j := p_2]))}{\text{semantic\_dual } \vec{p} \ i \ j}^*$$



# Protocol Consistency - Branching

Consider the extension of process 1 with a rerouter:

**let**  $(v, b) = c_1[0].\mathbf{recv}()$  **in**  $c_1[\mathbf{if } b \mathbf{ then } 2 \mathbf{ else } 3].\mathbf{send}(v)$

Protocols:

$$\vec{p}_0 = \mu\mathbf{rec}. ! [1] (\ell : \mathbf{Loc}, x : \mathbb{Z}, b : \mathbb{B}) \langle (\ell, b) \rangle \{ \ell \mapsto x \}.$$

$$? [\mathbf{if } b \mathbf{ then } 2 \mathbf{ else } 3] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \mathbf{rec}$$

$$\vec{p}_1 = \mu\mathbf{rec}. ? [0] (v : \mathbf{Val}, b : \mathbb{B}) \langle (v, b) \rangle. ! [\mathbf{if } b \mathbf{ then } 2 \mathbf{ else } 3] \langle v \rangle. \mathbf{rec}$$

$$\vec{p}_2, \vec{p}_3 = \mu\mathbf{rec}. ? [1] (\ell : \mathbf{Loc}, x : \mathbb{Z}) \langle \ell \rangle \{ \ell \mapsto x \}. ! [0] \langle () \rangle \{ \ell \mapsto (x + 1) \}. \mathbf{rec}$$

We can do case analysis on the binders:

$$\begin{array}{l} \vec{p}_i = ! [j] (\vec{x}_1 : \vec{\tau}_1) \langle v_1 \rangle \{ P_1 \}. p_1 \multimap \vec{p}_j = ? [i] (\vec{x}_2 : \vec{\tau}_2) \langle v_2 \rangle \{ P_2 \}. p_2 \multimap \\ \forall \vec{x}_1 : \vec{\tau}_1. P_1 \multimap \exists \vec{x}_2 : \vec{\tau}_2. v_1 = v_2 \multimap P_2 \multimap \triangleright (\mathbf{CONSISTENT} (\vec{p}[i := p_1][j := p_2])) \end{array}$$

$$\hline \mathbf{semantic\_dual} \vec{p} i j$$

# Benchmark: Chang and Roberts Ring Leader Election

# Leader Election

Consider  $n$  uniquely identifiable actors in a network

Leader election is an algorithm that upon satisfies:

- ▶ **Uniqueness:** There is exactly one actor that considers itself as leader
- ▶ **Agreement:** All other actors know who the leader is
- ▶ **Termination:** The algorithm finishes in finite time\*


**Goal:** Prove **uniqueness** and **agreement**

**Observation:** We prove partial correctness so **termination** is out of scope

We lift the properties to functional correctness as:

- ▶ **Uniqueness:** The leader can proceed with elevated permissions (resources)
- ▶ **Agreement:** Participants following interaction can depend on knowing leader

# Chang and Roberts Ring Leader Election - Overview



# Chang and Roberts Ring Leader Election - Algorithm

Consider  $n$  actors, with unique id's, arranged in a ring

- ▶ Ex1:  $0 \rightarrow 1, 1 \rightarrow 2, 2 \rightarrow 0$
- ▶ Ex2:  $0 \rightarrow 2, 2 \rightarrow 1, 1 \rightarrow 0$

Actors are tagged as participating or not; everyone starts untagged

- ▶ Tag as participating whenever any message is sent

Message types are election( $i'$ ) **(1)** and elected( $i'$ ) **(2)**

Received election( $i'$ ) messages are compared to the receivers id  $i$  and

- ▶ If  $i' > i$ , send election( $i'$ ) **(1.1)**
- ▶ If  $i' = i$ , we are elected, send elected( $i$ ) **(1.2)**
- ▶ If we are not participating, send election( $i$ ) **(1.3)**
- ▶ If we are already participating, do nothing **(1.4)**

Received elected( $i'$ ) messages are compared to the participants id  $i$  and

- ▶ If  $i' = i$ , terminate by returning  $i'$  **(2.1)**
- ▶ If  $i' \neq i$ , send elected( $i'$ ), and terminate by returning  $i'$  **(2.2)**

# Chang and Roberts Ring Leader Election - Implementation

We encode  $\text{election}(i)$  as **inl**  $i$  and  $\text{elected}(i)$  as **inr**  $i$ .

We write  $i_l$  and  $i_r$  for the left and right participants of participant  $i$ .

The leader election process can then be implemented as follows:

```
process  $c\ i \triangleq$  rec  $isp =$   
  match  $c[i_r].\text{recv}()$  with  
    | inl  $i' \Rightarrow$  if  $i < i'$  then  $c[i_l].\text{send}(\text{inl } i')$ ;  $rec\ \text{true}$  (1.1)  
      else if  $i = i'$  then  $c[i_l].\text{send}(\text{inr } i)$ ;  $rec\ \text{false}$  (1.2)  
      else if  $isp$  then  $rec\ \text{true}$  (1.3)  
      else  $c[i_l].\text{send}(\text{inl } i)$ ;  $rec\ \text{true}$  (1.4)  
    | inr  $i' \Rightarrow$  if  $i = i'$  then  $i'$  (2.1)  
      else  $c[i_l].\text{send}(\text{inr } i')$ ;  $i'$  (2.2)  
  end
```

# Chang and Roberts Ring Leader Election - Validation

Procedure for starting the election:

$$\text{init } c \ i \triangleq c[i_l].\mathbf{send}(\mathbf{inl} \ i); \text{ process } c \ i \ \mathbf{true}$$

Closed program example of election:

```
ring_ref_prog  $n \triangleq$   
  let  $\ell = \mathbf{ref} \ 42$  in  
  let  $(c_0, \dots, c_{n-1}) = \mathbf{new\_chan}(n)$  in  
  for  $(i = 1 \dots (n - 1)) \left\{ \mathbf{fork} \left\{ \mathbf{let} \ i' = \text{process } c_i \ i \ \mathbf{false} \ \mathbf{in} \right\} \right\};$   
  let  $i' = \text{init } c_0 \ 0$  in if  $i' = 0$  then free  $\ell$  else  $()$ 
```

**Goal:** Verify that only one leader is elected (no use-after-free)

# Chang and Roberts Ring Leader Election - Protocol

We can define the ring leader election protocol as:

$$\begin{aligned}
 \text{ring\_prot}(i : \mathbb{N})(P : \text{iProp})(p : \mathbb{N} \rightarrow \text{iProto}) : \mathbb{B} \rightarrow \text{iProto} &\triangleq \mu\text{rec}. \lambda(\text{isp} : \mathbb{B}). \\
 &\left\{ \begin{array}{ll}
 \text{inl}(i' : \mathbb{N}) \langle i' \rangle & \Rightarrow \text{if } i < i' \text{ then } ! [i_l] \langle \text{inl } i' \rangle. \text{rec true} & (1.1) \\
 & \text{else if } i = i' \text{ then } ! [i_l] \langle \text{inr } i \rangle. \text{rec false} & (1.2) \\
 & \text{else if } \text{isp} \text{ then } \text{rec true} & (1.3) \\
 & \text{else } ! [i_l] \langle \text{inl } i \rangle. \text{rec true} & (1.4) \\
 \text{inr}(i' : \mathbb{N}) \langle i' \rangle \{i = i' \Rightarrow P\} & \Rightarrow \text{if } i = i' \text{ then } p \ i' & (2.1) \\
 & \text{else } ! [i_l] \langle \text{inr } i' \rangle. p \ i' & (2.2)
 \end{array} \right. & \&[i_r]
 \end{aligned}$$

This lets us verify the following spec for the ring leader process:

$$\{c \multimap \text{ring\_prot } i \ P \ p \ \text{isp}\} \text{ process } c \ i \ \text{isp} \ \{i'. c \multimap (p \ i') * (i = i' \Rightarrow P)\}$$



# Chang and Roberts Ring Leader Election - Init

The protocol for starting an election is an extension of the ring protocol:

$$\begin{aligned} \text{init\_prot}(i : \mathbb{N})(P : \text{iProp})(p : \mathbb{N} \rightarrow \text{iProto}) : \text{iProto} &\triangleq \\ ! [i] \langle \mathbf{inl} \ i \rangle \{P\}. \text{ring\_prot } i \ P \ p \ \mathbf{true} \end{aligned}$$

With the initial message we yield the  $P$  resource to the network.

With this protocol we can prove the following specification for the starting process:

$$\{c \multimap (\text{init\_prot } i \ P \ p) * P\} \text{init } c \ i \ \{i'. c \multimap (p \ i') * (i = i' \Rightarrow P)\}$$

# Chang and Roberts Ring Leader Election - Leader Uniqueness

```
ring_ref_prog  $n \triangleq$   
  let  $\ell = \mathbf{ref} \, 42$  in  
  let  $(c_0, \dots, c_{n-1}) = \mathbf{new\_chan}(n)$  in  
  for  $(i = 1 \dots (n - 1))$  { fork { let  $i' = \text{process } c_i$  if  $i' = i$  then free  $\ell$  else  $()$  } } ;  
  let  $i' = \text{init } c_0$  if  $i' = 0$  then free  $\ell$  else  $()$ 
```

We verify the program for 3 participants with the following protocols:

$c_0 \multimap \mathbf{end}$

$c_1 \multimap \mathbf{end}$

$c_2 \multimap \mathbf{end}$

We can thus verify:  $\{\mathbf{True}\} \text{ ring\_ref\_prog } 3 \{\mathbf{True}\}$

# Chang and Roberts Ring Leader Election - Leader Agreement

```
ring_del_prog  $n \triangleq$   
  let ( $c_0, \dots, c_n$ ) = new_chan( $n + 1$ ) in  
    fork { let  $i' = c_n[0].\text{recv}()$  in for( $i = 1 \dots (n - 1)$ ) { assert( $c_n[i].\text{recv}() = i'$ ) } } ;  
    for( $i = 1 \dots (n - 1)$ ) { fork { let  $i' = \text{process } c_i \text{ } i$  false in  $c_i[n].\text{send}(i')$  } } ;  
    let  $i' = \text{init } c_0 \text{ } 0$  in  $c_0[n].\text{send}(i')$ 
```

We verify the program for 3 participants and 1 central coordinator:

$c_0 \multimap \text{end}$

$c_1 \multimap \text{end}$

$c_2 \multimap \text{end}$

$c_3 \multimap \text{end}$

We can thus verify:  $\{\text{True}\} \text{ ring\_del\_prog } 3 \{\text{True}\}$

# Language Parametricity of Multiparty Actris

# Multiparty Actris Ghost Theory

We prove language-generic ghost theory rules:

PROTO-ALLOC

$$\frac{\text{CONSISTENT } \vec{p}}{\models \exists \chi. \text{prot\_ctx } \chi \mid \vec{p} \mid * \bigstar_{i \mapsto p \in \vec{p}} \text{prot\_own } \chi \ i \ p}$$

PROTO-VALID

$$\frac{\text{prot\_ctx } \chi \ n \quad \text{prot\_own } \chi \ i \ p}{i < n}$$

PROTO-STEP

$$\frac{\text{prot\_ctx } \chi \ n \quad P_1[\vec{t}_1/\vec{x}_1] \quad \text{prot\_own } \chi \ i \ (![j] (\vec{x}_1 : \vec{\tau}_1) \langle v_1 \rangle \{P_1\}.p_1) \quad \text{prot\_own } \chi \ j \ (?[i] (\vec{x}_2 : \vec{\tau}_2) \langle v_2 \rangle \{P_2\}.p_2)}{\models \triangleright \exists (\vec{t}_2 : \vec{\tau}_2). \text{prot\_ctx } \chi * \text{prot\_own } \chi \ i \ (p_1[\vec{t}_1/\vec{x}_1]) * \text{prot\_own } \chi \ j \ (p_2[\vec{t}_2/\vec{x}_2]) * (v_1[\vec{t}_1/\vec{x}_1]) = (v_2[\vec{t}_2/\vec{x}_2]) * P_2[\vec{t}_2/\vec{x}_2]}$$

One can then define  $c \rightsquigarrow p$  and prove Hoare triple rules for a given language using the ghost theory

► Such as HT-SEND, HT-RECV, and HT-NEW

# Conclusion and Future Work

## **Dependent multiparty protocols are non-trivial to prove sound**

- ▶ Mismatched dependencies (quantifiers) makes syntactic analysis difficult
- ▶ Fullfillment of received resources is tricky

## **Concurrent separation logic (Iris) is a good fit for multiparty protocols**

- ▶ Quantifier scopes enable inherent tracking of dependencies
- ▶ Separation logic enables framing of resources
- ▶ Integration with other features readily available

## **Automation of protocol consistency proofs is warranted**

- ▶ Deterministic (often synchronous) protocols are barely manageable
- ▶ Brute-force procedure allows for some automation
- ▶ Asynchronous protocols would require more efficient techniques

## **Additional features**

- ▶ Asynchronous communication

## **More scalable methodology for proving protocol consistency**

- ▶ Abstraction and Modularity via separation logic
- ▶ Automation via model checking?

## **Semantic Multiparty Session Type System**

- ▶ Investigate correspondences with syntactic protocol consistency

## **Deadlock freedom guarantees**

- ▶ Leverage connectivity graphs for multiparty communication

## **Multiparty Actris for distributed systems**

- ▶ Leverage Aneris

**And much more?:** RefinedActris, Verified Secure MPC, Non-interference, ...



$! [1] \langle \text{"Thank you"} \rangle \{ \text{MultrisOverview} \}.$   
 $\mu \text{rec}. ? [1] (q : \text{Question } i) \langle q \rangle \{ \text{AboutMultris } q \}.$   
 $! [i] (a : \text{Answer}) \langle a \rangle \{ \text{Insightful } q \ a \}. \text{rec}$