
Knowing Before Saying: Internal Correctness Signals in Mathematical Reasoning

Anonymous Author(s)

Affiliation

Address

email

Abstract

1 Language models often answer math problems wrong while reporting high
2 confidence. Does the model lack self-knowledge, or does it have it and fail to
3 express it? To separate the two, we read the model’s internal state directly
4 instead of asking it. The study is anchored by a geometry-construction
5 testbed whose outputs a symbolic compiler grades exactly, so no human
6 or model judge is in the loop. We test four open models with distinct
7 architectures on four domains: compiler-verified geometry, MMLU-Pro,
8 MATH, and GPQA-Diamond. A simple linear detector trained on that
9 state, a probe, predicts whether an attempt is correct better than the model’s
10 stated confidence in 12 of 16 cells (one tie, mean +0.09 AUROC). The gap
11 is largest on MATH (+0.20), where a wrong answer looks as clean as a right
12 one. The signal is specific to the attempt: it survives a within-question
13 control that pushes the model’s own $P(\text{True})$ toward chance. It is largely
14 domain-general: a probe trained in one domain still discriminates in the
15 others. And the model uses it. Amplifying the model’s own correctness
16 direction, with no labels at intervention time, drops stated confidence on
17 wrong answers from 80 to 43 while correct answers hold near 90, and halves
18 calibration error. Models substantially know when they are wrong. How
19 much of that knowledge reaches speech varies by architecture, and we outline
20 a global-workspace test of why.

21 1 Introduction

22 A mathematical agent that errs is unavoidable. One that errs *and knows it* can abstain,
23 retry, or escalate. Stated confidence is a weak guide to correctness, and weakest where
24 mathematics is hardest. A wrong multi-step derivation still ends in a cleanly formatted final
25 answer, and nothing on the page gives it away. We split the problem into two questions. Do
26 models internally represent that an output is wrong (**knowing**)? Does that representation
27 reach what they report (**saying**)? If a gap exists, it is both an unused reliability signal and
28 a concrete claim about machine introspection.

29 Prior work shows that output probabilities are often better calibrated than words [4], and
30 that the truth of *given statements* is linearly readable from activations [1, 2, 6]. Verbalized-
31 calibration studies measure what models say [5, 7]. We combine these threads on the model’s
32 *own attempts*. We elicit confidence before and after each attempt, measure blind (no-feedback)
33 updating, take four readouts of the same latent quantity on identical records, and intervene
34 on the representation [8]. Measuring this well requires ground-truth correctness labels for
35 open-ended generation at scale. That is why the study is anchored by a machine-verified

testbed (Section 2). Our findings (Section 3): the internal signal exceeds the spoken one almost everywhere. It is specific to the individual attempt. It transfers across domains. And it causally sets stated confidence, to a degree that depends on architecture. We argue that this dependence is itself the finding.

2 The instrument: ground truth without a judge

Metacognition experiments live or die by their correctness labels, and labels from an LLM judge inherit the judge’s blind spots. Our anchor domain uses no judge: instead of judging a diagram by eye, it compiles the construction and checks each requirement of the prompt as an equation. In GEOGENBENCH, a model receives a natural-language request for a geometric construction, for example “draw an acute triangle EFG with $\angle E=60^\circ$, $\angle F=70^\circ$; construct the altitude from G meeting EF at H .” Its output is compiled to SymPy coordinates. Each clause of the prompt is then decided as an exact symbolic predicate (15 typed predicates, tolerance 5×10^{-3}). Grading is deterministic, reproducible, and about $1000\times$ cheaper than a vision-language judge. The task is hard for current open models (13–39% pass). Prompts and rubrics are generated from the same Python source, so the grader cannot drift from the question. A pre-registered human study ($N=200$, two trained raters, blind) finds that the verifier’s disagreements with humans run in one direction only: it is lenient, never harsh. A **fail** label, the label metacognition needs, is therefore trustworthy. We report a benchmark of six frontier models on the 801-prompt suite elsewhere. Two findings matter here. A structured intermediate representation lifts every model (+2 to +25 p.p., with three flagships converging within 1 p.p.). And most wrong outputs are rendered diagrams with wrong geometry, not broken code. They read as fluent and confident, and they are wrong, which is the failure mode that motivates reading the model’s internals. MMLU-Pro, MATH, and GPQA-Diamond complete the domain grid with programmatic grading. We drop benchmarks the models have saturated, since metacognition is failure-hungry.

3 Knowing versus saying

Protocol. We test four open models with different architectures: Qwen3.6-27B (hybrid Mamba-attention), GLM-4.7-Flash (MoE), Mistral-Small-24B (dense), and Gemma-4-26B-A4B (MoE, VLM-derived). Each runs on all four domains, about 750 records per cell. Each problem takes three turns: prospective confidence, the attempt, and retrospective confidence. Grading is external and never shown to the model, so any post-attempt revision is blind self-assessment. We take four readouts of the same latent quantity on identical records: stated confidence (0–100); $P(\text{True})$, the model’s probability of answering “True” when asked whether its answer is correct; the answer’s log-probability; and a linear *probe*. The residual stream is the model’s internal state, a vector of a few thousand numbers at every token and layer. The probe is a logistic regression trained to read correctness from that vector at the confidence decision token, the position that is about to produce the confidence digit. It is scored out-of-fold with question-grouped folds and reported at one pre-specified layer at 0.7 of network depth rather than the best layer. Our metric throughout is AUROC, the probability that a random correct attempt scores above a random wrong one: 0.5 is chance, 1.0 is perfect. Four controls guard the readout. The probe adds +0.22 mean AUROC over a surface-features baseline (answer length and shape) in 15 of 16 cells. The read token is identical across records, so layer-0 activations carry no signal by construction (per-fold AUROC 0.500); anything decoded deeper was computed during the attempt. A within-question control holds difficulty fixed. A public deviations log records four bugs that planned controls caught, which we fixed and re-ran.

Knowing exceeds saying, most where errors look clean. The internal state ranks right and wrong answers better than the model’s own words do. The probe beats stated confidence in **12 of 16** cells (Table 1, left). The three losses are small- n cells, two of them Gemma-4. The gap is widest on MATH (mean +0.20). Stated confidence there is weak, while the internal signal is the strongest of any domain (up to 0.95). Verbalized confidence appears to lean on surface fluency, and multi-step computation defeats fluency. The internal

Table 1: Left: post-attempt correctness discrimination (AUROC), stated confidence vs. residual-stream probe, in representative cells. Overall the probe wins 12 of 16 cells with one tie, mean +0.09. A paired bootstrap is significantly positive in 10 of 16 and never significantly negative. Right: the within-question control, with difficulty fixed. The model’s own P(True) falls toward chance while the probe holds.

model $\times$ domain	stated	probe
Gemma-4 $\times$ MATH	0.57	0.78
Qwen3.6 $\times$ MMLU-Pro	0.67	0.84
GLM $\times$ MMLU-Pro	0.67	0.85
Mistral $\times$ MATH	0.79	0.83

within-question	probe	P(True)
Qwen3.6 $\times$ MMLU-Pro	0.74	0.47
GLM $\times$ MMLU-Pro	0.73	0.59
Mistral $\times$ MATH	0.72	0.59

state encodes the computation itself. Post-attempt internal readouts also exceed pre-attempt ones. Doing the work sharpens the internal signal even where it degrades the stated one.

The signal tracks the attempt, not the question. A skeptic’s alternative is that the probe has only learned which questions are hard. Holding the question fixed rules this out. Within a single question, across its five sampled attempts, only attempt-level information can discriminate. There the model’s own P(True) falls toward chance while the probe holds (Table 1, right). P(True) largely recovers *which questions are hard*. The probe tracks *whether this attempt succeeded*. Two further cuts of the data agree. Residualizing post-attempt probe scores on pre-attempt scores leaves substantial AUROC (0.59–0.87), so the post signal is attempt-specific rather than difficulty re-expressed. And the post-attempt direction transfers only weakly to the pre-attempt site. *Did I succeed?* and *Is this hard?* are largely distinct directions. Blind post-attempt confidence drops are also larger on failures than on successes. That is a genuine, under-expressed self-monitoring process.

One correctness direction, largely domain-general. If the model had one internal sense of “this is wrong,” a probe trained on one subject should work on another. It does: a probe trained in one domain and evaluated in another keeps most of its in-domain AUROC. In the original matrix, retention was about 87–90% (Qwen3.6 off-diagonal 0.71 vs. diagonal 0.81), and sometimes lossless within QA (Qwen3.6 MMLU-Pro→MATH 0.86 vs. 0.91). A fresh Mistral capture across MMLU-Pro, MATH, and GPQA, analysed with a corrected standardization step, gives 96% retention (off-diagonal 0.69 vs. diagonal 0.72; MMLU-Pro→MATH 0.84 vs. 0.83 in-domain), with direction cosines of 0.54–0.82. GPQA is Mistral’s weakest domain (in-domain 0.57), and transfer into it is bounded accordingly. Geometry is partly special. On Gemma-4, geometry-trained probes *anti-transfer* to QA (0.31–0.39), while QA-trained probes work on geometry (about 0.70). Probes trained on the generative task can latch onto task-specific features; QA-trained probes find the general direction. A shared correctness direction is what a deployable readout needs, and what a workspace account (below) predicts.

The signal is causally used. Reading shows the signal exists; steering shows the model uses it. We steer at the confidence token, after the answer is written, so the answer cannot change. We amplify the model’s own projection onto its correctness direction, with no labels at intervention time. On Mistral $\times$ MATH, as gain rises from 1 to 2 to 4, stated confidence on *failed* answers falls from 80 to 65 to 43. Correct answers hold near 90. Calibration error halves (0.31 $\rightarrow$ 0.13). Dampening the signal *increases* overconfidence, so the dose–response runs both ways. An independent replication on a fresh 750-record capture, with the random control scaled to the same per-record perturbation magnitude, reproduces the effect: failed-answer confidence 84 $\rightarrow$ 69 $\rightarrow$ 55, correct 96 $\rightarrow$ 94 $\rightarrow$ 88, calibration error 0.33 $\rightarrow$ 0.18, while the matched random direction leaves confidence unchanged at gain 2 and only degrades the output at gain 4. Replication depends on architecture. Gemma-4 shows the right specificity

but is underpowered. GLM is null at the gains we tested; its stated confidence saturates near 100, exactly where the probe most exceeds $P(\text{True})$. We read this spectrum as the finding: *how much internal knowledge reaches speech varies by model*.

A label-free witness, and an architecture-gated one. Trained probes invite an overfitting critique, so we added an unsupervised instrument: the Jacobian lens of the global-workspace account [3]. The lens is fit on generic text, with no task labels anywhere in its construction, and scores the same stored activations as a wrong-vs-correct disposition. On dense models it lands in probe territory (Mistral 0.76–0.82; Qwen2.5-14B, a dense within-family control, 0.88) and beats stated confidence with no labels. Two independent instruments find one direction. And because the lens reads through the model’s own speech pathway, the knowledge it finds sits in the subspace the model can put into words: it is *speakable*. On the other architectures the lens itself fails (Mamba-hybrid 0.43, MoE 0.31) while the supervised probe still reads the signal in every model. The failure has a fingerprint. Transported through the averaged map, the lens’s “correct” and “wrong” readout vectors collapse to cosine 0.96 on MoE, against about 0.4 on dense models. An averaged map is only faithful when wiring barely varies per input. Swapping Mamba for dense within one model family flips the lens from 0.43 to 0.88. So the *label-free shortcut* is architecture-gated, and the signal is not. The open frontier is the gate itself. We want a direct per-input wiring-variance measurement, and to learn whether unexpressed knowledge on the failing architectures is speakable but suppressed, or an access failure. The question is no longer *whether* models know. It is *what gates the knowing from the saying*.

4 Discussion

For reliable mathematical agents. Where a domain admits a verifier, use it. Symbolic checks are exact, cheap, and conservative in a known direction. Where it does not, the internal signal is the best attempt-specific readout we found. Abstaining on the probe’s lowest-scoring outputs raises accuracy far more than abstaining on low stated confidence. In the cells where verbalized abstention fails outright, internal abstention still works. The steering result suggests stated confidence itself can be made honest by amplification rather than retraining. Domain-generalizability means one direction may serve many tasks.

Limitations. Linear probes at a single token undercount nonlinear or multi-token signal. On MATH, an early-layer channel next to the answer text may contribute lexical signal that the within-question control cannot fully exclude. The steering test is the discriminator, which is why we weight the causal arm heavily. The causal arm is one clean model plus one underpowered and one null replication. Two MATH cells ran at reduced n . The architecture explanation for the lens rests on a readout-geometry fingerprint, not yet on a direct per-input wiring-variance measurement. Whether the knowing–saying gap is an artifact of preference tuning is open; a base-model arm would test it.

5 Conclusion

Anchored by a compiler-graded geometry testbed, we showed that open language models carry a linear, largely domain-general internal signal of their own correctness. It exceeds their stated confidence, tracks the individual attempt, and causally sets what they say, to a degree that varies by architecture. Models substantially *know* when their mathematics is wrong. The open problem is the gate between knowing and saying, and we have a concrete, falsifiable test of it in flight.

References

- [1] Amos Azaria and Tom Mitchell. The internal state of an LLM knows when it’s lying. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, 2023.
- [2] Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. In *International Conference on Learning Representations (ICLR)*, 2023.

- 176 [3] Wes Gurnee, Nicholas Sofroniew, Adam Pearce, Mateusz Piotrowski, Isaac Kauvar, Runjin
177 Chen, Anna Soligo, Paul Bogdan, Euan Ong, Rowan Wang, T. Ben Thompson, David
178 Abrahams, Subhash Kantamneni, Emmanuel Ameisen, Joshua Batson, and Jack Lindsey.
179 Verbalizable representations form a global workspace in language models. *Transformer*
180 *Circuits Thread*, 2026. [https://transformer-circuits.pub/2026/workspace/index.](https://transformer-circuits.pub/2026/workspace/index.html)
181 [html](https://transformer-circuits.pub/2026/workspace/index.html); code: <https://github.com/anthropics/jacobian-lens>.
- 182 [4] Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan
183 Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, et al.
184 Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.
- 185 [5] Stephanie Lin, Jacob Hilton, and Owain Evans. Teaching models to express their
186 uncertainty in words. *Transactions on Machine Learning Research*, 2022.
- 187 [6] Samuel Marks and Max Tegmark. The geometry of truth: Emergent linear structure in
188 large language model representations of true/false datasets. In *Conference on Language*
189 *Modeling (COLM)*, 2024.
- 190 [7] Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu
191 Yao, Chelsea Finn, and Christopher D. Manning. Just ask for calibration: Strategies
192 for eliciting calibrated confidence scores from language models fine-tuned with human
193 feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural*
194 *Language Processing (EMNLP)*, 2023.
- 195 [8] Andy Zou, Long Phan, Sarah Chen, James Campbell, Phillip Guo, Richard Ren, Alexan-
196 der Pan, Xuwang Yin, Mantas Mazeika, Ann-Kathrin Dombrowski, et al. Representation
197 engineering: A top-down approach to AI transparency. *arXiv preprint arXiv:2310.01405*,
198 2023.