

Inductance/ μ H	4.0-4.2
Resistance/ Ω	0.097-0.182
Breakdown Voltage/V	500 (worst case scenario)

Methodology

Inductance and resistance are measured via LCR meter at 100kHz frequency.
Breakdown Voltage:



Kupferlackdraht CUL auf Mini Spule

Enamelled copper wire CUL on mini bobbins

- Isolierlackbasis min. Polyurethan, mod.
Insulating varnish min. Polyurethan, mod.
- Dauerwärmebeständigkeit 155 °C (Kl. F)
Heat resistant 155 °C (Cl. F)
- Verzinnbarkeit >350 °C
Tin-plate >350 °C

Kupferlackdraht nach IEC 60317-20
Grad 1
T_J min. 155 °C
Lötlbar

Enamelled copper wire to IEC 60317-20
Degree 1
T_J min. 155 °C
Solderable

CUL 200

[Datasheet Source](#)

Technical Data for Enamelled Copper Wire by Size acc. to IEC 60317																											
Nominal Diameter	Conductor (Bare Wire)	Enamelled Copper Wire (overall diameter)										Resistance at 20 °C				Stratification acc. to IEC				Breakdown Voltage acc. to IEC **			Length of 1 kg of enamelled wire			Filling Factor number of enamelled wires/cm³	Working Tension
		Grade 1		Grade 2		Grade 3		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C		Resistance at 20 °C			
		max	min	max	min	max	min	max	min	max	min	max	min	max	min	max	min	max	min	max	min	max	min	max	min		
0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	0.095	
0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	0.100	
0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	0.105	

[IEC 60317 Source](#)