

Scalable Learning of Probabilistic Circuits

Renato Lui Geh

THESIS PRESENTED TO THE
INSTITUTE OF MATHEMATICS AND STATISTICS
OF THE UNIVERSITY OF SÃO PAULO
IN PARTIAL FULFILLMENT
OF THE REQUIREMENTS
FOR THE DEGREE OF
MASTER OF SCIENCE

Program: Computer Science

Advisor: Prof. Denis Deratani Mauá, PhD

This work was supported by CNPq grant #133787/2019-2,
CAPES grant #88887.339583/2019-00 and EPECLIN FM-USP.

São Paulo
November 1, 2021

Scalable Learning of Probabilistic Circuits

Renato Lui Geh

This is the original version of the thesis
prepared by candidate Renato Lui Geh, as
submitted to the Examining Committee.

I hereby authorize the total or partial reproduction and publishing of this work for educational ou research purposes, as long as properly cited.

Acknowledgements

Resumo

Renato Lui Geh. **Aprendizado Escalável de Circuitos Probabilísticos**. Dissertação (Mestrado). Instituto de Matemática e Estatística, Universidade de São Paulo, São Paulo, 2021.

Palavras-chave: Circuitos probabilísticos. Aprendizado de máquina. Modelos probabilísticos.

Abstract

Renato Lui Geh. **Scalable Learning of Probabilistic Circuits**. Thesis (Master's). Institute of Mathematics and Statistics, University of São Paulo, São Paulo, 2021.

Keywords: Probabilistic circuits. Machine learning. Probabilistic models.

Nomenclature

List of Symbols

σ Sigmoid function

List of Figures

List of Tables

List of Algorithms

Notation

We use the following notation throughout the work. Random variables are written in upper case (e.g. X , Y) and their values in lower case (e.g. x , y). We identify propositional variables with 0/1-valued random variables, and use them interchangeably. Sets of variables and their joint values are written in boldface (e.g. \mathbf{X} , \mathbf{x}). Given a Boolean formula f , we write $\langle f \rangle$ to denote its semantics, i.e. the Boolean function represented by f . For Boolean formulas f and g , we write $f \equiv g$ if they are logically equivalent, that is, if $\langle f \rangle = \langle g \rangle$; we abuse notation and write $\phi \equiv f$ to indicate that $\phi = \langle f \rangle$ for a Boolean function ϕ .

Contents

1	Introduction	1
1.1	Contributions and Dissertation Outline	3
2	Probabilistic Circuits	5
2.1	Distributions as Computational Graphs	5
2.2	Deciding What to Constraint	8
 Appendices		
A	Appendix	9
A.1	Proofs	9
 Annexes		
 References		 11

Chapter 1

Introduction

When reasoning about the world, rarely can we find a realistic model that perfectly subsumes all of the needed relationships for flawless prediction. As such, the presence of a reliable uncertainty quantifier in intelligent systems is essential in developing performant yet diagnostible agents. This is made explicitly clear in the case of high-risk settings, such as autonomous vehicles or automated power plant systems, where a wrong prediction could cause disastrous consequences. A well known example in the case of the former is obstacle avoidance: while the agent should be capable of accurately identifying obstructions in its way during normal conditions, so should it be able to identify its own lack of confidence in high uncertainty situations like ones brought by environmental factors, such as severe blizzard or heavy rain. In these situations where predictions are highly unreliable, the safest option might be for the agent to first identify its uncertainty, and second to reach out for human help. Other interesting applications of uncertainty quantification include out-of-distribution detection, which in our previous example could be visualized as the agent identifying a human's driving as abnormally irregular (due to inebriation, infirmity, etc.) and appropriately taking control of the vehicle before a potential accident takes place.

One popular approach to quantifying uncertainty is through probability theory. By abstracting the world as a probability distribution with a finite number of observable random variables that encode a possibly incomplete knowledge of the environment, we are, in theory, able to answer a diverse set of complex queries as long as we have access to the (approximate) true data distribution. Practice is far different from theory, however, as most machine learning models either lie within a very limited range in the tractability spectrum in terms of inference (VERGARI, CHOI, PEHARZ, *et al.*, 2020) or are too simplistic for complex real-world problems. Besides, although the majority of recent advances in deep learning claim some probabilistic meaning from the model's output, they are often uncalibrated distributions, a result of focusing on maximizing predictive accuracy at the expense of predictive uncertainty (GUO *et al.*, 2017; OVADIA *et al.*, 2019; CHERNIKOVA *et al.*, 2019), ultimately producing overconfident and peculiar results (SZEGEDY *et al.*, 2013; WEI *et al.*, 2018; SU *et al.*, 2019; CHERNIKOVA *et al.*, 2019). Crucially, mainstream deep models (i.e. standard neural networks) usually optimize a conditional distribution over the to-be-predicted random variables – and are thus often called *discriminative* models – and

do not model the actual joint distribution of the data, limiting inference capabilities and uncertainty estimation.

In contrast, *generative* models seek to extract information from the joint (in varying capacities), and have lately seen a sharp rise in interest within deep learning. Despite this, most popular models do not admit either exact or tractable querying of key inference scenarios. For instance, although Generative Adversarial Networks (GANs) allow for efficient sampling (GOODFELLOW *et al.*, 2014), basic queries such as likelihood or marginals are outside of their capabilities. Similarly, Normalizing Flows (NF) also permit access to efficient sampling, with the added feature of computing likelihoods, but are severely limited by the base distribution when it comes to discrete data (REZENDE and MOHAMED, 2015; PAPAMAKARIOS *et al.*, 2021) albeit recent works on discretizing NFs have shown empirically good results (LIPPE and GAVVES, 2021; ZIEGLER and RUSH, 2019). Variational Auto-Encoders (VAEs) are (under certain conditions) a generalization of NFs (YU, 2020; GRITSENKO *et al.*, 2019) with known extensions for categorical data (ROLFE, 2017; VAHDAT, MACREADY, *et al.*, 2018; VAHDAT, ANDRIYASH, *et al.*, 2018), but only permit access to sampling and an upper-bound on the likelihood, with the latter available only after solving a complex optimization task (KINGMA and WELLING, 2014).

Despite the impressive achievements of the aforementioned generative models on realistically producing samples consistent with evidence, in none of the previous models are complex queries like structured prediction under partial observations, *maximum a posteriori* (MAP), conditional or marginal probabilities tractable. An obvious alternative would be Probabilistic Graphical Models (PGMs), although they too suffer from intractability when dealing with high treewidth networks (R. DECHTER, 1998; KOLLER and FRIEDMAN, 2009), severely limiting expressivity. Instead, we draw our attention to an expressive class of models that subsumes several families of probabilistic models with tractable inference capabilities.

Probabilistic Circuits (PCs) define a superclass of probabilistic models distinctly specified by recursive compositions of distributions through graphical formalisms. Vaguely speaking, PCs are computational graphs akin to neural networks, but whose network structure and computational units abide by special constraints. Within these specific conditions span a wide range of subclasses, each establishing a distinct set of restrictions on their structure in order to enable different segments within the tractability spectrum. As an example, Sum-Product Networks (SPNs, POON and P. DOMINGOS, 2011) are usually loosely defined over a couple of constraints: namely *smoothness* and *decomposability*, which in turn enables likelihood, marginal and conditional computations. Arithmetic Circuits (ACs, DARWICHE, 2003) add *determinism* to the mix, allowing for tractable computation of MAP probabilities. Similarly, Cutset Networks (C Nets, RAHMAN *et al.*, 2014) employ the same constraints as ACs, but accept more expressive distributions as part of their computational units. Probabilistic Sentential Decision Diagrams (PSDDs, KISA *et al.*, 2014), Probabilistic Decision Graphs (PDGs, JAEGER, 2004) and And/Or-Graphs (AOGs, RINA DECHTER and MATEESCU, 2007) all require *smoothness* and *determinism*, but also call for a stronger version of *decomposability*, permitting all queries previously mentioned as well as computation of the Kullback-Leibler divergence and expectation between two circuits (CHOI *et al.*, 2020). Usually, PCs represent the joint distribution of the data, although they are sufficiently expressive for generative *and* discriminative modeling (KHOSRAVI *et al.*, 2019; RASHWAN

et al., 2018; ROOSHENAS and LOWD, 2016; GENS and P. DOMINGOS, 2012; SHAO *et al.*, 2020). In this dissertation though, we shall focus on the generative side of PCs.

While inference is usually straightforward, as we shall see in ??, learning the structure of PCs so that they obey the needed structural restrictions requires either careful handcrafted architectures (POON and P. DOMINGOS, 2011; CHENG *et al.*, 2014; NATH and P. M. DOMINGOS, 2016) or usually involves running costly (in)dependence tests over most (if not all) variables (GENS and P. DOMINGOS, 2013; JAINI, GHOSE, *et al.*, 2018; VERGARI, MAURO, *et al.*, 2015; DI MAURO *et al.*, 2017), which can become prohibitive in higher dimension data. Alternatively, some learning algorithms resort to structure preserving iterative methods to grow a PC that already initially satisfies desired constraints, adding complexity to the underlying distribution at each iteration (LIANG, BEKKER, *et al.*, 2017; DANG *et al.*, 2020). However, these can take several iterations until visible improvement and often take several minutes for each iteration when the circuit is big. Common techniques used in deep learning for generating scalable architectures for neural network also pose a problem, as the nature of the needed structural constraints make for sparse computational graphs. To circumvent these issues, work on scaling PCs to higher dimensions has focused mainly on random architectures, with competitive results (PEHARZ, VERGARI, *et al.*, 2020; MAURO *et al.*, 2021; GEH and Denis Deratani MAUÁ, 2021; PEHARZ, LANG, *et al.*, 2020). Apart from the scalability side of random structure generation, usual structure learning algorithms often require grid-search for hyperparameter tuning to achieve top quality performance, which is usually not the case for random algorithms. For the usual data scientist or machine learning practitioner, hyperparameter tuning can become exhaustive, especially if the goal is to analyze and infer from large data, and not to achieve top tier performance on benchmark datasets.

In this dissertation, we propose two scalable structural learning algorithms for probabilistic circuits that are especially suited for large data and fast deployment. They both take advantage of random network generation to quickly construct PCs with little to no need for hyperparameters. The first is effective for constructing PCs from binary data with a highly constrained structure, and thus appropriate when complex querying is needed. The second builds less constrained random PCs, but supports both discrete and continuous data.

1.1 Contributions and Dissertation Outline

We organize this dissertation as follows. We begin [Chapter 2](#) by formally defining probabilistic circuits, conducting a review of some of the structural constraints that we might impose on PCs, as well as what we may gain from them in terms of tractability. We then list existing formalisms that may be viewed as instances of PCs, and what their structure entail in terms of inference power. In [Chapter 3](#), we address existing PC structure learning algorithms, and which guarantees in terms of tractability each give. We cover the two new structure learners in [Chapter 4](#), providing empirical results on their performance. The final chapter is dedicated to summarizing our research contributions and pointing to potential future work in learning PCs.

Our contributions in this dissertation address the following research topics.

Scalably learning PCs directly from background knowledge

In [GEH and Denis Deratani MAUÁ \(2021\)](#), we provide a learning algorithm for PSDDs that learns a PC directly from background knowledge in the form of logical constraints. The algorithm samples a structure from a distribution of possible PSDDs that are weakly consistent with the logical formula. How weak consistency is depends on a parameter that trades permission of false statements as non zero probability events with circuit complexity. We provide the algorithm and empirical results in Section 4.??.

Using ensembles to strengthen consistency

The PC sampler given by [GEH and Denis Deratani MAUÁ \(2021\)](#) produces competitive probabilistic models (in terms of likelihood), albeit weak logical models in the sense that it possibly assigns non-zero probability to false variable assignments – as we discuss in Section 4.??, it never assigns zero probability to true statements. By producing many weak models, we not only gain in terms of data fitness, but also consistency: if any one component in the ensemble returns an assignment to be impossible, the whole model should return false.

Random projections to efficiently learn PCs

Usual methods often employ clustering algorithms for constructing convex combinations of computational units. These can take many iterations to converge or require space quadratic in the number of data points. Instead, in Section 4.?? we present linear alternatives based on random projections ([FREUND *et al.*, 2008](#); [DASGUPTA and FREUND, 2008](#)).

Chapter 2

Probabilistic Circuits

As we briefly mentioned in the last chapter, Probabilistic Circuits (PCs) are conceptualized as computational graphs under special conditions. In this chapter, [Section 2.1](#) to be more precise, we formally define PCs and give an intuition on their syntax, viewing other probabilistic models through the lenses of the PC framework. In [Section 2.2](#), we describe the special structural constraints that give PCs their inference power over other generative models and state which queries (as far as we know) are enabled from each constraint.


2.1 Distributions as Computational Graphs

Probabilistic circuits are directed acyclic graphs usually recursively defined in terms of their computational units. In its simplest form, a PC is a single unit corresponding to some tractable distribution. These can range from univariate or multivariate exponential distributions to complex non-parametric models, and are the foundational units of PCs. We shall refer to these computational units as *leaf nodes*, as no edges come out of them. To simplify notation, in this dissertation, unless specified, leaf nodes will denote univariate distributions. Let L_p a PC leaf node and denote p as its inherent probability distribution. By definition, any query $f : \mathcal{X} \rightarrow \mathcal{Y}$ which is tractable on p is tractable on L_p . We shall denote $L_p(X) = p(X)$, and often omit p when its explicit form is not needed.

Example 2.1.1: Gaussians as probabilistic circuits

Let L_p a leaf node and $p(X) = \mathcal{N}(X; \mu, \sigma^2)$ a univariate Gaussian distribution. Computing any query on L_p is straightforward: any query on L_p directly translates to p . As an example, suppose $\mu = 0$ and $\sigma^2 = 1$ and we wish to compute $L_p(x = 0.8)$. The probability of this leaf shall then be

$$L_p(x = 0.8) = \mathcal{N}(x = 0.8; \mu = 0, \sigma^2 = 1) = 0.29.$$



Evidently, a single leaf node lacks the expressivity for modeling complex models, otherwise we would have just used the leaf distribution as a standalone model. The expressiveness of PCs comes from recursively combining distributions into complex functions. This can be done through computational units that either compute convex combinations or products of their children. Let us first look at convex combinations, known in the literature as *sum nodes*.


Let S be a PC sum node, and denote by $\text{Ch}(S)$ the children nodes of S . For every edge \overrightarrow{SC} coming out of S and going to C , we attribute a weight $w_{S,C} > 0$, such that $\sum_{C \in \text{Ch}(S)} w_{S,C} = 1$. A sum node semantically defines a mixture model over its children, essentially acting as a latent variable over the component distributions (PEHARZ, GENS, *et al.*, 2016). Its value is the weighted sum of its children $p_S(X = \mathbf{x}) = \sum_{C \in \text{Ch}(S)} w_{S,C} \cdot p_C(X = \mathbf{x})$. To simplify notation, we shall use $N(X = \mathbf{x})$ as an alias for $p_N(X = \mathbf{x})$, that is, the probability function given by the N 's induced distribution.

Example 2.1.2: Gaussian mixture models as probabilistic circuits

A Gaussian Mixture Model (GMM) defines a mixture over Gaussian components. Say we wish to compute the probability of $X = x$ for a GMM \mathcal{G} with three components $\mathcal{N}_1(\mu_1 = 1, \sigma_1^2 = 0.65)$, $\mathcal{N}_2(\mu_2 = 2.5, \sigma_2^2 = 0.85)$ and $\mathcal{N}_3(\mu_3 = 4, \sigma_3^2 = 0.6)$, and suppose we have weights set to $\phi = (0.4, 0.25, 0.35)$. Computing the probability of G amounts to the weighted summation

$$\mathcal{G}(X = x) = 0.4 \cdot \mathcal{N}_1(x; \mu_1, \sigma_1^2) + 0.25 \cdot \mathcal{N}_2(x; \mu_2, \sigma_2^2) + 0.35 \cdot \mathcal{N}_3(x; \mu_3, \sigma_3^2),$$

which is equivalent to a computational graph (i.e. a PC) with a sum node whose weights are set to ϕ and children are the components of the mixture. The figure on the right shows \mathcal{G} (top) and its corresponding PC (bottom). Given $x = 1.5$ (in blue), leaf nodes are computed following the inference flow (gray edges) up to the root sum node (in red), where a weighted summation is computed to output the probability (in green).



Before we address products as computational units in PCs, we first need to discuss the concept of scope of a PC node. Denote by $\text{Sc}(N)$ the set of all variables that appear in N . We inductively compute the scope of circuit by a bottom-up approach: the scope of a leaf node L_p is the set of variables that appear in p , and the scope of any other node is the union of all of its children's scopes. The notion of a node's scope is essential to the structural constraints seen in Section 2.2.

So far, the only nonlinearities present in PCs come from the internal computations of leaf nodes. In fact, a PC that only contains sum and leaf nodes can always be reduced

to a sum node rooted PC with a single layer, i.e. a mixture model (see [Theorem A.1.1](#)). Adding *product nodes* as another form of nonlinearity increases expressivity sufficiently for PCs to be capable of representing any (discrete) probability distribution. are products of their childrens' distribution: if P is a PC product node, then its value $P(\mathbf{X} = \mathbf{x}) = \prod_{C \in \text{Ch}(P)} C(\mathbf{X} = \mathbf{x})$. Semantically, product nodes are factorizations of its children, indicating an independence relationship between variables from different children as long as

Remark 2.1.1: On operators and tractability

Throughout this work we consider only products and convex combinations (apart from the implicit operations contained within leaf nodes) as potential computational units. The question of whether any other operator could be used to gain expressivity without loss of tractability is without a doubt an interesting research question, and one that is actively being pursued. However, this is certainly out of the scope of this dissertation, and so we restrict discussion on this topic and only give a brief comment on operator tractability here, pointing to existing literature in this area of research.

[A. FRIESEN and P. DOMINGOS \(2016\)](#) formalize the notion of replacing sums and products in PCs with any pair of operators in a commutative semiring, giving results on the conditions for marginalization to be tractable. They provide examples of common semirings and to which known formalisms they correspond to. One such example are PCs under the Boolean semiring $(\{0, 1\}, \vee, \wedge, 0, 1)$ for logical inference, which are equivalent to Negation Normal Form (NNF, [BARWISE, 1982](#)) and constitute an instance of Logic Circuits (LCs), of which Sentential Decision Diagrams (SDDs, [DARWICHE, 2011](#)) and Binary Decision Diagrams (BDDs, [AKERS, 1978](#)) are a part of. Another less common semiring in PCs is the real min-sum semiring $(\mathbb{R}_\infty, \min, +, \infty, 0)$ for nonconvex optimization ([A. L. FRIESEN and P. DOMINGOS, 2015](#)).

Recently, [VERGARI, CHOI, LIU, et al. \(2021\)](#) extensively covered tractability conditions and complexity bounds for convex combinations, products, exp (and more generally powers in both naturals and reals), quotients and logarithms, even giving results for complex information-theoretic queries, such as entropies and divergences. Notably, they analyze whether structural constraints (and thus, in a sense, tractability) are preserved.

Up to now, we have only considered summations as nonnegative weighted sums. Indeed, in most literature the sum node is defined as a convex combination. However, negative weights have appeared in Logistic Circuits ([LIANG and VAN DEN BROECK, 2019](#)) for discriminative modeling; and in Probabilistic Generating Circuits ([ZHANG et al., 2021](#)), a class of tractable probabilistic models that subsume PCs. [Denis D. MAUÁ et al. \(2017\)](#) extend (nonnegative) weights in sum nodes with probability intervals, effectively inducing a credal set ([COZMAN, 2000](#)) for measuring imprecision.

Other works have extended PCs with quotients ([SHARIR and SHASHUA, 2018](#)), transformations ([PEVNÝ et al., 2020](#)), max ([MELIBARI et al., 2016](#)), and einsum ([PEHARZ, LANG, et al., 2020](#)) operators.

2.2 Deciding What to Constraint

referenced structural constraints in passing

Appendix A

Appendix

A.1 Proofs

Theorem A.1.1. *Let C a probabilistic circuit whose first n layers are composed solely of sum nodes. Call N the set of all nodes in layer $n + 1$. C is equivalent to a PC C' whose root is a sum node with N as children.*

Proof. We adapt a similar proof due to [JAINI, POUPART, et al. \(2018\)](#). Every sum node is of the form

$$S(\mathbf{x}) = \sum_{C \in \text{Ch}(S)} w_{S,C} \cdot C(\mathbf{x}).$$

Particularly, every child C in a sum node in layer $1 \leq i \leq n - 1$, is a sum node, and so for the first layer we have that

$$\begin{aligned} S(\mathbf{x}) &= \sum_{C_1 \in \text{Ch}(S)} w_{S,C_1} \sum_{C_2 \in \text{Ch}(C_1)} w_{C_1,C_2} C_2(\mathbf{x}) \\ &= \sum_{C_1 \in \text{Ch}(S)} \sum_{C_2 \in \text{Ch}(C_1)} w_{S,C_1} w_{C_1,C_2} C_2(\mathbf{x}). \end{aligned}$$

Define a one-to-one mapping that takes a tuple (i, j) where $i \in$

□

References

- [AKERS 1978] S. B. AKERS. “Binary decision diagrams”. In: *IEEE Transactions on Computers* 27.6 (1978), pp. 509–516 (cit. on p. 7).
- [BARWISE 1982] Jon BARWISE. *Handbook of Mathematical Logic*. 1982 (cit. on p. 7).
- [CHENG *et al.* 2014] Wei-Chen CHENG, Stanley KOK, Hoai Vu PHAM, Hai Leong CHIEU, and Kian Ming A. CHAI. “Language modeling with sum-product networks”. In: *Fifteenth Annual Conference of the International Speech Communication Association*. 2014 (cit. on p. 3).
- [CHERNIKOVA *et al.* 2019] A. CHERNIKOVA, A. OPREA, C. NITA-ROTARU, and B. KIM. “Are self-driving cars secure? evasion attacks against deep neural networks for steering angle prediction”. In: *2019 IEEE Security and Privacy Workshops*. 2019, pp. 132–137 (cit. on p. 1).
- [CHOI *et al.* 2020] YooJung CHOI, Antonio VERGARI, and Guy Van den BROECK. “Probabilistic circuits: a unifying framework for tractable probabilistic models”. In: (2020). In preparation (cit. on p. 2).
- [COZMAN 2000] Fabio G. COZMAN. “Credal networks”. In: *Artificial Intelligence* 120.2 (2000), pp. 199–233. ISSN: 0004-3702. DOI: [https://doi.org/10.1016/S0004-3702\(00\)00029-1](https://doi.org/10.1016/S0004-3702(00)00029-1). URL: <https://www.sciencedirect.com/science/article/pii/S0004370200000291> (cit. on p. 7).
- [DANG *et al.* 2020] Meihua DANG, Antonio VERGARI, and Guy Van den BROECK. “Strudel: learning structured-decomposable probabilistic circuits”. In: *Proceedings of the 10th International Conference on Probabilistic Graphical Models*. PGM. 2020 (cit. on p. 3).
- [DARWICHE 2003] Adnan DARWICHE. “A differential approach to inference in bayesian networks”. In: *Journal of the ACM* 50.3 (2003), pp. 280–305 (cit. on p. 2).
- [DARWICHE 2011] Adnan DARWICHE. “SDD: a new canonical representation of propositional knowledge bases”. In: *Proceedings of the Twenty-Second International Joint Conference on Artificial Intelligence*. 2011, pp. 819–826 (cit. on p. 7).

- [DASGUPTA and FREUND 2008] Sanjoy DASGUPTA and Yoav FREUND. “Random projection trees and low dimensional manifolds”. In: *Proceedings of the fortieth annual ACM symposium on Theory of computing*. STOC. 2008, pp. 537–546 (cit. on p. 4).
- [R. DECHTER 1998] R. DECHTER. “Bucket elimination: a unifying framework for probabilistic inference”. In: *Learning in Graphical Models*. Ed. by Michael I. JORDAN. Dordrecht: Springer Netherlands, 1998, pp. 75–104. ISBN: 978-94-011-5014-9. DOI: [10.1007/978-94-011-5014-9_4](https://doi.org/10.1007/978-94-011-5014-9_4). URL: https://doi.org/10.1007/978-94-011-5014-9_4 (cit. on p. 2).
- [Rina DECHTER and MATEESCU 2007] Rina DECHTER and Robert MATEESCU. “And/or search spaces for graphical models”. In: *Artificial Intelligence* 171.2 (2007), pp. 73–106. ISSN: 0004-3702. DOI: <https://doi.org/10.1016/j.artint.2006.11.003>. URL: <https://www.sciencedirect.com/science/article/pii/S000437020600138X> (cit. on p. 2).
- [DI MAURO *et al.* 2017] Nicola DI MAURO, Floriana ESPOSITO, Fabrizio G. VENTOLA, and Antonio VERGARI. “Alternative variable splitting methods to learn sum-product networks”. In: *AI*IA 2017 Advances in Artificial Intelligence*. Ed. by Floriana Esposito, Roberto BASILI, Stefano FERILLI, and Francesca A. LISI. Cham: Springer International Publishing, 2017, pp. 334–346. ISBN: 978-3-319-70169-1 (cit. on p. 3).
- [FREUND *et al.* 2008] Yoav FREUND, Sanjoy DASGUPTA, Mayank KABRA, and Nakul VERMA. “Learning the structure of manifolds using random projections”. In: *Advances in Neural Information Processing Systems*. Vol. 20. NeurIPS. 2008 (cit. on p. 4).
- [A. FRIESEN and P. DOMINGOS 2016] Abram FRIESEN and Pedro DOMINGOS. “The sum-product theorem: a foundation for learning tractable models”. In: *Proceedings of The 33rd International Conference on Machine Learning*. Ed. by Maria Florina BALCAN and Kilian Q. WEINBERGER. Vol. 48. Proceedings of Machine Learning Research. New York, New York, USA: PMLR, June 2016, pp. 1909–1918. URL: <https://proceedings.mlr.press/v48/friesen16.html> (cit. on p. 7).
- [A. L. FRIESEN and P. DOMINGOS 2015] Abram L. FRIESEN and Pedro DOMINGOS. “Recursive decomposition for nonconvex optimization”. In: *Proceedings of the 24th International Conference on Artificial Intelligence*. IJCAI’15. Buenos Aires, Argentina: AAAI Press, 2015, pp. 253–259. ISBN: 9781577357384 (cit. on p. 7).
- [GEH and Denis Deratani MAUÁ 2021] Renato Lui GEH and Denis Deratani MAUÁ. “Learning probabilistic sentential decision diagrams under logic constraints by sampling and averaging”. In: *Proceedings of The 37th Uncertainty in Artificial Intelligence Conference*. Proceedings of Machine Learning Research. PMLR, 2021 (cit. on pp. 3, 4).
- [GENS and P. DOMINGOS 2012] Robert GENS and Pedro DOMINGOS. “Discriminative learning of sum-product networks”. In: *Advances in Neural Information Processing Systems* 25. NIPS, 2012, pp. 3239–3247 (cit. on p. 3).

REFERENCES

- [GENS and P. DOMINGOS 2013] Robert GENS and Pedro DOMINGOS. “Learning the structure of sum-product networks”. In: *Proceedings of the 30th International Conference on Machine Learning*. ICML. 2013, pp. 873–880 (cit. on p. 3).
- [GOODFELLOW *et al.* 2014] Ian GOODFELLOW *et al.* “Generative adversarial nets”. In: *Advances in Neural Information Processing Systems 27*. Ed. by Z. GHAHRAMANI, M. WELING, C. CORTES, N. D. LAWRENCE, and K. Q. WEINBERGER. Curran Associates, Inc., 2014, pp. 2672–2680. URL: <http://papers.nips.cc/paper/5423-generative-adversarial-nets.pdf> (cit. on p. 2).
- [GRITSENKO *et al.* 2019] Alexey A. GRITSENKO, Jasper SNOEK, and Tim SALIMANS. “On the relationship between normalising flows and variational- and denoising autoencoders”. In: *Deep Generative Models for Highly Structured Data, ICLR 2019 Workshop, New Orleans, Louisiana, United States, May 6, 2019*. OpenReview.net, 2019. URL: https://openreview.net/forum?id=HkIKEUY%5C_E (cit. on p. 2).
- [GUO *et al.* 2017] Chuan GUO, Geoff PLEISS, Yu SUN, and Kilian Q WEINBERGER. “On calibration of modern neural networks”. In: *Proceedings of the 34th International Conference on Machine Learning-Volume 70*. JMLR. org. 2017, pp. 1321–1330 (cit. on p. 1).
- [JAEGER 2004] Manfred JAEGER. “Probabilistic decision graphs-combining verification and ai techniques for probabilistic inference”. In: *Int. J. Uncertain. Fuzziness Knowl.-Based Syst.* 12.1 supp (Jan. 2004), pp. 19–42. ISSN: 0218-4885. DOI: [10.1142/S0218488504002564](https://doi.org/10.1142/S0218488504002564). URL: <https://doi.org/10.1142/S0218488504002564> (cit. on p. 2).
- [JAINI, GHOSE, *et al.* 2018] Priyank JAINI, Amur GHOSE, and Pascal POUPART. “Prometheus: directly learning acyclic directed graph structures for sum-product networks”. In: *International Conference on Probabilistic Graphical Models*. PGM. 2018, pp. 181–192 (cit. on p. 3).
- [JAINI, POUPART, *et al.* 2018] Priyank JAINI, Pascal POUPART, and Yaoliang YU. “Deep homogeneous mixture models: representation, separation, and approximation”. In: *Advances in Neural Information Processing Systems*. Ed. by S. BENGIO *et al.* Vol. 31. Curran Associates, Inc., 2018. URL: <https://proceedings.neurips.cc/paper/2018/file/c5f5c23be1b71adb51ea9dc8e9d444a8-Paper.pdf> (cit. on p. 9).
- [KHOSRAVI *et al.* 2019] Pasha KHOSRAVI, Yitao LIANG, YooJung CHOI, and Guy VAN DEN BROECK. “What to expect of classifiers? reasoning about logistic regression with missing features”. In: *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*. International Joint Conferences on Artificial Intelligence Organization, July 2019, pp. 2716–2724. DOI: [10.24963/ijcai.2019/377](https://doi.org/10.24963/ijcai.2019/377). URL: <https://doi.org/10.24963/ijcai.2019/377> (cit. on p. 2).

- [KINGMA and WELLING 2014] Diederik P. KINGMA and Max WELLING. “Auto-encoding variational bayes”. In: *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*. Ed. by Yoshua BENGIO and Yann LECUN. 2014. URL: <http://arxiv.org/abs/1312.6114> (cit. on p. 2).
- [KISA *et al.* 2014] Doga KISA, Guy Van den BROECK, Arthur CHOI, and Adnan DARWICHE. “Probabilistic sentential decision diagrams”. In: *Knowledge Representation and Reasoning Conference (2014)* (cit. on p. 2).
- [KOLLER and FRIEDMAN 2009] Daphne KOLLER and Nir FRIEDMAN. *Probabilistic Graphical Models: Principles and Techniques - Adaptive Computation and Machine Learning*. The MIT Press, 2009. ISBN: 0262013193 (cit. on p. 2).
- [LIANG, BEKKER, *et al.* 2017] Yitao LIANG, Jessa BEKKER, and Guy Van den BROECK. “Learning the structure of probabilistic sentential decision diagrams”. In: *Proceedings of the Thirty-Third Conference on Uncertainty in Artificial Intelligence*. 2017 (cit. on p. 3).
- [LIANG and VAN DEN BROECK 2019] Yitao LIANG and Guy VAN DEN BROECK. “Learning logistic circuits”. In: *Proceedings of the AAAI Conference on Artificial Intelligence* 33.01 (July 2019), pp. 4277–4286. DOI: [10.1609/aaai.v33i01.33014277](https://doi.org/10.1609/aaai.v33i01.33014277). URL: <https://ojs.aaai.org/index.php/AAAI/article/view/4336> (cit. on p. 7).
- [LIPPE and GAVVES 2021] Phillip LIPPE and Efstratios GAVVES. “Categorical normalizing flows via continuous transformations”. In: *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. URL: <https://openreview.net/forum?id=-GLNZeVDuik> (cit. on p. 2).
- [DENIS D. MAUÁ *et al.* 2017] Denis D. MAUÁ, Fabio G. COZMAN, Diarmaid CONATY, and Cassio P. CAMPOS. “Credal sum-product networks”. In: *Proceedings of the Tenth International Symposium on Imprecise Probability: Theories and Applications*. Ed. by Alessandro ANTONUCCI, Giorgio CORANI, Inés COUSO, and Sébastien DESTERCKE. Vol. 62. Proceedings of Machine Learning Research. PMLR, Oct. 2017, pp. 205–216. URL: <https://proceedings.mlr.press/v62/mau%C3%A117a.html> (cit. on p. 7).
- [MAURO *et al.* 2021] Nicola Di MAURO, Gennaro GALA, Marco IANNOTTA, and Teresa M. A. BASILE. “Random probabilistic circuits”. In: *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*. 2021 (cit. on p. 3).
- [MELIBARI *et al.* 2016] Mazen MELIBARI, Pascal POUPART, and Prashant DOSHI. “Sum-product-max networks for tractable decision making”. In: *Proceedings of the Twenty-Fifth International Joint Conference on Artificial Intelligence. IJCAI’16*. New York, New York, USA: AAAI Press, 2016, pp. 1846–1852. ISBN: 9781577357704 (cit. on p. 7).

REFERENCES

- [NATH and P. M. DOMINGOS 2016] Aniruddh NATH and Pedro M DOMINGOS. “Learning tractable probabilistic models for fault localization”. In: *Thirtieth AAAI Conference on Artificial Intelligence*. 2016 (cit. on p. 3).
- [OVADIA *et al.* 2019] Yaniv OVADIA *et al.* “Can you trust your model’s uncertainty? evaluating predictive uncertainty under dataset shift”. In: *Proceedings of the 33rd International Conference on Neural Information Processing Systems*. 2019 (cit. on p. 1).
- [PAPAMAKARIOS *et al.* 2021] George PAPAMAKARIOS, Eric NALISNICK, Danilo Jimenez REZENDE, Shakir MOHAMED, and Balaji LAKSHMINARAYANAN. “Normalizing flows for probabilistic modeling and inference”. In: *Journal of Machine Learning Research* 22.57 (2021), pp. 1–64. URL: <http://jmlr.org/papers/v22/19-1028.html> (cit. on p. 2).
- [PEHARZ, GENS, *et al.* 2016] Robert PEHARZ, Robert GENS, Franz PERNKOPF, and Pedro DOMINGOS. “On the latent variable interpretation in sum-product networks”. In: *IEEE transactions on pattern analysis and machine intelligence* 39.10 (2016), pp. 2030–2044 (cit. on p. 6).
- [PEHARZ, LANG, *et al.* 2020] Robert PEHARZ, Steven LANG, *et al.* “Einsum networks: fast and scalable learning of tractable probabilistic circuits”. In: *Proceedings of the 37th International Conference on Machine Learning*. Ed. by Hal Daumé III and Aarti SINGH. Vol. 119. Proceedings of Machine Learning Research. PMLR, July 2020, pp. 7563–7574. URL: <https://proceedings.mlr.press/v119/peharz20a.html> (cit. on pp. 3, 7).
- [PEHARZ, VERGARI, *et al.* 2020] Robert PEHARZ, Antonio VERGARI, *et al.* “Random sum-product networks: a simple and effective approach to probabilistic deep learning”. In: *Proceedings of The 35th Uncertainty in Artificial Intelligence Conference*. Ed. by Ryan P. ADAMS and Vibhav GOGATE. Vol. 115. Proceedings of Machine Learning Research. PMLR, July 2020, pp. 334–344. URL: <https://proceedings.mlr.press/v115/peharz20a.html> (cit. on p. 3).
- [PEVNÝ *et al.* 2020] Tomáš PEVNÝ, Václav SMÍDL, Martin TRAPP, Ondřej POLÁČEK, and Tomáš OBERHUBER. “Sum-product-transform networks: exploiting symmetries using invertible transformations”. In: *Proceedings of the 10th International Conference on Probabilistic Graphical Models*. Ed. by Manfred JAEGER and Thomas Dyhre NIELSEN. Vol. 138. Proceedings of Machine Learning Research. PMLR, Sept. 2020, pp. 341–352. URL: <https://proceedings.mlr.press/v138/pevny20a.html> (cit. on p. 7).
- [POON and P. DOMINGOS 2011] Hoifung POON and Pedro DOMINGOS. “Sum-product networks: a new deep architecture”. In: *Proceedings of the Twenty-Seventh Conference on Uncertainty in Artificial Intelligence*. 2011, pp. 337–346 (cit. on pp. 2, 3).

- [RAHMAN *et al.* 2014] Tahrima RAHMAN, Prasanna KOTHALKAR, and Vibhav GOGATE. “Cutset networks: a simple, tractable, and scalable approach for improving the accuracy of chow-liu trees”. In: *Proceedings of the 2014th European Conference on Machine Learning and Knowledge Discovery in Databases*. 2014, pp. 630–645 (cit. on p. 2).
- [RASHWAN *et al.* 2018] Abdullah RASHWAN, Pascal POUPART, and Chen ZHITANG. “Discriminative training of sum-product networks by extended baum-welch”. In: *Proceedings of the Ninth International Conference on Probabilistic Graphical Models*. Vol. 72. Proceedings of Machine Learning Research. 2018, pp. 356–367 (cit. on p. 2).
- [REZENDE and MOHAMED 2015] Danilo REZENDE and Shakir MOHAMED. “Variational inference with normalizing flows”. In: *Proceedings of the 32nd International Conference on Machine Learning*. Ed. by Francis BACH and David BLEI. Vol. 37. Proceedings of Machine Learning Research. Lille, France: PMLR, July 2015, pp. 1530–1538. URL: <https://proceedings.mlr.press/v37/rezende15.html> (cit. on p. 2).
- [ROLFE 2017] Jason Tyler ROLFE. “Discrete variational autoencoders”. In: *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net, 2017. URL: <https://openreview.net/forum?id=ryMxXPfex> (cit. on p. 2).
- [ROOSHENAS and LOWD 2016] Amirmohammad ROOSHENAS and Daniel LOWD. “Discriminative structure learning of arithmetic circuits”. In: *Proceedings of the 19th International Conference on Artificial Intelligence and Statistics*. Ed. by Arthur GRETTON and Christian C. ROBERT. Vol. 51. Proceedings of Machine Learning Research. Cadiz, Spain: PMLR, Sept. 2016, pp. 1506–1514. URL: <https://proceedings.mlr.press/v51/rooshenas16.html> (cit. on p. 3).
- [SHAO *et al.* 2020] Xiaoting SHAO *et al.* “Conditional sum-product networks: imposing structure on deep probabilistic architectures”. In: *Proceedings of the 10th International Conference on Probabilistic Graphical Models*. Ed. by Manfred JAEGER and Thomas Dyhre NIELSEN. Vol. 138. Proceedings of Machine Learning Research. PMLR, Sept. 2020, pp. 401–412. URL: <https://proceedings.mlr.press/v138/shao20a.html> (cit. on p. 3).
- [SHARIR and SHASHUA 2018] Or SHARIR and Amnon SHASHUA. “Sum-product-quotient networks”. In: *Proceedings of the Twenty-First International Conference on Artificial Intelligence and Statistics*. Ed. by Amos STORKEY and Fernando PEREZ-CRUZ. Vol. 84. Proceedings of Machine Learning Research. PMLR, Sept. 2018, pp. 529–537. URL: <https://proceedings.mlr.press/v84/sharir18a.html> (cit. on p. 7).
- [SU *et al.* 2019] Jiawei SU, Danilo Vasconcellos VARGAS, and Kouichi SAKURAI. “One pixel attack for fooling deep neural networks”. In: *IEEE Transactions on Evolutionary Computation* 23.5 (2019), pp. 828–841 (cit. on p. 1).

REFERENCES

- [SZEGEDY *et al.* 2013] Christian SZEGEDY *et al.* “Intriguing properties of neural networks”. In: *arXiv preprint arXiv:1312.6199* (2013) (cit. on p. 1).
- [VAHDAT, ANDRIYASH, *et al.* 2018] Arash VAHDAT, Evgeny ANDRIYASH, and William MACREADY. “Dvae#: discrete variational autoencoders with relaxed boltzmann priors”. In: *Advances in Neural Information Processing Systems*. Ed. by S. BENGIO *et al.* Vol. 31. Curran Associates, Inc., 2018. URL: <https://proceedings.neurips.cc/paper/2018/file/9f53d83ec0691550f7d2507d57f4f5a2-Paper.pdf> (cit. on p. 2).
- [VAHDAT, MACREADY, *et al.* 2018] Arash VAHDAT, William G. MACREADY, Zhengbing BIAN, Amir KHOSHAMAN, and Evgeny ANDRIYASH. “DVAE++: discrete variational autoencoders with overlapping transformations”. In: *Proceedings of the 35th International Conference on Machine Learning, ICML 2018, Stockholmsmässan, Stockholm, Sweden, July 10-15, 2018*. Ed. by Jennifer G. DY and Andreas KRAUSE. Vol. 80. Proceedings of Machine Learning Research. PMLR, 2018, pp. 5042–5051. URL: <http://proceedings.mlr.press/v80/vahdat18a.html> (cit. on p. 2).
- [VERGARI, CHOI, LIU, *et al.* 2021] Antonio VERGARI, YooJung CHOI, Anji LIU, Stefano TESO, and Guy Van den BROECK. “A compositional atlas of tractable circuit operations: from simple transformations to complex information-theoretic queries”. In: *CoRR abs/2102.06137* (2021). arXiv: [2102.06137](https://arxiv.org/abs/2102.06137) (cit. on p. 7).
- [VERGARI, CHOI, PEHARZ, *et al.* 2020] Antonio VERGARI, YooJung CHOI, Robert PEHARZ, and Guy Van den BROECK. *Probabilistic Circuits: Representations, Inference, Learning and Applications*. AAAI Tutorial. 2020 (cit. on p. 1).
- [VERGARI, MAURO, *et al.* 2015] Antonio VERGARI, Nicola Di MAURO, and Floriana ESPOSITO. “Simplifying, regularizing and strengthening sum-product network structure learning”. In: *ECML/PKDD*. 2015 (cit. on p. 3).
- [WEI *et al.* 2018] Wenqi WEI *et al.* “Adversarial examples in deep learning: characterization and divergence”. In: *arXiv preprint arXiv:1807.00051* (2018) (cit. on p. 1).
- [YU 2020] Ronald YU. *A Tutorial on VAEs: From Bayes’ Rule to Lossless Compression*. 2020. arXiv: [2006.10273](https://arxiv.org/abs/2006.10273) [cs.LG] (cit. on p. 2).
- [ZHANG *et al.* 2021] Honghua ZHANG, Brendan JUBA, and Guy VAN DEN BROECK. “Probabilistic generating circuits”. In: *Proceedings of the 38th International Conference on Machine Learning*. Ed. by Marina MEILA and Tong ZHANG. Vol. 139. Proceedings of Machine Learning Research. PMLR, July 2021, pp. 12447–12457. URL: <https://proceedings.mlr.press/v139/zhang21i.html> (cit. on p. 7).
- [ZIEGLER and RUSH 2019] Zachary M. ZIEGLER and Alexander M. RUSH. “Latent normalizing flows for discrete sequences”. In: *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*. Ed. by Kamalika CHAUDHURI and Ruslan SALAKHUTDINOV. Vol. 97. Proceedings of Machine Learning Research. PMLR, 2019, pp. 7673–7682. URL: <http://proceedings.mlr.press/v97/ziegler19a.html> (cit. on p. 2).

