

# End-To-End Imitation Learning of Lane Following Policies Using Sum-Product Networks

Renato Lui Geh    Denis Deratani Mauá

Institute of Mathematics and Statistics  
University of São Paulo

ENIAC 2019

# Sum-product networks

Sum-product networks (SPNs) are deep tractable density estimators with a neural network-like structure subject to only sums and products as activation functions.


## Definition 1 (Sum-product network).

A sum-product network (SPN) is a DAG where each node  $n$  is either:

- ① A tractable univariate probability distribution;
- ② A product of SPNs:  $v_n = \prod_{j \in \text{Ch}(n)} v_j$ ; or
- ③ A weighted sum of SPNs:  $v_n = \sum_{j \in \text{Ch}(n)} w_{n,j} v_j$ .

Where  $v_n$  is the value of node  $n$ ,  $\text{Ch}(n)$  its set of children and  $w_{n,j}$  the weight of edge  $n \rightarrow j$ .

## Example



Where each leaves are binomial distributions over each RV  $X_i$ .

# The task


Given a track, bot must autonomously complete the whole course without going off road by making use of a single frontal camera.



Inspired by Moraes and Salvatore 2018, which was itself inspired by Bojarski et al. 2016.

# Dataset

Dataset used: Moraes and Salvatore 2018



Lane tracking dataset with  $80 \times 45$  RGB images. Each labeled with either UP, LEFT or RIGHT.


# Self-driving as image classification



LEFT



UP



RIGHT



Training track in Moraes and Salvatore 2018.

# Berry

## Raspberry Pi 3 Model B — Berry

CPU: Quad Core 1.2GHz Broadcom BCM2837 64bit ARMv7

Memory: 1GB RAM

Storage: 16GB SSD



# Brick

## Lego Mindstorms NXT v2 — Brick

CPU: Atmel AT91SAM7S256 48MHz 32bit ARMv4

Memory: 64KB RAM

Storage: 256KB Flash



# Robot



Message passing through USB cable.

# Modelling

Every pixel  $X_i$  is a variable in the distribution represented by the SPN, i.e. no additional feature extraction, end-to-end.

Two architectures:

**GD:** LearnSPN with  $k$ -means and  $G$ -test

**DV:** Clustering on Variables

Three weight setups:

**g:** Generative gradient descent

**d:** Discriminative gradient descent

**s:** Proportional weights for GD, random weights for DV

# Accuracy

Accuracy (%)	DV+g	DV+d	DV+s	GD+g	GD+d	GD+s
$B$	78.8	78.8	78.8	82.8	83.8	85.0
$Q_2$	78.6	78.0	78.0	78.6	80.4	79.4
$Q_2 + E$	76.6	76.6	76.8	79.6	82.8	81.8
$Q_3$	77.4	77.4	77.4	77.6	80.2	79.8
$Q_3 + E$	70.4	76.6	76.6	79.2	81.2	77.4
$Q_4$	78.2	78.4	78.2	76.0	<b>78.2</b>	76.4
$Q_4 + E$	76.6	76.6	76.8	76.0	74.6	80.6
$Q_5$	77.8	78.4	78.4	77.6	74.0	73.8
$Q_5 + E$	76.6	76.6	76.6	72.0	72.8	72.0
$Q_6$	77.4	78.4	78.4	75.2	<b>74.4</b>	72.0
$Q_6 + E$	76.0	76.4	76.4	73.0	75.0	73.6
$Q_7$	78.2	78.4	78.4	62.8	72.2	71.4
$Q_7 + E$	76.2	76.4	76.4	70.6	71.4	71.6
$\emptyset$	78.0	78.4	78.4	62.4	<b>62.4</b>	62.4
$E$	76.4	76.4	76.4	60.4	60.0	61.2

$B$ : binarization,  $Q_n$ :  $n$ -bit quantization,  $E$ : histogram equalization.

## Inference time

Inference (secs)	DV+g	DV+d	DV+s	GD+g	GD+d	GD+s
$B$	0.23	0.25	0.25	0.38	0.37	0.31
$Q_2$	0.22	0.24	0.23	0.28	0.34	0.16
$Q_2 + E$	0.22	0.23	0.23	0.38	0.30	0.27
$Q_3$	0.22	0.23	0.22	0.22	0.32	0.17
$Q_3 + E$	0.22	0.23	0.22	0.34	0.32	0.31
$Q_4$	0.22	0.22	0.23	0.16	<b>0.17</b>	0.13
$Q_4 + E$	0.23	0.27	0.29	0.13	0.14	0.13
$Q_5$	0.22	0.26	0.28	0.07	0.05	0.02
$Q_5 + E$	0.22	0.29	0.25	0.05	0.05	0.02
$Q_6$	0.23	0.24	0.23	0.04	<b>0.05</b>	0.01
$Q_6 + E$	0.22	0.24	0.28	0.03	0.04	0.02
$Q_7$	0.23	0.23	0.26	0.03	0.01	0.01
$Q_7 + E$	0.22	0.26	0.24	0.01	0.01	0.01
$\emptyset$	0.22	0.26	0.23	0.02	<b>0.01</b>	0.01
$E$	0.23	0.23	0.22	0.01	0.01	0.02

$B$ : binarization,  $Q_n$ :  $n$ -bit quantization,  $E$ : histogram equalization.

# Chosen models

Model 1:  $Q_4$ , **GD+d**

Accuracy: 78.2%

Desktop time: 170ms

Berry time: 700ms

Model 2:  $Q_6$ , **GD+d**

Accuracy: 74.4%

Desktop time: 50ms

Berry time: 150ms

Model 3:  $\emptyset$ , **GD+d**


Accuracy: 62.4%

Desktop time: < 10ms

Berry time: 75ms

# Training

Training was done on an Intel i7-4500U CPU 1.80 Hz.



Saved SPN was then passed to the Raspberry.

# Prediction

## Pre-processing



Gray

Binarized

## SPN loading



LoadDisk



Predicted: RIGHT

## Comparison to neural networks

Comparison to Moraes and Salvatore 2018:

Model	Accuracy (%)	Speed (seconds)
DFN	81.3	$\approx 1.35$
CNN	80.6	$\approx 1.35$
$Q_4$ , GD-SPN+d	78.2	$\approx 0.70$
$Q_6$ , GD-SPN+d	74.4	$\approx 0.15$
GD-SPN+d	62.4	$\approx 0.07$

Neural networks were slightly more accurate, but real-time prediction with them is unfeasible.

Our implementation did not make use of the GPU, which could increase speed dramatically.

## “Real world” scenario

**Mobile Robot Self-Driving Through Image Classification Using Discriminative Learning of Sum-Product Networks — YouTube (<https://youtu.be/vhpWQDX2cQU>)**

# Implementation

**Inference and learning:** GoSPN  
(<https://github.com/RenatoGeh/gospn>)

**Mobile robot implementation:** GoDrive  
(<https://github.com/RenatoGeh/godrive>)

**Thank you.**

**Questions?**

# References I

(N.d.).

Bojarski, Mariusz et al. (2016). "End to End Learning for Self-Driving Cars". In: *CoRR abs/1604.07316*.

Chen, Z. and X. Huang (2017). "End-to-end learning for lane keeping of self-driving cars". In: *2017 IEEE Intelligent Vehicles Symposium (IV)*, pp. 1856–1860.

Conaty, Diarmuid, Cassio Polpo de Campos, and Denis Deratani Mauá (2017). "Approximation Complexity of Maximum A Posteriori Inference in Sum-Product Networks". In: *Proceedings of the Thirty-Third Conference on Uncertainty in Artificial Intelligence*.

Dennis, Aaron and Dan Ventura (2012). "Learning the Architecture of Sum-Product Networks Using Clustering on Variables". In: *Advances in Neural Information Processing Systems 25*. NIPS, pp. 2033–2041.

## References II

- Ester, Martin et al. (1996). "A Density-based Algorithm for Discovering Clusters in Large Spatial Databases with Noise". In: *Proceedings of the Second International Conference on Knowledge Discovery and Data Mining*. KDD'96. AAAI Press, pp. 226–231.
- Gens, Robert and Pedro Domingos (2012). "Discriminative Learning of Sum-Product Networks". In: *Advances in Neural Information Processing Systems 25*. NIPS, pp. 3239–3247.
- Gens, Robert and Domingos Pedro (17–19 Jun 2013). "Learning the Structure of Sum-Product Networks". In: *Proceedings of the 30th International Conference on Machine Learning*. Vol. 28. Proceedings of Machine Learning Research 3. Atlanta, Georgia, USA: PMLR, pp. 873–880.
- Hussein, Ahmed et al. (2017). "Imitation Learning: A Survey of Learning Methods". In: *ACM Computing Surveys* 50.2, 21:1–21:35. ISSN: 0360-0300. DOI: 10.1145/3054912.

## References III

- Levinson, Jesse et al. (2011). "Towards Fully Autonomous Driving: Systems and Algorithms". In: *Proceedings of the IEEE Intelligent Vehicles Symposium*, pp. 163–168.
- Mei, Jun, Yong Jiang, and Kewei Tu (2018). "Maximum A Posteriori Inference in Sum-Product Networks". In: *AAAI Conference on Artificial Intelligence*.
- Moraes, Paula and Felipe Salvatore (2018). *Self-Driving Pi Car*.  
[https://github.com/felipessalvatore/self\\_driving\\_pi\\_car](https://github.com/felipessalvatore/self_driving_pi_car).
- Otsu, Nobuyuki (Jan. 1979). "A Threshold Selection Method from Gray-Level Histograms". In: *IEEE Transactions on Systems, Man, and Cybernetics* 9.1, pp. 62–66. ISSN: 0018-9472. DOI: 10.1109/TSMC.1979.4310076.
- Paden, Brian et al. (2016). "A survey of motion planning and control techniques for self-driving urban vehicles". In: *IEEE Transactions on Intelligent Vehicles* 1.1, pp. 33–55.

## References IV

- Pan, Yunpeng et al. (2018). "Agile Autonomous Driving using End-to-End Deep Imitation Learning". In: *Proceedings of Robotics: Science and Systems XIV*.
- Peharz, Robert (2015). "Foundations of Sum-Product Networks for Probabilistic Modeling". PhD thesis. Graz University of Technology.
- Peharz, Robert et al. (2018). "Probabilistic Deep Learning using Random Sum-Product Networks". In: *CoRR abs/1806.01910*.
- Pfeiffer, Mark et al. (2017). "From Perception to Decision: A Data-driven Approach to End-to-end Motion Planning for Autonomous Ground Robots". In: *Proceedings of the IEEE International Conference on Robotics and Automation*, pp. 1527–1533.
- Pomerleau, Dean A. (1989). "Alvinn: An autonomous land vehicle in a neural network". In: *Advances in Neural Information Processing Systems*, pp. 305–313.

## References V

- Poon, Hoifung and Pedro Domingos (2011). "Sum-Product Networks: A New Deep Architecture". In: *Proceedings of the Twenty-Seventh Conference Annual Conference on Uncertainty in Artificial Intelligence (UAI-11)*. Corvallis, Oregon: AUAI Press, pp. 337–346.
- Rashwan, Abdullah, Pascal Poupart, and Chen Zhitang (Nov. 2018). "Discriminative Training of Sum-Product Networks by Extended Baum-Welch". In: *Proceedings of the Ninth International Conference on Probabilistic Graphical Models*. Vol. 72. Proceedings of Machine Learning Research. Prague, Czech Republic: PMLR, pp. 356–367.
- Sguerra, B. M. and F. G. Cozman (2016). "Image Classification Using Sum-Product Networks for Autonomous Flight of Micro Aerial Vehicles". In: *2016 5th Brazilian Conference on Intelligent Systems (BRACIS)*, pp. 139–144.
- Vergari, Antonio, Nicola Di Mauro, and Floriana Esposito (2015). "Simplifying, Regularizing and Strengthening Sum-Product Network Structure Learning". In: *ECML/PKDD*.

## References VI

- Zhao, Han, Tameem Adel, et al. (2016). "Collapsed Variational Inference for Sum-Product Networks". In: *Proceedings of The 33rd International Conference on Machine Learning*. Vol. 48. Proceedings of Machine Learning Research. PMLR, pp. 1310–1318.
- Zhao, Han, Pascal Poupart, and Geoffrey J Gordon (2016). "A Unified Approach for Learning the Parameters of Sum-Product Networks". In: *Advances in Neural Information Processing Systems 29*. NIPS, pp. 433–441.