API Reference - Introduction

Welcome to the EasyWeek API Reference, your comprehensive guide to integrating EasyWeek's online booking functionalities into your applications. This documentation provides detailed information on available endpoints, request and response formats, authentication methods, and more.

The EasyWeek API is a robust tool meticulously crafted to enable online booking functionality for various business categories, including but not limited to beauty salons, barbershops, healthcare facilities, and entertainment venues. The EasyWeek API is offering a range of features that can be used to create custom booking flows, integrate with chatbots, AI systems, and custom management solutions.

Getting Started

Before you begin, make sure you have obtained your API key to authenticate your requests. If you haven't generated an API key yet, refer to the API Key Guide for instructions.

Base URL

All API requests should be made to the base URL.

Authentication

To access the EasyWeek API, you need to include your API key in the headers of your requests. The authentication process is explained in detail in the Authentication Guide.

Rate Limits

Please be aware of the rate limits imposed on API requests to ensure fair usage and system stability. Refer to the Rate Limits section for more information.

Error Handling

Understand how errors are handled in the EasyWeek API by referring to the Error Handling Guide. This section provides insights into common error responses and their meanings.

Pagination

For endpoints that return a large set of data, the EasyWeek API supports pagination. Learn how to navigate through paginated results in the Pagination Guide.

Explore Endpoints

Now that you are familiar with the basics, explore the available endpoints in the categories below:

- **Config:** Retrieve information about staffers, locations, and services for your EasyWeek integration. This category provides everything you need to prepare the payload for creating bookings.
-
- **Availability:** Retrieve information about the availability of services, time slots, and resources. Use these endpoints to display real-time availability to your users.
-
-

Booking: Perform booking-related actions, such as creating new bookings, retrieving booking details, and managing existing bookings. These endpoints are crucial for handling reservations made through your integration.

Explore the documentation for each category to understand the specific endpoints, request and response formats, and usage details. If you have any questions or need further clarification, feel free to reach out to our support team.

Support

Please note that this is a high-level outline, and you should provide detailed information for each endpoint, including request headers, query parameters, request body (if applicable), and specific response structures. Additionally, make sure to document any authentication requirements and security considerations for your API.

The EasyWeek API is proudly developed and maintained by Awescode Agency. The dedicated team behind this project, who have worked tirelessly to create a robust and user-friendly API for your business needs. If you have any questions, feedback, or require assistance while using the EasyWeek API, please don't hesitate to reach out to our team for support. We are committed to delivering a seamless experience for your business analytics and data management.

Key Features

The API supports effective booking management by enabling real-time availability checks for staff and units. It simplifies the booking process, allowing customers to schedule appointments with specific details and offers functionality for cancellations.

Furthermore, the API facilitates booking status and payments management, enabling businesses to modify the status of bookings and record payment information, ensuring a smooth and organized booking process.

In essence, the EasyWeek API equips businesses with the essential tools to enhance their online booking systems and create a customer-centric experience.

Use Cases

- **Online Booking Systems:** Implement the API to create online booking systems for businesses such as beauty salons, healthcare providers, and entertainment venues.
- **Custom Booking Flows:** Develop customized booking processes to match the unique requirements and branding of businesses.
- **Chatbot Integration:** Integrate the API with chatbots to automate customer interactions, check availability, and handle booking inquiries in real-time.
- **AI Enhancements:** Utilize AI integration to analyze booking patterns, predict demand, and offer personalized recommendations to customers, enhancing the booking experience.
- **Custom Management Systems:** Create tailored management systems that handle bookings, staff schedules, customer data, and financial transactions within a unified solution.

How to connect to API

To connect to EasyWeek API, use the secure HTTPS protocol with the host `my.easyweek.io` and prefix all API URLs with `/api/public/v2/`. Authentication is mandatory for all endpoints, ensuring data security and access control. Please refer to the API documentation for specific authentication methods and endpoint details.

Here is an example of a base URL for connecting to the EasyWeek API:

```
https://my.easyweek.io/api/public/v2/
```

Authentication

The EasyWeek API requires authentication to ensure that only authorized systems can access data and perform actions. Follow these steps to authenticate your API requests.

Include the Authentication Key and Your Workspace

To authenticate your API requests, you need to include the authentication key in the **`Authorization`** header. The key should be in the format of a Bearer

token. Additionally, you must include your workspace slug in the `Workspace` header.

Use cURL for Authentication (Example)

You can use cURL, a command-line tool, to make authenticated API requests. Here's an example of how to include your authentication key in a cURL request:

```
curl -i -X GET \
  https://my.easyweek.io/api/public/v2/ping \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Make sure to replace `<YOUR_SECRET>` with your actual authentication key and `<YOUR_WORKSPACE>` with the relevant workspace slug.

Verifying Authentication

Upon successful authentication, the API response should have a status code of `200`, indicating a successful request. Additionally, the response text should be `pong`.

Get Workspace

Method `GET`

```
https://my.easyweek.io/api/public/v2/workspace
```

Description: This endpoint retrieves details about a specific workspace. It provides key information including the workspace's name, slug, and description, along with various settings and configurations.

Example Request

```
curl -i -X GET \
  https://my.easyweek.io/api/public/v2/workspace \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Example Response


```
{
  "uuid": "d679011b-f488-4fc4-a436-89b1e6d7e14b",
  "name": "Your company GmbH",
  "slug": "company-gmbh",
  "icon": "https://example.com/icon.png",
  "logo": "https://example.com/logo.png",
  "domain": "demo-gmbh.eyw.me",
  "country_iso": "Germany",
  "locale": "de",
  "currency": "EUR",
  "time_format": "24h",
  "first_week_day": "monday",
  "html_dir": "ltr",
  "languages": [
    "de"
  ],
  "language_default": "de",
  "theme": "light",
  "custom_colors": {
    "surface": "#ffffff",
    "on-surface": "#383868",
    "primary": "#36ab48",
    "secondary": "#ffffff"
  },
  "socials": {
    "instagram": "https://www.instagram.com/example",
    "facebook": "https://www.facebook.com/example",
    "tiktok": "https://www.tiktok.com/example",
    "youtube": "https://www.youtube.com/example",
    "twitter": "https://www.x.com/@example"
  },
  "contacts": {
    "phone": "+493012345678",
    "whatsapp": "+493012345678",
    "viber": "+493012345678",
    "telegram": "@example"
  }
}
```


Get Locations

Method `GET`

```
https://my.easyweek.io/api/public/v2/locations
```

Description: This endpoint is used to retrieve a list of locations for the current workspace. It provides information about each location, including its name, logo, description, opening hours, timezone, address details, and images. The primary image is always listed first in the array of images.

Example Request

```
curl -i -X GET \
  https://my.easyweek.io/api/public/v2/locations \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Example Response


```
{
  "data": [
    {
      "uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
      "name": "Location 1",
      "images": [

"https://storage.easyweek.io/example_main_images_images_HwPbmMatZl.jpg",

"https://storage.easyweek.io/example_images_images_2qryC62Soi.jpg"
      ],
      "description": "This is a test location description.",
      "opening_hours": {
        "days": {
          "mon": [
            {
              "from": "09:00",
              "to": "21:00"
            }
          ],
          "wed": [
            {
              "from": "08:00",
              "to": "12:00"
            },
            {
              "from": "13:00",
              "to": "17:00"
            }
          ],
          "tue": null,
          "thu": null,
```

```
          "fri": null,
          "sat": null,
          "sun": null
        }
      },
      "timezone": {
        "name": "Europe/Berlin",
        "short": "CET",
        "offset": "+01:00"
      },
      "is_address_hidden": false,
      "address": {
        "address_1": "Musterstraße 123",
        "city": "Berlin",
        "postal_code": "12345",
        "apt": "Wohnung 4B",
        "position": {
          "lat": 52.5200066,
          "lng": 13.404954
        }
      }
    }
  ],
  "links": {
    "first": "https://my.easyweek.io/api/public/v2/locations?page=1",
    "last": "https://my.easyweek.io/api/public/v2/locations?page=1",
    "prev": null,
    "next": null
  },
  "meta": {
    "current_page": 1,
    "from": 1,
    "last_page": 1,
    "links": [
      {
        "url": null,
        "label": "&laquo; Previous",
        "active": false
      },
      {
        "url":
"https://my.easyweek.io/api/public/v2/locations?page=1",
        "label": "1",
        "active": true
      },
      {
        "url": null,
        "label": "Next &raquo;",
        "active": false
      }
    ],
    "path": "https://my.easyweek.io/api/public/v2/locations",
    "per_page": 15,
    "to": 1,
```

```
    "total": 1
  }
}
```

Get Service Categories

Method GET

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/servi
ce-categories
```

Description: This endpoint is used to retrieve a list of service categories for a specific location. It provides information about each category, including its UUID, name, display order, and cover image.

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/servi
ce-categories \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): This parameter represents the unique identifier of the location for which you want to retrieve service categories. By specifying the location by its UUID, the endpoint will return the categories available at that particular location.

Example Response

```
{
  "data": [
    {
      "uuid": "41765a3f-d8eb-4853-8558-0718c49c58d0",
      "name": "Hair Styling",
      "order": 1,
      "cover":
"https://storage.easyweek.io/example_images_images_gJuFjyzB1j.jpg"
```

```
    }
  ]
}
```

Without pagination

Get Services

Method `GET`

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/servi
ces
```

Description: This endpoint is used to retrieve a list of services offered at a specific location, within a specified category. It provides detailed information about each service, including its name, description, pricing, duration, and other attributes.

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/servi
ces?category_uuid={category_uuid}&staffer_uuid={staffer_uuid} \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): This is a parameter that represents the unique identifier of the location for which you want to retrieve services. It allows you to specify the location by its UUID, and the endpoint will return the services available at that particular location.

Query Parameters

- **category_uuid** (string, optional): This is an optional parameter that allows you to filter services by category. You can specify the `category_uuid` to narrow down the results to services within a specific category. To retrieve services that are not assigned to any category, use `category_uuid=none`.

- **staffer_uuid** (string, optional): An optional parameter that further filters the services by a specific staffer. By providing a `staffer_uuid`, you can retrieve only those services that the specified staffer is eligible to perform.

> **INFO**

The fields `duration`, and `extra_time` are always returned as objects in the response, even if they are not set or are set to their default values. This ensures a consistent response structure for consumers of the API.

Example Response


```
{
  "data": [
    {
      "uuid": "43537759-435b-4871-bf11-e3ace6a4464b",
      "name": "Beard trim",
      "description": null,
      "images": [],
      "is_price_hidden": false,
      "starting_at": false,
      "currency": "EUR",
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": null,
      "discount_formatted": null,
      "is_duration_hidden": false,
      "duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      },
      "is_extra_time": false,
      "extra_time": {
        "value": 0,
        "label": "minutes",
        "iso_8601": "PT0M"
      },
      "is_top": false,
      "category": {
        "uuid": "41765a3f-d8eb-4853-8558-0718c49c58d0",
        "name": "Hair Styling",
        "order": 1,
        "cover":
"https://storage.easyweek.io/e2e/media/74/category_images_yqlKmA9h.jpg"
      }
```

```
    }
  ],
  "links": {
    "first":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/services?page=1",
    "last":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/services?page=1",
    "prev": null,
    "next": null
  },
  "meta": {
    "current_page": 1,
    "from": 1,
    "last_page": 1,
    "links": [
      {
        "url": null,
        "label": "&laquo; Previous",
        "active": false
      },
      {
        "url":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/services?page=1",
        "label": "1",
        "active": true
      },
      {
        "url": null,
        "label": "Next &raquo;",
        "active": false
      }
    ],
    "path":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/services",
    "per_page": 15,
    "to": 1,
    "total": 1
  }
}
```


Get Staffer Categories

Method `GET`

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/staff
er-categories
```

Description: This endpoint is used to retrieve a list of categories associated with staffers at a specific location. It provides information about each category, including its name.

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/staff
er-categories \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): This is a parameter that represents the unique identifier of the location for which you want to retrieve categories associated with staffers. It allows you to specify the location by its UUID, and the endpoint will return the categories linked to staffers at that particular location.

Example Response

```
{
  "data": [
    {
      "uuid": "b4cecf14-e42f-46b8-b501-cf6244974a31",
      "name": "Hair Styling",
      "order": 1
    },
    {
      "uuid": "0be3a85c-52ab-4bb6-9580-d2f7f11dbeda",
      "name": "Barbering",
      "order": 2
    },
    {
      "uuid": "66c23785-bdf0-497d-94f4-8fd74400fd1b",
      "name": "Nail Care",
      "order": 3
    }
  ]
}
```

Without pagination

Get Staffers

Method `GET`

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/staff
ers
```

Description: This endpoint is used to retrieve a list of staffers working at a specific location. It provides information about each staffer, including their first name, last name, position, description, and avatar (if available).

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/staff
ers \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): This is a parameter that represents the unique identifier of the location for which you want to retrieve a list of staffers. It allows you to specify the location by its UUID, and the endpoint will return the staffers associated with that particular location.

Example Response

```
{
  "data": [
    {
      "uuid": "eac5a506-69c0-40c4-8758-85c501d26bcb",
      "first_name": "John",
      "last_name": "Doe",
      "position": "Barber",
      "description": "Experienced barber with a passion for creating
great haircuts.",
      "avatar": "https://storage.easyweek.io/media/75/avatar.png",
      "category": {
```

```
        "uuid": "0be3a85c-52ab-4bb6-9580-d2f7f11dbeda",
        "name": "Barbering",
        "order": 2
      }
    }
  ],
  "links": {
    "first":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/staffers?page=1",
    "last":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/staffers?page=1",
    "prev": null,
    "next": null
  },
  "meta": {
    "current_page": 1,
    "from": 1,
    "last_page": 1,
    "links": [
      {
        "url": null,
        "label": "&laquo; Previous",
        "active": false
      },
      {
        "url":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/staffers?page=1",
        "label": "1",
        "active": true
      },
      {
        "url": null,
        "label": "Next &raquo;",
        "active": false
      }
    ],
    "path":
"https://my.easyweek.io/api/public/v2/locations/123b2980-3506-4f8c-
abce-97e1ab653406/staffers",
    "per_page": 15,
    "to": 1,
    "total": 1
  }
}
```


Get available time slots

Method GET

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/time-slots
```

Description: This endpoint retrieves available time slots for appointments at a specific location, given the selected service and staff member within a specified date range. It provides detailed information about each date, including available slots with start and end times, the quantity available for booking, and pricing details, as well as any booking intervals that might exist.

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/time-slots/?service_uuid={service_uuid}&staffer_uuid={staffer_uuid}&range_start={range_start}&range_end={range_end}&timezone={timezone} \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): This parameter is the unique identifier of the location for which available time slots are being requested. It is used to specify the location by its UUID.

Query Parameters

- **service_uuid** (string, required): A required parameter that specifies the UUID of the service for which the appointment slots are needed.
- **staffer_uuid** (string, optional): A required parameter that represents the UUID of the staff member for whom the appointment time slots are requested.
- **range_start** (string, required): This parameter defines the start date of the range from which you want to retrieve available time slots.
- **range_end** (string, required): This parameter sets the end date of the range for the time slot query.
- **timezone** (string, optional): Represents the timezone identifier for the client's local timezone. Used to adjust the time slots to the client's local time.

The response includes the current date (`today`), the time zone for the location (`timezone`), and an array of dates each with its own array of available time slots (`slots`) and intervals during which bookings can be made (`intervals`). Each slot object includes a start and end time and the price information with the amount, formatted price, and currency. Intervals denote chunks of time during the day when time slots can be booked.

Example Response

```
{
  "today": "2023-12-20",
  "timezone": "Europe/Berlin",
  "currency": "EUR",
  "dates": [
    {
      "date": "2023-12-20",
      "slots": [
        {
          "start": "09:00",
          "start_formatted": 32400,
          "end": "09:30",
          "end_formatted": 34200,
          "quantity": 1,
          "price": 10000,
          "price_formatted": "€100.00"
        }
      ],
      "intervals": [
        {
          "start": "09:00",
          "start_formatted": 32400,
          "end": "12:00",
          "end_formatted": 43200
        }
      ]
    }
  ]
}
```

Get next available slots

Method `GET`

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/time-slots/next
```

This endpoint retrieves the next available time slots for a selected service and staff member at a specific location. It can be used to quickly find upcoming slots for scheduling without searching through the full range of dates.

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/time-slots/next?service_uuid={service_uuid}&staffer_uuid={staffer_uuid}&timezone={timezone} \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): This parameter signifies the unique identifier of the location from which you wish to query the next available time slots.

Query Parameters

- **service_uuid** (string, required): The UUID of the service for which time slot availability is being requested.
- **staffer_uuid** (string, optional): This parameter represents the individual staff member's UUID for whom the time slot availability is being checked.
- **timezone** (string, optional): Represents the timezone identifier for the client's local timezone. Used to adjust the time slots to the client's local time.

Example Response

```
{
  "data": [
    {
      "timezone": "Europe/Berlin",
      "currency": "EUR",
      "dates": [
        {
          "date": "2023-12-20",
          "slot": {
            "start": "13:40",
            "end": "14:10",
```

```
            "start_formatted": 49200,
            "end_formatted": 51000,
            "price": 10000,
            "price_formatted": "€100.00",
            "staffers": [
              {
                "uuid": "eac5a506-69c0-40c4-8758-85c501d26bcb"
              }
            ]
          }
        }
      ]
    }
  ]
```


Create booking

Method POST

```
https://my.easyweek.io/api/public/v2/bookings
```

Description: This endpoint is used for creating a new booking at a specified location and service. It sets up an appointment for a customer, optionally with a chosen staff member, and captures essential details such as customer contact information and booking notes.

Example Request

```
curl -i -X POST \
  https://my.easyweek.io/api/public/v2/bookings \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Request body


```
{
  "staffer_uuid": "eac5a506-69c0-40c4-8758-85c501d26bcb",
  "reserved_on": "2023-12-21T10:00:00Z",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "service_uuid": "43537759-435b-4871-bf11-e3ace6a4464b",
  "customer_phone": "+491621234567",
  "customer_first_name": "Name",
  "customer_last_name": "",
  "customer_middle_name": "",
```

```
  "customer_email": "user@example.com",
  "booking_comment": "Hello world",
  "source": "instagram",
  "timezone": "Europe/Berlin",
  "customer_browser_tz": "Europe/Berlin",
  "customer_browser_language": "en",
  "booking_callback": false,
  "booking_google_meet_guest_emails": "test1@mail.com,
test2@mail.com"
}
```

Body Parameters

- **location_uuid** (string, required): The unique identifier of the location where the service is to be booked.
- **service_uuid** (string, required): The UUID of the service being booked.
- **reserved_on** (string, required): The date and time when the service is to be reserved, in ISO 8601 format.
- **customer_phone** (string, required): The phone number of the customer making the booking.
- **customer_first_name** (string, required): The first name of the customer.
- **customer_email** (string, optional): The email address of the customer.
- **staffer_uuid** (string, optional): The UUID of the staff member with whom the booking is to be made. Bookings can only be created with staff members who are marked as active in the booking widget. If this parameter is not specified, the booking will be automatically assigned to one of the available active staff members in the widget.
- **customer_last_name** (string, optional): The last name of the customer.
- **customer_middle_name** (string, optional): The middle name of the customer.
- **booking_comment** (string, optional): Any notes or special instructions associated with the booking.
- **source** (string, optional): The source from where the booking was made, such as a social media platform. If the source parameter is provided incorrectly or is empty, the system will automatically record it as `unknown`.
- **timezone** (string, optional): The timezone in which the booking is made, used for time calculation.
- **customer_browser_tz** (string, optional): The timezone of the customer's browser, useful for user experience customization.
- **customer_browser_language** (string, optional): The preferred language of the customer's browser.
- **booking_callback** (string, optional): A boolean flag indicating whether a callback is required for the booking.

- **booking_google_meet_guest_emails** (string, optional): A list of guest email addresses for a Google Meet booking. This option is available only if the integration with Google Meet is enabled.

> The designation of certain fields as optional or required may vary according to booking configurations. To set or verify the requirement status of these fields, navigate to Settings -> Administration -> Form Builder within the platform interface.

This endpoint captures the booking details submitted by the client and schedules the service accordingly. The response will confirm the successful creation of the booking and provide any relevant details or identification numbers associated with the booking.

Example Response


```
{
  "uuid": "f017724b-d95a-4267-8704-df99a9edaf56",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "start_time": "2023-12-21T10:00:00Z",
  "end_time": "2023-12-21T10:30:00Z",
  "timezone": "Europe/Berlin",
  "duration": {
    "value": 30,
    "label": "minutes",
    "iso_8601": "PT30M"
  },
  "quantity": 1,
  "slots_count": 1,
  "cancel_reason": null,
  "canceled_by": null,
  "is_canceled": false,
  "is_completed": false,
  "public_notes": "Hello world",
  "currency": "EUR",
  "policy": {
    "policy_text": null,
    "is_cancelable": true,
    "cancellation_offset": 0,
    "cancellation_text": null,
    "is_changeable": true,
    "change_offset": 0,
    "change_text": null
  },
  "links": [
    {
      "type": "ical",
      "link":
"https://my.easyweek.io/api/notifications/bookings/6929741/icalendar
```

"
    },
    {
      "type": "google_meet",
      "link": ""
    },
    {
      "type": "zoom",
      "link": ""
    },
    {
      "type": "microsoft_teams",
      "link": ""
    }
  ],
  "order": {
    "tax": [],
    "subtotal": 10000,
    "subtotal_formatted": "€100.00",
    "amount_paid": 0,
    "amount_paid_formatted": "€0.00",
    "total": 10000,
    "total_formatted": "€100.00"
  },
  "ordered_services": [
    {
      "uuid": "ce889d66-dbf5-462f-bf67-a0dec4a48941",
      "timezone": "Europe/Berlin",
      "reserved_on": "2023-12-21T10:00:00Z",
      "reserved_until": "2023-12-21T10:30:00Z",
      "quantity": 1,
      "name": "Beard trim",
      "currency": "EUR",
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": 0,
      "discount_formatted": "€0.00",
      "original_price": 10000,
      "original_price_formatted": "€100.00",
      "tax_name": null,
      "tax_value": null,
      "duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      },
      "original_duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      }
    }
  ]
}

Get booking

Method `GET`

```
https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}
```

Description: This endpoint retrieves detailed information for a specific booking using the unique booking identifier (UUID). It is used to obtain the full details of a booking, such as service information, staff member assigned, customer details, and any notes or special instructions related to the appointment.

Example Request

```
curl -i -X GET \
  https://my.easyweek.io/api/public/v2/bookings/{booking_uuid} \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **booking_uuid** (string, required): The unique identifier for the booking you wish to retrieve. This UUID is a distinctive code that represents an individual booking within the system.

Example Response

```
{
  "uuid": "f017724b-d95a-4267-8704-df99a9edaf56",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "start_time": "2023-12-21T10:00:00Z",
  "end_time": "2023-12-21T10:30:00Z",
  "timezone": "Europe/Berlin",
  "duration": {
    "value": 30,
    "label": "minutes",
    "iso_8601": "PT30M"
  },
  "quantity": 1,
```

```
  "slots_count": 1,
  "cancel_reason": null,
  "canceled_by": null,
  "is_canceled": false,
  "is_completed": false,
  "public_notes": "Hello world",
  "currency": "EUR",
  "policy": {
    "policy_text": null,
    "is_cancelable": true,
    "cancellation_offset": 0,
    "cancellation_text": null,
    "is_changeable": true,
    "change_offset": 0,
    "change_text": null
  },
  "links": [
    {
      "type": "ical",
      "link":
"https://my.easyweek.io/api/notifications/bookings/6929741/icalendar
"
    },
    {
      "type": "google_meet",
      "link": ""
    },
    {
      "type": "zoom",
      "link": ""
    },
    {
      "type": "microsoft_teams",
      "link": ""
    }
  ],
  "order": {
    "tax": [],
    "subtotal": 10000,
    "subtotal_formatted": "€100.00",
    "amount_paid": 0,
    "amount_paid_formatted": "€0.00",
    "total": 10000,
    "total_formatted": "€100.00"
  },
  "ordered_services": [
    {
      "uuid": "ce889d66-dbf5-462f-bf67-a0dec4a48941",
      "timezone": "Europe/Berlin",
      "reserved_on": "2023-12-21T10:00:00Z",
      "reserved_until": "2023-12-21T10:30:00Z",
      "quantity": 1,
      "name": "Beard trim",
      "currency": "EUR",
```

```
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": 0,
      "discount_formatted": "€0.00",
      "original_price": 10000,
      "original_price_formatted": "€100.00",
      "tax_name": null,
      "tax_value": null,
      "duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      },
      "original_duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      }
    }
  ]
}
```


Get booking statuses

Method `GET`

```
https://my.easyweek.io/api/public/v2/bookings/statuses
```

Description: This endpoint retrieves a list of non-final booking statuses within the system. It's designed to show the various intermediate states a booking can have before reaching a final status, such as being completed or canceled.

Example Request

```
curl -i -X GET \
  https://my.easyweek.io/api/public/v2/bookings/statuses \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Example Response


```
{
  "data": [
    {
      "uuid": "87720786-2e2c-4df8-a9f3-7719be6b41c8",
```

```
      "name": "Bestätigt"
    },
    {
      "uuid": "ab72e362-c8c2-4238-b863-398f03baf457",
      "name": "In Arbeit"
    }
  ]
}
```

Without pagination

Get accounts

Method `GET`

```
https://my.easyweek.io/api/public/v2/locations/{location_uuid}/accounts
```

Description: This endpoint is utilized to retrieve a list of financial accounts associated with a specific location. It is designed to show where booking-related payments are credited for a location, providing visibility into the financial channels within the platform.

Example Request

```
curl -i -X GET \

https://my.easyweek.io/api/public/v2/locations/{location_uuid}/accounts \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Path Parameters

- **location_uuid** (string, required): The unique identifier of the location for which the financial accounts list is being retrieved. This UUID ensures that the returned accounts are specific to the location in question.

Example Response

```
{
  "data": [
    {
      "uuid": "d679011b-f488-4fc4-a436-89b1e6d7e14b",
      "name": "Bargeld"
    }
  ]
}
```

Without pagination

Set booking compete

Method PUT

```
https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}/status/
complete
```

Description: This endpoint is used to mark a booking as complete within the system. It updates the status of a specific booking to reflect that the service has been rendered and handles the accounting aspects of the completed booking.

Example Request

```
curl -i -X PUT \

https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}/status/
complete \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Request body

```
{
  "account_uuid": "d679011b-f488-4fc4-a436-89b1e6d7e14b",
  "internal_notes": "",
  "paid_amount": 80000
}
```

Path Parameters

- **booking_uuid** (string, required): The unique identifier of the booking to be marked as complete.

Body Parameters

- **account_uuid** (string, required): The UUID of the financial account where the payment for the booking should be credited.
- **internal_notes** (string, optional): Optional field for any notes staff members need to record regarding the booking completion.
- **paid_amount** (string, optional): The amount paid upon completion of the service. By default, if this field is not provided, the system will use the booking's total amount.
- **staffer_uuid** (string, optional): The UUID of the staff member who closed the booking. This parameter is used to identify the individual who marked the service as complete within the system.

When this API call succeeds, the booking's status will be updated to complete, and any provided financial details will be processed as specified. This allows for the closure of the transaction cycle and proper recording in the financial logs.

Example Response


```
{
  "uuid": "f017724b-d95a-4267-8704-df99a9edaf56",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "start_time": "2023-12-21T10:00:00Z",
  "end_time": "2023-12-21T10:30:00Z",
  "timezone": "Europe/Berlin",
  "duration": {
    "value": 30,
    "label": "minutes",
    "iso_8601": "PT30M"
  },
  "quantity": 1,
  "slots_count": 1,
  "cancel_reason": null,
  "canceled_by": null,
  "is_canceled": false,
  "is_completed": true,
  "public_notes": "Hello world",
  "currency": "EUR",
  "policy": {
    "policy_text": null,
```

```
    "is_cancelable": true,
    "cancellation_offset": 0,
    "cancellation_text": null,
    "is_changeable": true,
    "change_offset": 0,
    "change_text": null
  },
  "links": [
    {
      "type": "ical",
      "link":
"https://my.easyweek.io/api/notifications/bookings/6929741/icalendar
"
    },
    {
      "type": "google_meet",
      "link": ""
    },
    {
      "type": "zoom",
      "link": ""
    },
    {
      "type": "microsoft_teams",
      "link": ""
    }
  ],
  "order": {
    "tax": [],
    "subtotal": 10000,
    "subtotal_formatted": "€100.00",
    "amount_paid": 80000,
    "amount_paid_formatted": "€800.00",
    "total": 10000,
    "total_formatted": "€100.00"
  },
  "ordered_services": [
    {
      "uuid": "ce889d66-dbf5-462f-bf67-a0dec4a48941",
      "timezone": "Europe/Berlin",
      "reserved_on": "2023-12-21T10:00:00Z",
      "reserved_until": "2023-12-21T10:30:00Z",
      "quantity": 1,
      "name": "Beard trim",
      "currency": "EUR",
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": 0,
      "discount_formatted": "€0.00",
      "original_price": 10000,
      "original_price_formatted": "€100.00",
      "tax_name": null,
      "tax_value": null,
      "duration": {
```

```
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      },
      "original_duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      }
    }
  ]
}
```

Set booking cancel

Method `PUT`

```
https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}/status/cancel
```

Description: This endpoint is used to cancel an existing booking and record the reason for cancellation. The status of a specific booking is updated to reflect that it has been canceled, and an internal note can be optionally added for further context.

Example Request

```
curl -i -X PUT \

https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}/status/cancel \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Request body

```
{
  "cancel_reason": "wrong_order",
  "internal_notes": ""
}
```

Path Parameters

- **booking_uuid** (string, required): The unique identifier for the booking that is being canceled.

Body Parameters

- **cancel_reason** (enum, optional): A predefined reason for the cancellation. Acceptable reasons include `canceled`, `didnt_come`, `postponed`, `wrong_order`, `spam`, or `other`.
- **internal_notes** (string, optional): Optional field to include any additional notes or information relevant to the cancellation.
- **staffer_uuid** (string, optional): The UUID of the staff member who canceled the booking. This parameter is used to identify the individual who marked the service as canceled within the system.

Once the endpoint is called with a valid `booking_uuid` and cancelation reason, it will update the booking's status to canceled and log the specified reason along with any internal notes. This operation is crucial for maintaining accurate records and analytics pertaining to booking management.

Example Response


```
{
  "uuid": "f017724b-d95a-4267-8704-df99a9edaf56",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "start_time": "2023-12-21T10:00:00Z",
  "end_time": "2023-12-21T10:30:00Z",
  "timezone": "Europe/Berlin",
  "duration": {
    "value": 30,
    "label": "minutes",
    "iso_8601": "PT30M"
  },
  "quantity": 1,
  "slots_count": 1,
  "cancel_reason": null,
  "canceled_by": null,
  "is_canceled": true,
  "is_completed": false,
  "public_notes": "Hello world",
  "currency": "EUR",
  "policy": {
    "policy_text": null,
    "is_cancelable": true,
    "cancellation_offset": 0,
    "cancellation_text": null,
```

```
    "is_changeable": true,
    "change_offset": 0,
    "change_text": null
  },
  "links": [
    {
      "type": "ical",
      "link":
"https://my.easyweek.io/api/notifications/bookings/6929741/icalendar
"
    },
    {
      "type": "google_meet",
      "link": ""
    },
    {
      "type": "zoom",
      "link": ""
    },
    {
      "type": "microsoft_teams",
      "link": ""
    }
  ],
  "order": {
    "tax": [],
    "subtotal": 10000,
    "subtotal_formatted": "€100.00",
    "amount_paid": 0,
    "amount_paid_formatted": "€0.00",
    "total": 10000,
    "total_formatted": "€100.00"
  },
  "ordered_services": [
    {
      "uuid": "ce889d66-dbf5-462f-bf67-a0dec4a48941",
      "timezone": "Europe/Berlin",
      "reserved_on": "2023-12-21T10:00:00Z",
      "reserved_until": "2023-12-21T10:30:00Z",
      "quantity": 1,
      "name": "Beard trim",
      "currency": "EUR",
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": 0,
      "discount_formatted": "€0.00",
      "original_price": 10000,
      "original_price_formatted": "€100.00",
      "tax_name": null,
      "tax_value": null,
      "duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
```

```
      },
      "original_duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      }
    }
  ]
}
```

Update booking notes

Method `POST`

```
https://my.easyweek.io/api/public/v2/bookings/{booking_uid}/public_notes
```

Description: This endpoint is designed to update or add a public note to an existing booking. Public notes are visible to both staff and customers and can be used for additional information or special instructions related to the booking.

Example Request

```
curl -i -X POST \

https://my.easyweek.io/api/public/v2/bookings/{booking_uid}/public_notes \
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Request body

```
{
  "value": "my notes"
}
```

Path Parameters

- **booking_uuid** (string, required): The unique identifier of the booking for which the public note is to be updated.

Body Parameters

- **value** (string, required): The text content of the public note to be associated with the booking.

Example Response


```
{
  "uuid": "ceeabc63-7502-4158-b27e-7d051ce36c24",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "start_time": "2023-12-21T10:00:00Z",
  "end_time": "2023-12-21T10:30:00Z",
  "timezone": "Europe/Berlin",
  "duration": {
    "value": 30,
    "label": "minutes",
    "iso_8601": "PT30M"
  },
  "quantity": 1,
  "slots_count": 1,
  "cancel_reason": null,
  "canceled_by": null,
  "is_canceled": false,
  "is_completed": false,
  "public_notes": "my notes",
  "currency": "EUR",
  "policy": {
    "policy_text": null,
    "is_cancelable": true,
    "cancellation_offset": 0,
    "cancellation_text": null,
    "is_changeable": true,
    "change_offset": 0,
    "change_text": null
  },
  "links": [
    {
      "type": "ical",
      "link":
"https://my.easyweek.io/api/notifications/bookings/6005979/icalendar
"
    },
    {
      "type": "google_meet",
      "link": ""
    },
    {
      "type": "zoom",
      "link": ""
```

```
    },
    {
      "type": "microsoft_teams",
      "link": ""
    }
  ],
  "order": {
    "tax": [],
    "subtotal": 10000,
    "subtotal_formatted": "€100.00",
    "amount_paid": 0,
    "amount_paid_formatted": "€0.00",
    "total": 10000,
    "total_formatted": "€100.00"
  },
  "ordered_services": [
    {
      "uuid": "1e5851a6-eb6b-4b3c-a328-66cfbe1ac965",
      "timezone": "Europe/Berlin",
      "reserved_on": "2023-12-21T10:00:00Z",
      "reserved_until": "2023-12-21T10:30:00Z",
      "quantity": 1,
      "name": "Beard trim",
      "currency": "EUR",
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": 0,
      "discount_formatted": "€0.00",
      "original_price": 10000,
      "original_price_formatted": "€100.00",
      "tax_name": null,
      "tax_value": null,
      "duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      },
      "original_duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      }
    }
  ]
}
```


Update booking status

Method PUT

```
https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}/status
```

Description: This endpoint is utilized to update the status of an existing booking. By specifying a new status UUID, the booking's current status can be changed to reflect its latest state within the booking lifecycle.

Example Request

```
curl -i -X PUT \

https://my.easyweek.io/api/public/v2/bookings/{booking_uuid}/status
\
  -H 'Authorization: Bearer <YOUR_SECRET>' \
  -H 'Workspace: <YOUR_WORKSPACE>'
```

Request body

```
{
  "status_uuid": "87720786-2e2c-4df8-a9f3-7719be6b41c8"
}
```

Path Parameters

- **booking_uuid** (string, required): The unique identifier of the booking whose status needs to be updated.

Body Parameters

- **status_uuid** (string, required): The UUID of the new status to be applied to the booking. This should correspond to one of the status types defined in the system.

By sending a request to this endpoint with the appropriate `booking_uuid` and a new `status_uuid`, the system will record the change and update the booking accordingly. This function is essential for dynamic booking management and ensuring that the booking's progress is accurately tracked and communicated.

Example Response

```
{
  "uuid": "ceeabc63-7502-4158-b27e-7d051ce36c24",
  "location_uuid": "123b2980-3506-4f8c-abce-97e1ab653406",
  "start_time": "2023-12-21T10:00:00Z",
  "end_time": "2023-12-21T10:30:00Z",
  "timezone": "Europe/Berlin",
  "duration": {
    "value": 30,
    "label": "minutes",
    "iso_8601": "PT30M"
  },
  "quantity": 1,
  "slots_count": 1,
  "cancel_reason": null,
  "canceled_by": null,
  "is_canceled": false,
  "is_completed": false,
  "public_notes": "Hello world",
  "currency": "EUR",
  "policy": {
    "policy_text": null,
    "is_cancelable": true,
    "cancellation_offset": 0,
    "cancellation_text": null,
    "is_changeable": true,
    "change_offset": 0,
    "change_text": null
  },
  "links": [
    {
      "type": "ical",
      "link":
"https://my.easyweek.io/api/notifications/bookings/6005979/icalendar
"
    },
    {
      "type": "google_meet",
      "link": ""
    },
    {
      "type": "zoom",
      "link": ""
    },
    {
      "type": "microsoft_teams",
      "link": ""
    }
  ],
  "order": {
    "tax": [],
    "subtotal": 10000,
    "subtotal_formatted": "€100.00",
    "amount_paid": 0,
    "amount_paid_formatted": "€0.00",
```

```
    "total": 10000,
    "total_formatted": "€100.00"
  },
  "ordered_services": [
    {
      "uuid": "1e5851a6-eb6b-4b3c-a328-66cfbe1ac965",
      "timezone": "Europe/Berlin",
      "reserved_on": "2023-12-21T10:00:00Z",
      "reserved_until": "2023-12-21T10:30:00Z",
      "quantity": 1,
      "name": "Beard trim",
      "currency": "EUR",
      "price": 10000,
      "price_formatted": "€100.00",
      "discount": 0,
      "discount_formatted": "€0.00",
      "original_price": 10000,
      "original_price_formatted": "€100.00",
      "tax_name": null,
      "tax_value": null,
      "duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      },
      "original_duration": {
        "value": 30,
        "label": "minutes",
        "iso_8601": "PT30M"
      }
    }
  ]
}
```