OLX

OLX Partner API (2.0)

Download OpenAPI specification:Download

OLX Europe shares public API for its partners. It allows to easily integrate with local sites by posting, managing adverts and communicating with OLX users via internal messaging system.
API documentation is the same for every OLX across the Europe.
To help you get started, this is API calls collection to be used with Postman.

Run in Postman

Versioning

- Major version is reserved for completely new version or redesigned API
- Minor version is for potentially backward incompatible changes (e.g. field is removed/added/changed name, etc)
- We do not support “bugfix” part of the versioning as minor versioning is enough in this case - if bugfix has backward incompatible change, it will bump up minor version.
- Version is defined using Version header (e.g. If you want to use endpoint in version 2.0, just send request with header “Version: 2.0”).
- Version header is required.

Language

- In multilingual countries (like Ukraine) switching between languages is supported by sending header “Accept-Language: xx” where xx is language code
- There are two endpoints exposing available languages and currencies (see endpoints references below).

Authentication

OAuth 2.0

OLX API implements OAuth2 standard. For more information you can visit https://www.oauth.com/oauth2-servers/definitions/.
Basic principle of OAuth is one point of authorization and accessing all of resources with access token, granting (or not) access to certain endpoints.

OAuth access token is string which should be passed to every request made to OLX API endpoints. Token is valid for certain amount of time, after that application have to send request with refresh token to receive new token.
Remember Access token is like password - when someone obtains token, then gains full access to given account, limited only by token scope.
In order to use API partner should request to receive API Client data. One partner may have more than one application eligible for OLX API, each with different set of credentials. Basic API credentials are client_id and client_secret - both are required regardless of selected authentication method.

Credentials

Please store client_id, client_secret in safe place, as it will be needed to complete configuration and authentication process.

How to obtain Access Token

In order to receive token, client should send POST request to /api/open/oauth/token. Required fields:

```
{
 "grant_type": "",
 "client_id": "",
 "client_secret": "",
 "scope": "v2 read write"}
```

client_id and client_secret are data you have received from OLX business person. scope is requested token scope, but limited by partner settings - basically “v2”, “read” and “write”.
Depends on grant type, request should contain other necessary fields.
As response client will receive:

```
{
 "access_token": "454c3cd39a980500e9b787e03d53ec5c320f644b",
 "expires_in": 86400,
 "token_type": "bearer",
 "scope": "v2 read write",
 "refresh_token": "12a13560163da7901d7f74c89fc5df3ea7625942"}
```

Access token should be passed with each request to API as header Authorization.
Authorization: Bearer 454c3cd39a980500e9b787e03d53ec5c320f644b
Field expires_in defines how many more seconds since now (now = last request to oauth/token endpoint) access token will be valid.
Refresh token is valid for one month (2592000 seconds). Also it can be changed when new access token is generated.
Please store access token and refresh token in safe place.

Supported grant types

Grant Type	Context	Actions
authorization_code	User	Add or fetch adverts adverts / messages, etc.
client_credentials	Client	Fetch config data: categories, cities, etc.

Grant Type	Context	Actions
refresh_token	User or Client	

Scopes

Scopes are specific permissions for API usage as a given user type. The authorization and token endpoints allow your application to specify the scope of the access request.
Each API endpoint can demand access token with the specific scope. See the endpoint reference for information about required scope.
Please note your application has closed list of allowed scopes, so you should ensure you are able to ask about given scope and always verify the scopes of issued token.
Default scopes are: v2 read write.

Grant type: authorization_code

Requirements:
Client must specify Callback URL. You can specify more than one Callback URL. Please avoid special chars like & (multiple), # in Callback URL.
Flow:
On Application site user clicks on button "Authenticate with OLX".
Auth URL: /oauth/authorize/?client_id=XXX&response_type=code&state=XXX&scope=read write v2&redirect_uri=XXX
Parameter state is optional. It will be returned in step 4 so application can validate if response is not crafted by someone else.
Parameter redirect_uri is optional if you specified only one Callback URL. If you have more than one Callback URL parameter redirect_uri is mandatory. Please avoid special chars like & (multiple), # in redirect_uri.
URL will be used in step 4. redirect_uri should base on defined earlier Callback URL.
Example:
Callback URL: http://myadomain.com/auth/connect
Auth URL: https://www.olx.ua/oauth/authorize/?client_id=123&response_type=code&state=x93ld3v&scope=read+write+v2&redirect_uri=http://myadomain.com/auth/connect
Example 2:
Callback URL: http://myadomain.com/auth/connect
Auth URL: https://www.olx.ua/oauth/authorize/?client_id=123&response_type=code&state=x93ld3v&scope=read+write+v2
If you have only one Callback URL you don't have to pass redirect_uri parameter.
User is redirected to OLX login screen User logs in and authorize client User is redirected back to redirect_uri with some additional query parameters: code and state (optional).
Example: http://myadomain.com/auth/connect?code=d34feg43g456g&state=x93ld3v
Application exchange received code to access token by grant type authorization_code.

Request to get access token, sent to /api/open/oauth/token endpoint, should have:

```
{
 "grant_type": "authorization_code",
 "client_id": "",
 "client_secret": "",
 "code": "",
 "scope": "v2 read write",
 "redirect_uri": "http://myadomain.com/auth/connect"}
```

Note: redirect_uri parameter is optional unless you use parameter redirect_uri in Auth URL in step 1. If you use redirect_uri in step 1, then redirect_uri is also mandatory in request in step 5.

Grant type: refresh_token - when access token is expired

When access token expires use saved refresh token to acquire new access token.
Refresh token is special token used to obtain new access token without need to authorization with user credentials again.
Notice: refresh token is valid only for one month (2592000 seconds).
Request to refresh access token, sent to /api/open/oauth/token endpoint, should have:

```
{
 "grant_type": "refresh_token",
 "client_id": "",
 "client_secret": "",
 "refresh_token": ""}
```

New access token will be issued.
Refresh Token Response:

- A new refresh token will be issued. We issue a new refresh token each day, so if the token was issued that day, the most recent token will be returned.
- Since the refresh token's validity is one month, you should store the new refresh token and use it in your subsequent requests.
- If the refresh token is not used for a month, it will be invalidated and you will need to re-authenticate the user.

Please store access token and refresh token and keep it in safe place.

Grant type: client_credentials - authenticate as Client application

Required fields:

```
{
 "grant_type": "client_credentials",
 "client_id": "",
 "client_secret": "",
 "scope": "v2 read write"}
```

Now you're logged in with Client application context. You can obtain list of categories, cities, etc. (but not add advert!). To perform actions on user account you must use other grant type and log in with User context.

Access token usage

From now on all request to any API endpoints should be performed with authorization header: Authorization: Bearer ACCESS_TOKEN.

Example:

```
curl -X POST -H “Content-Type: application/json” -d ‘{ data }’ -H “Authorization: Bearer 011c945f30ce2cbafc452f39840f025693339c42” -H “Version: 2.0” “https://www.olx.ua/api/partner/adverts”
```

Application with multiple OLX users

Overview

Lets say you have your application that has its own users and each user needs to manage his olx account (post adverts, reply to messages etc.). Flow is actually no different than for single user.

- Your app has client_id and client_secret
- Your app user needs to connect his account to OLX and in return he will get code
- Code is used one time only to get access_token and refresh token
- Your app user is authenticated with access_token until it gets expired
- Your app user gets new access_token by using refresh token

As you see this is exactly the same as you would have single user. As soon as user is authenticated, OLX API works in context of that user.

Obtaining client_id and client_secret

As you already know, you get it by filling online form. If your request is accepted you will get them by email.

Connecting app user account to OLX

Usually on your app there will be a button “connect olx account” or it can be done on authentication itself “login with olx” or something similar. This action is connected with uri:

```
/oauth/authorize/?client_id=XXX&response_type=code&state=XXX&redirect_uri=XXX&scope=read write v2
```

client_id - your app client id that you got by email

response_type - is set to “code”, that is oauth 2.0 standard

state - is your random hash that you need to save for the time of request, when you get response with state you need to check if it is the same as your saved one just to be sure that it is correct response (and there is no one in the middle trying to give you false secret data)

redirect_uri - is the uri where response with code will be sent

scope - is the scope you ask for, typically it is “read write v2”

Whenever user triggers that uri, he/she is redirected to OLX login page (or account if is already logged in) and after authentication and accepting application connection is redirected back to redirect_uri with code and state.

code - is one time authorization token

scope - is the scope that you sent on request

Example: http://myadomain.com/auth?code=d34feg43g456g&state=x93ld3v

Getting access_token and refresh_token for user

Now, finally you can get user api credentials that will be used for API authentication. Your app needs to make POST request for that:

```
POST /api/open/oauth/token
{
```

```
 "grant_type": "authorization_code",
 "client_id": "<your client_id>",
 "client_secret": "<your client_secret>",
 "code": "<code from previous action>",
 "scope": "v2 read write"}
```

In response you will get user data:

```
{
 "access_token": "454c3cd39a980500e9b787e03d53ec5c320f644b",
 "expires_in": 86400,
 "token_type": "bearer",
 "scope": "v2 read write",
 "refresh_token": "12a13560163da7901d7f74c89fc5df3ea7625942"}
```

acccess_token - is a token that user will user to authenticate with API

expires_in - indicates when access_token will expire

token_type - is always set to bearer, this means that access_token will be sent in every request header as Bearer

scope - is your requested scope, typically “v2 read write”

refresh_token - is a token that will be needed to refresh expired access_token. Token is valid for one month (2592000 seconds).

From now on you will add to each api request of that user a header “Authorization: Bearer 454c3cd39a980500e9b787e03d53ec5c320f644b”. You need to store securly each user’s access_token and refresh_token. Whenever your app user will authenticate to your app and manage olx account, you will use this data for OLX API requests. Refreshing access_token with refresh_token

Every period of time access_token will expire. When it does you need to make call to refresh it (and get new one).

```
POST /api/open/oauth/token{
 "grant_type": "refresh_token",
 "client_id": "<your client_id>",
 "client_secret": "<your client_secret>",
 "refresh_token": "<your user's refresh_token>"}
```

grant_type - is set to “refresh_token”, which means user is refreshing access_token with refresh_token

client_id, client_secret - are your app secrets

refresh_token - is your app user’s refresh_token that you got for him in previous requests.

Response depends on state of access token:

- when access token is expired, in response client will receive new access token.
- if token was not expired yet, client will receive same token, with information about remaining time left.

Notice: refresh token is valid for one month (2592000 seconds). Also it can be changed when new access token is generated.

You need to update access and refresh token in your database. Please keep them safe. More users

Notice that this whole flow has to be completed for each app user. So finally you will have data stored something like that:

User	Access Token	Refresh Token
user1@domain.com	6c29bb64200ba868442b95cf16d14122ecd95816	c9fd39b05bdf01b233915b9

User	Access Token	Refresh Token
user2@test.com	011c945f30ce2cbafc452f39840f025693339c42	1c6637a8f2e1f75e06ff99848

(…)

Now, when your application wants to perform any action in context of these any user, it has to use corresponding data (access_token, refresh_token).

Lets say, your app user user2@test.com wants to add new advert, then your requests should look like this:

```
curl -X POST -H "Content-Type: application/json" -d '{ data }' -H "Authorization: Bearer 011c945f30ce2cbafc452f39840f025693339c42" "https://www.olx.ua/api/partner/adverts"
```

Notice which token is used.

Another case: application wants to fetch all threads of user1@domain.com:

```
curl -X GET  -H "Authorization: Bearer 6c29bb64200ba868442b95cf16d14122ecd95816" "https://www.olx.ua/api/partner/threads"
```

Same rule applies to all endpoints in OLX API.

Security Scheme Type	OAuth2
authorizationCode OAuth Flow	**Authorization URL:** https://www.olx.ua/oauth/authorize **Token URL:** https://www.olx.ua/api/open/oauth/token **Refresh URL:** https://www.olx.ua/api/open/oauth/token **Scopes:** v2 - access to api v2 write - modify resources read - read resources
clientCredentials OAuth Flow	**Token URL:** https://www.olx.ua/api/open/oauth/token **Refresh URL:** https://www.olx.ua/api/open/oauth/token **Scopes:** v2 - access to api v2 write - modify resources read - read resources

Troubleshooting

The aim of this section is to familiarise you with the possible errors that may appear during the development process or directly after launching the integration for the very first time.

Error handling

This API uses standard HTTP status codes to indicate the status of a response.

Name	Code	Description
Bad request	400	The request was unacceptable. For example validation didn't pass.
Unauthorized	401	The request has not been applied because it lacks valid authentication credentials for the target resource.
Forbidden	403	The server understood the request, but is refusing to fulfill it

Name	Code	Description
Not Found	404	The server has not found anything matching the request URI
Not acceptable	406	The server is unable to return a response in the format that was requested the client
Unsupported Media Type	415	The server is refusing to service the request because the entity of the req in a format not supported by the requested resource for the requested me
Too many requests	429	Too many requests hit the API too quickly
Server error	500	An error that is not caused by client, something bad happend on server

Example

```
{
 "error": {
  "status": 400,
  "title": "Invalid request",
  "detail": "Data validation error occurred",
  "validation": [
   {
    "field": "title",
    "title": "Musisz podać tytuł",
    "detail": "Musisz podać tytuł"
   },
   {
    "field": "description",
    "title": "Musisz podać opis",
    "detail": "Musisz podać opis"
   }
   ]
 }}
```

Authorization errors

These errors are related to the authorization process. Below you can find the most common situations and proposed solutions.

1. Missing parameter: code is required

HTTP code: 400 Bad Request

```
{
 "error": "invalid_request",
 "error_description": "Missing parameter: \"code\" is required",}
```

Solution:

- provide missing code parameter in the request

Example:

```
{
 "grant_type":"authorization_code"
 "scope":"read write v2"
 "client_id":"<your client_id>"
 "client_secret":"<your client_secret>"
 "code":"<one time authorization token>"}
```

2. Authorization code doesn't exist or is invalid for the client

HTTP code: 400 Bad Request

```
{
 "error": "invalid_grant",
 "error_description": "Authorization code doesn't exist or is invalid for the client",}
```

Solution:

- provide valid code parameter in the request (please remember that it is valid for 10 minutes only)

3. The grant type was not specified in the request

HTTP code: 400 Bad Request

```
{
 "error": "invalid_request",
 "error_description": "The grant type was not specified in the request",}
```

Solution:

- provide required grant_type parameter in the request

4. The scope requested is invalid for this client

HTTP code: 400 Bad Request

```
{
 "error": "invalid_scope",
 "error_description": "The scope requested is invalid for this client",}
```

Solution:

- verify provided scope
- make sure that your API account is allowed to use a given scope

5. Client is not active

HTTP code: 401 Unauthorized

```
{
 "error": "invalid_client",
 "error_description": "Client is not active",}
```

Solution:

- verify client_id provided in the request

6. The client credentials are invalid

HTTP code: 400 Bad Request

```
{
 "error": "invalid_client",
 "error_description": "The client credentials are invalid",}
```

Solution:

- verify client_id and client_secret provided in the request

7. The access token provided is invalid

HTTP code: 401 Unauthorized

```
{
 "error": "invalid_token",
 "error_description": "The access token provided is invalid",}
```

Solution:

- verify access_token provided in the request

8. Insufficient scope

HTTP code: 401 Unauthorized

```
{
   "error": "insufficient_scope",
   "error_description": "The request requires higher privileges than provided by the access token",
   "error_human_title": "Insufficient scope."}
```

Solution:

- you need to authorize yourself with a higher privileges
- make sure that you are authorized with a proper scopes: read write v2 instead of read write

9. Invalid owner in token

```
{
 "error": {
   "status": 400,
   "title": "Bad Request",
   "detail": "Invalid owner in token"
 }}
```

Solution:

- make sure that you are authenticated in the user context - "grant_type":"authorization_code" instead of "grant_type":"client_credentials"

10. The grant type is unauthorized for this client_id

```
{
   "error": "unauthorized_client",
   "error_description": "The grant type is unauthorized for this client_id",
   "error_human_title": "Unauthorized client."}
```

Solution:

- your API account is not allowed to use a given grant_type
- reach out to us in order to check it out

11. Invalid refresh token

```
{
   "error": "invalid_grant",
   "error_description": "Invalid refresh token",
   "error_human_title": "Provided authorization credentials are invalid or expired."}
```

Solution:

- make sure that refresh_token is valid (please remember that it lasts for 2592000 seconds and can be changed when new access token is generated)
- authenticate yourself once again in order to receive a new one

Publishing errors

These errors happen when something goes wrong during the advert publishing.

1. Category with given ID doesn't exists

```
{
 "error": {
  "status": 400,
  "title": "Bad Request",
  "detail": "Category with given ID doesn't exists"
 }}
```

Solution:

- provide valid category_id in the request

2. Fix the category

```
{
 "error": {
  "status": 400,
  "title": "Invalid request",
  "detail": "Data validation error occurred",
  "validation": [
    {
     "field": "category_id",
     "title": "Fix the category",
     "detail": "Fix the category"
    }
  ]
 }}
```

Solution:

- provide valid category_id in the request
- make sure that the category_id is a leaf category:

```
GET /api/partner/categories/1755
{
 "data": {
    "id": 1755,
    "name": "Praca inżynieryjna, techniczna",
    "parent_id": 1447,
    "photos_limit": 0,
    "is_leaf": true
 }}
```

3. Error while decoding JSON data: Syntax error

```
{
 "data": {
  "error": {
   "status": 400,
   "title": "Bad Request",
   "detail": "Error while decoding JSON data: Syntax error"
  }
 }}
```

Solution:

- make sure that the payload you are sending does not contain any extra fields
- make sure that the field names are valid and do not contain any typos

4. Partner is not allowed to use external URL

```
{
 "error": {
  "status": 400,
  "title": "Bad Request",
  "detail": "Partner is not allowed to use external URL"
 }}
```

Solution:

- your API account is not allowed to use external_url field
- this feature is available only for a Jobs category in PL
- reach out to us in order to enable this option

5. Invalid value: district_id

```
{
 "error": {
  "status": 400,
  "title": "Invalid request",
  "detail": "Data validation error occurred",
  "validation": [
    {
     "field": "district_id",
     "title": "Invalid value"
    }
  ]
 }}
```

Solution:

- verify district_id provided in the request:

```
GET /api/partner/cities/{cityId}/districts
```

6. Your coordinates are too far from picked location

```
{
 "error": {
  "status": 400,
  "title": "Invalid request",
  "detail": "Data validation error occurred",
  "validation": [
```

```
    {
      "field": "district/city_id",
      "title": "Your coordinates are too far from picked location."
    }
  ]
}}
```

Solution:

- verify if latitude and longitude fields are valid for a given district/city_id:

```
GET /api/partner/locations/?latitude={lat}&longitude={lon}
```

7. This value is not valid: attributes

```
{
 "error": {
   "status": 400,
   "code": 400,
   "title": "Invalid request",
   "detail": "Data validation error occurred",
   "validation": [
     {
       "field": "attributes",
       "title": "This value is not valid."
     }
   ]
 }}
```

Solution:

- make sure that the attributes array contains code and value keys only:

```
"attributes": [
  {
    "code": "type",
    "value": "fulltime"
  },
  {
    "code": "contract",
    "value": "contract"
  },
  {
    "code": "manager",
    "value": "0"
  },
  {
    "code": "remote_recruitment",
    "value": "0"
  }]
```

8. Invalid value: params.state

```
{
 "error": {
   "status": 400,
   "title": "Invalid request",
   "detail": "Data validation error occurred",
   "validation": [
     {
```

```
      "field": "params.state",
      "title": "Invalid value"
    }
  ]
}}
```

Solution:

- verify state value in the attributes array

9. Image error: Remote file not exists

```
{
 "error": {
   "status": 400,
   "title": "Bad Request",
   "detail": "Image error: Remote file not exists"
 }}
```

Solution:

- verify all URLs provided in the images array

10. Image error: Image limit exceeded

```
{
 "error": {
   "status": 400,
   "title": "Bad Request",
   "detail": "Image error: Image limit exceeded"
 }}
```

Solution:

- make sure that the request does not contain more images than it is allowed:

```
GET /api/partner/categories/1581
{
 "data": {
    "id": 1581,
    "name": "Bluzki i koszulki",
    "parent_id": 642,
    "photos_limit": 8,
    "is_leaf": true
 }}
```

11. Unsupported API version

HTTP code: 404 Not Found

```
{
 "error": {
   "type": "NotFoundException",
   "message": "Unsupported API version"
 }}
```

Solution:

- make sure that the URL you are trying to call to is valid

12. Advert not found

```
{
 "error": {
   "status": 404,
   "title": "Not Found",
   "detail": "Advert not found"
 }}
```

Solution:

- make sure that the advert ID is valid

13. You are not the owner of this ad

```
{
 "error": {
   "status": 400,
   "title": "Invalid request",
   "detail": "Data validation error occurred",
   "validation": [
     {
       "field": "ad",
       "title": "You are not the owner of this ad"
     }
   ]
 }}
```

Solution:

- you are not allowed to manage the ads created by other users

14. Too many capital letters

```
{
   "error": {
      "status": 400,
      "title": "Invalid request",
      "detail": "Data validation error occurred",
      "validation": [
         {
            "field": "title",
            "title": "Too many capital letters"
         }
      ]
   }}
```

Solution:

- make sure that the title or description does not contain more than 50% text written in capital letters

15. Field is not valid. Emails and www addresses are not allowed

```
{
   "error": {
      "status": 400,
      "title": "Invalid request",
      "detail": "Data validation error occurred",
      "validation": [
```

```
        {
          "field": "title",
          "title": "Field is not valid. Emails and www addresses are not allowed"
        }
      ]
    }}
```

Solution:

- make sure that the title or description does not contain any e-mail/www address

16. Field is not valid. Phone numbers are not allowed

```
{
  "error": {
    "status": 400,
    "title": "Invalid request",
    "detail": "Data validation error occurred",
    "validation": [
        {
          "field": "title",
          "title": "Field is not valid. Phone numbers are not allowed"
        }
      ]
    }}
```

Solution:

- make sure that the title or description does not contain any phone number

17. Field contains to much punctuation

```
{
  "error": {
    "status": 400,
    "title": "Invalid request",
    "detail": "Data validation error occurred",
    "validation": [
        {
          "field": "title",
          "title": "Field contains to much punctuation"
        }
      ]
    }}
```

Solution:

- following characters cannot be provided in the title and in the description three times in a row: ! ? . , - = + # % & @ * _ > < : ( ) |

18. Deactivate advert - ad has to be active

```
{
  "error": {
    "status": 400,
    "title": "Invalid request",
    "detail": "Data validation error occurred",
    "validation": [
        {
```

```
            "field": "ad",
            "title": "Ad has to be active"
        }
    ]
}}
```

Solution:

- make sure that the advert you want to deactivate is active

19. Delete advert - invalid status

```
{
  "error": {
    "status": 400,
    "title": "Invalid request",
    "detail": "Data validation error occurred",
    "validation": [
        {
            "field": "ad",
            "title": "Invalid status"
        }
    ]
}}
```

Solution:

- make sure that the advert you want to delete is not active
- deactivate the advert before deletion:

```
POST /api/partner/adverts/{advertId}/commands
{
 "command": "deactivate",
 "is_success": true // this flag indicates whether you have succeeded in selling the product or not}
```

20. Cannot refresh advert

```
{
  "error": {
    "status": 400,
    "title": "Invalid request",
    "detail": "Data validation error occurred",
    "validation": [
        {
            "field": "time",
            "title": "You cannot refresh ad more often than once in 14 days"
        }
    ]
}}
```

Solution:

- depending on the country you cannot refresh advert more than once in a given period of time
- please wait until the refresh option will be available for the advert

21. City with given ID doesn't exists

```
{
  "error": {
```

```
    "status": 400,
    "title": "Bad Request",
    "detail": "City with given ID doesn't exists"
  }}
```

Solution:

- verify city_id provided in the request:

```
GET /api/partner/cities/{cityId}
{
  "error": {
    "status": 404,
    "title": "Not Found",
    "detail": "City not found"
  }}
```

22. Invalid phone format

```
{
  "error": {
    "status": 400,
    "title": "Invalid request",
    "detail": "Data validation error occurred",
    "validation": [
      {
        "field": "phone",
        "title": "Invalid phone format"
      }
    ]
  }}
```

Solution:

- make sure that the phone provided in the request is valid

23. Missing required 'Version' header

```
{
  "data": {
    "error": {
      "status": 400,
      "title": "Bad Request",
      "detail": "Missing required 'Version' header!"
    }
  }}
```

Solution:

- add "Version": "2.0" header to your request

Payment errors

Errors described in this section are related to the payment process

1. No possibility to buy the packet

```
{
```

```
  "error": {
    "status": 400,
    "title": "Bad Request",
    "detail": "There is no variant with size 123 for category 123"
  }}
```

Solution:

- verify if the packet you are interested in is available for a given category:

```
GET /api/partner/packets?category_id={categoryId}
```

2. Invalid payment method

```
{
  "error": {
    "status": 400,
    "title": "Bad Request",
    "detail": "Invalid payment method"
  }}
```

Solution:

- make sure that the payment_method provided in the request is valid:

```
GET /api/partner/users/me/payment-methods
```

3. Payment method postpaid is not activated

```
{
  "error": {
    "status": 400,
    "title": "Bad Request",
    "detail": "Payment method 'postpaid' is not activated"
  }}
```

Solution:

- postpaid method is not activated for the OLX account
- reach out to the local OLX support team to activate this option

4. Not enough credits

```
{
  "error": {
    "status": 400,
    "title": "Bad Request",
    "detail": "Not enough credits"
  }}
```

Solution:

- make sure that there is enough credits on your OLX account to pay for a given feature:

```
GET /api/partner/users/me/account-balance
```

Users

Get authenticated user

Get currently Authenticated User

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/users/me

Response samples

- 200

Content type

application/json

Copy

{

- "id": 123,
- "email": "john@mail.com",
- "status": "confirmed",
- "name": "John",

"phone": 123123123,

"phone_login": 123123123,

"created_at": "2018-01-29 14:04:13",

"last_login_at": "2018-01-30 08:20:28",

"avatar": null,

"is_business": true

}

Get user

Get any User

AUTHORIZATIONS:

access_token

PATH PARAMETERS

id
required

integer

Responses

200

Status 200

GET/users/{id}

Response samples

- 200

Content type

application/json

Copy


```
{
  "id": 1,
  "name": "John",
  "avatar": null
}
```


Get account balance

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/users/me/account-balance

Response samples

- 200

Content type

application/json

Copy

```
{
  "sum": 6988.02,
  "wallet": 6988.02,
  "bonus": 0,
  "refund": 0,
  "currency": "PLN"
}
```

Get available payment methods

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/users/me/payment-methods

Response samples

- 200

Content type

application/json

Copy

[

- "account",

-

- "postpaid"

-

]

Cities & Districts

List of country regions

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/regions

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "id": 1,
    "name": "Wielkopolskie"
  }
]
```


Get region

AUTHORIZATIONS:

access_token

PATH PARAMETERS

regionId required	integer Region ID

Responses

200

Status 200

GET/regions/{regionId}

Response samples

- 200

Content type

application/json

Copy


```
{
  "id": 1,
  "name": "Wielkopolskie"
}
```


Get cities

Get list of cities

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

offset	integer Starting element
limit	integer Elements limit per page (default 1000)

Responses

200

Status 200

GET/cities

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "id": 627,
    "region_id": 123,
    "name": "Aleksandrów Kujawski",
    "county": "aleksandrowski",
```

"municipality": "Aleksandrów Kujawski",

"latitude": 52.86653,

"longitude": 18.69801

}

]

Get city

AUTHORIZATIONS:

access_token

PATH PARAMETERS

cityId required	string

Responses

200

Status 200

GET/cities/{cityId}

Response samples

- 200

Content type

application/json

Copy

{

"id": 627,

"region_id": 123,

"name": "Aleksandrów Kujawski",

"county": "aleksandrowski",

"municipality": "Aleksandrów Kujawski",

"latitude": 52.86653,

"longitude": 18.69801

}

Get city districts

AUTHORIZATIONS:

access_token

PATH PARAMETERS

cityId required	string

Responses

200

Status 200

GET/cities/{cityId}/districts

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    {
      "id": 97,
      "city_id": 5659,
      "name": "Aniołki",
```

"latitude": 54.36306,

"longitude": 18.63193

}

]

Get districts

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/districts

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

[

{

```
"id": 97,

"city_id": 5659,

"name": "Aniołki",

"latitude": 54.36306,

"longitude": 18.63193

}
]
```


Get district

AUTHORIZATIONS:

access_token

PATH PARAMETERS

districtId required	string

Responses

200

Status 200

GET/districts/{districtId}

Response samples

- 200

Content type

application/json

Copy

{

"id": 97,

"city_id": 5659,

"name": "Aniołki",

"latitude": 54.36306,

"longitude": 18.63193

}

Get locations

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

latitude required	number Location latitude
longitude required	number Location longitude

Responses

200

Status 200

GET/locations

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

```
[
  {
    "city": {},
    "district": {}
```

•

}

]

Languages & currencies

Get languages

Get site available languages

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/languages

Response samples

• 200

Content type

application/json

Copy

Expand allCollapse all

[

•

{

•

•

"code": "pl",

•

•

"is_default": true

}

]

Get currencies

Get site available currencies

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/currencies

Response samples

200

Content type

application/json

Copy

Expand allCollapse all

[

{

"code": "PLN",

"label": "zł",

"is_default": true

}

]

Categories & attributes

Get categories

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

parent_id	integer Parent category ID

Responses

200

Status 200

GET/categories

Response samples

200

Content type

application/json

Copy

Expand allCollapse all

[

{

```
"id": 1291,
"name": "Akcesoria kuchenne\\",
"parent_id": 1409,
"photos_limit": 0,
"is_leaf": true
}
```


]

Get category

AUTHORIZATIONS:

access_token

PATH PARAMETERS

categoryId required	integer Identifier of the Category

Responses

200

Status 200

GET/categories/{categoryId}

Response samples

- 200

Content type

application/json

Copy


```
{
  "id": 1291,
  "name": "Akcesoria kuchenne\\",
  "parent_id": 1409,
  "photos_limit": 0,
  "is_leaf": true
}
```

Get category attributes

Gets attribute definitions for given category

AUTHORIZATIONS:

access_token

PATH PARAMETERS

categoryId required	integer Category ID

Responses

200

Status 200

GET/categories/{categoryId}/attributes

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

[

- {

- "code": "price",

- "label": "Cena",

"unit": null,

"validation": {},

"values": [ ]

}

]

Get category suggestions

Gets category suggestions for a given Ad title

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

q required	string >= 3 characters Ad title

Responses

200

Status 200

GET/categories/suggestion

Response samples

- 200

Content type
application/json

Copy

Expand allCollapse all


```
[
  {
    "id": 451,
    "name": "Pozostała elektronika",
    "path": []
  }
]
```


Threads & messages

Get threads

Get threads

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

advert_id	integer Advert ID
interlocutor_id	integer User ID
offset	integer Starting element
limit	integer Limit

Responses

200

Status 200

GET/threads

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

[

- {

- "id": 1,

- "advert_id": 1,

"interlocutor_id": 1,

"total_count": 1,

"unread_count": 0,

"created_at": "2018-01-30 08:26:36",

"is_favourite": false

}

]

Get thread

Get thread

AUTHORIZATIONS:

access_token

PATH PARAMETERS

threadId	integer

required

Responses

200

Status 200

GET/threads/{threadId}

Response samples

- 200

Content type

application/json

Copy


```
{
  "id": 1,
  "advert_id": 1,
  "interlocutor_id": 1,
  "total_count": 1,
  "unread_count": 0,
```

-
-

"created_at": "2018-01-30 08:26:36",

-
-

"is_favourite": false

-

}

Get messages

Get messages from given thread

AUTHORIZATIONS:

access_token

PATH PARAMETERS

threadId required	integer

Responses

200

Status 200

GET/threads/{threadId}/messages

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

[

```
{

"id": 1,

"thread_id": 1,

"created_at": "2018-01-30 08:26:36",

"type": "sent",

"text": "This is my message",

"attachments": null,

"is_read": true
```

•

```
}
```

Post Message

Posts new message in a given thread. Field 'phone' is optional and depends on the category - used in Jobs categories right now.

AUTHORIZATIONS:

access_token

PATH PARAMETERS

threadId required	integer

REQUEST BODY SCHEMA: application/json

text required	string Text of the message
attachments	Array of objects

Responses

200

Status 200

POST/threads/{threadId}/messages

Request samples

• **Payload**

Content type

application/json

Copy

Expand allCollapse all

```
{
```

•

```
"text": "string",
```

-
-

"attachments": [

-
  -

{}

  -

]

}

Get message

AUTHORIZATIONS:

access_token

PATH PARAMETERS

threadId required	integer
messageId required	integer

Responses

200

Status 200

GET/threads/{threadId}/messages/{messageId}

Response samples

- 200

Content type

application/json

Copy

{

"id": 1,

"thread_id": 1,

"created_at": "2018-01-30 08:26:36",

"type": "sent",

"text": "This is my message",

"attachments": null,

"is_read": true

}

Take action on thread

AUTHORIZATIONS:

access_token

PATH PARAMETERS

threadId required	integer

REQUEST BODY SCHEMA: application/json

command required	string Enum: "mark-as-read" "set-favourite" Commands mark-as-read - to mark thread as read, set-favourite - to set thread as favourite
is_favourite	boolean Set is thread favourite or not. Required for set-favourite command

Responses

204

Status 204

POST/threads/{threadId}/commands

Request samples

- **Payload**

Content type

application/json

Copy

```
{
  "command": "mark-as-read",
  "is_favourite": true
}
```

Paid features

Get available paid features

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/paid-features

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "code": "promoted_ad_7",
    "type": "topads",
    "duration": 7,
```

-
-

"name": "Wyróżnienie ogłoszenia na 7 dni"

-

}

]

Get active paid features

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer Advert ID

Responses

200

Status 200

GET/adverts/{advertId}/paid-features

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

[

-

{

-

-

"code": "promoted_ad_7",

"type": "topads",

"duration": 7,

"name": "Wyróżnienie ogłoszenia na 7 dni",

"valid_to": "2018-02-05 12:12:12"

}

Purchase paid feature

AUTHORIZATIONS:

None

PATH PARAMETERS

advertId required	integer Advert ID

REQUEST BODY SCHEMA: application/json

payment_method required	string Enum: "account" "postpaid"

code required	string

Responses

204

Status 204

POST/adverts/{advertId}/paid-features

Request samples

- Payload

Content type

application/json

Copy

```
{
  "payment_method": "account",
  "code": "string"
}
```

Adverts

Get user adverts

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

offset	integer Offset

limit	integer Limit
external_id	string External ID
category_ids	string Comma separated list of categories IDs

Responses

200

Status 200

GET/adverts

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

```
{
  "data": [
    {}
  ]
}
```

Create advert

Validation rules

- Following characters cannot be provided in the title and in the description three times in a row: ! ? . , - = + # % & @ * _ > < : ( ) |
- The amount of capital letters in the title and in the ad description cannot be greater than 50% of a whole text.
- The title has to be at least 16 characters long and cannot be longer than 70 characters.
- The description has to be at least 80 characters long and cannot be longer than 9000 characters.
- E-mail addresses and phone numbers are not allowed in the title and in the description.
- Salary currency has to be written in uppercase (for example: EUR instead of eur).
- Lower or upper value of the salary cannot be greater than 99999999999999.

Advert lifecycle

- Post new advert
- In response you will get current status of posted advert:
  - if status is limited then you must buy packet for advert or category and activate advert (check out Packets section and Adverts section)
  - if status is new then flow goes to point 3.
- Advert is awaiting for moderation. Usually it takes some seconds.
  - if advert is accepted it will be activated automatically and visible for all users
  - if advert is rejected (possible reasons: scam, illegal items offered etc)
  - if advert is rejected but user can fix issues, and advert goes back to moderation
- Advert is active. How long advert will be valid is defined in field valid_to in advert response.

- When “valid to” date is passed, advert becomes outdated - user can activate advert again.

User can manually deactivate advert, status is set to removed_by_user. Deactivated advert can be activated again. To completly remove advert user should deactivate it at first and then delete it (check out Adverts section).

Advert statuses

- new: fresh advert before activation and moderation
- active: visible on OLX
- limited: advert exceeded limit of free adverts in selected category
- removed_by_user: manually removed by user
- outdated: advert reached expiration date
- unconfirmed: waiting for confirmation
- unpaid: waiting for payment
- moderated: negative moderation result
- blocked: blocked by moderation
- disabled: disabled by moderation, offer blocked and waiting for verification
- removed_by_moderator: removed by moderator

Posting Advert

To add an advert client have to send request to /api/partner/adverts endpoint.

This endpoint requires POST HTTP method, and expects data to be sent as JSON along with Content-Type: application/json header.

Remember to send Authorization: Bearer ACCESS_TOKEN and Version: 2.0 headers either.

Using this endpoint creates advert in the name of currently authenticated user.

You must send all required fields (as it's described in /api/partner/adverts endpoint reference), inlcuding required attributes.

For list of available categories, attributes, cities please check out appropriate endpoint references like /api/partner/categories, /api/partner/cities and so on.

You can get list of required attributes by /api/partner/categories/ID/attributes endpoint where ID is the category ID you choosed. Endpoint return list of required and optional attributes to create advert - attributes vary in different countries and categories.

Important: please note that attributes with type salary and price have different structures than normal attributes. For more details about those attributes please read Create advert endpoint description.

When some required fields are missing in response you will get a list of errors as a result:

```
{
 "error": {
  "status": 400,
  "title": "Invalid request",
  "detail": "Data validation error occurred",
  "validation": [
    {
      "field": "title",
      "title": "Musisz podać tytuł",
      "detail": "Musisz podać tytuł"
```

```
    },
    {
      "field": "description",
      "title": "Musisz podać opis",
      "detail": "Musisz podać opis"
    }
  ]
}}
```


API will return full advert model if request succeded:


```
{
  "id": 123,
  "status": "active",
  "url": "https://www.olx.ua/oferta/url.html",
  "created_at": "2018-02-02 09:35:16",
  "activated_at": "2018-02-02 09:32:52",
  "valid_to": "2018-03-04 09:32:52",
  "title": "This is title",
  "description": "This is description",
  "category_id": 123,
  "advertiser_type": "private",
  "external_id": "12345",
```

```
"external_url": "http://myshop.com/advert/123",
"contact": {
  "name": "John",
  "phone": "2341235435,1245134254,12452145"
},
"location": {
  "city_id": 1,
  "district_id": null,
  "latitude": 53.123,
  "longitude": 17.123
},
"images": [
  {
    "url": "https://www.olx.ua/advert-picture-1.jpg"
  },
  {
    "url": "https://www.olx.ua/advert-picture-2.jpg"
  }
],
"price": {
  "value": 123,
```

```
  "currency": "PLN",
  "negotiable": false,
  "trade": false,
  "budget": false
},
"salary": null,
"attributes": [
  {
    "code": "model",
    "value": "cts",
    "values": null
  },
  {
    "code": "year",
    "value": "2015",
    "values": null
  }
],
"courier": null}
```


If status is new, it's mean that advert will be activated soon (after moderation process). But if status is limited you must perform two extra steps:

- buy “packet” for a single advert (check out /api/partner/adverts/ID/packets) or whole category (check out /api/partner/users/me/packets).

- activate advert (checkout /api/partner/adverts/ID/commands - activate command)

After some time (usually few seconds) advert should become active and be visible to all users.

You can deactivate active advert with deactivate command (checkout /api/partner/adverts/ID/commands). You can activate inactive advert with activate command.

If you want to completely remove advert please use DEL /api/partner/adverts/ID/ endpoint.

You can buy extra paid features for active advert. For more details check out “Paid features” section.

AUTHORIZATIONS:

access_token

REQUEST BODY SCHEMA: application/json

title required	string
description required	string May contain html tags (only in Jobs category) <ul><li><p>
category_id required	integer
advertiser_type required	string Enum: "private" "business"
external_url	string Advert's URL in origin system
external_id	string Advert's ID in origin system
contact required	object

location required	object
images	Array of objects
price	object Used by most of the categories, i.e. cars, houses, clothes, etc. Required by mo mentioned categories.
salary	object Used by some of the categories, i.e. jobs. Required by most of the mentioned
attributes required	Array of objects
courier	boolean Is delivery possible. If true that means that delivery is possible. (Available in PT, RO).
auto_extend_enabled	boolean Should the advert be automatically extended when it expires. Omitting this fi that auto extend is disabled.
product_safety_regulation	object (ProductSafetyRegulation)

Responses

200

Status 200

POST/adverts

Request samples

- Payload

Content type

application/json

Copy

Expand allCollapse all

```
{
```

-

```
"title": "string",
```

"description": "string",

"category_id": 0,

"advertiser_type": "private",

"external_url": "string",

"external_id": "string",

"contact": {

"name": "string",

"phone": "string"

},

"location": {

"city_id": 0,

"district_id": 0,

"latitude": 0,

"longitude": 0

},

"images": [

```
        {}
            •
],
•
"price": {
•
            •
        "value": 0,
            •
            •
        "currency": "string",
            •
            •
        "negotiable": true,
            •
            •
        "trade": true,
            •
            •
        "budget": true
            •
},
•
```

"salary": {

"value_from": 0,

"value_to": 0,

"currency": "string",

"negotiable": true,

"type": "hourly"

},

"attributes": [

{}

```
],
"courier": true,
"auto_extend_enabled": true,
"product_safety_regulation": {
    "placed_before_2024": false,
    "manufacturer": {},
    "contact_person": {},
    "warning_and_safety": "Handle with care. Keep away from children."
```

}

}

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

{

"data": {

"id": 123,

"status": "active",

"url": "https://www.olx.ua/oferta/url.html",

"created_at": "2018-02-02 09:35:16",

"activated_at": "2018-02-02 09:32:52",

"valid_to": "2018-03-04 09:32:52",

"title": "This is title",

"description": "This is description",

"category_id": 123,

"advertiser_type": "private",

"external_id": 12345,

"external_url": "http://myshop.com/advert/123",

"contact": {},

"location": {},

"images": [],

"price": {},

"salary": null,

"attributes": [],

"courier": null,

"auto_extend_enabled": true,

"product_safety_regulation": {}

}

}

Get advert

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer

Responses

200

Status 200

GET/adverts/{advertId}

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

{

"data": {

"id": 123,

-
-

"status": "active",

-
-

"url": "https://www.olx.ua/oferta/url.html",

-
-

"created_at": "2018-02-02 09:35:16",

-
-

"activated_at": "2018-02-02 09:32:52",

-
-

"valid_to": "2018-03-04 09:32:52",

-
-

"title": "This is title",

-
-

"description": "This is description",

-

-

```
"category_id": 123,
```

-

-

```
"advertiser_type": "private",
```

-

-

```
"external_id": 12345,
```

-

-

```
"external_url": "http://myshop.com/advert/123",
```

-

-

```
"contact": {},
```

-

-

```
"location": {},
```

-

-

```
"images": [],
```

-

-

```
"price": {},
```

```
    "salary": null,
    "attributes": [],
    "courier": null,
    "auto_extend_enabled": true,
    "product_safety_regulation": {}
  }
}
```


Update advert

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer

REQUEST BODY SCHEMA: application/json

required

title required	string
description required	string May contain html tags (only in Jobs category)
category_id required	integer
advertiser_type required	string Enum: "private" "business"
external_url	string Advert's URL in origin system
external_id	string Advert's ID in origin system
contact required	object
location required	object
images	Array of objects
price	object
salary	object
attributes required	Array of objects
courier	boolean
auto_extend_enabled	boolean Should the advert be automatically extended when it expires. Omitting this fi that auto extend is not changed.
product_safety_regulation	object (ProductSafetyRegulation)

Responses

200

Status 200

PUT/adverts/{advertId}

Request samples

- **Payload**

Content type

application/json

Copy

Expand allCollapse all

```
{
  "title": "string",
  "description": "string",
  "category_id": 0,
  "advertiser_type": "private",
  "external_url": "string",
```

```
"external_id": "string",
```

```
"contact": {
```

```
"name": "string",
```

```
"phone": "string"
```

```
},
```

```
"location": {
```

```
"city_id": 0,
```

```
"district_id": 0,
```

```
"latitude": 0,
```

"longitude": 0

},

"images": [

{}

],

"price": {

"value": 0,

"currency": "string",

"negotiable": true,

"trade": true,

"budget": true

},

"salary": {

"value_from": 0,

"value_to": 0,

"currency": "string",

"negotiable": true,

"type": "hourly"

},

"attributes": [

{}

],

"courier": true,

"auto_extend_enabled": true,

"product_safety_regulation": {

"placed_before_2024": false,

"manufacturer": {},

"contact_person": {},

"warning_and_safety": "Handle with care. Keep away from children."

}

}

Response samples

200

Content type

application/json

Copy

Expand allCollapse all

{

"id": 123,

"status": "active",

"url": "https://www.olx.ua/oferta/url.html",

•

•

"created_at": "2018-02-02 09:35:16",

•

•

"activated_at": "2018-02-02 09:32:52",

•

•

"valid_to": "2018-03-04 09:32:52",

•

•

"title": "This is title",

•

•

"description": "This is description",

•

•

"category_id": 123,

•

•

"advertiser_type": "private",

•

"external_id": 12345,

"external_url": "http://myshop.com/advert/123",

"contact": {

"name": "John",

"phone": "2341235435,1245134254,12452145"

},

"location": {

"city_id": 1,

"district_id": null,

"latitude": 53.123,

"longitude": 17.123

},

"images": [

{},

{}

],

"price": {

"value": 123,

"currency": "PLN",

"negotiable": false,

"trade": false,

"budget": false

},

"salary": null,

"attributes": [

{},

{}

],

"courier": null,

"auto_extend_enabled": true,

"product_safety_regulation": {

"placed_before_2024": false,

"manufacturer": {},

"contact_person": {},

```
"warning_and_safety": "Handle with care. Keep away from children."
}
```

Delete advert

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer

Responses

204

Status 204

DELETE/adverts/{advertId}

Take action on advert

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer

REQUEST BODY SCHEMA: application/json

command required	string Enum: "activate" "deactivate" "finish" "extend" Commands activate - to activate advert, deactivate - to deactivate active advert, finish - to inactive advert (limited) to finished section, extend - to extend the activation period of th (not available in UA, PT).
is_success	boolean If transaction was successful. Required for deactivate command.

Responses

204

Status 204

POST/adverts/{advertId}/commands

Request samples

- **Payload**

Content type

application/json

Copy

{

-

"command": "activate",

-

-

"is_success": true

-

}

Advert statistics

Get advert statistics

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer Advert ID

Responses

200

Status 200

GET/adverts/{advertId}/statistics

Response samples

- 200

Content type

application/json

Copy

```
{
  "advert_views": 123,
  "phone_views": 100,
  "users_observing": 10
}
```

Clear statistics

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer Advert ID
statisticName required	string Enum: "phone-views" "advert-views" Type of the statistic

Responses

204

Status 204

DELETE/adverts/{advertId}/statistics/{statisticName}

Advert moderation reason

Get moderation reason

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer Advert ID

Responses

200

Status 200

GET/adverts/{advertId}/moderation-reason

Response samples

- 200

Content type

application/json

Copy


```
{
  "email_notification": "<p>Your advert was moderated because it promotes restricted items.</p>"
}
```


Advert logo

Get advert logos

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	string Advert ID

Responses

200

Status 200

GET/adverts/{advertId}/logos

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "id": 1,
    "url": "http://mydomain.com/logo.jpg"
  }
]
```


Add logo

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	string Advert ID

REQUEST BODY SCHEMA: application/json

url required	string Logo URL

Responses

200

Status 200

POST/adverts/{advertId}/logos

Request samples

- Payload

Content type

application/json

Copy

```
{
  "url": "string"
}
```

Response samples

- 200

Content type

application/json

Copy

```
{
```

•

```
"id": 1,
```

•

•

```
"url": "http://mydomain.com/logo.jpg"
```

•

```
}
```

Delete logo

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	integer Advert ID
logoId required	integer Logo ID

Responses

204

Status 204

```
DELETE/adverts/{advertId}/logos/{logoId}
```

Users Business

Get user business data

AUTHORIZATIONS:

access_token

Responses

200

Status 200

```
GET/users-business/me
```

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
{
  "id": 1,
  "name": "My company name",
  "description": "My company description",
  "subdomain": "mysubdomain",
  "website_url": "http://website.com",
  "address": {
```

-
    -
    "street": "Street",
    -
    -
    "number": 123,
    -
    -
    "postcode": "12-456",
    -
    -
    "city": "City Name"
    -
},
-
"phones": [
-
    -
    123456789
    -
],
-
"logo": {

```
"url": "https://www.olx.ua/logo.jpg"
},
"banner": {
"url": "https://www.olx.ua/banner.jpg"
}
}
```

Update user business data

AUTHORIZATIONS:

access_token

REQUEST BODY SCHEMA: application/json

name	string
description	string
subdomain	string
website_url	string
address	object
phones	Array of strings

Responses

200

Status 200

PUT/users-business/me

Request samples

- **Payload**

Content type

application/json

Copy

Expand allCollapse all

```
{
```

-

```
"name": "string",
```

-

-

```
"description": "string",
```

-

-

```
"subdomain": "string",
```

-

-

```
"website_url": "string",
```

-

-

```
"address": {
```

-

```
        "street": "string",
        "number": "string",
        "postcode": "string",
        "city": "string"
    },
    "phones": [
        "string"
    ]
}
```

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
{
    "id": 1,
    "name": "My company name",
    "description": "My company description",
    "subdomain": "mysubdomain",
    "website_url": "http://website.com",
    "address": {
        "street": "Street",
```

"number": 123,

"postcode": "12-456",

"city": "City Name"

},

"phones": [

123456789

],

"logo": {

"url": "https://www.olx.ua/logo.jpg"

},

"banner": {

"url": "https://www.olx.ua/banner.jpg"

}

}

Get user business logos

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/users-business/me/logos

Response samples

200

Content type

application/json

Copy

Expand allCollapse all

[

{

```
    "id": 123,
    "url": "https://www.olx.ua/logo.jpg"
}
]
```

Set user business logo

AUTHORIZATIONS:

access_token

REQUEST BODY SCHEMA: application/json

url required	string

Responses

200

Status 200

POST/users-business/me/logos

Request samples

- **Payload**

Content type

application/json

Copy

```
{
    "url": "string"
}
```

}

Response samples

- 200

Content type
application/json

Copy

Expand allCollapse all

[

- {

- "id": 123,

- "url": "https://www.olx.ua/logo.jpg"

}

]

Remove user business logo

AUTHORIZATIONS:

access_token

PATH PARAMETERS

logoId required	integer

Responses

204

Status 204

DELETE/users-business/me/logos/{logoId}

Get user business banners

AUTHORIZATIONS:

access_token

Responses

200

Status 200

GET/users-business/me/banners

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "id": 123,
    "url": "https://www.olx.ua/banner.jpg"
  }
]
```

Set user business banner

AUTHORIZATIONS:

access_token

REQUEST BODY SCHEMA: application/json

url required	string

Responses

200

Status 200

POST/users-business/me/banners

Request samples

- **Payload**

Content type

application/json

Copy

```
{
  "url": "string"
}
```

Response samples

- **200**

Content type

application/json

Copy

Expand allCollapse all

```
[
```

```
{
    "id": 123,
    "url": "https://www.olx.ua/banner.jpg"
}
```


]

Remove user business banner

AUTHORIZATIONS:

access_token

PATH PARAMETERS

bannerId required	integer

Responses

204

Status 204

```
DELETE/users-business/me/banners/{bannerId}
```

Packets

Get available packets

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

category_id required	integer
payment_method required	string Enum: "account" "postpaid" Payment method
type	string Enum: "base" "mega" "all" Packet type. 'base' by default, use 'all' to fetch both types
with_features	integer Enum: 0 1 Optional field to return features in response
zone_id	string Field to specify location zone - it's required for categories with enabled "Regional pricin (Available in UA)

Responses

200

Status 200

400

Status 400

GET/packets

Response samples

- 200
- 400

Content type

application/json

Copy

Expand allCollapse all

[

- {

-

"size": 50,

"category_id": 164,

"name": "Pakiet 50 ogłoszeń",

"price": 2091,

"is_premium": false,

"type": "base",

"features": []

}

]

Get available location zones - regional pricing feature has to be enabled (Available in UA)

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

category_id
required

integer

Responses

200

Status 200

400

Status 400

GET/zones

Response samples

- 200
- 400

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "id": "99040cfe-d68c-416f-85a9-1401cfa5f109",
```

"whole_country": false,

"whole_region": true,

"labels": [],

"sub_zones": []

}

]

Get bought packets

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

limit	integer Number of results [default 50]
offset	integer Starting element
availability	string Enum: "active" "inactive" availability filter
sort_by	string Enum: "expired_at" "activated_at" descending order

Responses

200

Status 200

GET/users/me/packets

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "id": "23423-dfdf-3432-df",
    "name": "Pakiet 10 ogłoszeń",
    "is_active": true,
    "size": 10,
```

"left": 9,

"active_to": "2018-05-14 11:49:30",

"price": 430.5,

"categories_labels": [],

"categories_ids": [],

"zone_id": "a257ef6a-673e-49f5-b903-eea4c775b74c",

"location_name": "Region without Main City"

}

Purchase packet

AUTHORIZATIONS:

access_token

REQUEST BODY SCHEMA: application/json

payment_method required	string Enum: "account" "postpaid"
category_id required	integer
size required	integer Size of the packet. This value should not be equal to 1.
type	string Enum: "base" "mega" Packet type. 'base' by default
zone_id	string Field to specify location zone - it's required for categories with enabled "Regional pricin (Available in UA)

Responses

204

Status 204

400

Status 400

POST/users/me/packets

Request samples

- Payload

Content type

application/json

Copy

```
{
```

-

```
"payment_method": "account",
```

-

-

"category_id": 0,

-

-

"size": 0,

-

-

"type": "base",

-

-

"zone_id": "string"

-

}

Response samples

- 400

Content type
application/json

Copy

Expand allCollapse all

[

-

{

-

  -

    "error": {}

•

}

Purchase packet for an advert

AUTHORIZATIONS:

access_token

PATH PARAMETERS

advertId required	string

REQUEST BODY SCHEMA: application/json

payment_method required	string Enum: "account" "postpaid"
is_premium	boolean Type of the packet. Set true to choose premium packet.

Responses

204

Status 204

POST/adverts/{advertId}/packets

Request samples

• Payload

Content type

application/json

Copy

{

•

"payment_method": "account",

•

•

"is_premium": true

-

}

Payments

Get billing

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

page	integer Page number, starts from 1
limit	integer Number of results per page

Responses

200

Status 200

GET/users/me/billing

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

[

-

{

-

  -

"id": 56,

"name": "Pakiet 10 ogłoszeń",

"date": "2018-04-09 13:08:27",

"price": -430.5,

"advert_id": 1234567

}

]

Get prepaid invoices

This endpoint is available only for BG and PL.

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

page	integer Page number, starts from 1
limit	integer Number of results per page

Responses

200

Status 200

GET/users/me/prepaid-invoices

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all


```
[
  {
    "payment_id": 53,
    "name": "Pakiet 10 ogłoszeń",
    "amount": 430.5,
    "amount_formatted": "430,50 zł",
```

```
"advert_id": 1234567
}
]
```

Get postpaid invoices

This endpoint is available only for OLX.pl

AUTHORIZATIONS:

access_token

QUERY PARAMETERS

page	integer Page numbers, starts from 1
limit	integer Number of results per page

Responses

200

Status 200

GET/users/me/postpaid-invoices

Response samples

- 200

Content type

application/json

Copy

Expand allCollapse all

```
[
  {
```

```
"invoice_id": "2018/12345",
"issue_date": "2018-03-31",
"due_date": "2018-04-14",
"amount_gross": 430.5,
"amount_net": 350,
"amount_formatted": "430,50 zł",
"advert_id": 1234567
}
```