

# Mistral-SPLADE: LLMs for better Learned Sparse Retrieval

Meet Doshi<sup>\*</sup>, Vishwajeet Kumar<sup>†</sup>, Rudra Murthy<sup>†</sup>, Vignesh P<sup>‡</sup>, and Jaydeep Sen<sup>‡</sup>

<sup>\*</sup>Indian Institute of Technology Bombay, India

<sup>†</sup>IBM Research, India

<sup>\*</sup>meetdoshi@cse.iitb.ac.in

<sup>‡</sup>{vishk024, jaydesen, rmurthyv}@in.ibm.com

## Abstract

Learned Sparse Retrievers (LSR) have evolved into an effective retrieval strategy that can bridge the gap between traditional keyword-based sparse retrievers and embedding-based dense retrievers. At its core, learned sparse retrievers try to learn the most important semantic keyword expansions from a query and/or document which can facilitate better retrieval with overlapping keyword expansions. LSR like SPLADE has typically been using encoder only models with MLM (masked language modeling) style objective in conjunction with known ways of retrieval performance improvement such as hard negative mining, distillation, etc. In this work, we propose to use decoder-only model for learning semantic keyword expansion. We posit, decoder only models that have seen much higher magnitudes of data are better equipped to learn keyword expansions needed for improved retrieval. We use Mistral as the backbone to develop our Learned Sparse Retriever similar to SPLADE and train it on a subset of sentence-transformer data which is often used for training text embedding models. Our experiments support the hypothesis that a sparse retrieval model based on decoder only large language model (LLM) surpasses the performance of existing LSR systems, including SPLADE and all its variants. The LLM based model (Echo-Mistral-SPLADE) now stands as a state-of-the-art learned sparse retrieval model on the BEIR text retrieval benchmark.

## Disclaimer

This work is still in progress, we aim to present preliminary results for learned sparse retrievers using LLMs.

## 1 Introduction

Information Retrieval (IR) has been greatly influenced by traditional systems like BM25, which use lexical matching and inverted indices for efficient retrieval. These methods have been the backbone

of search engines for years. However, Pre-trained Language Models (PLMs) like BERT (Devlin et al., 2019) have brought a major shift towards contextualized semantic matching. While bag-of-words (BOW) models remain strong baselines (Yang et al., 2019), they suffer from the long-standing vocabulary mismatch problem, where relevant documents might not contain terms that appear in the query. Thus, there have been attempts to substitute standard Bag of Words approaches with neural rankers.

In modern IR, dense representations combined with Approximate Nearest Neighbors (ANN) search has become the standard for first-stage ranking to reduce inference and maintain semantic representation similarity. These models have improved their in-domain performance thanks to better training pipelines. Despite these improvements, the generalization ability of these models has been questioned, especially with the BEIR benchmark (Thakur et al., 2021) showing that traditional systems like BM25 can outperform neural retrievers in various IR tasks and in some cases only show incremental gains. Moreover, dense models have also not been able to explicitly model term matching.

Recent advances in the “lexical representation space” through learned sparse retrieval (LSR) have shown encouraging results for fast sparse inference (Formal et al., 2021a,b; Lassance et al., 2024). This approach aims to combine the strengths of lexical bag-of-words and vector embedding algorithms by learning sparse representations that can be integrated with inverted indexing techniques. These methods often involve term weighting and expansion, using the benefits of explicit lexical matching and the efficiency of inverted indices. LSR methods have shown good generalization capabilities, both in inference latency and IR performance.

Despite their potential, sparse retrieval models have not yet been fully used to their full potential. We investigate LSR systems using LLMs and demonstrate substantial performance improve-

ments over existing SPLADE based models and its variants. Additionally, we examine the effects of LSR training on interpretability, offering insights into the future of learned sparse retrieval systems.

## 2 Related Work

We review the literature on different retrieval paradigms including embedding based dense models with an Approximate Nearest Neighbor (ANN) search and more recent attempts to do learned sparse retrievals which aims to learn semantic expansion of contextual synonyms to do better retrieval and retain interpretability. We also touch upon the latest research advances that attempts to utilize causal only decoder models to learn better dense representations, which as we will see in our work, is also suitable for learned sparse retrievers.

### 2.1 Dense Representation Learning

Dense retrieval has become a prevalent method for applying PLM retrievers in Information Retrieval (IR) where the models typically rely on the [CLS] token representation. Various training strategies have been proposed to enhance learned representations including but not limited to distillation (Hofstätter et al., 2020; Hofstätter et al., 2021; Lin et al., 2021; Santhanam et al., 2022), hard negative mining (Ren et al., 2021; Xiong et al., 2021; Zhan et al., 2020; Qu et al., 2021), pre-training (Gao and Callan, 2022; Izacard et al., 2022) and also all of them combined. Models such as DPR (Karpukhin et al., 2020) and ANCE (Xiong et al., 2021) have been recently evaluated on generalization tasks, as demonstrated in the BEIR benchmark (Thakur et al., 2021). Colbert (Khattab and Zaria, 2020) which is a dense representation model utilizes a late-interaction mechanism that allows fine-grained term-level matching at the expense of higher indexing cost and latency.

### 2.2 Sparse Representation Learning

Sparse representations based on PLM have garnered increasing interest due to their inherent advantages from lexical models. These approaches generally involve a term-importance component and/or a term-expansion mechanism. Various designs have been proposed to address these aspects. COIL (Gao et al., 2021a) learns term-level dense representations for a contextualized lexical match, while uniCOIL (Lin and Ma, 2021) simplifies this by learning a single weight per term, extending methods like DeepCT (Dai and Callan, 2020) and

DeepImpact (Mallia et al., 2021). SPLADE (Formal et al., 2021b), on the other hand, directly learns high-dimensional sparse representations capable of joint expansion and re-weighting through the Masked Language Modeling head of the PLM and sparse regularization. Recent Splade versions like (Formal et al., 2022) and (Lassance et al., 2024) show the importance of mining stronger hard negatives and utilization of distillation losses to boost in-domain and out-of-domain retriever performance. There have also been works to combine both sparse and dense representations for better retrieval (Kong et al., 2023) while maintaining linear time complexity.

### 2.3 Echo embeddings

Since LLMs are decoder-only causal language models, they are inherently weak at contextual representation due to unidirectional attention (BehnamGhader et al., 2024). To mitigate this Springer et al. (2024) proposed to use repetition to overcome this bias. In this idea, they propose to use two occurrences of the same text which is passed to the language model, and take a mean representation of only the second occurrence. This way, all the tokens from the second occurrence can already be seen in the whole context, leading to better representations. We utilize echo embeddings instead of an expensive retraining of the model for bidirectional attention.

## 3 Splade and Methodology

In this section, we first describe in detail SPLADE (Formal et al., 2021b), alongside how to leverage diverse data without any hard negative mining and how to utilize causal LLMs for SPLADE training.

### 3.1 SPLADE

**Model.** SPLADE generates interpretable sparse representations by utilizing the BERT Wordpiece vocabulary for token expansion and the MLM head for assigning term weights. This way the model performs implicit vocabulary expansion without any need for providing manual expansion terms. The interpretability of SPLADE is maintained due to the tied weight matrices of the embedding and the MLM layer. For a query or document  $t$ , let  $w_{i,j}$  denote the resulting importance of the  $j$ -th vocabulary token, for the input token  $i$ . Text representations are obtained by pooling such importance predictors over the input sequence, after a log-saturation



Figure 1: Learned Sparse Retrieval: Training vs Inference

effect. We thus consider by default the following formulation:

$$w_j = \max_{i \in t} \log (1 + \text{ReLU}(w_{ij}))$$

and the ranking score  $s(q, d)$  is given by the dot product between  $q$  and  $d$  representations.

**Training.** Given a query  $q$ , a positive document  $d^+$ , and additional in-batch negatives  $d_j^-$  (which are documents from other queries within the same batch), the model is trained through a combined approach. This involves optimizing a contrastive InfoNCE loss (van den Oord et al., 2018), as commonly employed in various prior works on learning first-stage rankers, alongside FLOPS regularization (Paria et al., 2020). The regularization is directly applied to the representations in the vocabulary space to achieve the desired sparsity factor in the indices during inference:

$$\mathcal{L} = \mathcal{L}_{\text{InfoNCE}} + \lambda_q \mathcal{L}_{\text{FLOPS}}^q + \lambda_d \mathcal{L}_{\text{FLOPS}}^d$$

Since we rely only on in-batch negatives  $d_j^-$ , we reduce the cost of any additional hard negative mining as compared to previous SPLADE versions (Formal et al., 2021b; Lassance et al., 2024; Formal et al., 2022).

### 3.2 Scaling SPLADE for Causal decoder LLMs

Learned Sparse Retriever models maintain their interpretability by expanding the input sequence

into a set of related tokens, which leads to better retrieval. This interpretability is ensured by the tied weight matrices of the embedding layer and the language modeling head (Press and Wolf, 2017). Models like BERT (Devlin et al., 2019) are pre-trained with tied weight matrices, and thus no intervention is required during SPLADE training apart from keeping them tied. Untying the weights would lead the language modeling layer to be equivalent to a linear layer, which does not correspond to any token for every logit. Many LLMs today are trained with untied weight matrices (Touvron et al., 2023; Jiang et al., 2023), which is bad for SPLADE training since the latent space is not bound to generate interpretable logits. Freezing the embedding and the output layer can still lead to uninterpretable logits and defeat the purpose of sparse retrieval systems. Another approach could be to reinitialize the language modeling head layer with the embedding layer and then retrain on a causal LM objective with tied weights. However, this is expensive and can also lead to loss of information. We thus use LoRA finetuning (Hu et al., 2022) to avoid this altogether. This way, we also reduce the number of parameters to be trained while maintaining interpretability. Another problem of causal LLMs is the weak representation of past context due to unidirectional attention. We utilize Echo embeddings (Springer et al., 2024) to improve the representation of the LLM. This effectively doubles the sequence length during training and inference.

Corpus	Baselines					Ours	
	BM25	ColBERTv2	SPLADE++	Spladev3	ElserV2	Bert-base +Sent-Trans	Echo-Mistral +Sent-Trans
Dense/Sparse	Sparse	Dense	Sparse	Sparse	Sparse	Sparse	Sparse
TREC-COVID	65.6	73.8	72.5	74.8	72.9	63.7	<b>76.79</b>
NFCorpus	32.5	33.8	34.5	35.7	36.7	34.29	<b>42.28</b>
NQ	32.9	56.2	53.3	<b>58.61</b>	55.9	43.27	55.96
HotpotQA	60.3	66.7	69.3	69.2	67	64.76	<b>70.17</b>
FiQA-2018	23.6	35.6	34.9	37.4	41.6	39.86	<b>57.71</b>
ArguAna	31.5	46.3	51.8	50.96	55.6	51.56	<b>56.21</b>
Touché-2020	<b>36.7</b>	26.3	24.2	29.29	26.3	19.44	17.99
Quora	78.9	85.2	84.9	81.4	84.69	<b>87.05</b>	86.68
DBPedia	31.3	44.6	43.6	<b>44.9</b>	42.7	35.32	41.99
SCIDOCs	15.8	15.4	16.1	15.78	16.2	21.24	<b>25.62</b>
FEVER	75.3	78.5	79.6	79.6	78.5	70.64	<b>84.43</b>
Climate-FEVER	21.3	17.6	<b>23.7</b>	23.3	27.1	22.11	22.83
SciFact	66.5	69.3	71	70.96	71.8	69.31	<b>77.24</b>
<b>Avg</b>	44.02	49.95	50.72	51.68	52.07	47.89	<b>55.07</b>

Table 1: Zero shot ndcg@10 ↑ on BEIR (13). For comparison, we report results directly from corresponding papers, where the evaluation is generally done on the subset of 13 readily available BEIR datasets.

We refer to this model as Echo-Mistral SPLADE in our experiments.

## 4 Experiments and Results

In this section, we discuss our experimental setup for all the proposed methods and discuss their potential advantages and limitations through empirical results.

### 4.1 Training

All the reference models are trained on the MS MARCO passage ranking dataset, which contains 8.8M passages and 500k training queries with shallow annotations. These models have been trained in multiple stages with each stage introducing more and more hard negatives and better margin scores for distillation. Instead, we rely on the same training mechanism with much more diverse training data. Specifically, we use the Sentence-transformers embedding data (15.5M subset) which has been previously used for sentence similarity tasks. Instead of mining hard negatives and calculating distillation scores which requires a lot of excess compute and effort. We rely only on in-batch negatives for training, with a batch size of 512. We use the same number of steps (150k) as other splade variants with echo embeddings during training and inference for our Echo-Mistral SPLADE model.

We initialized the smaller SPLADE models with the BERT-base checkpoint and the LLM with Mis-

tralv3<sup>1</sup>. Models are trained with the ADAM optimizer, using a learning rate of 2e-5 with linear scheduling and a warmup of 6000 steps. We consider a maximum length of 256 for input sequences. To mitigate the contribution of the regularizer at the early stages of training, we follow (Paria et al., 2020) and use a scheduler for  $\lambda$ , quadratically increasing  $\lambda$  at each training iteration, until a given step (50k in our case), from which it remains constant. For training the larger Echo-Mistral-7B SPLADE model we use QLoRA finetuning (Dettmers et al., 2023) with  $\alpha = 8$ ,  $rank = 16$ , and a dropout value of 0.1 over the projection layers. Models are trained using PyTorch (Paszke et al., 2019) and HuggingFace transformers (Wolf et al., 2019), on 4 NVIDIA DGX A100 GPUs with 80GB memory.

### 4.2 Sentence Transformers embedding data

Sparse retrievers have been trained only on individual datasets like the MSMarco passage ranking dataset which has 8.8M passages and 500k training queries. MSMarco is a high-quality retrieval dataset that is generated from Bing search logs. Specifically, it contains anonymized data derived from real user queries submitted to the Bing search engine. Instead of MSMarco, we rely on a large-scale sentence embedding dataset called Sentence-Transformer<sup>2</sup> that has shown improve-

<sup>1</sup><https://huggingface.co/mistralai/Mistral-7B-v0.3>

<sup>2</sup><https://huggingface.co/collections/sentence-transformers/>

Corpus	LLM2Vec Mistral Supervised	Echo Embeddings Mistral	Echo-Mistral SPLADE
Dense/Sparse	Dense	Dense	Sparse
TREC-COVID	<b>77.69</b>	76.02	76.79
NFCorpus	39.33	37.18	<b>42.28</b>
NQ	<b>61.7</b>	61.51	55.96
HotpotQA	74.07	<b>75.75</b>	70.17
FiQA-2018	53.11	54.11	<b>57.71</b>
ArguAna	<b>57.48</b>	56.52	56.21
Touché-2020	<b>22.18</b>	18.92	17.99
Quora	87.75	<b>89.33</b>	86.68
DBpedia	<b>49.58</b>	48.19	41.99
SCIDOCs	22.5	17.73	<b>25.62</b>
FEVER	89.4	<b>91.14</b>	84.43
Climate-FEVER	35.19	<b>37.07</b>	22.83
SciFact	<b>78.86</b>	73.57	77.24
Avg	<b>57.6</b>	56.69	55.07

Table 2: Comparison with DPR models trained on Mistral-7B on zero-shot nDCG@10 ↑ on BEIR (13). The training sets of NQ, FEVER, HotpotQA, and Climate-FEVER were included while training LLM2Vec (BehnamGhader et al., 2024) and Mistral with Echo Embeddings (Springer et al., 2024), so the comparison with our sparse model is not entirely fair.

ments over BEIR benchmark for many DPR models (Reimers and Gurevych, 2019; Ni et al., 2022; Wang et al., 2022; Gao et al., 2021b; Li et al., 2023; BehnamGhader et al., 2024). Specifically, we take the 15.5M sample subset and set their sampling probabilities proportional to their dataset size. We list all the dataset names in Appendix A. We use this dataset for Echo-Mistral-SPLADE training without any hard negative mining or distillation.

### 4.3 Evaluation

We report nDCG@10 for comparing zero-shot performance of our models on the BEIR benchmark (Thakur et al., 2021). We rely on the subset of 13 readily available datasets to compare with other baselines, thus we do not consider CQADupstack, BioASQ, Signal-1M, TREC-NEWS, and Robust04 BEIR datasets for evaluation.

### 4.4 Results and Discussion

We compare our model with the most prelevant learned sparse models from SPLADE family and its subsequent variations and extensions like Elserv2 (Formal et al., 2022, 2021b; Lassance et al., 2024; Elastic, 2024) and also with ColBERT(Khattab and Zaharia, 2020) which is a state-of-the-art dense baseline. Our results can be summarized in Table 1, we can see that scaling with echo embeddings work significantly well over the same dataset, achieving

state-of-the-art results for sparse retrieval on BEIR-13 without any need for complicated training and hard negative mining.

For a fair comparison with similar-sized LLM-based dense retriever models, we also compare our results with LLM2Vec on Mistral7B in a supervised setting after MNTP and SimCSE pre-training (BehnamGhader et al., 2024) and Echo Embeddings on Mistral7B with pooled representation of the second occurrence (Springer et al., 2024). Firstly, we do not use any of the BEIR train sets while training our LSR model so all the numbers reported are purely zero shot as compared to LLM2Vec and Echo Embeddings which use train sets of NQ, Fever, and HotpotQA during their training. In Table 2 we can see that a similar-sized Echo-Mistral SPLADE model achieves competitive performance to dense models. If we exclude in-domain performance for all models, we see Echo-Mistral SPLADE surpassing the performance of Echo Embeddings but lagging behind LLM2Vec which shows performance gains due to unsupervised pretraining. This is a strong indicator of how well LSR systems can perform in practice.

## 5 Conclusion

In this paper, we present Echo-Mistral SPLADE, which uses Mistral-7B LLM with Echo embeddings as the backbone for learned sparse retrieval training. Echo-Mistral-SPLADE achieves state-of-the-art performance on BEIR benchmark outperforming existing sparse retrieval models including SPLADE and its variants. We also compare with a similar-sized dense model and show that Echo-Mistral-SPLADE can outperform dense models in out-of-domain setting, which can be further improved with unsupervised pretraining. We believe such diverse data and the model scale is the leading reason for improvement but further exploration like joint distillation and hard negatives can further improve this performance. With this, we aim to motivate the use of LSR systems in practice due to their low inference latency and interpretability over dense retriever systems.

## References

- Parishad BehnamGhader, Vaibhav Adlakha, Marius Mosbach, Dzmitry Bahdanau, Nicolas Chapados, and Siva Reddy. 2024. *Llm2vec: Large language models are secretly powerful text encoders*. *CoRR*, abs/2404.05961.

- Zhuyun Dai and Jamie Callan. 2020. [Context-aware term weighting for first stage passage retrieval](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR ’20*, page 1533–1536, New York, NY, USA. Association for Computing Machinery.
- Tim Dettmers, Artidoro Pagnoni, Ari Holtzman, and Luke Zettlemoyer. 2023. [Qlora: Efficient finetuning of quantized llms](#). In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Elastic. 2024. Elasticsearch language-specific embedding model (elser). <https://www.elastic.co/guide/en/machine-learning/current/ml-nlp-elser.html#elser-v2>. Accessed: 2024-08-13.
- Thibault Formal, Carlos Lassance, Benjamin Piwowarski, and Stéphane Clinchant. 2021a. [SPLADE v2: Sparse lexical and expansion model for information retrieval](#). *CoRR*, abs/2109.10086.
- Thibault Formal, Carlos Lassance, Benjamin Piwowarski, and Stéphane Clinchant. 2022. [From distillation to hard negative sampling: Making sparse neural IR models more effective](#). In *SIGIR ’22: The 45th International ACM SIGIR Conference on Research and Development in Information Retrieval, Madrid, Spain, July 11 - 15, 2022*, pages 2353–2359. ACM.
- Thibault Formal, Benjamin Piwowarski, and Stéphane Clinchant. 2021b. [Splade: Sparse lexical and expansion model for first stage ranking](#). In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR ’21*, page 2288–2292, New York, NY, USA. Association for Computing Machinery.
- Luyu Gao and Jamie Callan. 2022. [Unsupervised corpus aware language model pre-training for dense passage retrieval](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pages 2843–2853. Association for Computational Linguistics.
- Luyu Gao, Zhuyun Dai, and Jamie Callan. 2021a. [COIL: revisit exact lexical match in information retrieval with contextualized inverted list](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021*, pages 3030–3042. Association for Computational Linguistics.
- Tianyu Gao, Xingcheng Yao, and Danqi Chen. 2021b. [Simcse: Simple contrastive learning of sentence embeddings](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, pages 6894–6910. Association for Computational Linguistics.
- Sebastian Hofstätter, Sophia Althammer, Michael Schröder, Mete Sertkan, and Allan Hanbury. 2020. [Improving efficient neural ranking models with cross-architecture knowledge distillation](#). *CoRR*, abs/2010.02666.
- Sebastian Hofstätter, Sheng-Chieh Lin, Jheng-Hong Yang, Jimmy Lin, and Allan Hanbury. 2021. [Efficiently teaching an effective dense retriever with balanced topic aware sampling](#). In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR ’21*, page 113–122, New York, NY, USA. Association for Computing Machinery.
- Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. [Lora: Low-rank adaptation of large language models](#). In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.
- Gautier Izacard, Mathilde Caron, Lucas Hosseini, Sebastian Riedel, Piotr Bojanowski, Armand Joulin, and Edouard Grave. 2022. [Unsupervised dense information retrieval with contrastive learning](#). *Trans. Mach. Learn. Res.*, 2022.
- Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de Las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. [Mistral 7b](#). *CoRR*, abs/2310.06825.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick S. H. Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. [Dense passage retrieval for open-domain question answering](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, EMNLP 2020, Online, November 16-20, 2020*, pages 6769–6781. Association for Computational Linguistics.
- Omar Khattab and Matei Zaharia. 2020. [Colbert: Efficient and effective passage search via contextualized late interaction over bert](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR ’20*, page 39–48, New York, NY, USA. Association for Computing Machinery.

- Weize Kong, Jeffrey M. Dudek, Cheng Li, Mingyang Zhang, and Michael Bendersky. 2023. [Sparseembed: Learning sparse lexical representations with contextual embeddings for retrieval](#). In *Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR 2023, Taipei, Taiwan, July 23-27, 2023*, pages 2399–2403. ACM.
- Carlos Lassance, Hervé Déjean, Thibault Formal, and Stéphane Clinchant. 2024. [Splade-v3: New baselines for SPLADE](#). *CoRR*, abs/2403.06789.
- Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. 2023. [Towards general text embeddings with multi-stage contrastive learning](#). *CoRR*, abs/2308.03281.
- Jimmy Lin and Xueguang Ma. 2021. [A few brief notes on deepimpact, coil, and a conceptual framework for information retrieval techniques](#). *CoRR*, abs/2106.14807.
- Sheng-Chieh Lin, Jheng-Hong Yang, and Jimmy Lin. 2021. [In-batch negatives for knowledge distillation with tightly-coupled teachers for dense retrieval](#). In *Proceedings of the 6th Workshop on Representation Learning for NLP (Rep4NLP-2021)*, pages 163–173, Online. Association for Computational Linguistics.
- Antonio Mallia, Omar Khattab, Torsten Suel, and Nicola Tonello. 2021. [Learning passage impacts for inverted indexes](#). In *Proceedings of the 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR ’21*, page 1723–1727, New York, NY, USA. Association for Computing Machinery.
- Jianmo Ni, Chen Qu, Jing Lu, Zhuyun Dai, Gustavo Hernández Ábreo, Ji Ma, Vincent Y. Zhao, Yi Luan, Keith B. Hall, Ming-Wei Chang, and Yinfei Yang. 2022. [Large dual encoders are generalizable retrievers](#). In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing, EMNLP 2022, Abu Dhabi, United Arab Emirates, December 7-11, 2022*, pages 9844–9855. Association for Computational Linguistics.
- Biswajit Paria, Chih-Kuan Yeh, Ian En-Hsu Yen, Ning Xu, Pradeep Ravikumar, and Barnabás Póczos. 2020. [Minimizing flops to learn efficient sparse representations](#). In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.
- Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Köpf, Edward Z. Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. 2019. [Pytorch: An imperative style, high-performance deep learning library](#). In *Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada*, pages 8024–8035.
- Ofir Press and Lior Wolf. 2017. [Using the output embedding to improve language models](#). In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics, EACL 2017, Valencia, Spain, April 3-7, 2017, Volume 2: Short Papers*, pages 157–163. Association for Computational Linguistics.
- Yingqi Qu, Yuchen Ding, Jing Liu, Kai Liu, Ruiyang Ren, Wayne Xin Zhao, Daxiang Dong, Hua Wu, and Haifeng Wang. 2021. [Rocketqa: An optimized training approach to dense passage retrieval for open-domain question answering](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2021, Online, June 6-11, 2021*, pages 5835–5847. Association for Computational Linguistics.
- Nils Reimers and Iryna Gurevych. 2019. [Sentence-bert: Sentence embeddings using siamese bert-networks](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing, EMNLP-IJCNLP 2019, Hong Kong, China, November 3-7, 2019*, pages 3980–3990. Association for Computational Linguistics.
- Ruiyang Ren, Yingqi Qu, Jing Liu, Wayne Xin Zhao, Qiaoqiao She, Hua Wu, Haifeng Wang, and Ji-Rong Wen. 2021. [Rocketqav2: A joint training method for dense passage retrieval and passage re-ranking](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, pages 2825–2835. Association for Computational Linguistics.
- Keshav Santhanam, Omar Khattab, Jon Saad-Falcon, Christopher Potts, and Matei Zaharia. 2022. [Colbertv2: Effective and efficient retrieval via lightweight late interaction](#). In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL 2022, Seattle, WA, United States, July 10-15, 2022*, pages 3715–3734. Association for Computational Linguistics.
- Jacob Mitchell Springer, Suhas Kotha, Daniel Fried, Graham Neubig, and Aditi Raghunathan. 2024. [Repetition improves language model embeddings](#). *CoRR*, abs/2402.15449.
- Nandan Thakur, Nils Reimers, Andreas Rücklé, Abhishek Srivastava, and Iryna Gurevych. 2021. [BEIR: A heterogenous benchmark for zero-shot evaluation of information retrieval models](#). *CoRR*, abs/2104.08663.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay

Bashlykov, Soumya Batra, Prajwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton-Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurélien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023. [Llama 2: Open foundation and fine-tuned chat models](#). *CoRR*, abs/2307.09288.

Aäron van den Oord, Yazhe Li, and Oriol Vinyals. 2018. [Representation learning with contrastive predictive coding](#). *ArXiv*, abs/1807.03748.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. 2022. [Text embeddings by weakly-supervised contrastive pre-training](#). *CoRR*, abs/2212.03533.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pieric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, and Jamie Brew. 2019. [Huggingface’s transformers: State-of-the-art natural language processing](#). *CoRR*, abs/1910.03771.

Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul N. Bennett, Junaid Ahmed, and Arnold Overwijk. 2021. [Approximate nearest neighbor negative contrastive learning for dense text retrieval](#). In *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net.

Wei Yang, Kuang Lu, Peilin Yang, and Jimmy Lin. 2019. [Critically examining the "neural hype": Weak baselines and the additivity of effectiveness gains from neural ranking models](#). In *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR 2019, Paris, France, July 21-25, 2019*, pages 1129–1132. ACM.

Jingtao Zhan, Jiaxin Mao, Yiqun Liu, Min Zhang, and Shaoping Ma. 2020. [Learning to retrieve: How to train a dense retrieval model effectively and efficiently](#). *CoRR*, abs/2010.10469.

probabilities are calculated by normalizing the size of each dataset and we exclude any dataset that conflicts with our evaluation on zero-shot out-of-domain BEIR retrieval datasets ([Thakur et al., 2021](#)).

Dataset Name	Sampling ratio
gooaq_pairs	20.53
yahoo_answers_title_answer	8.17
msmarco_triplets	3.43
stackexchange_title_title	2.08
eli5_question_answer	2.22
yahoo_answers_title_question	4.50
squad_pairs	0.60
yahoo_answers_question_answer	4.64
wikihow	0.88
amazon_qa	17.08
quora question pairs	1.02
stackexchange_title_body_title_body	1.71
stackexchange_body_body	1.71
agnews	7.89
AIINLI	2.14
npr	4.05
specter_train_triples	2.59
SimpleWiki	0.70
altnlex	0.77
ccnews_title_text	4.19
sentence_compression	1.23
TriviaQA_pairs	0.50
cnn_dailymail	1.96
flickr30k_captions	1.08
xsum	1.54
coco_captions	2.82

Table 3: Dataset Sampling Probabilities

## A Dataset Details

In this section we list down the dataset details and sampling probabilities during training. The